

Distance Vector Algorithm – Problems, Solutions and a Standard

Kameswari Chebrolu

All the figures used as part of the slides are either self created or from the public domain with either 'creative commons' or 'public domain dedication' licensing. The public sites from which some of the figures have been picked include:

<http://commons.wikimedia.org> (Wikipedia, Wikimedia and workbooks); <http://www.sxc.hu> and <http://www.pixabay.com>

Recap

- Nodes exchange with their neighbors their current routing table information (destination, estimated cost)
- On receipt of a message, nodes update cost to destination based on Bellman-ford equation
- Messages sent periodically as well as when table changes

Reference Node C

D	C	H
A	5	A
B	3	B
D	4	D

Routing Table of C
(1)

To	A
A	0
B	1
C	5

Message from A
C to A: C = 5

D	C	H
A	5	A
B	3	B
D	4	D

Routing Table of C

D	C	H
A	5	A
B	3	B
D	4	D

Routing Table of C
(2)


To	B
A	1
B	0
C	3
E	9

Message from B
C to B: C = 3

D	C	H
A	4	B
B	3	B
D	4	D
E	12	B

Routing Table of C

Example



D	C	H
A	4	B
B	3	B
D	4	D
E	12	B

Routing Table of C
(3)

To	D
C	4
D	0
E	2

Message from D
C to D: C = 4

D	C	H
A	4	B
B	3	B
D	4	D
E	6	D


Routing Table of C

Every path has its puddle!

Counting to Infinity

Distance to Node D


Mesg.	A	B	C
	2,B	∞ , -	2,B
$B \rightarrow A$	∞ , -	∞ , -	2,B
$C \rightarrow A$	3,C	∞ , -	2,B
$B \rightarrow C$	3,C	∞ , -	∞ , -
$A \rightarrow B$	3,C	4,A	∞ , -
$C \rightarrow A$	∞ , -	4,A	∞ , -
$B \rightarrow C$	∞ , -	4,A	5,B
$A \rightarrow B$	∞ , -	∞ , -	5,B



State maintained by nodes A,B and C


Partial Solutions

- Make infinity small
 - Use for example 16 to represent infinity (assumes max no of hops under 16)
↗ hop count
 - Bounds time it takes to count to infinity
- Split horizon
 - Don't send routes learnt from a neighbor back to it




Partial Solutions

- Split horizon with poison reverse
 - Send routes learnt from a neighbor back to it but with infinite cost




- Split horizon with and without poison reverse



- Both don't work for loops with more than 2 nodes

Partial Solutions

- Hold-Down Timer: Wait some time before propagating link failure
 - Slows down convergence
- Path-vector routing is a variation of distance-vector
 - Each node sends to its neighbors not just the cost, but the entire path to the destination
 - Avoids the looping problem of DV but more overhead



RIP

- Routing Information Protocol (RIP) is a standard that implements DV routing
- One of the oldest DV based protocol
 - Popular once, not used much due to convergence problems
↳ size

RIP Features

- Uses UDP and work over reserved port 520
- Period updates sent every 30 sec
- Supports multiple address families IP
- Cost of a link is 1 (finds minimum hop route)
- 16 represents infinity, *split horizon, hold-down timer*
- RIP can run only on very small networks

RIPv1 Packet Format

→ R₁ C₁ (NH₁)

0	Command	Version	Reserved	31
	Family of Net 1		Reserved	
	Address of Net 1 (IP Address)			
	Reserved			
	Reserved			
	Distance to Net 1			
	Family of Net 2		Reserved	
	Address of Net 2 (IP Address)			
	Reserved			
	Reserved			
	Distance to Net 1			

→ IP Prefix (NH₁)
Route

Reserved fields are set to all zero

$\left. \begin{matrix} IPF_1 \\ R \end{matrix} \right\} \left. \begin{matrix} IPF_2 \\ R \end{matrix} \right\} \left. \begin{matrix} IPF_3 \\ R \end{matrix} \right\}$
 $\begin{matrix} 1 & 1 & 1 \\ 0 & 0 & 0 \end{matrix}$
 $\begin{matrix} IPF_1 & 0 \\ IPF_2 & 0 \\ IPF_3 & 1 \end{matrix}$

1 to 25 sets of entries, each entry is 20 bytes

classless

Summary

- Distance vector is a distributed, dynamic algorithm
- Exchanges information locally to determine routes
- Suffers from poor convergence, routing loops
- RIP is a standard that implements the DV protocol
 - Handles above problems via (split horizon, hold-down timer and using a value of 16 to represent infinity)
- Better approach: Link-state routing