



CS 228 : Logic in Computer Science

Krishna. S

So Far

- ▶ Syntax, semantics of LTL
- ▶ Temporal operators of LTL \bigcirc , U , \Diamond , \Box

Syntax of LTL

Given AP , a set of propositions,

- ▶ Propositional logic formulae over AP
 - ▶ $a \in AP$ (atomic propositions)
 - ▶ $\neg\varphi, \varphi \wedge \psi, \varphi \vee \psi$
- ▶ Temporal Operators
 - ▶ $\bigcirc\varphi$ (Next φ)
 - ▶ $\varphi \mathbf{U}\psi$ (φ holds until a ψ -state is reached)

$$\varphi ::= a \mid \varphi \vee \varphi \mid \neg\varphi \mid \varphi \wedge \varphi \mid \bigcirc\varphi \mid \varphi \mathbf{U}\varphi$$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

- ▶ $\sigma \models a$ iff $a \in A_0$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

- ▶ $\sigma \models a$ iff $a \in A_0$
- ▶ $\sigma \models \varphi_1 \wedge \varphi_2$ iff $\sigma \models \varphi_1$ and $\sigma \models \varphi_2$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

- ▶ $\sigma \models a$ iff $a \in A_0$
- ▶ $\sigma \models \varphi_1 \wedge \varphi_2$ iff $\sigma \models \varphi_1$ and $\sigma \models \varphi_2$
- ▶ $\sigma \models \neg \varphi$ iff $\sigma \not\models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

- ▶ $\sigma \models a$ iff $a \in A_0$
- ▶ $\sigma \models \varphi_1 \wedge \varphi_2$ iff $\sigma \models \varphi_1$ and $\sigma \models \varphi_2$
- ▶ $\sigma \models \neg \varphi$ iff $\sigma \not\models \varphi$
- ▶ $\sigma \models \bigcirc \varphi$ iff $A_1 A_2 \dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Let $\sigma = A_0 A_1 A_2 \dots$.

- ▶ $\sigma \models a$ iff $a \in A_0$
- ▶ $\sigma \models \varphi_1 \wedge \varphi_2$ iff $\sigma \models \varphi_1$ and $\sigma \models \varphi_2$
- ▶ $\sigma \models \neg\varphi$ iff $\sigma \not\models \varphi$
- ▶ $\sigma \models \bigcirc\varphi$ iff $A_1 A_2 \dots \models \varphi$
- ▶ $\sigma \models \varphi \mathbf{U} \psi$ iff
 $\exists j \geq 0$ such that $A_j A_{j+1} \dots \models \psi \wedge \forall 0 \leq i < j, A_i A_{i+1} \dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

► $\sigma \models \Diamond \varphi$ iff $\exists j \geq 0, A_j A_{j+1} \dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

- ▶ $\sigma \models \Diamond \varphi$ iff $\exists j \geq 0, A_j A_{j+1} \dots \models \varphi$
- ▶ $\sigma \models \Box \varphi$ iff $\forall j \geq 0, A_j A_{j+1} \dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

- ▶ $\sigma \models \Diamond \varphi$ iff $\exists j \geq 0, A_j A_{j+1} \dots \models \varphi$
- ▶ $\sigma \models \Box \varphi$ iff $\forall j \geq 0, A_j A_{j+1} \dots \models \varphi$
- ▶ $\sigma \models \Box \Diamond \varphi$ iff $\forall j \geq 0, \exists i \geq j, A_i A_{i+1} \dots \models \varphi$

Semantics over Infinite Words

Given LTL formula φ over AP ,

$$L(\varphi) = \{\sigma \in (2^{AP})^\omega \mid \sigma \models \varphi\}$$

- ▶ $\sigma \models \Diamond \varphi$ iff $\exists j \geq 0, A_j A_{j+1} \dots \models \varphi$
- ▶ $\sigma \models \Box \varphi$ iff $\forall j \geq 0, A_j A_{j+1} \dots \models \varphi$
- ▶ $\sigma \models \Box \Diamond \varphi$ iff $\forall j \geq 0, \exists i \geq j, A_i A_{i+1} \dots \models \varphi$
- ▶ $\sigma \models \Diamond \Box \varphi$ iff $\exists j \geq 0, \forall i \geq j, A_i A_{i+1} \dots \models \varphi$

If $\sigma = A_0 A_1 A_2 \dots$, $\sigma \models \varphi$ is also written as $\sigma, 0 \models \varphi$. This simply means $A_0 A_1 A_2 \dots \models \varphi$. One can also define $\sigma, i \models \varphi$ to mean $A_i A_{i+1} A_{i+2} \dots \models \varphi$ to talk about a suffix of the word σ satisfying a property.

Paths and States: Semantics

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

Paths and States: Semantics

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

- ▶ For $s \in S$,

$$s \models \varphi \text{ iff } \forall \pi \in \text{Paths}(s), \pi \models \varphi$$

Paths and States: Semantics

Let $TS = (S, S_0, \rightarrow, AP, L)$ be a transition system, and φ an LTL formula over AP

- ▶ For an infinite path π of TS ,

$$\pi \models \varphi \text{ iff } \text{trace}(\pi) \models \varphi$$

- ▶ For $s \in S$,

$$s \models \varphi \text{ iff } \forall \pi \in \text{Paths}(s), \pi \models \varphi$$


- ▶ $TS \models \varphi$ iff $\text{Traces}(TS) \subseteq L(\varphi)$

Paths and States: Semantics

Assume all states in TS are reachable from S_0 .


- ▶ $TS \models \varphi$ iff $\pi \models \varphi \forall \pi \in Paths(TS)$
- ▶ $\pi \models \varphi \forall \pi \in Paths(TS)$ iff $s_0 \models \varphi \forall s_0 \in S_0$

Example




► $TS \models \Box a,$

Example




- ▶ $TS \models \Box a$,
- ▶ $TS \not\models \bigcirc(a \wedge b)$

Example



- ▶ $TS \models \Box a,$
- ▶ $TS \not\models \bigcirc(a \wedge b)$
- ▶ $TS \not\models (b \cup (a \wedge \neg b))$

Example



- ▶ $TS \models \Box a$,
- ▶ $TS \not\models \bigcirc(a \wedge b)$
- ▶ $TS \not\models (b \cup (a \wedge \neg b))$
- ▶ $TS \models \Box(\neg b \rightarrow \Box(a \wedge \neg b))$

More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$


More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$
 $trace(\pi) \in L(\varphi)$ iff $trace(\pi) \notin L(\neg\varphi) = \overline{L(\varphi)}$
- ▶ $TS \not\models \varphi$ iff $TS \models \neg\varphi$?
 - ▶ $TS \models \neg\varphi \rightarrow \forall$ paths π of TS , $\pi \models \neg\varphi$
 - ▶ Thus, $\forall\pi$, $\pi \not\models \varphi$. Hence, $TS \not\models \varphi$

More Semantics

- ▶ For paths π , $\pi \models \varphi$ iff $\pi \not\models \neg\varphi$
 $\text{trace}(\pi) \in L(\varphi)$ iff $\text{trace}(\pi) \notin L(\neg\varphi) = \overline{L(\varphi)}$
- ▶ $TS \not\models \varphi$ iff $TS \models \neg\varphi$?
 - ▶ $TS \models \neg\varphi \rightarrow \forall$ paths π of TS , $\pi \models \neg\varphi$
 - ▶ Thus, $\forall\pi, \pi \not\models \varphi$. Hence, $TS \not\models \varphi$
 - ▶ Now assume $TS \not\models \varphi$
 - ▶ Then \exists some path π in TS such that $\pi \models \neg\varphi$
 - ▶ However, there could be another path π' such that $\pi' \models \varphi$
 - ▶ Then $TS \not\models \neg\varphi$ as well
- ▶ Thus, $TS \not\models \varphi \not\equiv TS \models \neg\varphi$.

An Example



$TS \not\models \Diamond a$ and $TS \not\models \Box \neg a$

Equivalence of LTL Formulae

Equivalence

φ and ψ are equivalent ($\varphi \equiv \psi$) iff $L(\varphi) = L(\psi)$.

Expansion Laws

- ▶ $\varphi \text{ U } \psi \equiv \psi \vee (\varphi \wedge \bigcirc(\varphi \text{ U } \psi))$
- ▶ $\diamond\varphi \equiv \varphi \vee \bigcirc\diamond\varphi$
- ▶ $\Box\varphi \equiv \varphi \wedge \bigcirc\Box\varphi$

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Distribution

$$\bigcirc(\varphi \vee \psi) \equiv \bigcirc\varphi \vee \bigcirc\psi,$$

$$\bigcirc(\varphi \wedge \psi) \equiv \bigcirc\varphi \wedge \bigcirc\psi,$$

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Distribution

$$\bigcirc(\varphi \vee \psi) \equiv \bigcirc\varphi \vee \bigcirc\psi,$$

$$\bigcirc(\varphi \wedge \psi) \equiv \bigcirc\varphi \wedge \bigcirc\psi,$$

$$\bigcirc(\varphi \text{ U } \psi) \equiv (\bigcirc\varphi) \text{ U } (\bigcirc\psi),$$

Equivalence of LTL Formulae

φ and ψ are equivalent iff $L(\varphi) = L(\psi)$.

Distribution

$$\bigcirc(\varphi \vee \psi) \equiv \bigcirc\varphi \vee \bigcirc\psi,$$


$$\bigcirc(\varphi \wedge \psi) \equiv \bigcirc\varphi \wedge \bigcirc\psi,$$

$$\bigcirc(\varphi \mathbf{U} \psi) \equiv (\bigcirc\varphi) \mathbf{U} (\bigcirc\psi),$$

$$\Diamond(\varphi \vee \psi) \equiv \Diamond\varphi \vee \Diamond\psi,$$

$$\Box(\varphi \wedge \psi) \equiv \Box\varphi \wedge \Box\psi$$

Equivalence of LTL Formulae



$$TS \models \Diamond a \wedge \Diamond b, TS \not\models \Diamond(a \wedge b)$$

$$TS \models \Box(a \vee b), TS \not\models \Box a \vee \Box b$$

Satisfiability, Model Checking LTL

Two Questions

1. Given transition system TS , and an LTL formula φ . Does $TS \models \varphi$?
2. Given an LTL formula φ , is $L(\varphi) = \emptyset$?

Satisfiability, Model Checking LTL

Two Questions

1. Given transition system TS , and an LTL formula φ . Does $TS \models \varphi$?
2. Given an LTL formula φ , is $L(\varphi) = \emptyset$?

How we go about this:

- ▶ Translate φ into an automaton A_φ that accepts infinite words such that $L(A_\varphi) = L(\varphi)$. Check (somehow) for emptiness of A_φ to check satisfiability of φ .

Satisfiability, Model Checking LTL

Two Questions

1. Given transition system TS , and an LTL formula φ . Does $TS \models \varphi$?
2. Given an LTL formula φ , is $L(\varphi) = \emptyset$?

How we go about this:

- ▶ Translate φ into an automaton A_φ that accepts infinite words such that $L(A_\varphi) = L(\varphi)$. Check (somehow) for emptiness of A_φ to check satisfiability of φ .
- ▶ Check (somehow) $TS \cap \overline{A_\varphi}$ is empty, to answer the model-checking problem.

Notations for Infinite Words

- ▶ Σ is a finite alphabet
- ▶ Σ^* set of finite words over Σ
- ▶ Σ^ω set of infinite words over Σ
- ▶ An infinite word is written as $\alpha = \alpha(0)\alpha(1)\alpha(2)\dots$, where $\alpha(i) \in \Sigma$
- ▶ Such words are called ω -words
- ▶ $Inf(\alpha) = \{a \in \Sigma \mid \alpha(i) = a \text{ for infinitely many } i\}$. $Inf(\alpha)$ gives the set of symbols occurring infinitely often in α .

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

ω -automata

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

Run

A run ρ of \mathcal{A} on an ω -word $\alpha = a_1 a_2 \dots \in \Sigma^\omega$ is an infinite state sequence $\rho(0)\rho(1)\rho(2)\dots$ such that

- ▶ $\rho(0) = q_0$,
- ▶ $\rho(i) = \delta(\rho(i-1), a_i)$ if \mathcal{A} is deterministic,
- ▶ $\rho(i) \in \delta(\rho(i-1), a_i)$ if \mathcal{A} is non-deterministic,

ω -automata

An ω -automaton is a tuple $\mathcal{A} = (Q, \Sigma, \delta, q_0, Acc)$ where

- ▶ Q is a finite set of states
- ▶ Σ is a finite alphabet
- ▶ $\delta : Q \times \Sigma \rightarrow 2^Q$ is a state transition function (if non-deterministic, otherwise, $\delta : Q \times \Sigma \rightarrow Q$)
- ▶ $q_0 \in Q$ is an initial state and Acc is an acceptance condition

Run

A run ρ of \mathcal{A} on an ω -word $\alpha = a_1 a_2 \dots \in \Sigma^\omega$ is an infinite state sequence $\rho(0)\rho(1)\rho(2)\dots$ such that

- ▶ $\rho(0) = q_0$,
- ▶ $\rho(i) = \delta(\rho(i-1), a_i)$ if \mathcal{A} is deterministic,
- ▶ $\rho(i) \in \delta(\rho(i-1), a_i)$ if \mathcal{A} is non-deterministic,

i_n

Büchi Acceptance

For Büchi Acceptance, Acc is specified as a set of states, $G \subseteq Q$. The ω -word α is accepted if there is a run ρ of α such that $Inf(\rho) \cap G \neq \emptyset$.

Comparing NFA and NBA

(Non)deterministic Büchi Automata

$$L(\mathcal{A}) = \{\alpha \in \Sigma^\omega \mid \alpha \text{ has a run } \rho \text{ such that } \text{Inf}(\rho) \cap G \neq \emptyset\}$$

(Non)deterministic Finite Automata

$$L(\mathcal{A}) = \{\alpha \in \Sigma^* \mid \alpha \text{ has a run } \rho \text{ ending in some final state } \}$$



Comparing NFA and NBA

(Non)deterministic Büchi Automata

$$L(\mathcal{A}) = \{\alpha \in \Sigma^\omega \mid \alpha \text{ has a run } \rho \text{ such that } \text{Inf}(\rho) \cap G \neq \emptyset\}$$

(Non)deterministic Finite Automata

$$L(\mathcal{A}) = \{\alpha \in \Sigma^* \mid \alpha \text{ has a run } \rho \text{ ending in some final state}\}$$







Comparing NFA and NBA

(Non)deterministic Büchi Automata


$$L(\mathcal{A}) = \{\alpha \in \Sigma^\omega \mid \alpha \text{ has a run } \rho \text{ such that } \text{Inf}(\rho) \cap G \neq \emptyset\}$$

(Non)deterministic Finite Automata

$$L(\mathcal{A}) = \{\alpha \in \Sigma^* \mid \alpha \text{ has a run } \rho \text{ ending in some final state}\}$$



ω -Automata with Büchi Acceptance




- ▶ Left (T-B): Inf many b 's, Inf many a 's
- ▶ Right (T-B): Finitely many b 's, $(a + b)^\omega$

Büchi Acceptance

A language $L \subseteq \Sigma^\omega$ is called ω -regular if there exists a NBA \mathcal{A} such that $L = L(\mathcal{A})$. Recall definition of regular languages and NFA/DFA acceptance.

NBA and DBA

- ▶ Is every DBA as expressible as a NBA, like in the case of DFA and NFA?
- ▶ Can we do subset construction on NBA and obtain DBA?



NBA and DBA

- ▶ Is every DBA as expressible as a NBA, like in the case of DFA and NFA?
- ▶ Can we do subset construction on NBA and obtain DBA?

