

REC-CIS

OUTPUT

The first and only line of output must contain the length of the correct password and its central letter.

CONSTRAINTS

$$1 \leq N \leq 100$$

SAMPLE INPUT

4
abc
def
feg
cba

SAMPLE OUTPUT

3 b



Type here to search



08:37
13/01/2025



REC-CIS

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3 int main()
4 {
5     int n, flag = 0;
6     char temp;
7     scanf("%d", &n);
8     char words[n][14];
9     for (int i = 0; i < n; i++)
10         scanf("%s", words[i]);
11     char reverse[14];
12     for (int i = 0; i < n - 1; i++)
13     {
14         strcpy(reverse, words[i]);
15         int size = strlen(reverse);
16
17         for (int k = 0; k < size / 2; k++)
18         {
19             temp = reverse[k];
20             reverse[k] = reverse[size - k - 1];
21             reverse[size - k - 1] = temp;
22         }
23
24         for (int j = i + 1; j < n; j++)
25         {
26             if (strcmp(reverse, words[j]) == 0)
27             {
28                 flag = 1;
29                 break;
30             }
31         }
32         if (flag == 1)
33             break;
34     }
35     int len = strlen(reverse);
36     printf("%d %c ", len, reverse[len / 2]);
```



Type here to search

08:37
13/01/2025

REC-CIS

```
36     printf("%d %c ", len, reverse[len / 2]);
37     return 0;
38 }
```

	Input	Expected	Got	
✓	4 abc def feg cba	3 b	3 b	✓

Passed all tests! ✓

Question **3**

Correct

Marked out of 1.00

Flag question

Joey loves to eat Pizza. But he is worried as the quality of pizza made by most of the restaurants is deteriorating. The last few pizzas ordered by him did not taste good :(Joey is feeling extremely hungry and wants to eat pizza. But he is confused about the restaurant from where he should order. As always he asks Chandler for help.

Chandler suggests that Joey should give each restaurant some points, and then choose the restaurant having **maximum points**. If more than one restaurant has same points, Joey can choose the one with **lexicographically smallest** name.

Joey has assigned points to all the restaurants, but can't figure out which restaurant satisfies Chandler's criteria. Can you help him out?

Input:

REC-CIS

Input:

First line has N, the total number of restaurants.

Next N lines contain Name of Restaurant and Points awarded by Joey, separated by a space. Restaurant name has **no spaces**, all lowercase letters and will not be more than 20 characters.

Output:

Print the name of the restaurant that Joey should choose.

Constraints:

$$1 \leq N \leq 10^5$$

$$1 \leq \text{Points} \leq 10^6$$

SAMPLE INPUT

3

Pizzeria 108

Dominos 145

Pizzapizza 49

SAMPLE OUTPUT

REC-CIS

Dominos

Explanation**Dominos** has maximum points.**Answer:** (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3 int main()
4 {
5     int n;
6     scanf("%d", &n);
7     char res[n][21];
8     int rate[n];
9     for (int i = 0; i < n; i++)
10    {
11        scanf("%s", res[i]);
12        scanf("%d", &rate[i]);
13    }
14    int max = rate[0];
15    char ans[20];
16    strcpy(ans, res[0]);
17    for (int i = 1; i < n; i++)
18    {
19        if (rate[i] > max)
20        {
21            max = rate[i];
22            strcpy(ans, res[i]);
23        }
24    }
```



Type here to search

08:37
13/01/2025

▲

Flag question

REC-CIS

Input:

First line of input is T representing total number of test cases.

Next T line each representing "S" as described in in problem statement.

Output:

Print "YES" if it is valid mobile number else print "NO".

Note: Quotes are for clarity.

Constraints:

$$1 \leq T \leq 10^3$$

$$\text{sum of string length} \leq 10^5$$

SAMPLE INPUT

3

1234567890

0123456789

0123456.87

REC-CIS

SAMPLE OUTPUT

YES
NO
NO

Answer: (penalty regime: 0 %)

```
1
2 #include<stdio.h>
3 #include<string.h>
4 int main()
5 {
6     int t;
7     scanf("%d",&t);
8     while(t-->0)
9     {
10         int flag=1;
11         char s[100000];
12         scanf("%s",s);
13         int k=strlen(s);
14         if(k==10)
15         {
16             for(int i=0;i<10;i++)
17             {
18                 if(s[i]!='0')
19                 {
20                     flag=0;
21                     break;
22                 }
23                 if(s[i]<'0' || s[i]>'9')
24                 {
```




1

Duration 42 mins 26 secs

Question 1

Correct

Marked out of 1.00

Flag question

Select a prefix from the string **A** (possibly empty), and increase the alphabetical value of all the characters in the prefix by the same valid amount. For example, if the string is **xyz** and we select the prefix **xy** then we can convert it to **yx** by increasing the alphabetical value by 1. But if we select the prefix **xyz** then we cannot increase the alphabetical value.

Input format

Next line: String **B**

For each test case, print **YES** if string **A** can be converted to string **B**, otherwise print **NO**.

 $1 \leq \text{len}(A) \leq 1000000$
$$1 \leq \text{len}(B) \leq 1000000$$

REC-CIS

$1 \leq \text{len}(B) \leq 1000000$

SAMPLE INPUT

abaca

cdbda

SAMPLE OUTPUT

YES

Explanation

The string **abaca** can be converted to **bcdba** in one move and to **cdbda** in the next move.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 #include<string.h>
3 int main()
4 {
5     char str1[1000000], str2[1000000];
6     int flag = 1;
7     scanf("%s", str1);
8     scanf("%s", str2);
9     int a = strlen(str1);
10    int b = strlen(str2);
11    if (a == b)
```



Type here to search



08:37
13/01/2025



REC-CIS

```
5 char str1[1000000], str2[1000000];
6 int flag = 1;
7 scanf("%s", str1);
8 scanf("%s", str2);
9 int a = strlen(str1);
10 int b = strlen(str2);
11 if (a == b)
12 {
13     for (int i = a - 1; i >= 0; i--)
14     {
15         while (str1[i] != str2[i])
16         {
17             for (int j = 0; j <= i; j++)
18             {
19                 if (str1[j] < 'z')
20                     str1[j]++;
21                 else
22                 {
23                     flag = 0;
24                     break;
25                 }
26             }
27             if (flag == 0)
28                 break;
29         }
30         if (flag == 0)
31             break;
32     }
33 }
34 else
35     flag = 0;
36
37 if (flag == 0)
38     printf("NO");
39 else
40     printf("YES");
41 return 0;
42 }
```



Type here to search

08:37
13/01/2025

▲

Flag question