

1

1

1

REC-CIS

Finish review

Duration61 days / hours

Question 1

Correct

Marked out of 3.00

Flag question

Many people think about their height in feet and inches, even in some countries that primarily use the metric system. Write a program that reads a number of feet from the user, followed by a number of inches. Once these values are read, your program should compute and display the equivalent number of centimeters.

Hint:

One foot is 12 inches.

One inch is 2.54 centimeters.

Input Format

First line,read the number of feet.

Second line, read the number of inches.

Output Format

In one line print the height in centimeters.

Note: All of the values should be displayed using two decimal places.

Sample Input 1

5 6

Sample Output 1

167.64

Answer: (penalty regime: 0 %)

1#include<stdio.h>

2int main()

3{

4int feet,inches;

5float cms;

6scanf("%d %d",&feet, &inches);

REC-CIS

```
1 #include<stdio.h>
2 int main()
3 {
4     int feet,inches;
5     float cms;
6     scanf("%d %d",&feet, &inches);
7     cms=(feet*12*2.54)+(inches*2.54);
8     printf("%.2f",cms);
9     return 0;
10 }
11
```

	Input	Expected	Got	
✓	5	167.64	167.64	✓
	6			

Passed all tests! ✓

REC-CIS

Question 2

Correct

Marked out of
5.00[Flag question](#)

Create a program that reads two integers, a and b, from the user. Your program should compute and display:

- The sum of a and b
- The difference when b is subtracted from a
- The product of a and b
- The quotient when a is divided by b
- The remainder when a is divided by b

Input Format

First line, read the first number.

Second line, read the second number.

Output Format

First line, print the sum of a and b

Second line, print the difference when b is subtracted from a

Third line, print the product of a and b

Fourth line, print the quotient when a is divided by b

Fifth line, print the remainder when a is divided by b

Sample

Input 1 100 6

Sample Output

106 94 600 16 4

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,sum,dif,pr,q,rem;
5     scanf("%d %d",&a,&b);
6     sum=a+b;
7     dif=a-b;
8     pr=a*b;
9     q=a/b;
```



Type here to search



08:15
13/01/2025



▲

1

1

APPENDIX III

▼

REC-CIS

[Flag question](#)

Input Format

Read the number of day old loaves.

Output Format

First line, print Regular price: price

Second line, print Discount: discount

Third line, print Total: total

Note: All of the values should be displayed using two decimal places.

Sample Input 1

10

Sample Output 1

Regular price: 34.90

Discount: 20.94

Total: 13.96

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int n;
5     float r,d,total;
6     scanf("%d",&n);
7     r=n*3.49;
8     d=r*0.6;
9     total=r-d;
10    printf("Regular price: %.2f\n",r);
11    printf("Discount: %.2f\n",d);
12    printf("Total: %.2f",total);
13    return 0;
```



Type here to search



08:15
13/01/2025



1

1

A screenshot of a quiz navigation interface. At the top, the text 'Quiz navigation' is displayed. Below it are three square buttons with rounded corners, each containing a number: '1', '2', and '3'. The buttons are arranged horizontally. Below the buttons, the text 'Show one page at a time' is displayed. At the bottom, there is a blue rectangular button with rounded corners containing the text 'Finish review'.

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Monday, 28 October 2024, 12:35 PM
Duration	56 days 4 hours

Correct

Flag question

INPUT

OUTPUT

CONSTRAINTS

 $1 \leq N \leq 1000000$ $1 \leq X, Y \leq 1000000$

SAMPLE INPUT 1

100 110

SAMPLE OUTPUT 1

YES

SAMPLE INPUT 2

REC-CIS

100 110

SAMPLE OUTPUT 1

YES

SAMPLE INPUT 2

100 90

SAMPLE OUTPUT 2

NO

Answer: (penalty regime: 0 %)

```

1  #include<stdio.h>
2  int main()
3  {
4      int X,Y;
5      scanf("%d",&X);
6      scanf("%d",&Y);
7      if (X>Y)
8          printf("NO");
9      else
10         printf("YES");
11     return 0;
12 }
```



Type here to search



08:16
13/01/2025



Passed all tests! ✓

Flag question

SAMPLE OUTPUT 2

Explanation Case 1: The lonely board member shakes no hands, hence 0. Case 2: There are 2 board members, 1 handshake takes place.

```
1 #include<stdio.h>
2 int main()
3 {
4     int N,result;
5     scanf("%d",&N);
6     result=N*(N-1)/2;
7     printf("%d",result);
8     return 0;
9 }
```

	Input	Expected	Got	
✓	1	0	0	✓
✓	2	1	1	✓

REC-CIS

✓

2

1

1

✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

Flag question

In our school days, all of us have enjoyed the Games period. Raghav loves to play cricket and is Captain of his team. He always wanted to win all cricket matches. But only one last Games period is left in school now. After that he will pass out from school. So, this match is very important to him. He does not want to lose it. So he has done a lot of planning to make sure his teams wins. He is worried about only one opponent - Jatin, who is very good batsman. Raghav has figured out 3 types of bowling techniques, that could be most beneficial for dismissing Jatin. He has given points to each of the 3 techniques. You need to tell him which is the maximum point value, so that Raghav can select best technique. 3 numbers are given in input. Output the maximum of these numbers.

Input:
Three space separated integers.

Output:
Maximum integer value

SAMPLE INPUT

8 6 1

SAMPLE OUTPUT

8

Explanation Out of given numbers, 8 is maximum.

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a,b,c;
5     scanf("%d %d %d",&a,&b,&c);
```