### Experiment – 3 Flask

Name of Student	Shravani Patil
Class Roll No	D15A_37
D.O.P.	11.02.2025
D.O.S.	
Sign and Grade	

**AIM**: To develop a basic Flask application with multiple routes and demonstrate the handling of GET and POST requests.

#### **PROBLEM STATEMENT:**

Design a Flask web application with the following features:

- 1. A homepage (/) that provides a welcome message and a link to a contact form.
  - a. Create routes for the homepage (/), contact form (/contact), and thank-you page (/thank\_you).
- 2. A contact page (/contact) where users can fill out a form with their name and email.
- 3. Handle the form submission using the POST method and display the submitted data on a thank-you page (/thank you).
  - a. On the contact page, create a form to accept user details (name and email).
  - b. Use the POST method to handle form submission and pass data to the thank-you page
- 4. Demonstrate the use of GET requests by showing a dynamic welcome message on the homepage when the user accesses it with a query parameter, e.g.,

/welcome?name=<user name>.

a. On the homepage (/), use a query parameter (name) to display a personalized welcome message.

### Theory:

1. List some of the core features of Flask

Core Features of Flask

- Flask is a lightweight and flexible web framework for Python. Some of its core features include:
- Micro-framework Flask is minimalistic and does not include built-in ORM, authentication, or admin panels.

- Lightweight and Modular Developers can add only the necessary components, keeping applications efficient.
- Built-in Development Server and Debugger Provides an interactive debugger for error tracking.
- Jinja2 Templating Engine Supports dynamic HTML rendering with template inheritance.
  - Routing System Allows handling multiple URLs using route decorators.
- WSGI Compliance Uses Werkzeug as its WSGI toolkit for handling requests.
- Support for RESTful APIs Simplifies API development with built-in support for request handling.
- Extensible with Extensions Many third-party extensions are available for ORM, authentication, and other features.
- 2. Why do we use Flask( name ) in Flask?

The Flask(\_\_name\_\_) function initializes a Flask application. The parameter \_\_name\_\_ helps:

- Identify the App's Module Flask uses it to locate resources, templates, and static files.
- Enable Debugging and Error Handling Helps in logging and debugging by determining the root path of the application.
- Allow Different Import Configurations Ensures Flask works correctly whether run as a script or imported as a module.
- 3. What is Template (Template Inheritance) in Flask?

Flask uses Jinja2 as its templating engine, allowing developers to create dynamic HTML pages.

- Templates: HTML files that contain dynamic placeholders ({{}} for variables and {% %} for control structures like loops and conditions).
- Template Inheritance: A feature where a base template is created with common elements (like headers and footers), and child templates extend it.
- Benefit: Avoids code duplication by keeping the layout consistent across multiple pages.
- 4. What methods of HTTP are implemented in Flask.

Flask supports multiple HTTP methods, including:

- GET Retrieves data from the server.
- POST Submits data to the server (e.g., form submission).
- PUT Updates an existing resource.
- DELETE Deletes a resource.
- PATCH Partially updates an existing resource.

- HEAD Similar to GET but retrieves only headers.
- OPTIONS Returns the allowed HTTP methods for a resource.

# 5. What is difference between Flask and Django framework

Feature	Flask	Django
Туре	Micro-framework (lightweight)	Full-stack framework (batteries included)
Flexibility	More flexible, developers choose components	Less flexible but provides built-in features
Learning Curve	Easier to learn for beginners	Steeper learning curve due to built-in components
Built-in Features	Minimalistic, requires third-party extensions	Comes with authentication, ORM, admin panel, and more
ORM Support	No built-in ORM (uses SQLAlchemy or others)	Has built-in ORM (Django ORM)
Template Engine	Jinja2	Django Template Language (DTL)
Best for	Small projects, APIs, and microservices	Large-scale applications with complex features
Performance	Faster due to minimal structure	Slightly slower due to built-in components
Community Support	Large, but smaller than Django	Very large and widely used for enterprise applications

## **Routing**

```
@app.route('/')
def home():
   name = request.args.get('name', 'Guest') # Default to 'Guest' if no name is provided
   return render_template('index.html', name=name)
```

### **URL** building

```
@app.route('/user/<username>')
def user_profile(username):
    return f"Hello, {username}!"
Instead of hardcoding URLs, Flask provides url_for():
url_for('user_profile', username='Alice')
```

```
GET REQUEST
```

```
@app.route('/')
def home():
  name = request.args.get('name', 'Guest') # Default to 'Guest' if no name is provided
  return f"Welcome, {name}!"
POST REQUEST
@app.route('/contact', methods=['GET', 'POST'])
def contact():
  if request.method == 'POST':
    name = request.form['name']
    email = request.form['email']
    return redirect(url for('thank you', username=name, email=email))
  return render template('contact.html')
OUTPUT
app.py
from flask import Flask, render template, request, redirect, url for
app = Flask(name)
@app.route('/')
def home():
  name = request.args.get('name', 'Guest') # Default to 'Guest' if no name is provided
  return render template('index.html', name=name)
@app.route('/contact/<username>', methods=['GET', 'POST'])
def contact(username):
  if request.method == 'POST':
    name = request.form['name']
    email = request.form['email']
    return redirect(url for('thank you', username=name, email=email))
  return render template('contact.html', username=username)
@app.route('/thank you/<username>/<email>')
def thank you(username, email):
  return render template('thank you.html', username=username, email=email)
if name == ' main ':
  app.run(debug=True)
```

#### Index.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Home</title>
</head>
<body style="font-family: Arial, sans-serif; background-color: #f4f4f4; text-align: center;</p>
padding: 20px;">
  <div style="max-width: 500px; background: white; padding: 20px; margin: auto;</pre>
border-radius: 10px; box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);">
    <h1 style="color: #333;">Welcome, {{ name }}!</h1>
    This is the homepage.
    <a href="{{ url for('contact', username=name) }}" style="display: inline-block;
background-color: #28a745; color: white; padding: 10px; text-decoration: none; border-radius:
5px;">Go to Contact Form</a>
  </div>
</body>
</html>
```

#### Contact.html

```
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Contact</title>
</head>
<body style="font-family: Arial, sans-serif; background-color: #f4f4f4; text-align: center;
padding: 20px;">
  <div style="max-width: 500px; background: white; padding: 20px; margin: auto;</pre>
border-radius: 10px; box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);">
     <h1 style="color: #333;">Contact Us, {{ username }}</h1>
     <form action="{{ url for('contact', username=username) }}" method="post" style="display:</pre>
flex; flex-direction: column; align-items: center;">
       <label for="name" style="margin: 10px 0;">Name:</label>
       <input type="text" id="name" name="name" required value="{{ username }}"</pre>
style="padding: 8px; border: 1px solid #ccc; border-radius: 5px; width: 80%;">
```

```
<label for="email" style="margin: 10px 0;">Email:</label>
       <input type="email" id="email" name="email" required style="padding: 8px; border: 1px</pre>
solid #ccc; border-radius: 5px; width: 80%;">
       <button type="submit" style="background-color: #28a745; color: white; padding: 10px;</p>
border: none; border-radius: 5px; cursor: pointer; margin-top: 15px;">Submit</button>
     </form>
  </div>
</body>
</html>
Thank you.html
<!DOCTYPE html>
<html lang="en">
<head>
  <meta charset="UTF-8">
  <meta name="viewport" content="width=device-width, initial-scale=1.0">
  <title>Thank You</title>
</head>
<body style="font-family: Arial, sans-serif; background-color: #f4f4f4; text-align: center;</p>
padding: 20px;">
  <div style="max-width: 500px; background: white; padding: 20px; margin: auto;</pre>
border-radius: 10px; box-shadow: 0 0 10px rgba(0, 0, 0, 0.1);">
    <h1 style="color: #333;">Thank You, {{ username }}!</h1>
```

<a href="\{\{\text{url\_for('home')}}\}"\ style="display: inline-block; background-color: #007bff; color: white; padding: 10px; text-decoration: none; border-radius: 5px;">Go Back to Home</a>

Your email ({{ email }}) has been received.

</div>
</body>
</html>

## **OUTPUT:**

