

Shravani Pore
D15A_45
Batch B

MPL EXPT 6


AIM:

How To Set Up Firebase with Flutter for iOS and Android Apps


THEORY / STEPS:

(Wherever testing mode is available, I have opted for testing mode.)

1. Create a project in firebase console.



2. Go to authentication section inside the project we have created and enable email/password verification under sign-in method.



3. Similarly enable firestore database.

(Further part is done using Flutter CLI i.e Flutter command line interface)

Following are the commands for the same

4. Installing firebase CLI

npm install -g firebase-tools

5. We have to connect our project with the google account we have made out firebase project on.

firebase login

It would open a browser where we can choose our account.

6. Activation of flutter fire cli

Dart pub global activate flutterfire_cli

7. Configuration of flutterfire

Flutterfire configure

This shows us our firebase projects and we can select our project that we created for this application. I.e app1

8. It would then show us the platforms that we want to make our application compatible for.

9. Configured applications will be now available in firebase.

10. We check the flutter initialization in main function of our application.

```
future: Firebase.initializeApp(),
```

11. We add dependencies:

```
cupertino_icons: ^1.0.2
  firebase_core: ^2.25.4
  firebase_auth: ^4.17.4
  cloud_firestore: 4.15.5
  provider:
```

These should be compatible with the flutter SDK version we are using.

If we get an error with any of these we can try running:

Flutter pub upgrade

Flutter pub get

CODE:

Auth_gate.dart

```

// ignore: unused_import
import 'package:firebase_auth/firebase_auth.dart';
import 'package:flutter/material.dart';
import 'package:twitter/main.dart';

class AuthGate extends StatelessWidget {
  static final GlobalKey<NavigatorState> navigatorKey = GlobalKey();
  const AuthGate({super.key});
  @override
  Widget build(BuildContext context) {
    return Scaffold(
      body: StreamBuilder(
        stream: FirebaseAuth.instance.authStateChanges(),
        builder: (context, snapshot) {
          //user is logged in
          if (snapshot.hasData) {
            return ProfilePage();
          }
          //user is not logged in
          else {
            return LoginPage();
          }
        },
      ),
    );
  }
}

```

Auth_service.dart

```

import 'package:firebase_auth/firebase_auth.dart';
import 'package:flutter/material.dart';
import 'package:cloud_firestore/cloud_firestore.dart';

class AuthService extends ChangeNotifier {
  final FirebaseAuth _firebaseAuth = FirebaseAuth.instance;

  //sign user in
  Future<UserCredential> signInWithEmailandPassword(
    String email, String password) async {
    try {

```

```

        //signin
        UserCredential userCredential =
            await _firebaseAuth.signInWithEmailAndPassword(
                email: email,
                password: password,
            );
        return userCredential;
    } on FirebaseAuthException catch (e) {
        //catch errors
        throw Exception(e.code);
    }
}

Future<void> changePassword(String newPassword) async {
    try {
        // Get the currently logged-in user
        User? user = _firebaseAuth.currentUser;

        // Update the password
        await user!.updatePassword(newPassword);

        // Sign out the user after changing the password
        await signOut();

        // You may choose to navigate the user to the sign-in page or any
other page after password change
    } catch (e) {
        // Handle any errors that occur during password change
        print('Error changing password: $e');
        throw Exception(e);
    }
}

//create a new user
Future<UserCredential> signUpWithEmailandPassword(
    String email, String password) async {
    try {
        //signin
        UserCredential userCredential =
            await _firebaseAuth.createUserWithEmailAndPassword(

```

```

        email: email,
        password: password,
    );
    return userCredential;
} on FirebaseAuthException catch (e) {
    //catch errors
    throw Exception(e.code);
}
}

//sign user out
Future<void> signOut() async {
    return await FirebaseAuth.instance.signOut();
}

}

//saving tweets
Future<void> saveTweet(String tweetText) async {
    try {
        String uid = FirebaseAuth.instance.currentUser!.uid;
        await FirebaseFirestore.instance
            .collection('users')
            .doc(uid)
            .collection('tweets')
            .add({
                'text': tweetText,
                'timestamp': DateTime.now(),
            });
        print('Tweet added successfully');
    } catch (e) {
        print('Error adding tweet: $e');
    }
}
}

```

The functions defined here are called in the pages files. Also some code is added to main file itself and not in the Auth_service file.

OUTPUT:

Authentication:

Search by email address, phone number, or user UID					Add user	↺	⋮
Identifier	Providers	Created ↓	Signed In	User UID			
soham@gmail.com	✉	Feb 21, 2024	Feb 21, 2024	fqTuV23PF3SEdXKSjYd73L7...			
prajakta@gmail.com	✉	Feb 21, 2024	Feb 21, 2024	Z1A4tQFzfKOQeQvCTZji7hqa...			
hetal@gmail.com	✉	Feb 21, 2024	Feb 22, 2024	R152GmwWfwN3dNMVUntnQ...			
shrava@gmail.com	✉	Feb 20, 2024	Feb 21, 2024	vSQ5sRvI90haR5Vs3H5feQST...			
shra@gmail.com	✉	Feb 20, 2024	Feb 20, 2024	8HCmiX3psgN1ntPuE3bVRs9...			
shravani@gmail.com	✉	Feb 20, 2024	Feb 20, 2024	1THqn9uBsAhZZPLyB36cx6T...			
test@gmail.com	✉	Feb 20, 2024		hO5Y6pBv7udESWFOJxgYY2v...			
					Rows per page:	50 ▼	1 – 7 of 7 < >

Tweets in firestore database:

🏠 > users > R152GmwWfwN... > tweets > RF9C0RnFd1ru... ✎			☁ More in Google Cloud ▼
📁 R152GmwWfwN3dNMVUntnQixyH2h1 ⋮	📁 tweets ⌵ ⋮	📁 RF9C0RnFd1ruCqIXBqJb ⋮	
+ Start collection	+ Add document	+ Start collection	
tweets >	RF9C0RnFd1ruCqIXBqJb >	+ Add field	
+ Add field		text: "hello this is shravani"	
		timestamp: February 21, 2024 at 11:06:27 AM UTC+5:30	

With this connection we are able to achieve the following:

- Saving email and password in database.
- Saving tweets and their timestamps in the database under current user's uid.
- Fetching tweets from the database to display on the profile page.
- Updating the values in the database for password in the authentication database.

CONCLUSION:

Connected firebase with twitter clone project and handled related errors.

