



Features :

- Advanced battery charge in UPS OFF mode
- Cold Start
- EMI/RFI noise filter
- Full protection function
- Fully digitized microprocessor control
- High reliability digital control
- High frequency and double conversion online technology
- Highly Efficient up to 91%
- High input power factor 0.99
- LCD Display
- IGBT both Inverter & Rectifier stage
- Short circuit & overload protection
- Smart RS232 communication with monitoring software
- Optional SNMP card slot
- Wide Input voltage range

Application :

- Digital printers
- Server and Other Networking Equipments
- Medical equipments
- Laboratory equipments
- Personal Computers

► REAR PANEL



Technical Specifications :

MODEL	UPS 1000IB	UPS 1000EX	UPS 2000IB	UPS 2000EX	UPS 3000IB	UPS 3000EX
Capacity (VA)	1000		2000		3000	
INPUT						
Nominal Voltage	220 / 230 / 240VAC					
Operating Voltage Range	110-300 VAC (Based on load at 50%), 160-280VAC (based on load at 100%)					
Operating Frequency Range	46-54Hz ± 0.5Hz or 56-64Hz±0.5Hz (auto sensing)					
Power Factor	>0.99					
OUTPUT						
Output Voltage/Power Factor	220 / 230 /240VAC±1%/0.8 Std					
Output Frequency	Synchronized with the utility on AC mode: 50Hz/60Hz, 0.2% on Battery mode					
Harmonic distortion (THD)	<2% (Linear load) <5% (Non Linear Load)					
Crest Factor	3:1 (max)					
Efficiency	>91%					
BATTERY						
DC Voltage	36Vdc		96Vdc			
Battery Type & Number	12V / 7AHx3		12V / 7AHx8		12V / 7AHx8	
Backup Time (50% load)	12 min		19 min		16 min	
Backup Time (Full Load)	5 min		8 min		5 min	
Charge Current (Standard unit)	1Amp					
Charge Current (Long run unit)		6A		6A		6A
Typical recharge time	8 hours (to 90% of full capacity)					
SYSTEM FEATURES						
LCD Indication	1) Input voltage/frequency, battery voltage, Battery percentage output voltage/frequency, Loadwatt /VA, Internal temperature.					
LED Indication	1) Green LED for normal operation 2) Yellow LED for warning condition 3) Red LED for abnormal operation 4) Amber LED for normal battery mode					
Overload Capability	1) >110%, 30s turn to bypass mode 2) >150%, 300ms turn to bypass mode					
Transfer Time	Between AC Mode and Battery Mode - 0 ms Between AC Mode and Bypass Mode: 4ms (typical value 2.5ms)					
Communication Interface	RS232: SNMP (Optional)					
ENVIRONMENTAL						
Operating Temperature	0-40°C					
Storage Temperature	-25-55°C					
Humidity Range	0%-95% (non-condensing)					
Altitude	<1500m					
Noise Level	<45dB					
PHYSICAL						
Dimension W x D x H (mm)	144 x 421 x 215		191 x 478 x 339		191 x 478 x 339	
Packing W x D x H (mm)	258 x 524 x 334		332 x 603 x 482		332 x 603 x 482	
Net/Shipping Weight (kg) (Standard unit)	14/16		33/35		34/36	
Net/Shipping Weight (kg) (Long run unit)	7.5/9		14/16		15/17	
STANDARDS						
Safety	IEC/EN62040-1, IEC/EN60950-1					
EMC	IEC/EN62040-2: IEC61000-4-2, IEC61000-4-3: IEC61000-4-4, IEC61000-4-5, IEC61000-4-5: IEC61000-4-8					

Specifications are subject to change without prior notice.

Web. : www.vp-ups.com

Address : Chopde Audyogik Sankul, Ramtekadi Industrial Area,
Near ION Exam Centre, Plot No. 4/8+9+40, Ramtekdi, Hadapsar, Pune 411028.