

To perform and find the accuracy of K means algorithm

```
In [ ]: #Name: Shruti .P. Arsode
        #Roll No : 03
        #Section: 'A'
```

```
In [23]: import numpy as np # linear algebra
import pandas as pd # data processing, CSV file I/O (e.g. pd.read_csv)
import matplotlib.pyplot as plt # for data visualization
import seaborn as sns # for statistical data visualization
matplotlib inline

import warnings
warnings.filterwarnings('ignore')
```

```
In [4]: os.getcwd()
```

```
Out[4]: 'C:\\Users\\lenovo'
```

```
In [5]: os.chdir('C:\\Users\\lenovo\\Desktop')
```

```
In [6]: df=pd.read_csv('CHD_preprocessed.csv')
```

```
In [7]: df.head()
```

```
Out[7]:
```

	male	age	education	currentSmoker	cigsPerDay	BPMeds	prevalentStroke	prevalentHyp	diabetes	totChol	sysBP	diaBP	BMI	heartRate
0	1	39	1	0	0.0	0.0	0	0	0	195.0	106.0	70.0	26.97	80.1
1	0	46	0	0	0.0	0.0	0	0	0	250.0	121.0	81.0	28.73	95.1
2	1	48	0	1	20.0	0.0	0	0	0	245.0	127.5	80.0	25.34	75.1
3	0	61	1	1	30.0	0.0	0	1	0	225.0	150.0	95.0	28.58	65.1
4	0	46	1	1	23.0	0.0	0	0	0	285.0	130.0	84.0	23.10	85.1

```
In [8]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 4133 entries, 0 to 4132
Data columns (total 16 columns):
#   Column              Non-Null Count  Dtype
---  ---
0   male                 4133 non-null  int64
1   age                  4133 non-null  int64
2   education            4133 non-null  int64
3   currentSmoker        4133 non-null  int64
4   cigsPerDay           4133 non-null  float64
5   BPMeds               4133 non-null  float64
6   prevalentStroke       4133 non-null  int64
7   prevalentHyp         4133 non-null  int64
8   diabetes              4133 non-null  int64
9   totChol              4133 non-null  float64
10  sysBP                4133 non-null  float64
11  diaBP                4133 non-null  float64
12  BMI                  4133 non-null  float64
13  heartRate            4133 non-null  float64
14  glucose              4133 non-null  float64
15  TenYearCHD           4133 non-null  int64
dtypes: float64(8), int64(8)
memory usage: 516.8 KB
```

```
In [9]: df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 4133 entries, 0 to 4132
Data columns (total 16 columns):
#   Column              Non-Null Count  Dtype
---  ---
```

```
0   male          4133 non-null   int64
1   age           4133 non-null   int64
2   education     4133 non-null   int64
3   currentSmoker 4133 non-null   int64
4   cigsPerDay    4133 non-null   float64
5   BPMeds        4133 non-null   float64
6   prevalentStroke 4133 non-null   int64
7   prevalentHyp  4133 non-null   int64
8   diabetes      4133 non-null   int64
9   totChol       4133 non-null   float64
10  sysBP         4133 non-null   float64
11  diaBP         4133 non-null   float64
12  BMI           4133 non-null   float64
13  heartRate     4133 non-null   float64
14  glucose       4133 non-null   float64
15  TenYearCHD    4133 non-null   int64
dtypes: float64(8), int64(8)
memory usage: 516.8 KB
```

```
In [10]: df.size
```

```
Out[10]: 66128
```

```
In [12]: df.shape
```

```
Out[12]: (4133, 16)
```

```
In [13]: df.describe()
```

	male	age	education	currentSmoker	cigsPerDay	BPMeds	prevalentStroke	prevalentHyp	diabetes	totCh
count	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000	4133.000000
mean	0.427293	49.557222	0.280668	0.494798	9.101621	0.034358	0.006049	0.311154	0.025647	236.664400
std	0.494745	8.561628	0.449380	0.500033	11.918440	0.182168	0.077548	0.463022	0.158100	43.909100
min	0.000000	32.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	107.000000
25%	0.000000	42.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	206.000000
50%	0.000000	49.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	0.000000	234.000000
75%	1.000000	56.000000	1.000000	1.000000	20.000000	0.000000	0.000000	1.000000	0.000000	262.000000
max	1.000000	70.000000	1.000000	1.000000	70.000000	1.000000	1.000000	1.000000	1.000000	600.000000

```
In [16]: from sklearn.cluster import KMeans
from sklearn.metrics import adjusted_rand_score
```

```
In [26]: from sklearn.cluster import KMeans

kmeans = KMeans(n_clusters=2, random_state=0)

kmeans.fit(X)
```

```
Out[26]: KMeans(n_clusters=2, random_state=0)
```

```
In [27]: kmeans.cluster_centers_
```

```
Out[27]: array([[3.91715976e-01, 5.22526627e+01, 2.79881657e-01, 4.64497041e-01,
                8.65029586e+00, 5.20710059e-02, 7.69230769e-03, 4.27810651e-01,
                3.07692308e-02, 2.77700592e+02, 1.39265385e+02, 8.59387574e+01,
                2.63765816e+01, 7.74721893e+01, 8.30378698e+01, 1.88757396e-01],
                [4.51903397e-01, 4.76925911e+01, 2.81211625e-01, 5.15759312e-01,
                9.41383545e+00, 2.21039705e-02, 4.91199345e-03, 2.30454359e-01,
                2.21039705e-02, 2.08276709e+02, 1.27594965e+02, 8.07509210e+01,
                2.53648839e+01, 7.48550962e+01, 8.11915677e+01, 1.26483831e-01]])
```

```
In [28]: kmeans.inertia_
```

Out[28]: 9283500.938229598

In []:

Loading [MathJax]/jax/output/CommonHTML/fonts/TeX/fontdata.js