

5G-Cellular-Basics

How a 5G Base Station Operates

A **5G base station** (gNB) is responsible for handling wireless communication between user devices (UEs) and the core network. It operates using advanced **radio access technologies (RATs)** to provide high-speed, low-latency, and massive connectivity. The operation involves **scheduling, signal processing, and multiple access coordination**.

Key Functions of a 5G Base Station (gNB)

1. Radio Resource Management (RRM)

- Allocates spectrum dynamically to users.
- Manages handovers and power control.
- Implements beamforming and spatial multiplexing.

2. Multiple Access Control

- Determines the best **multiple access scheme** (OFDMA, NOMA, MU-MIMO, etc.) based on the network conditions.
- Allocates resources efficiently for different users.

3. Massive MIMO and Beamforming

- Uses **Massive MIMO** to serve multiple users efficiently.
- **Beamforming** directs signals toward specific users, reducing interference.

4. Network Slicing

- Supports **multiple virtual networks** over the same physical infrastructure.
- Assigns resources based on service type (e.g., low-latency for autonomous vehicles, high bandwidth for streaming).

5. Backhaul Connectivity

- Connects to the 5G Core Network (5GC) via fiber or wireless backhaul.
- Manages data traffic between user devices and the internet.

Does a 5G Base Station Use MIMO?

Yes, 5G base stations **extensively use MIMO**, specifically **Massive MIMO**. This involves:

- **Large Antenna Arrays** (e.g., 64×64 , 128×128).
- **Beamforming** for precise signal targeting.
- **MU-MIMO (Multi-User MIMO)** to communicate with multiple users simultaneously.

Massive MIMO Benefits:

- Increases spectral efficiency.
 - Enhances signal strength and reliability.
 - Supports more users in dense urban areas.
-

How Does a 5G Base Station Decide on a Multiple Access Scheme?

A 5G base station dynamically selects the **best multiple access technique** based on several factors:

1. User Density & Traffic Load

- **OFDMA** is used for general users (provides orthogonal subcarriers).
- **NOMA** is applied when users have similar frequency allocations but different power levels.
- **MU-MIMO** is used when multiple users can be spatially separated.

2. Channel Conditions & Interference

- If channel conditions are good: **MU-MIMO** is preferred.
- If interference is high: **Beamforming** is applied to mitigate it.
- If users have poor channel conditions: **NOMA** can be used.

3. Service Type (QoS Requirements)

- **Low-latency services (e.g., URLLC)** → Uses low-latency scheduling and dedicated resources.
- **High-bandwidth applications (eMBB)** → Allocates wide OFDMA subcarriers.
- **Massive IoT (mMTC)** → Uses grant-free access schemes and NOMA.

4. Network Conditions & Slicing

- Network slicing enables different access schemes per slice (e.g., URLLC slice uses dedicated spectrum).
- AI/ML-based optimizations dynamically adjust access techniques.

Conclusion

- **5G base stations use Massive MIMO** for better spectral efficiency.
- **They dynamically select multiple access schemes** (OFDMA, NOMA, MU-MIMO) based on network conditions, user demand, and service requirements.
- **Beamforming and spatial multiplexing** enhance network capacity and reduce interference.

This flexibility enables **high-speed, low-latency, and efficient** wireless communication in 5G networks. 🚀

Detailed Description of 5G Network Operation and Functionalities of Each Entity

The **5G network architecture** is designed to support **ultra-fast data rates, ultra-low latency, massive device connectivity, and high reliability**. It operates based on a **service-based architecture (SBA)**, dividing functionalities between the **Radio Access Network (RAN)**, **Core Network (5GC)**, and **Transport Network**.

1. 5G Network Architecture Overview

a) 5G Core Network (5GC)

The **5G Core Network (5GC)** is based on a **cloud-native, service-based architecture (SBA)** and is responsible for handling data routing, mobility management, security, and quality of service (QoS). It replaces the LTE EPC (Evolved Packet Core) with a modular approach.

b) 5G Radio Access Network (5G RAN)

The **5G RAN** consists of **gNBs (Next-Generation Base Stations)**, which provide wireless connectivity to UEs (User Equipment). It supports **Massive MIMO, Beamforming, and Dynamic Spectrum Sharing (DSS)**.

c) 5G Transport Network

The **transport network** connects the RAN to the 5G Core and provides high-speed fiber or wireless backhaul. It supports **network slicing** to allocate resources dynamically.

2. Functional Entities in a 5G Network

A. User Equipment (UE)

Functionality:

- Mobile devices, IoT sensors, and other 5G-enabled devices.
 - Supports **dual connectivity** (LTE + 5G) and **multi-RAT (Radio Access Technology)**.
 - Communicates with the **gNB** via **5G NR (New Radio)**.
-

B. 5G Radio Access Network (5G RAN)

Functionality:

- Handles **radio signal transmission** and **wireless communication**.
- Manages **beamforming, Massive MIMO, and dynamic resource allocation**.
- Connects to the **5G Core (5GC)** via the **NG interface**.

Key Components:

1. gNB (Next-Generation Node B)

- The 5G base station responsible for radio communication with UEs.
- Uses **OFDMA, NOMA, and MU-MIMO** to maximize spectral efficiency.
- Interfaces:
 - **NG-C (Control Plane) to AMF in 5GC**
 - **NG-U (User Plane) to UPF in 5GC**

2. DU (Distributed Unit)

- Manages **real-time baseband processing**, such as scheduling and beamforming.
- Lower Layer (L1/L2) functions like **HARQ, MAC, and PHY layer processing**.

3. CU (Centralized Unit)

- Handles **higher-layer functions**, including RRC (Radio Resource Control) and SDAP (Service Data Adaptation Protocol).
 - Communicates with **DUs via the F1 interface**.
-

C. 5G Core Network (5GC)

The **5GC (5G Core Network)** is **fully cloud-native** and uses **Service-Based Architecture (SBA)** to enable flexible service management.

Core Network Functional Entities:

1. AMF (Access and Mobility Management Function)

- Handles **UE authentication, mobility management, and security**.
- Communicates with **gNB** and **UPF** via NGAP protocol.

2. SMF (Session Management Function)

- Manages **PDU (Packet Data Unit) sessions** and **IP address allocation**.
- Selects the **UPF (User Plane Function)** for traffic routing.

3. UPF (User Plane Function)

- Routes user traffic to the internet or enterprise networks.
- Handles **traffic steering, QoS enforcement, and packet filtering**.

4. PCF (Policy Control Function)

- Defines policies for **QoS management, traffic prioritization, and slicing**.
- Ensures compliance with operator-defined rules.

5. UDM (Unified Data Management)

- Stores **user subscription data, profiles, and authentication credentials**.

6. NEF (Network Exposure Function)

- Enables external applications to access 5G network capabilities via APIs.

7. NSSF (Network Slice Selection Function)

- Allocates **network slices** based on user requirements (e.g., URLLC, eMBB, mMTC).

8. AUSF (Authentication Server Function)

- Performs **user authentication** with SIM or other identity mechanisms.

9. NWDAF (Network Data Analytics Function)

- Uses **AI/ML for traffic analysis, predictive maintenance, and anomaly detection**.

3. 5G Network Operation Flow

Step 1: UE Attach & Authentication

- The **UE connects** to the **gNB** via 5G NR.
- The **AMF authenticates** the user with **AUSF and UDM**.
- The **SMF assigns an IP address** and establishes a PDU session.

Step 2: Network Slicing & Resource Allocation

- **NSSF selects a network slice** based on user requirements.
- **PCF enforces policies** for QoS and traffic management.

- **UPF routes traffic** to the desired network destination.

Step 3: Data Transmission & Mobility Management

- The **gNB schedules radio resources** dynamically.
- **Beamforming and MU-MIMO** enhance user connectivity.
- The **AMF handles handovers** to maintain connectivity.

Step 4: Service Termination & Session Release

- **SMF deallocates resources** after service completion.
 - **AMF deregisters the UE** when it detaches from the network.
-

4. 5G Network Features & Enhancements

a) Network Slicing

- Creates **virtual networks** for different applications (e.g., IoT, gaming, industrial automation).
- Ensures **optimized performance** for each use case.

b) Edge Computing (MEC)

- Deploys **processing closer to users** to reduce latency.
- Used for applications like **autonomous driving and AR/VR**.

c) Beamforming & Massive MIMO

- **Beamforming** focuses energy toward the user.
- **Massive MIMO** increases capacity using large antenna arrays.

d) Dual Connectivity (NSA Mode)

- **4G LTE + 5G NR** coexists in **Non-Standalone (NSA) mode**.
- Ensures **seamless migration from LTE to 5G**.

e) Ultra-Low Latency & High Reliability

- 5G enables **1 ms latency** for applications like **remote surgery**.
- URLLC (Ultra-Reliable Low-Latency Communication) ensures **99.999% reliability**.

5. Summary of 5G Network Entities and Their Roles

Entity	Functionality
UE (User Equipment)	Connects to the 5G network via gNB
gNB (Next-Generation NodeB)	Provides wireless access and communicates with 5GC
DU (Distributed Unit)	Manages real-time signal processing
CU (Centralized Unit)	Handles higher-layer functions (RRC, SDAP)
AMF	Manages access, mobility, and security
SMF	Manages session establishment and IP allocation
UPF	Routes user traffic to the internet or private networks
PCF	Controls QoS, policies, and network slicing
UDM	Stores user subscription and authentication data
AUSF	Handles authentication
NSSF	Selects network slices
NEF	Provides APIs for external applications
NWDAF	Performs AI-based analytics

Conclusion

- The **5G network is highly flexible, scalable, and cloud-native**.
- It **uses network slicing, edge computing, and AI-driven optimizations**.
- **Massive MIMO, Beamforming, and OFDMA/NOMA** improve spectral efficiency.
- The **service-based architecture (SBA)** ensures **faster service deployment and management**.

Inside the 5G Core (5GC): Architecture & Functionalities

The **5G Core (5GC)** is a **cloud-native, service-based architecture (SBA)** that replaces the **LTE Evolved Packet Core (EPC)**. It provides **high-speed connectivity, ultra-low latency, and massive IoT support** by enabling **flexible service orchestration, network slicing, and edge computing**.

1. 5G Core Network Architecture

The **5GC** consists of **interconnected network functions (NFs)**, each with a specialized role. These NFs communicate through **HTTP-based APIs**, making the 5GC more **scalable and flexible** than traditional networks.

Key Functional Entities in the 5G Core:

1. **AMF (Access and Mobility Management Function)**
2. **SMF (Session Management Function)**
3. **UPF (User Plane Function)**
4. **PCF (Policy Control Function)**
5. **UDM (Unified Data Management)**
6. **AUSF (Authentication Server Function)**
7. **NSSF (Network Slice Selection Function)**
8. **NEF (Network Exposure Function)**
9. **NWDAF (Network Data Analytics Function)**
10. **CHF (Charging Function)**

Each entity provides a **modular, microservice-based function**, enabling **dynamic and optimized 5G network operations**.

2. Functional Entities and Their Roles in 5GC

A. Control Plane Functions

These entities handle **signaling, authentication, policy control, and session management**.

1. AMF (Access and Mobility Management Function)

- Handles **UE authentication and registration**.
- Manages **mobility and handovers** between gNBs.
- Interacts with **SMF to establish PDU sessions**.
- **Replaces MME (Mobility Management Entity) from LTE**.

2. SMF (Session Management Function)

- Manages **PDU (Packet Data Unit) sessions** and IP address allocation.
- Controls **traffic flow policies**.
- Selects **User Plane Function (UPF)** for data routing.
- Supports **session continuity during handovers**.

3. PCF (Policy Control Function)

- Defines policies for **QoS (Quality of Service), traffic prioritization, and data limits**.
- Manages **network slicing policies**.
- Ensures user **subscription-based data handling**.

4. UDM (Unified Data Management)

- Stores **user subscription profiles and authentication data**.
- Manages **subscriber policies** (e.g., data limits, roaming).
- Works alongside **AUSF for authentication**.

5. AUSF (Authentication Server Function)

- Performs **mutual authentication** between UE and network.
- Uses **EAP-AKA** and **5G SIM authentication** mechanisms.
- Ensures **secure user access**.

6. NSSF (Network Slice Selection Function)

- Allocates **specific network slices** based on user or service type.
- Supports **multiple slices for different applications** (e.g., eMBB, URLLC, mMTC).
- Works with **PCF for policy-based slicing**.

7. NEF (Network Exposure Function)

- Provides APIs for **external applications** (e.g., IoT services, cloud providers).
- Supports **network slicing, QoS adjustments, and security functions**.
- Facilitates **edge computing and 3rd-party service integration**.

8. NWDAF (Network Data Analytics Function)

- Uses **AI/ML for predictive analytics and anomaly detection**.
- Optimizes **network resource allocation** based on usage trends.
- Enhances **QoS and energy efficiency**.

9. CHF (Charging Function)

- Handles **real-time billing, prepaid/postpaid charging**.
 - Monitors **data consumption and service usage**.
 - Works with **PCF for policy-based charging**.
-

B. User Plane Function (UPF)

The **UPF (User Plane Function)** is the **only user plane entity** in the 5GC, handling **actual data transfer**.

UPF Functions:

- Routes **user data traffic** between the RAN and the internet.
- Enforces **QoS, packet filtering, and traffic prioritization**.
- Supports **Multi-Access Edge Computing (MEC)** for ultra-low latency applications.

- Can be deployed **closer to the edge** for better performance.
-

3. 5G Core Operation Flow

Step 1: UE Registration & Authentication

1. **UE connects to gNB (5G base station)** using **5G NR**.
2. **gNB communicates with AMF** over the NG-C (Control Plane) interface.
3. **AMF authenticates UE** via **AUSF and UDM**.
4. **AMF assigns a slice** via **NSSF** (if applicable).

Step 2: Session Establishment & IP Allocation

1. **SMF selects UPF** for user data routing.
2. **SMF assigns an IP address** and configures the session.
3. **PCF applies QoS rules and policy enforcement**.

Step 3: Data Transmission

1. **UPF routes data** between the UE and the internet.
2. **PCF monitors QoS**, ensuring latency and bandwidth requirements are met.
3. **NWDAF analyzes traffic** to optimize resource allocation.

Step 4: Mobility & Handover

1. **AMF manages handovers** between different gNBs.
2. **UPF ensures seamless session continuity**.
3. **SMF updates routing policies dynamically**.

Step 5: Network Slice Management

1. **NSSF assigns slices** to UEs based on application needs.
2. **NEF exposes APIs** for external applications to request specific network behaviors.

Step 6: Service Termination

1. **UE session is released** by SMF.
2. **PCF updates billing records** via CHF.
3. **AMF de-registers the UE.**

4. Key Advantages of 5GC over LTE EPC

Feature	5G Core (5GC)	LTE EPC (Evolved Packet Core)
Architecture	Service-Based (SBA)	Hierarchical
Flexibility	Microservices-based, cloud-native	Fixed functions
Network Slicing	Supports multiple slices per user	Not supported
Latency	<1ms (URLLC support)	10-50ms
Edge Computing	Supported (via UPF placement)	Limited
AI/Analytics	Integrated (via NWDAF)	Not present

5. Summary of 5GC Entities and Their Functions

5GC Entity	Functionality
AMF	Manages authentication, mobility, and access control
SMF	Handles session establishment and IP allocation
UPF	Routes user traffic to the internet or private networks
PCF	Controls QoS, policy enforcement, and slicing
UDM	Stores subscriber data and policies
AUSF	Manages user authentication
NSSF	Allocates network slices
NEF	Provides APIs for external applications
NWDAF	Performs AI-based analytics
CHF	Handles billing and charging

Conclusion

- **5G Core (5GC)** is cloud-native and microservices-based, allowing **greater flexibility and scalability**.
- It supports **network slicing, ultra-low latency, edge computing, and AI-based analytics**.
- **The separation of control and user planes (CUPS)** improves performance and **reduces latency**.
- **UPF enables edge computing**, making 5G ideal for **real-time applications** like **autonomous driving, IoT, and VR**.

Would you like details on specific **5GC functions** or **deployment models**? 🚀

In **5G**, the network is logically divided into two major planes:

1. **Control Plane (CP)** – Handles signaling, mobility, and session management.
2. **User Plane (UP)** – Carries user data traffic (actual data transmission).

1. User Plane vs. Control Plane in 5G

Feature	User Plane (UP)	Control Plane (CP)
Function	Handles user data transmission	Manages signaling, authentication, and mobility
Components in 5G Core (5GC)	UPF (User Plane Function)	AMF, SMF, PCF, UDM, AUSF, NSSF, etc.
Components in 5G RAN	gNB-DU (Distributed Unit)	gNB-CU (Central Unit - Control Plane)
Traffic Type	High-bandwidth user data (e.g., video streaming, web browsing)	Low-bandwidth signaling messages
Protocols	GTP-U (GPRS Tunneling Protocol - User Plane)	HTTP/2, SCTP, NGAP, PFCP
Latency Requirement	Ultra-low latency for real-time apps (e.g., gaming, VR)	Tolerant to some delay
Example Operations	Forwarding packets between the UE and the internet via UPF	Managing mobility, handovers, session setup, and authentication

How They Work Together in 5G

- The **Control Plane (CP)** decides how and where the user data should be routed.
- The **User Plane (UP)** carries the actual user traffic based on CP decisions.
- The **UPF (User Plane Function)** forwards data packets, while **AMF (Access and Mobility Management Function)** handles mobility.

Difference Between Distributed Unit (DU) & Centralized Unit (CU) in 5G RAN

In **5G Radio Access Network (RAN)**, the **gNB (Next-Generation NodeB)** is divided into two logical units:

1. **DU (Distributed Unit)** – Handles lower-layer processing closer to the user.
2. **CU (Central Unit)** – Handles higher-layer functions, can be centralized.

2. Distributed Unit (DU) vs. Centralized Unit (CU) in 5G RAN

Feature	Distributed Unit (DU)	Centralized Unit (CU)
Location	Placed closer to users (cell site)	Can be placed at a regional/cloud data center
Function	Handles real-time, low-latency radio processing	Manages high-level radio control and signaling
Layer Processing	L1 (Physical Layer) & L2 (MAC, HARQ, RLC)	L3 (RRC - Radio Resource Control, SDAP - QoS management)
Latency Sensitivity	Highly latency-sensitive	Can tolerate some delay
Interfaces	Connects to CU via F1 interface	Connects to Core Network via NG interface
Example Operations	Beamforming, scheduling, HARQ, MAC retransmissions	RRC signaling, handover decisions, policy enforcement

How DU and CU Work Together in 5G

- The **DU** handles **real-time, latency-critical processing** like **beamforming and HARQ**.
 - The **CU** processes **non-time-sensitive signaling** like **RRC (Radio Resource Control)** and session management.
 - The **CU** can be centralized to **optimize resource allocation and enable cloud-based RAN (C-RAN)**.
-

Key Relationships Between These Concepts

1. User Plane (UP) & Control Plane (CP) in 5G Core:

- **UPF (User Plane)** = Forwards user data.
- **AMF, SMF, PCF (Control Plane)** = Manage mobility, authentication, and session setup.

2. DU & CU in 5G RAN:

- **DU (Distributed Unit)** = Handles **User Plane functions** (real-time radio processing).
- **CU (Centralized Unit - CP)** = Handles **Control Plane functions** (high-level RAN management).

Example Flow: How These Components Work Together

1. **UE requests a connection** → Handled by **AMF (Control Plane)** in 5GC.
 2. **AMF authenticates UE** via **AUSF & UDM (Control Plane)**.
 3. **SMF sets up session** and selects **UPF (User Plane)** for data transfer.
 4. **UPF forwards user data** via the **DU (User Plane)** in RAN.
 5. **CU (Control Plane in RAN)** manages **handovers** and **QoS policies**.
-

Conclusion

- **User Plane (UP)** = Carries user data (UPF, DU).
- **Control Plane (CP)** = Manages signaling (AMF, SMF, CU).

- **DU (Distributed Unit) = Real-time, low-latency radio processing.**
- **CU (Centralized Unit) = High-level radio control and RRC functions**

Difference Between HTTP and FTP

Overview

HTTP (**H**ypertext **T**ransfer **P**rotocol) and FTP (**F**ile **T**ransfer **P**rotocol) are both used for data transfer over the Internet, but they serve different purposes and operate differently.

Feature	HTTP (Hypertext Transfer Protocol)	FTP (File Transfer Protocol)
Purpose	Transfers web pages, images, and multimedia from web servers to browsers	Transfers files between computers over a network
Port Used	Port 80 (HTTP), Port 443 (HTTPS - Secure HTTP)	Port 21 (Control), Port 20 (Data)
Connection Type	Stateless, request-response protocol	Stateful, persistent connection
Authentication	No authentication required (except for login-protected pages)	Requires username & password (anonymous FTP is allowed)
Encryption	HTTPS encrypts data using TLS/SSL	FTPS (FTP Secure) and SFTP (SSH FTP) encrypt data
Data Transfer Mode	Transfers hypertext, media, and documents	Transfers files (binary or text mode)
Control & Data Connection	Uses a single connection for both control and data transfer	Uses two separate channels (Control: Port 21, Data: Port 20)
Speed	Faster for small web files (HTML, CSS, JS, images)	Faster for large file transfers
Use Cases	Web browsing, accessing websites, REST API communication	Uploading/downloading large files, website backups, file sharing

Key Differences in Detail

1. Connection Type

- **HTTP is stateless:** It creates a new connection for each request and does not maintain a session.
- **FTP is stateful:** It establishes a persistent connection between the client and the server, which remains open until explicitly closed.

2. Ports & Communication Model

- **HTTP uses a single connection (Port 80 or 443 for HTTPS).**
- **FTP uses two connections:**
 - **Control Connection (Port 21)** – For sending commands (e.g., login, navigation).
 - **Data Connection (Port 20 or dynamically assigned)** – For transferring files.

3. Security & Encryption

- **HTTP itself is not secure** (data is sent in plain text), but **HTTPS uses TLS/SSL encryption** for secure communication.
- **FTP sends login credentials in plaintext**, making it insecure, but **SFTP (Secure FTP) and FTPS (FTP over SSL/TLS) encrypt data.**

4. Data Transfer Mode

- **HTTP transfers structured content** (HTML, CSS, JSON, etc.), making it ideal for web browsing and API communication.
- **FTP transfers files** (either binary or text) and is optimized for **large file transfers.**

Use Case Examples

When to Use HTTP?

- ✓ Browsing websites
- ✓ Streaming videos and images
- ✓ API requests and responses
- ✓ Online shopping, banking, and web applications

When to Use FTP?

- ✓ Uploading/downloading large files
 - ✓ Managing website files on a remote server
 - ✓ Backing up data to a remote location
 - ✓ Sharing large documents or media files
-

Conclusion

- **HTTP is for accessing web pages**, APIs, and streaming media.
- **FTP is for transferring files** between computers efficiently.
- **HTTPS and SFTP/FTPS provide encryption for security.**

In a 5G RAN (Radio Access Network), the **Distributed Unit (DU)** and **Centralized Unit (CU)** correspond to different layers of the **OSI (Open Systems Interconnection)** model, depending on their functions and tasks.

Here's how the OSI layers associate with the **DU** and **CU** in the 5G architecture:

1. Centralized Unit (CU)

The **Centralized Unit (CU)** handles higher-layer control and management functions in the 5G RAN and is mainly responsible for the **Control Plane (CP)** operations.

CU OSI Layer Mapping

- **Layer 3: Network Layer** (primarily the control plane functions)

- The CU deals with **Radio Resource Control (RRC)** and higher layers, such as **Mobility Management (MME)** functions.
- It handles tasks like **session management**, **radio link management**, and **QoS (Quality of Service) management**.
- **Layer 2: Data Link Layer** (partially)
 - The CU handles control signaling for packet scheduling, radio bearer management, and signaling for scheduling requests to the DU.
- **Layer 1: Physical Layer** (minimal control)
 - The CU generally does not deal with actual physical data transmission but interacts with the DU to influence this indirectly via scheduling information and resource allocations.

Key Functions in CU (Control Plane)

- **RRC (Radio Resource Control)**: Handles signaling related to cell access, mobility, and QoS parameters.
- **SDAP (Service Data Adaptation Protocol)**: Implements QoS management by mapping different services to the appropriate bearer paths.
- **S1 Interface**: This is the interface between the CU and the **Core Network (5GC)** for the transport of control-plane messages.

CU Example

The **CU** primarily communicates with the **Core Network** (like AMF, SMF) and manages the overall configuration and control of the radio access.

2. Distributed Unit (DU)

The **Distributed Unit (DU)** handles lower-layer functions, including real-time **user-plane data** processing. It's more focused on **data transmission** between the user equipment (UE) and the internet or core network, and it is typically responsible for:

- **Layer 1 (Physical Layer)**: The DU processes signals and modulates data for wireless communication with the UE. It handles **radio frequency (RF)**

processing, beamforming, modulation, coding, and HARQ (Hybrid Automatic Repeat Request).

- **Layer 2 (Data Link Layer):** The DU handles **Medium Access Control (MAC)** and **Radio Link Control (RLC)** functions for controlling how data is transmitted and managed over the radio link.
 - **MAC:** Deals with resource scheduling, error correction, and retransmission.
 - **RLC:** Handles segmentation, reassembly, and retransmission of data packets.
- **Layer 3 (Network Layer):** Although most Layer 3 functions are carried out by the CU, the DU may also perform certain tasks related to packet forwarding and routing for data packets.

Key Functions in DU (User Plane)

- **PHY (Physical Layer):** Actual radio transmission and reception, converting bits into signals that can be sent via radio waves.
- **MAC (Medium Access Control):** Scheduling resources, managing access to the wireless medium, and ensuring proper transmission.
- **RLC (Radio Link Control):** Ensures reliable transmission over the air interface, performing retransmissions if necessary.
- **PDCP (Packet Data Convergence Protocol):** This layer provides header compression and encryption, often functioning in the DU for data transfer optimization.

DU Example

The **DU** directly communicates with the **gNB (Next-Generation Node B)**, which is responsible for controlling the physical layer and ensuring the correct user data transmission over the radio interface.

Summary of OSI Layer Mapping in DU and CU

Component	OSI Layer	Description
-----------	-----------	-------------

Centralized Unit (CU)	Layer 3: Network Layer	Handles Control Plane functions such as RRC signaling, mobility management, and session management.
Distributed Unit (DU)	Layer 1: Physical Layer, Layer 2: Data Link Layer, Layer 3: Network Layer	Handles data transmission, resource scheduling, error correction, and modulation/demodulation.

DU & CU Communication

- The **CU** manages **higher-layer control operations**, while the **DU** handles the **lower-layer real-time data processing**.
- **CU** communicates with the **Core Network** (AMF, SMF) and influences how resources are managed at the **DU** level.

Conclusion

- **CU (Centralized Unit)** is focused on **control-plane tasks** (Layer 3), such as **signaling, mobility management, and session management**.
- **DU (Distributed Unit)** focuses on **user-plane tasks** (Layer 1 and Layer 2), such as **radio processing, scheduling, and data transmission**.

In a 5G RAN (Radio Access Network), the **Distributed Unit (DU)** and **Centralized Unit (CU)** correspond to different layers of the **OSI (Open Systems Interconnection)** model, depending on their functions and tasks.

Here's how the OSI layers associate with the **DU** and **CU** in the 5G architecture:

1. Centralized Unit (CU)

The **Centralized Unit (CU)** handles higher-layer control and management functions in the 5G RAN and is mainly responsible for the **Control Plane (CP)** operations.

CU OSI Layer Mapping

- **Layer 3: Network Layer** (primarily the control plane functions)
 - The CU deals with **Radio Resource Control (RRC)** and higher layers, such as **Mobility Management (MME)** functions.
 - It handles tasks like **session management**, **radio link management**, and **QoS (Quality of Service) management**.
- **Layer 2: Data Link Layer** (partially)
 - The CU handles control signaling for packet scheduling, radio bearer management, and signaling for scheduling requests to the DU.
- **Layer 1: Physical Layer** (minimal control)
 - The CU generally does not deal with actual physical data transmission but interacts with the DU to influence this indirectly via scheduling information and resource allocations.

Key Functions in CU (Control Plane)

- **RRC (Radio Resource Control)**: Handles signaling related to cell access, mobility, and QoS parameters.
- **SDAP (Service Data Adaptation Protocol)**: Implements QoS management by mapping different services to the appropriate bearer paths.
- **S1 Interface**: This is the interface between the CU and the **Core Network (5GC)** for the transport of control-plane messages.

CU Example

The **CU** primarily communicates with the **Core Network** (like AMF, SMF) and manages the overall configuration and control of the radio access.

2. Distributed Unit (DU)

The **Distributed Unit (DU)** handles lower-layer functions, including real-time **user-plane data** processing. It's more focused on **data transmission** between the user equipment (UE) and the internet or core network, and it is typically responsible for:

- **Layer 1 (Physical Layer):** The DU processes signals and modulates data for wireless communication with the UE. It handles **radio frequency (RF) processing, beamforming, modulation, coding**, and **HARQ (Hybrid Automatic Repeat Request)**.
- **Layer 2 (Data Link Layer):** The DU handles **Medium Access Control (MAC)** and **Radio Link Control (RLC)** functions for controlling how data is transmitted and managed over the radio link.
 - **MAC:** Deals with resource scheduling, error correction, and retransmission.
 - **RLC:** Handles segmentation, reassembly, and retransmission of data packets.
- **Layer 3 (Network Layer):** Although most Layer 3 functions are carried out by the CU, the DU may also perform certain tasks related to packet forwarding and routing for data packets.

Key Functions in DU (User Plane)

- **PHY (Physical Layer):** Actual radio transmission and reception, converting bits into signals that can be sent via radio waves.
- **MAC (Medium Access Control):** Scheduling resources, managing access to the wireless medium, and ensuring proper transmission.
- **RLC (Radio Link Control):** Ensures reliable transmission over the air interface, performing retransmissions if necessary.
- **PDCP (Packet Data Convergence Protocol):** This layer provides header compression and encryption, often functioning in the DU for data transfer optimization.

DU Example

The **DU** directly communicates with the **gNB (Next-Generation Node B)**, which is responsible for controlling the physical layer and ensuring the correct user data transmission over the radio interface.

Summary of OSI Layer Mapping in DU and CU

Component	OSI Layer	Description
Centralized Unit (CU)	Layer 3: Network Layer	Handles Control Plane functions such as RRC signaling, mobility management, and session management.
Distributed Unit (DU)	Layer 1: Physical Layer, Layer 2: Data Link Layer, Layer 3: Network Layer	Handles data transmission, resource scheduling, error correction, and modulation/demodulation.

DU & CU Communication

- The **CU** manages **higher-layer control operations**, while the **DU** handles the **lower-layer real-time data processing**.
- **CU** communicates with the **Core Network** (AMF, SMF) and influences how resources are managed at the **DU** level.

Conclusion

- **CU (Centralized Unit)** is focused on **control-plane tasks** (Layer 3), such as **signaling, mobility management, and session management**.
- **DU (Distributed Unit)** focuses on **user-plane tasks** (Layer 1 and Layer 2), such as **radio processing, scheduling, and data transmission**.

How OSI Layers Interact During Specific Operations (e.g., Handover, Data Transfer) in 5G RAN

In a 5G network, the **Distributed Unit (DU)** and **Centralized Unit (CU)** work together to ensure efficient **data transfer** and **mobility management**, such as **handover**. Here's how the OSI layers interact during these operations:

1. Data Transfer Operation:

Step-by-Step Flow:

When a **User Equipment (UE)** requests data (such as browsing a website or streaming video), the data transfer process goes through different layers of the

network, with the **DU** and **CU** handling specific functions at different OSI layers.

Step 1: UE Requests Data (Application Layer)

- **Layer 7 (Application Layer):** The UE requests data from an external server (e.g., a website) via an HTTP request (or another application layer protocol).
 - **Example:** `GET /index.html HTTP/1.1`

Step 2: Session Setup (Control Plane - Layer 3)

- **Layer 3 (Network Layer):** The **CU** (Control Plane) initiates the session setup between the **UE** and the **Core Network** (5GC).
 - **Session Management Function (SMF)** is responsible for setting up the bearer for data transfer.
 - **AMF (Access and Mobility Management Function)** establishes the connection with the **UE** and manages authentication.

Step 3: Bearer Establishment (Layer 3 and 2)

- **Layer 2 (Data Link Layer) and Layer 3 (Network Layer):** The **CU** manages bearer resources (QoS parameters, routing) and informs the **DU** about how to route the data from the UE.
 - **SMF** establishes the bearer path through the **User Plane Function (UPF)**.
 - **RRC (Radio Resource Control)** in the **CU** signals the **DU** about the bearer setup.

Step 4: Data Transmission (Layer 1 and 2)

- **Layer 1 (Physical Layer) and Layer 2 (Data Link Layer):** The **DU** handles the actual **radio transmission** and **resource scheduling** for data transfer.
 - **MAC (Medium Access Control)** in the **DU** schedules resources for the UE.
 - The **PHY** layer in the **DU** modulates and demodulates the data.
 - **RLC (Radio Link Control)** at the **DU** handles retransmissions if there are any errors in transmission.

Step 5: Data Forwarding to the Core Network (Layer 2 and 3)

- **Layer 2 (Data Link Layer):** The **DU** forwards the data to the **UPF (User Plane Function)** in the **Core Network**, using GTP (GPRS Tunneling Protocol) for packet forwarding.
 - **Layer 3 (Network Layer):** **UPF** routes the data to the destination (e.g., internet server or external application).
-

2. Handover Operation:

When a **UE** moves from one cell to another (e.g., due to mobility), **handover** ensures that the connection is seamlessly transferred from one **gNB (Next-Generation Node B)** to another, without interrupting the service. Handover involves interaction between both the **CU** and **DU** at multiple layers.

Step-by-Step Flow:

Step 1: Handover Trigger (Control Plane - Layer 3)

- **Layer 3 (Network Layer):** As the **UE** moves toward a different cell, the **CU** detects a **handover trigger** based on signal strength or mobility patterns. This is communicated to the **AMF** and **SMF** in the Core Network.
 - The **AMF** sends a **handover request** to the new gNB, which will act as the target for the handover.
 - **RRC (Radio Resource Control)** signaling between **gNB-CU** and **gNB-DU** is initiated.

Step 2: Handover Preparation (Control & User Plane - Layer 3 and 2)

- **Layer 3 (Network Layer):** The **CU** communicates with the **SMF** and **AMF** to establish the bearer in the target gNB, ensuring QoS continuity.
 - The **AMF** forwards the **handover request** to the target gNB, and the **SMF** reconfigures the bearer path.
- **Layer 2 (Data Link Layer):** The **DU** in the target cell (new gNB) prepares its resources for the **UE**.
 - The **target DU** starts scheduling radio resources for the incoming **UE**.

- **RLC** and **MAC** layers in both the source and target **DU** ensure that the data buffers are correctly managed.

Step 3: Data Forwarding and Handover Execution (Layer 2 and 1)

- **Layer 1 (Physical Layer):** The **source DU** transmits the data packets and prepares to hand over control of the UE to the **target DU**.
 - At the **Physical Layer**, the **target DU** takes over radio resource management and synchronizes the data stream.
- **Layer 2 (Data Link Layer):** The **RLC (Radio Link Control)** in the target **DU** manages data continuity, ensuring that packets are not lost during the handover.
 - The **MAC** layer in the source **DU** begins sending buffered data to the **target DU**, which will continue transmitting to the **UE**.

Step 4: Handover Completion (Control & User Plane - Layer 3 and 2)

- **Layer 3 (Network Layer):** Once the **handover** is successfully completed, the **AMF** and **SMF** confirm the new bearer path in the target gNB.
 - The **AMF** updates the **UE's** context in the new cell, and the session management continues in the new cell without disruption.
- **Layer 2 (Data Link Layer):** The **MAC and RLC** layers in the target **DU** handle further data transmission. All data sent to the **UE** is now routed through the **target DU**.

Summary: How OSI Layers Interact During Operations:

Operation	Layer 1 (Physical)	Layer 2 (Data Link)	Layer 3 (Network)	Layer 7 (Application)
Data Transfer	PHY layer modulates data and sends/receives over radio	MAC/RLC schedules, transmits, handles retransmissions	Session management by CU, data forwarding via UPF	Application requests (e.g., HTTP GET/POST)

Handover	PHY resources transferred to target DU	MAC/RLC ensures data buffer management and transfer	AMF/SMF handle bearer reconfiguration, target CU updates context	No impact on application layer
-----------------	---	--	---	--------------------------------

Conclusion:

- **Data transfer** focuses on routing, resource scheduling, and error correction through **DU** and **CU**.
- **Handover** ensures that a **UE**'s session continues seamlessly by transitioning from one **DU** (source) to another (target), with the **CU** managing session continuity and mobility.

The **5G Core (5GC)**, which is responsible for the overall control, management, and orchestration of the 5G network, is typically distributed across **multiple geographic locations** based on the network architecture, the need for low latency, and network redundancy. The geographic location of 5G Core components can vary depending on network design and operator requirements. Here's a breakdown of where the 5G Core might be located:

1. Centralized Locations (Data Centers)

- **Regional or National Data Centers:** The **5G Core** is often deployed in centralized **data centers** within a country or a region. These data centers can host the core functions of the 5G network, including **control plane** and **user plane** components (AMF, SMF, UPF, etc.).
 - **Example:** Large cloud providers like **Amazon Web Services (AWS)**, **Microsoft Azure**, or **Google Cloud Platform (GCP)** are used by telecom operators to host parts of the 5G Core.
 - These data centers provide a highly scalable and reliable environment for hosting core network elements.
- **Operators' Own Data Centers:** In some cases, telecom operators may also deploy their **own private data centers** to host the 5GC. These data centers are typically located in **centralized hubs** within specific geographic regions (e.g., cities or country capitals).

Key Benefits:

- **Scalability:** Centralized locations offer better scalability and are easier to manage for high-volume traffic.
 - **Security:** Centralized data centers provide strong security and network management capabilities.
-

2. Distributed Locations (Edge Data Centers)

With the increasing need for **low latency**, **edge computing** is becoming a more important part of the 5G Core architecture. The 5G Core can be deployed at the **edge** of the network, closer to users, to reduce **round-trip times** for critical services (e.g., autonomous vehicles, remote healthcare, gaming, and AR/VR applications).

- **Edge Data Centers:** These are smaller, local data centers that are deployed closer to the **radio access network (RAN)**, typically in **cities** or **local geographic areas**. The 5G Core can have **distributed functions** that run in these edge locations to reduce the latency for real-time services.
 - These are often deployed as part of the **multi-access edge computing (MEC)** architecture.

Key Benefits:

- **Low Latency:** Edge locations enable faster data processing, reducing latency, which is crucial for time-sensitive applications.
 - **Local Breakout:** Allows for more localized data handling, improving performance for services that require real-time responses.
-

3. Cloud and Virtualized Locations

The **5G Core Network** can also be implemented in **cloud-native environments**, which means that its components are virtualized and distributed across multiple cloud platforms or regions.

- **Cloud Provider Locations:** Telecom operators are increasingly leveraging cloud providers' **global infrastructure** for hosting their 5G Core functions.

These can be located in various regions or even in specific countries depending on data sovereignty and compliance requirements.

- **Global Cloud Regions:** Cloud providers such as AWS, Azure, and Google Cloud have **regions and availability zones** in different parts of the world (North America, Europe, Asia Pacific, etc.), allowing the 5G Core to be geographically distributed.
- **Network Slicing & Virtualization:** The **virtualization** of network functions in the 5G Core allows network operators to use **multiple cloud regions** for specific use cases or customer segments, making it possible to have a distributed 5G Core network that provides flexibility and resilience.

Key Benefits:

- **Elasticity:** Cloud platforms can provide elastic resources that scale according to demand.
 - **Global Reach:** Using multiple cloud regions, the 5G Core can ensure high availability and resilience across wide geographic areas.
-

4. Geographic Redundancy and Reliability

- **Redundancy and Backup:** To ensure continuous availability, operators often deploy **redundant** 5G Core components in different geographic locations. If one data center or region fails, the core network can quickly failover to another region without disrupting services.
 - **Distributed Control and User Plane:** In some cases, the **control plane** (CU) and **user plane** (DU) functions of the 5G Core can be distributed across different locations for **optimized routing** and **reliability**.
-

Summary of Geographic Locations:

- **Centralized Data Centers** (Regional or National Hubs): Host the primary 5G Core functions in large data centers located in major cities or operator hubs.
- **Edge Data Centers** (Local Hubs or MEC Locations): Deploy 5G Core functions closer to the user to reduce latency for critical services.

- **Cloud Locations:** Hosted in public or private cloud infrastructure with **distributed cloud regions**, enabling scalability and flexibility.
 - **Redundant Locations:** To ensure resilience, 5G Core components are often spread across **multiple geographic regions** for fault tolerance.
-

Example: Geographic Distribution of 5G Core

If a telecom operator like **Verizon** or **Vodafone** is deploying 5G services, they may have a **primary 5G Core** in a **national data center** in **London**, with **edge data centers** located in **Manchester**, **Birmingham**, and other cities to handle **low-latency** applications. Additionally, the **5G Core functions** could be hosted in **AWS cloud regions** in Europe and North America, with **redundant sites** in **Frankfurt**, **Dublin**, and **Chicago** for failover and service continuity.

Nw coding and basics of network coding