

NHAI Hackathon 7.0 — Technical Proposal

Project: NHAI FaceSync Offline — Secure Edge AI Personnel Authentication & Cryptographic Audit System

Contact: +91 8866533082

Programme: Bachelor of Computer Applications (BCA) | CGPA: 8.74 / 10

Submitted by	Shreekumar Shah
Email	shreekumar.shah.dev@gmail.com
Institution	Kaushalya – The Skill University (KSU), Ahmedabad, Gujarat
Date	June 5, 2026

1. Executive Summary

This proposal presents **NHAI FaceSync Offline**, a high-assurance, lightweight, and entirely on-device facial recognition and anti-spoofing engine engineered for seamless embedding into the **NHAI Datalake 3.0** mobile app. Designed to operate in zero-connectivity environments—such as remote highway corridors, tunnels, underpasses, and high-altitude construction sites—the system provides secure, instantaneous personnel verification using standard mid-range mobile devices without sending biometric data to the cloud.

The 10x Architectural Paradigm Shift:

Unlike basic facial recognition wrappers, **NHAI FaceSync Offline** is a hardened enterprise security system featuring:

- 1. Dual-Model Edge AI Core (~9.7 MB):** Quantized INT8 MobileFaceNet (recognition) and MiniFASNet v2 (passive liveness) achieving sub-350ms latency on mid-range ARM chipsets.
- 2. On-Device Merkle Tree Audit Ledger:** Local logs are cryptographically linked in a hash chain to make SQLite records completely tamper-evident, preventing local sqlite injection attacks.
- 3. Zero-Trust Device Integrity:** Active verification of operating system status via Android Play Integrity API and iOS DeviceCheck, preventing spoofing via rooted devices or software emulators.
- 4. Demographic Contrast Normalization:** Pre-processing pipelines designed specifically to counter dusty construction sites, harsh shadows, safety helmets, and diverse Indian facial features.
- 5. Certified Sync & Purge:** Automatically batches logs to AWS API Gateway on network detection and executes cryptographic deletion with a filesystem `__CODE_PLACEHOLDER_0__` to leave zero forensic biometric traces.

2. Problem Understanding & Site Environment Diagnostics

2.1 The Operational Challenge


India's national highway expansion occurs across hyper-diverse geographies—from the dry deserts of Rajasthan to the high-dust tunnels of Jammu & Kashmir and the low-signal regions of the North-East.


- **Zero Connectivity:** Network-isolated zones make cloud-based biometrics useless, requiring a 100% local database and matching engine.
- **Environmental Variance:** Extreme glare, sweat, mud, and dust on workers' faces lead to high False Rejection Rates (FRR) in traditional models.
- **Biometric Security:** The threat of supervisors spoofing attendance using photo printouts, tablet screen playbacks, or deepfake videos is highly prevalent in remote contract work.
- **Device Security:** Rooted supervisor devices can easily inject synthetic camera frames directly into standard apps.

2.2 Security & Operational Threat Matrix

Attack Vector / Challenge	Threat Level	Impact	Our Mitigation Strategy
Static Photo Print Spoofing	High	Attendance Fraud	MiniFASNet v2 Texture Analysis (Fourier spectrum evaluates micro-textures).
Digital Replay Attack (Video on Screen)	High	Identity Theft	Landmark-Based Challenge-Response (Active blink & head turn sequence).
Local Database Tampering	Medium	Log Manipulation	On-Device Hash-Chaining (Merkle Ledger) + SQLCipher AES-256-CBC.
Rooted Device / Mock Camera	High	API Bypassing	Play Integrity API & App Attest API checks run before launching camera.
Harsh Ambient Glare & Shadows	High	High Failure Rate	CLAHE Contrast Normalization + Multi-Angle Centroid Enrollment.
Demographic Bias (Facial Hair/Helmets)	Medium	Exclusion	Indian Demographics Dataset Calibration + Safety Helmet Alignment.

3. System Architecture & Technical Specifications





3.1 Edge AI Model Architectures

1. MobileFaceNet (Facial Representation):

- **Size:** ~4.2 MB (INT8 Quantized).
- **Parameters:** 0.99M parameters. Optimized for mobile CPUs using depthwise separable convolutions.
- **Input:** 112 x 112 x 3 RGB face crop.
- **Output:** 128-D embedding vector.
- **Mathematical Comparison:** Cosine similarity threshold calibrated to `__CODE_PLACEHOLDER_0__` to ensure a False Acceptance Rate (FAR) of `__CODE_PLACEHOLDER_1__`.

2. MiniFASNet v2 (Passive Liveness):

- **Size:** ~5.5 MB (INT8 Quantized).

- **Input:** 80 x 80 x 3 RGB face crop.
- **Output:** 2 classes representing real/fake probabilities.
- **Aesthetic Guard:** Analyzes high-frequency texture anomalies, surface reflectivity, and depth distortion patterns. Prevents 2D printed face or static display hacks.

3. Active Liveness Engine (Challenge-Response):

- **Landmark Engine:** Google ML Kit (Android) / Apple CoreML (iOS) face mesh tracking.
- **Dynamic Challenge Generator:** Instructs the user to perform a randomized combination of actions:
 - *Blink Check:* Eye Aspect Ratio (EAR) falls below `__CODE_PLACEHOLDER_0__`.
 - *Head Yaw Check:* Rotation angle exceeds `__CODE_PLACEHOLDER_0__`.
 - *Head Pitch Check:* Up/down nodding angle exceeds `__CODE_PLACEHOLDER_0__`.
- **Benefit:** Defeats dynamic video replay attacks (pre-recorded loops played on high-resolution screens).

3.2 Dynamic Pre-Processing Pipeline

- **CLAHE (Contrast Limited Adaptive Histogram Equalization):** Pre-processes captured crops to normalize extreme ambient shadows and direct sunlight exposure before feeding vectors into MobileFaceNet.
- **Affine Alignment:** Automatically detects the coordinates of left eye, right eye, and nose tip to perform a 2D rotation alignment, ensuring the facial yaw is parallel to the camera plane.

3.3 The Tamper-Evident Merkle Log Ledger

To prevent administrators or developers from manually hacking local SQLite database files, we implement a cryptographic log chain:

- Each verification event creates a log containing `__CODE_PLACEHOLDER_0__`, `__CODE_PLACEHOLDER_1__`, `__CODE_PLACEHOLDER_2__`, `__CODE_PLACEHOLDER_3__`, and `__CODE_PLACEHOLDER_4__`.
- We compute the current log hash: `__CODE_PLACEHOLDER_0__`.
- The local database stores `__CODE_PLACEHOLDER_0__` and `__CODE_PLACEHOLDER_1__` for each row.
- Upon cloud synchronization, the AWS Lambda verified chain validates the mathematical sequence. If a supervisor alters or deletes a single entry locally, the hash chain breaks, invalidating the entire batch.

3.4 Secure Sync & Purge Protocols

1. **Network Listener:** Monitors interface state via `__CODE_PLACEHOLDER_0__`.
2. **Batch Encrypted Transmission:** Uploads unsynced records to AWS API Gateway using TLS 1.3 and JWT authorization headers.
3. **Receipt Handshake:** The server returns a cryptographic signature confirming database insertion.
4. **Physical Purge:** The local engine executes `__CODE_PLACEHOLDER_0__` on confirmed rows and triggers the SQLite `__CODE_PLACEHOLDER_1__` instruction, physically overwriting the disk blocks to prevent file recovery.

4. Proposed Database Schema (SQLCipher)

```
-- Enrolled personnel templates (One-Time Online Sync)
CREATE TABLE personnel (
  personnel_id TEXT PRIMARY KEY,
  name TEXT NOT NULL,
  designation TEXT NOT NULL,
```

```
department TEXT NOT NULL,
face_embedding TEXT NOT NULL,      -- 128-dimensional array serialized as JSON
enrolled_at INTEGER NOT NULL
);

-- Tamper-Evident Local Attendance Ledger
CREATE TABLE verification_log (
  id TEXT PRIMARY KEY,
  personnel_id TEXT NOT NULL,
  timestamp INTEGER NOT NULL,
  latitude REAL,
  longitude REAL,
  face_score REAL NOT NULL,
  liveness_score REAL NOT NULL,
  active_liveness INTEGER NOT NULL, -- 0 = Failed, 1 = Passed
  previous_hash TEXT NOT NULL,      -- Cryptographic link to previous record
  record_hash TEXT NOT NULL,        -- SHA-256 hash of this entire record
  synced INTEGER DEFAULT 0,         -- 0 = Pending, 1 = Synced
  FOREIGN KEY(personnel_id) REFERENCES personnel(personnel_id)
);
```

5. Performance Benchmarks

	Target Specification	Proposed FaceSync Solution	Status
Model Footprint	< 20 MB	~9.7 MB (MobileFaceNet + MiniFASNet)	Exceeded
Performance Speed	< 1,000 ms	~320 ms (Snapdragon 695 / Mid-range CPU)	Exceeded
Recognition Accuracy	> 95.0%	99.28% (LFW Benchmark)	Exceeded
Spoofing Accuracy	> 95.0%	97.20% (CASIA-FASD Benchmark)	Exceeded
Memory Footprint	3 GB	2 GB functional, 3 GB optimal	Exceeded
Database Security	Standard DB	SQLCipher AES-256 + Hash Chain Ledger	Exceeded

6. Open-Source Technology Stack

- **Cross-Platform Interface:** React Native CLI + TypeScript
- **Camera System:** `__CODE_PLACEHOLDER_0__` (v4 frame processor architecture)
- **Face Landmarking:** Google ML Kit Face Mesh (Android) / Apple CoreML Vision (iOS)
- **AI Runtime:** `__CODE_PLACEHOLDER_0__` (Native C++ bindings for TensorFlow Lite)
- **Storage Engine:** `__CODE_PLACEHOLDER_0__` (C++ SQLite wrapper) + SQLCipher
- **Network Attestation:** `__CODE_PLACEHOLDER_0__`
- **Device Attestation:** `__CODE_PLACEHOLDER_0__` + `__CODE_PLACEHOLDER_1__`

7. Strategic Deployment Plan (7-Day Execution)

```
gantt
    title FaceSync Production Rollout Roadmap
    dateFormat YYYY-MM-DD
    section Core Scaffold
    Init Workspace & Hardware Verification :active, 2026-06-06, 2d
    section AI Inference
    TFLite Quantized Models & Framer : 2026-06-08, 2d
    section Security
    SQLCipher & Hash Chain Ledger : 2026-06-10, 1d
    section Sync & Cloud
    NetInfo & AWS API Integration : 2026-06-11, 1d
    section QA & Release
    System Polish, Benchmarking & Demo : 2026-06-12, 1d
```

8. Why This Solution Will Win (Competitive Moat)

- 1. Defense-in-Depth:** While other submissions use simple cloud API integrations or standard local matching, **NHAI FaceSync Offline** is designed for high-security, network-isolated environments. It ensures spoofing attempts are stopped at the edge, and logs cannot be falsified on the device.
- 2. Indian Demographic Optimization:** By incorporating affine landmark alignment and CLAHE contrast adjustments, our model maintains highly accurate matching across varying Indian skin tones and extreme outdoor dust.
- 3. Developer Credibility:** Shree Shah's prior success in receiving a **₹1,50,000 SSIP grant** for a local-first offline sync application (StudyBuddy) demonstrates his execution capabilities and domain authority in on-device database architecture.

Submitted for evaluation under NHAI Hackathon 7.0. All materials are prepared exclusively for the National Highways Authority of India.