

SSHVisual: Visual Tool to Analyze SSH Data

Shreeman Gautam*, Robert Ricci*

*University of Utah

Abstract

Attackers attempt to log in to computer systems or servers all over the world in order to use them for nefarious purposes. We have collected the login attempts by these attackers on our servers over SSH. Previous works in network visualization have 1. analyzed the attackers' IP and AS dimension of the SSH logins, 2. used automated detection systems to find anomalous network events given baseline events and, 3. employed collaborative methods to help analysts share findings about network events with each other. With our visualization SSHVisual, we 1. analyze the IP and AS and give more attention to the username dimension of SSH attacker logins to draw a holistic picture of SSH attackers in service of SSH campaign detection, 2. utilize detection by analysts of anomalous events in absence of baseline events, 3. employ collaboration like previous works, 4. use a novel similarity metric to find out attacker persistence over time and 5. correlate SSH attacks with real-world events. We build all these features in SSHVisual by studying tasks and requirements of network administrators. Using case studies with network admins, we demonstrate that our approach helps them find important events from data.

I Introduction

Computer systems worldwide employ SSH [1] to allow their users to securely connect to them in order to execute commands and do remote administration. A lot of users do a username, password combination (password based authentication) in order to gain entry to the SSH server. Attackers, who are adversarial in nature, can use brute force attack mechanisms [2] to get into SSH servers. Sometimes, they guess what the username, password combinations are and other times, they take advantage of poorly secured servers to build botnets [2] to carry out further attacks [3, 4] or steal resources from the servers, like cryptomining [5, 6].

Knowing the prevalence of SSH attacks in the IPv4 space, we decided to collect SSH data with our servers with the purpose of understanding attacker behavior visually and holistically. To that end, we built a visual tool called SSHvisual in order to address the gaps that existing network visualizations have and use best practices that network visualizations already employ. Surveys of network visualizations [7, 8, 9, 10, 11] establish both the maturity of the network visualization field and the gaps we target.

Three visual contributions address the gaps we have found. First, actor-level analysis: we treat the attacker as a first-class

actor — including the username identity, not only the source IP or autonomous system (AS) — and we identify coordinated campaigns, since our data affords no stable baseline for automated detection. Second, we apply a novel similarity metric to these actors, particularly in the username dimension, as they evolve over time. Third, we corroborate actor behavior in the visualization with real world events, with a particular emphasis on the username dimension given the limitations of IP corroboration. Additionally, following established practices, we allow for analyst driven collaboration and labeling of irregularities found in the data.

II Related Work

A long line of tools [12, 13, 14, 15, 16, 17, 18, 19] render network traffic and security events navigable for operators and analysts with the majority being network flow and traffic oriented. Additionally, a smaller alert- and log-oriented group [20, 21, 22, 23, 24, 25, 26, 27, 28, 29] organizes IDS output and heterogeneous logs of which [22] contributes a visual analysis (of the CICIDS2017 dataset) that isolates attack clusters — including SSH brute-force (SSH-Patator) — through clustering and dimensionality reduction, namely a multi-resolution wavelet-feature analysis.

A Attack Campaigns (Emphasis on the Username Dimension) with Time

Honeypot literature does not promote the username identity as an actor in its own right (for attack campaign detection purposes): it remains an attribute to count, never a unit to track — the unit that, alongside the IP and AS, anchors our analysis. Some papers [30, 31, 32, 33, 34, 35, 36] collect and chart honeypot traffic, with several of them capturing SSH credentials (usernames and passwords). Where credentials are charted — the SCADA SSH honeypot [33], kippo-graph [34], and the container deployment [35] — usernames and passwords appear only as static top-N tallies (kippo-graph's top-10 username and password bars are the archetype), never placed on a time axis even where the same tool charts attack volume over time. The WAN honeypot framework [37] is the closest prior system on the credential axis: it computes an IP-to-IP dictionary-overlap (containment) score to probe whether six same-/24 source IPs share a wordlist — a manual, one-off prototype of credential-based coordination analysis, performed on the IP unit and without a temporal dimension.

B Attacker Similarity (Emphasis on the Username Dimension) with Time

Computed similarity between entities is well established in literature [38, 39, 40, 41]. We do not claim similarity computation itself as novel; the contribution lies in the entity it operates on and how it moves through time. On the entity: these systems cluster internal hosts [38], behavioral profiles [40], IP/port members [41], or internal enterprise users grouped by shared resources — not external attacker identities [39]. None treats the username as an attacker actor. On time: [40, 41] reach into the temporal dimension, but both do not compute the similarity of the attacker population across consecutive windows. We apply similarity based metrics — for example, Jaccard overlap of attackers between successive windows — particularly to the username actor unit, capturing how the attacker population persists or churns over time.

C Limits of automated detection

A central premise of our approach is that SSH traffic does not admit the “normal baseline” that automated anomaly and campaign detection presuppose. The broader literature documents why such detection is fragile: Sommer and Paxson [42] note that, despite extensive research, machine-learning anomaly detection is rarely deployed for intrusion detection, given the enormous variability of “normal,” the high cost of errors, and the difficulty of sound evaluation; Axelsson [43] shows that automated anomaly detection is throttled by the base-rate fallacy: where intrusions are rare relative to benign traffic, the false-positive rate becomes the limiting factor. Honeypot traffic departs from that setting entirely — it offers no stable “normal” against which to define an anomaly, with Gates and Taylor [44] supporting our approach by challenging the paradigm directly, questioning that anomalies and attacks are rare, that a stable normal exists and sometimes normal traffic may be malicious and malicious traffic may be normal, finally observing that detection ultimately devolves to an analyst manually investigating clusters of activity.

This fragility is visible from some of the papers referenced so far. The automated detectors there are built on a per-actor baseline: Situ [38] learns a probabilistic model of each IP’s behavior and flags low-probability events, and CLIQUE [45] scores each actor’s deviation from a calculated baseline of its own expected activity. Both presume the stable per-actor “normal” that honeypot traffic — near-uniformly hostile and constantly churning — cannot supply, so they do not transfer to this setting by construction. And even where such a baseline does hold, Situ itself concedes that automation is not enough: having reviewed the limits of signature-, supervised-, and reputation-based detection, it argues that operators “do not want another automated tool with algorithms they do not trust,” and builds a human-in-the-loop visual analytics system instead. We reach the same conclusion from a starker starting point: lacking even the per-actor baseline these systems assume, we treat anomaly and campaign detection as analyst-driven from the outset, providing visual support for it rather

than another automated detector.

D Actor identity and real-world event correlation

The attacks we observe do not arrive at a steady rate; they rise, fall, and change in character as events unfold in the wider world, so understanding them means lining them up against what is happening outside the network. The link is well documented: Bilge and Dumitras [46] found that the number of attacks against a given vulnerability can jump by up to five orders of magnitude — a hundred-thousand-fold increase — once it is publicly disclosed, and Sabottke et al. [47] showed that future exploitation can be predicted from signals in disclosure channels alone. Allodi and Massacci [48] add that a vulnerability’s official severity score is a poor guide to whether it is actually attacked, so the dependable way to learn what attackers are reacting to is to watch real activity and line it up against real events, not to read it off a score. We want to do this at the level of a campaign — a group of attackers acting together — rather than one attacker at a time, and that raises a practical problem: a campaign rarely shows up as a single source address. IP addresses do not stay tied to one machine — one host is assigned many addresses over time [49], hosts cycle through new addresses [50], and counting by address can overstate the number of real machines by orders of magnitude [51] — so it is likely that a view organized by address scatters one campaign across dozens of entries that look unrelated. The username pulls those pieces back together: the same login names likely recur across the changing addresses, so grouping by username re-assembles the campaign that an address-by-address view splits apart. A username is not a perfect identity either — names like “root” are tried by almost everyone, and one campaign runs through a whole list of names — so we treat it as one analysis dimension alongside the address and the network it belongs to (its AS), resolving the overlaps with the similarity and grouping methods above.

E Analyst labeling and collaboration (Emphasis on the Username Dimension)

Because detection on this data is analyst-driven, the findings an operator produces by hand must be captured and shared rather than discarded. In two, lines of work [52, 18], interactive labeling has been used to fold the analyst’s judgments back into the system. Collaborative analysis has been supported through shared artifacts with [16] and [19] being notable examples. These systems establish that labeling and collaboration are valuable, but each works on a different kind of data and a different unit: none lets an analyst group username-level campaign actors observed in SSH login traffic into a named, persistent artifact that other operators can see and build on. Our labeling-and-sharing mechanism is the step that turns a manually identified set of usernames into a durable, shared campaign.

Table 1: Example placeholder table

Requirement	Task 1	Task 2	Task 3	Task 4
Row A	+	-	+	+
Row B	tech	plan	-	+
Row C	+	+	+	-

III Typical Tasks and Visualization Requirements

Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Donec odio elit, dictum in, hendrerit sit amet, egestas sed, leo. Praesent feugiat sapien aliquet odio. Integer vitae justo. Aliquam vestibulum fringilla lorem. Sed neque lectus, consectetur at, consectetur sed, eleifend ac, lectus. Nulla facilisi. Pellentesque eget lectus. Proin eu metus. Sed porttitor. In hac habitasse platea dictumst. Suspendisse eu lectus. Ut mi mi, lacinia sit amet, placerat et, mollis vitae, dui. Sed ante tellus, tristique ut, iaculis eu, malesuada ac, dui. Mauris nibh leo, facilisis non, adipiscing quis, ultrices a, dui.

A Data and Domain Characterization

Morbi luctus, wisi viverra faucibus pretium, nibh est placerat odio, nec commodo wisi enim eget quam. Quisque libero justo, consectetur a, feugiat vitae, porttitor eu, libero. Suspendisse sed mauris vitae elit sollicitudin malesuada. Maecenas ultricies eros sit amet ante. Ut venenatis velit. Maecenas sed mi eget dui varius euismod. Phasellus aliquet volutpat odio. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Pellentesque sit amet pede ac sem eleifend consectetur. Nullam elementum, urna vel imperdiet sodales, elit ipsum pharetra ligula, ac pretium ante justo a nulla. Curabitur tristique arcu eu metus. Vestibulum lectus. Proin mauris. Proin eu nunc eu urna hendrerit faucibus. Aliquam auctor, pede consequat laoreet varius, eros tellus scelerisque quam, pellentesque hendrerit ipsum dolor sed augue. Nulla nec lacus.

B Task Abstraction

Suspendisse vitae elit. Aliquam arcu neque, ornare in, ullamcorper quis, commodo eu, libero. Fusce sagittis erat at erat tristique mollis. Maecenas sapien libero, molestie et, lobortis in, sodales eget, dui. Morbi ultrices rutrum lorem. Nam elementum ullamcorper leo. Morbi dui. Aliquam sagittis. Nunc placerat. Pellentesque tristique sodales est. Maecenas imperdiet lacinia velit. Cras non urna. Morbi eros pede, suscipit ac, varius vel, egestas non, eros. Praesent malesuada, diam id pretium elementum, eros sem dictum tortor, vel consectetur odio sem sed wisi.

Sed feugiat. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Ut pellentesque augue sed urna. Vestibulum diam eros, fringilla et, consectetur




Figure 1: Show campaign detection using username+IP+AS

eu, nonummy id, sapien. Nullam at lectus. In sagittis ultrices mauris. Curabitur malesuada erat sit amet massa. Fusce blandit. Aliquam erat volutpat. Aliquam euismod. Aenean vel lectus. Nunc imperdiet justo nec dolor.

IV Approach

Etiam euismod. Fusce facilisis lacinia dui. Suspendisse potenti. In mi erat, cursus id, nonummy sed, ullamcorper eget, sapien. Praesent pretium, magna in eleifend egestas, pede pede pretium lorem, quis consectetur tortor sapien facilisis magna. Mauris quis magna varius nulla scelerisque imperdiet. Aliquam non quam. Aliquam porttitor quam a lacus. Praesent vel arcu ut tortor cursus volutpat. In vitae pede quis diam bibendum placerat. Fusce elementum convallis neque. Sed dolor orci, scelerisque ac, dapibus nec, ultricies ut, mi. Duis nec dui quis leo sagittis commodo. Our clustering of daily time series builds on the calendar-based approach of [?], while the multi-dimensional filtering view is inspired by parallel sets [?] and parallel coordinates [?].

A First Component

Aliquam lectus. Vivamus leo. Quisque ornare tellus ullamcorper nulla. Mauris porttitor pharetra tortor. Sed fringilla justo sed mauris. Mauris tellus. Sed non leo. Nullam elementum, magna in cursus sodales, augue est scelerisque sapien, venenatis congue nulla arcu et pede. Ut suscipit enim vel sapien. Donec congue. Maecenas urna mi, suscipit in, placerat ut, vestibulum ut, massa. Fusce ultrices nulla et nisl.

B Second Component

Etiam ac leo a risus tristique nonummy. Donec dignissim tincidunt nulla. Vestibulum rhoncus molestie odio. Sed lobortis, justo et pretium lobortis, mauris turpis condimentum augue, nec ultricies nibh arcu pretium enim. Nunc purus neque, placerat id, imperdiet sed, pellentesque nec, nisl. Vestibulum imperdiet neque non sem accumsan laoreet. In hac habitasse




Figure 2: Show collaboration + labeling




Figure 4: Show correlation of attacks with real events




Figure 3: Show similarity metric at play

platea dictumst. Etiam condimentum facilisis libero. Suspendisse in elit quis nisl aliquam dapibus. Pellentesque auctor sapien. Sed egestas sapien nec lectus. Pellentesque vel dui vel neque bibendum viverra. Aliquam porttitor nisl nec pede. Proin mattis libero vel turpis. Donec rutrum mauris et libero. Proin euismod porta felis. Nam lobortis, metus quis elementum commodo, nunc lectus elementum mauris, eget vulputate ligula tellus eu neque. Vivamus eu dolor.

C Third Component

Nulla in ipsum. Praesent eros nulla, congue vitae, euismod ut, commodo a, wisi. Pellentesque habitant morbi tristique senectus et netus et malesuada fames ac turpis egestas. Aenean nonummy magna non leo. Sed felis erat, ullamcorper in, dictum non, ultricies ut, lectus. Proin vel arcu a odio lobortis euismod. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Proin ut est. Aliquam odio. Pellentesque massa turpis, cursus eu, euismod nec, tempor congue, nulla. Duis viverra gravida mauris. Cras tincidunt. Curabitur eros ligula, varius ut, pulvinar in, cursus faucibus, augue.

V Implementation

Nulla mattis luctus nulla. Duis commodo velit at leo. Aliquam vulputate magna et leo. Nam vestibulum ullamcorper leo. Vestibulum condimentum rutrum mauris. Donec id mauris. Morbi molestie justo et pede. Vivamus eget turpis sed nisl

cursus tempor. Curabitur mollis sapien condimentum nunc. In wisi nisl, malesuada at, dignissim sit amet, lobortis in, odio. Aenean consequat arcu a ante. Pellentesque porta elit sit amet orci. Etiam at turpis nec elit ultricies imperdiet. Nulla facilisi. In hac habitasse platea dictumst. Suspendisse viverra aliquam risus. Nullam pede justo, molestie nonummy, scelerisque eu, facilisis vel, arcu.

A System Architecture

Curabitur tellus magna, porttitor a, commodo a, commodo in, tortor. Donec interdum. Praesent scelerisque. Maecenas posuere sodales odio. Vivamus metus lacus, varius quis, imperdiet quis, rhoncus a, turpis. Etiam ligula arcu, elementum a, venenatis quis, sollicitudin sed, metus. Donec nunc pede, tincidunt in, venenatis vitae, faucibus vel, nibh. Pellentesque wisi. Nullam malesuada. Morbi ut tellus ut pede tincidunt porta. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam congue neque id dolor.

B Data Pipeline

Donec et nisl at wisi luctus bibendum. Nam interdum tellus ac libero. Sed sem justo, laoreet vitae, fringilla at, adipiscing ut, nibh. Maecenas non sem quis tortor eleifend fermentum. Etiam id tortor ac mauris porta vulputate. Integer porta neque vitae massa. Maecenas tempus libero a libero posuere dictum. Vestibulum ante ipsum primis in faucibus orci luctus et ultrices posuere cubilia Curae; Aenean quis mauris sed elit commodo placerat. Class aptent taciti sociosqu ad litora torquent per conubia nostra, per inceptos hymenaeos. Vivamus rhoncus tincidunt libero. Etiam elementum pretium justo. Vivamus est. Morbi a tellus eget pede tristique commodo. Nulla nisl. Vestibulum sed nisl eu sapien cursus rutrum.

Nulla non mauris vitae wisi posuere convallis. Sed eu nulla nec eros scelerisque pharetra. Nullam varius. Etiam dignissim elementum metus. Vestibulum faucibus, metus sit amet mattis rhoncus, sapien dui laoreet odio, nec ultricies nibh augue a enim. Fusce in ligula. Quisque at magna et nulla commodo consequat. Proin accumsan imperdiet sem. Nunc porta. Donec feugiat mi at justo. Phasellus facilisis ipsum quis ante. In ac elit eget ipsum pharetra faucibus. Maecenas viverra nulla in massa.

VI Evaluation and Discussion

Nulla ac nisl. Nullam urna nulla, ullamcorper in, interdum sit amet, gravida ut, risus. Aenean ac enim. In luctus. Phasellus eu quam vitae turpis viverra pellentesque. Duis feugiat felis ut enim. Phasellus pharetra, sem id porttitor sodales, magna nunc aliquet nibh, nec blandit nisl mauris at pede. Suspendisse risus risus, lobortis eget, semper at, imperdiet sit amet, quam. Quisque scelerisque dapibus nibh. Nam enim. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Nunc ut metus. Ut metus justo, auctor at, ultrices eu, sagittis ut, purus. Aliquam aliquam.

Etiam pede massa, dapibus vitae, rhoncus in, placerat posuere, odio. Vestibulum luctus commodo lacus. Morbi lacus dui, tempor sed, euismod eget, condimentum at, tortor. Phasellus aliquet odio ac lacus tempor faucibus. Praesent sed sem. Praesent iaculis. Cras rhoncus tellus sed justo ullamcorper sagittis. Donec quis orci. Sed ut tortor quis tellus euismod tincidunt. Suspendisse congue nisl eu elit. Aliquam tortor diam, tempus id, tristique eget, sodales vel, nulla. Praesent tellus mi, condimentum sed, viverra at, consectetur quis, lectus. In auctor vehicula orci. Sed pede sapien, euismod in, suscipit in, pharetra placerat, metus. Vivamus commodo dui non odio. Donec et felis.

A Case Studies

Etiam suscipit aliquam arcu. Aliquam sit amet est ac purus bibendum congue. Sed in eros. Morbi non orci. Pellentesque mattis lacinia elit. Fusce molestie velit in ligula. Nullam et orci vitae nibh vulputate auctor. Aliquam eget purus. Nulla auctor wisi sed ipsum. Morbi porttitor tellus ac enim. Fusce ornare. Proin ipsum enim, tincidunt in, ornare venenatis, molestie a, augue. Donec vel pede in lacus sagittis porta. Sed hendrerit ipsum quis nisl. Suspendisse quis massa ac nibh pretium cursus. Sed sodales. Nam eu neque quis pede dignissim ornare. Maecenas eu purus ac urna tincidunt congue.

B Discussion

Donec et nisl id sapien blandit mattis. Aenean dictum odio sit amet risus. Morbi purus. Nulla a est sit amet purus venenatis iaculis. Vivamus viverra purus vel magna. Donec in justo sed odio malesuada dapibus. Nunc ultrices aliquam nunc. Vivamus facilisis pellentesque velit. Nulla nunc velit, vulputate dapibus, vulputate id, mattis ac, justo. Nam mattis elit dapibus purus. Quisque enim risus, congue non, elementum ut, mattis quis, sem. Quisque elit.

VII Summary

Maecenas non massa. Vestibulum pharetra nulla at lorem. Duis quis quam id lacus dapibus interdum. Nulla lorem. Donec ut ante quis dolor bibendum condimentum. Etiam egestas tortor vitae lacus. Praesent cursus. Mauris bibendum pede at elit. Morbi et felis a lectus interdum facilisis. Sed suscipit gravida turpis. Nulla at lectus. Vestibulum ante ipsum primis

in faucibus orci luctus et ultrices posuere cubilia Curae; Praesent nonummy luctus nibh. Proin turpis nunc, congue eu, egestas ut, fringilla at, tellus. In hac habitasse platea dictumst.

A Limitations

Vivamus eu tellus sed tellus consequat suscipit. Nam orci orci, malesuada id, gravida nec, ultricies vitae, erat. Donec risus turpis, luctus sit amet, interdum quis, porta sed, ipsum. Suspendisse condimentum, tortor at egestas posuere, neque metus tempor orci, et tincidunt urna nunc a purus. Sed facilisis blandit tellus. Nunc risus sem, suscipit nec, eleifend quis, cursus quis, libero. Curabitur et dolor. Sed vitae sem. Cum sociis natoque penatibus et magnis dis parturient montes, nascetur ridiculus mus. Maecenas ante. Duis ullamcorper enim. Donec tristique enim eu leo. Nullam molestie elit eu dolor. Nullam bibendum, turpis vitae tristique gravida, quam sapien tempor lectus, quis pretium tellus purus ac quam. Nulla facilisi.

B Future Work

Duis aliquet dui in est. Donec eget est. Nunc lectus odio, varius at, fermentum in, accumsan non, enim. Aliquam erat volutpat. Proin sit amet nulla ut eros consectetur cursus. Phasellus dapibus aliquam justo. Nunc laoreet. Donec consequat placerat magna. Duis pretium tincidunt justo. Sed sollicitudin vestibulum quam. Nam quis ligula. Vivamus at metus. Etiam imperdiet imperdiet pede. Aenean turpis. Fusce augue velit, scelerisque sollicitudin, dictum vitae, tempor et, pede. Donec wisi sapien, feugiat in, fermentum ut, sollicitudin adipiscing, metus.

Acknowledgments

Curabitur tellus magna, porttitor a, commodo a, commodo in, tortor. Donec interdum. Praesent scelerisque. Maecenas posuere sodales odio. Vivamus metus lacus, varius quis, imperdiet quis, rhoncus a, turpis. Etiam ligula arcu, elementum a, venenatis quis, sollicitudin sed, metus. Donec nunc pede, tincidunt in, venenatis vitae, faucibus vel, nibh. Pellentesque wisi. Nullam malesuada. Morbi ut tellus ut pede tincidunt porta. Lorem ipsum dolor sit amet, consectetur adipiscing elit. Etiam congue neque id dolor.

References

- [1] T. Ylonen, “Ssh—secure login connections over the internet,” in *Proceedings of the 6th USENIX Security Symposium*, vol. 37, pp. 40–52, 1996.
- [2] S. K. Singh, S. Gautam, C. Cartier, S. Patil, and R. Ricci, “Where the wild things are: Brute-Force SSH attacks in the wild and how to stop them,” in *21st USENIX Symposium on Networked Systems Design and Implementation (NSDI 24)*, (Santa Clara, CA), pp. 1731–1750, USENIX Association, Apr. 2024.

- [3] M. Antonakakis, T. April, M. Bailey, M. Bernhard, E. Bursztein, J. Cochran, Z. Durumeric, J. A. Halderman, L. Invernizzi, M. Kallitsis, *et al.*, “Understanding the mirai botnet,” in *26th USENIX security symposium (USENIX Security 17)*, pp. 1093–1110, 2017.
- [4] C. Kolias, G. Kambourakis, A. Stavrou, and J. Voas, “Ddos in the iot: Mirai and other botnets,” *computer*, vol. 50, no. 7, pp. 80–84, 2017.
- [5] F. Dang, Z. Li, Y. Liu, E. Zhai, Q. A. Chen, T. Xu, Y. Chen, and J. Yang, “Understanding fileless attacks on linux-based iot devices with honeycloud,” in *Proceedings of the 17th Annual International Conference on Mobile Systems, Applications, and Services*, pp. 482–493, 2019.
- [6] S. Pastrana and G. Suarez-Tangil, “A first look at the crypto-mining malware ecosystem: A decade of unrestricted wealth,” in *Proceedings of the Internet Measurement Conference*, pp. 73–86, 2019.
- [7] V. T. Guimarães, C. M. D. S. Freitas, R. Sadre, L. M. R. Tarouco, and L. Z. Granville, “A survey on information visualization for network and service management,” *IEEE Communications Surveys & Tutorials*, vol. 18, no. 1, pp. 285–323, 2016.
- [8] H. Shiravi, A. Shiravi, and A. A. Ghorbani, “A survey of visualization systems for network security,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 18, no. 8, pp. 1313–1329, 2012.
- [9] T. Zhang, X. Wang, Z. Li, F. Guo, Y. Ma, and W. Chen, “A survey of network anomaly visualization,” *Science China Information Sciences*, vol. 60, no. 12, p. 121101, 2017.
- [10] J. Raynor, T. Crnovrsanin, S. Di Bartolomeo, L. South, D. Saffo, and C. Dunne, “The state of the art in bgp visualization tools: A mapping of visualization techniques to cyberattack types,” *IEEE Transactions on Visualization and Computer Graphics*, vol. 29, no. 1, pp. 1059–1069, 2022.
- [11] C. Wu, S. Sheng, and X. Dong, “Research on visualization systems for ddos attack detection,” in *2018 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, pp. 2986–2991, IEEE, 2018.
- [12] F. Mansmann and S. Mansmann, “Interactive exploration of data traffic with hierarchical network maps,” 2006.
- [13] J. Oberheide, M. Goff, and M. Karir, “Flamingo: Visualizing internet traffic,” in *2006 IEEE/IFIP Network Operations and Management Symposium NOMS 2006*, pp. 150–161, IEEE, 2006.
- [14] F. Mansmann, F. Fischer, D. A. Keim, and S. C. North, “Visual support for analyzing network traffic and intrusion detection events using treemap and graph representations,” in *Proceedings of the Symposium on Computer Human Interaction for the Management of Information Technology*, pp. 19–28, 2009.
- [15] T. Taylor, D. Paterson, J. Glanfield, C. Gates, S. Brooks, and J. McHugh, “Flovis: Flow visualization system,” in *2009 Cybersecurity Applications & Technology Conference for Homeland Security*, pp. 186–198, IEEE, 2009.
- [16] S. Chen, C. Guo, X. Yuan, F. Merkle, H. Schaefer, and T. Ertl, “Oceans: Online collaborative explorative analysis on network security,” in *Proceedings of the Eleventh Workshop on Visualization for Cyber Security*, pp. 1–8, 2014.
- [17] T. Tremel, J. Kogel, F. Jauernig, S. Meier, D. Thom, F. Becker, C. Muller, and S. Koch, “Vitalflow: Visual interactive traffic analysis with netflow,” in *NOMS 2022-2022 IEEE/IFIP Network Operations and Management Symposium*, pp. 1–6, IEEE, 2022.
- [18] L. Xiao, J. Gerth, and P. Hanrahan, “Enhancing visual analysis of network traffic using a knowledge representation,” in *2006 IEEE symposium on visual analytics science and technology*, pp. 107–114, IEEE, 2006.
- [19] J. R. Goodall and M. Sowul, “Viassist: Visual analytics for cyber defense,” in *2009 IEEE conference on technologies for homeland security*, pp. 143–150, IEEE, 2009.
- [20] Y. Livnat, J. Agutter, S. Moon, and S. Foresti, “Visual correlation for situational awareness,” in *IEEE Symposium on Information Visualization, 2005. INFOVIS 2005.*, pp. 95–102, IEEE, 2005.
- [21] A. King, B. Huffaker, A. Dainotti, and K. Claffy, “A coordinated view of the temporal evolution of large-scale internet events,” *Computing*, vol. 96, no. 1, pp. 53–65, 2014.
- [22] D. H. Jeong, B.-K. Jeong, and S.-Y. Ji, “Multi-resolution analysis with visualization to determine network attack patterns,” *Applied Sciences*, vol. 13, no. 6, p. 3792, 2023.
- [23] D. H. Jeong, J.-H. Cho, F. Chen, L. Kaplan, A. Jøsang, and S.-Y. Ji, “Interactive web-based visual analysis on network traffic data,” *Information*, vol. 14, no. 1, p. 16, 2022.
- [24] D. Ceneda, M. Di Bartolomeo, V. Di Donato, M. Patrignani, M. Pizzonia, and M. Rimondini, “Routingwatch: Visual exploration and analysis of routing events,” in *NOMS 2016-2016 IEEE/IFIP Network Operations and Management Symposium*, pp. 591–597, IEEE, 2016.
- [25] J. C. Roberts, “State of the art: Coordinated & multiple views in exploratory visualization,” in *Fifth international conference on coordinated and multiple views in exploratory visualization (CMV 2007)*, pp. 61–71, IEEE, 2007.

- [26] J. S. Yi, Y.-a. Kang, J. T. Stasko, and J. A. Jacko, "Understanding and characterizing insights: how do people gain insights using information visualization?," in *Proceedings of the 2008 Workshop on BEyond time and errors: novel evaluation methods for Information Visualization*, pp. 1–6, 2008.
- [27] H. Choi, H. Lee, and H. Kim, "Fast detection and visualization of network attacks on parallel coordinates," *computers & security*, vol. 28, no. 5, pp. 276–288, 2009.
- [28] C. Humphries, N. Prigent, C. Bidan, and F. Majorczyk, "Elvis: Extensible log visualization," in *Proceedings of the Tenth Workshop on Visualization for Cyber Security*, pp. 9–16, 2013.
- [29] T. Yu, R. Lippmann, J. Riordan, and S. Boyer, "Ember: a global perspective on extreme malicious behavior," in *Proceedings of the seventh international symposium on visualization for cyber security*, pp. 1–12, 2010.
- [30] R. Djap, C. Lim, K. E. Silaen, and A. Yusuf, "Xb-pot: Revealing honeypot-based attacker's behaviors," in *2021 9th International Conference on Information and Communication Technology (ICoICT)*, pp. 550–555, IEEE, 2021.
- [31] V. Visoottiviseth, U. Jaralrunroj, E. Phoomrungraungsuk, and P. Kultanon, "Distributed honeypot log management and visualization of attacker geographical distribution," in *2011 Eighth International Joint Conference on Computer Science and Software Engineering (JCSSE)*, pp. 23–28, IEEE, 2011.
- [32] M. Baykara and R. Das, "A novel honeypot based security approach for real-time intrusion detection and prevention systems," *Journal of Information Security and Applications*, vol. 41, pp. 103–116, 2018.
- [33] A. Belqruch and A. Maach, "Scada security using ssh honeypot," in *Proceedings of the 2nd International Conference on Networking, Information Systems & Security*, pp. 1–5, 2019.
- [34] I. Koniaris, G. Papadimitriou, and P. Nicosopolitidis, "Analysis and visualization of ssh attacks using honeypots," in *Eurocon 2013*, pp. 65–72, IEEE, 2013.
- [35] A. Kyriakou and N. Sklavos, "Container-based honeypot deployment for the analysis of malicious activity," in *2018 Global Information Infrastructure and Networking Symposium (GIIS)*, pp. 1–4, IEEE, 2018.
- [36] I. Koniaris, G. Papadimitriou, P. Nicosopolitidis, and M. Obaidat, "Honeypots deployment for the analysis and visualization of malware activity and malicious connections," in *2014 IEEE international conference on communications (ICC)*, pp. 1819–1824, IEEE, 2014.
- [37] D. Fraunholz, M. Zimmermann, S. D. Anton, J. Schneider, and H. D. Schotten, "Distributed and highly-scalable wan network attack sensing and sophisticated analysing framework based on honeypot technology," in *2017 7th International Conference on Cloud Computing, Data Science & Engineering-Confluence*, pp. 416–421, IEEE, 2017.
- [38] J. R. Goodall, E. D. Ragan, C. A. Steed, J. W. Reed, G. D. Richardson, K. M. Huffer, R. A. Bridges, and J. A. Laska, "Situ: Identifying and explaining suspicious behavior in networks," *IEEE transactions on visualization and computer graphics*, vol. 25, no. 1, pp. 204–214, 2018.
- [39] Q. Liao and A. Striegel, "Intelligent network management using graph differential anomaly visualization," in *2012 IEEE Network Operations and Management Symposium*, pp. 1008–1014, IEEE, 2012.
- [40] W. A. Pike, C. Scherrer, and S. Zabriskie, "Putting security in context: Visual correlation of network activity with real-world information," in *VizSEC 2007: Proceedings of the Workshop on Visualization for Computer Security*, pp. 203–220, Springer, 2008.
- [41] L. Hao, C. G. Healey, and S. E. Hutchinson, "Ensemble visualization for cyber situation awareness of network security data," in *2015 IEEE Symposium on Visualization for Cyber Security (VizSec)*, pp. 1–8, IEEE, 2015.
- [42] R. Sommer and V. Paxson, "Outside the closed world: On using machine learning for network intrusion detection," in *2010 IEEE symposium on security and privacy*, pp. 305–316, IEEE, 2010.
- [43] S. Axelsson, "The base-rate fallacy and the difficulty of intrusion detection," *ACM Transactions on Information and System Security (TISSEC)*, vol. 3, no. 3, pp. 186–205, 2000.
- [44] C. Gates and C. Taylor, "Challenging the anomaly detection paradigm: A provocative discussion," in *Proceedings of the 2006 workshop on New security paradigms*, pp. 21–29, 2006.
- [45] D. M. Best, R. P. Hafen, B. K. Olsen, and W. A. Pike, "Atypical behavior identification in large-scale network traffic," in *2011 IEEE Symposium on Large Data Analysis and Visualization*, pp. 15–22, IEEE, 2011.
- [46] L. Bilge and T. Dumitraş, "Before we knew it: an empirical study of zero-day attacks in the real world," in *Proceedings of the 2012 ACM conference on Computer and communications security*, pp. 833–844, 2012.
- [47] C. Sabottke, O. Suciu, and T. Dumitraş, "Vulnerability disclosure in the age of social media: Exploiting twitter for predicting real-world exploits," in *24th USENIX security symposium (USENIX security 15)*, pp. 1041–1056, 2015.

- [48] L. Allodi and F. Massacci, “A preliminary analysis of vulnerability scores for attacks in wild: The ekits and sym datasets,” in *Proceedings of the 2012 ACM Workshop on Building analysis datasets and gathering experience returns for security*, pp. 17–24, 2012.
- [49] Y. Xie, F. Yu, K. Achan, E. Gillum, M. Goldszmidt, and T. Wobber, “How dynamic are ip addresses?,” in *Proceedings of the 2007 conference on Applications, technologies, architectures, and protocols for computer communications*, pp. 301–312, 2007.
- [50] B. Stone-Gross, M. Cova, L. Cavallaro, B. Gilbert, M. Szydlowski, R. Kemmerer, C. Kruegel, and G. Vigna, “Your botnet is my botnet: analysis of a botnet takeover,” in *Proceedings of the 16th ACM conference on Computer and communications security*, pp. 635–647, 2009.
- [51] G. C. Moura, C. Ganán, Q. Lone, P. Poursaied, H. Asghari, and M. van Eeten, “How dynamic is the isps address space? towards internet-wide dhcp churn estimation,” in *2015 IFIP Networking Conference (IFIP Networking)*, pp. 1–9, IEEE, 2015.
- [52] J. L. Guerra, E. Veas, and C. A. Catania, “A study on labeling network hostile behavior with intelligent interactive tools,” in *2019 IEEE Symposium on Visualization for Cyber Security (VizSec)*, pp. 1–10, IEEE, 2019.