

Agent_DA — Retro-Futuristic Frontend Redesign PRD

Version: 1.0
Prepared for: AI Coding Agent
Stack: Next.js 14 · TypeScript · Tailwind CSS 3 · Clerk · Supabase · Plotly

1. OBJECTIVE

Redesign the Agent_DA frontend from its current black-border retro-newspaper aesthetic into a **retro-futuristic terminal/CRT aesthetic** inspired by [smfs.ai](#). The application is a conversational data analysis tool that lets users upload CSVs/Excel files or connect to PostgreSQL and ask questions in plain English — getting back Python-executed results, narratives, and Plotly charts.

The new design must feel like a **1990s unix workstation terminal crossed with a modern development IDE**: deep dark backgrounds, phosphor-green and cyan accents, monospace typography, technical schematic layouts, subtle scan-line effects, and prompt-style interactivity cues.

No layout rewrites. Every existing page and component retains its routing, data-fetching, and functional logic. This PRD is a **pure styling and copy pass**.

2. CURRENT STATE SUMMARY

File	Current role
<code>tailwind.config.ts</code>	Defines <code>retro.*</code> and <code>cohere.*</code> color tokens, custom fonts, zero border-radius
<code>src/app/globals.css</code>	Sets white bg, black body text, 8px page frame border, scrollbar styles
<code>src/app/layout.tsx</code>	ClerkProvider with black/white appearance, wraps in <code>page-frame</code> div
<code>src/app/page.tsx</code>	Public landing page (Dell-ad retro style)
<code>src/app/dashboard/page.tsx</code>	Authenticated workspace dashboard
<code>src/app/data/upload/page.tsx</code>	File upload / PostgreSQL connector page
<code>src/app/session/[id]/page.tsx</code>	Chat analysis session page
<code>src/components/layout/PageShell.tsx</code>	TopNav + Sidebar wrapper
<code>src/components/layout/TopNav.tsx</code>	Header bar with logo and auth controls
<code>src/components/layout/Sidebar.tsx</code>	Collapsible session list sidebar

File	Current role
src/components/chat/MessageList.tsx	Renders user/assistant message bubbles
src/components/chat/MessageInput.tsx	Textarea + send button for queries
src/components/agent/ChartRenderer.tsx	Plotly chart wrapper
src/components/agent/ExecutionConsole.tsx	Collapsible code/stdout/stderr log
src/components/data/DataProfileCard.tsx	Schema/stats/anomalies tabs for a data source
src/components/data/FileUploader.tsx	Drag-and-drop file upload zone
src/components/data/SQLConnector.tsx	PostgreSQL connection form

3. DESIGN LANGUAGE

3.1 Aesthetic Concept

"Deep Scan" — the terminal of a machine that has been running analysis jobs since 1994 and has never been rebooted. Text glows faintly. Borders feel etched. Every section has a layer number. Prompts precede interactive elements. Code output looks like it came out of a real TTY.

3.2 Color Palette

Replace ALL existing `retro.*` and `cohere.*` tokens in `tailwind.config.ts` with the following:

```
// tailwind.config.ts → theme.extend.colors
colors: {
  // Background layers
  "bg-base": "#08080d", // deepest background (page root)
  "bg-surface": "#0f0f17", // card / panel surface
  "bg-raised": "#161620", // raised element (input, hover)
  "bg-overlay": "#1c1c28", // modal / tooltip overlay

  // Borders
  "border-dim": "#1e1e2a", // subtle structural border
  "border-normal": "#2a2a3a", // default visible border
  "border-bright": "#3a3a52", // highlighted/active border

  // Text
  "text-primary": "#e2e2f0", // main readable text
  "text-muted": "#5a5a78", // secondary / dimmed
  "text-faint": "#2e2e42", // barely-visible decorative
  "text-code": "#a8ffb2", // terminal green output

  // Accents
  "accent-cyan": "#00d9ff", // primary interactive accent (links,
active states)
  "accent-green": "#00ff88", // success / ready / running
```

```

"accent-red":    "#ff3366", // error / danger / delete
"accent-yellow": "#ffc832", // warning / pending
"accent-purple": "#9b60ff", // info / neutral highlight

// Legacy aliases (keep these so any missed class doesn't break)
"retro-red":     "#ff3366",
"retro-sage":    "#00ff88",
"retro-link":    "#00d9ff",
},

```

3.3 Typography

```

// tailwind.config.ts → theme.extend.fontFamily
fontFamily: {
  display: ["Space Grotesk", "Arial Black", 'Arial', 'sans-serif'],
  heading: ["JetBrains Mono", "Fira Code", "Courier New",
'monospace'],
  body:    ["JetBrains Mono", "Fira Code", "Courier New",
'monospace'],
  mono:    ["JetBrains Mono", "Fira Code", "Courier New",
'monospace'],
  sans:    ['Inter', 'Helvetica', 'Arial', 'sans-serif'],
},

```

Note: JetBrains Mono and Space Grotesk are available via Google Fonts. Add them to `src/app/layout.tsx` using `next/font/google`:

```

// src/app/layout.tsx – add at top of file
import { JetBrains_Mono, Space_Grotesk } from "next/font/google";

const jetbrainsMono = JetBrains_Mono({
  subsets: ["latin"],
  variable: "--font-mono",
  weight: ["400", "500", "700"],
});

const spaceGrotesk = Space_Grotesk({
  subsets: ["latin"],
  variable: "--font-display",
  weight: ["400", "500", "700"],
});

```

Apply both `variable` props to the `<body>` or `<html>` tag:

```

<body className={` ${jetbrainsMono.variable} ${spaceGrotesk.variable}
...`} >

```

Then update tailwind fontFamily to use CSS vars:

```
fontFamily: {
  display: ['var(--font-display)', '"Arial Black"', 'sans-serif'],
  heading: ['var(--font-mono)', '"Courier New"', 'monospace'],
  body:    ['var(--font-mono)', '"Courier New"', 'monospace'],
  mono:    ['var(--font-mono)', '"Courier New"', 'monospace'],
},
```

3.4 Global CSS (src/app/globals.css)

Replace entirely with:

```
@tailwind base;
@tailwind components;
@tailwind utilities;

/* — Root defaults — */
:root {
  --scan-line-opacity: 0.03;
  --glow-cyan: 0 0 8px rgba(0, 217, 255, 0.4);
  --glow-green: 0 0 8px rgba(0, 255, 136, 0.4);
  --glow-red: 0 0 8px rgba(255, 51, 102, 0.4);
}

html, body {
  background-color: #08080d;
  color: #e2e2f0;
  font-family: 'JetBrains Mono', 'Fira Code', 'Courier New', monospace;
}

/* — Page frame: thin phosphor border — */
.page-frame {
  min-height: 100vh;
  border: 1px solid #1e1e2a;
  position: relative;
}

/* CRT scan-line overlay on page-frame */
.page-frame::before {
  content: "";
  pointer-events: none;
  position: fixed;
  inset: 0;
  z-index: 9999;
  background: repeating-linear-gradient(
    0deg,
```

```

    transparent,
    transparent 2px,
    rgba(0,0,0, var(--scan-line-opacity)) 2px,
    rgba(0,0,0, var(--scan-line-opacity)) 4px
  );
}

/* — Scrollbars — */
::-webkit-scrollbar { width: 4px; height: 4px; }
::-webkit-scrollbar-track { background: #08080d; }
::-webkit-scrollbar-thumb { background: #2a2a3a; border-radius: 2px; }
::-webkit-scrollbar-thumb:hover { background: #00d9ff; }

/* — Cursor blink for prompt UIs — */
@keyframes cursor-blink {
  0%, 100% { opacity: 1; }
  50% { opacity: 0; }
}
.cursor-blink::after {
  content: "█";
  display: inline-block;
  animation: cursor-blink 1s step-end infinite;
  color: #00d9ff;
  margin-left: 2px;
}

/* — Glow utilities (apply with Tailwind @apply or class) — */
.glow-cyan { box-shadow: var(--glow-cyan); }
.glow-green { box-shadow: var(--glow-green); }
.glow-red { box-shadow: var(--glow-red); }
.text-glow-cyan { text-shadow: 0 0 8px rgba(0,217,255,0.6); }
.text-glow-green { text-shadow: 0 0 8px rgba(0,255,136,0.6); }

/* — Grid background pattern (for landing/dashboard) — */
.grid-bg {
  background-image:
    linear-gradient(rgba(0,217,255,0.03) 1px, transparent 1px),
    linear-gradient(90deg, rgba(0,217,255,0.03) 1px, transparent 1px);
  background-size: 32px 32px;
}

/* — Pulse animation (used on loading states) — */
@keyframes pulse-slow {
  0%, 100% { opacity: 1; }
  50% { opacity: 0.4; }
}
.animate-pulse-slow { animation: pulse-slow 2s ease-in-out infinite; }

/* — Plotly overrides — */
.js-plotly-plot .plotly .modebar { background-color: transparent !important; }
.js-plotly-plot .plotly .main-svg { background: transparent !important; }

```

```

/* — Input / form focus — */
input:focus, textarea:focus {
  outline: none;
  border-color: #00d9ff !important;
  box-shadow: 0 0 0 1px #00d9ff22;
}

```

3.5 Design Micro-Patterns

These patterns should appear consistently across components:

Pattern	Usage	Example class combo
Layer labels	Section eyebrows: // 01, // 02	font-mono text-[9px] text-text-muted uppercase
Prompt prefix	Before input placeholders: >	Prepend in JSX or use ::before
Status badges	Pill with left dot	flex items-center gap-1.5 font-mono text-[9px]
Divider lines	Horizontal rules with label	border-t border-border-dim + centered label
Hover glow	Buttons and links	hover:border-accent-cyan hover:text-glow-cyan
Active neon	Selected/active state	border-accent-cyan text-accent-cyan glow-cyan

4. COMPONENT REDESIGNS

PROF

Apply each of the following changes. Components not listed require only the global color token substitution (swap `bg-white` → `bg-bg-surface`, `border-black` → `border-border-normal`, `text-black` → `text-text-primary`, `text-black/50` → `text-text-muted`).

4.1 TopNav (src/components/layout/TopNav.tsx)

Visual goal: Thin terminal status bar. Logo glows cyan. Version tag is a bright badge.

```

// Replace entire return block with:
<header className="bg-bg-base border-b border-border-normal">
  <div className="flex h-10 items-center justify-between px-4 md:px-6">

    <Link href="/dashboard" className="flex items-center gap-2.5 group">
      <BarChart3 className="h-4 w-4 text-accent-cyan" />
      <span className="font-display text-xs font-bold uppercase

```

```

tracking-widest text-text-primary group-hover:text-accent-cyan
transition-colors">
    Agent_DA
  </span>
  <span className="font-mono text-[8px] font-bold text-bg-surface
bg-accent-cyan px-1.5 py-0.5 leading-none">
    v1.0
  </span>
</Link>

{ /* Right: decorative status + nav */}
<nav className="flex items-center gap-4">
  { /* Live indicator */}
  <div className="hidden md:flex items-center gap-1.5 font-mono
text-[9px] text-text-muted">
    <span className="h-1.5 w-1.5 rounded-full bg-accent-green
animate-pulse" />
    <span>SYS.ONLINE</span>
  </div>

  <Link
    href="/data/upload"
    className="flex items-center gap-1.5 border border-border-normal
bg-bg-surface text-text-primary font-mono text-[10px] uppercase px-3 py-
1.5 hover:border-accent-cyan hover:text-accent-cyan transition-colors
leading-none"
    >
    <Database className="h-3 w-3" />
    <span>+ Connect</span>
  </Link>

  {isSignedIn && (
    <div className="pl-3 border-l border-border-normal">
      <UserButton appearance={{
        elements: { avatarBox: "h-6 w-6 border border-border-bright
rounded-none" }
      }} />
    </div>
  )}
</nav>
</div>
</header>

```

PROF

4.2 Sidebar (src/components/layout/Sidebar.tsx)

Visual goal: Dark terminal file-tree panel. Sessions listed like filesystem entries.

Key class changes:

- Root `<aside>`: `bg-bg-base border-r border-border-normal`

- "New Analysis" button: `bg-accent-cyan text-bg-base font-mono text-[10px] uppercase` with `hover:bg-accent-cyan/80`
- Section label: Add `// recent` as layer label above sessions list: `font-mono text-[9px] text-text-faint uppercase tracking-widest`
- Each session link (inactive): `border-transparent text-text-muted hover:border-border-normal hover:text-text-primary`
- Each session link (active): `border-border-bright bg-bg-raised text-accent-cyan`
- Delete button: `text-text-faint hover:text-accent-red`
- Collapse toggle: `border-border-dim bg-bg-surface hover:border-accent-cyan hover:text-accent-cyan`

4.3 `MessageInput` (`src/components/chat/MessageInput.tsx`)

Visual goal: Terminal prompt with `>_` prefix feel.

```
// Replace <form> and interior with:
<form onSubmit={handleSubmit} className="relative bg-bg-surface border
border-border-normal focus-within:border-accent-cyan transition-colors
px-3 py-2.5">
  {/* Prompt glyph */}
  <span className="absolute left-3 top-3 font-mono text-xs text-accent-
cyan select-none pointer-events-none">
    &gt;
  </span>
  <textarea
    ref={textareaRef}
    rows={1}
    placeholder="ask anything about your dataset..."
    value={text}
    onChange={(e) => setText(e.target.value)}
    onKeyDown={handleKeyDown}
    disabled={disabled}
    className="w-full resize-none bg-transparent font-mono text-xs text-
text-primary placeholder-text-faint outline-none disabled:opacity-40 pl-
5 pr-10 min-h-[22px] max-h-[160px] overflow-y-auto"
  />
  <div className="absolute right-2.5 bottom-2.5">
    <button
      type="submit"
      disabled={!text.trim() || disabled}
      className="flex h-6 w-6 items-center justify-center bg-accent-cyan
text-bg-base hover:bg-accent-cyan/80 transition-colors disabled:opacity-
20 disabled:cursor-not-allowed"
    >
      <ArrowUp className="h-3 w-3" />
    </button>
  </div>
</form>
```

4.4 `MessageList` (`src/components/chat/MessageList.tsx`)

Visual goal: Chat messages look like terminal I/O sessions.

Key changes per message bubble:

- User message container: `border border-border-dim bg-bg-raised` (dimmer)
- Assistant message container: `border border-border-normal bg-bg-surface`
- User avatar: `bg-bg-raised border-border-bright text-accent-cyan`
- Assistant avatar: `bg-accent-cyan/10 border-accent-cyan text-accent-cyan`
- Role label (user): `font-mono text-[9px] text-text-muted`
- Role label (assistant): `font-mono text-[9px] text-accent-cyan text-glow-cyan`
- Body text: `font-mono text-xs text-text-primary leading-relaxed`
- Inline `<code>`: `bg-bg-overlay border border-border-bright text-text-code px-1 font-mono text-[10px]`
- Loading skeleton lines: `bg-border-normal animate-pulse-slow`

Loading indicator text: Change "Anton Agent is analyzing..." → `"// executing analysis"` with `.cursor-blink` class.

4.5 `ExecutionConsole` (`src/components/agent/ExecutionConsole.tsx`)

This component already has a dark theme. Make the following adjustments:

- Outer border: `border border-border-normal`
- Toggle button bar: `bg-bg-surface hover:bg-bg-raised`
- Status badges: Keep existing logic but change color classes:
 - success: `text-accent-green border-accent-green bg-accent-green/10`
 - timeout: `text-accent-yellow border-accent-yellow bg-accent-yellow/10`
 - failed: `text-accent-red border-accent-red bg-accent-red/10`
- Inner dark block (code/stdout/stderr): `bg-[#04040a]` (slightly deeper than surface)
- Generated code label: `text-[9px] uppercase tracking-widest text-text-muted`
- The `pre` block for code: Keep `text-text-code` (already `#a8ffb2`)
- Stdout text: `text-text-primary`
- Stderr section label: `text-accent-red + text-[9px] uppercase tracking-widest`

4.6 `ChartRenderer` (`src/components/agent/ChartRenderer.tsx`)

Update Plotly theme layout object inside `useEffect`:

```
const themeLayout = {
  ...layout,
  paper_bgcolor: "transparent",
  plot_bgcolor: "#0f0f17",
  font: {
    family: "'JetBrains Mono', 'Courier New', monospace",
```

```

    size: 10,
    color: "#e2e2f0",
  },
  title: {
    text: visualization.title,
    font: { family: "'Space Grotesk','Arial Black',sans-serif", size:
13, color: "#e2e2f0" },
    x: 0.0,
  },
  margin: { t: 40, r: 16, b: 48, l: 48 },
  colorway: ["#00d9ff", "#00ff88", "#ff3366", "#ffc832", "#9b60ff",
"#ff9966"],
  gridcolor: "#1e1e2a",
  zerolinecolor: "#2a2a3a",
  height: 380,
  autosize: true,
  xaxis: { gridcolor: "#1e1e2a", zerolinecolor: "#2a2a3a" },
  yaxis: { gridcolor: "#1e1e2a", zerolinecolor: "#2a2a3a" },
};

```

Outer wrapper: `border border-border-normal bg-bg-surface`

4.7 `DataProfileCard` (`src/components/data/DataProfileCard.tsx`)

- Root border: `border border-border-normal bg-bg-surface`
 - Header bar: `border-b border-border-normal bg-bg-base px-4 py-3`
 - Dataset name: `font-mono text-xs font-bold text-text-primary`
 - Metadata row: `font-mono text-[9px] text-text-muted`
 - Tab buttons (inactive): `bg-bg-base text-text-muted hover:text-text-primary hover:bg-bg-raised`
 - Tab buttons (active): `bg-bg-raised text-accent-cyan border-b-2 border-accent-cyan`
(change the existing `border+bg` logic to `border-bottom active indicator`)
 - Anomaly badge counter: `bg-accent-red text-bg-base`
 - Profiling spinner: `border-accent-cyan border-t-transparent`
 - Schema table header row: `text-[9px] uppercase text-text-muted font-mono`
 - Schema table rows: `font-mono text-[11px] text-text-primary hover:bg-bg-raised`
 - Dtype values: `text-accent-cyan`
 - Stat cards: `border border-border-dim bg-bg-base`
 - Stat card label: `font-mono text-[8px] uppercase text-text-muted`
 - Stat card value: `font-mono text-xs font-bold text-text-primary`
-

4.8 `FileUploader` (`src/components/data/FileUploader.tsx`)

- Drop zone border: Change `border-2 border-black` → `border border-dashed border-border-bright`
- Drop zone active: `border-accent-cyan bg-accent-cyan/5`

- Drop zone default: `bg-bg-surface hover:bg-bg-raised`
- Upload icon: `text-text-muted`
- Primary text: `font-mono text-sm text-text-primary`
- "browse" link text: `text-accent-cyan hover:text-glow-cyan`
- Constraint label: `font-mono text-[9px] uppercase text-text-faint`
- File selected — filename: `font-mono text-sm text-accent-green`
- Upload progress bar: `bg-accent-cyan` (track: `bg-bg-raised border border-border-dim`)
- Error block: `border border-accent-red bg-accent-red/5 text-accent-red`

4.9 `SQLConnector` (`src/components/data/SQLConnector.tsx`)

- Form labels: `font-mono text-[9px] uppercase text-text-muted`
 - All inputs: `bg-bg-raised border border-border-normal text-text-primary font-mono text-xs placeholder-text-faint focus:border-accent-cyan`
 - "Verify Connection" button: `border border-border-bright bg-bg-surface text-text-primary font-mono text-[10px] uppercase hover:border-accent-cyan hover:text-accent-cyan`
 - "Save Data Source" button: `border border-accent-cyan bg-accent-cyan text-bg-base font-mono text-[10px] uppercase hover:bg-accent-cyan/80`
 - Success result block: `border border-accent-green bg-accent-green/5 text-accent-green`
 - Failure result block: `border border-accent-red bg-accent-red/5 text-accent-red`
-

5. PAGE REDESIGNS

5.1 Landing Page (`src/app/page.tsx`)

Visual goal: Full-screen terminal hero with grid-bg, followed by feature sections in schematic-layer style.

Key layout changes:

PROF


Remove:

- The Dell ad top banner
- The icon-label nav grid (Search/Home/Store/Service)
- The "PC Mag Readers Choice" seal
- The bottom footer icon-nav row
- The "browser compat note"

Add:

- `grid-bg` class on `<div className="bg-bg-base grid-bg min-h-screen">`
- Hero section with blinking cursor on headline

New landing page structure:



```
[header bar – logo left, signin right]  dark, h-10
```

```
// 01                                [STATUS: ONLINE ●]
```

```
AGENT_DA
```

```
Conversational Data Analysis ■
```

```
Ask your database anything in plain english.
```

```
Python executes in an isolated sandbox. Charts render.
```

```
> [  Get Started – free  ]  [ View on GitHub ]
```

```
— SUPPORTED FORMATS —
```

```
.csv .xlsx .json PostgreSQL
```

```
// 02  HOW IT WORKS
```

```
[01 INGEST]  [02 PROFILE]  [03 QUERY]  [04 RENDER]
```

```
Upload file  Schema+stats  Natural lang  Plotly chart
```

```
// 03  FEATURE CARDS (3-col grid)
```

```
FLEXIBLE  
INGESTION
```

```
CONVERSATIONAL  
CONTEXT
```

```
SANDBOXED  
EXECUTION
```

Exact JSX changes to `page.tsx`:

1. Wrap entire return in `<div className="bg-bg-base grid-bg min-h-screen font-mono">`.
2. Replace header bar:

```
<div className="flex h-10 items-center justify-between border-b  
border-border-normal px-6">  
  <div className="flex items-center gap-2.5">  
    <BarChart3 className="h-4 w-4 text-accent-cyan" />  
    <span className="font-display text-xs font-bold uppercase  
tracking-widest text-text-primary">Agent_DA</span>  
    <span className="font-mono text-[8px] bg-accent-cyan text-bg-  
base px-1.5 py-0.5">v1.0</span>  
  </div>  
  <div className="flex items-center gap-3">  
    {!isSignedIn ? (  

```

```

    </>
    <SignInButton mode="modal">
      <button className="font-mono text-[10px] text-text-muted
hover:text-accent-cyan">sign_in</button>
    </SignInButton>
    <SignUpButton mode="modal">
      <button className="border border-accent-cyan text-accent-
cyan font-mono text-[10px] px-3 py-1.5 hover:bg-accent-
cyan/10">get_started</button>
    </SignUpButton>
  </>
) : (
  <Link href="/dashboard" className="border border-accent-cyan
text-accent-cyan font-mono text-[10px] px-3 py-1.5 hover:bg-accent-
cyan/10">
    dashboard →
  </Link>
)}
</div>
</div>

```

3. Replace hero with:

```

<div className="max-w-4xl mx-auto px-6 pt-20 pb-16">
  <div className="font-mono text-[9px] text-text-muted uppercase
tracking-widest mb-6">// 01 . INIT</div>
  <h1 className="font-display text-5xl md:text-7xl font-bold text-
text-primary leading-[0.9] mb-4">
    AGENT_DA
  </h1>
  <p className="font-mono text-base text-accent-cyan mb-2 cursor-
blink">
    conversational data analysis
  </p>
  <p className="font-mono text-sm text-text-muted max-w-xl leading-
relaxed mb-10">
    Upload a CSV or connect PostgreSQL. Ask anything in plain
English. The agent writes Python, runs it in a locked sandbox, and
returns charts + narrative.
  </p>
  <div className="flex flex-wrap gap-3">
    {/* Primary CTA */}
    <SignUpButton mode="modal">
      <button className="border border-accent-cyan bg-accent-
cyan/10 text-accent-cyan font-mono text-xs px-5 py-2.5 hover:bg-
accent-cyan/20 transition-colors">
        > get_started()
      </button>
    </SignUpButton>
    {/* Secondary */}
    <a href="#features" className="border border-border-normal

```

```

text-text-muted font-mono text-xs px-5 py-2.5 hover:border-border-
bright hover:text-text-primary transition-colors">
  learn_more →
</a>
</div>
{ /* Format pills */ }
<div className="flex flex-wrap gap-2 mt-8">
  [{"csv", ".xlsx", ".json", "PostgreSQL"}].map((f) => (
    <span key={f} className="font-mono text-[9px] border border-
border-dim text-text-muted px-2 py-1">
      {f}
    </span>
  )))
</div>
</div>

```

4. Replace the two-column feature section with a horizontal "how it works" pipeline:

```

<div className="border-t border-border-dim px-6 py-16 max-w-4xl mx-
auto">
  <div className="font-mono text-[9px] text-text-muted uppercase
tracking-widest mb-8">02 · PIPELINE</div>
  <div className="grid grid-cols-2 md:grid-cols-4 gap-px bg-border-
dim border border-border-dim">
    {[
      { n: "01", title: "INGEST", desc: "CSV · XLSX · JSON ·
PostgreSQL" },
      { n: "02", title: "PROFILE", desc: "Schema, stats, anomaly
detection" },
      { n: "03", title: "QUERY", desc: "Plain English → Python
code" },
      { n: "04", title: "RENDER", desc: "Interactive Plotly
charts" },
    ]}.map((step) => (
      <div key={step.n} className="bg-bg-surface p-5">
        <div className="font-mono text-[9px] text-text-faint mb-2">
{step.n}</div>
        <div className="font-mono text-xs font-bold text-accent-
cyan mb-1">{step.title}</div>
        <div className="font-mono text-[10px] text-text-muted
leading-relaxed">{step.desc}</div>
      </div>
    )))
  </div>
</div>

```

5. Replace feature ribbon cards with a 3-col card grid (id="features"):

```

<div id="features" className="border-t border-border-dim px-6 py-16
max-w-4xl mx-auto">
  <div className="font-mono text-[9px] text-text-muted uppercase
tracking-widest mb-8">// 03 · CAPABILITIES</div>
  <div className="grid md:grid-cols-3 gap-px bg-border-dim border
border-border-dim">
    {[
      {
        icon: Database,
        title: "FLEXIBLE INGESTION",
        body: "CSV, Excel, and JSON files or live read-only
PostgreSQL. Automatic schema profiling on load.",
        accent: "text-accent-cyan",
      },
      {
        icon: MessageSquare,
        title: "CONVERSATIONAL CTX",
        body: "Follow-up questions work naturally. Agent remembers
schema, prior code, and findings.",
        accent: "text-accent-green",
      },
      {
        icon: ShieldCheck,
        title: "SANDBOXED EXEC",
        body: "All code runs in a locked, network-less Docker
container. Memory-capped. No data leakage.",
        accent: "text-accent-purple",
      },
    ]}.map((f) => (
      <div key={f.title} className="bg-bg-surface p-6 hover:bg-bg-
raised transition-colors">
        <f.icon className={`h-5 w-5 mb-3 ${f.accent}`} />
        <div className="font-mono text-[10px] font-bold text-text-
primary mb-2">{f.title}</div>
        <div className="font-mono text-[10px] text-text-muted
leading-relaxed">{f.body}</div>
      </div>
    )))
  </div>
</div>

```

PROF

6. Footer:

```

<footer className="border-t border-border-dim px-6 py-6 font-mono
text-[9px] text-text-faint flex justify-between items-center">
  <span>© {new Date().getFullYear()} Agent_DA</span>
  <span>SYSTEM READY</span>
</footer>

```

5.2 Dashboard (`src/app/dashboard/page.tsx`)

Visual goal: Workstation command-center. Grid layout feels like a filesystem browser.

Key changes:

1. Page root background: ensure `bg-bg-base` (applied by PageShell body)
2. Page header:
 - Title: `font-display text-xl font-bold uppercase text-text-primary`
 - Subtitle: `font-mono text-[10px] text-text-muted`
 - "Connect New Data" button: `border border-accent-cyan text-accent-cyan bg-transparent font-mono text-[10px] px-4 py-2 hover:bg-accent-cyan/10`
3. Section label "Connected Datasets": `font-mono text-[9px] uppercase text-text-faint` with `// ds` prefix
4. Each data source row:
 - Container: `border border-border-dim bg-bg-surface hover:bg-bg-raised hover:border-border-normal`
 - Icon box: `bg-bg-overlay border border-border-dim`
 - Name: `font-mono text-xs font-bold text-text-primary`
 - Metadata: `font-mono text-[9px] text-text-muted`
5. Status badges:
 - `complete` → `text-accent-green border-accent-green bg-accent-green/10 + ● READY`
 - `running` → `text-accent-yellow border-accent-yellow bg-accent-yellow/10 animate-pulse + ● PROFILING`
 - `failed` → `text-accent-red border-accent-red bg-accent-red/10 + ● FAILED`
 - `pending` → `text-text-muted border-border-dim + ○ PENDING`
6. "Analyze" button: `border border-accent-cyan text-accent-cyan bg-transparent font-mono text-[10px] hover:bg-accent-cyan/10`
7. Delete button: `text-text-faint hover:text-accent-red`
8. Empty state: Dark panel with `font-mono text-xs text-text-muted` and cyan CTA button

PROF

5.3 Upload Page (`src/app/data/upload/page.tsx`)

Visual goal: Terminal configuration panel. Tabs look like CLI flags.

Key changes:

1. Page header background: `bg-bg-base border-b border-border-dim`
2. "← Back" link: `font-mono text-[10px] text-text-muted hover:text-accent-cyan border border-border-dim px-2 py-1`
3. Tab buttons:
 - Inactive: `border-transparent text-text-muted bg-bg-surface hover:text-text-primary`
 - Active: `border-t border-l border-r border-border-normal text-accent-cyan bg-bg-raised -mb-px`

- Font: `font-mono text-[10px] uppercase`
- 4. Tab content wrapper: `border border-border-normal bg-bg-surface`
- 5. Error block: Replace with `border border-accent-red bg-accent-red/5 text-accent-red font-mono text-[10px]`

5.4 Session Page (`src/app/session/[id]/page.tsx`)

Visual goal: Split-pane terminal IDE. Left = I/O feed, right = schema inspector.

Key changes:

1. Session header: `bg-bg-base border-b border-border-dim`
2. Dataset name: `font-mono text-[10px] text-text-muted`
3. Session title: `font-mono text-xs font-bold text-text-primary`
4. "Toggle Profile" button: `border border-border-dim font-mono text-[9px] uppercase px-2.5 py-1 text-text-muted hover:border-accent-cyan hover:text-accent-cyan`
5. Message feed area: `bg-bg-base`
6. Empty state copy: Change "Anton Sandbox Ready" to `// sandbox initialized` and update suggestion buttons to `border border-border-dim bg-bg-surface text-text-muted font-mono text-[10px] hover:border-accent-cyan hover:text-accent-cyan`
7. Sidebar panel: `bg-bg-surface border-l border-border-dim`
8. "Dataset Introspection" label: `font-mono text-[9px] uppercase text-text-muted`

6. CLERK APPEARANCE OVERRIDES

In `src/app/layout.tsx`, update ClerkProvider appearance:

```
appearance={{
  variables: {
    colorPrimary: "#00d9ff",
    colorBackground: "#0f0f17",
    colorInputBackground: "#161620",
    colorInputText: "#e2e2f0",
    colorText: "#e2e2f0",
    colorTextSecondary: "#5a5a78",
    borderRadius: "0px",
  },
  elements: {
    card: "border border-[#2a2a3a] shadow-none bg-[#0f0f17]",
    formButtonPrimary: "bg-[#00d9ff] text-[#08080d] font-bold text-xs py-2.5 px-4 hover:bg-[#00d9ff]/80",
    footerActionLink: "text-[#00d9ff]",
    input: "bg-[#161620] border-[#2a2a3a] text-[#e2e2f0] font-mono text-xs focus:border-[#00d9ff]",
  }
}}
```

7. IMPLEMENTATION CHECKLIST

Execute in this exact order to minimize broken states:

- ☐ **Step 1:** Update `tailwind.config.ts` — replace color tokens and font families
- ☐ **Step 2:** Update `src/app/globals.css` — full replacement with new version above
- ☐ **Step 3:** Update `src/app/layout.tsx` — add Google Fonts, update Clerk appearance, update `<html>/<body>` classnames
- ☐ **Step 4:** Update `TopNav` — dark header, cyan accent, status indicator
- ☐ **Step 5:** Update `Sidebar` — dark panel, session entries
- ☐ **Step 6:** Update `PageShell` — ensure `bg-bg-base` on main
- ☐ **Step 7:** Update `MessageInput` — terminal prompt style
- ☐ **Step 8:** Update `MessageList` — terminal I/O bubbles
- ☐ **Step 9:** Update `ExecutionConsole` — keep dark, update badge colors
- ☐ **Step 10:** Update `ChartRenderer` — new Plotly theme object
- ☐ **Step 11:** Update `DataProfileCard` — dark panels, cyan active tab
- ☐ **Step 12:** Update `FileUploader` — dashed border, cyan drop zone
- ☐ **Step 13:** Update `SQLConnector` — dark inputs, cyan CTA
- ☐ **Step 14:** Rewrite `src/app/page.tsx` — full landing page redesign
- ☐ **Step 15:** Update `src/app/dashboard/page.tsx` — dark status badges, layout polish
- ☐ **Step 16:** Update `src/app/data/upload/page.tsx` — terminal tabs
- ☐ **Step 17:** Update `src/app/session/[id]/page.tsx` — split-pane terminal IDE feel
- ☐ **Step 18:** Run `next build` and fix any TypeScript/ESLint errors
- ☐ **Step 19:** Visual QA — open each route, verify no white backgrounds leak, no broken borders

8. COPY / MICROCOPY CHANGES

Replace all user-visible button/label copy from retro-print style to terminal-command style:

Current	New
"Connect New Data"	" + connect_data()"
"Get Started"	"> get_started()"
"Analyze"	"run →"
"Upload File"	"upload.file"
"PostgreSQL Database"	"postgres.connect"
"Verify Connection"	"test_conn()"
"Save Data Source"	"save_source()"
"New Analysis"	" + new_session"
"Anton Agent is analyzing..."	"// executing analysis"

Current	New
"Anton Sandbox Ready"	"// sandbox initialized"
"No datasets connected"	"// no data sources found"
"No active analyses."	"// no active sessions"
"Sandbox Log"	"// exec.log"
"Dataset Introspection"	"// schema.inspect"

9. WHAT NOT TO CHANGE

- **All TypeScript types** in `src/lib/types.ts` — unchanged
- **All API call logic** in `src/lib/api.ts` — unchanged
- **All hooks** in `src/hooks/` — unchanged
- **All routing** — unchanged
- **Middleware** in `src/middleware.ts` — unchanged
- **Supabase client** in `src/lib/supabase.ts` — unchanged
- **Functional logic** inside any component (handlers, `useEffects` for data, etc.) — unchanged

10. KNOWN EDGE CASES

1. **Tailwind purge:** New token names (`bg-bg-base`, `text-text-primary`, etc.) must exactly match tailwind config keys. Double-check naming.
2. **bg- * collision:** Tailwind has a built-in `bg-*` namespace. Use `"bg-base"`, `"bg-surface"` etc. as the *key names* under `colors`, not `bg-bg-base`. So in tailwind config: `colors: { "bg-base": "#08080d" }` → class is `bg-bg-base`. This is fine.
3. **Font variables:** The `var(--font-mono)` approach requires `jetbrainsMono.variable` to be applied to `<html>` or `<body>`, not just `<main>`.
4. **Scan-line z-index:** The `::before` overlay is `position:fixed; z-index:9999`. If Clerk modal or any other overlay has a lower z-index, they'll appear behind the scan lines. Apply `z-index:10000` on Clerk's modal if needed, or lower scan-line z-index to `9000`.
5. **Plotly height on mobile:** The `height: 380` in `themeLayout` may cause overflow on small screens. Conditionally set `height: 280` if `window.innerWidth < 640`.