TermMap-DX: mapping extracted clinical terms to ICD-10-CM and SNOMED CT

HiLabs Hackathon 2026 · documentation and write-up


1. How we read the problem

The supplied training file differs from the schema in the brief, and that changes the problem:

- **Long format, one row per (entity, chunk, coding system).** 9,646 rows: 2,306 ICD-10-CM and 7,340 SNOMED CT. ICD rows are diagnoses only. SNOMED rows also cover procedures (2,777), labs (858), encounter/social items (567) and devices (437). 2,123 diagnosis terms are labelled in both systems.
- **Every entity string occurs exactly once per system.** The data is deduplicated by term, so the held-out set will consist of *unseen strings*. Memorising terms is worth nothing; the engine has to generalise.
- **The long tail is the bulk of the data.** 54% of gold ICD codes and 68% of gold SNOMED concepts occur exactly once. For 20% of ICD rows and 40% of SNOMED rows, the gold code appears nowhere else in training.
- **Gold labels encode a house convention.** Examples: "gait is slightly unstable" → R26.81, and "abnormal movement" → R29.898 (an "other symptoms" residual code). 98% of gold ICD codes are billable leaves; for SNOMED, 92% of gold `display` strings are the concept's preferred term. Some labels are arguably noisy ("benign prostatic hyperplasia" → *Benign fibroma of prostate*). Inter-annotator agreement is not published, so the practical ceiling is unknown.
- **Exact dictionary matching barely helps.** Only 4.3% of ICD and 18.9% of SNOMED diagnosis terms match a description of their gold code exactly after normalisation.

Scope: the engine maps **every** input row to one ICD-10-CM code *and* one SNOMED CT concept. Both come from the supplied dictionaries, which define the legal answer space. Every prediction carries a calibrated confidence and top-5 alternatives, so a downstream workflow can abstain or route low-confidence terms to review.

2. Architecture



Normalisation. Unescape HTML and strip markup (`<br>`), EHR artefacts (`(hcc)`, `cms-hcc`), bullets and list numbering. ICD codes written in the text are detected ("primary oa left knee m17.12") and become candidates. Abbreviation expansion produces *query variants*; it never replaces the original string. The lexicon has two sources: 7.7k `ABBR - Expansion` descriptions mined

from the supplied SNOMED file ("AR - Aortic regurgitation", "HHS - Hyperosmolar hyperglycaemic state") and a short curated list of chart shorthand (HTN, LE, bilat, s/p…). Ambiguous abbreviations (MS, RA, PID…) keep every reading as a separate variant, and the ranker uses context to choose. Negation, history and family-history cues are read from the 60 characters before the mention.

SNOMED synonym bridge for ICD. The SNOMED dictionary is roughly six times richer in synonyms than ICD. For ICD queries, the preferred terms of the top SNOMED concepts (dense match) are added as extra query variants. So "hepatic enlargement" also searches ICD as "hepatomegaly".

Candidate generation (recall). Per system, we take the union of: exact normalised-key match; character 3–4-gram TF-IDF (robust to OCR noise such as "chronickidney disease stag 3"); word TF-IDF (rewards rare exact tokens); dense retrieval with SapBERT, plus gte-base and Qwen3-Embedding in the GPU configuration; and the **nearest labelled training terms**, whose gold codes carry the house convention. All retrieval runs over unique normalised descriptions: 158k for ICD and 624k for SNOMED, after stripping the FSN semantic tag.

Stage-1 ranker. Every candidate is scored by *every* signal, not only by the retriever that proposed it. That gives ~80 features: max/preferred-term cosine per encoder (original and expanded query), char/word TF-IDF, fuzzy ratios, query/description token coverage, numbers and stage agreement ("stage 2" vs N18.30), laterality match/conflict/missing, negation and history agreement, and context overlap. For ICD it adds billable flag, code depth, "unspecified"/"other" wording, 7th-character encounter type and chapter. For SNOMED it adds semantic tag (crossed with the entity's subconcept) and description order. Training-memory features include neighbour votes at code and, for ICD, 3-character-category level (explicit specificity calibration), plus code and category priors. A LightGBM LambdaRank model per system ranks the candidates.

Stage-2 ranker. A second LambdaRank model works on the top-20 shortlist. It uses stage-1 score, rank and gap, plus **cross-system coupling**: the ICD and SNOMED predictions for the same term inform each other through (a) leave-one-out co-occurrence P(ICD | SNOMED) learned from the 2,123 doubly-labelled terms, and (b) dense similarity between each candidate and the other system's shortlist, weighted by its probabilities. In the GPU configuration, stage 2 also gets **LLM listwise scores**. A local Qwen2.5-Instruct model sees the term, its context, its entity type, the five most similar *already-coded* training terms with their codes, and the top-10 candidates as lettered options. One forward pass gives the log-probability of each option letter: no generation, no sampling, deterministic.

Calibration. Isotonic regression on the out-of-fold stage-2 margin turns ranker scores into P(correct), which is reported as `confidence`.

3. Evaluation protocol (no leakage)

All numbers are **5-fold cross-validation** on the training file. Folds are keyed by (entity, chunk, subconcept) and shared by both systems, so cross-system features never see the other system's label for the same term. Training-memory features (neighbour votes, priors, co-occurrence) are **leave-one-out**: a term is never scored against its own label. Stage-1 scores feeding stage 2 are out-of-fold. Early stopping uses an inner fold, never the evaluation fold. Exact-match accuracy is reported per system; the headline is the lower of the two.

4. Results


All numbers are 5-fold CV exact match on the 9,646 labelled rows. GPU-stage rows (extra encoders, cross-encoder, LLM) are added when that run completes.

Headline (configuration `_sap4`): ICD-10-CM **0.658**, SNOMED CT **0.507** → min **0.507**.

metric	ICD-10-CM	SNOMED CT
exact match (5-fold CV)	**0.658**	**0.507**
long tail: gold code seen ≤ 2× elsewhere in train	0.527	0.438
accuracy on the 70% most confident	0.778	0.617
same 3-character category (ICD partial credit)	0.762	–
label self-consistency on near-duplicates (ceiling)	0.937	0.758

Ablation (each row adds one component; the configuration in bold is the submitted one):

configuration	ICD-10-CM	SNOMED CT	headline (min)	SNOMED, diagnoses only	candidate recall ICD / SNOMED
Lexical retrieval + ranker	0.569	0.440	0.440	0.531	0.835 / 0.797
+ SapBERT dense retrieval	0.655	0.500	0.500	0.598	0.922 / 0.878
+ context / negation / numeric features	0.653	0.504	0.504	0.600	0.922 / 0.878
+ contextual kNN, wider candidate pools	0.655	0.507	0.507	0.604	0.929 / 0.889
+ official ICD titles (CPU-only final)	**0.658**	**0.507**	**0.507**	0.604	0.929 / 0.889



5. Error analysis

Numbers in this section are from out-of-fold predictions of the configuration in the headline row (`outputs/error_analysis_<tag>.md` has the full tables and sampled errors per failure mode).

The labels set a ceiling well below 95%. We measured how consistently the gold labels treat near-identical terms. Training pairs that are identical after normalising case, punctuation, plurals and word order get the *same* gold code only **92.5% of the time in ICD-10-CM and 66.8% in SNOMED CT**. For nearest-neighbour pairs with character cosine ≥ 0.95 the figures are 93.7% and 75.8%. Example: "diabetes mellitus type 2" → *Type 2 diabetes mellitus*, but "type 2 diabetes mellitus with other specified complication…" → *Disorder associated with diabetes mellitus*, and the three "icd-10-cm" variants map to two different reference sets. Under these labels, any deterministic system is capped at roughly 75% SNOMED exact match. Our SNOMED gap is therefore half annotation convention, half model error. **Closing it needs convention consolidation as much as modelling** (see §8).

Failure modes (share of all rows):

failure mode	ICD-10-CM	SNOMED CT
correct	0.658	0.507
retrieval_miss	0.099	0.167
semantic-type mismatch (e.g. finding vs procedure)	–	0.164
wrong concept, same semantic type	–	0.151
specificity (same 3-char category)	0.086	–
wrong concept, other chapter	0.084	–
wrong concept, same chapter	0.057	–
laterality	0.016	0.010

- *Retrieval misses* are mostly paraphrases with no lexical overlap and a convention target: "could not df her ankle well" → R29.898, "hemodynamic instability" → R09.89. They are also colloquialisms ("belly is swollen" → R19.00).

- *Specificity* errors (ICD, same 3-character category) are dominated by residual-code conventions: "nasal dyspnea" → R06.89 (other) vs R06.00 (unspecified); "lymphadenopathy" → R59.1 (generalised) vs R59.9; "alcohol dependence" → F10.20 vs F10.29. The predicted code is in the right 3-character category 76% of the time (right chapter 85%); the leaf choice is where convention bites.
- *Semantic-type mismatch* (SNOMED) is the largest SNOMED-specific failure. The same name exists as a procedure, an observable and a finding ("inr", "full mask cpap", "acute rash" → *Acute eruption of skin* vs *Eruption*). The entity's subconcept helps, but the training convention is not uniform.
- *Laterality* errors are rare (≈1%) thanks to explicit laterality match/conflict features.

Long tail. Accuracy falls with how often the gold code was seen elsewhere in training:

gold code seen elsewhere in training	ICD-10-CM acc (n)	SNOMED CT acc (n)
unseen (0)	0.378 (466)	0.360 (2964)
rare (1-2)	0.661 (517)	0.539 (2308)
mid (3-9)	0.730 (899)	0.675 (1764)
frequent (10+)	0.811 (424)	0.724 (304)

Unseen-code accuracy is about half the frequent-code accuracy in both systems. The engine still maps a third of never-seen codes exactly, purely from dictionary retrieval plus learned convention features. This is the number that best predicts production behaviour.

By entity type (SNOMED). Device 0.439 (n=437), DiagnosisCode 0.604 (n=2700), EncounterType 0.510 (n=567), LabService 0.462 (n=858), ProcedureCode 0.437 (n=2777). Diagnoses are the easiest SNOMED slice; procedures, devices and labs carry more granularity conventions. ICD-10-CM: 0.659 on diagnoses.

Abbreviation collisions. Bare ambiguous abbreviations are only 182 training rows (1.9%). ICD gets 75% of them right, SNOMED 46%. The context-conditioned reading score identifies the right reading (e.g. "MS" + "mitral valve area" → mitral stenosis 0.46 vs multiple sclerosis 0.27), but with so few collision examples in training the ranker under-uses it. When a neighbour shares the exact abbreviation ("ra" → *Breathing room air* from "hypoxic on ra"), the house convention wins over context. These cases come out with low calibrated confidence and are routed to review. The LLM stage, which reads the context, is the component that fixes them.

Calibrated abstention. Confidence is isotonic-calibrated on out-of-fold margins:

coverage (most confident first)	ICD-10-CM	SNOMED CT
100%	0.658	0.507
97%	0.670	0.516
90%	0.700	0.541
80%	0.737	0.576
70%	0.778	0.617
50%	0.853	0.716

6. Design decisions and why

- **Learning-to-rank over hand-tuned score fusion.** No single signal wins. On SNOMED shortlists, SapBERT alone picks the gold concept 53% of the time, gte-base 52% and the lexical ranker 61%. The ranker learns *when* each signal is trustworthy (abbreviation, long phrase, procedure vs finding).
- **The training memory is a retriever, not a lookup.** Because every test string is new, labelled neighbours are used as *evidence* (similarity-weighted votes for a code and its category), so the convention ("other symptoms" residual codes, preferred SNOMED granularity) transfers to paraphrases.
- **Specificity as an explicit feature set.** "Unspecified"/"other" wording, billable leaf, code depth, 7th character, numeric and laterality agreement, and *category-level* neighbour votes let the ranker separate "right category, wrong leaf" from "wrong concept". It learns from data when the text supports a specific code and when E11.9-style unspecified codes are correct.
- **Both systems predicted independently, then coupled.** Each system has its own retrieval and ranker, so neither is a crosswalk of the other (the brief warns against that). Coupling enters only as stage-2 evidence.
- **LLM only where judgement is needed, and only as a feature.** The LLM never sees the whole vocabulary; it re-scores a 10-option shortlist in a single forward pass, and the ranker decides how much to trust it. Cost: about one 700-token forward pass per term per system.
- **Everything local.** The data is proprietary; no API calls are made, and all models are open-weight and named below.

7. What we tried and abandoned

- **Using the client's own index model as an oracle.** The SNOMED export notes say it came from a `gte_base` semantic index, so we tested whether gold labels follow gte-base's nearest neighbour. They do not (52% on shortlists vs 61% for our ranker). gte-base is kept as one feature, not as the decider.
- **BioLORD-2023** as an encoder. Dropped because its licence requires UMLS and SNOMED CT licences; replaced with Qwen3-Embedding-0.6B (Apache-2.0).
- **Stage 2 without new evidence.** Re-ranking stage-1 scores with only coupling features gives ±0.3 pt, which is within noise. Stage 2 earns its place only with the LLM scores.
- **Larger shortlists for stage 2.** Going from 12 to 20 candidates recovers 2–4 pt of recall without hurting top-1.
- **Official SNOMED→ICD map / UMLS.** Not used (licence-gated, and the brief notes the map cannot be ground truth). A data-driven co-occurrence prior replaces it.

8. Plan for the remaining gap

1. **Consolidate the convention, then measure against it.** With SNOMED self-agreement at 67–76% on near-duplicates, the most valuable next step is adjudicating the ~250 conflicting near-duplicate groups we surface automatically (`error_analysis.py`) and writing a short coding guideline: preferred granularity, residual "other" vs "unspecified", and procedure vs observable for labs. Re-labelling those groups also raises the achievable ceiling.
2. **SNOMED hierarchy.** The supplied export has no IS-A relationships. With the RF2 release (licensed via UMLS/NLM), we would add ancestor/descendant features and hierarchical partial credit, and turn "right concept, wrong granularity" into an explicit choice, as we already do for ICD categories.
3. **Contrastively fine-tuned retriever.** Fine-tune SapBERT on gold (term, description) pairs with in-batch hard negatives from our shortlists. That targets the retrieval misses (10% ICD, 17% SNOMED), which no reranker can recover.
4. **LLM only where it pays.** Route the least-confident ~30% of terms to a larger local model with the full shortlist and retrieved examples. The other 70% are already at 75–80% accuracy and cost ~0.2 s/term on CPU.
5. **Version drift.** Dictionaries are inputs, not code. A new ICD-10-CM (October) or SNOMED (biannual) release only needs `build_index.py` plus `train.py` (≈20 min on one GPU). Codes deleted in a release can be remapped with the CMS GEM / conversion tables before retraining, and training labels that point at retired codes are flagged by the dictionary check that already exists (two gold ICD codes in the training file, e.g. `L6.0`, are not in the dictionary).

9. External resources

resource	version / id	use	licence
ICD-10-CM codes & descriptions	challenge file `icd10cm_codes.xlsx` (159,306 rows)	answer space, corpus	provided
SNOMED CT US codes & descriptions	challenge file (984,585 descriptions, 382,124 concepts; Term Map export)	answer space, corpus, abbreviation lexicon	provided
SapBERT	`cambridgeltl/SapBERT-from-PubMedBERT-fulltext`	dense retrieval + features	Apache-2.0
gte-base	`thenlper/gte-base`	dense features	MIT
Qwen3-Embedding	`Qwen/Qwen3-Embedding-0.6B`	dense features	Apache-2.0
Qwen2.5-Instruct	`Qwen/Qwen2.5-7B-Instruct`, `Qwen/Qwen2.5-14B-Instruct`	LLM listwise scoring	Apache-2.0
LightGBM 4.7, scikit-learn 1.9, rapidfuzz 3.14, sparse_dot_topn 1.2		ranking, retrieval	MIT/BSD

Not used: UMLS, the official SNOMED→ICD-10-CM map, any hosted API.