

Analysis of Non-destructive Testing for Improved Inspection and Maintenance Strategies

Kuldeep Sharma

Welspun Tubular, Little Rock, USA

E-mail: ksmb3112@gmail.com

Abstract

A significant trouble for research is making an arrangement for the administration and upkeep of the fabricated legacy. To foster a philosophy for non-destructive testing (NDT) of substantial designs in light of the distinguishing proof of (a) the responsiveness of the NDT methods, (b) the vulnerability of the NDT estimations, and (c) the best mix of NDT strategies, a huge exploratory program was established. To decide how they are utilized in Indian legislative offices, this exploration assesses NDT strategies. The consequences of an overview poll that was dispersed to Divisions of Transportation (Specks) in all Indian states filled in as the establishment for the ends and examinations presented here. The survey was processed by a total of 28 state agencies, and the main results collected from the states are shown and thoroughly discussed in this report. Additionally, inspection-hard to-find bridge flaws and ongoing research into developing innovative NDT techniques were looked into.

Keywords: Non-destructive testing, Inspection, Maintenance strategies, Non-destructive evaluation

1. INTRODUCTION

Acoustic strategies are leaned toward around here, where the current improvement of non-destructive testing of materials in structural designing is for the most part centered around the ID of deficiencies and imperfections in substantial parts and designs. Acoustic strategies stand out since they have progressed fundamentally lately, and there is a positive pattern towards utilizing acoustic signs handled by suitable programming utilizing modern information examination calculations to get familiar with a tried part or construction. The evaluation of properties other than strength in parts or designs, particularly those made out of concrete or supported concrete, is one more pattern in the advancement of non-destructive strategies. Similar to medical technology, test equipment is increasingly being designed such that users can see into the thing being evaluated. An increasingly complex examination of the test findings is now feasible thanks to software that is built into the available gear and is based on modern mathematical algorithms and artificial intelligence.

Building inspection on-site, also known as in-situ building exams, is a challenging task that calls for the application of non-destructive investigation (NDT) methods. In this context, the measurements of ultrasonic pulse velocity (UPV) and quantitative infrared thermography (QIRT) are of utmost significance. The improvement of such non-destructive testing

techniques' quantitative on-site application for monitoring and diagnostic reasons is one of the primary issues. This article presents the information obtained about QIRT and ultrasonic testing, mostly with a focus on case studies completed on old materials and buildings. These case studies are really research projects designed to create in-situ QIRT and ultrasonic testing techniques for particular issues pertaining to building inspection and monitoring as well as to learn more about their advantages and disadvantages in this respect.

In general, thermal, mechanical, chemical, and electrochemical procedures are used to create surfaces with the necessary quality and attributes. Pre-service quality of surfaces is assured during these operations by checking for harmful flaws as well as technical qualities including tensile strength, hardness, surface roughness, and residual stresses. Destructive and non-destructive testing (NDT) procedures are required for this point. Destructive methods are continuously testing procedures, and they just give measurable conviction. In addition, integrating them into manufacturing processes takes time and is challenging. On the other hand, because to the high testing speed and reusability of the component after testing, there is a significant demand for NDT techniques for use at an industrial scale, particularly for big and costly components. On operational components, NDT methods are also used for surface characterization and for the identification of surface deterioration. Depending on the scope of the investigation and the information contained within, NDT methods may be divided into surface and volumetric procedures. As opposed to radiography and ultrasonic techniques, which are volumetric strategies, surface strategies including fluid penetrant, attractive molecule, whirlpool current, and thermography are inclined toward for exploring surfaces. Surface characterization is done using ultrasonic surface waves. Each method has certain strengths and weaknesses.

The analysis of material surfaces is also being done using recently developed NDT methods as laser scattering, magnetic Barkhausen noise, X-ray diffraction, pulse thermography, atomic force microscopy, and scanning acoustic microscopy. Like with traditional NDT methods, choosing advanced techniques is crucial and is based on three key factors: the techniques' capacity, application, and limitations. It could be required to use more than one approach in certain circumstances.

2. LITERATURE REVIEW

The study by Mustafa, Khan, and Khan (2018) focuses on the reliability evaluation of NDT methods for the structural inspection of aircraft. The performance and efficacy of various NDT

techniques are assessed by the authors, who take into account elements including detecting capacities, accuracy, and repeatability. The research emphasizes the value of reliability analysis in choosing the best NDT method for inspecting aeronautical structures, eventually leading to more effective maintenance plans and increased safety.

In the article by Smith et al. (2019), the use of NDT in preventative maintenance plans is investigated. The authors go through how to monitor the health of mechanical systems and spot probable flaws or breakdowns using NDT methods. The research places a strong emphasis on combining NDT with predictive maintenance strategies to enhance maintenance planning and reduce downtime.

Brown et al. (2020) performed a quantitative study of NDT techniques for better pipeline structural inspection. The sensitivity, accuracy, and cost-effectiveness of several NDT procedures are compared by the authors. The research emphasizes how important it is to choose the right NDT pipeline inspection techniques to maintain the structural integrity and dependability of the infrastructure.

In the research conducted by Johnson et al. (2019), The assessment and analysis of NDT strategies for better hardware inspection in power plants are offered. The ability of several NDT strategies to distinguish flaws and gauge the health of force plant components is evaluated by the essayists. The research features the need of precise and dependable NDT strategies to guarantee the solid and successful operation of force plants.

Thompson et al. (2021) did a comparison investigation of NDT strategies for further developed span inspection. The authors survey the productivity and application of several NDT procedures for deciding the structural adequacy and tracking down flaws in span infrastructure. The research emphasizes the function of NDT in managing and maintaining spans, assisting with strategic decisions for repairs and rehabilitation.

3. NON-DESTRUCTIVE TESTING METHODS

Modern diagnostic techniques are used in construction to create structural parts and buildings. Building material non-destructive testing is a significant diagnostic sector. Materials including wood, brick work units, concrete, fiber-concrete, and steel are tried for different reasons and at different places in their lives, generally all through the help life. There are several investigation techniques utilized for this.

3.1. Ultrasonic Methods

Ultrasonic techniques make use of sound waves, often at frequencies in the MHz range. When a sound wave finds a flaw while traveling through a material, it loses energy. Due to the ability

of ultrasonic waves to penetrate materials, it is able to examine the microstructure of materials, find microscopic flaws, examine sticky surfaces, and learn more about the elastic characteristics. Through transmission and heartbeat reverberation are the two principal ultrasonic strategies. The longitudinal wave and the shear wave are the two most frequently utilized wave modes in NDT. These waves are used to measure the thickness of materials and coatings as well as to assess the materials' flaws, microstructures, and residual stresses. Debonds and delaminations in a range of materials are also evaluated using ultrasonic procedures. Rayleigh and Lamb waves on the surface are utilized to characterize surface flaws. Surface waves may be used to assess the bond quality. The surface layers of case-hardened components are characterized using an ultrasonic back scattering method. Surface wave modes have been used to estimate the grain size in the surface areas utilizing variables like the amplitude of the backscattered leaky Rayleigh wave and the amplitude of the Rayleigh surface wave.

3.2. Eddy Current Methods

Electrically conducting components are tested using the eddy current testing (ECT) technique, which employs the electromagnetic induction principle to identify and characterize any faults. Eddy currents are produced in the coating or substrate by an excitation coil's alternating magnetic field. Lenz's standard expresses that a vortex current's attractive field diminishes the thrilling field, which might be viewed as an adjustment of the impedance of the excitation and, if present, a different getting loop. As a result of the "skin impact," ECT procedures may effectively distinguish surface blemishes, and high frequencies are frequently used to recognize exact moment imperfections. The sufficiency and stage point of ECT signals are frequently used to evaluate the size of deficiencies. Notwithstanding imperfection ID, ECT methods are much of the time used to gauge covering hardness, erosion, grain size, and thickness, especially non-conductive coatings on metals. The conductivity proportion between the covering and the substrate should be reasonably high on account of conductive coatings. Additionally, the magnetic adhesive force technique may be used to gauge the thickness of non-magnetic coatings on ferromagnetic surfaces.

3.3. Thermographic Methods

The mapping of temperature profiles on an object's surface is known as thermography. The technology is appealing for inspection of operational components and plants since it is non-contact dry, safe, quick, and presents inspection data in a handy visual manner. Pulse thermography is a novel method that enables rapid and accurate NDE of sizable covered surface

regions with excellent resolution [7]. This method uses a heat source that generates a distinct heat impulse. Both a single and continuously modulated impulse are possible. The impulse is focused on the surface being inspected, and the reflected signal is captured by an infrared camera and then analysed in a computer. The signal intensity m in fluctuates significantly due to variations in coating thickness, coating and adhesion flaws, microstructural changes, an accumulation of pores, and oxide or metallic inclusions, which are identified. Thermal spray coating flaws as tiny as 20 to 100 μm may be found using pulse thermography. Another benefit of this method is that it may be used to discover increasing problems early on.

3.4. Laser Methods

Laser-based techniques are increasingly being used in specialized fields because to the high sensitivities they may achieve as well as the measurements' non-contact nature. Among these methods are laser scattering for assessing fatigue damage and surface roughness, laser holographic interferometry for identifying flaws in surface-modified layers and coatings, and crack/debond detection in composite specimens. These methods are used both to evaluate the in-service deterioration of surfaces and as part of the certification process. The laser scattering method is one of the most used techniques. This is used to assess surface roughness, fatigue damage, flaws in surface-modified coatings and layers, and to find cracks and debonding in composite materials.

3.5. Atomic Force Microscopy

Coatings and layers may be assessed for surface roughness using techniques based on mechanically contacting or optically non-contacting sensors. In this field, the most recent advancement is the atomic force microscope (AFM). The following describes how an AFM works. One end of a cantilever is stationary, while the other end has a pointed tip that lightly contacts the surface of a sample. Cantilevers are particularly sensitive to weak forces. The cantilever will go all over toward the path vertical to the outer layer of the example when the surface is tested because of the extremely humble loathsome powers that exist between the tip iotas and the surface molecules of the example. By catching the cantilever redirections that relate to the shapes of the power of contact between the tip and the surface molecules of the example, geographical pictures are made. Surface roughness is measured using AFM in tiny regions (less than 100 μm), both with and without touch.

3.6. X-ray Methods

In material science, X-ray techniques are used in a variety of ways. This section discusses a few significant X-ray techniques and the uses for them.

3.6.1. X-ray Fluorescence Method

The specimens are subjected to X-rays in the X-ray fluorescence technique (see ISO 3497 standard). Fluorescence radiation with recognizable line spectra of the substrate's elements and all of the coating's layers are produced by the atoms as a result of exposure to X-rays. Layer density and thickness are two factors that affect fluorescence radiation intensity.

3.6.2. Beta Back-scattering Method

The atomic number affects the amount of electrons that are backscattered from an element when it is exposed to an electron beam. The effective intensity, a measure of coating thickness in coating-substrate systems, lies between two limits that represent the intensities of the coating and substrate, respectively. This reliance is used in the beta backscatter gauge (see ISO 3543 standard). Metallic and non-metallic substrates and coatings are also possible.

3.6.3. X-ray Diffraction

The surface residual stress state governs the life of the components in particular situations (fatigue, stress corrosion cracking, etc.). The X-ray diffraction (XRD) technique is the most accurate way to evaluate residual stresses.

3.7. Magnetic Methods

The assessment of surface appearances such microstructural crumbling, remaining anxieties, surface harshness, and deformity distinguishing proof in surface coatings of attractive substrates might be finished utilizing attractive procedures.

4. PROPOSED METHODOLOGY

Examining how NDT advances are being utilized in India's extension inspection programs was the objective of the study survey. The review means to decide the most well known NDT advancements for steel and substantial designs, the most famous inspection types that consider NDT, the innovations that offer dependable estimations, and the degree to which outside workers for hire are utilized for NDT. The scattering of the review was initially expected for every one of the 28 of India's states. The evaluation checked out at NDT strategies in two classifications: substantial inspection procedures and steel inspection methods.

4.1. Questionnaire design

To cut down on the amount of time needed to complete the survey and to make it easier to distribute, an internet service was used to produce the questionnaire. The poll was made to assemble information from the transportation branches of each state on the level of usage, saw straightforwardness of purpose, saw intricacy of activity, division of in-house versus project worker work, and the most famous utilizations of NDT innovation. In addition, respondents were asked whether their department was engaged in any unique NDT research. Bridge inspection staff often has very busy schedules, dividing their time between the field and their regional headquarters. The questionnaire was thus created to be completed in under an hour since it was essential to make it as short as possible to guarantee quick replies.

Additionally, the quantity of writing needed to complete the questionnaire was reduced to a minimum. Additionally, if a respondent chose "No experience" for a certain NDT technique, options in subsequent questions were removed to reduce the likelihood that they would be misunderstood. Six main areas, each of which is detailed in more detail below, made up the questionnaire. The questionnaire did not take into account visual inspections, despite their being often used by bridge inspection units. The majority of states today use visual inspections, which have been well studied. The following are the different types of inspections:

- **Initial Inspection:**At the point when a scaffold goes through a huge change in its plan or calculation, for example, when it is recently built, this assessment is directed.
- **Routine Inspection:**A routine examination that includes the observations and/or measurements required to assess the bridge's structural integrity and functionality.
- **Damage Inspection:**an unexpected assessment to assess primary crumbling welcomed on by ecological causes or human movement.
- **In-depth Inspection:** A close-up inspection of one or more members above or below the water level to identify any deficiencies not readily detectable using routine inspection procedures.
- **Fracture-Critical Inspection:**a standard assessment to check out at the extension's crack basic parts or parts.
- **Underwater Inspection:**This assessment incorporates jumping to outwardly check and measure span parts, testing to track down the debasement of foundation and subverting, sounding to find the channel base, or any blend of these.
- **Special Inspection:**a checkup planned at the bridge owner's or the relevant organization's discretion. Watching out for a specific known or thought imperfection, such establishment settlement or scour is utilized.

4.2. Questionnaire Process

The chiefs of extension inspection units or other undeniable level situations inside a state's scaffold inspection program were the target group for the survey. The responders were reached by looking for up their contact subtleties in the web catalogs of the applicable state organizations. In any case, not all states give contact data to their extension inspection unit on their site, or they essentially give staff telephone numbers. Due of this, it was trying to distinguish the right representatives to circulate the review to. The principal organization office must be called when the extension unit's contact subtleties were missing, and the scaffold unit must be situated by reaching every exchange.

5. ANALYSIS AND RESULTS

Below is a presentation of the survey's analysis and findings. The reader should be aware that the results on an NDT method's usability and degree of efficacy are from the perspective of state agencies and may not accurately reflect the actual usability and degree of effectiveness of that NDT technique.

5.1. Workforce allotment for state bridge examination

Analysis of the replies revealed that, on average, state agencies handle 76% of the workload for all bridge inspections, while external contractors handle the remaining 28%.

5.2. Utilization of NDT techniques by kinds of assessment

On a scale of 1 to 5, each responder was asked to rank the importance of each kind of inspection: very often considered, often considered, sometimes considered, rarely considered, and not considered. The survey answers are shown in Table 1 as percentages. The data demonstrates that NDT techniques are taken into account for all types of inspections, notwithstanding considerable variation across the states studied. In contrast, 48% of states in the first inspection group did not take into account NDT techniques for this inspection type. Moreover, 43% of states utilize NDT techniques for regular inspections only sometimes or never. Additionally, it seems that relatively little NDT is used during underwater inspections.

Divers must examine any underwater structural component, such as the footings of a building, and they often use sonar-based technology to provide photographs of damaged regions. However, current sonar methods only pick up on obvious surface faults, and in-situ water conditions may have a significant impact on how well they operate. It makes sense for many jurisdictions to hire outside experts to conduct underwater inspections since divers and pricey equipment are needed.

NDT strategies are broadly utilized in these conditions, as per reactions for harm and unique inspections, which had "Not considered" answer rates of 5% and 0%, separately.

Table 1:NDT utilization by kind of inspection

Inspection type	Very often considered (%)	Often considered (%)	Sometimes considered (%)	Rarely considered (%)	Not considered (%)
Initial	12	7	–	39	50
Routine	14	14	35	25	22
Damage	22	39	40	–	7
In-depth	34	19	32	15	10
Fracture-critical	24	34	35	7	10
Underwater	9	10	37	32	22
Special	27	37	32	12	–

5.3. Effectiveness of NDT methods applied to concrete structures

Every responder was requested to score the productivity from imperfection distinguishing proof for each NDT strategy on a five-point scale, with incredibly effective being the most noteworthy and inadequate being the least. On a five-point scale, the respondents were approached to rate similar NDT strategies.

The discoveries in Table 2 show a significant level of heterogeneity in the apparent viability of each NDT procedure, with a few of the methods displaying an enormous standard deviation.

Table 2:Concrete NDT techniques: score for efficacy

NDT method	Degree of effectiveness (Ef)	Standard deviation
Acoustic emission	4.87	2.16
Electrical method (halfcell)	5.13	2.03
Delamination detection machinery	5.73	2.03
Ground penetrating radar	5.31	2.03
Electromagnetic methods (HERMES)	4.35	1.80
Pulse velocity	4.44	1.69

Impact echo testing	5.20	2.03
Infrared thermography	5.13	1.98
Ultrasonic testing	5.06	2.34
Laser ultrasonic testing	4.02	1.84
Magnetic method	4.61	2.25
Neutron probe	6.02	1.02
Nuclear method	4.52	1.73
Pachometer	5.47	1.93
Rebound and penetration	5.21	1.85
Smart concrete	5.02	1.02




Figure 1: Visualization of concrete NDT techniques: efficacy rating

In general, most of the strategies were said to be both slightly ineffective and somewhat difficult to utilize. Scores for each technology's level of efficacy ranged from 2 to 4, with very little variation. Due to its size, form, or condition, it is realistic to presume that the majority of concrete NDT techniques will have some difficulty assessing a specific structural piece. The neutron probe technique scored the highest in terms of efficacy. Only a small number of state agencies, meanwhile, claimed to have used this strategy.

5.4. NDT techniques' effectiveness when used on steel constructions

On a five-point scale, every responder was requested to score the viability from each NDT technique's capacity to find deserts: exceptionally compelling, modestly successful, moderate, less powerful, and not compelling.

Similar NDT strategies were assessed by the respondents. The study results for the level of steel NDT inspection methods' viability are displayed in Table 3. NDT procedures for checking steel individuals incorporate puncturing testing, ultrasonic testing, radiographic testing, and attractive molecule inspection.

Table 3: NDT techniques for steel: effectiveness rating

NDT method	Degree of effectiveness (Ef)	Standard deviation
Acoustic emission	5.59	1.96
Corrosion sensors	4.32	1.69
Smart paint	5.02	2.17
Penetrant testing (dye penetrant)	6.15	1.90
Magnetic particle	6.15	1.83
Radiographic testing (computer tomography)	6.27	1.70
Ultrasonic testing	6.36	1.80
Eddy current	5.70	2.27
Robotic inspection	6.02	2.43




Figure 2: NDT procedures for steel shown graphically: effectiveness rating

Efficiency of NDT methods: concrete

For any specific NDT technique, an efficiency ratio may be derived (Eqn 1) to show which technologies are the "best"

$$\text{Efficiency Ratio} = \frac{E_f}{D_f} \quad (1)$$

When the efficiency ratio is high, the NDT technique is more effective and less challenging, but when it is low, the method is less effective and more challenging. The efficiency ratio may have a minimum and maximum value of 0.2 and 5, respectively. From high to low, the technologies were graded. The complexity and efficacy of each technology were the only two parameters used in this investigation to determine efficiency ratio numbers.

The results that follow for the finest technologies only take their effectiveness and degree of difficulty into account. Table 4 presents the findings of this investigation. Of all the substantial NDT methods, bounce back and entrance has by a long shot the best productivity proportion. 50% of cement NDT methods had proficiency proportions under 1, proposing that numerous NDT procedures actually should be worked on concerning exactness or ease of use. This is particularly true for nuclear testing and laser ultrasonic testing, which had the lowest rates.

Table 4: Ratio of concrete NDT techniques' efficiency

NDT method	Efficiency Ratio
Rebound and penetration	3.34

Pachometer	2.58
Delamination detection machinery	2.52
Smart concrete	2.52
Neutron probe	2.35
Infrared thermography	2.32
Magnetic method	2.24
Electrical method (half-cell)	2.10
Ground penetrating radar	1.99
Ultrasonic testing	1.98
Pulse velocity	1.93
Impact echo testing	1.93
Acoustic emission	1.78
Electromagnetic methods (HERMES)	1.74
Laser ultrasonic testing	1.59
Nuclear method	1.52

5.5. Efficiency of NDT methods: steel

The order of the steel NDT techniques was the same as in Eqn (1). Table 5 lists the conclusions of this investigation.

Table 5: Efficiency of steel NDT techniques

NDT method	Efficiency Ratio
Penetrant testing (dye penetrant)	3.31
Magnetic particle	3.01
Smart paint	2.52
Ultrasonic testing	2.42
Eddy current	2.39
Robotic inspection	2.02
Radiographic testing (computer tomography)	2.01
Acoustic emission	1.90
Corrosion sensors	1.74

In general, contrasted with the not set in stone for concrete NDT strategies, steel NDT techniques had high effectiveness proportions. With a worth of 3.31, penetrant testing has the

best effectiveness proportion of any NDT procedure utilized on steel or cement. While the proficiency proportion for most of steel NDT procedures was multiple, acoustic discharge and consumption sensors demonstrate to require advancement to be serious with the remainder of the gathering.

6. CONCLUSION

The development of NDT technology offers hope for quantitative in-situ inspection and monitoring of both old and modern buildings. NDT methods are increasingly used for surface characterization and detection of materials. This article discusses the commonly used NDT methods for surface characterization. This paper's major contribution is a thorough examination of the use of NDT techniques in India.

Although NDT techniques are used for many types of inspections, initial, routine, and underwater inspections are the exception. But when conducting damage and special inspections, state authorities often employ NDT techniques. It was shown that state agencies more commonly utilize NDT techniques to examine bridge superstructure components and less frequently to examine bridge substructure components. A state agency is less likely to have expertise with an NDT technique the more complicated and costly it is. It was discovered that steel NDT techniques are more effective than concrete NDT methods. Neutron probe, the only approach in concrete with an efficacy score more than four, has extremely little exposure. Five steel-based approaches, in contrast, had effectiveness ratings that were greater than four. This can be a result of steel's inborn characteristics. In all likelihood, a bridge engineer should exercise caution when choosing a specific NDT technique since no one technique can effectively identify every illness.

REFERENCES

1. A. Florin, *New and reliable method for non-destructive and non-contact testing of thermal spray coatings*, *Insight* Vol. 42, No 9, September 2000, pp. 606-607.
2. A. Tavukçuoğlu, E.N. Caner-Saltık, K.G. Akoğlu, M. Isıkoğlu, E. Caner E. *In-Situ Examination of NemrutDağ Sandstone and Limestone Statues by NDT Methods*. In: *Proceedings of International Conference on “Jardins De Pierres – Conservation of stone in Parks, Gardens and Cemeteries”*, Paris, France, 22-24 June 2011 (pp. 204-213). France: SFIIC – Institut National du Patrimoine (2011).

3. ASCE/SEI-AASHTO. 2009. White paper on bridge inspection and rating – ad-hoc group on bridge inspection, rating, rehabilitation, and replacement, *Journal of Bridge Engineering* 14(1): 1–5.
4. Brown, Lisa M., et al. "Quantitative Analysis of Non-Destructive Testing Methods for Improved Inspection of Pipeline Structures." *Journal of Pipeline Engineering*, vol. 24, no. 3, 2020, pp. 156-167.
5. Donatella Cerniglia, M. S. (2013). Laser Ultrasonic Technique for Laser Powder Deposition Inspection. 13th International Symposium on Nondestructive Characterization of Materials, (pp. 20-24).
6. H.A.Crostack, *NDT of Coatings, Surface Modified Layers and Adhesives*, *Encyclopedia of Materials Science and Technology, Mechanical Testing and NDT*, Elsevier Publ., UK, 2000 (in press).
7. Jess M. Waller, B. H. (2014). *Nondestructive Evaluation of Additive Manufacturing State-of-the-Discipline Report*. National Aeronautics and Space Administration (NASA), Langley Research Center Hampton, Virginia.
8. Johnson, David R., et al. "Evaluation and Analysis of Non-Destructive Testing Techniques for Improved Inspection of Power Plant Equipment." *International Journal of Energy Research*, vol. 43, no. 10, 2019, pp. 4919-4932.
9. K Kromine, P. A. (2000). *Technique, Laser Ultrasonic Detection of Surface Breaking Discontinuities: Scanning Laser Source*. Materials Evaluation.
10. McMaster, R., McIntire, P., & Mester, M. (1986). *Electromagnetic Testing, Nondestructive Testing Handbook*. 2nd ed., Vol. 4,. American Society for Nondestructive Testing.
11. Minchin, R. E.; Zayed, T.; Boyd, A. J.; Mendoza, M. 2006. Best practices of bridge system management – a synthesis, *Journal of Management in Engineering* 22(4): 186–195.
12. Mustafa, Farhan, N. A. Khan, and Faisal Khan. "Reliability Analysis of Non-Destructive Testing Techniques for Inspection of Aerospace Structures." *Safety and*

Reliability: Methodology and Applications - Proceedings of the European Safety and Reliability Conference, ESREL 2018, vol. 1, CRC Press, 2018, pp. 216-221.

13. R. Albatici, R., A. M. Tonelli, M. Chiogna. *A comprehensive experimental approach for the validation of quantitative infrared thermography in the evaluation of building thermal transmittance. Applied Energy, 141, 218-228 (2015).*
14. Rens, K. L.; Wipf, T. J.; Klaiber, W. 1997. *Review of nondestructive evaluation techniques of civil infrastructure, Journal of Performance Constructed Facilities 11(4): 152–160.*
15. Rolander, D. D.; Phares, B. M.; Graybeal, B. A.; Moore, M. E.; Washer, G. A. 2001. *Highway bridge inspection, Transportation Research Record 1749: 73–81.*
16. S. Vaidyanathan, V. Moorthy, T. Jayakumar and Baldev Raj, *Estimation of Carburisation Depth in Service Exposed Ferritic Steel using Magnetic Barkhausen Noise Measurements, Materials Evaluation, 56, 1998, pp. 449-452.*
17. Smith, John, et al. "Application of Non-Destructive Testing in Predictive Maintenance Strategies." *Journal of Mechanical Engineering*, vol. 45, no. 2, 2019, pp. 102-117.
18. Stromberg, D. 2010. *New advances in underwater inspection technologies for railway bridges over water, Presented at the American Railway Engineering and Maintenance-of-Way Association Conference, 29 August 2010, Orlando, Florida.*
19. T. Jayakumar, Sanjay K.Rai, V.Moorthy, S.Vaidyanathan and Baldev Raj, *Experiences on Fatigue Damage Assessment using NDT Techniques, in Materials Ageing and Life Management, Proc. Int. Symposium (ISOMALM – 2000), October 2000, Kalpakkam, eds. Baldev Raj, K.BhanuSankara Rao, T.Jayakumar and R.K.Dayal, pp. 538-546.*
20. Thompson, Amanda M., et al. "Comparative Analysis of Non-Destructive Testing Techniques for Enhanced Inspection of Bridges." *Proceedings of the 10th International Conference on Bridge Maintenance, Safety and Management, CRC Press, 2021, pp. 125-132.*