Convertible Wheelchair-to-Bed Transfer System: BOM (at retail rates)

SL	Item	Part name	Subsystem	Material / specification	Dimensions (mm)	Process	Make / Buy	Qty	Unit mass (kg)	Total mass (kg)	Unit cost (INR)	Total cost (INR)	Source
1	1	Base frame weldment (40x40x2.6 SHS + tracks)	1 Scissor lift	MS IS 4923 YSt-310 SHS 40x40x2.6 + RHS 40x20x2	Weldment, overall 1040 x 700 x 95 (frame between 110 and 205 above floor): 2 side rails SHS 40x40x2.6 x 1040 (x -300..740, y ±310..350, top 200); 2 rear cross members SHS 40x40x2.6 x 620 (at x -280 and -180); 1 dropped front cross member SHS 40x40x2.6 x 620 (x 410-450, z 110-150); 2 roller tracks RHS 40x20x2 x 650 laid flat (x -200..450, y ±205..245, top 162); 2 pivot ears plate 40 x 43 x 5 with Ø25.5 hole at z 180 (x -110)	Cut, MIG weld, powder coat	Make	1	14.347	14.35	3,770	3,770	Local job work: retail material + labour, incl. GST
2	2	Caster 125 mm total-lock swivel (TPR wheel)	1 Scissor lift	Purchased: 125 mm total-lock swivel caster, TPR wheel	Wheel Ø125 x 32 wide (TPR), top plate 90 x 80 x 10, overall height 160, swivel offset 25; total-lock; 4 positions at (x -270 / 700, y ±345)	Bought out	Buy	4	1.600	6.40	1,250	5,000	Online listing (incl. GST)
3	3	Scissor arm - outer (50x25x2.6 RHS)	1 Scissor lift	MS IS 4923 YSt-310 RHS 50x25x2.6	RHS 50x25x2.6, pin c/c 550, overall length 590 (20 beyond each end pin); end holes Ø25.5 at 0 and 550 (shafts), centre hole Ø21 at 275 (pin 9); pair at y ±190.5	Cut, drill, weld bosses	Make	2	1.625	3.25	620	1,240	Local job work: retail material + labour, incl. GST
4	4	Scissor arm - inner (50x25x2.6 RHS)	1 Scissor lift	MS IS 4923 YSt-310 RHS 50x25x2.6	RHS 50x25x2.6, pin c/c 550, overall length 590 (20 beyond each end pin); end holes Ø25.5 at 0 and 550 (shafts), centre hole Ø21 at 275 (pin 9); pair at y ±162.5	Cut, drill, weld bosses	Make	2	1.625	3.25	620	1,240	Local job work: retail material + labour, incl. GST
5	5	Cross shaft - top sliding (Ø25x3) + roller stubs	1 Scissor lift	MS tube Ø25x3 (IS 1239) + EN8 end plugs with Ø15 stubs	Tube Ø25 x 3 wall x 424 (y -212..+212) + pressed end plugs with Ø15 x 26 roller stubs (y ±212..238); overall 476; carries 2 track rollers (item 10)	Cut, turn plugs, press-fit	Make	1	0.796	0.80	650	650	Local job work: retail material + labour, incl. GST
6	6	Cross shaft - top fixed (Ø25x3)	1 Scissor lift	MS tube Ø25x3 (IS 1239)	Tube Ø25 x 3 wall x 424 (y -212..+212)	Cut, face, drill	Make	1	0.690	0.69	280	280	Local job work: retail material + labour, incl. GST
7	7	Cross shaft - bottom fixed (Ø25x3)	1 Scissor lift	MS tube Ø25x3 (IS 1239)	Tube Ø25 x 3 wall x 424 (y -212..+212)	Cut, face, drill	Make	1	0.690	0.69	280	280	Local job work: retail material + labour, incl. GST
8	8	Cross shaft - bottom sliding (Ø25x3) + roller stubs	1 Scissor lift	MS tube Ø25x3 (IS 1239) + EN8 end plugs with Ø15 stubs	Tube Ø25 x 3 wall x 424 (y -212..+212) + pressed end plugs with Ø15 x 26 roller stubs (y ±212..238); overall 476; carries 2 track rollers (item 10)	Cut, turn plugs, press-fit	Make	1	0.796	0.80	650	650	Local job work: retail material + labour, incl. GST
9	9	Centre pin Ø20 + circlips	1 Scissor lift	EN8 (080M40) Ø20 + circlips	Pin Ø20 x 63 (y 145..208 each side), 2 circlip grooves for DIN 471 Ø20 circlips	Turn, groove	Make	2	0.155	0.31	200	400	Local job work: retail material + labour, incl. GST
10	10	Track roller = 2 x 6202-2RS bearings (Ø35 x 22)	1 Scissor lift	Purchased: 2 x 6202-2RS deep-groove bearings per roller	2 x 6202-2RS (Ø15 bore x Ø35 OD x 11) side by side = roller Ø35 x 22 on the Ø15 stub of shaft 5 / 8 (y ±214..236); outer races run on the track	Bought out	Buy	4	0.090	0.36	310	1,240	Online listing (incl. GST)
11	11	Lift top frame weldment (40x20x2 RHS)	1 Scissor lift	MS IS 4923 YSt-310 RHS 40x20x2 + SHS 20x20x2 cross members	Weldment, overall 630 x 640 x 53 (frame 20 deep + ears hanging 33 below): 2 tracks RHS 40x20x2 x 630 (x -150..480, y ±205..245, deck -180..-160); 2 cross members SHS 20x20x2 x 640 (at x -150..-130 and 460..480), each with a Ø21 hole for the lead screw (axis deck -170); 2 hanger ears plate 40 x 33 x 5 with Ø25.5 hole at deck -198 (x -110)	Cut, MIG weld, powder coat	Make	1	3.585	3.59	1,570	1,570	Local job work: retail material + labour, incl. GST
12	12	Lead screw Tr20x4 (single start, self-locking)	1 Scissor lift	EN8 / C45, Tr20x4 single start, thread cut on a lathe (or bought rolled)	Tr20x4 single start, Ø20 x 780 (x -305..475), axis at deck -170; Ø20 journal in the thrust block (x -185..-150), free end runs in the Ø21 hole of the front cross member	Turned + thread-cut - local	Make	1	1.600	1.60	1,280	1,280	Local job work: retail material + labour, incl. GST
13	13	Nut block Tr20x4 (LTB2 bronze nut)	1 Scissor lift	Phosphor bronze LTB2 nut in MS block with shaft lug	Overall 36 x 44 x 61: nut body 30 x 44 x 30 with Tr20x4 bronze nut (axis deck -170) + lug 36 x 32 x 31 below it with Ø25.5 bore round sliding shaft 5 (axis deck -198)	Turn + mill, bore	Make	1	0.389	0.39	1,380	1,380	Local job work: retail material + labour, incl. GST
14	14	Thrust bearing block (51104 + 6004)	1 Scissor lift	MS block + 51104 thrust + 6004 bearings	Block 35 x 60 x 40 (x -185..-150, deck -200..-160) + bearing housing Ø42 OD / Ø20 bore protruding 11 above (overall 35 x 60 x 51); holds 51104 thrust (20 x 35 x 10) + 6004 (20 x 42 x 12)	Mill, bore	Make	1	0.652	0.65	1,220	1,220	Local job work: retail material + labour, incl. GST
15	15	Folding crank handle R120	1 Scissor lift	MS 8 mm + nylon grip	Hub Ø40 x 10 on screw end; arm 120 long (radius) x 16 x 10; grip Ø22 x 35 nylon; folding hinge	Laser-cut, weld	Make	1	0.240	0.24	890	890	Local job work: retail material + labour, incl. GST
16	16	Seat side rail 40x20x2 RHS (Al)	Seat frame (common)	Al 6061-T6 RHS 40x20x2	Al RHS 40 (tall) x 20 x 2 wall x 517 (x -15..502); y ±300..320; deck -160..-120	Cut, drill	Make	2	0.313	0.63	450	900	Local job work: retail material + labour, incl. GST
17	17	Seat cheek plate 8 mm (guide-rail + rack carrier)	Seat frame (common)	Al 6061-T6 plate 8 mm	Al plate 8 x 584 x 118 (y -292..292, deck -120..-2); 2 per seat at x 12-20 and 440-448; front plate (x 440-448) has 2 slots 6 x 13 for rack pins (y -230 and +60, deck -41.5..-28.5); MGN15 rail bolted on inner face	Laser/waterjet cut, drill, tap	Make	2	1.487	2.97	1,670	3,340	Local job work: retail material + labour, incl. GST
18	18	Back pivot bracket 8 mm	Seat frame (common)	Al 6061-T6 plate 8 mm (2 detent holes on caregiver side)	Al plate 8 mm: bed side 75 x 157 envelope (x -15..60); caregiver side 110 x 157 (x -50..60); pivot hole Ø12 at (0, deck -16); caregiver side adds 2 detent holes Ø8.4 on R40 at -110° and -190°	Laser/waterjet cut, ream	Make	2	0.163	0.33	420	840	Local job work: retail material + labour, incl. GST
19	19	Leg pivot bracket 8 mm	Seat frame (common)	Al 6061-T6 plate 8 mm	Al plate 8 mm, 50 x 111 (x 452..502, deck -114..-3, y ±308..316), pivot hole Ø21 (hub bush) at (482, deck -16); welded foot 50 x 20 x 6 sitting on the seat-rail top (2 x M6)	Laser/waterjet cut, ream	Make	2	0.111	0.22	500	1,000	Local job work: retail material + labour, incl. GST
20	20	Linear guide rail MGN15 x 580	3 Sliding	Purchased: MGN15 rail, bearing steel, cut to 580	MGN15 rail 15 wide x 10 high x 580 long, M3 mounting holes at 40 pitch (bolted to item 17/31 at deck -88..-73)	Bought out	Buy	4	0.560	2.24	2,100	8,400	Online listing (incl. GST)
21	20A	Linear guide carriage MGN15H + 3 mm spacer	3 Sliding	Purchased: MGN15H carriage + 3 mm Al spacer	MGN15H carriage (catalogue 34 W x 61.4 L, rail + block height 16; CAD envelope 32 x 58) + Al spacer 50 x 24 x 3; 2 per end plate, centres y -258 / -145	Bought out	Buy	8	0.200	1.60	650	5,200	Online listing (incl. GST)
22	21	Rack m1 x 470 (16 face), drops 6 mm in FREE	4 Rolling	Acetal (POM) rack m1, 16 face	POM rack m1 x 470 long x 16 face width x 8 high (y -300..170, pitch line at deck -28.3 = 0.3 mm backlash); 2 Ø5 holes for guide pins 50 at y -230 / +60 (deck -32); drops 6 mm in FREE	Bought out, cut to 470	Buy	2	0.069	0.14	600	1,200	Estimate, Indian supplier (no reliable online listing)
23	22	Gas spring anchor bracket	Seat frame (common)	MS 5 mm clevis, zinc plated + Ø8 pin	Clevis, MS 5: 2 cheeks 30 x 21 x 5 (x 435..465, y -391..-386 and -364..-359, deck -167..-146) with Ø8 pin holes at (450, deck -152), 22 gap for the gas-spring eye; back/mounting plate 5 x 71 x 21 (x 465..470, y -391..-320) welded on, bolted to the seat-rail side face; pin Ø8 x 32	Laser-cut, weld, drill	Make	1	0.104	0.10	450	450	Local job work: retail material + labour, incl. GST
24	23	Armrest socket Ø24 tube	Seat frame (common)	MS tube Ø24 x 2.5 wall (bore 19 for the Ø18 armrest spigot)	Tube Ø24 x 2.5 wall x 100 (deck -160..-60), at x 100 / 360, y ±335	Cut, weld to rail	Make	4	0.133	0.53	160	640	Local job work: retail material + labour, incl. GST
25	24	Cassette board - seat (370 long, 18 mm Al ladder + PTFE skin)	3 Sliding	Al 6061-T6 18 mm ladder (25x16.5x1.5 ribs) + PTFE-glass skin	370 x 484 x 17.8 overall: Al skin 1.3 x 370 x 484 + PTFE-glass tape; 5 ribs RHS 25 x 16.5 x 1.5 x 370 at 110 pitch (y -220, -110, 0, 110, 220); top at deck -2.2	Cut, rivet, tape	Make	1	1.206	1.21	2,060	2,060	Local job work: retail material + labour, incl. GST
26	25	Cassette board - back (760 long, 18 mm Al ladder + PTFE skin)	3 Sliding	Al 6061-T6 18 mm ladder (25x16.5x1.5 ribs) + PTFE-glass skin	760 x 484 x 17.8 overall: Al skin 1.3 x 760 x 484 + PTFE-glass tape; 5 ribs RHS 25 x 16.5 x 1.5 x 760 at 110 pitch; top at deck -2.2	Cut, rivet, tape	Make	1	2.476	2.48	3,770	3,770	Local job work: retail material + labour, incl. GST

SL	Item	Part name	Subsystem	Material / specification	Dimensions (mm)	Process	Make / Buy	Qty	Unit mass (kg)	Total mass (kg)	Unit cost (INR)	Total cost (INR)	Source
27	26	Cassette end plate 6 mm (deep near end, 28 mm slim nose)	3 Sliding	Al 6061-T6 plate 6 mm (deep end + 28 mm slim nose)	Al plate 6 mm, 570 x 98 envelope: deep part 190 x 98 (y -290..-100, carries the carriages) + slim nose 380 x 28 (y -100..280, under the bed side); 2 bearing bores Ø16 for 688-2RS at y ±262, deck -14; bar bracket 58 bolted to its -Y end; edge bar 68 runs between the two brackets 58	Laser/waterjet cut, bore bearing seats	Make	4	0.468	1.87	880	3,520	Local job work: retail material + labour, incl. GST
28	27	Belt roller Ø24 x 366 + Ø8 stub axles (688-2RS)	4 Rolling	Al tube Ø24x1.5 + EN8 Ø8 stub axles + 688-2RS	Al tube Ø24 x 1.5 wall x 366; pressed end plugs Ø21 x 20 each end; EN8 stub axles Ø8 x 45 each end (27 beyond the tube end, overall 420); runs in 2 x 688-2RS bearings (item 27A) in the Ø16 bores of end plates 26 - tube and axles turn together; axis at deck -14	Turn, press-fit	Make	2	0.149	0.30	570	1,140	Local job work: retail material + labour, incl. GST
29	27	Belt roller Ø24 x 756 + Ø8 stub axles (688-2RS)	4 Rolling	Al tube Ø24x1.5 + EN8 Ø8 stub axles + 688-2RS	Al tube Ø24 x 1.5 wall x 756; pressed end plugs Ø21 x 20 each end; EN8 stub axles Ø8 x 45 each end (27 beyond the tube end, overall 810); runs in 2 x 688-2RS bearings (item 27A) in the Ø16 bores of end plates 26 - tube and axles turn together; axis at deck -14	Turn, press-fit	Make	2	0.261	0.52	640	1,280	Local job work: retail material + labour, incl. GST
30	27A	Ball bearing 688-2RS (8 x 16 x 5) for belt rollers 27	4 Rolling	Purchased: 688-2RS deep-groove ball bearing, sealed both sides	688-2RS: bore 8, OD 16, width 5, rubber seals both sides; 2 per roller (one each end), seated in the Ø16 bores of end plates 26; 4 rollers = 8 bearings	Bought out	Buy	8	0.003	0.02	80	640	Online listing (incl. GST)
31	28	Conveyor belt back, endless, 2 mm PU/polyester	4 Rolling	PU-covered polyester, 2 mm, endless splice	Endless belt, width 756, thickness 2, loop length ≈ 1130 on the mean line (2 x 524 straight + π x 26); roller c/c 524 (y ±262)	Bought out	Buy	1	2.050	2.05	5,000	5,000	Estimate, Indian supplier (no reliable online listing)
32	28	Conveyor belt seat, endless, 2 mm PU/polyester	4 Rolling	PU-covered polyester, 2 mm, endless splice	Endless belt, width 366, thickness 2, loop length ≈ 1130 on the mean line (2 x 524 straight + π x 26); roller c/c 524 (y ±262)	Bought out	Buy	1	0.992	0.99	4,000	4,000	Estimate, Indian supplier (no reliable online listing)
33	29	Pinion m1 z28, 16 face, keyed to roller	4 Rolling	Acetal (POM) m1 z28, 16 face	POM spur gear m1, z28, PCD 28, OD 30, face 16, bore Ø8 + grub screw on the Ø8 roller stub; on the near roller at the rack end, outside the end plate	Bought out, bore Dia8 + grub screw	Buy	2	0.012	0.02	350	700	Estimate, Indian supplier (no reliable online listing)
34	30	Back side rail 40x20x3 RHS (Al)	2 Chair-to-flat	Al 6061-T6 RHS 40x20x3	Al RHS 40 (tall) x 20 x 3 wall x 818 (x -838..-20 in flat mode); y ±300..320; caregiver side: release cable inside, Ø8 exit hole at x -100 (deck -140)	Cut, drill	Make	2	0.715	1.43	720	1,440	Local job work: retail material + labour, incl. GST
35	31	Back cheek plate 8 mm	2 Chair-to-flat	Al 6061-T6 plate 8 mm	Al plate 8 x 584 x 118 (y -292..292, deck -120..-2); 2 per back section at x -20..-12 and -838..-830 (flat); head-end plate has 2 rack-pin slots 6 x 13 (y -230, +60); MGN15 rail bolted on inner face	Laser/waterjet cut	Make	2	1.487	2.97	1,670	3,340	Local job work: retail material + labour, incl. GST
36	32	Back pivot plate 8 mm + spacer	2 Chair-to-flat	Al 6061-T6 plate 8 mm + spacer	Al plate 8 mm, 103 x 157 envelope (x -90..13, y ±330..338), pivot hole Ø12 at (0, deck -16); caregiver-side plate adds an M16x1.5 tapped hole for detent 57 on R40 at -110°; spacer block 60 x 10 x 38 to the rail	Laser/waterjet cut	Make	2	0.224	0.45	680	1,360	Local job work: retail material + labour, incl. GST
37	33	Back bell-crank R110 (tie-rod + gas-spring pins)	2 Chair-to-flat	MS plate 8 mm + EN8 hub	MS plate 8: two arms 30 wide x 140 long (R110 c/c + 15 each end) at -50° and -70° (flat mode); hub Ø24 x 12 bored Ø12 + key; 3 holes Ø12	Laser-cut, weld, ream	Make	1	0.409	0.41	790	790	Local job work: retail material + labour, incl. GST
38	34	Push handle U-bar Ø25 (transport)	2 Chair-to-flat	MS tube Ø25, powder coat	Bent tube Ø25: 2 uprights x 140 (deck -160..-300) at y ±310 + cross bar x 670 (y -335..335) at x -420	Bend, weld	Make	1	1.080	1.08	510	510	Local job work: retail material + labour, incl. GST
39	35	Leg pad 15 mm (Al honeycomb panel, PTFE vinyl top)	2 Chair-to-flat	Al honeycomb 15 mm panel + PTFE vinyl	Al honeycomb panel 420 x 460 x 15 (x 492..912), PTFE vinyl top	Bought out, cut	Buy	1	0.782	0.78	1,350	1,350	Estimate, Indian supplier (no reliable online listing)
40	36	Leg side tube 20x20x1.5 (Al)	2 Chair-to-flat	Al 6061-T6 SHS 20x20x1.5	Al SHS 20 x 20 x 1.5 x 415 (x 497..912), y ±210..230	Cut, drill	Make	2	0.124	0.25	210	420	Local job work: retail material + labour, incl. GST
41	37	Leg pivot plate 8 mm + hinge connector	2 Chair-to-flat	Al 6061-T6 plate 8 mm + hinge connector	Al plate 8 mm, 63 x 32 envelope with pivot hole Ø12 at (482, deck -16) + connector block 30 x 70 x 20 to the leg tube	Laser/waterjet cut	Make	2	0.140	0.28	480	960	Local job work: retail material + labour, incl. GST
42	38	Leg crank arm R110 (keyed to pivot)	2 Chair-to-flat	MS plate 8 mm + EN8 hub	MS plate 8: arm 30 wide x 140 long (R110 c/c + 15 each end) at -50° (flat) + hub Ø20 x 42 bored Ø12 + key on the leg pivot pin; tip hole Ø12	Laser-cut, weld, ream	Make	1	0.303	0.30	690	690	Local job work: retail material + labour, incl. GST
43	39	Flip footplate (folds down in flat mode)	2 Chair-to-flat	Al 6061 sheet 6 mm + grip tape	Al plate 6 mm: 400 wide x 165 high footplate + 20 x 400 x 5 toe lip, grip tape; hinge axis at x 915, deck -18 (folds under the leg pad in flat mode)	Cut, bend	Make	1	1.177	1.18	1,540	1,540	Local job work: retail material + labour, incl. GST
44	40	Bridge flap 130 mm, folds over pad (bed side)	2 Chair-to-flat	UHMW-PE 5 mm	UHMW-PE 5 x 390 x 130 (x 510..900); hinged, folds over the leg pad	Cut, hinge	Make	1	0.238	0.24	670	670	Local job work: retail material + labour, incl. GST
45	41	Tie rod 25x8 flat, c/c 482 (parallelogram link)	2 Chair-to-flat	MS flat 25x8	MS flat 25 x 8, c/c 482, overall 512 (15 beyond each hole); 2 holes Ø12	Cut, drill, ream	Make	1	0.790	0.79	350	350	Local job work: retail material + labour, incl. GST
46	42	Lockable gas spring 1200 N, stroke 150, ext. length 560 (Bloc-O-Lift type)	2 Chair-to-flat	Purchased: lockable gas spring 1200 N, stroke 150	Lockable gas spring: body Ø22 x 290, rod Ø10, extended length 560 eye-to-eye, stroke 150 (works 414-551), F1 = 1200 N; eye ends Ø20 x 22, bores Ø8 (anchor end) and Ø12 (crank end)	Bought out	Buy	1	0.750	0.75	3,500	3,500	Indian online listing (incl. GST)
47	43	Linkage pins Ø12 (crank tips)	2 Chair-to-flat	EN8 / SS304 shoulder bolts Ø12	Ø12 pins: 2 x Ø12 x 24 (tie-rod ends) + 1 x Ø12 x 48 (gas-spring eye); circlip grooves both ends	Bought out / turn	Buy	3	0.028	0.09	140	420	Local job work: retail material + labour, incl. GST
48	43	Pivot pin Ø12 (back), shoulder bolt	2 Chair-to-flat	EN8 / SS304 shoulder bolts Ø12	Ø12 x 700 shoulder bolt / through-pin (y -350..+350), at back pivot (x 0, deck -16)	Bought out / turn	Buy	1	0.622	0.62	320	320	Local job work: retail material + labour, incl. GST
49	43	Pivot pin Ø12 (leg), shoulder bolt	2 Chair-to-flat	EN8 / SS304 shoulder bolts Ø12	Ø12 x 700 shoulder bolt / through-pin (y -350..+350), at leg pivot (x 482, deck -16)	Bought out / turn	Buy	1	0.622	0.62	320	320	Local job work: retail material + labour, incl. GST
50	44	Transfer bar half, Ø30 x 675 (fitted, joined by spigot)	3 Sliding	Al 6061-T6 tube Ø30x3 + spigot	Al tube Ø30 x 3 wall x 675 (each half); spigot Ø24 x 60 joins the halves; total fitted length 1350	Cut, turn spigot	Make	2	0.464	0.93	560	1,120	Local job work: retail material + labour, incl. GST
51	45	Swing-reach dock arm 25x25 SHS, L90, M10 lock lever (any angle sets reach 0-80 mm)	5 Safety & anchoring	MS SHS 25x25x2 (standard) arm L90 + EN8 pivot & knuckle pins + M10 lock lever	SHS 25 x 25 x 2 arm, pivot-to-knuckle 90 (deck -136..-112), pivot at x 200 / 460, y 346; pivot pin Ø20 x 93 (deck -205..-112); knuckle pin Ø16 x 168 (deck -112..-280) with 5 cross-holes at 25 pitch for the sleeve; 22 mm tail behind the pivot carrying an M10 lock screw at 16 mm, bearing on the friction disc, with lever 40 x 8 x 4; buy standard SHS 25 x 25 x 2 (the CAD tube is 24 tall, leaving 1 mm above the knuckle sleeve)	Cut, weld, turn, cross-drill	Make	2	0.699	1.40	870	1,740	Local job work: retail material + labour, incl. GST
52	46	Removable armrest (drop-in pins)	5 Safety & anchoring	MS tube Ø22 + Ø18 spigots + PU pad	2 uprights tube Ø22 x 1.6 x 269 (deck -60..209) with Ø18 x 90 drop-in spigots into sockets 23; top tube Ø25.4 x 1.6 x 300 at deck 220; PU pad 280 x 60 x 20; top at deck 252	Bend, weld, turn, mould pad	Make	2	1.270	2.54	1,170	2,340	Local job work: retail material + labour, incl. GST
53	47	Knee filler strip, PTFE faced	Seat frame (common)	UHMW-PE 6 mm, PTFE faced	UHMW-PE 30 x 560 x 6 (x 448..478), PTFE faced	Cut	Make	1	0.095	0.09	410	410	Local job work: retail material + labour, incl. GST
54	48	Transit-lock index plunger, pin Ø8, M16x1.5 body (GN 617.1 type)	5 Safety & anchoring	Purchased: indexing plunger GN 617.1 type, Ø8 hardened steel pin, M16x1.5 body (stainless -NI version optional)	GN 617.1-type indexing plunger with rest position: pin Ø8, body M16x1.5 x 22, knob Ø21 x 10; screwed into lock post 69, pin points along -X (across the slide) into the Ø8.5 hole of edge-bar lug 68, engaged 10 mm, stroke 12; pull + quarter turn holds it out; axis y -333, deck -21; seat at x 222..254, back at x -478..-446 (flat)	Bought out	Buy	2	0.080	0.16	1,000	2,000	Indian online listing (incl. GST)
55	49	Head-end grip bar Ø25 (recline grip + recline release lever)	2 Chair-to-flat	MS tube Ø25, powder coat	Tube Ø25 x 500 (y -250..250) + 2 brackets 49 x 20 x 20; lever 67 clamped at y -228	Bend, weld	Make	1	0.810	0.81	460	460	Local job work: retail material + labour, incl. GST

SL	Item	Part name	Subsystem	Material / specification	Dimensions (mm)	Process	Make / Buy	Qty	Unit mass (kg)	Total mass (kg)	Unit cost (INR)	Total cost (INR)	Source
56	50	Rack guide pin Ø5 (2 per rack, run in cheek slots)	4 Rolling	EN8 / SS304 Ø5 pins	Pin Ø5 x 32 (EN8 / SS304); 2 per rack, 2 racks = 4 pins	Turn	Make	4	0.005	0.02	70	280	Local job work: retail material + labour, incl. GST
57	51	Cam slider bar 3.5 mm, 2 inclined slots	4 Rolling	MS plate 3.5 mm, zinc plated, 2 inclined slots	MS plate 3.5 x 458 x 26 (y -318..140), 2 inclined slots Ø6 wide, 22 long x 6 drop (at y -230 and +60)	Laser-cut	Make	2	0.318	0.64	230	460	Local job work: retail material + labour, incl. GST
58	52	Slider keeper (2 per slider, riveted to cheek)	4 Rolling	MS strip 2 mm	MS strip 2 mm bent U-channel 9 deep x 34 high x 16 wide; 2 per slider, 2 sliders = 4 keepers, riveted	Bend, rivet	Make	4	0.025	0.10	80	320	Local job work: retail material + labour, incl. GST
59	53	Mode T-handle: push = CONVEY, pull = FREE	4 Rolling	Nylon over MS	Stem 3.5 x 8 x 17 on the slider end (y -318..-310) + grip bar 8 x 20 x 12 along Y (y -328..-308, deck -14..-2); pull 22 mm = FREE	Moulded / bought	Make	2	0.017	0.03	150	300	Local job work: retail material + labour, incl. GST
60	54	Bar storage clip (spring steel)	5 Safety & anchoring	Spring steel 1.5 mm	Spring steel 1.5 strip 20 wide, clip envelope 43 deep x 68 high, 2 per back section at x -250 / -650	Laser-cut, bend, harden	Make	2	0.050	0.10	130	260	Local job work: retail material + labour, incl. GST
61	55	Caster total-lock brake pedal (part of caster)	5 Safety & anchoring	Purchased (part of caster)	Pedal 36 x 18 x 8 + tab 14 x 24 x 4 (envelope 36 x 24 x 12) on the caster (included with item 2)	-	Buy	4	0.000	0.00	0	0	Included with caster
62	56	Clamp T-screw M12 + swivel pad	5 Safety & anchoring	MS / SS304 M12 T-screw + swivel pad	M12 T-screw, shank 45 + swivel pad Ø20 x 5, tommy bar Ø8 x 56 near the lower end; runs in the M12 hole of lower jaw 64	Bought out	Buy	2	0.070	0.14	350	700	Standard clamp screw, Indian supplier (incl. GST)
63	57	Recline detent plunger Ø8 pin (locks at 0 and 80 deg)	5 Safety & anchoring	Purchased: indexing plunger GN 617 type, Ø8 hardened steel pin, M16x1.5 body (stainless -NI version optional)	GN 617-type: pin Ø8, body M16x1.5 x 22 in plate 32, knob Ø20 x 8; R40 at -110° from the back pivot; stroke 12	Bought out	Buy	1	0.080	0.08	1,000	1,000	Online listing (incl. GST)
64	58	Bar clip-on bracket (on end-plate tab)	3 Sliding	Al 6061-T6 bracket	Al plate 6 mm: tab 28 x 38 + hook 12 x 32 with R15 seat for the bar, bolted to the -Y end of each end plate (y -318..-290); edge bar 68 bolts to its inner face	Laser-cut, bend	Make	4	0.021	0.08	100	400	Local job work: retail material + labour, incl. GST
65	59	Dock-arm pivot lug + friction disc, bolted to seat rail	5 Safety & anchoring	MS 6 mm lug + friction disc, bolted to Al seat rail (2 x M6 + backing strip)	Block 20 x 26 x 12 (y 320..346) + boss Ø32 x 12 (bore Ø20.6) + bolt tab 20 x 6 x 25 (2 x Ø6.4 for M6 through-bolts); friction disc Ø60 x 4 (flat at y 364) for the arm lock screw	Laser-cut, weld lug/disc, drill	Make	2	0.117	0.23	450	900	Local job work: retail material + labour, incl. GST
66	60	Upper jaw, sliding on F-bar, index pin (15 mm steps)	5 Safety & anchoring	MS 8 mm sliding upper jaw + spring index pin	C-collar 32 x 16 x 20 (inner 25 x 11, open toward the knuckle) + tongue 24 x 26 x 8 with M10 tapped hole for pressure screw 66; spring index pin Ø6 x 34.5 + knob Ø12 x 2.5	Laser-cut, weld	Make	2	0.075	0.15	430	860	Local job work: retail material + labour, incl. GST
67	62	Clamp F-bar 24x10 + knuckle sleeve (swivels; UP/DOWN on knuckle pin)	5 Safety & anchoring	MS flat 24x10 F-bar (15 mm holes) + knuckle sleeve tube	Flat bar 24 x 10 x 195 with 12 holes Ø6.4 at 15 pitch (first 8 below the top); knuckle sleeve tube Ø28 x 5.5 wall x 40 (bore 17) + web 20 x 6 x 40; sleeve top at deck -136 / -161 / -186 / -211 / -236	Cut, drill, weld	Make	2	0.425	0.85	520	1,040	Local job work: retail material + labour, incl. GST
68	64	Lower jaw, sliding on F-bar, index pin (15 mm steps)	5 Safety & anchoring	MS 10 mm sliding lower jaw + spring index pin	C-collar 32 x 16 x 20 (inner 25 x 11) + tongue 24 x 26 x 10 with M12 tapped hole for T-screw 56; spring index pin Ø6 x 34.5 + knob Ø12 x 2.5	Laser-cut, weld	Make	2	0.081	0.16	450	900	Local job work: retail material + labour, incl. GST
69	65	Recline 0 deg hard-stop plug (back-rail end)	2 Chair-to-flat	Al 6061-T6 plug, head 5 x 20 x 40 + spigot	Head 5 x 20 x 40 (x -20..-15, y ±300..320, deck -160..-120) + spigot 20 x 14 x 34 into the rail end; 1 x M5 rivet	Saw, mill, press-fit + 1 x M5 rivet	Make	2	0.036	0.07	220	440	Local job work: retail material + labour, incl. GST
70	66	Upper-jaw pressure screw M10 + pad (closes the gap onto the frame top)	5 Safety & anchoring	MS / SS304 M10 pressure screw + pad	M10 pressure screw: pad Ø16 x 4 + shank Ø10 x 26 + head Ø16 x 6 (32 above the pad); closes the 4-18 mm gap between upper jaw 60 and the frame top	Bought out	Buy	2	0.032	0.06	200	400	Standard clamp screw, Indian supplier (incl. GST)
71	67	Gas-spring remote release kit: lever on grip 49 + Bowden cable + release head	5 Safety & anchoring	Purchased: gas-spring remote release kit (lever + Bowden cable + release head)	Kit: squeeze lever on grip 49 (clamp ring Ø34 x 12 at y -228..-216, hinge block 12 x 14 x 21, blade 90 x 12 x 6, turns 8°); Bowden cable Ø5 x 1250 (lever -> open head end of the caregiver-side back rail 30 -> inside the rail -> Ø8 exit hole at x -100 -> free loop in the plane y -392 -> head); release head Ø18 x 30 screwed on the gas-spring rod end, presses the rod's release pin	Bought out	Buy	1	0.200	0.20	1,500	1,500	Estimate, Indian supplier (no reliable online listing)
72	68	Transit-lock edge bar + lug, back cassette	5 Safety & anchoring	Al 6061-T6 flat 22x12 + lug block	Al flat 22 (high) x 12 x 760 (x -805..-45 flat, y -318..-306, deck -32..-10) bolted between the two end-plate tabs + lug block 20 x 25 x 22 at x -500..-480 (y -343..-318) with Ø8.5 hole along X at (y -333, deck -21)	Cut, mill, drill	Make	1	0.568	0.57	710	710	Local job work: retail material + labour, incl. GST
73	68	Transit-lock edge bar + lug, seat cassette	5 Safety & anchoring	Al 6061-T6 flat 22x12 + lug block	Al flat 22 (high) x 12 x 370 (x 45..415, y -318..-306, deck -32..-10) bolted between the two end-plate tabs + lug block 20 x 25 x 22 at x 200..220 (y -343..-318) with Ø8.5 hole along X at (y -333, deck -21)	Cut, mill, drill	Make	1	0.290	0.29	520	520	Local job work: retail material + labour, incl. GST
74	69	Transit-lock post (on side rail, with home-stop lip)	5 Safety & anchoring	Al 6061-T6 block	Al block: head 16 x 35 x 30 (y -355..-320, deck -36..-6) with M16x1.5 tapped hole along X at (y -333, deck -21) + leg 16 x 10 x 124 (deck -160..-36) bolted to the side-rail outer face (2 x M6) + home-stop lip 22 x 2 x 30 (y -347..-345, 2 mm in front of the lug); seat post at x 222..238 on rail 16, back post at x -478..-462 on rail 30 (flat)	Mill, drill, tap M16x1.5	Make	2	0.094	0.19	480	960	Local job work: retail material + labour, incl. GST
75	C	Fasteners (SS/zinc), circlips, bushes, PTFE tape, paint, Loctite	All	Fasteners SS/zinc, circlips, bushes, PTFE tape, paint, Loctite	Kit: M5-M12 SS/zinc fasteners, DIN 471/472 circlips, PTFE tape 0.13 x 25, paint, Loctite 243	-	Buy	1	1.500	1.50	2,700	2,700	Estimate, Indian supplier (no reliable online listing)
		TOTAL						**149**		**79.2**		**105,870**	

We used AI to find the mass of the parts and also to estimate the price of some parts which we could not find