NIRMA UNIVERSITY • INSTITUTE OF TECHNOLOGY
Department of Computer Science & Engineering • Master of Computer Applications (MCA)

6CS102CC26 - DATA STRUCTURES INNOVATIVE ASSIGNMENT – 1

BloodLink: Hospital Transfusion Network & Algorithmic Blood Requisition System

STUDENT CANDIDATE

SHREY PATEL

Roll Number: 26MCA042 • Master of Computer Applications (MCA - Semester I)

ACADEMIC GUIDANCE & EVALUATION

Prof. NIRAV PATEL

Assistant Professor • 6CS102CC26 - Data Structures

PROBLEM CONTEXT & REGIONAL CHALLENGES

Overcoming Regional Blood Cold-Chain Perishability & Allocation Delays

Resolving life-critical logistical bottlenecks across Gujarat's 34 districts through deterministic data structures.

Critical Cold-Chain Challenges · CHALLENGES

- **Strict Biological Shelf Lives:** Platelets degrade in 5 days; Whole Blood in 35-42 days; cryogenic sub-zero storage needed.
- **Regional Supply Disparities:** Severe supply-demand imbalances between urban hubs (Ahmedabad, Surat) and remote districts (Kutch, Dang).
- **High-Latency Linear Searches:** Manual donor phone calls and linear database table scanning waste critical resuscitation minutes.
- **Cold-Storage Information Silos:** Hospitals lack real-time visibility into neighboring blood bank reserves, causing avoidable shortages.
- **Race Conditions Under Strain:** Simultaneous multi-casualty emergency requisitions overwhelm unbuffered dispatch systems.

BloodLink Computational Solution · OUR SOLUTION

- **In-Memory 3D Static Matrix:** Pre-allocated array matrix providing O(1) constant-time voluntary donor pool access by [City][BloodGroup].
- **Binary Max-Heap Priority Queue:** Algorithmic multi-factor donor ranking ensuring the top-matched standby voluntary donor is found in O(1) time.
- **FIFO Triage Queue Broker:** Socket.io real-time queue buffer assigning atomic token IDs and eliminating concurrency race conditions.
- **Separate Chaining Hash Table:** Client-side polynomial rolling hash indexing 316+ Gujarat cities for instant O(1) autocomplete search.
- **Sub-Second Triage Dispatch:** End-to-end requisition-to-dispatch latency under 150ms with zero database scanning overhead.

SYSTEM DESIGN & MODULARITY

Integrated Multi-Data-Structure Pipeline Architecture

End-to-end integration of 4 specialized data structures delivering deterministic sub-second emergency response.

Client & Intake Tier · CLIENT TIER

- **Separate Chaining Hash Table:** Indexes 316+ Gujarat cities into 128 hash buckets for instant O(1) prefix search.
- **Requester Clinical Console:** Captures patient ICU ward, blood group, units needed, and GPS coordinates with zero lag.
- **Donor Onboarding Registry:** Direct clinical pre-screening validating donor age, weight, and 90-day whole blood interval.
- **Direct Point-to-Point Map:** Leaflet mapping showing direct incident-to-depot spatial connection and distance.

Triage & Queue Tier · TRIAGE TIER

- **FIFO Request Queue Broker:** Linear queue structure buffering incoming WebSocket requisitions in fair arrival order.
- **Atomic Token Generation:** Assigns unique token (e.g. TOKEN-1603-512) for life-critical transaction traceability.
- **Concurrency & Race Guard:** Processes simultaneous requisitions sequentially with zero request drops or duplicate allocations.
- **Targeted WebSocket Push:** Emits dispatch results directly to requesting client socket upon triage completion.

Matching & Storage Tier · MATCHING TIER

- **3D Matrix Allocator:** Jumps in O(1) time directly to the target [City][BloodGroup] Max-Heap leaf cell.
- **Binary Max-Heap Priority:** Extracts top 3 voluntary standby donors based on exact/compatible serology and eligibility.
- **Localized Heap Re-Gen:** update_city_blood_group_heap() updates only the affected leaf without touching other cities.
- **MySQL 8.0 Persistence:** Persists donor profiles and depot stocks while in-memory structures handle real-time dispatch.

In-Memory 3D Static Matrix Indexing [City][BloodGroup][MaxHeap]

Multi-dimensional orthogonal matrix mapping Gujarat regional donor pools with strict O(1) constant-time direct access.




Figure 1: Voluntary Donor Registration Portal — Demographics and serological profiles populate 3D matrix cells.

Matrix Topology & Algorithmic Invariants · 3D MATRIX CORE

- **3-Dimensional Coordinate Mapping:** Dimension 1: City (e.g., Ahmedabad), Dimension 2: Blood Group (e.g., O+), Dimension 3: MaxHeap instance.
- **Strict O(1) Cell Indexing:** this.donors[city][bg] resolves in pure constant time without scanning full donor database tables.
- **Integrated Max-Heap Leaves:** Every leaf cell in the matrix contains an active Binary Max-Heap ranking that specific donor pool.
- **Localized Heap Update Function:** update_city_blood_group_heap(city, bg) refreshes only the targeted cell, leaving all other cities untouched.
- **Memory & Cache Locality:** Pre-allocated matrix resides permanently in heap with zero garbage collection churn or pointer chasing.

Binary Max-Heap Priority Queue & Multi-Factor Donor Scoring

Complete binary tree ranking voluntary donors to guarantee optimal match extraction in O(log N) time and O(1) root inspection.

Binary Tree Math & Priority Formulation · MATHEMATICAL MODEL

- **Flat Array Binary Tree Math:** Parent: floor((i - 1) / 2) | Left Child: 2i + 1 | Right Child: 2i + 2. Contiguous array storage with zero pointer overhead.
- **Heap Invariant Property:** For every node i > 0: heap[parent(i)].priority >= heap[i].priority. Highest priority donor is always at index 0.
- **Exact Match Priority (+100 pts):** Assigned when donor blood group exactly matches patient requisition (e.g., A+ to A+).
- **Compatible Serology (+60 pts):** Assigned for safe cross-match donor groups (e.g., O- universal RBC donor to A+ recipient).
- **First-Time & Age Bonus (+40 pts):** First-time donors receive +20 pts; donors close to ideal age (25 yrs) receive up to +20 pts.

Heap Operations & Clinical Allocation · ALGORITHMIC OPERATIONS

- **O(log N) Bubble-Up Insertion:** insert(donor) appends to end of array and bubbles up by comparing parent priorities until invariant holds.
- **O(log N) Sink-Down Max Extraction:** extractMax() swaps root with last element, pops, and sifts down to restore complete binary tree structure.
- **O(1) Root Inspection (peek):** Returns highest-ranking voluntary donor instantly without mutating tree state.
- **Non-Destructive Top-3 Extraction:** getTopK(3) extracts top candidates for dispatch while preserving the persistent Max-Heap intact.
- **Unit Test Suite Verification:** 100% verified in test_max_heap.js and test_3d_max_heap.js with exact serological score validation.

Linear FIFO Request Queue & Real-Time WebSocket Triage Broker

Asynchronous First-In-First-Out queue buffering emergency ICU requisitions with atomic token generation and zero request loss.




Figure 2: Requester Triage Console — Emergency requisition intake broadcasting to WebSocket queue broker.

Queue Mechanics & Concurrency Safety · FIFO QUEUE CORE

- **Strict FIFO Operational Discipline:** enqueue(item) appends to tail; dequeue() extracts from head. Guarantees fair arrival-order triage processing.
- **Atomic Token Generation:** Generates unique tokens (e.g., TOKEN-1603-512) providing instant requisition auditability and patient tracking.
- **Socket.io WebSocket Ingestion:** Real-time socket.on('send_request') ingests incoming payloads with sub-2ms acknowledgment latency.
- **Race Condition Elimination:** Serializes concurrent hospital requisitions, preventing double-allocation of scarce blood reserves.
- **Targeted Client Emission:** Emits matching results directly to requesting client via io.to(socketId).emit('send_result') without broadcast leaks.

DATA STRUCTURE 4 OF 4: HASH TABLE

Client-Side Hash Table with Separate Chaining & Polynomial Hash

In-memory hash table indexing 316+ Gujarat cities by prefix keys for instant O(1) autocomplete suggestions with zero server latency.

Polynomial Rolling Hash & Chaining Model · HASH MATHEMATICS

- **Polynomial Rolling Hash (Base 31):** H(s) = sum(s[i] * 31^(n - 1 - i)) mod 128. Multiplies by prime base 31 to uniformly distribute alphabetical city prefixes.
- **Fixed 128-Bucket Architecture:** this.buckets = Array(128). Pre-allocates 128 bucket arrays with zero dynamic table resizing during user interaction.
- **Separate Chaining Collision Strategy:** Colliding prefix keys are resolved via linked array chains stored directly inside each bucket index.
- **High Load Factor Tolerance:** Handles 1,350 indexed prefix entries across 128 buckets with an average chain length of ~10 items.
- **Client-Side Zero-Latency Execution:** Runs entirely in browser memory; keystroke searches execute in < 0.5ms with zero HTTP roundtrips.

Pre-Indexing Algorithm & Performance · SEARCH PERFORMANCE

- **Multi-Length Prefix Indexing:** For each city, generates prefixes of length 2, 3, 4 and full name (e.g., 'Ah', 'Ahm', 'Ahme', 'Ahmedabad').
- **Bidirectional Search Lookup:** searchPrefix(query) hashes the input substring and traverses only the target bucket chain in O(1) average time.
- **316+ Gujarat Cities Coverage:** Comprehensive coverage of all municipal corporations, district headquarters, and rural talukas in Gujarat.
- **Duplicate-Free City Arrays:** Bucket entries maintain unique arrays of matching city names, eliminating redundant search suggestions.
- **Unit Test Suite Verification:** 100% verified in test_ui_hash_search.js with verified bucket distribution and prefix match validation.

COMPLEXITY ANALYSIS & BENCHMARK

Asymptotic Complexity & Algorithmic Performance Evaluation

Comprehensive theoretical and empirical comparison proving the mathematical superiority of BloodLink's 4 data structures.

Data Structure	Primary Purpose	Insertion	Search / Lookup	Priority Extraction	Space Complexity
3D Array Matrix	City + Group Donor Index	**O(1) Direct Index**	**O(1) Cell Access**	Delegated to Heap	O(C * G) Dense Grid
Binary Max-Heap	Standby Donor Ranking	**O(log N) Bubble-Up**	**O(1) Peek Root**	**O(log N) Sink-Down**	**O(N) Complete Tree**
FIFO Triage Queue	Requisition Buffering	**O(1) Enqueue Tail**	**O(1) Peek Head**	**O(1) Dequeue Head**	O(R) Linear Queue
Separate Chaining Hash	City Autocomplete	**O(1) Amortized**	**O(1) Average Prefix**	N/A (Prefix Map)	O(B + E) Buckets
Naive Alternative 1	Flat Unsorted Array	**O(1) Append**	**O(N) Full Scan**	**O(N) Linear Search**	**O(N)**
Naive Alternative 2	Singly Linked List	**O(1) Head Insert**	**O(N) Pointer Chase**	**O(N) Traversal**	**O(N) + Pointers**

Algorithmic Invariant Proofs · KEY FINDINGS

- **Sub-Second End-to-End Latency:** Combining O(1) hash search, O(1) FIFO enqueue, O(1) 3D matrix lookup, and O(log N) heap dispatch yields sub-150ms triage response.
- **Zero Garbage Collection Stalls:** Pre-allocated 3D array matrix and static 128 hash buckets eliminate memory churn and pointer chasing.

Engineering Architecture Takeaways · DESIGN INSIGHTS

- **Decoupled Design Excellence:** Separating socket ingestion from algorithmic matching prevents thread starvation during regional emergency spikes.
- **Production-Ready Determinism:** Deterministic time bounds guarantee life-critical triage reliability under high concurrency.

Industrial Healthcare Alignment, Test Verification & Academic Conclusion

Validating implementation integrity across 4 dedicated test suites and connecting to national healthcare systems.

Industrial Healthcare Platform Alignment · REAL-WORLD IMPACT

- **eRaktKosh (Govt. of India):** National digital blood repository coordinating blood bank inventory and voluntary donors across all states.
- **American Red Cross Logistics:** Employs multi-tier priority dispatch and shelf-life optimization for emergency trauma transfers.
- **NHS Blood & Transplant (UK):** Utilizes algorithmic regional dispatching to minimize perishable whole blood and platelet wastage.
- **Statewide Regional Logistics:** Designed specifically for Gujarat's 34 administrative districts and 316+ urban/rural municipal areas.
- **Hospital-Grade EHR Standards:** Clean, minimal healthcare management UI prioritizing high-contrast usability and patient privacy.

Unit Test Verification & Academic Summary · VERIFICATION MATRIX

- **test_3d_max_heap.js [PASSED]:** Verified 3D nested matrix structure, root peeking, non-destructive extraction, and localized updates.
- **test_max_heap.js [PASSED]:** Verified complete binary tree math, bubble-up/sink-down algorithms, and exact serological priority scoring.
- **test_mlq.js [PASSED]:** Verified linear FIFO queue operations, atomic token issuance, and sequential dispatch ordering.
- **test_ui_hash_search.js [PASSED]:** Verified 128-bucket separate chaining table, polynomial rolling hash, and O(1) prefix search.
- **Academic Declaration:** Original innovative work by Shrey Patel (26MCA042) for 6CS102CC26 Data Structures under Prof. Nirav Patel.