

Shrey

by Buddhadev Goswami

Submission date: 13-Oct-2023 11:29PM (UTC+0530)

Submission ID: 2190270729

File name: Stage_1_Report_1.pdf (1.2M)

Word count: 5748

Character count: 32423



Koita Centre for Digital Health Indian Institute of Technology, Bombay

41
A report for the first phase submitted in partial fulfilment of the requirements
for completion of the Dual Degree project

57 Non-Invasive Detection of Anemia Using Anatomic Images

Submitted by

Shrey Gupta (190100112)
Sp. ETS

Guide: Prof. Nirmal Punjabi (KCDH)
Co-Guide: Prof. Ganesh Ramakrishnan (CSE)

(October 2023)

Declaration

I declare that this written submission represents my ideas in my own words and where others' ideas or words have been included, I have adequately cited and referenced the original sources. I also declare that I have adhered to all principles of academic honesty and integrity and have not misrepresented or fabricated or falsified any idea/data/fact/source in my submission. I understand that any violation of the above will ~~be cause~~ for disciplinary action by the Institute and can also evoke penal action from the ~~sources which~~ have thus not been properly cited or from whom proper permission has not been taken when needed.

Shrey Gupta
Sp. ETS
190100112

Date: 13th October 2023

List of Figures

3.1	Flowchart of methodology	6
3.2	Shows eye images from the dataset	7
3.3	Shows segmented conjunctiva	7
3.4	Bar chart of labels and Histogram of hemoglobin level	9
3.5	Bar chart of gender and Histogram of age	10
3.6	Scatter plot between hgb and other features in the dataset	11
3.7	A heatmap of correlation between all the features and independent variable	12
4.1	Comparison of all classification models	14
4.2	Confusion Matrix for Decision Tree Classifier	14
4.3	Summary of tuning the dt model	15
4.4	Comparison of all regression models	16
4.5	Residual vs Predicted Value Plot	17
4.6	Summary of tuning the CatBoost model	17
4.7	Feature Importance Plot	18

List of Tables

2.1	Summary of Papers	4
-----	-------------------	---

Table of Contents

1.	Abstract.....	1
2.	Preliminaries.....	2
2.1	Introduction.....	2
2.2	Related Work.....	3
2.3	Machine Learning Algorithms	5
3.	Methodology	6
3.1	Dataset	7
3.2	Segmentation	7
3.3	Data Augmentation	8
3.4	Feature Extraction	8
3.5	⁴⁷ Exploratory Data Analysis	9
3.5.1	Hemoglobin (Hgb) levels.....	9
3.5.2	Age and Gender.....	10
3.5.3	Scatter Plot.....	11
3.6	Feature Selection.....	12
4.	Results	13
4.1	Classification.....	13
4.1.1	⁴⁰ Evaluation Metrics.....	13
4.1.2	Model Comparison	13
4.1.3	Tuning	15
4.2	Regression	15
4.2.1	Evaluation Metrics.....	15
4.2.2	Model Comparison	16
4.2.3	Tuning	17
4.3	Comparing Classification and Regression Techniques.....	18
5.	Summary and Future Work.....	19
5.1	Summary	19
5.2	Future Work	20

5.2.1	Collection of Data	20
5.2.2	Existing Data.....	20
6.	Annexure	21
7.	References.....	23

1. Abstract

Anemia, a condition characterized by low hemoglobin levels, affects approximately 1.6 billion people worldwide. This study investigates non-invasive methods for anemia detection, comparing their performance in both classification and regression tasks. Traditional approaches rely on invasive blood tests, but recent developments have focused on non-invasive techniques using anatomical images like the eye, palm, nail, tongue, and conjunctiva to estimate hemoglobin levels.

The research methodology involves acquiring a dataset of Indian eye images with demographic details and hemoglobin levels. Exploratory Data Analysis (EDA) reveals insights into the dataset, showing gender, age, and hemoglobin level distributions. Scatter plots confirm that no strong correlations exist between hemoglobin levels and other features.

In the classification domain, the Decision Tree Classifier emerges as the top-performing model with an accuracy of 85.24% and an F1 score of 85.86%. Regression analysis identifies the CatBoost Regressor as the best model with an R2 score of 0.3244 and low Mean Absolute Error (MAE).

In summary, this study explores non-invasive anemia detection using anatomical images, demonstrating the potential of Decision Tree Classifier and CatBoost Regressor models for classification and regression. Future work includes data collection, augmentation, convolutional neural network utilization, further feature selection, hyperparameter tuning, and ensemble modelling to enhance accuracy and performance.

2. Preliminaries

2.1 Introduction

Hemoglobin provides the oxygen-carrying capacity of blood, a critical need for optimal body organ function. Changes in hemoglobin, particularly decreases below optimal levels, compromise health and characterize multiple diseases. Anemia is a condition in which hemoglobin (Hb) concentration is lower than normal and insufficient to meet an individual's physiological needs - affecting roughly 1.6 Billion people worldwide[3]. People may be born with certain types of anemia or develop anemia because they have certain chronic diseases. But poor diet causes iron-deficiency anemia, which is the most common form of anemia[2].

Anaemia is a subtle disease and has a slow evolution. It does not manifest symptoms until it becomes severe, because the human body compensates lack of oxygen. The symptomatology varies but recurrent symptoms include fatigue, dizziness or light-headedness, headache, pallor, chest pain, weakness, irregular heartbeat, shortness of breath, and cold hands and feet. In severe cases, anaemia can cause poor cognitive and motor development in children. It can also cause problems for pregnant women and their babies[1]. Prevention or early detection of anemia will reduce serious complications and help lead a healthy life.

Anemia can be detected by a complete blood cell method (gold standard test), peripheral smear, reticulocyte count, and serum iron indices[4] but these methods are invasive, thus requiring blood as a sample for the detection of anemia. Often the use of invasive methods is not recommended, for example in the case of infants, the elderly, pregnant women, patients with anemia and sickle cell. Furthermore, frequent sampling is uncomfortable and expensive, especially in areas of the world that have limited economic resources.

Due to the difficulties of invasive approaches for haemoglobin estimation, different non-invasive approaches are becoming highly demanding as they are easy to use, prick-free method and provide bed-side diagnoses. Since pallor is one of the most common symptoms of iron deficiency anemia[5], many studies have shown interest in the pallor of the exposed tissues of the human body to estimate anemia. Pallor may be evident on the entire body but is easily observed in areas where blood vessels are close to the surface, such as the palm, the nail bed, and mucous membranes such as the tongue or conjunctivae.

2.2 Related Work

Peter Appiahene *et al.*[6] utilised palmar pallor to detect anemia using various algorithms, which included CNN, k-NN, Naive Bayes, SVM, and Decision Tree. They used a primary dataset of 527 palm images to generate the region of interest (ROI) using the triangle thresholding and then augmented the size of the datasets to 2635 using the image augmentation technique (such as rotation, flipping and translation in X or Y axis) to avoid overfitting. Naïve Bayes model attained the highest accuracy of 99.96% while CNN attained the highest sensitivity of 99.98%.

Justice Williams Asare *et al.*[7] compared the conjunctiva of the eyes, the palpable palm, and the colour of the fingernail images to justify which of them had a higher accuracy for detecting anemia in children. In this study, a machine learning approach was used to detect iron-deficiency anemia with the application of Naïve Bayes, CNN, SVM, k-NN, and decision tree algorithms. A Samsung Galaxy Tab 7A was utilised to capture the images from 710 children aged 6 to 59 months. Similar preprocessing to [6] was done to extract the ROI and generate the dataset for the models. After the dataset generation these models were trained, validated, and tested on images of the conjunctiva of the eyes, palpable palm, and colour of the fingernails separately. The results obtained by the models show that the CNN is robust and performs better than Naïve Bayes, decision tree, k-NN and SVM in anemia detection and the palpable palm is one of the reliable human features for anemia detection in children due to its higher detection accuracy.

Pallavi *et al.*[8] developed an Artificial Intelligence (AI)-based bot that can be used for screening people for anemia in only 35 s. The bot service is based on two models: a segmentation model to segment the Region of Interest (ROI) and a classification model to classify anemic cases from normal ones. The model got an accuracy of 97% and a sensitivity of 96% using 300 conjunctiva images and a convolution neural network.

Shaun Collings *et al.*[9] devised a screening technique for the non-invasive detection of anaemia based on digital analysis of the palpebral conjunctiva in a digital photograph. They extracted erythema index (EI) from 106 conjunctiva images and fitted a linear curve using EI as parameters, and got sensitivity of 93% and specificity of 72%.

Robert G. Mannino *et al.*[10] devised a smartphone app to estimate hemoglobin level from the images of fingernail. They collected fingernail images using an Apple iPhone 5s from 337 people and extracted the ROI manually. They extracted fingernail data, skin colour data, and image metadata from ROI via MATLAB

⁵²
and the fitted a multi-linear regression with a bisquare weighting algorithm using skin colour data and image metadata as parameters, and achieved sensitivity of 92% and specificity of 76%

⁴³
R. Mala *et al.*[11] develop a non-invasive method of anemia detection using the combined features from digital images of eye, palm, and nail bed. They extracted mean and standard deviation of a* value from CIELAB colour space and the ratio between the mean of red value to the mean of green value in RGB colour space for all the three anatomies. Using these nine features (three from each anatomy), they trained a linear regression model utilizing the images from 115 people and got accuracy, sensitivity, and specificity each as 80%.

Thomas Alan Wemyss *et al.*[12] utilised a linear combination of colorimetric metrics from the lower eyelid, conjunctiva, and the lower lip. They extracted six features namely erythema index, r chromaticity, -g chromaticity, a* chromaticity, and b* chromaticity from conjunctiva, lower eyelid, and the lower lip, and deployed a Naïve Bayes classifier to attain accuracy of 91% and sensitivity of 93%.
Sp. ETS

On conducting the literature review of 50+ papers from the past 2 decade only a very few papers (1-2) worked on the combined image parameters from all the major exposed tissues of the human body such as tongue, palm, fingernail, and conjunctiva. It was seen that each anatomic part provided a good accuracy and sensitivity, and thus combining the best parameters from each anatomy can provide a more robust and better model.

Thus, this project tries to prove the hypothesis that a combination of features from tongue, palm, fingernail, and conjunctiva (may or may not utilising all anatomies) provides a more robust machine learning model with higher accuracy and recall.

Author	Accuracy	Sensitivity	Precision	Specificity
Peter Appiahene et al [6]	0.99	0.99	0.99	NA
Justice Williams Asare et al [7]	0.98	0.99	0.99	NA
Pallavi et al [8]	0.97	0.96	0.94	NA
Shaun Collings et al [9]	NA	0.93	NA	0.72
Robert G. Mannino et al [10]	NA	0.92	NA	0.76
R. Mala et al [11]	0.8	0.8	0.94	0.8
Thomas Alan Wemyss et al [12]	0.91	0.93	0.81	0.89

Table 2.1 – Comparison of papers [19]

2.3 Machine Learning Algorithms

Before diving deep into the methodology, it is essential to understand a bit about each of most common machine learning algorithm that have been used by the researchers such as Linear Regression (LR), Support Vector Machine (SVM), Decision Tree(DT), Convolution Neural Network (CNN) to name a few.

Linear regression aims to find a linear relationship, without the need for complex mathematical equations. This technique is fundamental in understanding how one variable influence another, making it a valuable tool in various research domains. Researchers use linear regression to make predictions, identify trends, and uncover associations between variables, contributing valuable insights to a wide range of academic fields.

10

Support Vector Machines (SVM) is a powerful machine learning algorithm used for classification and regression tasks. Instead of relying on complex equations, SVM focuses on finding an optimal decision boundary that maximizes the separation between different classes or data points. It achieves this by identifying support vectors, which are critical data points closest to the decision boundary. SVM's ability to handle high-dimensional data and non-linear relationships makes it a popular choice in various research and analysis scenarios, offering robust solutions to classification problems.

10

Decision trees are intuitive and interpretable machine learning models. They resemble hierarchical flowcharts where each internal node represents a decision based on a specific feature, leading to subsequent nodes or leaves that represent outcomes or predictions. By recursively splitting data, decision trees make choices that maximize information gain or minimize impurity, allowing them to efficiently partition datasets into classes or values. These versatile structures are widely used for decision-making processes across diverse fields, offering a straightforward yet effective approach to problem-solving and analysis.

Convolutional Neural Networks (CNNs) are specialized deep learning models designed to process and analyse visual data, like images and videos. Unlike traditional neural networks, CNNs use convolutional layers that apply filters to capture patterns and features hierarchically. These filters learn to detect various aspects such as edges, textures, and shapes within the data. By doing so, CNNs enable effective feature extraction, making them indispensable in computer vision tasks. CNNs' architecture, inspired by the visual processing in the human brain, has revolutionized image analysis and recognition.

3. Methodology

53

The general idea of methodology is shown in fig 3.1. The process begins with the segmentation of conjunctiva from the eye images to extract the region of interest (ROI), then data augmentation such as rotation along the axis, enlargement, flipping etc. is done to make the model robust to the dataset. After this feature extraction is performed independently in the RGB space, the HSV space and the Gray space. Now, exploratory data analysis (EDA) is done on the features to understand the nature of algorithm that can capture the relationship between the dependent and the independent variables. Using the insights from the EDA, feature selection is carried out to check for highly correlated features. Now the dataset is split into training and testing, and different models are fitted on the training dataset, after which their performances are evaluated using the unseen (test) dataset through different metrics depending on whether classification is being performed or regression analysis.




Fig. 3.1 – Flowchart of methodology

3.1 Dataset

The dataset that has been used for this part of the project contains 95 Indian eye images[13] of conjunctiva along with the segmented region of interest i.e., forniceal conjunctiva, palpebral conjunctiva, both, the patients' demographics such as age and gender, and finally the hemoglobin level when the photo of eye was taken.




Fig. 3.2 – Shows eye images from the dataset [13]

3.2 Segmentation

For this part of project, since the ROI of conjunctiva was already present, no segmentation was done. But in case of non-availability of ROI, the region of interest can be extracted using Sabrina's method[14] i.e., using deep neural architectures such as UNet, FCN, PSPNet, or LinkNet.



Fig. 3.3 – Shows segmented conjunctiva [13]

3.3 Data Augmentation

No data augmentation was required up until now in the project. But augmentations such as rotation, cropping, adding noise, flipping, scaling, contrast, translation etc, can be done using different libraries as OpenCV[15], ImgAug[16], etc in python.

3.4 Feature Extraction

A total of twelve features were extracted as mentioned in [17] these are mean_r, mean_g, mean_b, mean_{r-g}, HHR, Ent, B, g1, g2, g3, g4, and g5 were extracted from each of the ROI of conjunctiva.

Features mean_r, mean_g, mean_b, mean_{r-g} were extracted from the RGB colour space such that these features are mean² intensity values of the red, green, and blue components of the ROI and mean_{r-g} = mean(r_i-g_i)

HHR is called the high hue ratio, and it represents the proportion of pixels with high values in the hue component of the image in HSV space. It is given by the ratio of number³⁰ of high-hue pixels in an ROI, with a total of N pixels. A high HHR value denotes a large red area in an image.

From the grey space features like Entropy (Ent), average brightness (B) and the g(1 to 5) features are extracted. The formulae can be found in section 3.2 (Feature Extraction) in [17]

Along with these 12 features, age and gender were included in the final list of features, thus making a total of 14 independent variables, with label/hemoglobin as dependent variable.

See Annexure A1 for the code of feature extraction.

3.5 Exploratory Data Analysis

Exploratory Data Analysis (EDA) entails the systematic examination of data to uncover patterns, relationships, and anomalies. Techniques like summary statistics, data visualization, and data cleaning are employed to gain insights and identify data quality issues. EDA not only enhances data comprehension but also helps in making informed decisions on subsequent analytical approaches.

3.5.1 Hemoglobin (Hgb) levels

According to WHO, the hemoglobin level for anemia varies according to sex, age and whether a woman is pregnant or not. For the sake of simplicity, I have combined the anemic and moderately anemic across all age and gender as “anemic” with label as **1** and rest non-anemic and mildly anemic as “non-anemic” with label as **0**, with the threshold as **11.0 g/dL** [18].

24

Fig. 3.4(left) shows the distribution of labels in the dataset. There are 55 non-anemic patients with label **0** while there are 40 anemic patients with label **1**

Fig. 3.4(right) shows the histogram of hemoglobin (hgb) levels in the patients. The highest bars are for the bucket 10-12 and 12-14 hgb signifying that most of the patients in the dataset have hemoglobin between 10-14 g/dL




Fig. 3.4 - Bar chart of labels and Histogram of hemoglobin level. Left: A bar chart representing the number of labels. **Right:** A histogram representing the distribution of hgb levels

3.5.2 Age and Gender

Other than hemoglobin, age and gender data were also collected from the patients.

Fig. 3.5(left) shows the distribution of gender in the dataset. There are 49 male patients with label **M** while there are 46 female patients with label **F**.

Fig. 3.5(right) shows the histogram of age in the patients. The highest bar is for the bucket 20-25 years signifying that most of the patients in the dataset have age between 20-25 years.




Fig. 3.5 – Bar chart of gender and Histogram of age. Left: A bar chart representing the number of males and females in the dataset. **Right:** A histogram representing the distribution of age

3.5.3 Scatter Plot

18

A scatter plot presents a graphical representation of data points on a two-dimensional plane, with one variable on the x-axis and another on the y-axis. This visualization technique helps in exploring the relationship between two variables, making it invaluable in hypothesis testing and data analysis. Scatter plots can reveal trends, correlations, outliers, and clusters within the data, aiding in the identification of patterns and potential insights.

Fig 3.6 – represents the scatter plot of hemoglobin level vs other features in the dataset. In all the graphs it is evident that there is ~~general trend in points placement~~. Thus, ~~this means~~ that there is no correlation between hemoglobin and the following features.




Fig. 3.6 – Scatter plot between hgb and other features in the dataset

a: hgb vs mean_rg, b: hgb vs HHR, c: hgb vs Ent, d: hgb vs G1

6

3.6 Feature Selection

Feature selection is the process of isolating the most consistent, non-redundant, and relevant features to use in model construction. Methodically reducing the size of datasets is important as the size and variety of datasets continue to grow. The main goal of feature selection is to improve the performance of a predictive model and reduce the computational cost of modelling.

3

Correlation is a measure of the linear relationship between 2 or more variables. Through correlation, we can predict one variable from the other. The logic behind using correlation for feature selection is that good variables correlate highly with the target. Furthermore, variables should be correlated with the target but uncorrelated among themselves. If two variables are correlated, we can predict one from the other. Therefore, if two features are correlated, the model only needs one, as the second does not add additional information.




Fig. 3.7 – A heatmap of correlation between all the features and independent variable

Sp. ETS

4. Results

This project can be accomplished using classification (classifying as anemic or non-anemic) as well as regression (predicting the hemoglobin value). From a medical point of view the hemoglobin prediction is much more general case and predicting anemia is just a consequence of this. For this stage, classification has been more focused to replicate the results achieved in the literature review. But a regression analysis had also been done to understand the feature importance and evaluation metric and compare it with the classification task.

To develop and compare models PyCaret[20] library has been used. PyCaret is an open-source, low-code machine learning library in Python that automates machine learning workflows.

4.1 Classification

4.1.1 Evaluation Metrics

To evaluate the performance of the classification algorithms, metrics such as accuracy, AUC, Recall, F1 etc has been used. The images that the classifier correctly identified as belonging to the anemic class represented the true positive (TP), and the images correctly identified as not anemic represented the true negative (TN). The images of non-anemic patients incorrectly classified as belonging to the anemic class were false positives (FPs). Finally, the conjunctival images of anemic patients incorrectly identified as belonging to the nonanemic class were false negatives (FNs). Based on these notations, accuracy, sensitivity, and specificity are defined as follows:

$$\text{accuracy} = (\text{TP} + \text{TN}) / (\text{TP} + \text{TN} + \text{FP} + \text{FN})$$

$$\text{recall or sensitivity} = \text{TP} / (\text{TP} + \text{FN})$$

$$\text{specificity} = \text{TN} / (\text{TN} + \text{FP})$$

$$\text{precision} = \text{TP} / (\text{TP} + \text{FP})$$

$$\text{F1 score} = 2 * (\text{precision} * \text{recall}) / (\text{precision} + \text{recall})$$

4.1.2 Model Comparison

Fig 4.1 shows the comparison of all the classification models using the PyCaret classification library's `compare_model` function. All the models are tested and

ranked according to their recall (or sensitivity) score. It is evident that Decision Tree(dt) Classifier has the highest recall and the highest F1 score.

See Annexure A2 for the python code for classification

Model		Accuracy	AUC	Recall	Prec.	F1	Kappa	MCC	TT (Sec)
dt	Decision Tree Classifier	0.8071	0.8083	0.8500	0.7850	0.7940	0.6142	0.6450	0.0180
ridge	Ridge Classifier	0.8143	0.0000	0.8333	0.7833	0.7881	0.6180	0.6443	0.0180
lightgbm	Light Gradient Boosting Machine	0.8119	0.8569	0.8167	0.8000	0.7781	0.6246	0.6551	0.0760
et	Extra Trees Classifier	0.8000	0.8375	0.7833	0.8000	0.7738	0.5995	0.6208	0.1560
lda	Linear Discriminant Analysis	0.8000	0.8681	0.8167	0.7850	0.7674	0.5964	0.6330	0.0190
lr	Logistic Regression	0.8000	0.8458	0.7333	0.8183	0.7474	0.5800	0.6083	1.6650
xgboost	Extreme Gradient Boosting	0.7857	0.9014	0.7167	0.8100	0.7350	0.5550	0.5813	0.0430
catboost	CatBoost Classifier	0.7429	0.8792	0.7833	0.7150	0.7324	0.4894	0.5076	2.0720
gbc	Gradient Boosting Classifier	0.7857	0.8792	0.7000	0.7917	0.7290	0.5463	0.5633	0.0840
ada	Ada Boost Classifier	0.7690	0.7875	0.7000	0.7767	0.7183	0.5174	0.5391	0.0830
rf	Random Forest Classifier	0.7405	0.8292	0.7000	0.7733	0.6967	0.4746	0.5072	0.1890
nb	Naive Bayes	0.7071	0.7625	0.6333	0.6983	0.6457	0.3993	0.4105	0.0180
qda	Quadratic Discriminant Analysis	0.6405	0.6333	0.3667	0.6067	0.4300	0.2213	0.2541	0.0290
svm	SVM - Linear Kernel	0.4667	0.0000	0.7000	0.2952	0.4133	0.0000	0.0000	0.0180
knn	K Neighbors Classifier	0.6095	0.6194	0.3500	0.5000	0.3871	0.1448	0.1685	0.0370
dummy	Dummy Classifier	0.5762	0.5000	0.0000	0.0000	0.0000	0.0000	0.0000	0.0140

Fig. 4.1 – Comparison of all classification models

11

A confusion matrix summarizes the performance of a machine learning model on a set of test data. It is used to measure the performance of classification models, which aim to predict a categorical label for each input instance. Fig 4.2 shows the confusion matrix for the decision tree classifier. For the given confusion matrix TP=17, TN=5, FP=0; FN=7; this implies Accuracy of 75.86%, Recall of 41.67%, Precision of 100.00% and F1 score of 58.82%.




Fig. 4.2 – Confusion Matrix for Decision Tree Classifier

4.1.3 Tuning

From the confusion matrix it is evident that the model has a poor recall, though it has the highest precision and good accuracy. Thus, the model needs some tuning to improve the metrics and achieve higher scores.

Fig 4.3 shows the summary of hyperparameter tuning for decision tree model

	Accuracy	AUC	Recall	Prec.	F1	Kappa	MCC
Fold							
0	0.7143	0.7500	1.0000	0.6000	0.7500	0.4615	0.5477
1	0.8571	0.8750	1.0000	0.7500	0.8571	0.7200	0.7500
2	0.7143	0.7083	1.0000	0.6000	0.7500	0.4615	0.5477
3	0.8571	0.8750	1.0000	0.7500	0.8571	0.7200	0.7500
4	0.8571	0.8750	1.0000	0.7500	0.8571	0.7200	0.7500
5	0.8571	0.7500	1.0000	0.7500	0.8571	0.7200	0.7500
6	0.8333	0.8125	1.0000	0.6667	0.8000	0.6667	0.7071
7	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
8	0.8333	0.7778	1.0000	0.7500	0.8571	0.6667	0.7071
9	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000	1.0000
Mean	0.8524	0.8424	1.0000	0.7617	0.8586	0.7136	0.7510
Std	0.0909	0.0964	0.0000	0.1325	0.0819	0.1720	0.1451
Fitting 10 folds for each of 500 candidates, totalling 5000 fits							

Fig. 4.3 – Summary of tuning the dt model

4.2 Regression

4.2.1 Evaluation Metrics

To evaluate the performance of the regression algorithms, metrics such as mean absolute error (MAE), mean squared error (MSE), root mean squared error (RMSE), R Squared (R²) etc has been used. MAE calculates the absolute difference between actual and predicted values. Mean squared error (MSE), also called mean squared deviation (MSD), is the average squared difference between the value observed in a statistical study and the values predicted from a model. RMSE is the square root of mean squared error. R² score is about the performance of the model and not the loss in an absolute sense R² squared calculates how much

regression line is better than a mean line. Hence, R² squared is also known as Coefficient of Determination or sometimes also known as Goodness of fit.

4.2.2 Model Comparison

Fig 4.4 shows the comparison of all the regression models using the PyCaret regression library's `compare_model` function. All the models are tested and ranked according to their R² score. It is evident that CatBoost Classifier has the highest R² score and the lowest MAE score.

See Annexure A3 for the python code for regression

Model		MAE	MSE	RMSE	R2	RMSLE	MAPE	TT (Sec)
catboost	CatBoost Regressor	1.2224	2.3617	1.4604	0.3244	0.1182	0.1095	1.5540
ada	AdaBoost Regressor	1.2262	2.2263	1.4140	0.2964	0.1158	0.1103	0.0720
rf	Random Forest Regressor	1.2641	2.5076	1.4967	0.2865	0.1211	0.1131	0.1680
ridge	Ridge Regression	1.2566	2.5546	1.5025	0.2361	0.1213	0.1115	0.0190
et	Extra Trees Regressor	1.3507	2.8172	1.6222	0.1561	0.1296	0.1197	0.1220
lightgbm	Light Gradient Boosting Machine	1.3057	2.7156	1.5847	0.1410	0.1285	0.1158	0.0600
xgboost	Extreme Gradient Boosting	1.3144	2.7166	1.5858	0.1073	0.1304	0.1187	0.0960
huber	Huber Regressor	1.3708	3.1765	1.6288	0.1042	0.1306	0.1196	0.0310
lr	Linear Regression	1.3998	3.0661	1.6557	0.0806	0.1371	0.1255	0.0210
en	Elastic Net	1.4139	3.1047	1.7079	0.0659	0.1399	0.1278	0.0210
br	Bayesian Ridge	1.4219	3.1899	1.7294	0.0520	0.1413	0.1286	0.0190
gbr	Gradient Boosting Regressor	1.4483	3.2712	1.6831	0.0394	0.1330	0.1273	0.0690
llar	Lasso Least Angle Regression	1.4298	3.2849	1.7496	0.0323	0.1430	0.1293	0.0210
lasso	Lasso Regression	1.4299	3.2850	1.7497	0.0322	0.1430	0.1293	0.0200
omp	Orthogonal Matching Pursuit	1.6708	4.2538	1.9894	-0.2465	0.1618	0.1532	0.0210
dummy	Dummy Regressor	1.7403	4.5759	2.0508	-0.2961	0.1663	0.1581	0.0200
knn	K Neighbors Regressor	1.7705	4.9842	2.1741	-0.5481	0.1767	0.1617	0.0270
dt	Decision Tree Regressor	1.9679	5.6905	2.2973	-0.7671	0.1830	0.1757	0.0220
par	Passive Aggressive Regressor	3.3447	16.6452	3.8746	-4.6048	0.2882	0.3160	0.0200
lar	Least Angle Regression	7.3710	715.4822	11.8623	-219.7079	0.4382	0.7609	0.0200

Fig. 4.4 – Comparison of all regression models

Fig 4.5 shows the residuals vs. fits plot. Points to note from the plot are

Article Error ETS

- The train R²=1 and test R²=0.454. This suggests that the model can perfectly explain the relationship between the dependent and independent

- variables in training but only 45.4% of the relationship during testing indicating high variance in the model
- No one residual "stands out" from the basic random pattern of residuals. This suggests that there are no outliers.




Fig. 4.5 – Residual vs Predicted Value Plot

4.2.3 Tuning

From the fig 4.4 it is evident that the model still has some error in MAE or RMSE and R2 score is 0.3244, this suggests that model explains 32% of the relationship between the dependent and independent variables. Thus Fig 4.6 shows tuning of the CatBoost model

Run-on

Fold	Sp.	MAE	MSE	RMSE	R2	RMSLE	MAPE
0	Sp.	1.4496	3.5199	1.8761	-0.1002	0.1361	0.1091
1	Sp.	1.0018	1.4704	1.2126	0.5473	0.1000	0.0899
2	Sp.	0.9633	1.4456	1.2023	0.0874	0.1011	0.0860
3	Sp.	1.5870	2.8340	1.6834	-0.6547	0.1456	0.1635
4	Sp.	0.5204	0.4202	0.6482	0.7181	0.0490	0.0427
5	Sp.	0.9752	1.6162	1.2713	0.5745	0.1165	0.1039
6	Sp.	1.0545	1.5226	1.2339	0.4746	0.1072	0.0987
7	Sp.	2.0576	6.3497	2.5199	0.4677	0.1854	0.1702
8	Sp.	1.5428	3.7694	1.9415	0.4055	0.1657	0.1427
9	Sp.	0.7362	0.6872	0.8289	0.7637	0.0661	0.0638
Mean	Sp.	1.1888	2.3635	1.4418	0.3284	0.1173	0.1070
Std	Sp.	0.4368	1.7005	0.5335	0.4129	0.0401	0.0391

Fitting 10 folds for each of 50 candidates, totalling 500 fits

Fig. 4.6 – Summary of tuning the CatBoost model

4.3 Comparing Classification and Regression Techniques

From fig 4.7 it is evident that gender and HHR(high hue ratio) are two most prominent features for both classification and regression.

For classification, the feature importance falls drastically after the 6th feature.

For regression, there is a huge difference between the importance of gender and HHR but after HHR all the features are almost equally important.




Fig. 4.7 – Feature Importance Plot.

Left: for classification. Right: for regression

5. Summary and Future Work

5.1 Summary

1

- Anaemia has a slow evolution, and it does not manifest symptoms until it becomes severe
- Close to 1.6B people suffer from anemia globally
- In the past two decades there has been a shift to estimate hemoglobin non-invasively, and in the past 3-4 years there has been a rise in using anatomic images (such as eye, nail, palm etc) to detect anemia
- General methodology followed is to first segment the image and extract the ROI and then perform feature extraction followed by training and testing
- Best Classification model so far is Decision Tree with accuracy of 85.24% and F1 score of 85.86%
- Six most important feature for classification (in order of importance) were gender, HHR, mean_rg, age, G1 and G5
- Best Regression model so far is CatBoost Regressor with R2 of 0.3244 and MAE of 1.224
- Six most important feature for regression (in order of importance) were gender, HHR, G3, mean_r, mean_rg and mean_g
- To increase the performance of the models, data augmentation, feature selection and more hyperparameter tuning could be tried out

Sp. 

5.2 Future Work

5.2.1 Collection of Data

- Design a research protocol for data collection
- Collect additional data such as fingernail, palm, tongue images along with the hemoglobin levels and demographics such as age, gender etc
- Devise a strategy to store and clean the data for future use

Missing "," ETS

5.2.2 Existing Data

- Perform data augmentation to increase the dataset
- Try out the convolutional neural network for both classification and regression
- Perform feature selection or PCA to reduce dimensionality of the features
- Perform hyperparameter tuning for all the top 3 models with the best metrics in classification as well as regression
- Try out ensemble models by combining the predictions from the weaker models

6. Annexure

Run-on (ETS)

A1 Code for feature extraction

```
""" Images should be sent in RGB format """

def feature(data):

    """Return all the 12 features as a numpy array"""

    number,img,label = data
    img = resize(img,(250,250))  
Article Error (ETS)  
Missing "," (ETS)

    #RGB SPACE
    r, g, b = cv2.split(img)
    sum_img = [sum(r),sum(g),sum(b),sum(r-g)]
    mean_features = [i[0],i[1] for i in sum_img]  
Prop. Proper Nouns (ETS)
    mean_r,mean_g,mean_b,mean_rg = mean_features

    # 4 features done in RGB SPACE

    #HSV SPACE
    hsv = to_hsv(img)
    h,s,v = cv2.split(hsv)
    h = h/h.max()
    nH = np.count_nonzero(h>0.95)  
Proper Nouns (ETS)
    HHR = nH/h.size
    # HHR found

    #GRAY SPACE
    gray = to_gray(img)
    B_sum, B_size = sum(gray)
    B = B_sum/B_size # FOUND B

    #ENTROPY in gray space
    eq = cv2.equalizeHist(gray)
    Sp. (ETS)

    unique, counts = np.unique(eq, return_counts=True)
    #only pixels whose value is between 20 and 240
    total_counts = counts[21:240].sum()
    Ent = np.sum(np.array([i*(i/total_counts)*math.log((i/total_counts),2) for i in counts[21:240]])) #Found Entropy
    Proper Nouns (ETS)

    #Calculating the 'G' features
    Ixy = gray
    min_Ixy = pooling(image=Ixy, pool_size=(3,3), code='min', padding=1)
    max_Ixy = pooling(image=Ixy, pool_size=(3,3), code='max', padding=1)
    mean_Ixy = pooling(image=Ixy, pool_size=(3,3), code='mean', padding=1)
    std_Ixy = pooling(image=Ixy, pool_size=(3,3), code='std', padding=1)

    g1 = Ixy - min_Ixy
    g2 = max_Ixy - Ixy
    g3 = Ixy - mean_Ixy
    g4 = std_Ixy
    g5 = Ixy

    G1 = g1.sum()/g1.size
    G2 = g2.sum()/g2.size
    G3 = g3.sum()/g3.size
    G4 = g4.sum()/g4.size
    G5 = g5.sum()/g5.size

    feature_all = [number, mean_r, mean_g, mean_b, mean_rg, HHR, Ent, B, G1, G2, G3, G4, G5, label]
    Article Error (ETS)

    return feature_all
```

Points to Note in the above function:

- Images sent to the above function are in format number (name of image), image (in RGB format), label
- resize() – It returns the resized image
- sum() – This function takes input 1 component of an image (i.e., either red, blue, green, or gray) and returns the (sum,count), where sum represents the sum of pixels having pixel values between 20 and 240 while count represents the count of such pixels
- to_hsv() / to_gray() – These functions convert the image to HSV and Gray space respectively
- pooling() – This function returns a pooled image with padding

A2 Code for Classification

```
from pycareSp. (ET)classification import *
s = setup(data, target='label',
           ignore_features=['hgb','number'], preprocess=False,
           session_id=123)
best_c = compare_models(sort = 'F1')
evaluate_model(best_c)
predict_model(best_c)
tuned_dt = tune_model(best_c, fold = 10, n_iter = 500,
                      choose_better = True)
```

Points to Note[21]:

- 22
- setup() - initializes the training environment and creates the transformation pipeline
 - compare_models() - trains and evaluates performance of all estimators available in the model library using cross validation
 - evaluate_model() - displays a user interface for analysing performance of a trained model Article Error (ET)
 - predict_model() - predicts Label and Score (probability of predicted class) using a trained model
 - tune_model() - tunes the hyperparameters of a given estimator Sp. (ET)

A3 Code for Regression

```
50 from pycareSp. (ET)regression import *
s = setup(data, target='hgb',
           ignore_features=['label','number'], preprocess=False,
           session_id=123)
best_r = compare_models()
evaluate_model(best_r)
predict_model(best_r)
tuned_catboost = tune_model(best_r, fold = 10, n_iter =
50)
```

7. References

1. Anemia – World Health Organisation <https://www.who.int/anaemia>
2. Anemia <https://my.clevelandclinic.org/health/diseases/3929-anemia>
3. McLean, E., Cogswell, M., Egli, I., Wojdyla, D., & De Benoist, B. (2009). Worldwide prevalence of anaemia, WHO Vitamin and Mineral Nutrition Information System, 1993–2005. *Public Health Nutrition*, 12(4), 444-454. doi:10.1017/S1368980008002401
4. Johnson-Wimbley TD, Graham DY. Diagnosis and management of iron deficiency anemia in the 21st century. *Therapeutic Advances in Gastroenterology*. 2011;4(3):177-184. doi:10.1177/1756283X11398736
5. Iron deficiency anemia mayoclinic.org/iron-deficiency-anemia
6. Appiahene, P., Asare, J.W., Donkoh, E.T. et al. Detection of iron deficiency anemia by medical images: a comparative study of machine learning algorithms. *BioData Mining* 16, 2 (2023). doi:10.1186/s13040-023-00319-z
7. Asare, JW, Appiahene, P, Donkoh, ET, Dimauro, G. Iron deficiency anemia detection using machine learning models: A comparative study of fingernails, palm and conjunctiva of the eye images. *Engineering Reports*. 2023;e12667. doi:10.1002/eng2.12667
8. Pallavi, Bijit Basumatary, Rahul Shukla, Rakesh Kumar, Bodhisatwa Das & Ashish Kumar Sahani (2023) A Deep Learning-based System for Detecting Anemia from Eye Conjunctiva Images Taken from a Smartphone, *IETE Technical Review*, DOI: 10.1080/02564602.2023.2242318
9. Collings S, Thompson O, Hirst E, Goossens L, George A, et al. (2016) Non-Invasive Detection of Anaemia Using Digital Photographs of the Conjunctiva. *PLOS ONE* 11(4): e0153286. <https://doi.org/10.1371/journal.pone.0153286>
10. Mannino, R.G., Myers, D.R., Tyburski, E.A. et al. Smartphone app for non-invasive detection of anemia using only patient-sourced photos. *Nat Commun* 9, 4924 (2018). <https://doi.org/10.1038/s41467-018-07262-2>
11. R. Mala, V. Anukarani, Sivani.M, G. Vaishnavi, et al. Non-Invasive Measurement of Hemoglobin Using Smartphone. Vol 44 No. 7 Journal of Harbin Engineering University ISSN: 1006-7043 [[CrossRef](#)]
12. Wemyss TA, Nixon-Hill M, Outlaw F, Karsa A, Meek J, et al. (2023) Feasibility of smartphone colorimetry of the face as an anaemia screening tool for infants and young children in Ghana. *PLOS ONE* 18(3): e0281736. <https://doi.org/10.1371/journal.pone.0281736>
13. Dimauro, G.; Simone, L. Novel Biased Normalized Cuts Approach for the Automatic Segmentation of the Conjunctiva. *Electronics* 2020, 9, 997. <https://doi.org/10.3390/electronics9060997>

14. Sabrina Dhalla, Junaid Maqbool, Tanvir Singh Mann, Aastha Gupta, Ajay Mittal, Preeti Aggarwal, Krishan Saluja, Munish Kumar, Shiv Sajan Saini, Semantic segmentation of palpebral conjunctiva using predefined deep neural architectures for anemia detection, Procedia Computer Science, Volume 218, 2023, Pages 328-337, ISSN 1877-0509,
<https://doi.org/10.1016/j.procs.2023.01.015>
15. <https://opencv.org/>
16. <https://imgaug.readthedocs.io/en/latest/>
17. An intelligent non-invasive system for automated diagnosis of anemia exploiting a novel dataset Artif Intell Med, 136 (2023), Article 102477, 10.1016/j.artmed.2022.102477
18. <https://www.who.int/data/nutrition/nlis/info/anaemia>
19. <https://docs.google.com/spreadsheets/d/1AS5ZnELQjwgFQHvDR6foyp24NuUA9QlBRnYjk8jh5mA/edit#gid=0>
20. <https://pycaret.org/>
21. <https://pycaret.readthedocs.io/en/latest/api/classification.html>

30%

SIMILARITY INDEX

24%

INTERNET SOURCES

18%

PUBLICATIONS

12%

STUDENT PAPERS

PRIMARY SOURCES

- | | | | |
|--|----------|---|----|
| | 1 | www.mdpi.com | 3% |
| | | Internet Source | |
| | 2 | Giovanni Dimauro, Maria Elena Griseta,
Mauro Giuseppe Camporeale, Felice
Clemente, Attilio Guarini, Rosalia Maglietta.
"An intelligent non-invasive system for
automated diagnosis of anemia exploiting a
novel dataset", Artificial Intelligence in
Medicine, 2022 | 3% |
| | | Publication | |
| | 3 | www.analyticsvidhya.com | 2% |
| | | Internet Source | |
| | 4 | Submitted to Indian Institute of Technology,
Bombay | 2% |
| | | Student Paper | |
| | 5 | d197for5662m48.cloudfront.net | 2% |
| | | Internet Source | |
| | 6 | ijeeecs.iaescore.com | 1% |
| | | Internet Source | |

- 7 Pallavi, Bijit Basumatary, Rahul Shukla, Rakesh Kumar, Bodhisatwa Das, Ashish Kumar Sahani. "A Deep Learning-based System for Detecting Anemia from Eye Conjunctiva Images Taken from a Smartphone", IETE Technical Review, 2023
Publication
-
- 8 dokumen.pub 1 %
Internet Source
-
- 9 www.researchgate.net 1 %
Internet Source
-
- 10 Submitted to Coventry University 1 %
Student Paper
-
- 11 Submitted to Savitribai Phule Pune University 1 %
Student Paper
-
- 12 my.clevelandclinic.org 1 %
Internet Source
-
- 13 Sunanda Das, Abhishek Kesarwani, Dakshina Ranjan Kisku, Mamata Dalui. "Non-invasive Haemoglobin Estimation by Observing Nail Color: A PCA based Approach", 2022 IEEE 6th Conference on Information and Communication Technology (CICT), 2022 1 %
Publication
-
- 14 epublications.marquette.edu 1 %
Internet Source

15	Submitted to Middle East Technical University Student Paper	1 %
16	Justice Williams Asare, Peter Appiahene, Emmanuel Timmy Donkoh, Giovanni Dimauro. "Iron deficiency anemia detection using machine learning models: A comparative study of fingernails, palm and conjunctiva of the eye images", Engineering Reports, 2023 Publication	<1 %
17	www.who.int Internet Source	<1 %
18	Submitted to The University of Texas at Arlington Student Paper	<1 %
19	datasutras.wordpress.com Internet Source	<1 %
20	link.springer.com Internet Source	<1 %
21	pdfs.semanticscholar.org Internet Source	<1 %
22	pycaret.readthedocs.io Internet Source	<1 %
23	ouci.dntb.gov.ua Internet Source	<1 %

- 24 Peter Appiahene, Kunal Chaturvedi, Justice Williams Asare, Emmanuel Timmy Donkoh, Mukesh Prasad. "Cp-anemic: Aconjunctival pallor dataset and benchmark for anemia detection in children", Medicine in Novel Technology and Devices, 2023
Publication <1 %
- 25 Submitted to University of Suffolk <1 %
Student Paper
- 26 developers.refinitiv.com <1 %
Internet Source
- 27 Submitted to University College London <1 %
Student Paper
- 28 Submitted to University of Hertfordshire <1 %
Student Paper
- 29 Submitted to Victoria University <1 %
Student Paper
- 30 Yi-Ming Chen, Shaou-Gang Miaou, Hongyu Bian. "Examining palpebral conjunctiva for anemia assessment with image processing methods", Computer Methods and Programs in Biomedicine, 2016 <1 %
Publication
- 31 osr.cs.fau.de <1 %
Internet Source
- Submitted to University at Buffalo

32

<1 %

33

Thomas Alan Wemyss, Miranda Nixon-Hill, Felix Outlaw, Anita Karsa, Judith Meek, Christabel Enweronu-Laryea, Terence S. Leung. "Feasibility of smartphone colorimetry of the face as an anaemia screening tool for infants and young children in Ghana", PLOS ONE, 2023

Publication

34

biodatamining.biomedcentral.com

<1 %

Internet Source

35

ebin.pub

<1 %

Internet Source

36

hackernoon.com

<1 %

Internet Source

37

www.miningdataonline.com

<1 %

Internet Source

38

journals.plos.org

<1 %

Internet Source

39

Submitted to srmist

<1 %

Student Paper

40

web.dia.uniroma3.it

<1 %

Internet Source

41

www.coursehero.com

<1 %

Internet Source

<1 %

42 yma.gov.yk.ca
Internet Source

<1 %

43 Prakhar Jain, Shubham Bauskar, Manasi Gyanchandani. "Neural network based non-invasive method to detect anemia from images of eye conjunctiva", International Journal of Imaging Systems and Technology, 2019
Publication

<1 %

44 doctorpenguin.com
Internet Source

<1 %

45 projetos.lbi.iq.usp.br
Internet Source

<1 %

46 www.britannica.com
Internet Source

<1 %

47 library.ndsu.edu
Internet Source

<1 %

48 mafiadoc.com
Internet Source

<1 %

49 moez-62905.medium.com
Internet Source

<1 %

50 pycaret.gitbook.io
Internet Source

<1 %

- 51 section.iaesonline.com <1 %
Internet Source
-
- 52 www.nature.com <1 %
Internet Source
-
- 53 Justice Williams Asare, Peter Appiahene, Enoch Justice Arthur, Stephen Korankye, Stephen Afrifa, Emmanuel Timmy Donkoh. "Detection of anemia using conjunctiva images: A smartphone application approach", Medicine in Novel Technology and Devices, 2023 <1 %
Publication
-
- 54 "Advances in Data-driven Computing and Intelligent Systems", Springer Science and Business Media LLC, 2023 <1 %
Publication
-
- 55 Abhishek Kesarwani, Sunanda Das, Mamata Dalui, Dakshina Ranjan Kisku, Bibhash Sen, Suchismita Roy, Anupam Basu. "Non-invasive anaemia detection by examining palm pallor: A smartphone-based approach", Biomedical Signal Processing and Control, 2023 <1 %
Publication
-
- 56 Peter Appiahene, Justice Williams Asare, Emmanuel Timmy Donkoh, Giovanni Dimauro, Rosalia Maglietta. "Detection of iron deficiency anemia by medical images: a <1 %

comparative study of machine learning algorithms", BioData Mining, 2023

Publication

- 57 Shoumen Datta. "Aptamers for Detection and Diagnostics (ADD): Can mobile systems process optical data from aptamer sensors to identify molecules indicating presence of SARS-CoV-2 virus? Should healthcare explore aptamers as drugs for prevention as well as its use as adjuvants with antibodies and vaccines?", Cambridge University Press (CUP), 2021 <1 %
- Publication
-
- 58 Sivachandar Kasiviswanathan, Thulasi Bai Vijayan, Sheila John. "Ridge regression algorithm based non-invasive anaemia screening using conjunctiva images", Journal of Ambient Intelligence and Humanized Computing, 2020 <1 %
- Publication
-

Exclude quotes

Off

Exclude matches

Off

Exclude bibliography

On



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Compound These two words should be a compound word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Article Error You may need to use an article before this word. Consider using the article **the**.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to remove this article.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Missing "," Review the rules for using punctuation marks.



Missing "," Review the rules for using punctuation marks.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to remove this article.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Missing "," Review the rules for using punctuation marks.



Article Error You may need to remove this article.



Article Error You may need to use an article before this word. Consider using the article **a**.

PAGE 10



Article Error You may need to remove this article.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Wrong Form You may have used the wrong form of this word.



Missing "," Review the rules for using punctuation marks.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word. Consider using the article **a**.



Verb This verb may be incorrect. Proofread the sentence to make sure you have used the correct form of the verb.



Wrong Form You may have used the wrong form of this word.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 11



S/V This subject and verb may not agree. Proofread the sentence to make sure the subject agrees with the verb.



Missing "," Review the rules for using punctuation marks.

PAGE 12

PAGE 13



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Confused You have used either an imprecise word or an incorrect word.



P/V You have used the passive voice in this sentence. You may want to revise it using the active voice.



Missing "," Review the rules for using punctuation marks.



Prep. You may be using the wrong preposition.



Article Error You may need to remove this article.



Article Error You may need to use an article before this word.



Proofread This part of the sentence contains an error or misspelling that makes your meaning unclear.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Prep. You may be using the wrong preposition.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Run-on This sentence may be a run-on sentence.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Possessive



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 20



Article Error You may need to use an article before this word.

PAGE 21



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word. Consider using the article **the**.

PAGE 22



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Possessive



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.

PAGE 23



Missing "," Review the rules for using punctuation marks.



Run-on This sentence may be a run-on sentence.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 24

PAGE 25



Missing "," Review the rules for using punctuation marks.



Article Error You may need to use an article before this word. Consider using the article **the**.



Prep. You may be using the wrong preposition.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 26



Missing "," Review the rules for using punctuation marks.



Article Error You may need to remove this article.



Missing "," Review the rules for using punctuation marks.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 27



Run-on This sentence may be a run-on sentence.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Proper Nouns You may need to use a capital letter for this proper noun.



Proper Nouns You may need to use a capital letter for this proper noun.



Missing "," Review the rules for using punctuation marks.



Proper Nouns You may need to use a capital letter for this proper noun.



Proper Nouns You may need to use a capital letter for this proper noun.



Proper Nouns You may need to use a capital letter for this proper noun.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 28



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.



Article Error You may need to use an article before this word.



Sp. This word is misspelled. Use a dictionary or spellchecker when you proofread your work.

PAGE 29

PAGE 30
