

U - II

Performing Basic Server Configuration : Configure local server properties,
Configure server roles, Set up IP addressing service roles

Administering the Server : Update the server, Server administration access and control
methods, Create service level agreements, Monitor server performance

Implementing Storage Solutions : Perform capacity planning, Deploy primary storage
devices, Storage technologies, Configure RAID

- A directory is a hierarchical structure that stores information about objects on the network. A directory service, such as Active Directory Domain Services (AD DS), provides the methods for storing directory data and making this data available to network users and administrators.
- ***For example,*** AD DS stores information about user accounts, such as names, passwords, phone numbers, and so on, and enables other authorized users on the same network to access this information.

- Active Directory stores information about objects on the network and makes this information easy for administrators and users to find and use. Active Directory uses a structured data store as the basis for a logical, hierarchical organization of directory information.

NIC Teaming

- NIC Teaming, also known as load balancing and failover (LBFO).
- By 3 ways:
 - Static
 - Switch independent
 - Dynamic (LACP - Link Aggregation Control Protocol)

NIC Teaming Configuration

- By server manager:
- Check the two network adapters on machine by command `ncpa.cpl` in command window or in powershell (`ncpa.cpl` - The quickest way to go directly to the network adapters, `Ncpa.cpl`, also known as a **Network Connections Control-Panel Stub file**, was created by Microsoft for the development of Microsoft® Windows® Operating System. CPL files fall under under the Win32 DLL (Dynamic link library) file type category.)
- Server manager -> all servers -> right click on server

Server Manager

← → ▾

Server Manager ▸ All Servers

↺ | ▸

Manage Tools View Help

Dashboard

Local Server

All Servers

AD DS

DNS

File and Storage Services ▸

SERVICES

All servers | 1 total

Filter

Server Name	IPv4 Address
WIN-U7B2E0K2V75	192.168.128.130

EVENTS

All events | 12 total

Filter

Server Name	ID	Severity
WIN-U7B2E0K2V75	1014	Warning
WIN-U7B2E0K2V75	1014	Warning
WIN-U7B2E0K2V75	1014	Warning
WIN-U7B2E0K2V75	1014	Warning
WIN-U7B2E0K2V75	5781	Warning

Add Roles and Features

Shut Down Local Server

Computer Management

Remote Desktop Connection

Windows PowerShell

Configure NIC Teaming

Configure Windows Automatic Feedback

Active Directory Administrative Center

Active Directory Domains and Trusts

Active Directory Module for Windows PowerShell

Active Directory Sites and Services

Active Directory Users and Computers

ADSI Edit

Dcdiag.exe

DNS Manager

Dscls.exe

Dsdbutil.exe

Dsmgmt.exe

Gpfixup.exe

Ldp.exe

Netdom.exe

Nltest.exe

Ntdsutil.exe

Repadmin.exe

W32tm.exe

Manage As ...

Start Performance Counters

TASKS ▾

Windows Activation

Not activated

TASKS ▾

9 PM

1 PM

5 PM

9 PM

2 PM

- Now click on configure nic teaming

Windows Server 2012 - VMware Workstation 16 Player (Expired license)

Server Manager

Server Manager ▸ All Servers

NIC Teaming

SERVICES
All Servers | 1 total

Name	Status	Server Type	Operating System Version	Teams
WIN-U7B2E0K2V75.test.local	Online	Physical	Microsoft Windows Server 2012 R2 Standard	0

TEAMS
All Teams | 0 total

Team	Status	Teaming Mode	Load Balancing
------	--------	--------------	----------------


ADAPTERS AND INTERFACES

Network Adapters | Team Interfaces


Adapter	Speed	State	Reason
Available to be added to a team (2)			
Ethernet0	1 Gbps		
Ethernet1	1 Gbps		

WIN-U7B2E0K2V75 1014 Warning Microsoft-Windows-DNS Client Events System 3/8/2023 10:23:19 PM
WIN-U7B2E0K2V75 5781 Warning NETLOGON System 3/8/2023 10:16:22 PM

- Now right click on first network adapter and click on Add to New Team



- Now give Team Name and add another network adapter also



- **Address Hash:** In this mode, a hash is created based on the address components of the packet. This hash is assigned to one of the available adapters, thus creating a reasonable balance across available adapters.
- **Hyper-V Port:** In this mode, the NIC teams that are configured on Hyper-V hosts give independent MAC addresses to Virtual Machines (VMs).

- **Dynamic:** In this mode, the outbound loads are distributed based on the TCP port and IP address. This mode rebalances loads in real-time to ensure that a given outbound flow moves back and forth between team members.