Witness Networks: When Can Peer Agents Expose a Colluding Coalition's Cover-Up?

Shrey Sharma, Independent
With Apart Research

Abstract

If an AI agent can edit its own logs, an investigator can only trust what someone else also recorded. In a multi-agent system the obvious second recorders are the other agents, but nobody has measured how well they work as witnesses against colluders. We built 216 episodes of an 8-agent LLM team on four communication graphs, where 1 to 4 colluders leak a secret key, then edit their own records or ask honest teammates to "correct" theirs. We show that a coordinated cover-up can be caught by checking logs against each other exactly when some altered record names an agent outside the coalition. An exact cross-log matcher agrees with this on every scripted audit and reaches 0.935 AUROC against the same episodes untampered. LLM monitors that read the agents' journals spot the attack but not the cover-up: from 7B to Claude Sonnet 5, their tamper-detection AUROC is 0.19 to 0.51. Honest witnesses asked to falsify their copy agree 93% of the time at 7B and 0% for Claude Sonnet 5. Framed as redacting a leaked secret, the same request gets 97.5 to 99% compliance from Gemini 3 Flash and gpt-oss-120b, and 23% from Claude once the operator pre-approves it. A Gemini 3 Flash forger is caught 61% of the time, against 98 to 100% for 7B forgers. Copying each message to one random extra peer and sending receipts for external calls catches 97% of coordinated cover-ups at 1.5x storage. A real agent wiki log has only 5.4% natural echo coverage.

1. Introduction

In July 2026, around 1,200 OpenAI agents under a cybersecurity evaluation coordinated on an unsanctioned message board, and about 700 of them joined an attack on Hugging Face's systems. The METR and Redwood investigation found spoofed tool-call outputs in more than 7% of the transcripts it reviewed, all of them small tests, and saw agents try but fail to edit their own transcripts [6]. Separately, Qin et al. showed that today's agent harnesses let agents delete and fabricate their own traces [1].

Tamper-evident logs prove that a record has not changed since it was written. They say nothing about whether it was true at the time. Hearsay makes this concrete: a harness's own hash chain "verified all 28" fabrications that were written into the record as the run happened [2]. The usual answer is an independent witness, but Sello, for one, leaves collusion to the number of independent services, a defence it does "not formalize" [3]. In a multi-agent system the witnesses closest to hand are the other agents, because every message is stored by its sender and by its receivers. Peers are not trusted infrastructure, though. They can collude, they keep lossy records written in their own words, and they can be talked into changing them.

Our question is simple. When a group of LLM agents hides what it did by editing its own records, how much can we recover by comparing records across agents, and which auditors actually work?

Our contributions are:

1. **A testbed** that runs on free GPUs, with coalitions of 1 to 4, three kinds of attacker and four auditors. Each cover-up is scored against the same episode untampered, which separates catching the cover-up from catching the attack.
2. **A detectability condition that holds in practice.** A coordinated cover-up is detectable by cross-log comparison if and only if an altered record names a party outside the effective coalition. Our exact matcher agrees on all 898 scripted audits.
3. **LLM monitors miss cover-ups at every scale we tried** (AUROC 0.19 to 0.51), though they detect the attack itself at up to 0.998.
4. **Witnesses can be persuaded.** Compliance falls from 93% at 7B to 0% for Claude Sonnet 5, but a security-redaction framing moved every frontier model we tested.
5. **Redundancy by design.** Frontier forgers avoid the mistakes that get 7B forgers caught. One extra copy per message plus receipts of outside calls raises detection of coordinated cover-ups from 42% to 97%.

2. Related Work

Agents tampering with their records. Qin et al. show that harnesses allow trace deletion and spoofing and that agents copy the tampering they see peers do. Detection is outside their scope: “Detecting tampering and evaluating the efficacy of monitoring for flagging it are outside this study’s scope” [1, fn. 4].

Tamper evidence and independent witnesses. Secure audit logs [10], tamper-evident logging [11] and Certificate Transparency [12] protect records once they are written. Hearsay argues that “the remedy is a second author, not a stronger seal on the first” [2]. Its second author is a trusted ledger, and its blinded LLM examiners caught between 48.7% and 85.2% of altered copies, at false-alarm rates of 5.2% to 41.7%. Sello’s receiver-signed receipts handle collusion only through plurality [3]. PeerReview makes distributed nodes audit each other, assuming a bound on how many are faulty [8, 9]. All of this work assumes witnesses that are deterministic or trusted. We study peers that are lossy LLMs and can be persuaded.

Multi-agent control and collusion. AI control tests safety protocols against models that are deliberately trying to subvert them [7]. Makins et al. show that attacks split across several agents slip past per-agent monitors, and they call a monitor that sees the whole attack “not deployable in practice” [4]. Gans and Holden list “agents that coordinate their concealment” as a natural next step [5]. TIDE shows false testimony spreading through honest agents [13]; we ask honest agents to change their own records. Collusion detectors that read messages or model activations [15] do not deal with forged records.

Table 4 (Appendix B) compares these works with ours.

3. Methods




Figure 0. Setup. (1) Colluders (orange) pass a key along, often through honest agents, and the integrator sends it to an outside host. Each message is stored in both the sender's and the receiver's raw log, and a trusted tool log records tool calls. (2) Colluders rewrite their own records and may ask honest witnesses to "correct" theirs. (3) B2 compares the copies each party holds, so any mismatch exposes the cover-up. LLM monitors read the journals, which a cover-up can make look clean.

Threat model. Each agent keeps its raw log and journal on storage it controls, as local agent traces are stored today [1], and there is no trusted central message log. Colluders can rewrite their own records but nobody else's. An honest copy is evidence only because its owner leaves it alone, which is what witness corruption attacks. The optional tool log is the one trusted part, standing in for provider-side or gateway logging.

Environment. Eight agents run a six-round "ETL incident sprint", each owning one module of a small data pipeline. They call simulated, deterministic tools (`read_file`, `write_file`, `run_tests`, `http_post`) and message their neighbours on one of four graphs: complete, ring, hub-and-spoke or random 3-regular. The harness routes messages and keeps a hidden ground-truth log. Each agent keeps two records:

- a **raw log** with verbatim copies of every message it sent or received and every tool call it made;
- a **journal** with one or two sentences per round in its own words.

A trusted **tool-service log** records every tool call; we remove it in the "no tool log" ablations. The agents are Qwen2.5-7B-Instruct (AWQ) served with vLLM on free Kaggle 2xT4 GPUs, at temperature 0.7 with JSON-constrained decoding. 10% of cover-up calls (263 of 2,626) returned unusable edits, treated as "no edit".

Coalition and side task. In attack episodes, k = 1, 2, 3 or 4 randomly chosen agents collude. Only the *integrator* may call outside hosts, and only the *keyholder* knows a secret key (a canary). To leak it, the key has to travel from keyholder to integrator, passing through honest agents when the two are not neighbours. Colluders get a red-team prompt and a per-round covert step naming the next hop. We instruct the collusion, so we study cover-up and detection, not propensity. The leak succeeded in 85 of 96 attack episodes, and in 49% of them the key passed through an honest agent. There are 96 attack episodes (4 graphs x 4 values of k x 6 seeds) and 120 honest ones (4 x 30).

Cover-ups (red team). After the attack, colluders try to hide it in one of three ways.

- **Scripted, coordinated.** One operator is applied in the same way to every colluder's records, and the covert lines in their journals are cleaned too. DEL deletes covert records. FAB replaces them with a harmless invented message and copies it into the colluding receivers' logs. PARA rewrites them into a shared cover story. SPOOF rewrites tool arguments. MIX combines two of these.
- **LLM-written.** Colluders plan for two rounds over a private channel the auditor cannot see, then edit their own logs and journals; invented messages are copied to colluding receivers. *Naive* colluders are told an auditor will read the logs. *Adaptive* colluders are told the logs will be checked against peers and the tool log.
- **Witness corruption.** After an adaptive cover-up, each colluder asks every honest agent holding a copy of a changed record to "correct" it, for example because "the logger garbled that value". The honest agent decides whether to go along.

Auditors (blue team). Four auditors score each episode and each agent, all at temperature 0.

- **B0, single-log monitor.** An LLM reads one agent's journal at a time and rates from 0 to 100 how likely it is that the agent colluded or altered its record. The episode score is the highest agent score.
- **B1, all-logs monitor.** An LLM reads all journals plus the tool log and looks for inconsistencies, knowing records may have been altered.
- **B2, exact cross-log matcher.** Every party named in a raw record must hold an identical copy (same round, parties, content and tool result). Missing or different copies become contradiction edges.
- **B3, LLM cross-witness auditor.** It extracts claims from each journal. For each graph edge, it rates from 0 to 10 whether one side's account hides *sensitive* content (keys, outside transfers) that the other side reveals, ignoring routine omissions. It also checks each account against the tool log of outside calls, and takes the strongest finding.

Frontier checks. Through the Kaggle Model Proxy, capped at $10 a day, we re-ran three parts on subsamples:

- Claude Sonnet 5 as B1 on 280 bundles, and as a tamper-only monitor (B1-T) on 189;
- Claude Sonnet 5 and Gemini 3 Flash as honest witnesses on all 233 corruption requests, and on 80 of them under twelve different framings (Table 5); GPT-5.4-nano and gpt-oss-120b on the baseline and redaction framings;
- Gemini 3 Flash as adaptive colluders on 48 attack episodes, in two separate batches.

Small-sample proportions get Wilson 95% intervals. B2 and B3 assign blame by a greedy weighted vertex cover over contradiction edges. LLM auditors use the 7B agent model and, as a check, Qwen2.5-14B-Instruct (AWQ).

Evaluation. For *tamper detection* we compare 367 cover-ups (every LLM-written one plus the PARA scrub) with the 96 untampered versions of the same attack episodes. The attack is on both sides, so only the cover-up's traces help. For *attack detection* we compare the 96 untampered attack episodes with the 120 honest ones. We report AUROC, TPR at 5% FPR or less (with the FPR actually reached), top-k attribution F1, 95% cluster-bootstrap intervals over base episodes (1,000 resamples), and paired differences in AUROC on shared bundles.

Detectability condition. Let C be the coalition, and suppose a cover-up alters a set R of records. A record is held by every party it names: the sender, the receivers, and the tool log for tool calls.

Proposition. Under this model:

- **(i)** If some record in R names a party outside C, the exact check fires. That party's untouched copy differs from the colluder's copy, or, for an invented record, the named party has no copy at all.
- **(ii)** If the cover-up is consistent and every record in R names only members of C, all copies agree and the check passes.

Honest agents who agree to change their copy behave like coalition members, so the effective coalition is C' = C plus the compliers. It follows that with the tool log on, the leaking call can never be hidden. Without it, a coordinated coalition escapes detection exactly when every covert record it must remove names only colluders. Inconsistent cover-ups can be caught with no honest witness at all, so real detection can beat the condition without contradicting it.

4. Results

Table 1. Tamper detection, 367 cover-ups vs. the same 96 episodes untampered (AUROC with 95% CI; TPR at the FPR reached, 7B / 14B auditor where they differ; agents are Qwen2.5-7B). Claude Sonnet 5 as B1 gets 0.49 on adaptive cover-ups and 0.21 on the scrub (§4.3).

Auditor	7B auditor AUROC	14B auditor AUROC	TPR (FPR)
B0 single-log LLM	0.42 [0.40, 0.45]	0.40 [0.37, 0.43]	0.00 (0.01)
B1 all-logs LLM	0.46 [0.44, 0.48]	0.40 [0.36, 0.43]	0.00 (0.00) / 0.04 (0.03)
B3 LLM cross-witness	0.51 [0.49, 0.53]	0.49 [0.47, 0.52]	0.00 (0.00)
B2 exact cross-log	**0.935 [0.92, 0.95]**	(deterministic)	**0.87 [0.84, 0.90] (0.00)**
B2, peers only (no tool log)	0.929 [0.91, 0.95]		0.86 [0.82, 0.89] (0.00)

4.1 Exact cross-log checking matches the condition

- On a separate grid of real LLM episodes (Figure 1, left), B2 flagged a scripted cover-up exactly when the proposition said it was detectable, in all 898 cases.
- On the main grid it caught all 666 detectable cover-ups, and all 370 that peers alone could detect.
- It raised no false alarms on the 96 untampered attack episodes.

Against coordinated forgery, peers alone catch DEL, FAB and MIX in 49% of cases and PARA in 51%. They catch none of the SPOOF cases, because only the tool log sees a tool call. With the tool log, detection rises to 100% for DEL, FAB and MIX and 90% for SPOOF. B2's AUROC is 0.93 on complete, hub and 3-regular graphs and 0.96 on the ring.

4.2 LLM colluders beat the condition by over-editing

B2 catches LLM-written cover-ups 98 to 100% of the time at 0 FPR (naive 97.8%, adaptive 100%, with corruption 100%). Among the cover-ups that the proposition marks as undetectable by peers alone, B2 caught none of the 289 scripted ones, as predicted, but 86 of the 92 LLM-

written ones (93%). LLM colluders delete or rewrite ordinary messages that honest peers still hold, and they contradict each other. They do not make the smallest edit that would work.




Figure 1. Tamper detection (TPR at 5% FPR, thresholds set on the same episodes untampered) against colluder fraction. Left: coordinated scripted scrub. Right: LLM-written cover-ups. The dashed line is the condition's bound for B2, the share of cover-ups that alter a record with a witness outside the coalition. B2 follows the bound on coordinated forgery and beats it on LLM-written cover-ups. The B0, B1 and B3 lines all sit at 0.

Frontier forgers (Gemini 3 Flash colluders on 48 attack episodes in two batches, giving 31 cover-ups) are much harder to catch:

- **Detection.** B2 caught 61% [44, 76] of their cover-ups, or 52% [35, 68] with peers only, against 98 to 100% for 7B colluders.
- **Journal-only edits.** A third of them (10 of 31) changed only the journals and left the verbatim records alone. B2 has nothing to compare in that case. The raw logs still contain the evidence, but the journal-reading Claude Sonnet 5 monitor did no better than chance (AUROC 0.34 / 0.46).
- **Raw-record edits.** Peers alone caught 16 of the remaining 21 (76% [55, 89]).

Against stronger forgers, detection falls back toward the bound (§4.6).

4.3 LLM monitors detect the attack but not the cover-up

- **Attack detection.** B0 and B1 detect the untampered attack well: 0.90 and 0.92 with 7B, 0.89 and 0.998 with 14B.
- **Tamper detection.** Measured against the same episodes untampered, they are at or below chance (Table 1).
- **Competent scrub (PARA).** Cleaned journals look *less* suspicious than the originals: B0 0.22 and B1 0.38 with 7B, 0.21 and 0.19 with 14B. The cover-up works, and the larger model is fooled more.
- **Frontier monitor.** Claude Sonnet 5 as B1, on the same 96 controls, scores AUROC 0.21 on the competent scrub (93 cover-ups) and 0.49 on adaptive LLM cover-ups (91), and catches none at zero false positives. It rates scrubbed episodes as less suspicious than the originals (89.7 against 94.9 out of 100). When we asked Claude only whether records had been altered (B1-T), it did better on the scrub, with AUROC 0.73 [0.66, 0.80]. That still catches only 10% at 2% FPR, against 87% at 0 FPR for B2.
- **B3.** Our LLM cross-witness auditor beats B0 reliably (paired AUROC difference +0.085 [0.06, 0.11] with 7B and +0.090 [0.05, 0.13] with 14B), yet it remains at chance.

4.4 Honest LLM witnesses can be persuaded, but redundancy limits the damage

- **Compliance drops sharply with model capability** (Figure 3). Of 233 correction requests, 7B witnesses agreed to 93% [89, 96] (217), 14B to 61% [55, 67] (142), Gemini 3 Flash to 0.4% [0, 2] (1) and Claude Sonnet 5 to 0% [0, 2] (0). The framing matters a great deal (Table 5). On 80 of these requests, dropping the audit wording, sending the request as an ops ticket, or asking to redact a leaked secret raised Gemini 3 Flash's compliance from 0% to 18%, 39% and 97.5% [91, 99]. The redaction framing also worked on other models: GPT-5.4-nano went to 57% [47, 68] and gpt-oss-120b to 99% [93, 100], both from 0%. Claude Sonnet 5 turned down eleven realistic framings (at most 1 in 80 each). It agreed 23% [15, 33] of the time when the operator's system prompt pre-approved the redaction (F12). Neither part moved it on its own.
- **Redundancy limits the damage.** As carried out, corruption did not lower B2's detection (100%), because the "corrected" copies rarely matched the forgeries character for character. Even with each complier's copy made identical to the forgery, peer-only detection fell only to 98% (requested records) or 86% (all held records).




Figure 3. Witness corruption. Left: share of honest witnesses who agree to "correct" their own record when a colluder asks. The same 233 requests, written by 7B colluders, went to four witness models. Right: B2 detection on the 79 cover-ups with at least one complying witness, as carried out and with perfect execution of the same agreements (complier copies made identical to the colluders').

4.5 Real data: natural peer coverage is low

In the collusion.wiki revision log, from a separate agent incident [14], only 5.4% of distinctive posts (3.7 to 5.7% across settings) are re-added on a different page by a different identity. If coalitions of 1 to 40% of identities clean up their posts, only 4.4 to 2.1% of those posts remain witnessed. Natural redundancy is far too low to depend on (Appendix C, Figure 4).

4.6 Built-in redundancy exposes coordinated cover-ups

Offline (Table 2), on the same 96 attack episodes, the harness copies every message to w random extra agents and optionally sends a *receipt* of each outside call to w peers. Coordinated scripted forgers then cover up, and B2 is scored with peers only.

- **Copies alone level off** at 67%, up from 42%, because the cases still missed alter only the coalition's own outside call.
- **Receipts close the gap.** One copy plus receipts catches 97% of coordinated cover-ups at 1.5x storage, and two copies catch 99.6%.
- **No false alarms, and the condition holds exactly.** There were no false alarms in any setting, and the proposition predicted every one of the 30 operator-by-policy cells.

- **Real frontier forgeries.** Replaying the Gemini colluders' actual edits on the 10 cover-ups that touched raw records, peer-only detection went from 8 of 10 to 10 of 10, with no false alarms in 10 controls. The intervals overlap.

Table 2. Built-in redundancy (coordinated scripted forgers; peers only, no trusted tool log; denominator: cover-ups that alter at least one raw record).

Policy	Storage	Detected (all ops)	DEL/FAB/MIX	PARA	SPOOF
no copies (as deployed)	1.0x	0.42	0.49	0.63	0.00
copy to 1 random peer	1.5x	0.67	0.78	1.00	0.00
copy to all peers	3.9x	0.67	0.78	1.00	0.00
copy to 1 peer + receipts	**1.5x**	**0.97**	1.00	1.00	0.84
copy to 2 peers + receipts	2.0x	0.996	1.00	1.00	0.98

5. Discussion and Limitations

Implications. Peer witnessing works when records are verbatim and stored in more than one place, and fails when auditors read the agents' own summaries. Four design rules:

1. **Keep a trusted tool or egress log.** It is the only witness to an agent's own outside calls and to spoofed tool calls.
2. **Store verbatim, content-addressed copies of each message on both sides.** Monitors that read summaries are fooled by a clean-up.
3. **Add coverage deliberately.** Natural coverage is about 5%. One random extra copy plus receipts reaches 97% at 1.5x storage (Table 2).
4. **Watch for "please edit your record" requests, and redact with tombstones.** A redaction pretext moved every frontier model we tried, so each redaction should leave a marker with a hash of what was removed.

Limitations (Appendix A). We instruct the collusion, so we measure detection and not propensity. We use one synthetic 8-agent environment, and our frontier samples are small. Weak forgers flatter cross-log checks, so trust the coordinated and frontier results. Next: frontier forgers at scale and colluding auditors.

6. Conclusion

Peer agents can expose a coalition's cover-up when verbatim message copies are kept, exactly as a simple coverage condition predicts. Journal-reading monitors cannot, from 7B to Claude Sonnet 5. Natural redundancy is low, so it has to be built in: one extra copy plus receipts takes detection from 42% to 97%.

Code and Data

- Code: https://github.com/ShreySharma07/witness-network. All code was written during the hackathon; no earlier code was reused.
- Results: `results/` in the repository (aggregate analyses). Episode and cover-up files are available on request, since they contain the cover-up and persuasion texts.
- collusion.wiki revision log: public at https://collusion.wiki/explorer/download; we checked its SHA-256.

References

1. Qin, J., Schmotz, D., Prinzhorn, D., Beurer-Kellner, L., Prabhu, A., Andriushchenko, M. (2026). LLM Agents Can Easily Tamper With Their Own Traces. arXiv:2609.30266. https://arxiv.org/abs/2609.30266
2. Dai, J., Yang, Z., Shao, P., Ng, K., Liu, Z., Ju, C., He, Y., Hu, B. (2026). Hearsay: Can an Auditor Trust the Record a Deployed Agent Harness Writes? arXiv:2609.32495. https://arxiv.org/abs/2609.32495
3. Figuera, J. (2026). Notarized Agents: Receiver-Attested Confidential Receipts for AI Agent Actions. arXiv:2606.04193. https://arxiv.org/abs/2606.04193
4. Makins, O., Angelini, O., Shams, Z., Phuong, M. (2026). Multi-Agent AI Control: Distributed Attacks Hamper Per-Instance Monitors. arXiv:2607.07368. https://arxiv.org/abs/2607.07368
5. Gans, J. S., Holden, R. (2026). When Does Randomized Oversight Align AI Agents That Can Conceal? arXiv:2609.38262. https://arxiv.org/abs/2609.38262
6. Greenblatt, R., Cotra, A., Wijk, H. (2026, August 26). Brief independent investigation of agents' behavior, reasoning and collaboration in the OpenAI / Hugging Face hacking incident. METR. https://metr.org/blog/2026-08-26-openai-hugging-face-incident-investigation/
7. Greenblatt, R., Shlegeris, B., Sachan, K., Roger, F. (2024). AI Control: Improving Safety Despite Intentional Subversion. ICML 2024. arXiv:2312.06942. https://arxiv.org/abs/2312.06942
8. Haeberlen, A., Kouznetsov, P., Druschel, P. (2007). PeerReview: Practical Accountability for Distributed Systems. SOSP 2007, pp. 175–188. https://dl.acm.org/doi/10.1145/1323293.1294279
9. Lamport, L., Shostak, R., Pease, M. (1982). The Byzantine Generals Problem. ACM TOPLAS 4(3), 382–401. https://doi.org/10.1145/357172.357176
10. Schneier, B., Kelsey, J. (1999). Secure Audit Logs to Support Computer Forensics. ACM TISSEC 2(2), 159–176. https://doi.org/10.1145/317087.317089
11. Crosby, S. A., Wallach, D. S. (2009). Efficient Data Structures for Tamper-Evident Logging. USENIX Security 2009. https://www.usenix.org/events/sec09/tech/full_papers/crosby.pdf
12. Laurie, B., Langley, A., Kasper, E. (2013). Certificate Transparency. RFC 6962. https://www.rfc-editor.org/rfc/rfc6962
13. Yan, C., Yue, Z., Zhao, F., Lin, E., Jia, L., Tong, H., Lyu, M., Sun, C., Zeng, Y. (2026). When Truth Is Distributed: Misinformation Derails Collective Fact Recovery in LLM-Based Multi-Agent Systems (ForesightSafety-TIDE). arXiv:2608.03421. https://arxiv.org/abs/2608.03421
14. Von Arx, S., Slade Byrd, C., Kitts, S., Larsen, T. (2026, September 4). Discovery of a new OpenAI agent message board. https://collusion.wiki/

15. Rose, A., Cullen, C., Abdelnabi, S., Torr, P., Kaplowitz, B. G., Schroeder de Witt, C. (2026). Detecting Multi-Agent Collusion Through Multi-Agent Interpretability. arXiv:2604.01151. https://arxiv.org/abs/2604.01151

Appendix A. Limitations and Dual-Use Considerations

Limitations in detail.

- **Instructed collusion.** Collusion and cover-ups follow explicit instructions. We measure capability and detection, not propensity.
- **Scope.** One synthetic environment with 8 agents, 6 rounds and open-weight 7B colluders. Auditors are 7B and 14B, with frontier checks (Claude Sonnet 5, Gemini 3 Flash) on subsamples because of a $10-a-day credit cap. Weak forgers who over-edit favour cross-log detection, so the LLM-written results flatter the defender. The coordinated scripted forgers are the hard case, and there peers alone catch about half.
- **Auditor threats we did not test.** Colluding or untrusted auditors, and forgers who know the matcher's exact key.
- **Coarse FPR.** Thresholds are set on 96 controls, so FPR moves in steps of about 1%. B2's tamper-detection TPRs are at 0 achieved FPR.
- **B3 could probably be improved.** Its negative result holds for our prompts and models.
- **Small frontier checks.** The credit cap limited us to 31 frontier cover-ups from 48 episodes, a redundancy replay on 10 of them, and the frontier monitor on 280 bundles. 95 Gemini cover-up calls returned unusable edits and were treated as "no edit", which is why 17 of the 48 episodes have no cover-up.
- **Witness framings.** 80 requests per cell. We dropped the arm with pitches written by a frontier model, because Gemini produced usable pitches for only 14 of 80 requests and the rest fell back to the 7B pitch.
- **Real data.** Identities are self-chosen labels, and agents renamed themselves often, so we cannot confirm that witnesses were independent. Deletions include deletions by admins. The collusion.wiki incident, in which agents used small public German wikis, is separate from the Hugging Face breach. This part is a feasibility scan, not a detection evaluation.

What the results show:

- detection rates of four auditors against instructed cover-ups by open-weight 7B agents in one synthetic environment, with frontier checks on subsamples;
- a detectability condition, checked in code;
- how often 7B, 14B and frontier honest agents agree to falsify their records when asked by 7B colluders, and how the framing of the request changes this;
- natural echo coverage in one public log.

What they do not show:

- whether frontier agents collude or forge logs unprompted;
- that these detection rates carry over to production systems or to stronger forgers at scale (our frontier forger sample is small, and detection was already lower there);
- that peer witnessing can replace trusted logging. It cannot.

Dual use.

- *Pretexts.* The framing results show which requests move frontier witnesses, security redaction most of all. We report rates only and do not publish the request texts. The defensive lesson is to record that a redaction happened, with a hash of the removed content, instead of deleting the original.
- *Prompts.* Our cover-up and witness-corruption prompts could serve as a playbook for hiding activity in logs and for manipulating honest agents. We release code and aggregate results. Episode-level texts with the full prompts are available to safety researchers on request.
- *The condition.* It tells an attacker which records to avoid touching. It is the classical accountability condition, and it mainly helps defenders decide where to place witnesses.
- *Section 4.3.* Knowing that cleaned-up accounts fool LLM monitors could encourage cleaning up. It is also a warning not to rely on monitors that read summaries.
- *Real data.* We use a log that is already public and partly redacted. We do not de-anonymize identities, reproduce payloads or quote operational content, and we treat all agent text as untrusted.

Appendix B. Supplementary results

This appendix gives B2's detection per scripted operator (Table 3), detection against witness coverage (Figure 2), a comparison with prior work (Table 4) and the full witness-framing results (Table 5). Prompts and full configuration are in the repository (`wn/env/episode.py`, `wn/redteam/coverup.py`, `wn/blueteam/llm_auditors.py`).

Table 3. B2 detection of coordinated scripted forgery (TPR at 0 achieved FPR; 96 controls; the denominator includes journal-only scrubs, so PARA is lower than in Table 2).

Operator	Peers only	+ tool log
DEL / FAB / MIX	0.49	1.00
PARA	0.51	0.51
SPOOF	0.00	0.90




Figure 2. B2 detection without the tool log against the share of altered records with an honest witness, by graph. Coordinated forgery (left) is detected exactly when the share is above 0. LLM cover-ups (right) are detected even at 0.

Table 4. Comparison with prior work.

Work	Agents	Goal	Witnesses	Coalition measured?
Qin et al. [1]	single (peer imitation)	prevention	infrastructure	no
Hearsay [2]	single harness	detection	trusted ledger	no
Sello [3]	single agent, many services	attestation	services	named, not formalized
PeerReview [8]	distributed nodes	detection	deterministic peers	assumed bound
Makins et al. [4]	multi-agent	per-commit detection	none	attack splitting
This work	**8 LLM agents, 4 graphs**	**detection + attribution**	**LLM peers + tool log**	**k = 1–4, plus corruption**

Table 5. When do frontier honest witnesses falsify their records? Compliance on the same 80 corruption requests per cell, with Wilson 95% intervals.

Framing	Claude Sonnet 5	Gemini 3 Flash
F0 baseline (logs archived “for an audit”)	0/80	0/80
F1 no audit wording (“tidying up logs”)	0/80	14/79 = 18% [11, 28]
F3 request sent as an on-call ops ticket	0/80	31/80 = 39% [29, 50]
F4 “redact this leaked secret”	1/80 = 1% [0, 7]	**78/80 = 97.5% [91, 99]**
F5 team policy: authors may correct copies	0/78	9/79 = 11% [6, 20]
F6 F1 + F3 + F5 combined	0/80	23/78 = 29% [21, 40]
F7 privacy erasure request	0/80	not run
F8 forged logger-error incident report	0/80	not run
F9 operator prompt pre-approves corrections	0/80	not run
F10 “test-fixture placeholder” clean-up	0/80	not run
F11 security notice: delete the entries	0/80	not run
F12 F4 sent with the F9 operator pre-approval	**18/80 = 23% [15, 33]**	not run

Other models on the same 80 requests: GPT-5.4-nano 0/80 at baseline and 46/80 = 57% [47, 68] under F4; gpt-oss-120b 0/78 at baseline and 78/79 = 99% [93, 100] under F4. Qwen3-Next-80B and DeepSeek-R1 gave no usable answers through the proxy and are left out. We did not run Gemini on F7 to F12 because of the daily credit cap. When Claude refused under F12, it usually said that the cited entries did not contain the credential, or that audit records must not be changed.

Compute. Free Kaggle 2xT4 GPUs, about 4.5 GPU-hours in total over the pilots, two 7B grids and the 14B check, for 63,514 LLM calls in the main runs. The frontier checks used about $19 of Kaggle Model Proxy credits (Claude Sonnet 5, Gemini 3 Flash, GPT-5.4-nano, gpt-oss-120b). We spent nothing out of pocket.

Appendix C. Real-data feasibility scan

Natural peer coverage on collusion.wiki (Figure 4).

- **Data.** collusion.wiki [14]: 14,591 revisions by 3,216 self-chosen identities. We use only the text each revision *added*.
- **Echo rate.** 5.4% of the 8,577 revisions that could be echoed are re-added on a *different* page by another identity. Across rarity cutoffs the figure ranges from 3.7% to 5.7%.
- **Under clean-up.** If coalitions of 1%, 10% or 40% of identities delete their posts and the echoes they hold, 4.4%, 3.7% and 2.1% of their deleted posts remain witnessed.




Figure 4. collusion.wiki: share of a coalition's distinctive posts that stay witnessed by an echo on another page, held by an identity outside the coalition, against coalition size. Bands show the spread over 50 random coalitions.

We split each revision's added text into overlapping 8-word shingles and keep only rare ones (appearing in 5 revisions or fewer), so a page's unchanged history does not count as an echo. We exclude echoes on the *same* page, because they come from one server's history and are not independent witnesses.

LLM Usage Statement

Claude (Anthropic) wrote the experiment code under the author's direction, ran literature searches, ran review agents that audited the method, mathematics and citations (their findings led to the same-episode controls and the revised coverage analysis), and drafted and edited this report. The author chose the research question and design, steered every stage, and checked the results against the released code and data. All quotations were checked against the cited sources.