The Global V2X Ecosystem: Technical Architectures, Regulatory Frameworks, and Deployment Strategies for Intelligent Transportation

Chapter 1: The Foundations of Vehicle-to-Everything (V2X) Communication

Vehicle-to-Everything (V2X) technology constitutes the fundamental communication layer of the next-generation Intelligent Transportation System (ITS). It represents a paradigm shift from autonomous vehicle intelligence, which relies on local sensor suites, to cooperative intelligence, where road entities share a collective environmental model.[1] At its core, V2X is a multipoint-to-multipoint communication framework designed to facilitate the exchange of high-fidelity, time-sensitive data between vehicles, infrastructure, and other road users.[1] This connectivity operates as a "wireless sensor" with 360-degree, non-line-of-sight (NLOS) capabilities, effectively extending the vehicle's "digital horizon" by a factor of two to three compared to traditional sensors like cameras, radar, and LiDAR.[1]

The V2X taxonomy is categorized by the specific actors involved in the communication exchange. Vehicle-to-Vehicle (V2V) communication enables the direct transmission of status data, such as speed, position, and heading, between adjacent vehicles to support safety critical applications like collision avoidance.[1] Vehicle-to-Infrastructure (V2I) involves the bidirectional exchange of information with roadside equipment, such as traffic signal controllers and work zone warning trailers.[1] Vehicle-to-Network (V2N) leverages cellular infrastructure (4G LTE or 5G) to connect vehicles to cloud-based management platforms for long-range traffic coordination and software-defined vehicle updates.[1] Vehicle-to-Pedestrian (V2P) addresses the safety of vulnerable road users (VRUs) by integrating pedestrians and cyclists into the cooperative awareness loop via smartphones or wearable devices.[1] Emerging sub-categories such as Vehicle-to-Home (V2H) and Vehicle-to-Grid (V2G) further extend this ecosystem into the energy sector, enabling bidirectional charging and load balancing for the electrical grid.[1]

The Role of Cooperative Intelligence in ADAS

While modern Advanced Driver Assistance Systems (ADAS) utilize an "ego-centric" sensing model—relying on onboard hardware to interpret the immediate surroundings—V2X introduces "cooperative awareness".[2] This cooperative layer addresses inherent limitations in traditional sensing. Cameras are susceptible to occlusion, glare, and adverse weather

conditions; radar and LiDAR are limited by line-of-sight and physical obstructions.[1] V2X radio signals, particularly in the 5.9 GHz band, can penetrate obstacles, providing the vehicle with the ability to "see" through large trucks or around blind corners.[1] This capability is instrumental in supporting complex safety scenarios such as Intersection Movement Assist (IMA) and Emergency Electronic Brake Light (EEBL) warnings, where the critical event occurs beyond the field of view of the primary driver or onboard cameras.[1]

Feature	Onboard Sensors (Camera, Radar, LiDAR)	V2X Communication
Operational Range	100-250 meters (Line-of-Sight)	Up to 1,000 meters (NLOS support) [2]
Environmental Dependency	High (Weather, Lighting, Dust)	Low (Radio frequency resilience) [1]
Information Depth	Raw physical data requiring processing	Pre-structured semantic data (Position, Speed) [1]
Object Recognition	Inference-based (AI/ML interpretation)	Direct self-reporting from other entities [1]
Latency	Local processing delay	Transmission and network latency (1-10 ms) [1]

The integration of V2X into the ADAS "brain" allows for a multi-layered approach to safety. By combining sub-meter accuracy landmarks from 3D HD maps with real-time V2X status updates, vehicles can achieve a level of situational awareness necessary for Level 4 and Level 5 autonomy.[2] This synergy is projected to reduce the frequency and severity of crashes significantly, with pilot data suggesting equipped routes experience a crash rate reduction of over 50% compared to non-equipped corridors.[3]

Chapter 2: Communication Standards: DSRC vs. C-V2X

The technological foundation of V2X has been the subject of an intensive global debate between two primary radio access technologies (RATs): Dedicated Short-Range Communication (DSRC) and Cellular Vehicle-to-Everything (C-V2X).[7] DSRC, the legacy standard, is rooted in the IEEE 802.11p specification, a modification of the Wi-Fi protocol

adapted for the high-mobility vehicular environment.[7] Developed over two decades, DSRC provides a mature, contention-based communication method that facilitates direct short-range exchanges (typically 300 to 1,000 meters) without the need for a central network coordinator.[7]

C-V2X, standardized by the 3rd Generation Partnership Project (3GPP) starting with Release 14, represents a modern alternative that leverages cellular technology for both direct and network-based communication.[7] C-V2X offers two distinct interfaces: the PC5 (sidelink) interface for direct, low-latency communication between road entities in the 5.9 GHz band, and the Uu interface for communication through cellular base stations.[2] Unlike the contention-based mechanism of DSRC, C-V2X employs a more structured resource allocation strategy, which tends to provide superior range, reliability, and interference resilience, particularly in high-density urban or highway environments.[2]

Technical Specification Comparison

The performance characteristics of these two technologies differ significantly in terms of link budget, latency, and throughput. C-V2X benefits from advanced channel coding techniques and transmit diversity, allowing for reliable packet delivery at distances nearly double those of legacy DSRC.[2]

Metric	Dedicated Short-Range Communication (DSRC)	Cellular Vehicle-to-Everything (C-V2X)
Standardization	IEEE 802.11p (WAVE/ITS-G5)	3GPP Rel 14/15 (LTE) & Rel 16+ (5G) [7]
Communication Mode	Ad-hoc (CSMA/CA)	Scheduled & Sidelink (PC5) [2]
Maximum Range	~300m - 1,000m	Up to several kilometers (with Uu) [7]
Latency	~2-5 ms (Low congestion)	~1-10 ms (Deterministic options) [1]
Throughput (Max)	~27 Mbps [11]	High (Scales with 5G NR) [7]
Mobility Support	High (500 km/h) [10]	High (Optimized for

		high-speed handovers) [10]
Evolution Path	802.11bd (Proposed upgrade)	Direct path to 5G and 6G [8]

The ongoing transition toward C-V2X is driven by its synergy with the broader 5G rollout and its ability to provide a more future-proof architecture.[8] While Europe initially leaned toward the DSRC-based ITS-G5 standard, there has been a significant shift in North America and China toward C-V2X.[7] Simulation studies highlight that in highway scenarios, assigning more channels to DSRC can be efficient, whereas in urban settings, C-V2X's ability to manage complex interference through scheduled resource allocation results in superior performance.[11]

Chapter 3: Regulatory Landscapes and Spectrum Allocation

The governance of the 5.9 GHz spectrum is the most critical regulatory factor influencing V2X deployment. Historically, the Federal Communications Commission (FCC) in the United States allocated 75 MHz (5.850–5.925 GHz) for Intelligent Transportation Systems in 1999, specifically targeting DSRC technology.[7] However, the slow rate of commercialization and the emergence of competing technologies led to a comprehensive reassessment of the band's utility.[14]

In a landmark decision finalized in early 2021 and codified in the Second Report and Order (Second R&O) effective February 11, 2025, the FCC repurposed the 5.9 GHz band.[14] The lower 45 MHz was opened for unlicensed indoor use (such as Wi-Fi 6), while the upper 30 MHz (5.895–5.925 GHz) was dedicated exclusively to ITS using C-V2X technology.[14] This ruling effectively ended the era of DSRC in the United States, establishing a strict sunset date of December 14, 2026, after which DSRC operations will no longer be permitted.[14]

The Transition to C-V2X: Timelines and Rules

The regulatory shift necessitates a massive logistical transition for infrastructure owners and operators (IOOs) who had previously invested in DSRC hardware. The FCC's framework provides a two-year countdown for the removal or replacement of legacy equipment.[15]

Key Date	Regulatory Milestone	Impact on Stakeholders
May 2021	FCC First Report and Order	Repurposed 45 MHz for unlicensed use; retained 30 MHz for ITS.[14]

Feb 11, 2025	Second R&O Effective Date	New C-V2X rules take effect; no new DSRC licenses issued.[14]
July 2025	C-V2X Licensing Begins	Anyone can deploy authorized C-V2X units under technical rules.[16]
Dec 14, 2026	DSRC Sunset Date	Mandatory cessation of all DSRC-based operations in the 5.9 GHz band.[14]

The FCC's technical rules for C-V2X focus on mitigating interference with unlicensed devices and federal incumbent operations (such as Department of Defense radars).[14] These rules specify maximum power levels for On-Board Units (OBUs) and Roadside Units (RSUs), as well as antenna height restrictions for RSUs.[15] Notably, the FCC did not mandate a specific 3GPP release (e.g., Rel 14 vs. Rel 16), instead deferring to industry consensus to determine the appropriate technology standards while emphasizing the need for forward and backward compatibility.[15]

Under the new regime, OBUs are "licensed by rule," requiring no specific individual action from users, while RSUs require site-specific individual licenses to ensure coordination and prevent interference in the shared spectrum environment.[16] This regulatory clarity is expected to catalyze large-scale OEM deployments, as automakers now have a singular, legally protected standard to follow in the North American market.[8]

Chapter 4: Security Credential Management Systems (SCMS)

Trust and privacy are the dual pillars of V2X security. Because vehicles act on safety-critical information from nearby entities—many of whom are unknown—the system must verify that messages are authentic and have not been tampered with.[17] However, this authentication must not compromise the driver's privacy by allowing the tracking of vehicle movements.[17] The solution adopted in North America and Europe is a specialized Public Key Infrastructure (PKI) known as the Security Credential Management System (SCMS).[17]

The SCMS provides a framework for issuing, managing, and revoking digital certificates that act as "credentials" for road users.[17] Every message transmitted by an OBU or RSU is digitally signed using a private key; receiving devices use the sender's public key certificate to verify the signature.[18] To maintain privacy, vehicles do not use a single permanent certificate. Instead, they are issued "pseudonym certificates"—short-term credentials that rotate frequently to prevent an observer from linking a series of messages to a specific vehicle over

time.[17]

SCMS Architecture and Functional Roles

The SCMS is a distributed system designed to prevent any single entity (even an insider at the certificate authority) from being able to track a vehicle. This is achieved through the separation of roles among several logical components.[18]

Component	Description of Logical Role	Relationship to End Entity
Enrollment CA (ECA)	Issues enrollment certificates; acts as the primary "identity" proof.[17]	Initial bootstrapping only.[18]
Registration Authority (RA)	Gateway for certificate requests; validates permissions.[18]	Main point of contact for operational updates.[18]
Pseudonym CA (PCA)	Issues the actual short-term certificates for message signing.[17]	Indirect contact via RA for privacy.[18]
Linkage Authority (LA)	Generates linkage values that enable efficient revocation.[18]	Split into LA1 and LA2 to prevent tracking.[18]
Misbehavior Authority (MA)	Analyzes reports to identify and revoke malicious or faulty devices.[17]	Receives reports from peers in the network.[17]
CRL Generator	Produces the Certificate Revocation List (CRL) for the system.[18]	Broadcasts to all devices via RSUs or satellite.[18]

Advanced Cryptographic Mechanisms

Managing the sheer volume of certificates required for a national fleet is a significant scalability challenge. A typical SCMS design may provide a vehicle with a rolling three-year supply of pseudonym certificates, with approximately 20 certificates per week.[18] To manage this without constant network overhead, the system uses "butterfly keys".[19] This mechanism allows an OBU to submit a single "caterpillar" request, which the RA and PCA expand into

thousands of mathematically unlinkable pseudonym certificates through an automated process.[19]

Revocation is equally complex. Since a single vehicle might have thousands of valid certificates, traditional CRLs would become prohibitively large. The SCMS uses "linkage values" derived from a hash tree.[18] By publishing a single "linkage seed" on the CRL, all future certificates belonging to a specific revoked device can be identified and ignored by other road users, keeping CRL sizes manageable even in a nationwide deployment.[18]

Chapter 5: Application Messages and Use Cases

The utility of V2X is realized through standardized application-layer message sets, primarily defined by the Society of Automotive Engineers (SAE) J2735 and J2945 standards.[2] These standards ensure that regardless of the vehicle manufacturer or software developer, the data transmitted is structured in a way that all other actors can interpret and act upon.[1]

Core V2X Message Types

The V2X environment relies on a suite of messages, each tailored for specific environmental or operational context.[1]

- **Basic Safety Message (BSM):** The workhorse of V2V safety. Broadcast 10 times per second, it contains the vehicle's position, speed, acceleration, and brake status.[2] It allows neighboring vehicles to predict potential collisions even if the driver is unaware.[2]
- **Signal Phase and Timing (SPaT):** Transmitted by traffic signal controllers, it provides the current state of the signal and the time remaining before the next phase change.[1]
- **MAP Message:** Provides the high-definition topology of an intersection, including lane geometry and lane-signal mapping.[1] When combined with SPaT, it enables GLOSA (Green Light Optimal Speed Advisory) applications.[1]
- **Traveler Information Message (TIM):** Used for infrastructure-to-vehicle broadcasts regarding road closures, work zones, or severe weather alerts.[1]
- **Personal Safety Message (PSM):** The V2P equivalent of the BSM, transmitted by pedestrians or cyclists to warn nearby vehicles of their presence.[1]

High-Impact Use Cases

Deployments around the world have demonstrated that V2X can solve specific mobility and safety challenges. In Tampa, Florida, V2V-based Forward Collision Warnings (FCW) reduced conflicts by 9%, while in Georgia, C-V2X school bus priority reduced stops by 40%, significantly decreasing fuel consumption and travel time.[4]

Another high-value application is "platooning," where a lead vehicle (often a commercial truck) communicates with a following vehicle to synchronize braking and acceleration.[1] This

electronic coupling allows for shorter following distances, which reduces aerodynamic drag and fuel use.[5] In Minnesota, state law now permits platooning on freeways, provided vehicles use electronic communication to synchronize speed and a human operator is present in each vehicle.[23]

Chapter 6: Case Study: Minnesota V2X Deployments

The Minnesota Department of Transportation (MnDOT) has established itself as a pioneer in V2X through its Connected and Automated Vehicle (CAV) program.[24] Minnesota's approach is characterized by a focus on "smart infrastructure" and winter weather resilience, recognizing that V2X can provide situational awareness when cameras and lane markings are obscured by snow.[24]

The Connected Corridors: TH-55 and I-394

The cornerstone of Minnesota's V2X effort is the "Connected Corridor" along Trunk Highway 55 (TH-55) and I-394.[21] This foundational project involved equipping approximately 22 traffic signals between I-494 and I-94 with SPaT and MAP capabilities.[22]

The primary application for this corridor is the Snow Plow Signal Priority (SPSP) system.[22] Using DSRC technology, snowplows can request extended green or early green phases at traffic signals.[22] This system addresses several operational challenges:

- **Efficiency:** It improves plowing times and reduces the frequency of heavy vehicles coming to a full stop, which is energy-intensive.[21]
- **Gang Plowing Operations:** In "gang plowing," where multiple plows operate in a staggered formation to clear multiple lanes, the rightmost plow responsible for ramps often falls behind mainline plows due to traffic signals. SPSP helps maintain the integrity of the formation.[22]
- **Safety:** By reducing signal wait times, it minimizes the duration maintenance vehicles spend as stationary or slow-moving obstacles in the travel lane.[22]

Minnesota Automated Shuttle and Transit Pilots

MnDOT has conducted several high-profile automated vehicle demonstrations across diverse urban and rural settings.[21]

Project Name	Location	Duration	Outcomes
Med City Mover	Rochester, MN	12 Months	Over 3,000 passengers carried;

			studied pedestrian-AV interactions in a dense urban core.[21]
goMARTI	Grand Rapids, MN	27 Months	Rural on-demand shuttle service; 18,000+ passengers; addressed mobility for seniors and disabled residents.[21]
Bear Tracks	White Bear Lake, MN	12 Months	Focused on all-weather operations, specifically winter durability and sensor performance in snow.[26]
Smart Snelling	St. Paul, MN	Ongoing	Testing snowplow priority alongside connected cycle and pedestrian alerts.[26]

These projects have allowed MnDOT to gain valuable experience in procurement, licensing, and public engagement.[22] A critical finding from these pilots is that infrastructure must be designed for both human drivers and CAVs; MnDOT is currently prioritizing fiber optic expansion and traffic signal modernization to support this dual-use future.[21]

Chapter 7: Industry Ecosystem and Market Dynamics

The V2X market is a complex matrix of hardware manufacturers, software providers, and telecommunications firms.[27] Market analysis indicates a shift from small-scale pilots to coordinated, large-scale deployment, with the global V2X roadside unit market projected to grow at a CAGR of 19.7% through 2033.[8] In 2024, the market size was estimated at $1.82 billion, reflecting a robust growth trajectory driven by smart city initiatives and regulatory mandates.[28]

Key Market Players and Competitive Landscape

The ecosystem is dominated by semiconductor leaders and specialized ITS vendors who are providing the essential building blocks for connectivity.[27]

- **Semiconductors:** Qualcomm holds a leading 34% market share with its end-to-end C-V2X chipsets. NXP Semiconductors remains strong in DSRC, while Huawei leverages its 5G dominance in the Chinese market.[28] STMicroelectronics and Infineon focus on automotive-grade security and power management.[28]
- **Infrastructure (RSUs):** Key vendors include Yunex Traffic (formerly Siemens), Kapsch TrafficCom, and Commsignia. These companies provide the ruggedized outdoor units that manage the transition between vehicle signals and central traffic control.[10]
- **Software and Security:** Entities like Danlaw, Harman, and Applied Information develop the application layers and HMI (Human Machine Interface) integrations.[4]

The strategic direction of the market is currently favoring C-V2X due to its integration with 5G and its clearer path to ultra-low latency applications.[8] Major pilot zones in China and North America are scaling rapidly, and Tier-1 suppliers are increasingly providing modular hardware-software solutions that can be upgraded via software-defined vehicle architectures.[8]

Chapter 8: Future Frontiers: 5G-Advanced and 6G

As we look toward 2026 and beyond, the V2X roadmap is defined by 3GPP Releases 18 and 19, known as 5G-Advanced.[12] This evolution introduces "carrier-grade" enhancements to the 5G foundation, focusing on energy efficiency, spectral optimization, and the integration of Artificial Intelligence (AI).[12]

5G-Advanced Enhancements (Rel 18/19)

- **AI/ML-Native Design:** Release 18 introduces standardized hooks for AI-assisted link adaptation and mobility management. This allows the network to predict vehicle movement and optimize handovers before they occur, reducing packet loss in high-speed scenarios.[12]
- **RedCap (Reduced Capability):** Known as NR-Light, this feature enables lower-complexity, lower-cost V2X modules. This is critical for integrating lower-cost assets like e-bikes or industrial sensors into the V2X safety loop.[12]
- **Non-Terrestrial Networks (NTN):** Rel 18/19 harden the integration of satellite communication, allowing for V2N connectivity in rural or disaster-stricken areas where traditional cell towers are absent.[12]
- **Enhanced Sidelink Relay:** These releases expand the ability for one vehicle to act as a communication relay for another, extending the effective range of the direct PC5 interface beyond the physical line-of-sight of a single device.[12]

The Path to 6G (Rel 20 and Beyond)

Looking further ahead, early 6G studies (Release 20) are beginning to explore "Integrated Sensing and Communication" (ISAC).[12] In a 6G environment, the radio signals themselves will be used as a high-fidelity sensor, essentially turning the entire communication network into a giant radar.[12] This will enable "extreme positioning" with centimeter-level accuracy and the detection of non-connected objects (like animals or unequipped pedestrians) by analyzing the reflections of radio waves from the 6G base stations.[12]

The strategic goal of 6G is to move beyond ambigious connectivity to a "deterministic" network that can support mission-critical remote driving and fully autonomous fleets with absolute reliability.[12] As these technologies mature, the distinction between a vehicle's local sensors and the network's collective intelligence will disappear, creating a singular, unified digital environment for all road users.[8]

Index

- **3GPP (3rd Generation Partnership Project):** International standardization body for C-V2X (Releases 14-20).[7]
- **802.11p:** The IEEE standard for DSRC-based vehicular communication.[7]
- **ADAS (Advanced Driver Assistance Systems):** Vehicle systems enhanced by V2X situational awareness.[2]
- **BSM (Basic Safety Message):** Standardized status message for V2V communication.[2]
- **Butterfly Keys:** Scalability mechanism in SCMS for mass certificate generation.[19]
- **C-V2X (Cellular Vehicle-to-Everything):** Cellular-based communication standard for ITS.[2]
- **DSRC (Dedicated Short-Range Communication):** Wi-Fi-based V2X technology.[7]
- **FCC (Federal Communications Commission):** U.S. regulatory body managing the 5.9 GHz band.[14]
- **GLOSA (Green Light Optimal Speed Advisory):** V2I application for optimizing fuel and travel time.[1]
- **Linkage Values:** Mechanism for efficient certificate revocation in V2X PKI.[18]
- **MnDOT (Minnesota Department of Transportation):** State leader in CAV and winter weather V2X.[21]
- **PC5 Interface:** Direct sidelink interface for C-V2X.[1]
- **PKI (Public Key Infrastructure):** The security foundation for V2X trust.[17]
- **RedCap (Reduced Capability):** 5G-Advanced feature for low-cost IoT and wearables.[12]
- **RSU (Roadside Unit):** Infrastructure device for V2I communication.[7]
- **SCMS (Security Credential Management System):** U.S. framework for V2X security.[17]
- **SPaT (Signal Phase and Timing):** Message set for traffic signal communication.[1]
- **V2I (Vehicle-to-Infrastructure):** Communication between vehicles and road

equipment.[1]

- **V2V (Vehicle-to-Vehicle):** Direct data exchange between vehicles for safety.[1]
- **VRU (Vulnerable Road User):** Pedestrians and cyclists integrated into V2P.[1]

Works cited

1. Car2x/V2X Know-How | Vector, accessed February 3, 2026, https://www.vector.com/int/en/know-how/v2x/
2. Introduction to Cellular V2X | Qualcomm, accessed February 3, 2026, https://www.qualcomm.com/content/dam/qcomm-martech/dm-assets/documents/c-v2x_intro.pdf
3. V2X: Vehicle-to-Everything Solutions | Southwest Research Institute, accessed February 3, 2026, https://www.swri.org/newsroom/technology-today/v2x-vehicle-everything-solutions
4. Vehicle-to-Everything (V2X) Communications | ITS Deployment ..., accessed February 3, 2026, https://www.itskrs.its.dot.gov/success-strategies/snapshot/vehicle-everything-v2x-communications
5. Connected vehicles: A guide to V2V & V2X technology, accessed February 3, 2026, https://www.verizonconnect.com/resources/article/connected-vehicle-technology-v2v-v2i-v2x/
6. Discover the 10 Top V2X Companies and Startups to Watch in 2026 - StartUs Insights, accessed February 3, 2026, https://www.startus-insights.com/innovators-guide/v2x-companies/
7. DSRC vs. C-V2X: Understanding the Two Technologies - Ettifos, accessed February 3, 2026, https://www.ettifos.com/post/dsrc-vs-cv2x
8. Strategic Roadmap for the Global Automotive V2X Ecosystem: Enhancing Mobility, Safety, and Sustainability - RNG Strategy Consulting, accessed February 3, 2026, https://rngstrategyconsulting.com/industry/automotive/automotive-v2x-strategic-roadmap/
9. Interoperability of C-V2X and DSRC for V2X Communications : Application in Smart Parking Guidance - Preprints.org, accessed February 3, 2026, https://www.preprints.org/manuscript/202510.0177/v1/download
10. DSRC vs. C-V2X: A Complete Comparison | Grand-Tek, accessed February 3, 2026, https://www.grand-tek.com/en/smart-transportation-dsrc-c-v2x.aspx
11. Performance Evaluation of DSRC and C-V2X Coexistence in the 5.895–5.925 GHz Spectrum, accessed February 3, 2026, https://wicon.arizona.edu/sites/default/files/2024-07/ICNC2024_V2X.pdf
12. 3GPP Issue 11: Release 18–19 Highlights and Early 6G - TeckNexus, accessed February 3, 2026, https://tecknexus.com/3gpp-issue-11-release-18-19-highlights-and-early-6g/
13. 5G-Advanced:Overview, accessed February 3, 2026,

https://5gamericas.org/wp-content/uploads/2025/07/5G-AdvancedOverview.pdf
14. Use of the 5.850-5.925 GHz Band - Federal Register, accessed February 3, 2026, https://www.federalregister.gov/documents/2024/12/13/2024-28980/use-of-the-5850-5925-ghz-band
15. U.S. FCC adopts new ITS rules to govern C-V2X deployment in the 5.9 GHz band, accessed February 3, 2026, https://www.hoganlovells.com/en/publications/us-fcc-adopts-new-its-rules-to-govern-cv2x-deployment-in-the-59-ghz-band
16. 5.9 GHz Second Report and Order - 5GAA, accessed February 3, 2026, https://5gaa.org/content/uploads/2025/02/faq-5.9-ghz.pdf
17. SECURITY CREDENTIAL MANAGEMENT SYSTEM (SCMS) - Department of Transportation, accessed February 3, 2026, https://www.its.dot.gov/factsheets/pdf/CV_SCMS.pdf
18. Security Credential Management System (SCMS ... - ROSA P, accessed February 3, 2026, https://rosap.ntl.bts.gov/view/dot/43635/dot_43635_DS1.pdf
19. A Security Credential Management System for V2X Communications - André Weimerskirch, accessed February 3, 2026, https://www.weimerskirch.org/files/BrechtEtAl_SCMS.pdf
20. V2X Certificate Management with IEEE 1609.2.1: Status and Deployment, accessed February 3, 2026, https://avstandard.or.kr/uploads/file_content/64d56913-37ea-4248-b273-9b5d59d2b2cd/_%EB%B0%9C%ED%91%9C%EC%9E%90%EB%A3%8C__Korea-SCMS-Presentation-2022-01-20_Qualcomm_William_Whyte.pdf
21. CAV in MN - MnDOT, accessed February 3, 2026, https://www.dot.state.mn.us/automated/destinationcav/cavinmn.html
22. Trunk Highway 55 Connected Corridor - MnDOT, accessed February 3, 2026, https://www.dot.state.mn.us/its/projects/2016-2020/connectedcorridors.html
23. Connected and Automated Vehicles (CAV) | 2025 Autonomous Trucking Conference, accessed February 3, 2026, https://www.ugpti.org/resources/proceedings/downloads/2025-09-15-ATC-state-perspective-minnesota-dot.pdf
24. CAV Planning in MN - Connected and Automated Vehicles - MnDOT, accessed February 3, 2026, https://www.dot.state.mn.us/automated/cav-planning-mn.html
25. Connected and automated vehicles in Minnesota - MnDOT, accessed February 3, 2026, https://www.dot.state.mn.us/automated/destinationcav/getinvolved.html
26. Minnesota CAV Challenge - MnDOT, accessed February 3, 2026, https://www.dot.state.mn.us/automated/destinationcav/mncavchallenge.html
27. Cellular Vehicle-To-Everything (C-V2X) Roadside Unit Market Global Report 2026, accessed February 3, 2026, https://www.marketresearch.com/Business-Research-Company-v4006/Cellular-Vehicle-Everything-V2X-Roadside-43729061/
28. V2X Communication Chips Market Size, Forecasts Report 2034, accessed February 3, 2026, https://www.gminsights.com/industry-analysis/v2x-communication-chips-market
29. V2X C-V2X Roadside Unit Market Research Report 2033 - Dataintelo, accessed

February 3, 2026, https://dataintelo.com/report/v2x-c-v2x-roadside-unit-market
30. Release 18 - 3GPP, accessed February 3, 2026, https://www.3gpp.org/specifications-technologies/releases/release-18
31. 5G Advanced Release 19 project scope - Qualcomm, accessed February 3, 2026, https://www.qualcomm.com/content/dam/qcomm-martech/dm-assets/documents/5G-A-Rel-19-Presentation.pdf