ASSIGNMENT – 6

Introduction to Network Security and Cryptography in Network Security

Subject: Cryptography and Network Security

Submitted by: Shreya Paliwal

Course: BCA

Q1. Define network security and explain its fundamental principles and objectives. Discuss the importance of confidentiality, integrity, availability, authentication, and authorization in securing network systems.

Network security is the practice of protecting computer networks, connected devices, and transmitted data from unauthorized access, misuse, modification, disruption, or destruction. It uses policies, technologies, and procedures to keep network resources safe and reliable.

Fundamental principles and objectives:
1. Confidentiality: Information should be available only to authorized people. Encryption and access controls help protect confidential data.
2. Integrity: Data should remain accurate and complete and should not be changed without permission. Hashes, message authentication codes, and digital signatures can help detect unauthorized changes.
3. Availability: Network services and data should be accessible when authorized users need them. Backups, redundancy, updates, and protection against denial-of-service attacks support availability.
4. Authentication: The system verifies the identity of a user, device, or service. Passwords, multi-factor authentication, and digital certificates are examples.
5. Authorization: After identity is verified, the system decides what the user is allowed to access. Role-based permissions and least-privilege access are common methods.

Example: In online banking, TLS encryption helps keep account data confidential, integrity checks help detect tampering, login verification authenticates the customer, permissions control available actions, and redundant systems help keep the service available.

Together, these principles protect data, users, devices, and services while supporting trust and continuity.

Q2. Explain the threat landscape in network security. Discuss different types of network attacks and vulnerabilities, along with suitable examples and preventive measures.

The network-security threat landscape includes people, software, and events that can exploit weaknesses in systems or networks. A vulnerability is a weakness; a threat is a possible cause of harm; and an attack is an attempt to exploit a weakness.

Common attacks and examples:
1. Malware: Viruses, worms, ransomware, and spyware can damage systems or steal information. Example: ransomware encrypts an organization’s files.
2. Phishing and social engineering: Attackers trick users into revealing passwords or opening malicious links. Example: a fake bank email asks a user to sign in on a fraudulent website.
3. Denial-of-Service (DoS/DDoS): Large volumes of traffic overwhelm a service so legitimate users cannot access it.
4. Man-in-the-Middle (MitM): An attacker intercepts or alters communication between two parties, especially when connections are not properly protected.
5. Password attacks: Guessing, credential stuffing, or brute-force attempts target weak or reused passwords.
6. Spoofing and session hijacking: Attackers impersonate a device or user, or take over an authenticated session.
7. Unpatched software and misconfiguration: Old software, open ports, default passwords, and overly broad permissions can expose systems.

Preventive measures:
- Keep operating systems, applications, routers, and firewalls updated.
- Use strong unique passwords and multi-factor authentication.
- Apply firewalls, secure Wi-Fi settings, network segmentation, and least-privilege access.
- Use HTTPS/TLS and VPNs where appropriate; avoid sensitive work on untrusted networks.
- Train users to recognize phishing and verify unusual requests.
- Use anti-malware tools, monitoring, secure backups, and an incident-response plan.
- Perform authorized vulnerability scans and fix findings according to risk.

No single control prevents every attack. A layered defense reduces the chance and impact of compromise.

Q3. Discuss the legal and ethical considerations in network security. Explain the importance of data privacy, responsible security testing, authorized access, and compliance with applicable cybersecurity laws.

Network security work must be lawful, ethical, and respectful of people's rights. Technical ability does not give someone permission to access a system or data.

1. Data privacy: Personal information should be collected and used only for legitimate purposes, protected from unauthorized disclosure, and retained only as necessary. Organizations should limit access and apply suitable safeguards.
2. Responsible security testing: Penetration testing and vulnerability assessment should be performed only with clear written permission and an agreed scope. Testing should avoid unnecessary disruption, protect any data encountered, and report findings securely.
3. Authorized access: Users and administrators should access only systems and information they are permitted to use. Bypassing access controls, stealing credentials, or examining private data without permission may violate laws and policies.
4. Legal compliance: Organizations must follow the cybersecurity, privacy, contractual, and sector-specific rules that apply to them. In India, relevant frameworks may include the Information Technology Act, 2000 and applicable rules, as well as the Digital Personal Data Protection Act, 2023 and its applicable implementation requirements. Organizations should check current legal obligations rather than assume every provision applies in the same way.
5. Responsible disclosure: If a vulnerability is discovered, the finder should notify the owner through an appropriate channel, provide enough detail to reproduce it safely, avoid public release of sensitive information before coordination, and follow the agreed disclosure process.
6. Professional ethics: Security professionals should maintain confidentiality, be honest about findings, avoid conflicts of interest, and use their skills to reduce harm.

Following legal and ethical practices protects users, maintains trust, and helps organizations improve security without violating rights or disrupting services.

Q4. Explain the role of cryptography in securing network communications. Describe the working and security features of SSL/TLS and IPsec protocols.

Cryptography protects network communication by transforming information so that unauthorized parties cannot easily read or alter it. It supports confidentiality, integrity, authentication, and secure key establishment.

Role of cryptography:
• Encryption converts readable plaintext into ciphertext; only a party with the correct key can recover it.
• Hash functions produce fixed-length digests used in integrity mechanisms.
• Message Authentication Codes (MACs) and digital signatures help detect changes and authenticate messages or senders.
• Public-key cryptography supports authentication and key establishment, while symmetric encryption efficiently protects large amounts of data.

SSL/TLS:
SSL was an earlier protocol and is now obsolete. Modern secure web communication uses TLS (Transport Layer Security).
Working:
1. A client connects to a server and negotiates supported TLS parameters.
2. The server usually presents a digital certificate so the client can verify its identity.
3. The parties establish shared session keys, commonly using an authenticated key exchange.
4. They use the session keys and authenticated encryption to protect application data.
Security features include confidentiality, integrity, server authentication, and optional client authentication. TLS helps secure HTTPS, email connections, and many other network services. Correct certificate validation and modern protocol settings are essential.

IPsec:
IPsec is a suite of protocols that protects IP traffic at the network layer. It is commonly used for VPNs.
Working and modes:
• Transport mode mainly protects the IP packet payload and is often used for host-to-host communication.
• Tunnel mode protects the entire original IP packet by encapsulating it in a new packet; it is commonly used in

site-to-site VPNs.
• Authentication Header (AH) provides integrity and origin authentication but not encryption.
• Encapsulating Security Payload (ESP) can provide confidentiality and can also provide integrity and authentication.
IPsec uses Security Associations and key-management mechanisms, commonly IKE, to negotiate security parameters and keys.

TLS generally protects application connections, while IPsec protects IP traffic at the network layer. Both need secure configuration, sound key management, and regular updates.

Q5. What is Public Key Infrastructure (PKI)? Explain its components and working. Discuss the role of digital certificates and Certificate Authorities in establishing trust and securing network communications.

Public Key Infrastructure (PKI) is a system of people, policies, processes, hardware, and software used to create, distribute, manage, validate, and revoke digital certificates and public keys. It helps users and systems establish trust in public-key cryptography.

Main components:
1. Certificate Authority (CA): A trusted organization or service that issues and digitally signs certificates after applying its validation procedures.
2. Registration Authority (RA): An entity that may check an applicant's identity and approve certificate requests on behalf of a CA.
3. Digital certificate: An electronic document that binds an identity, such as a website name or organization, to a public key. It includes information such as the subject, public key, issuer, validity period, and CA signature.
4. Public and private keys: The public key can be shared; the corresponding private key must be kept secret and controlled by its owner.
5. Certificate repository and revocation services: Systems that publish certificates and help relying parties check whether a certificate has been revoked, for example through Certificate Revocation Lists (CRLs) or Online Certificate Status Protocol (OCSP).
6. Policies and procedures: Rules for identity checking, issuing, renewing, protecting, and revoking certificates.

Working of PKI:
1. An applicant generates a key pair and submits a certificate request.
2. The CA or RA verifies the applicant's identity or control of the relevant domain, according to its policy.
3. The CA issues and signs a digital certificate that binds the verified identity to the public key.
4. A server presents its certificate during a secure connection, such as TLS.
5. The client checks the CA signature, certificate chain, validity period, intended use, domain name, and revocation status where available.
6. If the checks succeed and the certificate is trusted, the client can use the certified public key as part of the protocol's authentication and key-establishment process.

Role in trust and security:
Digital certificates help prevent impersonation by linking a public key to a verified identity. Certificate Authorities create signed attestations that software can validate through a trusted certificate chain. PKI is widely used in HTTPS, enterprise authentication, VPNs, code signing, and secure email.

PKI does not automatically guarantee that a system is safe. Trust depends on correct validation, protection of private keys, trustworthy CA operations, and timely revocation of compromised certificates.