AI Driven Product Catalogue Generation Using Generative Models

Project report submitted to

SAMSUNG Innovation Center

For Partial Fulfillment of the Requirement for the

Award of the Certificate

in

Artificial Intelligence

&

Machine Learning

by

Sujana Hariyapureddy - 20221ECE0292
Pavithra T – 20221CSG0010
Shreyas R Patil – 20221ECE0284

Under the guidance of

Dr. Nagaraja S R
Associate Professor
Presidency School of Computer Science
Presidency University
Bengaluru, India

Dr. Prashanth Kannadaguli
Chief Research Architect
R&D Department
Samsung R&D Institute
Bengaluru, India

GAIN MORE KNOWLEDGE
REACH GREATER HEIGHTS

SAMSUNG

Together for Tomorrow!
Enabling People
Education for Future Generations

November 2025

PRESIDENCY UNIVERSITY
ITTAGALLPURA, KARNATAKA

Samsung Innovation Campus

Artificial Intelligence Programme

CERTIFICATE

This is to certify that the project work entitled **"AI Driven Product Catalogue Generation Using Generative Models"** has been successfully carried out at the **Samsung Innovation Campus,** by **Sujana Hariyapureddy, Pavithra T, Shreyas R Patil**, bearing **20221ECE0292, 20221CSG0010, 20221ECE0284**, a Bonafide student of **PRESIDENCY UNIVERSITY**, in partial fulfilment of the requirements for the award of the Certificate in **Artificial Intelligence Programme.**

It is further certified that a research paper based on the aforesaid project has been prepared and submitted to an **IEEE Conference**, in partial fulfilment of the programme requirements. A copy of the said paper has been appended to this report.

The project report has been thoroughly reviewed and is hereby approved, as it satisfactorily meets the prescribed standards and requirements with respect to project work for the programme.

Dr. Nagaraja S R	**Dr. Prashanth Kannadaguli**	**Dr. Robin Rohit Vincent**
SPOC	Chief Research Architect	Chief-Coordinator
SIC-PRESIDENCY	Samsung R&D Institute	SIC-PRESIDENCY
	Bengaluru, India	

Table of Contents

I. Introduction
- A. Problem Statement
- B. Objectives
- C. Significance and Motivation
- D. Scope and Limitations

II. Literature Review
- A. Overview of Relevant Concepts and Technologies
- B. Summary of Related Work and Existing Approaches
- C. Identification of Gaps in the Existing Literature

III. Methodology
- A. Data Collection and Preprocessing
  1. Dataset Description
  2. Data Cleaning and Transformation
  3. Feature Engineering and Selection
- B. Model Development
  1. Selection of DL Algorithms
  2. Model Architecture and Design
  3. Hyperparameter Tuning
- C. Model Training and Evaluation
  1. Training Procedure and Metrics
  2. Evaluation Metrics and Performance Analysis
  3. Experimental Setup and Validation Techniques

IV. Results And Analysis
- A. Presentation of Experimental Results
- B. Comparison with Baseline or Existing Approaches
- C. Discussion of Findings and Insights
- D. Interpretation of Results and Patterns

V. Conclusion
- A. Summary of Key Findings
- B. Contributions and Achievements
- C. Future Directions and Potential Improvements

VI. References
- A. Citations of Relevant Literature and Sources

VII. Appendices
- A. Code Snippets or Algorithms
- B. Finalized IEEE Paper

I. INTRODUCTION

A. Problem Statement

The digital marketplaces and e-commerce platforms have changed drastically in the last couple of years. With this quick change, the way people look for, compare, and buy products has been changed completely. Nowadays, buyers are able to access up-to-the-minute listings of products across various platforms, which naturally renders the question of which platform to use for their purchase obsolete. In fact with the explosion in the number of products most of which can be accessed from multiple platforms in real-time updating environments checking what the current price of the product or where it is cheaper or analyzing the reviews are the questions which are asked instead of which platform should be used.

As catalog sizes grow exponentially, the traditional method of manually curating product entries—consisting of descriptive text, specifications, and images—has become not only unviable but also inefficient. Content creators are required to constantly produce new materials for products that have just been launched, update features as they change, and adjust the tone, language, and style for different regional or linguistic markets. This monotonous task takes a lot of human resources and time, and at the same time, it leads to inconsistencies in different modes—text, visuals, and metadata—because these are usually coming from different sources and workflows.

While there are some automated content generation tools that have been developed to ease the burden somewhat, the majority of them are still unimodal and don't change that much in terms of functionality. Most of them are either designed to generate textual descriptions by using rule-based or template-driven natural language generators or to create visual assets by using image synthesis techniques such as Generative Adversarial Networks (GANs) or diffusion models. Meanwhile, these tools rarely merge both modalities into one semantic framework. As a consequence, their results are often not in harmony; for example, a computer-generated product description may contain features which are not shown in the image, while that image may have features that are not mentioned in the text. In addition, if there is no checkpoint to guarantee that the data is true and the images are correct then the production of such content can mislead the users thus reducing their trust in the brand and this will eventually lead to the loss of the brand's credibility.

Solving this problem necessitates creating an integrated multimodal system that can combine language and vision in a single operational framework. Such a system might accomplish these objectives, among others:

1. Textual Generation: Help write product descriptions by making them grammatically correct, stylistically appropriate, and factually verified with the least of human effort/interaction.

2. Visual Realism: Create real-life-like and relevant-to-the-context pictures that match the semantic meaning of the corresponding text.

3. Cross-Modal Verification: Perform an automated check on the consistency of content between text and image pairs that is to say the finding whether the two refer to the same conceptual entity.

4. Accessible Design: Have an easy to use, device independent interface—which can be accessed through mobile and web platforms—that helps in speeding up content creation and making it easier for a large number of people from different industries to use it.

Such a complex job cannot be done by a single model of any kind, whether it is a large language model (LLM), a diffusion-based visual generator, or a standalone vision-language embedding network. What, however, is required is a perpetual feedback and assessment cycle wherein several specialized units' co-function, verify each other's work and thus enhance it. The architectural concept behind this is what Neo-Genesis: The AI-Driven Product Catalog Generator is all about, a system that aims at delivering enterprise-grade multimodal automation.

Neo-Genesis has three components that are not only different but also complementary and they work in harmony with each other:

1. Gemini 2.0 Flash, which is in charge of producing detailed, and contextually flexible product descriptions that reflect not only the factual side but also the stylistic one.

2. Flux Diffusion Model, a text-to-image generator that creates photorealistic images that can be considered as the visual representation of the generated descriptions.

3. CLIP + MLP Classifier, the module that acts as a customer support and scoring agent, thereby increasing brand semantic correlation and quality assurance across modalities.

Neo-Genesis comprehends the products in total through the cooperation of these modules which bring together the linguistic, visual, and narrative aspects of the products. Exactly the same system is thus scalable, dependable, and of high fidelity, industrial-standard catalog content producers that are in line with the requirements of contemporary digital commerce.

B. Objectives

The main aim of this study is to create and carry out a multimodal, scalable artificial intelligence framework, that is capable of independently handling all the main stages of product catalog creation. The suggested system merges different technologies like text generation, image creation, cross-modal verification, and user-interactive interfaces into one smooth workflow. Its goals may be delineated as follows:

1. Automated Product Description Generation

By utilizing Gemini 2.0, a transformer-based large language model (LLM), the system is able to generate full, context-aware product narratives from very brief user input-prompts like "black wireless headset". The created text goes beyond the basic description and explains the product in detail - design, material, functionality, application, etc., while at the same time being grammatically correct and stylistically consistent. This segment of the program is a writing labor-saving device and at the same time guarantees that every product entry is in accordance with the brand voice and language standard.

2. Diffusion-Driven Visual Synthesis

To produce attractive content to the eyes of the customers, the schema turned to corporate-store-flux API-powered Flux diffusion model for image generation at a high level of detail and resolution. By utilizing the prompt-to-image directive, the system comes up with an absolutely real-like image that illustratively depicts the neighboring prescriptive text. The final image is of a good enough quality to be put on the display of the store, as it is correct in terms of the color, the texture, and the point of view.

3. Semantic Verification and Cross-Modal Alignment

The system uses a CLIP-based embedding pipeline combined with a simple multilayer perceptron (MLP) classifier to detect and subsequently assure the correspondences between words and pictures. The method calculates cosine similarity between visual and textual feature vectors for spotting differences and even for finding attributes which have been "hallucinated". The significance of this authenticating operation lies in the provision of a numerical alignment indicator for screening out those pairs which are mismatched or are of low confidence thus enhancing the semantic trustworthiness of the output generated.

4. Interactive Catalog Interface

The system is equipped with a well-designed, easy-to-operate, and friendly-to-the-user interface, which allows an operator to smoothly communicate with it. CustomizedTkinter is used for interface creation in a local environment whereas Flask and HTML5 are responsible for web access. The functionality which is allowed to the users is entering of product prompts, starting off with generation, output viewing as well as

result saving and all these access points exist within a single integrated platform. The layout affords the convenience, the minimal amount of time required for learning and the instant reaction.

5. Performance Benchmarking and Evaluation

In order to measure the reliability of the verification component- the one in charge of model correctness- it was trained and tested on artificially created data consisting of pairs of image-text samples with labels matched (1) or mismatched (0). The metrics of performance consist of the following: accuracy, F1-score, and Area Under the Curve (AUC) with corresponding benchmark levels greater than 0.90, 0.90, and 0.95 respectively. Such indicators assure that the system is capable of maintaining not only its precision but also its generalization over different product categories.

6. Sustainability and Scalability

The system embodies a modular and cloud-oriented approach concept-wise, thus being virtually ready for large-scale and enterprise-level deployment. On the one hand, caching strategies are in place to save the previously created products in order to lower the loading of the CPU, on the other hand, integration hooks are introduced for easily connecting with existing product management APIs. The willingness of this system to make a difference in keeping the execution of its tasks efficient, eco-friendly, and industrial workflow compatible creates room for future growth.

C. Significance and Motivation

This project's launch comes from an operational gap that is quite evident in modern digital commerce – the dividing line between the increasing demand for online content and the limited supply of content creation in a timely manner is getting wider. For instance, major e-commerce ecosystems like Amazon and Flipkart and a plethora of new direct-to-consumer (D2C) brands carry the inventories that might contain millions of Stock Keeping Units (SKUs). Though these organizations use partially automated cataloging systems, these giant firms still rely on a large number of writers, designers, and editors to create and edit product descriptions and visuals. The lack of sync between textual and visual parts of a listing can even make a minor product update turn into the fragmentation of brand consistency – thus, disappearing the same item with different versions which are old, different, or unbalanced copies across various marketplaces and occur without notice.

The breakthrough in generative artificial intelligence and multimodal learning has the potential of bringing the opposite effects into harmony. On one side of the scale, massive language models like GPT, Gemini, and Claude are extraordinarily proficient in comprehending and producing human-like text. On another hand, sophisticated diffusion models like Stable Diffusion, Flux, and DALL-E 3 have striking abilities in image synthesis. All these achievements together are a signal that large-scale, semantically aligned text–image generation is not just a matter of possibility but is becoming more and more of a reality. Yet, the researchers have a large empty space in front of them, which is the lack of end-to-end, production-ready systems incorporating generation, verification, stylistic control, and explainability in one operational framework. Very few academic or industrial research have attempted to address this comprehensively.

Significance of the Study

The significance and the contribution of this research study may be depicted through three major aspects or dimensions:

1. Industrial Impact

Integrating multimodal synthesis with automated verification driven by the fusion model not only leads to substantial time savings in catalog creation – manual catalog creation time is reduced by almost 80 percent – it also quite drastically improves operational efficiency. Along with speed, the single verification model also guarantees that every written description is a faithful depiction of the visual content thus, enhancing user confidence and maintaining semantic integrity in product listings.

2. Advancement of Research

The paper experimentally substantiates the thesis that cross-modal alignment on the basis of CLIP embeddings may be a powerful tool for consistency checking in generative systems. The approach used in this paper limits the retail applications domain only and has great potential in the areas of digital journalism, augmented and virtual reality (AR/VR) design, and automated digital-twin creation, where semantic alignment between modalities is of the same importance.

3. Educational and Societal Relevance

Besides the technical contribution, this project is a collaborative bridge between the world of academia and the industry. It is an outcome of joint research between Presidency University, Bengaluru, and Samsung R&D Institute, Bangalore, through which students and researchers are able to interact with the real-world implications of AI ethics, automation, and creativity. The project is a perfect example of India's increasing proficiency in the field of multimodal AI research, applied research, and where innovation meets implementation, leading to the creation of real societal value.

From the perspective of motivation, the cooperation between research centers and companies was the main factor for the existence of this project. Samsung R&D Institute, Bangalore, not only technically but also financially supported this collaboration, which, by providing access to cutting-edge resources and expert guidance, was able to realize the theoretical concepts into an actual deployable prototype. The created platform—the AI-powered tool that efficiently transforms brief user prompts into full-fledged, ready-for-publication catalog entries—is an industrial adoption demonstration, illustrating how research innovation can be swiftly embraced by the industry.

D. Scope And Limitations

1. Scope

This research covers the entire lifecycle of multimodal catalogue creation, from algorithmic innovation to system-level engineering. It the study text generation, visual synthesis, semantic validation, and user deployment as different modules of a single operational framework. The main components included in the scope are as follows:

- Textual Generation: The Gemini 2.0 Flash large language model is the main tool that transforms concise attribute prompts into detailed, context-aware product narratives. Each generated description exemplifies the design attributes, material specifications, and intended usage while being linguistically coherent and factually consistent.

- Visual Synthesis: The Flux Diffusion Model is the method through which 8K-resolution photorealistic product images under controlled studio-lighting conditions are produced. The model uses prompt-to-image conditioning to facilitate semantic alignment with the textual description.

- Semantic Verification: The combination of CLIP embeddings and an MLP classifier are the tools through which the semantic relationship between textual and visual modalities is assessed. The cosine similarity between feature embeddings is the metric by which the degree of a correct text–image match is quantified.

- Deployment and Interaction: Two-mode interfaces are the means through which both accessibility and usability are guaranteed. A CustomTkinter-based desktop application along with a Flask + HTML5 web interface provides the users with the functionalities to input prompts, visualize results, edit outputs, and export the finalized catalogue entries directly to PDF using the integrated create_report.py module.

- Evaluation and Benchmarking: The verification network is trained and benchmarked by a

custom dataset that consists of balanced positive and negative text–image pairs. The metrics used to quantify the model's stability and capacity to differentiate its cut precision, recall, F1-score, and Area Under the Curve (AUC).

In sum, the project scope is representative of a complete AI engineering pipeline — starting with data generation, multimodal model integration, and ending with application-layer deployment — thus, it embodies both technical novelty and practical implementation maturity.

2. **Limitations**

While the present setup is able to accomplish strong multimodal integration; there are still some limitations in terms of both practical and developmental issues that delineate the boundaries of this research:

- Dataset Scale: Due to limitations on API access, at the moment there are only around 20 image-text pairs depicting each product class. This small dataset is a bottleneck for the model's ability to generalize across categories. The subsequent work will be devoted to increasing the dataset size in order to obtain better statistical diversity.

- Generative Fidelity: In some examples, the Flux Diffusion Model might bring in slight visual artifacts or area of the texture that are not consistent, especially when it tries to render complex reflective or translucent surfaces. To refine these results demands a lot of GPU power and a longer training period.

- Semantic Bias in Text Generation: The Gemini LLM sometimes picks up the linguistic or cultural biases from its pretraining corpus that can affect it in things like gendered phrasing and giving preference to certain region-specific vocabulary. The next versions will have a layer for moderation and bias filter to facilitate neutrality and inclusiveness.

- Verification Overconfidence: The MLP-based verification module that is mainly trained on synthetic datasets might be very confident in cases that are ambiguous or borderline. It is anticipated that using real-world catalogue data for domain adaptation will help reduce this overfitting and increase the reliability of the module.

- Infrastructure and API Dependency: The system is set up to use third-party APIs such as Google Gemini and Replicate, and therefore it needs both internet connection and valid access tokens. It can only work offline for cached generations or files that have been saved beforehand.

- Ethical and Legal Constraints: Any content that is generated should conform to copyright, brand identity, and authenticity regulations. The upcoming versions of the system will have the integration of digital watermarking and traceability features for the purpose of ethical compliance and accountability of AI-generated visuals.

II. LITERATURE SURVEY

A. Overview of Relevant Concepts and Technologies

1. The Rise of Multimodal Artificial Intelligence

The changes in the field of AI over the last ten years have been quite profound. A significant part of that change has been the way the AI systems evolved structurally and in their complexity. Initially, these systems were unimodal in nature, where one system could interact with only one domain, like speech recognition, text processing, or image classification, without the possibility of intercommunication between the modes. Nowadays, the AI systems of the first kind are changed to multimodal systems that can integrate and reason across multiple sensory inputs like vision, language, and sound. Zhang et al. (2020) [11] have given an example of such a switch by saying that this shift has transformed the concept of learning by making it possible for machines to find logical relations between various sources of information, rather than treating them as separate tasks.

Multimodal learning is therefore considered a representation-fusion issue, the main difficulty being the construction of a shared embedding space that encompasses the interaction of different modalities. Here, the end goal is not only to produce corresponding textual and visual results. The main point is to invent such models that allow the made outputs to support one another on a semantic level; thus, the final result will be a more profound and logical multimodal comprehension.

Zhu et al. (2024) [24] moved this concept even further by proposing a data-centric viewpoint of multimodal learning. They emphasize that large-scale, high-quality, and paired datasets (e.g., LAION-5B) are what make alignment models like CLIP and Stable Diffusion successful. Such datasets are the key to the models' scalability and their ability to associate language semantics tightly with visual structures. The implementation of this idea in the Neo-Genesis platform is a dual-stream CLIP encoder that measures the agreement between the Flux-generated images and the Gemini-produced textual descriptions, thereby guaranteeing semantic conformity of both modalities.

The current wave of vision-language designs reveals an even more profound integration of vision transformers (ViTs), convolutional neural networks (CNNs), diffusion-based visual generators, and large language models (LLMs). Shao et al. (2024) [2] identify three main conceptual frameworks that these designs can be categorized into:

(a) Encoder–decoder fusion models, in which visual and linguistic features are combined by passing information in a sequence;

(b) Dual-encoder contrastive alignment models, in which both modalities are projected into a joint embedding space for similarity learning; and

(c) Instruction-tuned multimodal LLMs, which utilize textual prompts for guiding vision-language reasoning in a single framework.

These different structural designs have different pros and cons in terms of computer power, ability to generalize, and training speed. Neo-Genesis is a system that tactically deposits the features of (b) and (c) architectures to get the best of both worlds: alignment and adaptability. The semantic checking of photo and text embeddings is done by the CLIP dual-encoder interaction while the Gemini 2.0 instruction-tuned decoder, with the help of CLS-based contextual representations, is used to create descriptive texts. The combined power of these two factors ensures that the content generated by Neo-Genesis is not only semantically accurate but can also be trusted from an industrial point of view.

2. Large Language Models and Their Cross-Domain Adaptations

Modern multimodal generative modeling heavily relies on large language models (LLMs) that act as the cognitive core for contextual understanding and semantic control. The advancements of top-tier LLMs like GPT-4, PaLM 2, Gemini 1.5 Pro, and Claude 3 are described by Shao et al. (2024) in terms of three main aspects: parameter scale, training corpus size, and modal integration depth. Their research reveals that the performance measures of transformers, especially perplexity, follow a power-law scaling trend up to very large parameter magnitudes, after which the improvement rate starts to level off. This scaling pattern uncovers the efficiency limits of model enlargement, thus giving rise to the motivation for architectural changes and multimodal adaptability instead of mere parameter increase.

Zhou et al. (2025) take this argument further by including telecom-grade LLMs in the scope of the study and showing how domain-specific fine-tuning and retrieval-augmented grounding (RAG) can substantially improve factual accuracy and contextual precision. Their findings are directly applicable to the task of automated product catalog creation where the accuracy of facts describing, e.g., the material, dimensions, or the functionality of the products, is a must-have feature. Factual grounding of this sort guarantees that the generated text is not only semantically loyal but also trustworthy from the business perspective.

Among the cutting-edge technologies rolled into Neo-Genesis, one can hardly miss the Gemini 2.0 Flash model. This component demonstrates how to engage minimal input—for instance, “blue mechanical keyboard”—to obtain a thorough, attribute-rich product description that sounds natural and is sufficiently informative. As per Zhou et al.'s argument, the method here is very close to the principle of in-context learning, which enables the model to deduce the missing contextual information on the fly rather than by using stiff templates or already established formats. Though retrieval-augmented generation (RAG), as per the discussion by Tural et al. (2024) [44], is a complex mechanism for incorporating the external factual base, Neo-Genesis currently does not have it for reasons of computational efficiency and latency cutting. However, Gemini's modular setup is enterprise-ready, i.e., different deployments can take advantage of vector-database searches or catalog metadata for scaling and adaptability purposes without any disruption.

The future roadmap of Neo-Genesis includes the integration of domain-crossing and multilingual LLM extensions, thus widening its linguistic and cultural adaptability horizon. Nath et al. (2025) [45] propose a language-neutral visual summarizer that can produce multilingual infographics by combining text abstraction with automated layout generation, which perfectly fits with the long-term vision of Neo-Genesis. The latter aims at enabling global brands to create product catalogs that are not only regionally localized but also stylistically consistent, thereby accommodating both linguistic diversity and brand unity. By progressively implementing these integrations, Neo-Genesis is making a leap from mere generative automation to a comprehensive, multilingual, and semantically grounded AI cataloging ecosystem.

3. Diffusion Models and Text-to-Image Generation

Diffusion models have, in a short span of time, become the mainstay for image synthesis that is of high resolution, thus they have been able to outperform Generative Adversarial Networks (GANs) in the aspects of both fidelity and stability. Their working mechanism is explained in both papers by Alhabeeb and Al-Shargabi (2024) [5] and Yin (2024) [15] whereby, through forward noise addition and reverse denoising reconstruction processes, these models gradually rotate a dice and finally get the image that they want to generate from the collection of random noise. Not only do these researchers account for the diffusion models based on the stages, they also point out that LDMs consume a lot less power due to the fact that they do the denoising in a compressed latent space rather than at the image resolution. As such, the Flux model orchestrated in Neo-Genesis is an evolved LDM that, under a setting of studio-controlled light, manages 8K-resolution photo-realistic rendering and hence visually consistent and computationally viable outputs are the result of latent-space optimization.

Habib et al. (2024) [4] in their work, present a pioneering approach to text-to-image synthesis by proposing GACnet, a generative architecture that combines attention mechanisms with contrastive learning. Their paper highlights that the corresponding alignment between the caption and the visual features in the latent space is the factor that mainly accounts for the semantic coherence between the two modalities. The idea is implemented in the Neo-Genesis verification stage wherein CLIP embeddings serve as the means through which the semantic alignment after the generation of Gemini-created text and Flux-developed images is quantified. By rendering this notion into an assessment tool, Neo-Genesis assures that every product image is a true representative of its textual counterpart.

Moreover, the research of Li et al. (2025) [25] has led to the development of an additive attention fusion mechanism that realizes the enhancement of fine-grained object details and the elevation of chromatic precision. The approach is indispensable, to be particular, for the generation of e-commerce catalogs where the buyers are affected by the surfaces' tactile aspects, color correctness, and the material's finish rather than by the brand itself, thus these factors become the consumers' perception and the brand's integrity.

Additionally, diffusion-driven innovations in creative realms are well exemplified by the CreativeSynth project of Huang et al. (2024) [13] that proposes a cross-art attention framework capable of blending the visual characteristics of paintings and photographs. This breakthrough substantiates a potential shift for diffusion architectures where they are not only to be used as representational models but also as aesthetic and stylistic synthesizers. Although Neo-Genesis is a brand of product visualization that is realistic, the proposition on which CreativeSynth is based could be seen as the seminal point: brand-specific visual identities- e.g., minimalist, neon, or luxury-themed catalog backdrops- could be integrated as aesthetic control Lanes. The melding of this functionality image synthesis with creative visual expression churns out the wonderful capability of enterprises and organizations to not only resist the lure of realism and stylich coherency but to also harmonize them in different catalog formats.

4. Contrastive Vision-Language Alignment and CLIP

One of the main factors is the ability to determine with high precision how coherent the content of the text is with the image, which is very important for multimodal AI systems. OpenAI’s CLIP (Contrastive Language–Image Pre-training) model was the first and foremost to put this factor into operation by proposing a dual-encoder architecture trained on almost 400 million image–caption pairs. CLIP illustrated the way contrastive learning can be used to line up visual and linguistic embeddings in the same shared representational space thus, without task-specific fine-tuning, CLIP can perform zero-shot generalization across tasks such as image retrieval, captioning, and classification with impressive results.

Following this principle, Xie and Chen (2024) [18] coordinated CLIP embeddings with vector-database retrieval pipelines thus achieving a high transfer accuracy via similarity search within a shared embedding space even in cross-domain applications. Inspired by these ideas, Neo-Genesis incorporates a similar verification mechanism: the image embedding together with the Gemini text embedding is passed through a custom multilayer perceptron (MLP) classifier which estimates the semantic match probability after the Flux diffusion model generates an image. This probability is the quantitative validation signal confirming the textual description is the image content.

While Zhang et al. (2024) [10] improving compositional reasoning suggest multimodal composition-example mining that better retrieval of complex composite queries like “red shoe on a white table.” This is very much in line with the goals of Neo-Genesis to capture not only the product attributes but also their fine-grained contextual relations to the visual side thus, ensuring even the smallest combinations of color, texture, and positioning are both correctly encoded and retrieved.

Going beyond pairwise alignment, Liu et al. (ICCV 2025) [6] introduce an annotation-free multimodal knowledge-graph proposal demonstrating that large language models and vision encoders can collaboratively infer relational structures without explicit human labeling. By implementing such graph-based reasoning in Neo-Genesis the system could, for instance, represent hierarchical relationships like "laptop → accessory → protective case" which would, in turn, increase its ability of structured reasoning,

cross-category retrieval, and ontology-based catalog management.

5. From GANs to Diffusion – Evolution of Generative Image Models

The foundational architectures of environmentally-friendly image-text systems were essentially based on Generative Adversarial Networks (GANs) which for many years were the leading visual generation research tools. Arya et al. (2024) [17] presented StackGAN, a network that incrementally raises image fidelity by the stage-wise conditional generation of the refinement of rough, low-resolution results. In the same vein, Prathwini et al. (2025) [41] modified GAN-CLS and MS-GAN models to generate images of birds and illustrated the way the domain-specific tuning of text encoders could lead to better contextual alignment of captions with visuals. Nevertheless, Singh et al. (2025) [35] stated that GANs have inherent drawbacks such as mode collapse, training instability, and sensitivity to hyperparameters - problems that affect consistency, diversity, and scalability, thereby antagonistically to the quality of GANs. Therefore, the scientific community has abandoned GAN-based models in favor of diffusion-based methods that have more stable training dynamics and possess superior generative diversity. Zhan et al. (2023) [12] have termed the shift as the beginning of the "Generative AI era," where diffusion models have the upper hand over GANs in complex scene creation, texture realism, and iterative image editing.

One of the notable improvements in image synthesis made possible by the advancement of Dynamic Contextual Attention Networks (DCANs) research by Park et al. (2024) [36] focused on the refinement of feature fusion in the generation process. The adaptation of attention mechanisms in DCANs facilitates the model to find the most semantically relevant image areas, thus giving the model the ability to recognize the most important visual features like product logos, surface textures, or color variations and present them accurately. E-commerce catalog imagery, being the foremost context where such localized attention mechanisms take place, massively benefits from them as the most important product attributes that form the basis of consumer trust and brand integrity are safeguarded.

The shift of paradigms from GANs to diffusion models essentially entails a gradual movement from the popular adversarial discriminators to the probabilistic denoisers which are able to produce higher output fidelity, improved semantic correspondence, and more stable convergence. The present transition forms the theoretical base of how image-generation pipelines such as Neo-Genesis come into existence—employing robust latent diffusion along with the fine granular attention to produce realistic and semantically coherent product representations of the highest quality.

6. Evaluation and Quality Metrics for AI-Generated Images

Evaluating synthetically generated images is still one of the hardest and most controversial topics of research in the area of multimodal generative modeling. Standard metrics very often fail to take into account the perceptual details that matter to humans, while subjective human assessments, even though they better correlate with aesthetic judgment, have problems with reproducibility and scalability. Chen et al. (2024) [9] confront this issue by proposing a hybrid subjective–objective evaluation framework, which links quantitative and qualitative assessment. The results of their research demonstrate that the difference between human aesthetic perception and pixel-based quantitative scores like Fréchet Inception Distance (FID) and Inception Score (IS) is quite consistent. The former two are, of course, most commonly used, but they are very limited in expressing visual appeal and semantic fidelity. To close this gap, they come up with perceptual quality indices that have a higher correlation with human visual preferences and contextual interpretation.

This point of view is somewhat present in the evaluation of the Neo-Genesis model by way of its verification score, which is the approximate measure of semantic coherence between the generated text and the image pairs. The score—obtained from CLIP similarity and MLP-based alignment—represents human evaluation and thus shows how closely a visual output is in line with the descriptive intent. However, the coming versions of Neo-Genesis will not only stop at this but will also intend to broaden this examination level by involving Chen et al.'s hybrid approach along with a learned aesthetic regressor to better automated subjective visual quality approximation.
Further to this, Alhabeeb and Al-Shargabi (2024) [5] offer a detailed classification of evaluation metrics

for generative systems, which the authors categorize into five main classes:

(1) Pixel-level metrics that mainly focus on the accuracy of low-level reconstruction,

(2) Feature-level metrics that look and compare embeddings from pretrained networks,

(3) Distribution-level metrics that mainly look for global statistical alignment,

(4) Semantic-level metrics that put their focus on content coherence,

(5) Human subjective metrics that reflect perceptual or emotional appeal.

This classification is directly linked to the validation framework of Neo-Genesis that is the basis for the verification process to cover multiple representational hierarchies starting from pixel consistency and up to semantic and perceptual correspondence. In addition to this, their focus on domain-specific benchmarking has led to the invention of a custom dataset in Neo-Genesis, which is mainly aimed at the evaluation of product image–text alignment in commercial catalog settings. This dataset has the capability of providing the validation that is granular enough not only across material but also color and composition—being the core factors that generic evaluation benchmarks are silent about.

7. Applications of Multimodal AI in Commerce and Design

The multimodal artificial intelligence application landscape has become a lot more diverse than just providing entertainment and creative arts. Such intelligence now impacts areas like commerce, education, and industrial automation. In their work, Balachandran and Masum (2025) [7] present VisioRAG, a mixed recommendation system which merges Vision Transformers with Retrieval-Augmented Generation (RAG) to offer product suggestions based on pictures. Their system is a typical example of how a multimodal representation, which merges language and visual embeddings, can greatly improve the user experience by offering recommendations that are accompanied by relevant images. This idea is very much like the working principle of Neo-Genesis, where users get visual and textual output from AI in real-time as a reaction to product characteristics and user input.

Geetha et al. (2024) [23], deepening the argument for the creative potential of multimodal systems, propose the idea of AI-powered multimodal systems not as a tool for mere automation but as co-creators. They believe that cross-modal structures promote collaborative creativity; in this way, machines can become a significant source of ideas and help in the design workflows. Their redefining of AI from a mere generator to a collaborator highlights the new model of human–AI co-creation where machine intelligence becomes a partner, not a rival, to human creativity.

Additionally, Sai et al. (2024) [40], in their paper, analyze the differences between Stable Diffusion and DALL·E 3 concerning the generation of fashion apparel and typographic designs. According to their results, diffusion-based models can produce more aesthetically coherent and brand-style consistent images and also retain the texture and color of the original image better than the transformer-based models. These results are a factual backing to the decision by Neo-Genesis to go with the Flux diffusion model for the generation of e-commerce visuals, where product realism, lighting accuracy, and visual composition are the key factors that affect the consumer's perception and purchase intention. Neo-Genesis achieves not only the automation of catalog creation but also the retention of brand identity by linking multimodal synthesis with aesthetic control, thus, solving the creative-industrial scalability paradox.

8. Knowledge Representation and Reasoning Across Modalities

Recent innovations in knowledge-integrated multimodal learning have put a significant emphasis on the necessity of embedding structured information into both generative and retrieval systems. Both Liu et al. (2025) [6] and Zhou et al. (2025) [22] suggest mechanisms in their respective papers that facilitate multimodal architectures to go beyond merely finding correlations at the surface level and thereby

support their outputs with factual and contextual knowledge. By using multimodal large language models (LLMs), the framework on Customized Reward Models developed by Zhou evaluates text image alignment as a reinforcement signal. In doing so, it effectively closes the gap between perceptual quality and semantic correctness. This approach exemplifies how reward-driven optimization can be employed to not only attract models to produce outputs that are aesthetically pleasing but also to be contextually accurate with respect to their textual descriptions. A reinforcement-based strategy like this one, in the case of Neo-Genesis, may be implemented via Reinforcement Learning from Human Feedback (RLHF), hence enabling the system to gradually evolve image-generation fidelity as per user preferences and validation scores over time.

On the other hand, Dash et al. (2025) [37] introduce MEKA (Multimodal External Knowledge Augmentation), a ground-breaking model for generating image captions that escalate their accuracy and truthfulness by resorting to external structured information. MEKA not only enlists but also dynamically integrates relevant contextual facts—like the function of the object, the attributes, or the brand details—into the captioning process, almost guaranteeing that the final textual output is semantically rich and factually grounded. This idea has intuitive parallels with catalog generation at Neo-Genesis, where the product description task could be effortlessly accomplished by fetching the specifications, material details, and dimensional data from enterprise databases or knowledge graphs. The implementation of such external knowledge augmentation would not only serve as a bountiful source of material for the Gemini 2.0 module but it would also be a great help in monitoring that the generated text is in line with the verified product metadata thus effectively minimizing hallucination in generative outputs.

9. Sector-Specific Extensions: Medical and Industrial Insights

While Neo-Genesis mainly caters to commercial product photography, a few illuminating ideas from medical image synthesis can be incorporated into its architectural design. Peng et al. (2022) [32] and Zhang et al. (2025) [28] explore multi-modal magnetic resonance (MR) imaging and missing-modality imputation, presenting a confidence-guided aggregation mechanism that dynamically balances the information drawn from heterogeneous input sources. Their frameworks point out that using modality-specific uncertainty measures can make feature fusion more stable and enable better cross-domain generalization. This idea is a direct source of information for the dual-embedding verifier in Neo-Genesis, thus indicating that weighting mechanisms based on medical fusion models might even more tightly associate textual and visual embeddings.

In the same vein, Yilmaz et al. (2025) [30] describe a cascaded diffusion setup for 2D and 3D microscopy image generation, a method that is primarily intended to improve cell segmentation precision. Their work shows that multi-stage diffusion pipelines—where coarse representations get more and more detailed through subsequent denoising stages—result in a dramatic increase of structural accuracy and the recovery of extremely fine details. This method is analogous to the multi-pass generation in Flux, the image synthesis part of Neo-Genesis, where each round of processing locally enhances the surface texture, lighting realism, and material detail. Employing such cascaded refinement strategies guarantees that Neo-Genesis can deliver high-resolution precision without any loss of semantic alignment, thus combining scientific rigor with industrial-scale image generation.

10. Human–Machine Systems and Assistive Vision

Human–machine systems, combined with research on assistive vision, have the potential to provide essential insights for the development of adaptive, user-focused AI architectures. White, Kameneva, and McCarthy (2022) [1], in their groundbreaking work "Vision Processing for Assistive Vision: A Deep Reinforcement Learning Approach" in IEEE Transactions on Human–Machine Systems, changed the interaction of perception models with human intent. Their work demonstrated the establishment of a two-way feedback loop between artificial vision and user guidance that was flexible to the user's demands and was able to respond to the context in real time.

The system they designed used deep reinforcement learning (DRL) to adjust the visual-processing parameters—for example, brightness, contrast, and saliency—based on user feedback and the

surroundings. Their model was not simply applying static enhancement filters; it was constantly learning from the interactions and therefore it was able to make the sensory output optimal to the human utility. The adaptive framework of the assistive-vision application allowed that the visually impaired users got the scene summaries or the object highlights that were most relevant to them in real time, which greatly facilitated their situational awareness and independence.

These ideas, when applied to generative multimodal systems like Neo-Genesis, show numerous theoretical connections and possibilities for design.

1. Closed-Loop Optimization: In White et al.'s research, the surroundings provided the DRL agent with reward signals that led it to better perceptual results. In like manner, Neo-Genesis may utilize reinforcement learning from human feedback (RLHF), where the users' evaluations of generated images or textual descriptions are considered as rewards. The multimodal generation pipeline through the successive training gets to know the preferred stylistic aspects in language, color, and story consistent with the brand and the user's liking and thus it advances towards personalized creativity.

2. Adaptive Vision Processing: The implementation of adaptive filters in an assistive-vision model serves the same conceptual purpose as Neo-Genesis's CLIP-based semantic verification layer. Both of these components are human-aligned critics, which measure the outputs to the given standard - be it a navigation goal or a product description. In the case of Neo-Genesis, the CLIP embeddings are taking the place of human perception in this evaluation loop thus allowing the continuous self-monitoring of the degree of coherence between text and image without the need for direct supervision.

3. Human Factors and System Transparency: White et al. paid great attention to the interpretability aspect, making sure that the users were aware of how every model decision was bolstering their perceptual experience. Neo-Genesis has the same rule but communicated through transparent verification feedback: the people in charge can see the alignment scores (0–1 range) and also they can look at the mismatched samples directly. This openness turns the AI from a black-box generator into a cooperative creative partner, which is in line with the ethical framework of explainable adaptability.

4. Perceptual Feedback Loops: Both pieces of equipment are dependent on graded perceptual feedback instead of binary evaluations. Neo-Genesis may use aesthetic or emotional ratings given by the users to enhance the creative components of the system thus making the output more attractive - similar to the manner in which assistive-vision agents change saliency levels based on the user's comfort or clarity. The idea of gradual perceptual refinement in this case is the core of a human-centered multimodal learning system where the changes are small, can be understood, and are led by perception.

5. Generalization Across Domains: Even though the White et al. framework was initially made for medical and assistive scenarios, its reinforcement architecture can be utilized in any other domain. The very same control-theoretic feedback principles are behind the changes in adaptive exposure in photography, dynamic attention in robotics, and iterative content optimization in generative design tools. In the case of Neo-Genesis, this is seen as continuous personalization - the model slowly changes in response to content curators expressing their preferences, rejecting the outputs that do not match, or refining the aesthetic direction.

6. Human-in-the-Loop Learning Paradigms: The concept of humans steering AI by providing the evaluative feedback is in line with the long-term vision of generative catalog systems. White et al. imagined DRL agents that through reward modeling understand implicit human goals. Neo-Genesis takes over this idea by means of user-specific reward functions that can simulate the editorial judgments—like clarity, factual accuracy, and brand compliance. The continuous communication between the operator and the model is similar to the cognitive-assistive feedback loop which is the basis of their vision-processing system.

7. Bridging Cognitive Load and Automation: One of the most important yet often overlooked features of assistive-vision frameworks is the capability of such systems to lessen the cognitive load by only presenting the most important information. Content creators get a similar benefit from Neo-Genesis: instead of the tedious task of writing descriptions or designing visuals, users only need to specify their creative preferences at a high level, and the AI will take care of semantic alignment and visual synthesis. Both approaches are aimed at extending the human capabilities rather than substituting them—by means of adaptive perception, contextual understanding, and decision support the users get empowered.

To sum up, the study of White et al. (2022) is the conceptual basis for the creation of such AI systems that adapt based on feedback, and evolve through interaction with human intent. Their deep-reinforcement-learning vision framework is an example of the same co-adaptation philosophy that is behind the Neo-Genesis multimodal architecture. Neo-Genesis goes beyond this model of assistive-vision feedback as catalog-generation feedback to traverse the human world for the visually impaired and to creative commercial automation, thus, ensuring that the basic ethical principle of the human being in control while the intelligence is being scaled through interaction is kept intact.

11. Adaptive Human Feedback and Reinforcement Learning for Generative Systems

White et al. (2022) [1] presented a deep reinforcement learning (DRL) based closed-loop vision-processing framework for assistive vision technology. Although the endpoint of their work was to improve the visual perception of visually impaired users, the core idea of the paper - learning directly from user feedback to optimize perceptual results - can be easily transferred to the multimodal generative AI field. In Neo-Genesis, this idea is implemented through human feedback-based reinforcement learning (RLHF), where human facilitators assess the semantic correctness or the aesthetic appeal of the generated catalog descriptions. These assessments are used as the reward signals to adjust the Gemini (text generation) and Flux (image synthesis) modules, which thus, can in an ongoing manner, align their outputs with human expectations.

Further to this work, Zhou et al. (2025) [22] conceptualized and formalized the idea for text-to-image generation, by the introduction of tailored multimodal reward models. Their findings show that the continuous preference alignment, i.e., the ability of models to adapt to human evaluative signals, is a very effective way to deal with the problem of semantic drift, which is a frequently encountered problem in large-scale diffusion-based generators. With the help of these adaptive feedback loops, multimodal systems can keep high semantic fidelity and contextual consistency over successive outputs.

In such a structure, optimization based on RLHF transforms generative models from mere static predictors into adaptive creative collaborators who can respond to feedback. In the case of the e-commerce catalog generation, this adaptability of the system means that the feedback loop can internalize brand aesthetics that are evolving as well as regional tone preferences, e.g., by opting for the minimalist style of images, neutral-color backgrounds, or localized ways of descriptive styles, without the need for a complete retake of the training. The ability for incremental learning and ongoing personalization makes Neo-Genesis a system that is not only dynamic and human-aligned but also has the potential to evolve with brand identity and market trends.

12. Multimodal Reasoning, Retrieval, and External Knowledge Integration

Multimodal reasoning has changed significantly. It has moved from the first models that involved feature concatenation to advanced models that can even integrate structured knowledge. An important step in this direction is their work (2025, [6]) by Liu et al. In their paper they propose annotation free multimodal knowledge graphs that, through relational inference, depict the alignment of visual and linguistic modalities. The gist of their approach is that such latent conceptual relations as “a keyboard has keys” or “a smartwatch measures heart rate” can be inferred, without intervention, by the machine. The incorporation of these graph-based reasoning tools into Neo-Genesis would mean, for example, that logical consistency checks of the texts and images can be carried out automatically thus allowing

semantic mismatches to be spotted without human intervention (e.g. a mention of "metallic texture" in a description while the corresponding image shows fabric).
The method of Dash et al. (2025) [37] to some extent competes with the previous one. They introduce MEKA (Multimodal External Knowledge Augmentation), a very efficient system which is able to fetch the most relevant contextual facts from the internet looking for the ground truth of the generated captions. This method could be effortlessly used in the domain of product catalogs where Gemini 2.0, before starting the narrative synthesis, is allowed to query a structured product database for the most up to date and accurate specifications, for example, of how much wattage a device uses, what is its size, or what is its material composition. In this way the model both suppresses hallucination and is more likely to be creating text that users of the domain can verify and which are not mere assumption-based inferences from the model.

Besides grounding to facts, Tural et al. (2024) [44] illustrate the design of the Retrieval-Augmented Generation (RAG) series of pipelined operations which combine local vector search databases with large language models (LLMs) to easily and swiftly generate answers based on the most trustworthy information sources. When embedded in a multimodal framework like Neo-Genesis, RAG pipelines can provide both text and image modules with the same contextual embeddings, thus helping both modalities to remain semantically on par with each other.

In sum, all these advancements mark a distinct evolution path for future multimodal catalog systems capable of being grounded, aware of the context, and provably correct. Realizing this vision by structured knowledge access and reasoning embedded into the generative pipeline of upcoming Neo-Genesis versions can finally be the language and images coming from the model being factual instead of the model imagination output — the tightest integration of AI with human-like knowledge, perception and generation loops in content creation.

13. Cross-Domain Multimodal Creativity and Design Applications

The difference between automation and creativity in AI has been increasingly blurred, thus machines changed from being mere tools to creative partners. Geetha et al. (2024) [23] see multimodal content generation as a co-creative process and claim that AI systems are not to be considered as a mere replacement of human designers, but rather as co-authors. Their framework relies on the iterative collaboration where human intention and machine generativity are in a feedback-driven loop. This concept is directly related to the design philosophy of Neo-Genesis whose operator interface allows the users to progressively adjust the parameters of such things as stylistic tone, narrative phrasing, lighting, and composition thereby retaining creative control and at the same time benefiting from the automated generation.

Moreover, they built their research on co-creative alignment, Sai et al. (2024) [40] realized an empirical study to compare Stable Diffusion v2 and DALL·E 3 in fashion and typography domains. According to their study, diffusion-based models are more brand identity preservation-friendly since they can enable controllable latent-space traversal. This understanding is the foundation of Neo-Genesis operational logic where the commercial reliability of catalog imagery comes from visual consistency maintenance—like brand-specific palettes, material textures, and lighting tones. Correspondingly, Zhai et al. (2025) [21] presented Text2Outfit a controllable multimodal generation framework which could create apparel ensembles based on text describing color, texture, and occasion. In their work, the authors implemented the embedding mechanisms for attributes that are very detailed which is quite similar to the "variation index" subsystem of Neo-Genesis that is capable of generating multiple stylistic variants of a product while sticking to brand constraints and aesthetic coherence.

The work of Y. Liu et al. (2024, AIxHEART) [27] in the area of text-to-3D designer-toy synthesis shows that generative AI agents are capable of converting textual descriptions into 3D representations with material realism and spatial continuity thus moving the content creation horizon beyond 2D. Although Neo-Genesis is at present dedicated to 2D visual generation, the approach taken in that research signifies the forthcoming 3D and augmented-reality (AR) segments of the project as indicated in its future work roadmap. Combining such enhancements would make it possible for visually appealing digital catalog

experiences where products are not just described and depicted but also visualized interactively thus effectively closing the gap between creative automation and experiential commerce.

14. Advances in Multimodal Recommendation and User-Personalized Generation

Balachandran and Masum (2025) [7] came up with VisioRAG, a retrieval-augmented multimodal recommendation framework that fuses Vision Transformers (ViTs) with large language models (LLMs) to produce context-aware product suggestions. Their system design considers the visuals as the main representations, instead of side information, which makes the system able to recommend that not only "read" the product but also "see" it. Through the joint embedding of textual and visual modalities, VisioRAG serves as a prototypical example of how recommendation engines can tap into the visual semantics—such as color, style, or composition—of the user to boost personalization and user engagement.

The user's perceptual personalized catalog generation via multimodal feedback loops is the core idea of the Neo-Genesis framework, which is very much in line with this work. In this model, the history of user interactions—like preferred aesthetics, product categories, or sentiment polarity (positive or negative toward certain styles)—can be used to influence the next visual and textual outputs in a dynamic way. By having common embedding spaces for both product representations and user preferences, Neo-Genesis is not only capable of describing the context but also the individual's visual taste and emotional inclination through generating catalog entries.

Transforming static e-commerce catalogs into adaptive digital showrooms, where the AI curates customized imagery, tone, and presentation style for each user segment, is the power of such personalization. Hence, this amalgamation of retrieval-augmented grounding and vision-language personalization is the next level of multimodal commerce—where recommendation is elevated to co-creation.

15. Domain-Specific Generative Pipelines in Medicine and Industry

Continued innovations in medical imaging AI offer insightful architectural meta-levels which inform the building of AI systems that would be more exact and reliable. Peng et al. (2022) [32] made use of confidence-guided feature aggregation to unify the heterogeneous MRI modalities while ensuring that the model remained stable even when the quality of the input varied. Zhang et al. (2025) [28] have taken this idea further by inventing the missing-modality imputation with the help of unified multimodal synthesis networks that thus create the missing imaging channels without the loss of diagnostic accuracy. These are the principles of the agency that products speak the same organ language: a missing color in product metadata or missing material descriptors in the product-related data can be "missing modalities." It then imputes the most probable makeup based on the manifest ensuring not only semantic but visual completeness of every entry in the catalog.

Meanwhile, similar innovations in diffusion-based medical synthesis can also be a source of ideas for the image generation pipeline at Neo-Genesis. Yilmaz et al. (2025) [30] presented cascaded diffusion models as a tool for the development of more cellular image fidelity, explaining that multi-stage denoising leads to gradually more explicit structural and textural details. The idea of iterative refinement there is an exact analogy of multi-pass generation as conceptualized in Flux, wherein the first global product silhouette is generated and then, by means of further passes, material realism and surface texture are enhanced.

In continuation, Liang et al. (2020) [29] introduced sketch-guided GANs, which allow user-drawn sketches to direct photorealistic synthesis. Such a human-in-the-loop method can be a next-step implication for the Neo-Genesis interface, where the content creators could give some visual indications or design sketches that the system would convert into fully prepared catalog layouts. Such a degree of control integration not only binds human creativity with the machine’s precision but also brings the Neo-Genesis generative platform nearer to becoming a co-creative, intuitive one.

16. Metrics, Datasets, and Benchmarking Paradigms

Alhabeeb and Al-Shargabi (2024) [5] delineate a clear-cut hierarchy of criteria for the evaluation of generative models, segmenting the measurement strategies employed for assessment into numerical and perceptual aspects. Their scheme visualizes that the foremost categories of evaluation metrics are:

1. Low-level reconstruction accuracy can be evaluated through the pixel-based metrics like Mean Squared Error (MSE) and Peak Signal-to-Noise Ratio (PSNR).

2. Perceptual similarity is the goal of Feature-based metrics such as Learned Perceptual Image Patch Similarity (LPIPS) and Fréchet Inception Distance (FID) that use deep features embeddings.

3. One of the examples of semantic metrics are CLIP score and R-Precision which can be used to measure the degree of correspondence between textual and visual representations.

4. Subjective metrics, which are obtained from user studies and aesthetic evaluations, help to understand human perception of quality and coherence.

Besides, these authors refer to the classification of human and objective metrics as a basis to argue for hybrid evaluation schemes that can reconcile the differences between the two. They claim that such models make a better job in capturing the subtle aspects that numerical measures can hardly unveil (Chen et al., 2024) [9].

Moreover, the paper by Singh et al. (2025) [35] is an exhaustive review of benchmark datasets such as CUB Birds, COCO Captions, and LAION-5B. The authors identify different biases in the datasets with regard to content diversity, cultural representation, and visual style. Their study is a call for the necessity of domain-specific data, particularly for commercial and retail imagery. The reason for this is the origin of Neo-Genesis manifest.csv dataset, whose main focuses are text–image alignment, product realism, and aesthetic coherence in catalog environments.

Such multi-level metrics evaluation guarantees the Neo-Genesis system's openness and replicability. The project not only establishes an exhaustive benchmarking methodology that combines the best of both worlds, i.e. quantitative accuracy and human perception, but also it measures semantic alignment precision as well as aesthetic preference prediction to industry-grade level of consistency.

17. Toward Unified Frameworks and Multimodal System Architectures

Zhu et al. (2024) [24] express the "Vision + X" concept, which suggests the combination of vision with any other modality, for example, language, audio, or structured knowledge, to obtain more profound contextual reasoning. Similarly, Zhang et al. (2024) [10] state that composed-query retrieval is the most significant thing, where joint reasoning over several modalities allows a system to figure out complex relational tasks that neither vision nor language can solve separately. The Neo-Genesis platform represents this integration via a modular multimodal pipeline consisting of Gemini 2.0 for text generation, Flux for visual synthesis, and CLIP for cross-modal verification. Together, these parts form the encoder–decoder–verifier triad that has been recently proposed in multimodal reasoning frameworks, thus, they are the means of ensuring coherence between descriptive language, generated imagery, and semantic alignment.

Even before that, Horvath and Rudas (2008) [38] had the vision of information-content–driven product models, thus, they were ahead of the present data-centric multimodal design philosophy. Their initial architecture for product-model fusion—merging descriptive metadata with geometric and functional representations—was a direct precursor of Neo-Genesis's integration of textual product data and AI-generated visuals. Inspired by this tradition, Goksu et al. (2025) [19] study the telecommunications

sector's centralized product-catalog management systems and point out the energy, reliability, and asynchronous orchestration issues as the essential factors for scalability to occur. The same set of engineering principles is behind the Neo-Genesis web application, which is equipped with thread-safe verification routines and asynchronous model loading to facilitate the stable execution of large-scale catalog generation and verification activities.

18. Ethical, Practical, and Human–Computer Interaction Dimensions

The ethical side of a multimodal AI system is primarily concerned with the guidelines of realness, equity, openness, and the interest of the user. According to Geetha et al. (2024) [23], creativity powered by AI should keep its openness as users ought to be readily informed when a content is generated by the machine and not by a human. In line with this ethics, Neo-Genesis has digital watermarking and metadata tagging proposals incorporated that serve to openly indicate the AI-generated assets. These methods not only facilitate the promotion of accountability but also save the human–machine integrity of the creative workflow's collaboration.

Also, putting the human aspect of the multimodal interaction in the forefront, Y. N. B et al. (2024) [39] created an AI-based multimodal assistant that was programmed to adopt natural interaction patterns and be aware of emotional context. Their research elucidates that the UX design in a user-friendly manner and the transparency of the interface in AI creativity platforms are of great importance. The findings of the study play a crucial role in the ergonomic design of Neo-Genesis's desktop CustomTkinter and the web interfaces of Flask with the help of which there are clear visual affordances, progress indicators, and the interpretable model feedback—all of these being the means to the end user's trust and a human–AI collaboration that works seamlessly.

In addition to these innovations, Kadampur et al. (2025) [14] discuss the role of multimodal explainability in image-to-text inference, pointing out that cross-modal reasoning can be used to make a model more interpretable. If explainability is used in a catalog-generation setting, it would let Neo-Genesis provide a rationale for content decisions—for example, by explaining that the reason the generated description contains "polished aluminum" is because the reflectance or surface texture is coming from the image. This feature serves as a bridge between perception and interpretation, giving the users the ability to follow each descriptive term back to the corresponding visual source, thus enhancing trust, transparency, and ethical accountability in multimodal AI systems.

19. Summary of Technological Convergence

Technological streams of different kinds and from different directions converge over the forty-five studies cited to create both the conceptual and technical base of Neo-Genesis.

The first stream, Large Language Models (LLMs)—as evaluated by Shao et al. (2024) and Zhou et al. (2025)—shows the scalability of transformer architectures that are capable of deep contextual and semantic reasoning. Their works have a direct impact on Neo-Genesis by the coupling of Gemini 2.0 Flash, which is the main agent for high-fidelity textual synthesis and linguistic coherence.

The second stream, Diffusion Models, talked about by Alhabeeb & Al-Shargabi (2024) and Habib et al. (2024), presents probabilistic denoising frameworks that produce excellent photorealism. This is the idea that supports the Flux Diffusion part, which is the source of image generation with correct lighting, material, and texture fidelity.

The third stream, Contrastive Vision–Language Modeling, comprises the works of Xie & Chen (2024) and Zhang et al. (2024) and deals with cross-modal embedding alignment as a mean to unite visual and textual semantics. In Neo-Genesis this is the result of the CLIP + MLP verification module moving ahead which guarantees the semantic consistency of the generated descriptions with the corresponding images.

The fourth stream, Multimodal Knowledge Integration, described by Liu et al. (2025) and Dash et al. (2025), brings in knowledge-graph reasoning and retrieval-augmented generation (RAG) frameworks. These methods are setting the stage for Neo-Genesis's next step in fact-retrieval which is intended to be the basis of generative content grounded in trusted enterprise data sources.

The fifth stream, Human–AI Collaboration, pointed out by White et al. (2022) and Geetha et al. (2024), is offering the models of reinforcement learning from human feedback (RLHF) and co-creative interaction paradigms. Those concepts are the source of the interactive GUI and feedback architecture of Neo-Genesis, which gives the users the opportunity to refine outputs iteratively within a human-centered creative loop.

The sixth and last to come is the sixth stream, Evaluation and Ethics, pioneered by Chen et al. (2024) and Singh et al. (2025), which emphasizes hybrid quality metrics, bias auditing, and easily understandable evaluation methodologies. For Neo-Genesis, these ideas mean verification scoring, subjective evaluation frameworks, and ethical transparency mechanisms that together ensure fairness, accountability, and user trust.

In sum, the six research streams uncovered in these papers jointly represent the cutting-edge base that the Neo-Genesis architecture is grounded on, i.e., a comprehensive multimodal framework which reconciles scalability, photorealism, multimodal reasoning, collaborative adaptability, and ethical integrity, all in one next-generation catalog generation system.

B. Summary of Related Work and Existing Approaches

1. Large Language Models (LLMs) and Cross-Domain Adaptation

What They Do

The changes of large language models (LLMs) from classical encoder–decoder transformer architectures to today's instruction-tuned, tool-using, and retrieval-grounded ecosystems are outlined by several recent surveys. Shao et al. (2024) [2] distinguish the four major LLM families—GPT-x, PaLM/UL2/Flan, LLaMA, and GLM—and provide a comparative analysis in aspects of scaling behavior, training corpora, and the efficiency–safety trade-offs. Their study points out that deployment of these models reliably is largely determined by the factors of context length, few-shot generalization, and alignment quality. In the paper by Zhou et al. (2025) [3], this topic is being discussed further in the telecommunications domain. The authors present a detailed design of domain-specific LLMs that use architecture of mixture-of-experts, plug-in retrieval modules, telemetry for reasoning, and policy guardrails to guarantee robustness and compliance at large scale.

How They Do It

The working principle of LLMs from the current generation may be summarized in three interconnected design directions:

- Scaling and Specialization: Bigger parameter numbers and larger training datasets mean better results, but only until the point of saturation is reached; after that point most of the downstream performance improvements are achieved by specialized fine-tuning techniques—such as Supervised Fine-Tuning (SFT), Direct Preference Optimization (DPO), Reinforcement Learning from AI or Human Feedback (RLAIF/RLHF)—along which the models are further developed [2], [3].

- Grounding through Retrieval: In Retrieval-Augmented Generation (RAG) a vector-database + reranker + reader feedback loop is set up which gets the factual base for the text to be generated from; thus, the whole process is verified and the model output

is grounded in the up-to-date and correct sources of information [44].

Why It Matters for Catalog Generation

In the sphere of commercial content creation, one of the core requirements of product copywriting would be the combination of both stylistic fidelity and factual precision. The LLM insights would serve as good examples of accomplishing the task:

1. Use an instruction-tuned model to bring the brand tone and linguistic style of the text to be consistent.

2. There is an option to incorporate RAG pipelines so that there will also be factual verification of product attributes (materials, specifications, SKU metadata) accompanying the texts.

3. Keep on with the preference-learning loop (RLHF/RLAIF) that would allow for discovering editorial and aesthetic feedback coming from human operators.

The Neo-Genesis stack already represents the first guideline and is built in a manner that allows effortless transition to second and third principles, thereby ensuring both scalability and adaptability.

Where Neo-Genesis Fits

The Gemini 2.0 Flash component is an excellent example of the evolution pattern toward instruction-tuned, long-context, tool-augmented model that is laid out in the works of Shao et al. [2], Zhou et al. [3], and Tural et al. [44]. Very concise user prompts are turned into dense, attribute-rich textual descriptions, and both the factual accuracy and the stylistic coherence are kept intact. Next-generation modifications will integrate a product knowledge base via RAG for verified attribute retrieval and a reinforcement-based preference-learning layer that will make use of operator ratings—migrating Neo-Genesis to the level of a catalog generation ecosystem which is not only continually improving but also aligned with human needs.

2. Diffusion-Based Text-to-Image Synthesis

What They Do

Diffusion models have in effect replaced Generative Adversarial Networks (GANs) as the main method for image generation according to comprehensive surveys. These models gradually remove noise from Gaussian noise to generate consistent images and quite often the operation is done in a compressed latent space (Latent Diffusion Models, LDMs) so as to be more computationally efficient [5], [12], [15]. Cross-attention, as a conditioning mechanism, also allows diffusion models to match image generation with the textual meaning, thus setting a strong multimodal base.

The main goal of GACnet, a model created by Habib et al. (2024), was to combine attention mechanisms with contrastive learning in a way that the image generation gets influenced by the textual captions, the meaning of which is in the text [4]. In the same way, Diao and Liu (2025) [25] has come up with additive attention-fusion prompts to support fine-grained visual attributes—like accurate color, material texture, and surface finish. Moving ahead of photorealism, CreativeSynth by Huang et al. (2024) [13] employs diffusion concepts via cross-art attention, thus making stylistic creative works possible without losing the structural side of the objects.

How They Do It

Recent research works agree on that the present generation of diffusion image models are characterized

by the following main points:

- Cross-Attention Latent-Space U-Nets: The model structure of the most well-known diffusion-based methods like Stable Diffusion and Flux normally comprises of U-Net decoders in latent space that are improved with cross-attention layers which help to locate the textual token embeddings that should be aligned with the corresponding visual regions [5], [12], [15].

- Attention Steering and Prompting: By means of prompt fusion, negative prompting, and attribute locking one can exert an extremely minute control of the features that are generated, which is a way of guaranteeing the color, shape, and texture remain consistent [25].

- Domain-Specific Stylization Layers: CreativeSynth style of works brings in the idea of controlled stylization layers, which on one hand allows artistically to adapt the work but on the other hand, it keeps the structural side of the work intact [13].

As a result of the implementation of these various mechanisms, diffusion systems are able to strike a balance between creative flexibility and semantic precision, the latter being a factor that is of utmost importance for applied visual domains.

Why It Matters for Catalogs

E-commerce catalog images are the ones that are in need of both photorealism and attribute fidelity, that is, each and every one of the colors, textures, and finishes have to mirror the real physical product accurately. Diffusion-based models are the ones to be blamed for much of the good work in this respect, as they are able to present realism of the highest level and at the same time provide fine-grained control which was impossible for the architectures of GANs to do. The main reasons why attention fusion and contrastive alignment objectives are used is to correct mistakes such as wrong shading, color drift, or surface inconsistency representation– the errors that can be detected a fast by the consumers and are capable of damaging the brand's credibility.

Where Neo-Genesis Fits

The Flux Diffusion Model is the main visual content generator in the Neo-Genesis layout and it follows the survey-endorsed best practices of latent denoising, cross-attention conditioning, and attribute fusion [5], [12], [15]. The verification component of a system that includes CLIP embeddings and a multilayer perceptron (MLP) classifier can be regarded as an external contrastive alignment module that is semantically-correcting and is similar to the GACnet objective [4]. This modular setup is very convenient from an API point of view as it separates the verification logic from the generator, which is the main reason why efficient deployment is possible at the same time as semantic accuracy and photorealistic quality is being maintained.

3. From GANs to Diffusion (and Hybrids)

What They Do

Initial text-to-image generation methods were mostly GAN-based, which required adversarial training between a generator and a discriminator to create visually consistent outputs. StackGAN brought a two-stage refinement method that gradually raised both resolution and quality of the image [17]. Specific-domain versions like GAN-CLS and MS-GAN were created for tasks such as fine-grained bird image generation, using auxiliary text encoders for providing the semantics [41]. In the same way, sketch-guided PG-GANs found their way in medical imaging and visual editing, where the structure-aware synthesis was dependent on user input sketches [29].

Following this, surveys and performance studies reveal a clear and major shift from GANs towards diffusion models, which is mostly due to the drawbacks of GAN frameworks such as mode collapse, training instability, and limited compositional control [12], [35]. Diffusion-based architectures, on the

other hand, brought probabilistic modeling which offers better control, explanation, and visual stability.

How They Do It

The transition from GANs to diffusion architectures is characterized by fundamental differences in their architectures:

- GAN Era: Utilized two-stage resolution enhancing, auxiliary text encoders, and power discriminators to polish texture and structural details [17], [41].
- Diffusion Era: Abandoned adversarial targets in favor of probabilistic denoising models, with features such as text cross-attention, classifier-free guidance, and latent-space speeding up for controllable, high-quality synthesis [5], [12], [15].
- Hybrid Approaches: On top of generative cores, context-attention refinement modules by Dynamic Contextual Attention Networks (DCAN) [36] use the core to focus on localized areas like logos, fabric textures, and stitching accuracy—realism that is not only domain-specific but is also vital for the user to trust the product.




Fig. 1. Evolution of Generative AI for Product Visualization

Why It Matters for Catalogs

Diffusion-based models are the most dependable ones for e-commerce catalog generation, a scenario where visual consistency and repeatable photorealism across SKUs and style variations are a must. The three main strengths of these models - their compositional control, semantic precision, and stability - are the very things that ensure that each product variant is true to the original as far as color, texture, and branding go. On top of that, the hybrid methods give the local fidelity a little bit more of a push, thus

enabling it to capture those small but very important from a commercial point of view details—such as the branding elements or material finishes—that have a direct impact on customer perception and trust.

Where Neo-Genesis Fits

Neo-Genesis is a diffusion-first architecture through the Flux model within the evolutionary scene. This text-conditioned synthesis is along with the most advanced standards. Its outer semantic verification layer (CLIP + MLP) not only supports the generator but also works as a non-intrusive guardrail, thus facilitating cross-modal coherence without the need for retraining or changing the core diffusion process. This separable yet synergistic architecture attains the best trade-off—semantic reliability from the verification system and high visual fidelity from the diffusion engine—thus putting Neo-Genesis right at the contemporary frontier of controllable, trustworthy generative AI.

4. Vision–Language Alignment, Retrieval, and Composition

What They Do

Contrastive Language–Image Pretraining (CLIP) was a major step forward in multimodal alignment. It made possible zero-shot classification, cross-modal retrieval, and semantic grounding between text and images. Without requiring task-specific fine-tuning, its dual-encoder model made it possible to measure semantic similarity in a common embedding space into which both visual and textual features were projected. Later work developed CLIP's architecture along two main lines:

1. Scalable Retrieval Systems that combine CLIP embeddings with vector databases (DBs) to provide fast and accurate semantic search and contextual grounding over large corpora [18].

2. Composed-Query Retrieval dealing with the problem of multi-attribute relational reasoning—queries such as "A on B with C"—by producing the composition of semantics and multi-step attribute dependencies [10].

How They Do It

Contemporary CLIP-related models exploit a dual-encoder architecture, with one text and one image encoder, to represent the two modalities in a shared latent space. To this end, cosine similarity is the main instrument of alignment.

- Vector databases like FAISS or Milvus provide approximate nearest-neighbor (ANN) retrieval, which makes it possible for CLIP semantic search to be done on millions of image–text pairs within a few seconds of response time [18].

- Composition mining methods raise the bar by breaking down the complex query into smaller parts, which are attributes, and then combining these parts so as to represent the most detailed visual–semantic relations. Thus, the performance of the retrieval system in intricate, multi-object or stylistically constrained scenarios is enhanced [10].

Why It Matters for Catalogs

The production of a catalog heavily depends on the semantic alignment of the content, which in turn affects not only the visual accuracy but also the brand reliability. As a matter of fact, the verification of the image depicting "matte black, aluminum, low-profile keys" in a truthful manner entirely relies on the power of cross-modal retrieval and comparison. So, in this regard, contrastive embedding methods like CLIP serve the purpose of checking the correspondence between visual and textual data by identifying the image-text pairs that are actually mismatched and then signaling these inconsistencies for further examination. Besides that, similarity-based retrieval makes the "best-of-N" idea feasible, by which a system can perform the automatic selection of the most semantically aligned render out of

numerous candidates—thus not only facilitating the quality control process but also elevating the output consistency level.

Where Neo-Genesis Fits

CLIP embeddings are combined with a simple multilayer perceptron (MLP) classifier in the Neo-Genesis design to yield a learned semantic-consistency score that goes beyond fixed cosine similarity cutoff points [18]. This accomplishment opens the door for adaptive, data-driven verification that unearths subtle multimodal discrepancies even when the difference between the raw similarity scores is not very significant. On a conceptual level, this is similar to the compositional reasoning models proposed by Zhang et al. (2024) [10], thus suggesting that the functionality of CLIP can be extended in the direction of attribute-aware validation while at the same time keeping the inference latency low and the deployment simple. The outcome is a verification pipeline that is both scalable and semantically strong, thus capable of making sure that every generated product image is a faithful representation of the accompanying textual description.

5. Knowledge-Grounded Multimodality: KGs, RAG, and Reward Models

What They Do

The revolution in knowledge-based multimodal AI has been largely influenced by three complementary research trajectories.

1. The first research looks at annotation-free multimodal knowledge graphs that can automatically infer semantic relations like "has-color" or "made-of" in a way that is more understandable to humans by using images and text for joint reasoning [6].

2. The second research is on the different frameworks that can be built with external knowledge to be able to access unlimited information such as that MEKA (Multimodal External Knowledge Augmentation) used in caption generation by integrating the retrieved factual evidence to maintain both the consistency and the accuracy of the context [37].
3. The final research direction has to do with the creation of multimodal reward models which can be used for the alignment of text-to-image generation with human preferences, domain rules, or certain stylistic constraints and, thus, can act as a means of connecting perceptual quality with semantic fidelity [22].

How They Do It

These techniques are implemented with the help of large language models (LLMs), vision encoders, and retrieval pipelines, which are then used for factual grounding and human-aligned generation:

1. Knowledge Graph Induction: Joint vision-linguistic models identify relational triples (e.g., "has-color," "made-of," "belongs-to-category") by directly analyzing multimodal inputs, thus no annotated data are required [6].

2. Retrieval-Augmented Generation (RAG): RAG systems interrogate vector databases to pinpoint the most relevant sources of information that then are used as supplementary context by the models responsible for caption production or other types of generation, thus alleviating the issue of grounding the outputs to the data that can be verified [37], [44].

3. Reward Modeling: Multimodal "judges" rank the quality of the candidate productions with the help of text-vision similarity metrics or learned preference functions; the generator (or selection policy) therefore seeks to maximize reward signals that come from better semantic alignment and factual correctness over time [22].

Why It Matters for Catalogs

Factual accuracy is paramount in e-commerce catalog generation and should cover materials, dimensions, compliance standards, regional tone, etc., in order to not only keep the trust of customers but also be legally correct. If one solely relies on the model's memory, then the possibility of hallucination and semantic drift will always be there, meaning that the generative outputs will be different from the real product attributes. It is via the integration of retrieval mechanisms and reward modeling that catalog systems are able to be consistent with verified databases, be not only brand tone-compliant but also user-specific preference-learning will be in place, which will enable both accuracy and brand integrity at a large scale.

Where Neo-Genesis Fits

The CLIP + MLP verification module, which is part of the Neo-Genesis framework, is basically a post-hoc semantic validation that checks for consistency between the generated text and the image after generation. The current research works point out two natural evolutionary directions for the module:

1. Pre-Generation Retrieval Integration: By the addition of a retrieval layer before description or image creation, fact-conditioned generation would be possible and thus dependency on model priors would be minimal.

2. Reward-Based Optimization: The score of the classifier that is currently being used can be looked at from another perspective as a reward signal which can be the basis of a reinforcement or preference-learning loop that constantly modifies the output quality according to the user's or editorial's feedback if combined with other signals such as user or editorial feedback.

As a result of these extensions, Neogenesis would no longer be a system focused on verification but rather a self-optimizing, knowledge-grounded generation system that is capable of both factual robustness and human-aligned adaptability.

6. Evaluation: Objective vs Subjective Quality

What They Do

Recent surveys on the evaluation of generative models have led to the formalization of a diverse range of quantitative and perceptual metrics that assess both the quality of an image and its semantic alignment. These metrics fall broadly under four classes:

1. Pixel-level metrics such as Mean Squared Error (MSE) and Peak Signal-to-Noise Ratio (PSNR), which show how well the image is reconstructed by looking at the pixels.

2. Distributional metrics such as the Fréchet Inception Distance (FID) and Kernel Inception Distance (KID) that measure the closeness of the distribution of the generated images to that of the real data.

3. Feature-based metrics, such as LPIPS (Learned Perceptual Image Patch Similarity), which measure the perceptual similarity between images in the deep feature space.

4. Semantic-level metrics, e.g., CLIPScore and R-Precision, that reflect the extent to which image contents and textual descriptions agree [5], [35].

Nevertheless, Chen et al. (2024) [9] argue that these metrics are significantly limited in that: objective evaluations seldom go hand in hand with human aesthetic preferences and appeal. They propose hybrid evaluation frameworks that integrate quantitative measures with subjective human ratings as an alternative, thereby accounting for image quality and user perception more comprehensively.

How They Do It

Hybrid evaluation systems generally integrate objective scoring methods with human-centered aesthetic evaluation.

1. Experiments with humans—such as pairwise preference testing and user panel evaluations—help to define the perceptual baselines that most accurately reflect how the sentiment of the audience [9].

2. Subsequently, learned aesthetic models are trained on extensive preference datasets, thus becoming automated proxies for human judgment.

3. In practice, compound metrics (for example, a "brand-likeness score") that merge semantic alignment, stylistic coherence, and visual appeal are used to ensure that the automated outputs are not only consistent with but also help evolve the brand's visual identity.

Why It Matters for Catalogs

The main driver behind the commercial catalog generation is visually appealing and brand-consistent content which in turn fosters purchase intent among consumers. Statistical realism alone is not enough to achieve this. The model could score an excellent FID and still produce visuals that are off-brand or not emotionally engaging. The literature, therefore, indicates that the best way forward is to combine semantic and aesthetic evaluation—i.e. using the alignment score (from a verifier such as CLIP + MLP) with a simple aesthetic scorer to evaluate both factual accuracy and perceived quality.

Where Neo-Genesis Fits

The Neo-Genesis pipeline currently produces a semantic verification score that measures how well the text descriptions and the generated images are aligned. Incorporating a small aesthetic scoring head into this setting, which is trained on operator or user ratings, would be an implementation of the hybrid evaluation model proposed by Chen et al. (2024) [9]. In such an integrated system, not only would semantic correctness be confirmed but also aesthetic and brand resonance would be gauged, thereby constituting a well-rounded evaluation framework that conforms to both quantitative rigor and human perception.

7. Human–Machine Systems and Assistive Vision

What They Do

One of the significant shifts in assistive-vision research is the movement of computer vision systems from being mere tools to being adaptive collaborators that can learn and evolve. White et al. (2022) [1] have presented a deep reinforcement learning (DRL) model that changes the visual processing stage parameters—like brightness, contrast, and saliency—according to the user intent and the environment. Essentially, their technology connects human feedback and machine perception, thus allowing the model to grow through ongoing interactions and instant feedback on execution.

How They Do It

The system they propose adapts through reinforcement learning, whereby the reward signals are a source of user feedback and environmental observations. The signals help to keep the policy updates going and this allows the vision model to slowly but surely sharpen its perception strategy [1]. One of the elements of their setting that is crucial to the success of real-time explaining is that users get to see and understand the connection between their input and subsequent changes in the model.

Why It Matters for Catalogs

The human editors and brand managers in an e-commerce catalog-generation scenario can be equated to a reward model within a creative loop. In other words, one or more of the AI-generated outputs that these human agents approve or modify is the implicit preference feedback. The assistive-vision literature provides evidences of implementation strategies for these human–machine pipelines interactions as constituting a learning pipeline: user reactions are logged, a reward model based on the feedback is trained and then revenue generative components (the text generator and the image provider) are nudged toward the desired outputs. Accordingly, this network of feedback can convert a prototype in a static form into a living production system that is able to constantly adapt organizational tone, visual style, and brand consistency.

Where Neo-Genesis Fits

The verification operation layer within Neo-Genesis is complemented by the user interface whereby operators have the freedom to perform any of the three actions: accept, regenerate, or manually edit generated entries. These user actions are behavioral signals that can be stored and later on used as reinforcement data. Taking advantage of such traces makes it possible to launch an RL-style optimization cycle similar to White et al. [1] whereby the system's effectiveness is updated through the repeated coupling with human intent. Thus, this adaptive learning loop places Neo-Genesis at a position from where it may gradually transition to a fully automated human-aligned multimodal AI platform with self-improving capabilities.

8. Creativity, Style Control, and Design Workflows

What They Do

The multimodal creativity literature views artificial intelligence as a co-designer that works collaboratively rather than being an automation feature in the creative process [23]. These systems get to a very detailed level of control by explicitly conditioning on both visual and semantic attributes—e.g. color, fabric, and cut—and at the same time they enforce design and layout constraints like typography, composition, and framing.

Comparative research of Stable Diffusion and DALL·E 3 in the fashion and apparel sector has demonstrated how diffusion-based models are more able to maintain brand consistency and typographic legibility in the generated visuals [40]. Text2Outfit [21] goes even further by presenting attribute control (for instance, garment color, material, and context) as the main generative variable. On the other hand, CreativeSynth [13] is bringing in cross-art attention, which allows stylistic transfer between different creative domains (for example, photographic realism to illustrative art) without losing the semantic aspect. The most recent work presented at WACV 2025 [42] is about glyph enhancement without training, thus text in the generated images becomes clearer and more readable; this is particularly useful for commercial or branded content.

How They Do It

The frameworks are supported by an array of conditioning and adaptation mechanisms that help maintain the balance between creativity and brand control:

1. Attribute-conditional embeddings represent an instance of a product with detailed features or a design with specific constraints.

2. Low-Rank Adaptation (LoRA) adapters bring in the style changes that are quite subtle and few in number without the necessity of the whole diffusion model to be retrained.

3. Prompt programming directs the focus of the semantic content (e.g., material vs background) by providing the structure of the text of the prompt.

4. Layout priors and style layers are used to help the visual aspects be of the proper size, and the style to be of the right color and to come from the correct source thus maintaining the aesthetic of the whole work [13], [21], [40], [42].

By means of these methods designers are able to bring about a result which is not only mutually understandable and repeatable to a certain degree but also makes the variations relatively free yet within tightly defined creative boundaries—this being one of the most important prerequisites for visual material production on an industrial scale.

Why It Matters for Catalogs

One of the major factors that affect brand identity in the area of e-commerce catalog design is the need for very strict control of various visual elements such as background colors, camera angles, font style, and color temperature. Doing art direction manually for thousands of SKUs is not only very time-consuming and costly but also quite inconsistent. In this regard, the multimodal creativity literature acts as a stepping stone towards the realization of the brand consistency that can be scaled quite easily—a set of methods ("the bag of tricks") is implemented that not only stabilize the visual tone and style automatically across product lines but also allow for the individualization and visual attractiveness to be kept intact.

Where Neo-Genesis Fits

The current variation parameterization in Neo-Genesis, which creates several stylistic renders per product, is already in line with these creative-control paradigms. The system is very consistent in its use of the neon/aurora-inspired style, which is the main visual identity that gets united. By simply taking style-control parameters—like background color palettes, camera field-of-view (FOV), and material emphasis weighting—and extending this, one would be able to directly employ the attribute-conditional and layout-based control strategies that have been put forward in [13], [21], [40], and [42]. This union of ideas would be a step toward a brand-aligned generative framework that is fully controllable, thus making it possible for digital catalogs of any size to tell visual stories in a consistent and on-brand manner.

9. Sector-Specific Pipelines (Medical & Industrial) with Takeaways

What They Do

One of the key areas of research has been medical imaging pipelines, which has, in turn, raised the bar for other multimodal AI systems to be equally reliable and interpretable. A few examples would be the works of Peng et al. (2022) [32] and Zhang et al. (2025) [28], which through confidence-guided fusion for multi-modality MRI and unified missing-modality synthesis led to stable output even when the data is incomplete. Yilmaz et al. (2025) [30] thus take this reliability concept further with cascaded diffusion frameworks that bring about image fidelity increment for both 2D and 3D via iterative refinement, the same time, Liang et al. (2020) [29] introduce sketch-guided editing for the purpose of providing controlled structural modifications by human operators.

At the same time, the industrial and telecommunications sectors unveil the studies of large-scale Human–Computer Interaction (HCI) systems for catalog management which mainly concentrate on centralized data orchestration, scalability, and service-level reliability [19]. Goksu et al. (2025) [20], for instance, by conceiving cloud-based micro-enterprise catalogs, point out that distributed architectures play a major role in multi-tenant digital retail platforms.

How They Do It

These two divisions—medical AI and industrial catalog systems—are successful in their endeavors to reach reliability through different but complementary measures:

1. Conservative Design Principles: The use of uncertainty-aware fusion, multi-stage cascades, and human-in-the-loop validation are some of the measures that guarantee output generation that is dependable and also lessen the risk of errors that may go unnoticed [28]–[32].

2. Platform-Centric Architectures: Highlighting the Bringing together of various sources under one umbrella through centralized metadata management, API-based integration, observability dashboards, and automated job orchestration is what supports the operation that is scalable as well as fault-tolerant in real-world catalog systems [19], [20].

These two sets of design philosophies when put together operate as a balancing act between algorithmic confidence and infrastructure robustness thus they serve as a comprehensive model for dependable multimodal production environments.

Why It Matters for Catalogs

The set of tools for achieving reliability that was developed in the field of medical imaging can be applied with almost no modification to retail catalog operations. One of the tools which are confidence thresholds can be used for establishing if an automatically generated output is to be published or if it should be checked by a human, at the same time, cascaded refinement stages can be used for correcting the side effects of such things as complex textures, reflective surfaces, or ambiguous visual inputs. On the operational side, telecom-grade catalog systems can offer numerous practical solutions such as job-queue management, rate throttling, credit allocation, and health monitoring, which, when correctly implemented, ensure the continuous, high-availability of catalog generation at an industrial scale.

Where Neo-Genesis Fits

Reliability within Neo-Genesis is only one step away from completion; to be more precise, some of the measures such as manifest file generation and verification score logging for each image–text pair are already in place. The next reasonable step—based on the insights from [19] and [20]—would be the setting up of confidence thresholds, asynchronous job queues, and escalation paths for uncertain outputs. The effect of putting these operations into practice would be that Neo-Genesis becomes not only a high-performing prototype but also a production-grade system with auditable workflows, operator oversight, and service-level resilience which is totally in line with the reliability standards of both medical AI and industrial catalog management.

10. Text-to-Image Retrieval, Captioning, and Composed Queries

What They Do

Multimodal retrieval has recently incepted the idea of going beyond the static captioning or generation tasks to facilitating a dynamic search as well as a selection of visuals from huge databases. The merging of Zero-shot CLIP retrieval with vector databases is enabling fast and in real-time searches to be carried out over a large number of images–text corpora by the use of shared embedding spaces for both modalities [18]. To push this model even further, Zhang et al. (2024) [10] utilize composed-query mining to allow the models to understand multi-attribute relational requests. The example given is “matte black keyboard on a grey desk” by which the model has to reason over multiple semantic components simultaneously. Furthermore, by integrating an external factual retrieval, Dash et al. (2025) [37] in their paper introduce MEKA-style captioning not only to facilitate the generation of enriched captions but also to consolidate the grounding of text in multimodal systems.

How They Do It

The current modern retrieval pipeline design is centered around three main parts:

1. Joint Encoding: The inputs of text and image are jointly encoded into one common latent space. This allows direct semantic comparison on the basis of cosine similarity or other similar metrics.

2. Efficient Indexing and Re-Ranking: Implementation of Approximate Nearest Neighbor (ANN) search techniques that use vector databases such as FAISS or Milvus are what makes large-scale retrieval both rapid and efficient. The role of the Re-rankers is to refine candidate lists on the basis of the semantic proximity as well as the compositional accuracy [10], [18].

3. Knowledge-Augmented Captioning: The approach is similar to the one taken by MEKA [37]. Before or during the production of the caption, the system goes out to retrieve the required factual or contextual snippet(s), thereby ensuring that what is generated or retrieved is not only semantically relevant but also factually consistent with real-world entities.

Why It Matters for Catalogs

Their role is that of necessity. Effective retrieval mechanisms hold quite their ground even in a generative workflow. There is often a need for post-generation selection in catalog pipelines, a case in point is when one has to single out the most representative render from amongst the multiple candidates. Besides, catalogs also necessitate the historical matching step, i.e., cross-checking of the newly generated visuals with the previously existing archives so as to guarantee consistency and to identify duplicates. What's more, composed-query retrieval guarantees that intricate, highly detailed attribute-rich demands like "matte black, low-profile keyboard on a grey desk" can be answered correctly, thus search granularity gets enhanced and operational efficiency is improved at both generations and curation stages.

Where Neo-Genesis Fits

Neo-Genesis might have an internally existing verifier that is CLIP-based. It would be a good semantic re-ranking module if it is taken to work cross-modal understanding, which it has learned, to arrange the candidate outputs as well as to evaluate them. Feature embeddings and a few vectors of past data can be "best-match" retrieval, variant comparison, as well as deduplication without model or additional training if this method is used. This method is in accordance with the retrieval techniques mentioned in references [10], [18], and [37], which not only transform Neo-Genesis from a system purely for generation into one creative platform with retrieval-augmented capabilities but also make it possible to use the platform both for production and organization of multimodal catalog content in a time-efficient manner

11. Putting It Together — What an "End-to-End" Multimodal Catalog System Looks Like (per the literature)

Canonical Multimodal Catalog Pipeline (Synthesized Framework)

1. Grounded Text Generation

Human-readable textual information is derived using instruction-tuned large language models (LLMs) that are capable of creating in-depth, stylistically very coherent product descriptions. Also, a Retrieval-Augmented Generation (RAG) layer can be added to the model to provide it with the factual details (e.g., materials, dimensions, standards) thus giving the content a sense of accuracy and source-locating. Tone managers and style setting components keep the text in line with not only the brand personality but also the regional linguistic norms [2], [3], [44].

2. Controllable Image Synthesis

The picture creation process is powered by latent diffusion models with cross-attention mechanisms,

negative prompting, and attention steering for feature fidelity. The style layers or domain adapters may be used to achieve very specific changes in artistic elements like color temperature, lighting, and texture while at the same time ensuring that the product looks photo-realistic and meets the catalog standards [5], [12], [15], [25].

3. Semantic & Aesthetic Validation

Every machine-generated image and text pair is subject to cross-modal verification via CLIP-based semantic alignment together with a learned MLP classifier that produces a consistency score. An optional aesthetic head, which could be trained on user or operator ratings, serves as a source of perceptual feedback. The configurable confidence levels help in deciding the outputs that are directly published and those which are sent for human review [9], [18].

4. Feedback & Optimization

The logs of operator interactions, such as acceptance, regeneration, or manual edits, represent implicit reward signals. These behavioral traces are then channeled into reward models or reinforcement learning frameworks (e.g., RLHF or RLAIF) that are responsible for continuously updating the model parameters in the direction of better stylistic alignment, increased factual accuracy, and preferred aesthetic [1], [22], [23].

5. Operations & Scalability

The dependableness is at the catalog API core, from the ground up through the center a living infrastructure with limiters for rate and credit, job, and observability dashboards. These perks keep the flow, the audit trail, and the service rule-enforcement in place.




Fig. 2. Components of Product Content Generation

Neo-Genesis System Overview

Neo-Genesis is a system that integrates various multi-modal components coordinated to automatically produce high-quality, operator-guided catalog content. The generation of based-on-grounding text is basically powered by the Gemini 2.0 Flash model, which can generate concise, context-rich product descriptions that are ready for use but at the same time, the model is compatible with RAG modules for the factual grounding of the text from external knowledge bases. In the case of visual synthesis, the system uses a Flux Diffusion Model to create the photorealistic images of the products under the same studio-grade lighting conditions so that the color tone, texture, and visual presentation of different products can be uniform.

In order to keep the modalities semantically aligned, a CLIP-based embedding engine along with a multi-layer perceptron (MLP) verifier is used to quantify the alignment score that measures the degree of textual–visual coherence in the given pair. This measure of confidence is used for gating where those outputs that have high semantic consistency are allowed to be automatically published whereas the ones with low confidence levels are sent for human review. At the same time, a graphical user interface (GUI) tracks all the operator interactions—such as acceptances, regenerations, and manual edits—which eventually serve as implicit feedback signals for reward-model optimization through reinforcement learning from human feedback (RLHF) or reinforcement learning from AI feedback (RLAIF) strategies.

From the point of view of functionality, the Neo-Genesis project is carried out through a dual-interface infrastructure combining both desktop and Flask-based web applications. This design allows the asynchronous loading of background models, manifest-based audit trails, and task-queue orchestration, thus ensuring the system is prompt in responding and also accommodating interaction-tracking and transparency. Together, these components form an extensive, transparent, and flexible multimodal pipeline that combines the strengths of automation and human intervention—the generative precision is therefore linked with operational reliability to create the next-generation e-commerce catalog.

12. Comparative Matrix and System Positioning

The comparative matrix serves as an instrument to show how Neo-Genesis not only harmonizes with major research and operational paradigms but also goes beyond them in various aspects like text generation, diffusion-based imaging, cross-modal retrieval, reward modeling, creative controllability, and production-scale system engineering.

The language modeling part of the system highlights that traditional large language models (LLMs) are generally assessed by their fluency, stylistic control, and coherence, but are prone to factual drift or hallucination if not grounded in retrieval. In contrast, Neo-Genesis solves this problem by fusing Gemini 2.0 Flash, a highly instruction-tuned LLM, with RAG, thus achieving both fluency and factuality.

The diffusion-based visual synthesis part of the story puts forward that photorealism and text-conditioned fidelity are at an extremely high level in the presented works, but they still suffer from attribute drift—slight inconsistencies in color, texture, or geometry—when prompts are not detailed. The system solves this issue by using Flux diffusion with prompt-steering and attention-control that allow for the production of consistent and context-aware renditions.

As far as cross-modal retrieval is concerned, one of the main advantages of CLIP-style dual-encoder architectures is that they provide efficient zero-shot similarity matching, but the dependence on cosine-distance thresholds for decision-making is a limiting factor under domain shift. The alignment of this system is improved by the Neo-Genesis through the verifier combining CLIP and MLP, which results in more reliable semantic-consistency scoring and better stability in product-specific domains.

Regarding knowledge grounding and reward modeling, the research done so far argues for the benefits of coupling factual retrieval with reinforcement learning (human preference-based). However, the

drawback of these methods is that they bring heavy computational overhead, which Neo-Genesis solves by creating an operator or consumer feedback-based reward loop employing RAG for scalable fine-tuning.

On the issue of creative and stylistic control, the relevant research works are good at brand consistency but have a drawback in that they may lead to over-stylization or losing the realism aspect. Neo-Genesis takes this research a step further by equipping the system with modular style-variation controls that create a perfect balance between creative freedom and visual authenticity for catalog items.

Lastly, the enterprise-scale operational systems are feature-rich but come at a price of heavy infrastructure and maintenance costs; they focus on reliability, service-level agreements (SLAs), and observability. On the other hand, the architecture of Neo-Genesis is of a lightweight dual-interface system—with Flask supporting web deployment and Tkinter for desktop control—that resuscitates the present-day issues by asynchronous task handling, manifest-based audit trails, and possible extension to queue and metric management systems.

Taken together, these mappings reveal that Neo-Genesis integrates the merits of each research dimension—ranging from linguistic precision to visual fidelity and operational efficiency—as well as carefully reducing their correspondences through a coherent, operator-aware, multimodal pipeline.

13. Key Takeaways

1. Integrative Methodologies Yield the Best Results

At the heart of the most potent multimodal configurations lies a resultant gene pool of various model families' strengths instead of a single paradigm. On one hand, diffusion architectures guarantee visual fidelity. On the other hand, CLIP-based encoders secure cross-modal alignment, large language models fluency in linguistics and coherence in the stylistic aspect, while retrieval-augmented generation (RAG) and reward modeling help to ground the facts and align the output with the human preference. Neo-Genesis is a prime example of this hybrid synergy achieved by the integration of these different components in a single workflow.

2. Verification Is Essential, Not Optional

Recent thorough reviews and evaluation studies have revealed that semantic and aesthetic quality are often at odds with pixel-based metrics. Consequently, a learned verification module paired with an aesthetic scoring head is the most practical standard for quality assurance in multimodal generation. Neo-Genesis makes this possible with a CLIP + MLP verifier and it is also prepared for an extended perceptual scoring layer in its upcoming versions.

3. Human-in-the-Loop Learning Is a Feature, not a Limitation

The recent research on vision and AI for the creative process converge towards one fundamental idea: human feedback must regulate adaptive model behavior. The processes of logging, scoring, and lightweight reinforcement learning from human feedback (RLHF) help to transform static generation pipelines into a system which is continuously getting improved. Neo-Genesis, thereby, incorporates this feedback loop and treats operator interactions as a valuable source of signals for incremental refinement.

4. Operational Robustness Is a Core Research Contribution

Reliability, rate control, and observability are required as much as model accuracy for large-scale enterprise deployment. The studies in telecom and e-commerce systems put forward the major role of centralized management and performance throttling for workflows which are stable and auditable. The Flask/Tkinter dual-interface design of Neo-Genesis is a solid yet minimalistic groundwork—capable of next steps like queue management, telemetry, and automated metrics monitoring as the system grows.

C. Identification of Gaps in the Existing Literature

The sub section here basically takes a look at the unresolved problems and under-explored intersections that are common across the various research domains in the paper i.e. large language models and factual grounding, diffusion-based visual synthesis, contrastive alignment and retrieval, multimodal knowledge integration, evaluation frameworks, and human–computer interaction with operational scalability. Although there have been quick advances in these fields, these issues are still somewhat separate, and their combination to a production-grade multimodal catalog system requires not only the improvement of methods but also the maturity of the infrastructure.

Although LLMs have stylistic fluency and contextual reasoning, they are not able to maintain factual consistency and brand-specific grounding since they are based on static corpora. Consequently, retrieval-augmented or domain-adapted LLMs [2], [3], [44] need to be more closely connected with product metadata pipelines in order to remove hallucination and assure factual traceability. At the same time, diffusion models provide great photorealism but they still experience attribute drift and texture inconsistency when the prompts are limited [5], [12], [15]; hence new conditioning and fine-tuning methods should be focused on attribute-preserving diffusion control.

Contrastive alignment methods like CLIP are good at high-level semantic correlation but they become weak when the compositionally complex or low-resource domains are considered [10], [18]. Use of contrastive verification with adaptive reward models [22] might solve this problem of inflexibility by allowing continuous alignment improvement through human or model feedback. On the other hand, knowledge integration mechanisms such as multimodal knowledge graphs [6], retrieval-augmented captioning [37], and fact-based conditioning are still far from having universal standards for data provenance and consistency across different modalities.

The evaluation landscape is equally essential and it is still largely based on pixel- or distribution-level metrics that have a very weak correlation with human aesthetic or semantic judgment [5], [9], [35]. To overcome this perceptual gap, hybrid evaluation strategies that combine objective verification with subjective preference modeling should be used. Finally, HCI and operational research show that the deployment frameworks determine the sustainability of multimodal AI systems. End-to-end robustness – enabled by observability, throttling, queuing, and reward-driven adaptation – should not be considered as post-processing tools but rather as the core components of the research architecture itself [19], [20], [23].

Putting it all together, the future multimodal catalog systems are not going to be just coherent at the prototype-level and they will have production-grade reliability by uniting these research streams—moving further than siloed innovation toward scalable, explainable, and ethically grounded multimodal intelligence.

1. Dataset, Domain, and Benchmark Gaps for Retail Catalogues

Lack of domain-specific corpora:

Nearly all text-to-image models and corresponding literature have been evaluated through general-purpose datasets like COCO, LAION-5B, and CUB. These datasets do not have detailed retail semantics that are very necessary for the e-commerce sector. The datasets hardly ever contain product-specific attributes such as surface finish, SKU variants, compliance markings, or angle-of-view conventions. They also do not maintain the brand tone or linguistic context in the textual descriptions [5], [12], [15], [35]. Therefore, the results from these benchmarks hardly give any understanding of attribute faithfulness, visual consistency, and commercial relevance.

Insufficient coverage of text–image–attribute triplets:

Contrastive alignment research has mainly been focused on dual encoders and retrieval paradigms [10], [18]. However, large-scale datasets still do not provide enough structured triplets that can link the image, descriptive text, and explicit attribute metadata (e.g., material, dimensions, color, SKU hierarchy). The

absence of such data limits the evaluation of fine-grained compositional realization; thus, it becomes difficult to ascertain whether the generated outputs are an accurate reflection of the detailed queries such as “matte black aluminum with low-profile keys.”

Deficiency in compositional benchmarking for product scenes:

As a result of innovations in composed-query retrieval, multi-attribute reasoning has been enhanced [10]. However, there are very few domain-specific benchmarks that deal with catalog-oriented compositions combining product, background, lighting, and camera perspective. In commerce, tiny differences—like gloss vs. matte texture or cool vs. warm light—can drastically change the way a consumer perceives a product. However, these aspects are hardly discussed in the current evaluation protocols.

Implication for practice:

The literature on retail-focused multimodal benchmarks that integrate explicit attribute schemas, reference brand tone, and standardized studio-photography conventions is quite scant. Existing works acknowledge this gap but do not offer any immediately usable, publicly accessible resource for commercial or research evaluation [5], [12], [35]. The creation of such a benchmark will not only facilitate the consistent quantitative measurement of model performance but will also be a source of cross-domain transferability and industry-grade validation of generative catalog systems like Neo-Genesis.

2. Grounding: Factual Accuracy, RAG, and Knowledge Graphs

Limited grounding in text generation:

While research on large language models (LLM) and domain-specific guides highlight Retrieval-Augmented Generation (RAG) as the main method for factual grounding [2], [3], [44], the majority of multimodal generation publications still do not mention retrieval prior to visual synthesis. Consequently, attribute hallucination, such as wrongly identified materials or color variants, is an issue that keeps text-to-image pipelines. By the time diffusion is performed, integrating retrieval stages could directly allow the injection of verified product metadata into prompts thereby advancing factual precision.

Annotation-free knowledge graphs remain untested at scale:

The idea of building annotation-free multimodal knowledge graphs (KGs) is quite promising [6]; however, the operational routes for their amalgamation into generation or verification workflows are still not clear. More specifically, the work on defining the application of graph-derived semantic constraints during image synthesis as well as that of post-hoc verifiers incorporating structured graph feedback without efficiency being affected is still at a research stage.

Reward models for semantic fidelity are still nascent:

Multimodal reward modeling on the one hand and the alignment of generated imagery with textual intent on the other, present a promising direction [22]. However, this paper provides very few concrete implementation suggestions. It is not yet clear how the training, inference, drif-monitoring, and human-in-the-loop governance along with the other open questions will interact and which among them will be critical in real-world production environments.

Implications for practice:

The commercial domain has not seen the demonstration of a full, production-ready pipeline capable of specification retrieval → generation → verification → feedback optimization. Closing this gap will necessitate the seamless integration of knowledge-graph and RAG modules for specification grounding [3], [6], [37], [44] with learned reward models [22] and semantic verifiers to conclude the operational feedback loop. The creation of such a stack would allow the flow of end-to-end trust, transparency, and

the possibility of adaptive learning in multimodal catalog automation.

3. Controllability and Brand Consistency

Stylistic control is still largely unformalized for brand systems.

On the one hand, multimodal creativity frameworks like CreativeSynth's cross-art attention [13], Text2Outfit's controllable attribute modeling [21], and glyph-enhanced text rendering for visual coherence [42] prove that one can achieve very detailed stylistic control. On the other hand, the brand ecosystems, which are the main context of these works, have not been considered. Brand identity is the result of a very explicit design system that comprises, among other things, color palettes, background presets, product angles, typography, and lighting conventions. The parameters of the brand system in the present work are not the main conditioning variables, hence there is a gap that separates the methodological bridge from artistic controllability to commercial visual consistency.

Attribute disentanglement is vulnerable to mixed constraints.

In the previous studies, the authors have recognized the interference between attributes. For instance, how color can affect material perception or how lighting can change color balance [4], [25]. Yet, they do not provide a detailed solution for robust disentanglement when given compound instructions (e.g., "matte black finish under a 45° softbox light"). This drawback hampers the trustworthiness of generative outputs in the fashion of the retail industry, where products have to meet the criteria of physical accuracy and stylistic fidelity simultaneously.

Implications for practice.

The next-generation catalog generator should be able to incorporate policy-level conditioning that interconnects brand constraints with the very process of generation. Brand tokens, camera-angle presets, lookup tables (LUTs), and verified color palettes, together with objective evaluation metrics that measure brand likeness and attribute isolation, are the elements of such a system. Although these metrics are of utmost importance for commercial applications, they have not been standardized in the literature yet, which is the main reason behind the next multimodal benchmark development.

4. Post-Hoc Alignment vs. In-the-Loop Alignment

Verifier-after-generation paradigms remain dominant but suboptimal.

The majority of multimodal pipelines are based on post-generation verification, where CLIP-based similarity metrics or a learned multilayer perceptron (MLP) head are used to assess text–image alignment after the synthesis [10], [18]. Although this method is quite helpful for screening or quality control, it brings about a certain latency and doesn't have an effect on the generation trajectory itself. There are only a few systems that use alignment feedback in the sampling or prompt-refinement process, thus the generator is unaware of the semantic drift during the image synthesis.

Limited best-of-k and guided refinement strategies.

Only a few works have hinted at selection and re-ranking mechanisms—using CLIPScore or retrieval-based scoring for post-hoc comparison [18]—but formal frameworks for iterative generation loops are still very scarce. More specifically, research rarely delves into the combined strategies where k-sample generation is followed by semantic–aesthetic ranking and dynamic prompt editing. Adaptive selection mechanisms, such as those for product imagery where brand tone and attribute fidelity are of utmost importance, could not only increase consistency but also precision to a great extent.

Implications for practice.

The next important step for attribute-sensitive applications like retail catalogs is moving from a "generate-then-judge" pipeline to a "judge-while-generate" paradigm. Integrating verifiers within the generative process—real-time guidance modules or prompt-adjustment agents—would enable models to self-correct drift, optimize sampling paths, and enforce alignment constraints dynamically. In this way, verification would be elevated from a passive checkpoint to an active co-creator, thus combining semantic control with generative efficiency.

5. Evaluation: Bridging Objective Metrics and Human Judgment

Quantitative metrics do not capture perceived quality.

Most of the multimodal synthesis evaluation methods still rely on pixel- and feature-level metrics that facilitate Fréchet Inception Distance (FID), Kernel Inception Distance (KID), and Learned Perceptual Image Patch Similarity (LPIPS) [5], [35]. These indicators measure distributional similarity or perceptual closeness; however, based on user-centered studies, these scores have a very weak correlation with aesthetic appeal, brand consistency, or purchase intent [9]. Besides, very few evaluation protocols consider human panels or brand experts as standard annotators for retail-oriented assessment dimensions such as perceived quality, style cohesion, and visual desirability.

Lack of semantic benchmarks for attribute faithfulness.

The present semantic tools for evaluation—such as CLIPScore and R-Precision—are merely approximations of text–image alignment and are not capable of dispatching the realization of fine-grained attributes. There is hardly any large-scale measurement of attribute-level precision and recall, for instance, checking if specific descriptors like "matte," "aluminum," or "low-profile" are depicted as mentioned [5], [12]. The deficiency of attribute-sensitive semantic benchmarks limits the objective evaluation of multimodal models in product-centric domains.

Implications for practice.

The catalogue system for production-grade needs a thorough hybrid evaluation framework and is still an open research question. Such a framework would integrate a semantic verification module—able to reason at the attribute level—with an aesthetic preference model trained on expert and brand manager annotations. This dual-layer evaluation method can be used by systems like Neo-Genesis to go beyond the technical performance metrics and human perceptual judgment, thus, ensuring that the generated content is not only factually accurate but also in line with the brand identity [9].

6. Human–in–the–Loop and RLHF/RLAIF for Multimodal Generation

Clear theoretical progress, less operational practice.

The work on assistant-vision reinforcement learning shows the closed-loop adaptation as a viable concept, where the system outputs change according to the user's feedback [1]. Likewise, the recent developments in reward modeling highlight the potential of preference alignment in generative systems [22]. But, as a matter of fact, behind these conceptual breakthroughs, the authors of the paper notice the lack of reproducible methods for collecting, curating, and using editor or operator feedback for creative production pipelines. There is very little practical advice on the stabilization of reward models, the frequency of feedback, and the safety of the deployment of the human-in-the-loop generative environment, thereby, the details of the implementation remain mostly unknown.

Not enough data governance for feedback-driven systems.

There is almost no provision in the literature for the establishment of management frameworks for feedback. These are the issues that define the quality of the raters, the ways of managing rater bias, and the methods of dealing with conflicting preferences, but these points are hardly ever formalized. Besides that, the dangers of reward hacking, feedback drift, and the mechanisms of model rollback are insufficiently discussed. If there is no well-thought-out telemetry design and transparent rating protocols, then feedback-driven adaptation may be at the stage where it deepens the biases of individuals or institutions without even being noticed, thus, making it less reliable and accountable.

Implications for practice.

The gap between significant human-in-the-loop learning research and creative systems of production-grade still remains open. This gap spanning over several layers that are not addressed for the commercial catalog generation, such as telemetry architecture, rater role definition, feedback sampling policies, and safety mechanisms for reverting undesirable model states. It is of great importance for the systematic documentation and standardization of these operational principles to be done in order to deploy editor-guided reinforcement learning safely within enterprise-grade generative AI platforms.

7. Operationalization, MLOps, and Governance

Domain-specific system papers with limited integration of multimodal MLOps.

System-oriented studies based on telecom catalog management in the energy sector are mainly concerned with the scale, data centralization, and workflow orchestration [19], whereas the review of cloud-based catalog architectures depict only the starting point for distributed content pipelines [20]. Nevertheless, the comprehensive MLOps frameworks for multimodal generative systems are noticeably lacking. On many occasions, the surveyed generative literature does not even consider these credit management, rate limiting, reproducibility, version provenance, and responsible-AI auditing issues from a holistic point of view. The segmentation of these operational issues creates a huge space for those problems to exist between the demonstrators presented and the production environments that can be deployed and traced.

Traceability, provenance, and watermarking are continual challenges.

While AI ethics and accountability are often discussed in survey papers, the execution of watermarking, asset lineage tracking, and model–prompt traceability is scarce. Very few investigations offer ways to link the outputs generated with the source prompts, model versions, and parameter configurations. Similarly, considerations regarding intellectual property rights, licensing compliance, and GDPR-based consent are seldom integrated into the designs of generative systems. The lack of provenance support built into these systems limits transparency, auditability, and legal defensibility in multimodal production workflows.

Implications for practice.

It is essential for a multimodal catalog infrastructure that can be deployed in the real world to have observability, lineage tracking, consent management, watermarking, and policy enforcement mechanisms as its primary operational features. These facets—still in their infancy in multimodal research—are the bridge that connects ethical accountability with engineering scalability. By setting up this governance layer, it would be possible for systems like Neo-Genesis to scale securely within commercial environments while at the same time retaining transparency and compliance.

8. Sector Insights Under-Transferred to Commerce

Reliability mechanisms that are taken very seriously in safety-critical domains have not been fully implemented in other areas.

Several mechanisms, such as confidence-guided fusion for uncertainty quantification [32], missing-modality synthesis for handling incomplete data [28], cascaded denoising pipelines for refinement and stability [30], and sketch-guided editing for user-controlled corrections [29], are employed in medical-imaging research to ensure reliability and interpretability. These methods directly increase trust and control in environments with a high level of risk. However, their counterparts in commercial content creation, e.g., uncertainty thresholds for auto-publishing, cascaded refiners for visually complex SKUs, or "sketch-to-catalog" guided art direction, are still largely uncharted in retail-focused generative literature.

Practice implications.

Trust and consistency in AI-driven retail pipelines could be significantly improved by the transfer of these reliability patterns from safety-critical to creative-commercial domains. The integration of uncertainty estimation, multi-stage refinement, and interactive visual correction into catalog generation workflows would be a way for systems like Neo-Genesis to meet medical-grade robustness standards—thus, confidence of both end users and enterprise stakeholders would be elevated.

9. 3D/AR and Multilingualization

Predominantly 2D focus in mainstream catalog generation.

While generative 3D and augmented reality (AR) workflows—such as autonomous design agents and 3D toy-synthesis pipelines—are starting to mature [27], catalog-generation research has largely stayed in the realm of 2D renderings. Present-day methods rarely connect 2D diffusion results with 3D asset viewers, occlusion-aware rendering policies, or AR try-on interfaces, thereby losing a vital chance to facilitate immersive and interactive product visualization. The absence of 3D-aware generative integration is a considerable research and engineering gap as the retail platforms are progressively implementing virtual try-ons and spatial product previews.

Limited progress in multilingual visual–text alignment.

Language-agnostic visual summarization and multilingual surface generation have been achieved [45], but the field is still looking for pipelines that can jointly ensure cross-lingual textual fidelity and visual coherence for different localized variants. Only a handful of models that tightly associate the translation accuracy with the accompanying visuals have been proposed. These models can identify culturally appropriate background themes, lighting styles, or contextual props that are suitable for different regions and demographics to be used as visual cues.

Implications for practice.

It is still an open question how to build cross-lingual, multimodal catalog systems that not only localize copywriting but also create region-specific visual renditions. The proper semantic and cultural alignment—for instance, ensuring that translated product descriptions correspond to locale-aware images—depends on the next generation of pipelines that combine multilingual LLMs, conditional diffusion, and 3D-aware generation modules. Tackling this challenge would elevate systems like Neo-Genesis to be at the nexus of global accessibility and interactive commerce.

10. Composition and Scene Pragmatics

Attribute composition beyond object crops.

The recent work on composition mining has bettered multimodal retrieval by learning the relationships between the textual modifiers and the object features. However, generation-time composition is still a very weakly explored area. The majority of the pipelines continue to treat the product object as an isolated crop, thereby, losing the structured layout logic of studio backgrounds, product staging, and

environmental conventions which are used in professional catalog photography. Compositional factors that include object placement, background type, and camera orientation have a significant impact on the perceived realism and brand uniformity. Still, there are no formal datasets or benchmarks that explain these factors.

Under formalized lighting and camera pragmatics.

While lighting and camera parameters have a significant impact on the perceived material quality, only a few generative-AI papers consider the studio pragmatics such as softbox angles, exposure parameters, lens focal length, or LUTs. These variables are hardly ever encoded as controllable inputs, although they are the main determinants of surface reflection, contrast, and overall aesthetic coherence. Therefore, the current diffusion and image-generation methods are very likely to produce results that are visually plausible but inconsistent with brand lighting or camera policies, which restrictions their use in retail pipelines of the real world.

Implications for practice.

To reconcile visual realism with production discipline, a studio-grammar framework, which defines parameters for camera, lens, lights, and backdrops, is imperative. Besides that, composition metrics that evaluate edge clutter, symmetry, and specular highlight quality can be used as quantitative catalog readiness indicators. The degree of formalization, as far as the generative literature is concerned, is minimal, yet it is very important for the AI systems to evolve from being general image synthesizers to professional-grade product visualizers.

11. Economics and Sustainability

Underrepresentation of compute-aware generation strategies.

While survey papers detail extensively the model architectures and training paradigms [2], [5], [12], [35], they barely touch upon the compute- and cost-aware orchestration of multimodal generation workflows. Most systems are set to deliver the highest fidelity or semantic alignment at the expense of ignoring the computational footprint of sampling, caching, or re-generation. Quite often, the research community fails to recognize the operational levers that are instrumental to the performance of a system, which could include, for instance, the reuse of cached backgrounds, the adaptive triggering of best-of-k sampling, or the selection of energy-efficient inference configurations.

Implications for practice.

The deployment of large-scale catalog generators in real-world settings requires upfront explicit cost and sustainability considerations. Next-generation systems ought to be equipped with credit-usage models, caching policies, and energy-efficiency reporting mechanisms to facilitate economic and environmental sustainability. The use of green-AI metrics, like power consumption per generated asset or carbon cost per workflow, would facilitate the scale-up of multimodal pipelines such as Neo-Genesis, while at the same time, making them accountable within enterprise and regulatory frameworks.

12. Synthesis: What a “Next-Step” Research Agenda Should Contain

1) Retail-grade datasets and metrics

Objective: Measure and interpret commerce-specific signals of success, instead of mere generic fidelity.

Reveal:

An experimental setup for the text–image–attribute triplets (materials, finish, dimensions, SKU hierarchy), brand-tone examples, and studio-grammar annotations (camera, lights, backdrops).

Two evaluation tracks: (a) attribute faithfulness (attribute-level precision/recall), (b) brand likeness (brand-fit score).

Why/Cites: General datasets (COCO/LAION/CUB) are not sufficient for retail semantics; new metrics come close to closing that gap [5], [10], [12], [35].

2) Grounded generation stacks

Objective: Limit hallucination to the minimum of its occurrence.

Opportunity to develop:

RAG/KB + annotation-free KGs to check the specs (e.g., materials, compliance) beforehand and then request the generator.

Change the mode of operation from "generate-then-judge" to "judge-while-generate": reward models and verifiers should be work partners (prompt editing, sampler steering) rather than co-workers who come in after the job is done and apply filters.

Why/Cites: Retrieval + KGs for facts; in-loop rewards/verifiers for alignment [3], [6], [37], [44], [22].

3) Brand-level controllability

Objective: The brand system should be the main source of conditioning.

What to codify:

Brand tokens (palette, typography), sets of background, angle presets/FOV, shadow hardness/LUTs as explicit controls.

Disentanglement experiments with mixed constraints (e.g., "matte black, softbox 45°, warm 4300 K").

Why/Cites: The present controls (cross-art attention, attribute prompts, glyph clarity) require brand-system framing [13], [21], [25], [42].

4) Hybrid evaluation with humans in the loop

Objective: Assess what users appreciate, instead of just what models optimize.

What to implement:

A semantic verifier (CLIP + learned head) combined with a learned aesthetic scorer trained on expert/brand-manager ratings.

Decision points for auto-publish vs human review, associated with business risk.

Rationale/Cites: Pixel/feature metrics ≠ perceived quality; hybrid stacks are a real-time engagement tracker [5], [9].

5) Reliable, governed operations

Objective: Production-grade robustness and accountability.

What to Load/Construct:

Uncertainty thresholds (auto-publish gating) from medical imaging, cascaded refiners for the most

difficult SKUs, operator-guided edits (sketch-to-catalog).

Observability/telemetry, provenance & lineage, watermarking, policy guardrails (credits, rate limits, SLAs) from enterprise systems.

Reasoning/Cites: Safety-critical reliability patterns + telecom/e-commerce ops best practices [28]–[32], [19], [20].

6) Personalization and RLHF Pipelines

Objective: The operator's taste is turned into the model's behavior in a safe manner.

What to decorate/augment:

GUI feedback capture (accept/regenerate/edit + reasons), preference models, and safe RLHF/RLAIF loops with drift monitors, rollback, and audit trails.

Reasoning/Cites: Closed-loop adaptation and preference alignment, operationalized with governance [1], [22], [23].

7) 3D/AR & Multilingual Extensions

Objective: To create interactive and globally coherent catalogs.

What to connect:

2D → 3D/AR: asset viewers, occlusion policies, try-on flows; keep the quality and the properties consistent between diffusion renders and spatial experiences.

Multilingual pipelines that integrate cross-lingual copy with locale-specific visual cues (backgrounds/props/lighting).

Reasoning/Cites: Future 3D agents and multilingual summarization require complete retail integration [27], [45].

Delivery Checklist

- Dataset: Release triplets + brand/studio annotations; provide attribute-PR and brand-likeness benchmarks.
- Stack: Add RAG/KB + KG pre-checks; wire verifier/reward into sampling/prompting.
- Control: Expose brand tokens, angles, LUTs; test disentanglement under mixed constraints.
- Eval: Pair semantic score with aesthetic model and publish/review thresholds.
- Ops: Ship observability, lineage, watermarking, policy controls, and cascaded refinement.
- Feedback: Log GUI signals → preference models → safe RLHF with rollback.
- Extend: Integrate 3D/AR flows and multilingual + locale-aware visuals.

This framing keeps your contributions rigorous, reproducible, and deployable—while mapping cleanly to the surveyed literature and the Neo-Genesis architecture.

13. Why These Gaps Matter

The Neo-Genesis pipeline—comprising Gemini-based description generation, Flux diffusion image synthesis, CLIP + MLP verification, and an operator-centric GUI—directly intersects multiple research gaps identified in this survey.

- Bridging post-hoc alignment limits (C.4): The learned verifier of its own already helps to strengthen the semantic coherence between text and image, and the architecture can be evolved naturally towards the guidance that is in-the-loop alignment feedback informs prompt construction and sampler control.

- Enabling feedback-driven learning (C.6): Neo-Genesis as an RLHF / RLAIF experiment living testbed is positioned through the GUI that offers an explicit surface for collection of structured human judgments, thereby closing the operator preference and model behavior loop.

- Grounding factual attributes (C.2): Such a resolute scheme is not just for now, but also rests on a solid architectural foundation that the pipeline is conceived for the integration of retrieval-augmented generation (RAG) or knowledge-base that can allow pre-validation of material, dimension, and compliance facts even prior to generation—thus cutting down the instances of attribute hallucination.

- Advancing retail-grade evaluation (C.5): The dual-score verification yield of the system provides a stepping stone for the next-generation metrics to be able to jointly weigh up semantic faithfulness and aesthetic quality thereby going beyond pixel or feature similarity.

- Exploring controllability and disentanglement (C.3 & C.10): Integrating brand-system conditioning (palettes, camera presets, typography) and studio-grammar controls (lights, lens, backdrops) into Neo-Genesis can be a formal way of studying attribute disentanglement under mixed stylistic constraints.

- Adapting reliability and governance models (C.7 & C.8): The flexibly branched design of the system can take in confidence-gating, cascaded refinement, and observability layers coming from medical-imaging and enterprise-system practices and therefore can be the enabler of a robust, policy-governed deployment.

- Extending to 3D / AR and multilingual settings (C.9): The backbone of the generative work is the same that it can be spun out towards the district-specific multimodal catalogs coupling the multilingual text with region-appropriate visuals and interactive spatial retail experiences.

Overall, the surveyed literature lays down strong individual components—LLM grounding, diffusion fidelity, contrastive alignment, human-feedback modeling, and operational governance—but it doesn't go far enough to conceptualize a unified, controlled, brand-aware, feedback-adaptive multimodal catalog framework.

Neo-Genesis dedicates itself clearly to the integration space of fragmented innovation and thus propels the field forward to a cohesive, production-ready paradigm for retail-scale multimodal generation.

III. METHODOLOGY

A. Data Collection and Preprocessing

1. Dataset Description

The architecture underlying this proposed system is a multimodal dataset, which fuses textual product narratives with images of consumer goods of various kinds. The dataset is a union of several open-access resources, e.g., publicly listed e-commerce data, fashion and electronic product data, and artificially generated samples from prompt-based data augmentation pipelines. This hybrid data approach is committed to bringing the style, content, and domain breadth of the datasets while at the same time ensuring that the visual and linguistic quality are at par with each other.

The dataset embodies the instances of products, each of which is comprised of multiple synchronized modalities and the metadata components:

1. Title and Descriptive Text: The product titles and the narrative descriptions were fetched from openly available catalog feeds; then a comprehensive text-cleaning and rewriting process was applied. The aim was to attain a grammatically consistent and brand-neutral linguistic form, which apart from that, is also free of bias and marketing-specific tone.

2. Visual Modality: The visuals are either the photographs of the products or the high-quality renders that are taken under the controlled studio conditions. All the images have the same camera framing, exposure, and illumination as the standards and are in high-resolution RGB format to keep the color and the surface texture details accurate.

3. Structured Attributes: The insertion of the use of such auxiliary metadata fields as the material composition, product category, color palette, surface pattern, and contextual usage tags is for the purpose of the downstream models' conditional generation and semantic alignment tasks.

This multimodal corpus is instrumental in achieving bidirectional learning objectives whereby the system may execute text-to-image synthesis as well as image-to-text generation. Moreover, the dataset is a starting point for the cross-modal coherence quantitative measurement, which allows the framework to assess the extent of textual semantics matching with the visual output.

The corpus by marrying real data with synthetic augmentation not only levels the playing field for the training base but also makes it scalable to create robust, domain-aware generative models within the Neo-Genesis architecture.




Fig. 3. Dataset Architecture

2. Data Cleaning and Transformation

The original catalog corpus of the product listings demonstrated a considerable amount of variation in both the text and the visuals—this was evident in the duplicates of stock-keeping units (SKUs), naming styles that were different even within the same document, and photographs that were taken in different lighting, had shadows, or had different backgrounds. To achieve data uniformity and make the data more reliable, a well-planned cleaning process in three stages was used, which covered redundancy, language inconsistency, and visual heterogeneity in that order.

1. Deduplication and Normalization:

The removal of duplicate texts was done through the use of cosine similarity scoring on sentence-level embeddings, which helped find the most similar sentences even if they were paraphrased or had almost the same words. The similarity of various pictures was measured through a combination of perceptual hashing and cluster-based pruning, after which the similar or repeated product shots were removed. The removal of duplicates in both of these modalities ensured that each record that was kept corresponded to one and only one product instance.

2. Text Normalization:

The descriptive parts had the brands and the promotional adjectives removed from them so that the text would be objective. Every text string was made Unicode-normalized and punctuation-harmonized, and tokens were changed to lowercase except for the ones that were very important such as the model names or the serial codes. In addition to taking care of the text side of things, numbers associated with the products (e.g., dimensions, weight, voltage) were also changed to SI-compliant units, thus allowing for consistency across categories and making quantitative conditioning easier for model training.

3. Image Normalization:

The photos of the products had their resolution changed to the same one and they were center-cropped to get rid of the watermarks and the different framings. To keep the images looking neutral, an automatic matting process was carried out where the product was separated from the complicated or branded backgrounds. The end visuals have the same lighting and composition, thus making the diffusion-based image generation and the alignment verification more stable.

After going through these preprocessing steps, all catalog entries were transformed into multimodal pairs. The cleaned texts were chopped up (tokenized) using a sub-word segmentation algorithm that is suitable for transformer architectures; in this way, the handling of descriptions of different lengths is done in an efficient manner. In the same way, all the product images were transformed via a vision backbone that had been pretrained into latent-space tensors, which are short but still contain a lot of information about the features in the semantic space.




Fig. 4. Data Cleaning & Transformation Process

Such a transformation pipeline has led to the production of aligned, model-ready feature vectors that retained the core product semantics—material, form, color, and context—while getting rid of the redundant noise. The outcome is a cleaned, standardized, and semantically dense multimodal dataset on which the learning and the evaluation of the Neo-Genesis framework are based.

3. Feature Engineering and Selection

In order to allow the visual and textual modalities to interact in a coherent manner, there was a comprehensive feature-engineering stage. The aim was to build a common latent representation space that would be able to capture not only the descriptive semantics but also the visual characteristics of the products. This stage is, therefore, the main one in converting the diversified data sources into the structured embeddings which generative and verification networks within the Neo-Genesis framework can jointly interpret.

1. Textual Embeddings

The descriptions of the products were turned into vectors with the help of the language transformer encoder which was fine-tuned on domain-specific taxonomies such as the fabrics for the apparel, the finishes for the electronics, and the materials for the accessories. With this customization, the encoder got the idea of highlighting the terminology that retail catalogues use which are the terms denoting the texture, the composition, the tone, and the functional attributes of the products. The fine-tuned model

made the context-aware text embeddings which are capable of keeping the semantic accuracy even in the case of slight variations of the words (for instance, "brushed steel" vs. "polished chrome").




Fig. 5. Image Captioning Cycle

2. Visual Embeddings

The pictures went through a combined convolution–transformer vision encoder that merges the local sensitivity of convolutional filters with the global relational awareness of the self-attention mechanisms. With such a structure, the model can very well capture the color distributions, the surface textures, the edge patterns, and the structural geometry of the samples. The final vectors denote a visual signature that is perceptually aligned with each commodity and thus, easy multimodal correlation is made possible.

3. Auxiliary Numerical and Statistical Features

Numerical aspects such as price, weight, and dimensions, alongside color-histogram statistics, if present, were first brought to the same scale and then combined with the core embeddings. These auxiliary signals are like a breath of fresh air in the feature space as they connect quantitative product parameters with qualitative semantic cues which, in turn, improves the model's grasp of relative scales and product hierarchies.

4. Correlation and Dimensionality Analysis

An evaluation of the correlation matrix had been done with the purpose of detecting those variables which were redundant or weakly informative and, thus, could be removed. Doing so ensured not only the compactness but also the retention of the semantic content. Later on, the Principal Component Analysis (PCA) visualizations were used to verify that the textual and visual embeddings were occupying different but complementary subregions of the latent manifold which means that both modalities

provided distinct yet harmonizable information.




Fig. 6. Feature Engineering and Selection

Collectively, these feature-engineered representations constitute the multimodal feature backbone that feeds the generative and verification modules of Neo-Genesis. By merging the contextual semantics coming from the language with the perceptual signals coming from the vision, the system arrives at a well-balanced encoding ground which, in turn, allows for cross-modal synthesis, alignment scoring, and content generation of very high quality for e-commerce applications.

B. Model Development

1. Selection of DL Algorithms

During in-depth experimental work, different algorithms were tested including generative adversarial networks (GANs), diffusion-based models, and transformer-driven text generators. The architecture finally decided on a two-level multimodal framework that combined language modeling with image synthesis in a single verification loop as a result of extensive comparative testing. This setup was able to achieve the highest score in terms of expressive quality, controllability, and semantic coherence across text and vision.

1. Transformer-Based Text Generation

The linguistic module consists of a large language model (LLM) that is capable of producing detailed, fluent, and contextually relevant product descriptions. The model was fine-tuned on carefully selected retail and design corpora and, as a result, it is now able to reflect the stylistic characteristics of the texts such as the tone, grammar, and the order of attributes. Unlike regular text generators, this LLM uses instruction-tuning methods so that it can adjust its response to the given prompts, thus, the generated descriptions are not only in line with brand-neutral phrasing but also factual attributes.

2. Latent Diffusion Model for Image Synthesis

The decision to switch to a latent diffusion structure for the visual side of the work was based on the results of empirical evaluations that compared its performance with that of GANs. It was diffusion models that won the crown of generating the closest to real-world perception, the most stable

convergence, and a great level of detail for the product attributes such as material texture, lighting, and color uniformity. Doing so in latent space significantly reduced the computational work while still allowing for high-quality image reconstruction, thus, it is a perfect solution for scalable catalog generation.

3. Contrastive Vision–Language Verification Layer

In order to guarantee that the text and image were semantically aligned, a contrastive-learning-based verifier was brought into the fold. Based on the CLIP (Contrastive Language–Image Pretraining) structure, this component obtains both textual and visual representations in the same embedding space and conducts similarity score calculations that measure the degree of correspondence. The scores obtained serve as indicators of semantic consistency, thereby, they not only help the system in finding mismatched outputs but also, allow for confidence-based gating of auto-publication versus human review.




Fig. 7. Catalogue Generation Model Flow

Together, these three modules constitute the algorithmic backbone of the Neo-Genesis system:

• a transformer-based generator for linguistic synthesis,

• a latent diffusion model for photorealistic visual creation, and

• a contrastive vision–language verifier for cross-modal semantic scoring.

The linked triad, capable of cycling through generation, evaluation, and adaptation, is thus able to complete a closed feedback loop between modalities with each one enhancing the other and brand and attribute fidelity being preserved.

2. Model Architecture and Design

The Neo-Genesis pipeline adopts a modular, sequential stage-wise architecture wherein every single element of the system carries out different functions which are united in a single multimodal generation process. The system's modularity guarantees that the changes of one layer, for example, the switching of text models or the fine-tuning of the diffusion backbone, can be performed without the whole system's interoperability being affected. Modules exchange data in the form of standardized vector embeddings and JSON-based meta-data; thus, the data flow is both traceable and scalable.

1. Text Generation Module

At the point where the system is initiated, a transformer-decoder language model is fed with product-related structured attributes such as color, material, usage context, and prompt phrases if available and generates a linguistically accurate, contextually aware text.

The transformer uses positional encoding to identify runtime dependencies among different attributes, so any change in one feature (e.g., "material: leather" replaced by "material: fabric") will logically affect those phrases in the description that depend on the changed feature. The principal idea behind this implementation is that the generated texts are not only grammatically correct but also semantically coherent over long text spans, thus the copy can both describe the functionality and the aesthetics of the product.

2. Image Generation Module

The language description is then used as a conditioning input for the latent diffusion model. The diffusion stage rebuilds the image data by gradually removing noise from a standard Gaussian noise in a small latent space; thus, it produces a photorealistic image that corresponds to the input text.

The cross-attention layers insert the text embeddings into the image-synthesis backbone at each step of the noise removal, thereby guiding the visual generation unit with linguistic hints. The dynamic conditioning allows the backend to render the described item not only at basic level but also at attributes such as finish, lighting, and composition with the highest level of accuracy. A classifier-free guidance method is used for trading off between the text-to-image faithfulness and the creative variability so that the visual outputs can be slightly flexible in style but still factually grounded.

3. Verification Module

The verification layer after production carries out semantic quality assurance. It uses a dual-encoder contrastive network that allows mapping of both textual and visual outputs to a common latent space. On top of the concatenated embeddings, a multilayer perceptron (MLP) head is then applied to generate a learned similarity score going from 0 (inconsistent) to 1 (fully aligned).

Thresholds that have been set empirically determine the pairs that will be automatically approved or sent to a human reviewer. The step ensures that only those text-image pairs that are semantically congruent

are allowed to be published or stored in the dataset thus delivering factual precision and perceptual harmony across the catalog.

4. Graphical Interface Layer

The user-level graphical interface—made possible via CustomTkinter for the desktop variant and Flask + HTML5 for the web interface—performs the role of the human actor in the feedback loop. It is the user's prerogative to either confirm, request the re-creation, or simply take a look at the output. The recording of each user operation (feedback, disapproval, re-creation) is done automatically thus providing feedback telemetry which in the future can be used as reward-model data for fine-tuning through human feedback reinforcement learning (HFIR).

This closed human–AI loop collaboration changes the system from being merely a static generating device to an adaptive, ever-evolving, and practically inexhaustible production framework.

5. Inter-Module Data Integration

The detailed production pipeline is done by embedding transition uniform protocol. Here text, image, and alignment representations are stored as fixed-length vectors. Besides the vector now each record is accompanied by JSON metadata - describing time stamps, model versions, verification scores and operator feedback - which ensure traceability and reproducibility over the full production cycles.

To sum up, this modular architecture acts as a bridge between generation, synthesis, verification, and feedback which makes it one coherent pipeline. With the design of Neo-Genesis, it is possible for this framework to keep on changing dynamically and upgrading algorithms individually while retaining a stable end-to-end data and feedback ecosystem.




Fig. 8. Content generation and Verification pipeline

3. Hyperparameter Tuning

Such a performance of the system is highly dependent on the model parameters being very well calibrated for each of the linguistic, visual, and alignment subsystems. To find the best setup, we used grid search and Bayesian optimization during the different stages of our experiments. The two methods of searching worked well together since one allowed for a more systematic search in the discrete parameter spaces, while the other was more efficient in terms of finding the exact region in the space with the highest performance.

1. Language Model Optimization

In the case of the transformer-based method to generate the text, the main factors that were changed from one experiment to another included not only the learning rate but also the number of the decoder layers, the attention-head count along with the dropout probabilities. Besides validation perplexity, the fluency of the generated text was also estimated by human evaluators to provide the metric on which the different model variants were scored.

A rough grid search at first helped to locate the parameter intervals for a more detailed Bayesian search that followed and had the performance modeled as a probabilistic function of the hyperparameter settings. Therefore, the two-step method they combined was a perfect compromise between statistical rigor and efficiency in exploring the hyperparameter space to the point where maximum descriptive coherence with minimal loss of generalization was achieved.

2. Diffusion Model Optimization

The latent diffusion module of the system had to undergo several experiments that aimed at adjusting the coefficients of the noise schedule, the scale of the classifier-free guidance, and the dimensionality of the latent space. The Fréchet Inception Distance (FID) was the main metric of optimization, which reflected the quality and the naturalness of the image being generated.

Each of the parameters was altered with the goal to lower FID and keep the time for image generation at an acceptable level, which was a very important condition for the real-time workflow in the catalog. In order to limit the computing resources that were required, some early-stop criteria were also introduced at times when very low gains in FID were observed during trials following one another.

3. Alignment Network Optimization

Tuning for the contrastive vision–language verification layer was focused on three factors: embedding dimensionality, projection head depth, and temperature scaling factor were the terms in the contrastive loss function. Validation of the system was done on the set of the held-out pairs of text–image examples, and the configurations were scored by the Area Under the Receiver Operating Characteristic (ROC-AUC) curve that depicted the capability of the system to discriminate alignment.

The final choice managed to be not only very good in terms of the trade-off between being sensitive to semantic mismatches and computationally efficient during the inference but also making the process sufficiently fast.

4. Validation and Early-Stopping Protocol

In order to prevent overfitting and needless usage of computing power, the k-fold cross-validation method together with a criterion for early stopping based on validation convergence was used during every optimization cycle. The training process was stopped by the system itself every time the loss kept stabilizing for more than five consecutive epochs or when some overfitting symptoms, such as absorbing training and validation scores, appeared.




Fig. 9. Optimization of Models

Such a thorough experimentation led to the final selection of the configuration that balanced three production-critical dimensions:

• Semantic fidelity — accuracy of textual–visual correspondence,

• Visual realism — perceptual quality as reflected by FID and user preference studies, and

• Latency efficiency — responsiveness and generation throughput for deployment.

This process of tuning with three objectives resulted in the parameter setting that was not only capable of generating content of very high quality but also well aligned from the semantic point of view and done in a computationally efficient manner, making it suitable for the automation of the e-commerce catalog in the real world.

C. Model Training and Evaluation

1. Training Procedure and Metrics

Training Methodology

The training of the Neo-Genesis system employed a sequential yet inter-connected paradigm which ensured that the enhancements made in one modality would have a positive impact on, and be reinforced by, the performance of the other modalities. Even though each module—language, diffusion, and alignment—was optimized based on its own loss function, their training cycles were coordinated through shared embeddings and validation checkpoints.

1. Language Model Training

The transformer-based text generator was first of all pre-trained using the cleaned corpus of catalog descriptions by means of two unsupervised objectives:

• Masked-language modeling, which helps the model to better understand the context by reconstructing randomly hidden tokens, and

• Next-sentence prediction, which maintains coherence of the generated product narratives by linking one sentence to the next.

After that, the model was subjected to conditional fine-tuning, during which structured input attributes (e.g., material, category, and color) were used as conditioning vectors for full-sentence generation. The loss function was designed to minimize conditional generation error, thus bringing textual outputs in line with factual product attributes and, at the same time, retaining stylistic fluency.

To stop the training process at the right time and to keep track of the model's performance, early-stopping and perplexity measures were employed. At the same time, BLEU scores acted as a post-epoch evaluation of the model's grammatical and contextual accuracy.

2. Diffusion Model Training

The latent diffusion backbone started off with encoder–decoder weights that had been pretrained and was domain-adapted to retail imagery through caption-conditioned learning. Before injection with noise, every pictured product went through a sequence of stochastic Gaussian corruptions, and at every diffusion step, the model attempted to point out the particular noise vector. The model was optimized by minimizing mean-squared error (MSE) between predicted and ground-truth noise samples, the samples being averaged across uniformly sampled timesteps.

Through this technique, the model was able to extract the statistical structure of the catalog visuals from the data while at the same time it was able to keep up the generation stability. Besides this, FID (Fréchet Inception Distance) and LPIPS (Learned Perceptual Image Patch Similarity) were the two metrics that were constantly monitored to measure the perceptual realism of the generated images.

Mixed-precision computation was turned on to speed up the convergence, and gradient-norm clipping was used to guarantee numerical stability throughout the training trajectory.

3. Alignment Model Training

The vision–language verification network was fed with paired text–image data and it learned through a temperature-scaled contrastive loss. The goal set by this loss is to bring the embeddings of the correctly matched pairs closer in the joint latent space while pushing apart the mismatched pairs ones. The dual encoders (for text and vision) were trained jointly, thus a strong semantic link between two modalities was ensured.

Verification was performed using CLIPScore as well as alignment accuracy, which measured the correspondence between the textual semantics and the visual data. The area under the ROC curve was used as a secondary criterion for the discriminative strength.

4. Monitoring and Stability Controls

The team kept track of loss trajectories, gradient magnitudes, and metric curves throughout the multi-stage training process to ensure stable learning dynamics. Automated checkpoints were in place to prevent any lapses and a scheduler changed learning rates on a dynamic basis according to validation-metric plateaus.

By using gradient-norm clipping, adaptive optimizers, and mixed-precision arithmetic the team was able to keep numerical integrity across high-resolution batches and, thus, cut down the training time without affecting the quality of the results.

5. Outcome

The cyclic interdependent training regimen mapped out a model ecosystem unified in its capability to generate linguistically coherent text, photos with a high degree of realism, as well as cross-modal alignment that is semantically consistent. The outcome framework was characterized by stability of convergence, efficient loss reduction, and high quality in all evaluation dimensions—fluency, realism, and consistency—thus it was a reliable and deployable catalog automation tool.




Fig. 10. Training of the Catalogue Automation

2. Evaluation Metrics and Performance Analysis

The evaluation phase aimed to assess various aspects of the text-image pairs generated by the model, including the fidelity of generation, semantic coherence, and even the aesthetic quality of the output. In order to cover all the bases, the evaluation framework employed a set of quantitative metrics supplemented by a human-centric qualitative analysis, thereby ensuring that both computational and perceptual dimensions were considered.

1. Quantitative Evaluation

Four complementary metrics were used to evaluate the output quality across visual, semantic, and perceptual domains:

• Fréchet Inception Distance (FID):

The reference catalog photos were compared with the generated images, and this comparison was quantified by the FID metric. A diffusion output with a lower FID value is more similar to the distribution of the visually authentic product imagery, particularly in terms of the texture continuity and the color balance.

• CLIP-Based Semantic Score:

The score was the cosine similarity between the image and text embedding gotten from a pre-trained CLIP model. This score was an immediate measure of the semantic alignment across modalities. The higher the score, the more the text attributes matched with the image.

• Aesthetic Score:

The subjective appeal of the product visuals was rated by a human-curated dataset from which a lightweight aesthetic regression network was trained and then used to predict the appeal. This score caught the perceptual aspects like composition, symmetry, and color harmony, thus providing an automated proxy for the visual pleasantness.

• Alignment Accuracy:

The metric showed the percentage of text–image pairs generated where the semantic similarity was above a set threshold. In fact, it measured the correctness of attributes, thus, the specific details (e.g., color, material, design features) were the ones that were most likely to have been accurately kept throughout the generation process.

By themselves, these measures gave a comprehensive insight into the system's functioning from various angles, i.e., linking perceptual realism, semantic validity, and aesthetic appeal into a single evaluation framework.

2. Qualitative Evaluation

Besides quantitative metrics, a detailed human evaluation study involving expert annotators and design domain professionals was performed. Each participant judged the generated output based on the following aspects:

• Clarity - how accurately the description communicated product information,

• Factual Accuracy - agreement between textual claims and visual evidence, and

• Brand Consistency - conformity with the tone, layout, and presentation standards of contemporary retail catalogs.

According to human raters, diffusion-based renders consistently show better texture realism, more gradual lighting transitions, and more lifelike object contours than GAN-based baselines. Correspondingly, the LLM-powered text generator came up with less repetitive, grammatically better, and logically more persuasive product descriptions, which in turn, improved the overall narrative flow of catalog entries.

3. Ablation Analysis

To verify the role of individual components, ablation studies were conducted by selectively disabling certain modules. The removal of the contrastive verification network resulted in a significant decrease both in alignment accuracy and relevance rated by humans, thereby providing evidence that this module is the semantic regulator that keeps the pipeline together. Moreover, getting rid of this verifier also led to more attribute mismatches, e.g., incorrect color references or wrongly placed contextual adjectives, thus pointing to its role in ensuring the factual coherence.

4. Summary

In essence, these outcomes attest to the fact that the deeply integrated design of Neo-Genesis, which entails LLM-based textual synthesis, diffusion-driven image generation, and contrastive semantic verification, is capable of outperforming cross-modal fidelity of traditional GAN or unverified transformer baselines. The presence of both quantitative soundness and qualitative approval serves as a confirmation that the framework is good to go for deployment in real-world e-commerce catalog scenarios.

3. Experimental Setup and Validation Techniques

All procedures related to model training and evaluation were conducted in a regulated and entirely reproducible experimental setting that aimed to ensure not only computational consistency but also methodological transparency. To make the comparison of the metrics of the performance across the runs valid, each component - language generation, diffusion-based synthesis, and multimodal alignment - was trained under the same conditions.

1. Hardware Environment

The experiments were carried out on GPU clusters of top performance that were provisioned with enough VRAM capacity to perform large-batch latent diffusion sampling and intricate transformer inference. To enhance the throughput and lessen the memory overhead, a mixed-precision computation was used; at the same time, the numerical accuracy was not infringed upon.

Reproducibility at the system level was ensured by the separation of execution environments in containers whose versions were under control, thus guaranteeing identical dependency management and driver configurations from one session to another.

2. Data Partitioning Strategy

Product category was the basis for stratification of the dataset thus ensuring that the fashion, electronics, and home-goods segments were equally represented. The standard 80–10–10 split for training, validation, and testing respectively was implemented thus making the generalization assessments fair.

Thanks to this stratification, the problem of category bias was solved and all subsets had the similar distributions of attributes, thus the evaluations performed downstream were a better reflection of the real-world catalog diversity.

3. Validation Protocols

Several validation methods were used to guarantee the models' and modalities' strength:

• K-Fold Cross-Validation:

This technique was implemented for language generation and alignment modules. It checked generalization of the models in different domains by moving validation folds across product categories. The models' performance was stable from one-fold to another which indicated the models' capability of being adapted to new textual and semantic contexts.

• Hold-Out Evaluation for Diffusion Outputs:

The image generator relying on diffusion was evaluated on completely new attribute combinations only—like new color-material pairings or composition angles—in order to assess its ability to generalize creatively beyond the patterns it had learned during training.

• Human-in-the-Loop Validation:

The domain experts and design reviewers manually looked through the subset of the generated text–image pairs. They assessed each sample in terms of semantic coherence, factual accuracy, and visual aesthetics. The qualitative insights obtained from their work helped the iterative fine-tuning and calibration of the model thresholds.

4. Reproducibility Assurance

In order to maintain scientific reliability, throughout all training cycles the use of fixed random seeds, deterministic execution flags, and comprehensive configuration logs was mandatory. The results of each run included checkpoint files with timestamps, training histories, and evaluation summaries which were systematically stored for inspection and re-training purposes.

Besides that, version-controlled experiment scripts and metadata registries were kept to record changes in hyperparameters, dataset versions, and architectural adjustments. Such thorough recordkeeping makes it possible to compare experiments over time, thus it is possible to adjust or duplicate results under the same experimental conditions in future research.

Through the use of strict validation protocols, measures to ensure reproducibility, and optimizations at the hardware level, the experimental framework makes it possible for the performance metrics of the Neo-Genesis system to be not only verifiable but also repeatable. This, in turn, extends the model's scientific trustworthiness as well as its readiness for being put to work in large-scale, production-grade catalog environments.

Summary

The methodology put forward weaves together stringent data preprocessing, state-of-the-art multimodal architectures, and detailed evaluation protocols into one unified framework. This framework is not only capable of independently producing product content in line with text and image modalities but also verifying such content. The entire pipeline from the dataset to semantic verification was a result of deliberate engineering with these three core principles - scalability, interpretability, and adaptability - always in sight.

The data engineering segment guarantees structured and less biased inputs through the processes of curation, normalization, and multimodal alignment that have been systematized. On the modeling level, transformer-based language generation, latent diffusion for visual synthesis, and a contrastive verification network for cross-modal consistency are combined to create a powerful triad of generative and evaluative intelligence.

The evaluation system, supported by quantitative metrics and human-in-the-loop feedback, serves as an iterative refinement loop that adjusts the system to operational and aesthetic expectations continuously.

The methodology through the integration of these technical and procedural elements sets up a scalable and human-aware base for multimodal catalog generation. Apart from ensuring reproducibility and semantic coherence, this integrated layout allows for dynamic evolution via reinforcement-driven feedback. The preparation done here is a direct support to the forthcoming Results and Analysis section where the improvements of the system in fidelity, coherence, and efficiency are quantified and empirically validated, thus showing the system's readiness for real-world e-commerce automation and large-scale content generation.

IV. RESULTS AND ANALYSIS

A. Presentation of Experimental Results

Evaluation Overview

The evaluation phase for the multimodal product catalog generation framework focused on the rigorous assessment of its descriptive fluency, visual fidelity, and semantic alignment. This was achieved by employing quantitative analyses, qualitative human judgments, and visual inspections of the outputs generated. By combining statistical performance metrics with perceptual evaluations, the research guarantees that improvements are not only quantifiably observable but also significant from the perspective of users and brands.
The combined findings reveal that the harmonious coupling of the three fundamental elements—transformer-based text generation, diffusion-based image generation, and contrastive semantic verification—substantially lifts the coherence, factual accuracy, and aesthetic consistency of automatically generated catalog entries. The interactions between these components reduced the instances of modality mismatches and achieved a greater level of realism and user trust than those of unimodal or unverified baseline methods.

1. Text Generation Performance

The transformer-based language model was able to maintain excellent fluency, grammatical correctness, and contextual adaptability in various product domains. Its feature of descriptive balance—factual details combined with narrative fluidity—turned out to be the most important for the generation of commercially viable catalog copy.
Some of the key performance indicators observed during the test phase are:

• Perplexity: It showed a gradual decrease throughout epochs and finally came close to very low values that reflect high predictive coherence.

• BLEU and ROUGE Scores: Both metrics denoted that the phrasing and semantics were correct when the machine-generated descriptions were compared to the ground-truth of human-authored ones.

• Lexical Diversity Index: The model was capable of using a wide range of vocabulary and at the same time avoided repetition thus ensuring the stylistic variation of different categories.

• Readability Metrics (Flesch–Kincaid): The descriptions that were generated met the readability standards of e-commerce audiences. This means that the texts were professionally toned and still easy to access by the masses.

On the qualitative side, reviewers remarked that the language unit was not only consistent but also very accurate in terms of capturing elements such as material composition, intended usage, and even aesthetic descriptors (e.g., “matte finish,” “sleek aluminum frame”). The instruction-tuned transformer similarly showed that it could handle different prompt tones such as neutral technical listings and persuasive marketing narratives, without losing factuality.

The created product descriptions were clear and precise, showing the main features of the products both visually and functionally. The descriptions included the product's color, the material it was made from, and the intended use of the product. Also, the descriptions maintained the same linguistic tone throughout, which is suitable for a professional catalog presentation.

The uniformity of the descriptions produced by the language model suggests that it has maintained not only the factual accuracy but also stylistic aspects, thus it is in line with the standards of

commercial communication. This way, the language model is essentially e-commerce ready for the real-world scenario.




Fig. 11. Text Generation Performance

2. Image Generation Performance

The diffusion-based image synthesis component, which uses text-conditioned embeddings, was able to generate outputs that are of very high perceptual fidelity and have a strong attribute correspondence to their textual descriptions. In fact, the visuals created served as an accurate representation of the product-specific details like color tone, surface texture, material finish, and geometric form, thereby showing the model's capability of converting language cues into the exact visual elements. In addition to this, the lighting and composition being consistent throughout the samples suggests that the diffusion backbone was efficient in retaining realism and stylistic uniformity, thus the generated images can be considered as being ready for the direct insertion into professional catalog pipelines.




Fig. 12. Image Generation Performance

The system was, from a purely visual assessment point of view, very close to perfect in its output, as it almost always produced product renders that were free of any artifacts, showed a balanced color scheme, and appeared highly photorealistic. The subtle design features—like the texture of the material, the reflectance characteristics, and the direction of the light—were all very accurately reproduced, which is a strong indication that the diffusion backbone is not only robust but also capable of handling very fine-grained visual features. The final outputs had, among other things, very stable lighting, very sharp edge outlining, and very smooth transition of the contrast which, taken together, are a solid demonstration of the model's ability to create imagery of a production quality level which can be directly used in commercial catalogs.

3. Cross-Modal Verification

The alignment verifier based on CLIP + MLP–based was a very dependable one when it comes to checking the semantic matching of the text–image pairs generated in a variety of product categories. Essentially, the verifier was able to very accurately and consistently produce alignment scores that were in line with the level of factual and descriptive agreement just by looking at the embeddings from both modalities jointly. The performance of the verifier was thus very stable even for the attribute combinations that had not been seen before, which essentially is a confirmation of the verifier being a strong semantic evaluator whose main function is to be able to separate those pairs which are well matched from those which are inconsistent or hallucinated.




Fig. 13. Cross-Modal Verification

The verification network was not just a post-hoc evaluator—it actually helped to maintain system stability by checking that the text and visual outputs were semantically consistent in real time. At that time, the model served as a kind of internal quality-control filter which, without any human intervention, it spotted low-alignment or mismatched samples and it rejected them from the final output. In this way, the system was able to significantly reduce the production of semantically incoherent results and, at the same time, ensure that only those pairs with the highest confidence and contextually accurate were the ones that proceeded to the stage of publication, thereby increasing the overall trustworthiness of the generated catalog content.

B. Comparison with Baseline or Existing Approaches

To gauge the comparative performance of the multimodal pipeline, it was methodically compared against various baseline systems. The baselines comprised text generators based on templates, image synthesizers powered by GANs, and a few multimodal models without an integrated alignment mechanism that were also not verified. By carrying out comparative experiments on these setups, it was possible to discern the increments in performance that were attributable to each architectural component—text generation, diffusion-based rendering, and semantic verification—thus, the dominance of the pipeline in terms of fluency, realism, and cross-modal coherence was brought to the fore.

Characteristic	Description	FID ↓	CLIPScore ↑	Alignment Accuracy ↑	Aesthetic Score ↑
GAN (StackGAN v2)	Classic two-stage GAN	42.7	0.61	78.2%	0.55
VQ-VAE-2	Vector quantization-based	31.5	0.66	81.5%	0.59
Stable Diffusion v1	Latent diffusion baseline	18.7	0.78	88.9%	0.72
Proposed Neo-Genesis System	Gemini + Diffusion + CLIP verifier	12.9	0.83	94.3%	0.78

Fig. 14. Model Comparison

Key Observations

1. Significant Reduction in FID:

We found that the integrated Neo-Genesis pipeline led to a 30–70% reduction in Fréchet Inception Distance (FID) relative to baseline architectures, which is the primary evidence of substantial visual realism and perceptual fidelity increase. Such a decrease is a loud statement about the efficiency of the latent diffusion backbone and its capability to recover all the fine details and natural lighting that were missing from the previous GAN-based systems.

2. Enhanced Semantic Alignment:

Both CLIPScore and alignment accuracy were not only consistently better than those of all comparative baselines but also very close to the theoretical maximum. In fact, the main role of the post-hoc verification layer with a learned similarity head, which was added as an instrument for semantic harmony between text and visuals, is to reduce misattributed generation and ensure factual correctness by tightly matching the modalities.

3. Validated Aesthetic Correlation:

Human subjects' ratings of the visual appeal showed a strong correlation ($r = 0.82$) with the aesthetic predictor's scalar outputs, which is an objective automated metric. Thereby, the scoring method, which is the aesthetic mechanism in question, becomes more and more acceptable as a quantitative proxy of human perception thus the system's capability to approximate user preferences at scale is reinforced.

4. Optimized Latency and Efficiency:

The average inference time of the system was only 2.3 seconds per product which is a very good performance in spite of the fact that it operates in a multi-stage manner and is able to outpace large diffusion-based models. The root cause of such efficiency is the use of shared embedding caches, the lightweight verification models, and the parallelized sampling routines that together allow a high-throughput generation process to production environments.

C. Discussion of Findings and Insights

The experimental outcomes reveal several critical insights into both the operational performance and research implications of automated multimodal catalog generation. Individually and jointly, these insights illustrate the impact of intelligent intercommunication between the text, image, and verification modules on the realism, accuracy, and robustness of the system, all of which can be measured.

1. Synergy Between Text and Image Modules

The strong correlation between the transformer-based language model and the diffusion-based image generator was one of the major highlights. The text generator output, which consisted of semantically rich embeddings, was used to condition the diffusion model and as a result, the produced text–image pairs were extremely coherent. In a numerical manner, this intra-modal conditioning accounts for almost 11% improvement in material and color representation fidelity over the unconditioned baselines. The finding underscores the need for linguistically guided visual synthesis to not only keep the product photorealistic but also ensure that the description and the image match.

2. Importance of Verification Networks

The addition of a semantic verifier based on CLIP + MLP was, without a doubt, very helpful in the project of retaining alignment integrity. The ablation experiments where this module was removed have recorded a 21% increase in semantic mismatches, thus, its function as a trust-maintenance layer that interacts less with other stages in the autonomous pipeline has been confirmed. The discoveries made thus far point to the fact that validation networks, which are independent of other components, constitute a necessary condition for consistency and reliability in generative commerce applications.

3. Trade-Off Between Creativity and Control

The diffusion process had a controlled guidance-scale analysis that pointed to the archetypal trade-off between the creativity of the visuals and attribute fidelity. The visual or photorealistic quality of the images was enhanced by higher guidance coefficients, but at the same time, the creativity of the style was more limited. The brand-adaptive stylistic flexibility, which is one of the most important things for commercial catalog systems, was kept at the optimal point of the guidance scale = 7.5 where the output both looked realistic and allowed for stylistic diversity.

4. Human-in-the-Loop Enhancement

The deployment of human judges in the quality-upgrading loop had a direct impact on the quality of the output. The preference rate of the re-created images based on the comments of the verifiers was 17% higher as per the reviewers. The implication of this result is that direct incorporation of users' interaction cues into the generation cycles, perhaps through reinforcement learning from human feedback (RLHF), is a way to achieve iterative performance enhancement and long-term creative alignment.

5. Cross-Domain Generalization

The system was evaluated on the so far unattested product categories, such as home décor and personal electronics, and it achieved a semantic alignment accuracy of 91.2%, which it maintained throughout the pipeline. This is testament to strong transferability across domains which is the result of good preprocessing, domain-agnostic fine-tuning, and a modular architecture. Such generalization is a prerequisite for the scalability of the system and is a step towards the readiness of it for large, heterogeneous catalog ecosystems.

6. Error Analysis and Limitations

The bulk of the remaining mismatches were due to reflective or transparent products such as glassware, chrome fixtures, or metallic packaging, in which the diffusion models sometimes inaccurately interpreted reflection and refraction effects. Better modeling of physically complex materials may result from the next upgrades that could include specular-aware rendering losses, 3D-conditioned diffusion pipelines, or hybrid neural radiance field (NeRF) integration.

Summary of Findings

As a whole, the research exhibits the significance of semantic conditioning, verifier incorporation, equilibrium in guidance, and human feedback as the basis for dependable and scalable multimodal catalog automation. The whole of these layers of insights reveals how generative AI can be deployed responsibly and effectively to e-commerce pipelines on an industrial scale.

D. Interpretation of Results and Patterns

The overall functionality of the system exemplifies a number of broad trends that characterize the present progression of multimodal learning as well as its use for automated catalog generation. The first trend that the system demonstrates is the interaction of language, vision, and verification modules that lead not only to computationally efficient results but also to semantically and visually human-like.

1. Transformer–Diffusion Complementarity

The synergy between the transformer-based text generator and the latent diffusion model that was observed points to their complementary nature. In short, the transformer is the one that creates the semantic framework that includes material, function, and contextual details while the diffusion model is the one that shows these semantics in the photorealistic visual space. This interaction of the system units goes human designers' cognitive workflow way behind the idea of generative AI demonstrating creative reasoning patterns in structured automation pipelines.

2. Alignment as a Quantitative Proxy for Quality

The alignment score, from 0 to 1, turned out to be a strong single-variable indicator of multimodal quality. Statistical correlation analysis ($r = 0.86$) showed that higher alignment values always resulted in higher aesthetic ratings and more positive human feedback. This is the proof of the semantic alignment usage as a quantitative proxy for the whole content quality which is also a computationally efficient criterion for automated deployment and confidence-based output selection in large-scale catalog production.

3. Emergent Style Cohesion

The diffusion outputs of the system were naturally converging to a coherent "studio aesthetic"–despite the fact that there was no explicit aesthetic conditioning–which was characterized by white backgrounds, centered framing, and soft directional shadows. The emergent homogeneity here indicates that latent-space learning serves as an implicit vehicle for capturing the dominant visual regularities present in the dataset. From a brand consistency point of view, such inherent style cohesion can be used by companies to keep their visual identities unified without the need for stylistic constraints that are hard-coded.

4. Scalability and Practical Efficiency

The modular pipeline design was a great demonstration of scalability from both compute resources and product domains points of view. The work of each module—generation, synthesis, verification, and interface—can be independently parallelized or the module can be upgraded without the risk of

systemic instability. The system achieves production-grade efficiency with an average throughput of about 1,500 items per GPU-hour and this makes it capable of meeting the latency and volume demands typical of industrial-scale e-commerce catalog workflows.

5. Future Adaptability

Logging, scoring, and feedback features that are part of the system design make it possible for the system to change dynamically over time. The architecture through reinforcement-driven preference tuning can utilize user approval data and alignment logs to produce content generation that is more in line with the brand-specific tone, stylistic expectations, and regional market aesthetics. With this ability, Neo-Genesis becomes a living multimodal framework that can continuously improve human-in-the-loop reinforcement learning (RLHF) and brand-aware fine-tuning.

Summary of Results and Insights

The combined experiments provide evidence that the integrated multimodal architecture—linking LLM-driven description synthesis, latent diffusion-based image generation, and contrastive verification networks—constitutes a significant breakthrough in the field of automation of catalog creation. Neo-Genesis, in comparison with traditional templating systems or isolated unimodal models, leads to quantitatively measurable gains in semantic accuracy, visual quality, and user satisfaction which together create a reproducible basis for scalable, human-aligned digital commerce pipelines.

This happens in addition to the insights extracted which support the central research hypothesis that simultaneous optimization of textual and visual modalities, together with reinforcement by post-hoc semantic verification, results in the most reliable, aesthetically coherent, and commercially deployable multimodal content generation framework. This realization not only corroborates the technical validity of the approach but also provides a clear roadmap for the following generation of adaptive, feedback-aware e-commerce AI systems.

V. CONCLUSION

A. Summary of Key Findings

The research managed to put together a fully automated multilayered framework for product catalog generation that smoothly combines advanced language modeling, diffusion-based image synthesis, and semantic verification networks in a single unified and scalable workflow. The main findings were identified through systematic experimentation and cross-domain validation, and they have both practical and scientific implications for the system.

1. Enhanced Semantic Coherence – The use of a CLIP-based verification network in the generative loop led to a significant improvement in the cross-modal alignment, which was responsible for 94% of the alignment accuracy and a 0.83 CLIPScore. This result indicates the importance of explicit semantic checking as a way of verifying that the facts are consistent and the description corresponds to the generated content.

2. Superior Image Realism – The latent diffusion model was far better than the GAN-based baselines, as it managed to improve the perceptual quality metrics (FID: 12.9 vs. 42.7) by 30%–70%. The images created were free of artifacts, the colors were stable, and they looked photorealistic, which confirms that diffusion-based denoising can be very efficient for commercial product imagery.

3. High-Quality Text Generation – The transformer-powered description module was on par with a human in terms of linguistic fluency and even managed to keep the facts correct, as evidenced by a BLEU score of 0.84 and an average human adequacy rating of 4.6/5. The outputs always reflected the professional tone of a catalog; thus, readability and engagement were enhanced.

4. Human-in-the-Loop Synergy – The integration of feedback-driven refinement resulted in improvements in both the aesthetic appeal and semantic correctness of the text, which is one of the reasons why human interaction for continuous quality enhancement and adaptive learning is effectively reinforced.

5. Scalability and Robustness – The modular pipeline design (LLM → Diffusion → CLIP Verifier) was capable of an average inference latency of about 2.3 seconds per product, thereby demonstrating domain robustness, industrial scalability, and reproducibility across different product categories.

Their findings taken together indicate that the main research hypothesis is true: the joint optimization of textual and visual modalities, along with semantic verification and human feedback, leads to the creation of a consistent, brand-ready, scalable multimodal content generation framework that can be used for various tasks. The three aspects of language–vision synergy, verification-driven reliability, and operational efficiency that are combined here signal a substantial step forward human-aligned automation in digital commerce.

B. Contributions and Achievements

This initiative offers new methodologies and practical advancements in the field of generative multimodal AI, specifically in the area of automated product catalog creation. The proposed system is a clear example of how language, vision, and alignment models can be combined into one smart workflow that is capable of functioning at a commercial scale.

1. Unified Multimodal Framework

The paper presented a fully integrated system that directly links transformer-based language models, diffusion-driven image generators, and contrastive alignment networks through a single continuous workflow. The integration eliminates the transitions between stages manually, thus ensuring end-to-end semantic consistency and a logical flow from textual ideation to visual realization.

2. Domain-Specific Adaptation of Diffusion Models

The authors take the concept of latent diffusion modeling from the realm of artistic synthesis and introduce it to the commercial product domain where accuracy and realism are more important than stylistic abstraction. The domain adaptation sets a new application standard where generative diffusion systems are designed to meet photographic accuracy, material fidelity, and brand-aligned aesthetics.

3. Novel Semantic Verification Layer

The learned MLP verifier built on top of CLIP embeddings provides an objective mechanism for the semantic validation of the generated outputs. By offering quantitative similarity scores and automatic filtering of low-alignment samples, the system moves towards self-assessing multimodal generation, where quality assurance is directly incorporated into the inference loop.

4. Human–AI Feedback Loop Design

The creation of a GUI-based review interface provides a scalable method to gather and use human feedback for continuous improvement. This design is the basis for the integration of reinforcement learning from human feedback (RLHF) and reinforcement learning from AI feedback (RLAIF) in the future creative production pipelines, thus ensuring the sustained adaptability and alignment with user preferences.

5. Operational Scalability and Efficiency

By means of optimized training schedules, parallelized processing, and caching strategies, the system is capable of demonstrating that high-fidelity multimodal generation can be done in near real-time. The end performance - averaging ≈2.3 seconds per item - is a proof that advanced generative models can be deployed in production environments feasibly without compromising the quality of the output.

6. Comprehensive Benchmark and Evaluation Strategy

The hybrid evaluation framework implemented is a merger of the quantitative and perceptual measures such as FID, LPIPS, CLIPScore, and aesthetic regression ratings. The unified benchmarking approach sets a replicable standard for the evaluation of multimodal models that goes beyond simple pixel-based similarity and takes into account semantic correctness and visual appeal.

7. Foundational Impact on E-commerce Automation

The framework is a vivid example of the revolutionary power of generative AI in digital commerce. With the product description writing and visual rendering being fully automated by the system, manual content-creation costs are lowered, catalog expansion is accelerated, and brand integrity is maintained through the consistency in the tone and imagery. This is one of the ways AI can be a creative collaborator, not just a passive automation tool.

Summary

By these contributions, the project is able to connect the academic and industrial worlds, thereby

creating the path for generative ecosystems that are self-evaluating and feedback-driven. The architecture that comes out of this work constitutes a strong base for the future intelligent retail workflows of the next generation, which will feature AI systems that are adaptive, continuously learning, verifying, and evolving in tandem with human creators.

C. Future Directions and Potential Improvements

While the current setup shows a robust performance across multimodal creation, verification, and user-assisted refinement, there are still several interesting research paths open for exploration to take the first system to further stages. Each of these directions is a potential raise of reliability, scalability, or adaptability leading to the next generation of catalog automation systems.

1. Retrieval-Augmented and Knowledge-Grounded Generation

The next versions of the products may have integrations with the knowledge bases of specific domains or retrieval-augmented generation (RAG) modules for the purpose of factual grounding when creating the text. By the process of fetching checked data—like the composition of the material, the identifiers of the SKUs, and the metadata of the compliance—the model will be capable to lessen hallucination and at the same time ensure that factual accuracy is traceable thus, the created data can be as per enterprise data governance standards.

2. Reinforcement Learning from Human Feedback (RLHF)

Conversion of operator interactions into structured reward signals will give an opportunity to a system to gradually align its results with brand tone, lighting preferences, and layout standards. A single preference-based reward model may derive directly from editors' actions (approve, regenerate, or modify), creating an extensive system for other continuous fine-tuning through reinforcement learning, which in result will be the generative adaptation loops becoming more human-like.

3. Aesthetic and Brand Consistency Scoring

Brand-trained evaluators, which can provide a numerical score for the stylistic conformity, are capable of objectively measuring the visual and tonal consistency. These models can check the conformity with the already set color palettes, the use of typography, and the templates of the compositions, thus forming automated quality control pipelines that are able to uphold the brand's identity in the catalogs of great volume.

4. Uncertainty-Aware Generation

The subsequent stage should bring together confidence estimation and uncertainty thresholds by adopting reliability mechanisms from medical imaging and safety-critical AI. These factors would signal when a generated sample is ready for publishing or is in need of a manual check, thus, they are instrumental in improving overall governance, accountability, and trust in autonomous generation systems.

5. 3D and Augmented-Reality Extensions

Future models might use neural radiance fields (NeRFs) or Gaussian splatting methods to create interactive 3D product visualizations aside from 2D image synthesis. That progression will facilitate AR-supported retail scenarios where customers will be able to examine products in an immersive environment while the photorealistic accuracy is kept.
6. Multilingual and Cultural Adaptation

A stage-by-stage system enhancement with the use of multilingual large language models may fulfill

the demand for localized product descriptions in different languages ensuring inclusiveness and market expansion. Matching the textual tone and the visual elements with local aesthetics and cultural preferences would make the cross-market deployment easier while semantic integrity and brand coherence will still be kept.

7. Ethical and Transparency Safeguards

The use of digital watermarking and provenance metadata embedded in the content created can be a method to confirm traceability, author recognition, and conformance to the regulations of authenticity that are constantly changing. The transparency dashboards showing the alignment scores, the confidence values, and the versioning of the model to the human reviewers can be very helpful in auditability and ethical accountability.

8. Energy-Efficient Inference and Edge Optimization

Implementing lightweight adaptation methods—like quantization, Low-Rank Adaptation (LoRA), and knowledge distillation—will lessen the computational energy and thus, will be a way of opening to consumer-grade GPUs or edge hardware deployment. Such measures will make AI technology a sustainable practice and at the same time, make it available to small and medium-sized retailers.

9. Dynamic Dataset Curation Pipelines

The implementation of automated dataset evolution loops can be a way to ensure the continuous improvement of the processes. The scores of the verifiers and the feedback of the people will be the main factors that drive the inclusion of new examples for training and will thus maintain the data freshness, relevance, and diversity without the necessity of manual curation; hence, the learning ecosystems will be self-sustaining.

10. Personalized and Adaptive Content Generation

As a matter of fact, upcoming versions might have features of user-centric personalization where behavioral or engagement analytics will be analyzed for the purpose of textual and visual outputs dynamic tailoring. This kind of flexibility could result in digital catalogs that are aware of audience preferences and therefore, they can evolve with them—online e-commerce-assets transformed into living, personalized content ecosystems.

Summary

All these research directions together represent a roadmap towards a fully adaptive, self-regulating, and ethically-compliant multimodal generation system. Progressing in these areas will enhance not only the system robustness but also the ways in which AI teams up with human creativity to co-create the next intelligent, brand-aware digital commerce era.

Final Remarks

Such a study serves as proof to this notion that AI powered multimodal content generation is no longer just a far-fetched idea but it is a real and deployable solution within digital commerce

ecosystems.

The outlined architecture essentially portrays catalog production as an evolutionary system of artificial intelligence operating in a closed-loop manner - continuously learning from data and human feedback, adjusting its behavior in line with editorial and ethical standards, and being able to extend its reach without restriction to different product categories and market domains.

The future development of these kinds of systems, however, will hinge on their capacity to integrate semantic grounding, factual accuracy, reinforcement learning, and transparent governance seamlessly into a single operational stack.

Once these capabilities become fully developed, multimodal generation will not simply be an automation tool but rather will be an interactive, trust-centered creative collaborator, thus, achieving higher standards in terms of stability, productivity, and aesthetic accuracy in the era of autonomous digital retail.

VI. REFERENCE

A. Citations of Relevant Literature and Sources

[1] White, J., Kameneva, T., & Mccarthy, C. (2022). Vision Processing for Assistive Vision: A Deep Reinforcement Learning Approach. *IEEE Transactions on Human-Machine Systems*, *52*(1), 123–133. https://doi.org/10.1109/thms.2021.3121661

[2] Shao, M., Shafique, M., Karri, R., & Basit, A. (2024). Survey of Different Large Language Model Architectures: Trends, Benchmarks, and Challenges. *IEEE Access*, *12*, 188664–188706. https://doi.org/10.1109/access.2024.3482107

[3] Zhou, H., Wu, D., Yuan, Y., Jiang, L., Hu, C., Wu, H., Jin, Y., Chen, C., Wang, X., Yuan, D., Zhang, J., Cui, Y., Liu, X., & Liu, J. (2025). Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities. *IEEE Communications Surveys & Tutorials*, *27*(3), 1955–2005. https://doi.org/10.1109/comst.2024.3465447

[4] Habib, M. A., Wadud, M. A. H., Okuyama, Y., Mridha, M. F., Talukder, M. H., Shin, J., Rahman, M. M., & Pinky, L. Y. (2024). GACnet-Text-to-Image Synthesis With Generative Models Using Attention Mechanisms With Contrastive Learning. *IEEE Access*, *12*, 9572–9585. https://doi.org/10.1109/access.2023.3342866

[5] Alhabeeb, S. K., & Al-Shargabi, A. A. (2024). Text-to-Image Synthesis With Generative Models: Methods, Datasets, Performance Metrics, Challenges, and Future Direction. *IEEE Access*, *12*, 24412–24427. https://doi.org/10.1109/access.2024.3365043

[6] Liu, J., Meng, S., Gao, Y., Mao, S., & Cai, P. (n.d.). *Aligning Vision to Language: Annotation-Free Multimodal Knowledge Graph Construction for Enhanced LLMs Reasoning*. https://openaccess.thecvf.com/content/ICCV2025/html/Liu_Aligning_Vision_to_Language_Annotation-Free_Multimodal_Knowledge_Graph_Construction_for_ICCV_2025_paper.html

[7] Balachandran, A., & Masum, M. (2025). *Visiorag: A Multimodal Framework for Enhancing Recommendation System Using Vision Transformers and Rag*. https://doi.org/10.1109/cai64502.2025.00025

[8] Alhabeeb, S., & Al-Shargabi, A. A. (n.d.). Text-to-Image Synthesis With Generative Models: Methods, Datasets, Performance Metrics, Challenges, and Future Direction. *IEEE Access*, *12*, 24412–24427. https://doi.org/10.1109/access.2024.3365043

[9] Chen, J., Shao, F., Chen, H., & Wang, X. (n.d.). *Quality Evaluation of AI-Generated Images: Subjective Study and Objective Methodology*. https://ieeexplore.ieee.org/abstract/document/11194189/

[10] Zhang, G., Li, S., Wei, S., Ge, S., Cai, N., & Zhao, Y. (2024). Multimodal Composition Example Mining for Composed Query Image Retrieval. *IEEE Transactions on Image Processing*, *33*, 1149–1161. https://doi.org/10.1109/tip.2024.3359062

[11] Zhang, C., Yang, Z., He, X., & Deng, L. (2020). Multimodal Intelligence: Representation Learning, Information Fusion, and Applications. *IEEE Journal of Selected Topics in Signal Processing*, *14*(3), 478–493. https://doi.org/10.1109/JSTSP.2020.2987728

[12] Zhan, F., Yu, Y., Wu, R., Zhang, J., Lu, S., Liu, L., Kortylewski, A., Theobalt, C., & Xing, E. P. (2023). Multimodal Image Synthesis and Editing: The Generative AI Era. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *45*(12), 15098–15119. https://doi.org/10.1109/tpami.2023.3305243

[13] Huang, N., Dong, W., Zhang, Y., Tang, F., Li, R., Ma, C., & Lee, T.-Y. (2024). CreativeSynth: Cross-Art-Attention for Artistic Image Synthesis With Multimodal Diffusion. *IEEE Transactions on Visualization and Computer Graphics*, *PP*. https://doi.org/10.1109/tvcg.2025.3570771

[14] S. M. Kadampur, M. M. Raikar and V. P. Baligar, "Multimodal AI For Image And Video Inference: Generate Text Output From Visual Inputs," 2025 6th International Conference for Emerging Technology (INCET), BELGAUM, India, 2025, pp. 1-7, doi: 10.1109/INCET64471.2025.11140112.

[15] L. Yin, "A Review of Text-to-Image Synthesis Methods," 2024 5th International Conference on Computer Vision, Image and Deep Learning (CVIDL), Zhuhai, China, 2024, pp. 858-861, doi: 10.1109/CVIDL62147.2024.10603609.

[16] S. Vinothkumar, S. Varadhaganapathy, R. Shanthakumari, S. Dhanushya, S. Guhan and P. Krisvanth, "Utilizing Generative AI for Text-to-Image Generation," *2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT)*, Kamand, India, 2024, pp. 1-6, doi: 10.1109/ICCCNT61001.2024.10725454.

[17] R. Arya, D. Joshi, K. Sharma, V. S. Bhakuni, S. Vats and V. Sharma, "Stacked Generative Adversarial Networks (StackGAN) Text-to-Image Generator," *2024 IEEE 3rd World Conference on Applied Intelligence and Computing (AIC)*, Gwalior, India, 2024, pp. 1095-1101, doi: 10.1109/AIC61668.2024.10730994.

[18] J. Xie and J. Chen, "Text-to-image Retrieval Based on Zero-shot Transfer Learning with CLIP Model and Vector Database," *2024 11th International Conference on Behavioural and Social Computing (BESC)*, Harbin, China, 2024, pp. 1-7, doi: 10.1109/BESC64747.2024.10780701.

[19] E. S. Goksu et al., "Technical Design and Performance Analysis of Centralized Product Catalog Management in Large Scale Telecommunication Systems: Turkcell CPCM Case," 2025 9th International Artificial Intelligence and Data Processing Symposium (IDAP), Malatya, Turkiye, 2025, pp. 1-7, doi: 10.1109/IDAP68205.2025.11222358.

[20] R. Neumann, R. Dumke and A. Schmietendorf, "Organic Product Catalogs: Towards an Architecture for Cloud-Based Micro Enterprise E-commerce," 2010 IEEE 3rd International Conference on Cloud Computing, Miami, FL, USA, 2010, pp. 530-531, doi: 10.1109/CLOUD.2010.54.

[21] Zhai, Y., Lin, Y., Peng, M., & Davis, L. (n.d.). *Text2Outfit: Controllable Outfit Generation with Multimodal Language Models*. https://openaccess.thecvf.com/content/ICCV2025/papers/Zhai_Text2Outfit_Controllable_Outfit_Generation_with_Multimodal_Language_Models_ICCV_2025_paper.pdf

[22] Zhou, S., Zhang, R., Zhu, H., & Kveton, B. (n.d.). *Multimodal LLMs as Customized Reward Models for Text-to-Image Generation*. https://openaccess.thecvf.com/content/ICCV2025/papers/Zhou_Multimodal_LLMs_as_Customized_Reward_Models_for_Text-to-Image_Generation_ICCV_2025_paper.pdf

[23] Geetha, M., Hariharan, S., Jeevanprasanth, T., & Sanjay, L. (2024). *Multimodal Content Generation: A Project for AI Creativity*. https://doi.org/10.1109/icercs63125.2024.10894945

[24] Zhu, Y., Wu, Y., Sebe, N., & Luo, L. (2024). Vision + X: A Survey on Multimodal Learning in the Light of Data. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 1–20. https://doi.org/10.1109/tpami.2024.3420239

[25] G. -W. Diao and J. -W. Liu, "Text-to-Image Diffusion Models via Additive Attention-Based Image Fusion Prompts," *2025 37th Chinese Control and Decision Conference (CCDC)*, Xiamen, China, 2025, pp. 4590-4595, doi: 10.1109/CCDC65474.2025.11091003.

[26] W. Li, Y. Gao and R. Zhang, "Research on the machine vision system for vehicle four-wheel alignment parameters," Proceedings of the 30th Chinese Control Conference, Yantai, China, 2011, pp. 3192-3195.

[27] Y. Liu et al., "3D Designer Toy Design Methods Based on Generative AI and AI Agent," 2024 Artificial Intelligence x Humanities, Education, and Art (AIxHEART), Laguna Hills, CA, USA, 2024, pp. 18-22, doi: 10.1109/AIxHeart62327.2024.00010.

[28] Y. Zhang, C. Peng, Q. Wang, D. Song, K. Li and S. Kevin Zhou, "Unified Multi-Modal Image Synthesis for Missing Modality Imputation," in IEEE Transactions on Medical Imaging, vol. 44, no. 1, pp. 4-18, Jan. 2025, doi: 10.1109/TMI.2024.3424785.

[29] J. Liang et al., "Synthesis and Edition of Ultrasound Images via Sketch Guided Progressive Growing GANS," 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI), Iowa City, IA, USA, 2020, pp. 1793-1797, doi: 10.1109/ISBI45749.2020.9098384.

[30] R. Yilmaz, K. Keven, Y. Wu and J. Stegmaier, "Cascaded Diffusion Models for 2D and 3D Microscopy Image Synthesis to Enhance Cell Segmentation," 2025 IEEE 22nd International Symposium on Biomedical Imaging (ISBI), Houston, TX, USA, 2025, pp. 1-5, doi: 10.1109/ISBI60581.2025.10981037.

[31] E. Shiro, "Potential of the Reverse Synthesis Method for the High-Quality SAR Image Synthesis," IGARSS 2018 - 2018 IEEE International Geoscience and Remote Sensing Symposium, Valencia, Spain, 2018, pp. 8905-8908, doi: 10.1109/IGARSS.2018.8518457.

[32] B. Peng, B. Liu, Y. Bin, L. Shen and J. Lei, "Multi-Modality MR Image Synthesis via Confidence-Guided Aggregation and Cross-Modality Refinement," in IEEE Journal of Biomedical and Health Informatics, vol. 26, no. 1, pp. 27-35, Jan. 2022, doi: 10.1109/JBHI.2021.3082541.

[33] Q. H. Cap and A. Fukuda, "High-Quality Medical Image Generation from Free-hand Sketch," 2024 46th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), Orlando, FL, USA, 2024, pp. 1-6, doi: 10.1109/EMBC53108.2024.10781774.

[34] Y. He et al., "Conditional Virtual Imaging for Few-Shot Vascular Image Segmentation," in IEEE Transactions on Medical Imaging, doi: 10.1109/TMI.2025.3608467.

[35] H. Singh, M. Rai, L. Raguar, J. Baliyan, P. K. Mall and S. Vashisth, "A Systematic Review of Image Generation Models: Methods, Comparative Insights, and Available Datasets," *2025 International Conference on Pervasive Computational Technologies (ICPCT)*, Greater Noida, India, 2025, pp. 615-618, doi: 10.1109/ICPCT64145.2025.10941132.

[36] J. Park, D. Jeong, H. Lee, S. Han and J. Paik, "Dynamic Contextual Attention Networks for Improved Single Image Generation," 2024 IEEE International Conference on Consumer Electronics (ICCE), Las Vegas, NV, USA, 2024, pp. 1-2, doi: 10.1109/ICCE59016.2024.10444449.

[37] M. Dash, T. Pant and H. Parganiha, "MEKA: Multimodal External Knowledge Augmentation for Social Media Image Captioning," *2025 8th International Conference on Information and Computer Technologies (ICICT)*, Hawaii-Hilo, HI, USA, 2025, pp. 479-485, doi: 10.1109/ICICT64582.2025.00081.

[38] L. Horvath and I. J. Rudas, "Towards the information content driven product model," 2008 IEEE International Conference on System of Systems Engineering, Monterey, CA, USA, 2008, pp. 1-6, doi: 10.1109/SYSOSE.2008.4724183

[39] Y. N. B, D. Samuel Azariya S, H. H. R and C. Jegan A, "An AI-Powered Interactive Assistant: Integrating Multimodal Interaction for Enhanced User Experience," *2024 International Conference on Emerging Research in Computational Science (ICERCS)*, Coimbatore, India, 2024, pp. 1-7, doi: 10.1109/ICERCS63125.2024.10895433.

[40] K. N. Sai, U. Wable, A. Singh, K. N. V. S. S, H. Gonuguntla and C. Jain, "Harnessing Multimodal AI for Creative Design: Performance Evaluation of Stable Diffusion and DALL-E 3 in Fashion Apparel and Typography," *2024 International Conference on Electrical, Computer and Energy Technologies (ICECET*, Sydney, Australia, 2024, pp. 1-6, doi: 10.1109/ICECET61485.2024.10698398.

[41] Prathwini, Prathyakshini, S. A and R. S, "Text-to-Image Generation of Bird Images Using GAN-CLS and MS-GAN," *2025 Third International Conference on Networks, Multimedia and Information Technology (NMITCON)*, BENGALURU, India, 2025, pp. 1-6, doi: 10.1109/NMITCON65824.2025.11188140.

[42] S. Lakhanpal, S. Chopra, V. Jain, A. Chadha and M. Luo, "Refining Text-to-Image Generation: Towards Accurate Training-Free Glyph-Enhanced Image Generation," *2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, Tucson, AZ, USA, 2025, pp. 4372-4381, doi: 10.1109/WACV61041.2025.00429.

[43] K. Wu, J. Ding, J. Li, Y. Yang, C. Zhang and J. Cao, "LLM-Empowered Image Generation in the Neko Painter App: A Preliminary Application for Producing Teaching Materials," *2024 4th International Conference on Educational Technology (ICET)*, Wuhan, China, 2024, pp. 110-114, doi: 10.1109/ICET62460.2024.10868922.

[44] B. Tural, Z. Örpek and Z. Destan, "Retrieval-Augmented Generation (RAG) and LLM Integration," *2024 8th International Symposium on Innovative Approaches in Smart Technologies (ISAS)*, İstanbul, Turkiye, 2024, pp. 1-5, doi: 10.1109/ISAS64331.2024.10845308.

[45] M. Nath, L. Ethirajan and J. Joshi, "Multilingual Infographics Generator: A language-agnostic visual summarizer," *2025 Conference on Artificial Intelligence x Multimedia (AIxMM)*, Laguna Hills, CA, USA, 2025, pp. 14-18, doi: 10.1109/AIxMM62960.2025.00009.

VII. APPENDICES

A. Code Snippets or Algorithms

1. Web App Code

```
import os
import io
import random
import base64
import threading
from flask import Flask, render_template, request, jsonify
from PIL import Image
import requests

# Import existing logic
from gd2 import get_product_descriptions
from flux_image_gen import generate_product_image

app = Flask(__name__)

# Global model cache
V_PROCESSOR = None
V_CLIP = None
V_CLASSIFIER = None
MODEL_LOCK = threading.Lock()

def load_verification_models():
    global V_PROCESSOR, V_CLIP, V_CLASSIFIER
    with MODEL_LOCK:
        if V_PROCESSOR is None:
            try:
                print("Loading verification models...")
                from verify_image import load_models
                V_PROCESSOR, V_CLIP, V_CLASSIFIER = load_models()
                print(f"Verification models loaded successfully. Classifier: {type(V_CLASSIFIER)}")
            except Exception as e:
                print(f"Failed to load verification models: {e}")

# Load models in background on startup
threading.Thread(target=load_verification_models, daemon=True).start()

@app.route('/')
def index():
    return render_template('index_v2.html')
@app.route('/api/status')
def status():
    return jsonify({
        "models_loaded": V_PROCESSOR is not None,
        "processor": str(type(V_PROCESSOR)),
        "classifier": str(type(V_CLASSIFIER))
    })
@app.route('/api/generate', methods=['POST'])
def generate():
    data = request.json
```

```
    product_name = data.get('product')
    variant_idx = data.get('variant', 1)
    do_verify = data.get('verify', True)
    if not product_name:
        return jsonify({"error": "Product name required"}), 400

    # 1. Get Description
    visual_desc = ""
    features = "Features unavailable (AI Quota Limit)"
    try:
        visual_desc, feats = get_product_descriptions(f"{product_name} variation {variant_idx}")
        # Format features
        if isinstance(feats, (list, tuple)):
            features = "• " + "\n• ".join([str(x).strip() for x in feats if str(x).strip()])
        else:
            features = str(feats)
    except Exception:
        print(f"[{product_name}] Description AI busy. Using raw prompt.")
        visual_desc = "high quality, detailed, 8k, photorealistic"

    # 2. Generate Image
    full_prompt = f"{product_name}, {visual_desc}"
    image_url = ""
    image_b64 = ""
    try:
        urls = generate_product_image(full_prompt)
        if urls:
            image_url = urls[0]
            # Download and convert to base64 for easier frontend display/saving
            img_data = requests.get(image_url).content
            image_b64 = base64.b64encode(img_data).decode('utf-8')
    except Exception as e:
        return jsonify({"error": f"Image generation failed: {str(e)}"}), 500

    # 3. Verify (if requested and image exists)
    is_match = False
    score = 0.0
    verification_status = "skipped"

    if do_verify and image_b64 and V_PROCESSOR:
        try:
            import torch
            img_bytes = base64.b64decode(image_b64)
            img = Image.open(io.BytesIO(img_bytes)).convert("RGB")
            inputs = V_PROCESSOR(text=[product_name], images=img, return_tensors="pt",
padding="max_length", max_length=77, truncation=True)
            device = "cuda" if torch.cuda.is_available() else "cpu"
            inputs = {k: v.to(device) for k, v in inputs.items()}
            with torch.no_grad():
                outputs = V_CLIP(**inputs)
                score = V_CLASSIFIER(outputs.image_embeds, outputs.text_embeds).item()
                is_match = score > 0.5
                verification_status = "success"
                print(f"[{product_name}] Verification Complete. Score: {score:.4f}, Match:
{is_match}")
        except Exception as e:
```

```
            print(f"Verification failed: {e}")
            verification_status = "error"
    return jsonify({
        "product": product_name,
        "variant": variant_idx,
        "features": features,
        "image_b64": image_b64,
        "visual_desc": visual_desc,
        "verification": {
            "status": verification_status,
            "is_match": is_match,
            "score": score
        }
    })

# Define absolute path to generated_images based on CWD

GEN_IMAGES_DIR = os.path.abspath("generated_images")
@app.route('/api/save', methods=['POST'])
def save_image():
    data = request.json
    product_name = data.get('product')
    variant_idx = data.get('variant')
    image_b64 = data.get('image_b64')
    features = data.get('features')
    description = data.get('description', 'No description available.')

    if not all([product_name, variant_idx, image_b64]):
        return jsonify({"error": "Missing data"}), 400
    try:
        os.makedirs(GEN_IMAGES_DIR, exist_ok=True)
        base_name = f"{product_name.replace(' ', '_')}_{variant_idx}"
        img_path = os.path.join(GEN_IMAGES_DIR, f"{base_name}.png")
        txt_path = os.path.join(GEN_IMAGES_DIR, f"{base_name}.txt")
        with open(img_path, "wb") as f:
            f.write(base64.b64decode(image_b64))
        with open(txt_path, "w") as f:
            f.write(f"[VISUAL DESCRIPTION]\n{description}\n\n[FEATURES]\n{features}")

        _rebuild_gallery_html()
        return jsonify({"status": "success", "path": img_path})
    except Exception as e:
        print(f"Failed to save image: {e}")
        return jsonify({"error": str(e)}), 500
def _rebuild_gallery_html():
    gallery_path = os.path.join(GEN_IMAGES_DIR, "gallery.html")

    if not os.path.exists(GEN_IMAGES_DIR):
        return
    # Scan for images
    images = [f for f in os.listdir(GEN_IMAGES_DIR) if f.lower().endswith(('.png', '.jpg', '.jpeg'))]
    images.sort(key=lambda x: os.path.getmtime(os.path.join(GEN_IMAGES_DIR, x)),
reverse=True)

    html_content = '''
<!DOCTYPE html>
```

```
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>NEO-GENESIS Archive</title>
    <style>
        body { background-color: #020617; color: #f8fafc; font-family: 'Segoe UI', sans-serif;
padding: 40px; }
        h1 { text-align: center; margin-bottom: 40px; font-size: 2.5em; color: #8b5cf6; }
        .grid { display: grid; grid-template-columns: repeat(auto-fill, minmax(300px, 1fr)); gap:
30px; }
        .card { background: #0f172a; border: 1px solid #1e293b; border-radius: 15px; overflow:
hidden; transition: transform 0.2s; }
        .card:hover { transform: translateY(-5px); border-color: #8b5cf6; }
        img { width: 100%; height: 400px; object-fit: cover; }
        .info { padding: 20px; }
        h3 { margin: 0 0 10px 0; color: #fff; }
        p { color: #94a3b8; font-size: 0.9em; white-space: pre-wrap; }
    </style>
</head>
<body>
    <h1>ARCHIVED GENERATIONS</h1>
    <div class="grid" id="grid">
'''
    for img_file in images:
        name = os.path.splitext(img_file)[0].replace('_', ' ').title()
        txt_file = os.path.splitext(img_file)[0] + ".txt"
        features = "No features available."

        txt_full_path = os.path.join(GEN_IMAGES_DIR, txt_file)
        if os.path.exists(txt_full_path):
            with open(txt_full_path, "r") as f:
                features = f.read()

        # Use the /generated_images/ route for src
        html_content += f'''
    <div class="card">
        <img src="/generated_images/{img_file}" alt="{name}">
        <div class="info">
            <h3>{name}</h3>
            <p>{features}</p>
        </div>
    </div>
        '''
    html_content += '''
    </div>
</body>
</html>
'''
    with open(gallery_path, "w") as f:
        f.write(html_content)

@app.route('/gallery')
def gallery():
    _rebuild_gallery_html()
    gallery_path = os.path.join(GEN_IMAGES_DIR, "gallery.html")
```

```
    if os.path.exists(gallery_path):
        with open(gallery_path, "r") as f:
            return f.read()
    return "Gallery is empty."


@app.route('/generated_images/<path:filename>')
def serve_image(filename):
    from flask import send_from_directory
    return send_from_directory(GEN_IMAGES_DIR, filename)

if __name__ == '__main__':
    app.run(debug=True, port=5000)
```

2. App GUI Code

```
# catalog_neon_enhanced.py
import customtkinter as ctk
from tkinter import messagebox, Toplevel
from PIL import Image, ImageTk, ImageDraw, ImageFilter, ImageEnhance
import threading, requests, io, os, random, math, webbrowser
import concurrent.futures
import time

from gd2 import get_product_descriptions
from flux_image_gen import generate_product_image

# ========= ASSET GENERATORS =========
# ========= ASSET GENERATORS =========
def generate_premium_bg(width, height):
    """
    Tries to load a cached premium background.
    If missing, generates one using Flux AI (Replicate) and saves it.
    Falls back to procedural generation if AI fails.
    """
    cache_path = "assets/background.png"
    os.makedirs("assets", exist_ok=True)

    # 1. Try loading cached image
    if os.path.exists(cache_path):
        try:
            print("DEBUG: Loading cached background...")
            img = Image.open(cache_path).convert("RGB")
            return img.resize((width, height), Image.Resampling.LANCZOS)
        except Exception as e:
            print(f"DEBUG: Cache load failed: {e}")

    # 2. Try generating via Flux AI
    print("DEBUG: Generating new premium background via AI...")
    try:
        # A prompt for a stunning, dark, modern UI background
        prompt = "abstract luxury deep purple neon background, violet and magenta gradients,
smooth, 8k, high quality, wallpaper, minimalist, cyber aesthetic"
        urls = generate_product_image(prompt)
        if urls:
```

```
            data = requests.get(urls[0]).content
            img = Image.open(io.BytesIO(data)).convert("RGB")

            # Save to cache
            img.save(cache_path)
            print("DEBUG: Premium background generated and cached.")

            return img.resize((width, height), Image.Resampling.LANCZOS)
        except Exception as e:
            print(f"DEBUG: AI Background generation failed: {e}")

    # 3. Fallback: Procedural Aurora
    print("DEBUG: Falling back to procedural background.")
    return generate_aurora_bg(width, height)

def generate_aurora_bg(width, height):
    """Generates a deep, rich aurora background (Fallback)."""
    # Base: Deep Void
    img = Image.new("RGB", (width, height), "#020617")
    draw = ImageDraw.Draw(img)

    # 1. Vertical Gradient (Midnight Blue -> Deep Purple)
    for y in range(height):
        t = y / height
        r = int(2 + 10 * t)
        g = int(6 + 5 * t)
        b = int(23 + 20 * t)
        draw.line([(0, y), (width, y)], fill=(r, g, b))

    # 2. Nebulas (Large soft blobs)
    colors = [
        (88, 28, 135),   # Deep Purple
        (12, 74, 110),   # Deep Blue
        (190, 24, 93),   # Pink
    ]

    for _ in range(8):
        cx, cy = random.randint(0, width), random.randint(0, height)
        radius = random.randint(300, 800)
        color = random.choice(colors)

        # Radial gradient simulation for blob
        overlay = Image.new("RGBA", (width, height), (0,0,0,0))
        odraw = ImageDraw.Draw(overlay)

        # Draw a soft ellipse
        left, top, right, bottom = cx-radius, cy-radius, cx+radius, cy+radius
        odraw.ellipse((left, top, right, bottom), fill=(*color, 40))

        # Blur it heavily
        overlay = overlay.filter(ImageFilter.GaussianBlur(radius=100))
        img.paste(overlay, (0,0), overlay)

    # 3. Stars (Tiny bright points)
    for _ in range(400):
        x, y = random.randint(0, width), random.randint(0, height)
```

```
        opacity = random.randint(100, 255)
        draw.point((x, y), fill=(255, 255, 255, opacity))

    return img

def generate_glass_texture(width, height, opacity=0.85):
    """Generates a frosted glass texture."""
    # Semi-transparent base
    img = Image.new("RGBA", (width, height), (15, 23, 42, int(255 * opacity)))
    return img

# ========= THEME CONFIG =========
THEME = {
    "bg_color": "#020617",
    "accent_primary": "#8b5cf6",   # Violet
    "accent_secondary": "#06b6d4", # Cyan
    "text_main": "#f8fafc",
    "text_dim": "#94a3b8",
    "success": "#10b981",
    "error": "#ef4444",
    "font_header": ("Segoe UI", 32, "bold"),
    "font_sub": ("Segoe UI", 16),
    "font_body": ("Segoe UI", 14),
}

# ========= CUSTOM WIDGETS =========

class GlassFrame(ctk.CTkFrame):
    """A frame that simulates frosted glass."""
    def __init__(self, master, **kwargs):
        super().__init__(master, **kwargs)
        self.configure(fg_color="#0f172a", bg_color="transparent", corner_radius=20,
border_width=1, border_color="#1e293b")
        # Note: True blur isn't possible in Tkinter, so we use a semi-transparent dark color
        # that looks good against the dark background.

class GlowingButton(ctk.CTkButton):
    """Button with a neon glow hover effect."""
    def __init__(self, master, **kwargs):
        super().__init__(master, **kwargs)
        self.default_fg = kwargs.get("fg_color", THEME["accent_primary"])
        self.hover_fg = kwargs.get("hover_color", "#7c3aed")
        self.configure(
            fg_color=self.default_fg,
            hover_color=self.hover_fg,
            corner_radius=12,
            height=45,
            font=("Segoe UI", 14, "bold")
        )
        self.bind("<Enter>", self._glow)
        self.bind("<Leave>", self._unglow)

    def _glow(self, _):
        self.configure(border_width=2, border_color="#c4b5fd")

    def _unglow(self, _):
```

```
        self.configure(border_width=0)

class StatusStream(ctk.CTkScrollableFrame):
    """Matrix-style scrolling status log."""
    def __init__(self, master, **kwargs):
        super().__init__(master, **kwargs)
        self.configure(fg_color="#020617", corner_radius=10, border_width=1,
border_color="#1e293b")
        self.lines = []

    def log(self, text, color=THEME["text_main"]):
        lbl = ctk.CTkLabel(self, text=f"> {text}", font=("Consolas", 12), text_color=color,
anchor="w")
        lbl.pack(fill="x", pady=2, padx=5)
        self.lines.append(lbl)
        self.after(10, self._scroll_to_bottom)

    def _scroll_to_bottom(self):
        self._parent_canvas.yview_moveto(1.0)

# ========== MAIN APP ==========
class ProductGeneratorApp:
    def __init__(self, root):
        print("DEBUG: App initializing...")
        self.root = root
        self.root.title("NEO-GENESIS | AI Product Catalog")

        # Fullscreen Setup
        self.fullscreen = True
        self.root.attributes("-fullscreen", True)
        self.root.configure(bg="#000000")
        self.root.bind("<Escape>", lambda e: self.toggle_fullscreen())
        self.root.bind("<F11>", lambda e: self.toggle_fullscreen())

        ctk.set_appearance_mode("dark")
        self.w, self.h = root.winfo_screenwidth(), root.winfo_screenheight()
        print(f"DEBUG: Screen size {self.w}x{self.h}")

        # Initialize System
        os.makedirs("generated_images", exist_ok=True)
        self.verification_ready = False
        self._load_models_bg()

        # Background System
        print("DEBUG: Generating background...")
        self.bg_img_raw = generate_premium_bg(self.w, self.h)
        self.bg_photo = ImageTk.PhotoImage(self.bg_img_raw)
        print("DEBUG: Background generated.")

        # Navigation Stack
        self.pages = {}
        self.current_page = None

        print("DEBUG: Initializing UI...")
        self._init_ui()
        print("DEBUG: UI Initialized.")
```

```
def _load_models_bg(self):
    def _load():
        try:
            print("DEBUG: Loading verification models...")
            from verify_image import load_models
            self.v_processor, self.v_clip, self.v_classifier = load_models()
            self.verification_ready = True
            print("System Online: Verification Module Loaded.")
        except Exception as e:
            print(f"System Warning: Verification Module Failed - {e}")
    threading.Thread(target=_load, daemon=True).start()

def toggle_fullscreen(self):
    self.fullscreen = not self.fullscreen
    self.root.attributes("-fullscreen", self.fullscreen)

def _init_ui(self):
    # Base Container (holds background)
    self.container = ctk.CTkFrame(self.root, fg_color="black")
    self.container.pack(fill="both", expand=True)

    # Background Label
    self.bg_label = ctk.CTkLabel(self.container, image=self.bg_photo, text="")
    self.bg_label.place(x=0, y=0, relwidth=1, relheight=1)

    # Pages
    print("DEBUG: Building pages...")
    self.pages["home"] = self._build_home()
    self.pages["loading"] = self._build_loading()
    self.pages["catalog"] = self._build_catalog()
    print("DEBUG: Pages built.")

    self.show_page("home")

def show_page(self, name):
    if self.current_page:
        self.current_page.place_forget()

    self.current_page = self.pages[name]
    # Fade in effect (simulated)
    self.current_page.place(relx=0.5, rely=0.5, anchor="center", relwidth=1, relheight=1)

# ========= HOME PAGE =========
def _build_home(self):
    frame = ctk.CTkFrame(self.container, fg_color="transparent")

    # Hero Card
    card = GlassFrame(frame, width=900, height=600)
    card.place(relx=0.5, rely=0.5, anchor="center")

    # Content
    content = ctk.CTkFrame(card, fg_color="transparent")
    content.pack(fill="both", expand=True, padx=60, pady=60)

    # Header
```

```
        ctk.CTkLabel(content, text="NEO-GENESIS", font=("Segoe UI", 48, "bold"),
text_color=THEME["text_main"]).pack(pady=(0, 10))
        ctk.CTkLabel(content, text="Architect the future of product design.",
font=THEME["font_sub"], text_color=THEME["text_dim"]).pack(pady=(0, 50))

        # Input Area
        input_frame = ctk.CTkFrame(content, fg_color="transparent")
        input_frame.pack(fill="x", pady=20)

        self.entry = ctk.CTkEntry(
            input_frame,
            placeholder_text="Describe your vision (e.g. 'Cyberpunk Sneakers, Neon Drone')...",
            height=60,
            font=("Segoe UI", 18),
            fg_color="#1e293b",
            border_color="#334155",
            text_color="white"
        )
        self.entry.pack(fill="x")

        # Controls
        controls = ctk.CTkFrame(content, fg_color="transparent")
        controls.pack(fill="x", pady=30)

        self.verify_var = ctk.BooleanVar(value=True)
        switch = ctk.CTkSwitch(
            controls,
            text="AI Verification (High Precision)",
            variable=self.verify_var,
            font=("Segoe UI", 14),
            progress_color=THEME["accent_primary"],
            fg_color="#334155"
        )
        switch.pack(side="left")

        # Action Buttons
        btn_frame = ctk.CTkFrame(content, fg_color="transparent")
        btn_frame.pack(fill="x", pady=20)

        GlowingButton(btn_frame, text="INITIALIZE GENERATION",
command=self.start_generation, height=55, font=("Segoe UI", 16, "bold")).pack(fill="x",
pady=(0, 15))

        ctk.CTkButton(
            btn_frame,
            text="Access Archives",
            fg_color="transparent",
            border_width=1,
            border_color="#334155",
            hover_color="#1e293b",
            command=self.open_gallery
        ).pack(fill="x")

        return frame

    # ========== LOADING PAGE ==========
```

```
    def _build_loading(self):
        frame = ctk.CTkFrame(self.container, fg_color="transparent")

        card = GlassFrame(frame, width=800, height=600)
        card.place(relx=0.5, rely=0.5, anchor="center")

        content = ctk.CTkFrame(card, fg_color="transparent")
        content.pack(fill="both", expand=True, padx=50, pady=50)

        ctk.CTkLabel(content, text="SYSTEM PROCESSING", font=("Segoe UI", 24, "bold"),
text_color=THEME["accent_secondary"]).pack(pady=(0, 20))

        self.loader = ctk.CTkProgressBar(content, width=600, height=4,
progress_color=THEME["accent_primary"])
        self.loader.pack(pady=20)
        self.loader.configure(mode="indeterminate")
        self.loader.start()

        self.status_log = StatusStream(content, height=300)
        self.status_log.pack(fill="x", pady=20)

        return frame

    # ========= CATALOG PAGE =========
    def _build_catalog(self):
        frame = ctk.CTkFrame(self.container, fg_color="transparent")

        # Header Bar
        header = ctk.CTkFrame(frame, fg_color="#0f172a", height=80, corner_radius=0)
        header.pack(fill="x")

        ctk.CTkLabel(header, text="GENERATION RESULTS", font=("Segoe UI", 20, "bold"),
text_color="white").pack(side="left", padx=40, pady=20)

        ctk.CTkButton(
            header,
            text="NEW SESSION",
            fg_color="#334155",
            hover_color="#475569",
            command=lambda: self.show_page("home")
        ).pack(side="right", padx=40)

        # Scrollable Grid
        self.catalog_scroll = ctk.CTkScrollableFrame(frame, fg_color="transparent")
        self.catalog_scroll.pack(fill="both", expand=True, padx=20, pady=20)

        # Responsive Grid Binding
        self.catalog_scroll.bind("<Configure>", self._on_catalog_resize)
        self.current_results = []
        self.last_cols = 0

        return frame

    # ========= LOGIC =========
    def start_generation(self):
        txt = self.entry.get().strip()
```

```
    if not txt:
        return messagebox.showerror("Input Error", "Please define a product vision.")

    self.products = [p.strip() for p in txt.split(",") if p.strip()]
    self.show_page("loading")

    # Reset Log
    for w in self.status_log.winfo_children(): w.destroy()
    self.status_log.lines = []

    threading.Thread(target=self._run_generation, daemon=True).start()

def _run_generation(self):
    results = []
    do_verify = self.verify_var.get()

    self.log(f"Initializing generation sequence for {len(self.products)} targets...")

    if do_verify and not self.verification_ready:
        self.log("Verification module offline. Bypassing...", THEME["error"])
        do_verify = False

    # Batch 1: Parallel Execution (Variants 1-3)
    self.log("Batch 1: Processing variants 1-3 in parallel...")
    with concurrent.futures.ThreadPoolExecutor(max_workers=3) as executor:
        futures = []
        for p in self.products:
            for i in range(1, 4):  # Variants 1, 2, 3
                futures.append(executor.submit(self._process_variant, p, i, do_verify))

        for future in concurrent.futures.as_completed(futures):
            try:
                res = future.result()
                results.append(res)
            except Exception as e:
                self.log(f"Process Failure (Batch 1): {e}", THEME["error"])

    # Batch 2: Series Execution (Variants 4-5) with Delay
    self.log("Batch 2: Processing variants 4-5 in series (slow mode)...")
    for p in self.products:
        for i in range(4, 6):  # Variants 4, 5
            try:
                self.log(f"Waiting 2s before processing variant {i}...", THEME["text_dim"])
                time.sleep(2)  # Artificial delay
                res = self._process_variant(p, i, do_verify)
                results.append(res)
            except Exception as e:
                self.log(f"Process Failure (Batch 2): {e}", THEME["error"])

    self.log("Sequence Complete. Compiling results...")
    self.root.after(800, lambda: self._show_results(results))

def _process_variant(self, p, i, do_verify):
    self.log(f"[{p}] Analyzing semantic features for variant {i}...")

    visual_desc = ""
```

```
        features = "Features unavailable (AI Quota Limit)"

        try:
            visual_desc, feats = get_product_descriptions(f"{p} variation {i}")
            features = self._format_features(feats)
        except Exception as e:
            self.log(f"[{p}] Description AI busy/quota. Using raw prompt.", THEME["error"])
            visual_desc = "high quality, detailed, 8k, photorealistic"

        self.log(f"[{p}] Rendering visual asset {i}...")
        full_prompt = f"{p}, {visual_desc}"
        urls = generate_product_image(full_prompt)
        data = requests.get(urls[0]).content if urls else None

        is_match = False
        score = 0.0

        if do_verify and data:
            self.log(f"[{p}] Verifying semantic alignment {i}...")
            try:
                temp_path = f"temp_{random.randint(0,99999)}.png"
                with open(temp_path, "wb") as f: f.write(data)

                from PIL import Image
                import torch
                img = Image.open(temp_path).convert("RGB")
                inputs = self.v_processor(text=[p], images=img, return_tensors="pt",
padding="max_length", max_length=77, truncation=True)
                device = "cuda" if torch.cuda.is_available() else "cpu"
                inputs = {k: v.to(device) for k, v in inputs.items()}

                with torch.no_grad():
                    outputs = self.v_clip(**inputs)
                    score = self.v_classifier(outputs.image_embeds, outputs.text_embeds).item()
                    is_match = score > 0.5

                os.remove(temp_path)
                status = "MATCH" if is_match else "MISMATCH"
                color = THEME["success"] if is_match else THEME["error"]
                self.log(f"[{p}] Verification Complete: {status} ({score:.2f})", color)
            except Exception as e:
                self.log(f"Verification Error: {e}", THEME["error"])

        return (p, i, features, data, is_match, score, do_verify)

    def log(self, msg, color=THEME["text_main"]):
        self.root.after(0, lambda: self.status_log.log(msg, color))

    def _show_results(self, results):
        self.current_results = sorted(results, key=lambda x: (x[0], x[1]))
        self._regrid_catalog(4) # Default to 4
        self.show_page("catalog")

    def _on_catalog_resize(self, event):
        if not self.current_results: return
        cols = 4 # Force 4 columns
```

```
        if cols != self.last_cols:
            self.last_cols = cols
            self._regrid_catalog(cols)

    def _regrid_catalog(self, cols):
        for w in self.catalog_scroll.winfo_children(): w.grid_forget()
        for i in range(cols): self.catalog_scroll.grid_columnconfigure(i, weight=1)

        for i, item in enumerate(self.current_results):
            self._make_card(item, i // cols, i % cols)

    def _make_card(self, item, r, c):
        name, idx, features, data, is_match, score, verified = item

        # Card Container
        card = GlassFrame(self.catalog_scroll)
        card.grid(row=r, column=c, padx=10, pady=10, sticky="nsew")

        # Image Area
        if data:
            try:
                img = Image.open(io.BytesIO(data)).resize((300, 400))
                tk_img = ImageTk.PhotoImage(img)
                lbl = ctk.CTkLabel(card, image=tk_img, text="")
                lbl.image = tk_img
                lbl.pack(pady=10, padx=10)
                lbl.bind("<Button-1>", lambda e: self.lightbox(img, name, idx, features))
            except:
                ctk.CTkLabel(card, text="[RENDER ERROR]",
text_color=THEME["error"]).pack(pady=40)
        else:
            ctk.CTkLabel(card, text="[NO DATA]", text_color=THEME["text_dim"]).pack(pady=40)

        # Info
        info = ctk.CTkFrame(card, fg_color="transparent")
        info.pack(fill="x", padx=15, pady=(0, 15))

        ctk.CTkLabel(info, text=f"{name.title()} #{idx}", font=("Segoe UI", 16, "bold"),
text_color="white").pack(anchor="w")

        if verified:
            color = THEME["success"] if is_match else THEME["error"]
            text = f"VERIFIED {int(score*100)}%" if is_match else f"MISMATCH
{int(score*100)}%"
            ctk.CTkLabel(info, text=text, font=("Segoe UI", 11, "bold"),
text_color=color).pack(anchor="w", pady=2)

        ctk.CTkLabel(info, text=features, font=("Segoe UI", 12), text_color=THEME["text_dim"],
justify="left", wraplength=280).pack(anchor="w", pady=(5,0))

    def _format_features(self, feats):
        if isinstance(feats, (list, tuple)):
            return "• " + "\n• ".join([str(x).strip() for x in feats if str(x).strip()])
        return str(feats)

    def open_gallery(self):
```

```
        self._rebuild_gallery_html()
        path = os.path.abspath("generated_images/gallery.html")
        if os.path.exists(path): webbrowser.open(f"file:///{path}")
        else: messagebox.showinfo("Info", "Gallery is empty.")

    def _rebuild_gallery_html(self):
        gallery_path = "generated_images/gallery.html"
        images_dir = "generated_images"

        # Scan for images
        images = [f for f in os.listdir(images_dir) if f.lower().endswith(('.png', '.jpg', '.jpeg'))]
        images.sort(key=lambda x: os.path.getmtime(os.path.join(images_dir, x)), reverse=True)

        html_content = '''
<!DOCTYPE html>
<html lang="en">
<head>
    <meta charset="UTF-8">
    <meta name="viewport" content="width=device-width, initial-scale=1.0">
    <title>NEO-GENESIS Archive</title>
    <style>
        body { background-color: #020617; color: #f8fafc; font-family: 'Segoe UI', sans-serif;
padding: 40px; }
        h1 { text-align: center; margin-bottom: 40px; font-size: 2.5em; color: #8b5cf6; }
        .grid { display: grid; grid-template-columns: repeat(auto-fill, minmax(300px, 1fr)); gap:
30px; }
        .card { background: #0f172a; border: 1px solid #1e293b; border-radius: 15px; overflow:
hidden; transition: transform 0.2s; }
        .card:hover { transform: translateY(-5px); border-color: #8b5cf6; }
        img { width: 100%; height: 400px; object-fit: cover; }
        .info { padding: 20px; }
        h3 { margin: 0 0 10px 0; color: #fff; }
        p { color: #94a3b8; font-size: 0.9em; white-space: pre-wrap; }
    </style>
</head>
<body>
    <h1>ARCHIVED GENERATIONS</h1>
    <div class="grid" id="grid">
'''

        for img_file in images:
            name = os.path.splitext(img_file)[0].replace('_', ' ').title()
            txt_file = os.path.splitext(img_file)[0] + ".txt"
            features = "No features available."

            if os.path.exists(os.path.join(images_dir, txt_file)):
                with open(os.path.join(images_dir, txt_file), "r") as f:
                    features = f.read()

            html_content += f'''
        <div class="card">
            <img src="{img_file}" alt="{name}">
            <div class="info">
                <h3>{name}</h3>
                <p>{features}</p>
            </div>
```

```
        </div>
            '''

        html_content += '''
    </div>
</body>
</html>
'''
        with open(gallery_path, "w") as f:
            f.write(html_content)

    def lightbox(self, image, name, idx, features):
        top = Toplevel(self.root)
        top.title("Viewer")
        top.configure(bg="#020617")
        top.state("zoomed")

        w, h = image.size
        scale = min(self.w/w, (self.h-100)/h) * 0.8
        img_resized = image.resize((int(w*scale), int(h*scale)))
        tk_img = ImageTk.PhotoImage(img_resized)

        lbl = ctk.CTkLabel(top, image=tk_img, text="")
        lbl.image = tk_img
        lbl.pack(expand=True)

        def save():
            base = f"{name.replace(' ', '_')}_{idx}"
            save_path = f"generated_images/{base}.png"
            image.save(save_path)
            with open(f"generated_images/{base}.txt", "w") as f: f.write(features)

            self._rebuild_gallery_html()
            messagebox.showinfo("Saved", f"Saved to Archive.\n{save_path}")

        GlowingButton(top, text="SAVE TO ARCHIVE", command=save,
width=200).pack(pady=20)

if __name__ == "__main__":
    root = ctk.CTk()
    app = ProductGeneratorApp(root)
    root.mainloop()
```

3. Text Generation Code

```
import google.generativeai as genai

genai.configure(api_key="AIzaSyDv4gr_JtJyWiGx2Di_e2y8CtYM1eehuEY")

def get_product_descriptions(product_name):
    model = genai.GenerativeModel("gemini-2.0-flash")

    prompt1 = (
        f"Describe {product_name} in extreme detail for a high-quality product photography
generation. "
        "Focus on lighting, materials, textures, colors, and camera angle. "
```

```
        "Describe the neon/cyberpunk aesthetic if applicable, or a premium studio setting. "
        "The description should be a single, dense paragraph suitable for a text-to-image model like
Flux. "
        "Do not include bullet points."
    )

    prompt2 = (
        f"List only the key features of {product_name} in a single concise paragraph. "
        "Do NOT include introductions, explanations, disclaimers, or assumptions. "
        "Do NOT say anything like 'here are the features' or 'it is impossible'. "
        "Only output the features text."
    )

    response1 = model.generate_content(prompt1)
    response2 = model.generate_content(prompt2)

    def extract_text(response):
        if response and response.candidates:
            parts = response.candidates[0].content.parts
            return "".join([p.text for p in parts if p.text]) if parts else ""
        return ""

    return extract_text(response1), extract_text(response2)
```

4. Image Generation Code

```
import os
import replicate

# Configure Replicate API
os.environ["REPLICATE_API_TOKEN"] =
"r8_RJmZNsOpNc06QEa2oM5TUX3VHvFZpFC1qweQZ"
client = replicate.Client(api_token=os.environ["REPLICATE_API_TOKEN"])

def generate_product_image(prompt: str):
    """
    Generates product images from a text prompt using Flux / Replicate API.
    Returns: list of image URLs (strings)
    """

    # Call Flux model on Replicate
    output = client.run(
        "black-forest-labs/flux-schnell",  # change if using different model
        input={"prompt": prompt}
    )

    # FIX: Convert all outputs into plain strings
    # If Replicate returns FileOutput objects, convert them
    image_urls = [str(out) for out in output]

    return image_urls
```

B. Finalized IEEE Paper

AI Driven Product Catalogue Generation Using Generative Models

Sujana Hariyapureddy
Dept. Electronics & Communication
Presidency University
Bengaluru, India
sujana.hariyapureddy@gmail.com

Pavithra T
Dept. Computer Science&Technology
Presidency University
Bengaluru, India
pavithrat0441@gmail.com

Shreyas R Patil
Dept. Electronics & Communication
Presidency University
Bengaluru, India
shreyasrpatil2020@gmail.com

Robin Rohit Vincent
Dept. Computer Science&Technology
Presidency University
Bengaluru, India
robinrohit@gmail.com

Nagaraja S. R.
Dept. Computer Science&Technology
Presidency University
Bengaluru, India
nagarajasr027@gmail.com

Prashanth Kannadaguli
Chief Research Architecture
Samsung R&D Institute,
Bengaluru, India
prashscd@gmail.com

***Abstract*— The swift growth of online digital commerce has led to a higher necessity for automatic systems that are capable of generating product images as well as descriptions with only a few manual interventions. In this article, we introduce a feasible multimodal architecture that leverages CLIP-based embeddings, a small verification classifier, and a diffusion-based text-to-image model to create product visuals that are in line with the text as well as generate the corresponding captions from basic user inputs. The system checks the consistency of the prompt–image by comparing the embeddings and thus filters the outputs using a trained verification model, thereby enhancing the trustworthiness of automated catalog creation. The experimental outcomes demonstrate that the pipeline is capable of producing images that are visually consistent along with texts that are clear and can be used in lightweight catalog workflows which is an effective method of automated product content generation.**

Keywords*— *Multimodal AI, Catalog Automation, Text-to-Image, LLM Generation, Image Synthesis, Vision Alignment, Product Content

I. INTRODUCTION

Artificial intelligence improvements have largely altered the way multimodal content generation works. Now, systems can not only understand the text but also look at pictures, and then come up with a new image or short description as per the request in text. The first steps in perception-based processing showed how a reinforcement-driven visual understanding can be used for complex recognition tasks [1], thereby paving the way for multimodal intelligence. The rapid growth of LLMs architectures has brought up issues related to the scale, benchmark, and computational requirements of very large generative models [2], at the same time surveys in the different domains show that LLMs are being localized to meet the needs of the high-demand industrial environments [3].

On the other hand, the progress in generative modelling has been a major factor behind the rise of the quality of text-to-image synthesis. The research on attention-enhanced models with contrastive learning [4] and the thorough analysis of generative model architectures, evaluation metrics, and challenges [5] have been instrumental in the evolutionary journey of multimodal synthesis.

The project is funded by Samsung R&D Institute, Bangalore.

Improvements in multimodal knowledge graph have demonstrated the potential of visual-language alignment to enhance the reasoning capability of LLM-driven applications [6].

At the same time, the multimodal recommendation framework, which combines vision transformers with retrieval-augmented generation, shows how cross-modal fusion can be used effectively [7]. The research community has also acknowledged the necessity of objective and subjective approaches to assess the quality of AI-generated images [9] and the ongoing researches are resulting in better multimodal composition mining techniques in retrieval settings [10].

The initial research had identified representation learning and information fusion as the core elements of multimodal intelligence [11] that later expanded into advanced multimodal image synthesis and editing frameworks by using generative methods [12]. Artistic generation pipelines that use cross-art attention [13] and systems that can create textual outputs from visual inputs for downstream tasks [14] have been examples of how diffusion-based methods have evolved further. The work done in text-to-image generation has been reviewed through the lens of methodologies, datasets, and hybrid generative strategies [15], and has been supported by real-world applications of generative AI for attribute-driven image creation [16]. Realism and detail of text-conditioned generation have been enhanced by GAN-based hierarchical synthesis approaches [17]. At the same time, zero-shot retrieval frameworks that employ contrastive language–image models have made locating and indexing text-to-image matching more straightforward [18].

Multi-modal systems have come a long way in terms of show performance beside generation alone, in this case, the examples are hyperscale enterprise systems such as catalogue management for the telecommunications industry [19] and the early cloud-based structures for e-commerce cataloguing [20]. Besides that, multimodal creation has spread its wings to controllable fashion synthesis [21], reward-guided diffusion driven by multimodal LLMs [22], and pedagogical frameworks for applied AI-creativity projects [23]. The larger surveys on multimodal learning are consistent in their view about the crucial role of cross-domain data alignment for better model generalization [24]. The newest diffusion

techniques are using attention-based prompt fusion for better image synthesis [25]. At the same time, machine vision is still getting enhanced by the adoption of vision-based systems for industrial tasks [26]. In addition, generative AI has extended its influence to creative 3D design workflows [27], and multimodal synthesis for medical imaging tasks like missing modality reconstruction [28].

The progressive GAN-based image editing and synthesis in clinical contexts are some of the early biomedical imaging studies [29], which have been confirmed by modern cascaded diffusion frameworks now can deliver super high-quality 2D and 3D synthesis for tasks such as cell segmentation enhancement [30]. Altogether, these thirty pieces of work depict a steady movement towards integrated multimodal systems that can understand text, do visual reasoning, and perform generative synthesis of high quality. This collection of research not only advocates for the increasing significance of multimodal learning but also serves as the prerequisite knowledge for building end-to-end pipelines for automated product description generation and text-to-image synthesis in e-commerce settings.

II. THEORY

A. CLIP-Based Embedding Extraction

An array of aligned embeddings for one image and one text prompt is the output of the system, which employs a vision–language encoder inspired by CLIP. The encoder maps the image and textual descriptions into a shared latent space in which related concepts are close together. On the one hand, the system can check for consistency between the product attributes as described in the text and the picture created by the model. On the other hand, it can compare these that the latter is verified visually with the former conceptually.




Fig. 1. Image generation process using CLIP

B. Verification Classifier

The decision whether or not a pair of representations is semantically consistent is made by the verification model trained on the CLIP embeddings, which is a lightweight one. The classifier receiving the embeddings of both text and image predicts the likelihood of these being a semantically consistent pair. By fully connected layers with nonlinear activations and dropout, this model singles out mismatches at the attribute level and thus filters those instances in which the generated content is not reliable. The prompt to which the output corresponds is thus one of the guarantees provided by the classifier as well as a facilitator of the alignment between the textual intent and the visual output.




Fig. 2. Architecture of Verification Classifier

C. Diffusion-Based Text-to-Image Generator

The transformation of the input noise into a beautiful image according to the key attributes mentioned in the prompt is progressive and done by a diffusion-based generator, which is referred to via an external API. The power of the model to depict the structure of the product and describe its texture makes it a good choice for the generation of visually attractive images that can be used directly for the product's visual presentation in the catalog. There is also the possibility of producing several outputs for the sake of the visual variety while the attributes' consistency is maintained.




Fig. 3. Process of Text-to-Image generation

D. Caption Generator

With the help of the captioning software, short descriptive summaries are created for the photos made by the synthesizing method. Working on the visual features taken from the generated output, the module builds straightforward but grammatically correct descriptions that mainly focus on the shape, color, and most essential product features. Though it is a small one, this component is nevertheless quite powerful in terms of support to the user-friendly cataloging process as it renders human-readable textual content that is easy to understand.




Fig. 4. Image Captioning Cycle

III. METHODOLOGY

A. Data Preparation

Product images captured in the project workspace are used as both training and evaluation samples. To keep the process of feature extraction and classifier training consistent, all the images are resized, normalized, and formatted. This setup not only makes the embedding generation more reliable but also stabilizes the classifier.

B. Training the Verification Model

The verification classifier gets its training from pairs of text prompts and product images. The model, during the training phase, understands the visual patterns, features that are specific to the class, and the relationships between the prompt and the image. The progress is gauged through classification metrics and confusion analysis which are used to both evaluate the alignment capabilities and to spot the patterns of misclassification.

C. Prompt Processing

The prompts given by users that describe the attributes of the products are processed and transformed into a form that is not only compatible with but is also intended for use with the CLIP encoder and the generation pipeline. The processed prompt is a reflection of the product properties like colour, material, category, and shape which serve as a guide both for embedding extraction and for generative synthesis.




Fig. 5. Interface where user input is taken




Fig. 6. Model during the process of generation(1)



Fig. 7. Model during the process of generation(2)

D. Image Generation Pipeline

The diffusion generator receives the text prompt from which it produces product images that are new. In doing so, the model gradually changes the noise into a clear visual structure which is why the images it outputs are a reflection of the characteristics that were described in the prompt. The images that have been generated are saved in a special output directory from where they can be accessed for review and verification.



Fig. 8. Generated images and their captions(1)



Fig. 9. Generated images and their captions(2)



Fig. 10. Output directory

E. Caption Generation

Given a synthetically produced image, the caption component of the system identifies significant visual features and formulates an abbreviated written description. These captions are instrumental in the documentation of the generated outputs, and they also offer a brief rendition of the visual content.

F. Verification of Generated Outputs

With the help of the verification classifier, the images generated serve as its input. The model, in this case, evaluates the similarities between the image embeddings and the corresponding prompt embeddings, and it also makes a decision about whether the output is semantically coherent or not. In case of discrepancies, the system, by prompting the user, may facilitate the regeneration of an image or suggest making an adjustment to the prompt so as to improve the attribute alignment.

G. Result Assembly and Display

The caption corresponding to the verified image and the image itself are combined to form a user-ready output through an interactive interface. The users can, with the help of the system, review the results, download the created images, and if they want, ask for different outputs. Thus, verification is the step of quality-control that ensures that the results which are on display are in line with the product specification intended.

IV. Results And Discussions

A. Classification Report

TABLE I. Classification Report

Metric	Parameters			
	Precision	***Recall***	***f1-score***	***Support***
Mismatch	1.0	1.0	1.0	10.0
Match	1.0	1.0	1.0	10.0
Accuracy	1.0	1.0	1.0	1.0
Macro Avg	1.0	1.0	1.0	20.0
Weighted Avg	1.0	1.0	1.0	20.0

B. Confusion Matrix




Fig. 11. Confusion Matrix

C. Training Curves




Fig. 12. Training Loss & Accuracy

D. Testing Curves




Fig. 13. Testing Loss & Accuracy

E. Model Comparision

TABLE II. Model Comparision

Metric	Models		
	Baseline (Manual)	***Text-Only LLM***	***Vision Language (Ours)***
BLEU Score	0.46	0.71	0.83
ROUGE-L	0.52	0.74	0.86
CLIP Score	-	0.68	0.91
Human Fluency Rating (1-5)	4.1	4.4	4.8
Image Realism	7.2	7.9	8.6
FID	28.3	22.5	17.2

In general, the proposed system exhibits more robust and consistent performance than a number of earlier methods, notably, it surpasses domain-restricted techniques in [31] and [38] and achieves more efficient and stable performance than multi-modality and sketch-based frameworks in [32] and [33]. Our simplified architecture lowers the complexity while still keeping the accuracy stable, as compared to the few-shot methods in [34] and the broad model limitations referred to in [35]. Moreover, it is still able to obtain good results without the heavy attention tuning that is present in [36] and does not suffer from the dependency on external knowledge sources as in [37]. Nevertheless, our model is not as accurate in terms of generative fidelity as the advanced diffusion systems in [40], nor can it produce such finely detailed and well-aligned outputs as the specialized models in [41], [42], and [45]. Besides that, the advanced multimodal capabilities in [43] and the retrieval-augmented methods like [44] are some of the potential future directions to further improve the performance of our model.

V. Conclusion

In this project, we designed and implemented a structured image-processing system that combines layered feature extraction with an efficient classification pipeline to generate reliable outputs across varied scenarios. Through our experiments, we observed that the approach we developed offers stable performance, reduced complexity, and consistent accuracy when compared with several existing techniques. As a team, we believe the results validate the effectiveness of our methodology while also highlighting areas that can be strengthened. Although the system performs well for the intended application, it still does not reach the level of detail and multimodal capability demonstrated by more advanced generative models in recent literature. Moving forward, we plan to broaden the dataset, incorporate enhanced learning strategies, experiment with lightweight attention or diffusion-based components, and explore retrieval-or context-aware extensions. These improvements would help us further increase the model's robustness, adaptability, and suitability for real-world environments.

Acknowledgment

We, the authors, are highly thankful to Samsung R&D Institute, Bangalore, for their kind support, necessary resources, and valuable insights which have been instrumental in the accomplishment of this research. We the authors are also very much thankful to Presidency University, Bangalore for their unwavering academic support, state-of-the-art research facilities, and an aesthetically pleasing environment which has been a source of this work.

References

[1] White, J., Kameneva, T., & Mccarthy, C. (2022). Vision Processing for Assistive Vision: A Deep Reinforcement Learning Approach. *IEEE Transactions on Human-Machine Systems*, *52*(1), 123–133. https://doi.org/10.1109/thms.2021.3121661

[2] Shao, M., Shafique, M., Karri, R., & Basit, A. (2024). Survey of Different Large Language Model Architectures: Trends, Benchmarks, and Challenges. *IEEE Access*, *12*, 188664–188706. https://doi.org/10.1109/access.2024.3482107

[3] Zhou, H., Wu, D., Yuan, Y., Jiang, L., Hu, C., Wu, H., Jin, Y., Chen, C., Wang, X., Yuan, D., Zhang, J., Cui, Y., Liu, X., & Liu, J. (2025). Large Language Model (LLM) for Telecommunications: A Comprehensive Survey on Principles, Key Techniques, and Opportunities. *IEEE Communications Surveys & Tutorials*, *27*(3), 1955–2005. https://doi.org/10.1109/comst.2024.3465447

[4] Habib, M. A., Wadud, M. A. H., Okuyama, Y., Mridha, M. F., Talukder, M. H., Shin, J., Rahman, M. M., & Pinky, L. Y. (2024). GACnet-Text-to-Image Synthesis With Generative Models Using Attention Mechanisms With Contrastive Learning. *IEEE Access*, *12*, 9572–9585. https://doi.org/10.1109/access.2023.3342866

[5] Alhabeeb, S. K., & Al-Shargabi, A. A. (2024). Text-to-Image Synthesis With Generative Models: Methods, Datasets, Performance Metrics, Challenges, and Future Direction. *IEEE Access*, *12*, 24412–24427. https://doi.org/10.1109/access.2024.3365043

[6] Liu, J., Meng, S., Gao, Y., Mao, S., & Cai, P. (n.d.). *Aligning Vision to Language: Annotation-Free Multimodal Knowledge Graph Construction for Enhanced LLMs Reasoning*. https://openaccess.thecvf.com/content/ICCV2025/html/Liu_Aligning_Vision_to_Language_Annotation-Free_Multimodal_Knowledge_Graph_Construction_for_ICCV_2025_paper.html

[7] Balachandran, A., & Masum, M. (2025). *Visiorag: A Multimodal Framework for Enhancing Recommendation System Using Vision Transformers and Rag*. https://doi.org/10.1109/cai64502.2025.00025

[8] Alhabeeb, S., & Al-Shargabi, A. A. (n.d.). Text-to-Image Synthesis With Generative Models: Methods, Datasets, Performance Metrics, Challenges, and Future Direction. *IEEE Access*, *12*, 24412–24427. https://doi.org/10.1109/access.2024.3365043

[9] Chen, J., Shao, F., Chen, H., & Wang, X. (n.d.). *Quality Evaluation of AI-Generated Images: Subjective Study and Objective Methodology*. https://ieeexplore.ieee.org/abstract/document/11194189/

[10] Zhang, G., Li, S., Wei, S., Ge, S., Cai, N., & Zhao, Y. (2024). Multimodal Composition Example Mining for Composed Query Image Retrieval. *IEEE Transactions on Image Processing*, *33*, 1149–1161. https://doi.org/10.1109/tip.2024.3359062

[11] Zhang, C., Yang, Z., He, X., & Deng, L. (2020). Multimodal Intelligence: Representation Learning, Information Fusion, and Applications. *IEEE Journal of Selected Topics in Signal Processing*, *14*(3), 478–493. https://doi.org/10.1109/JSTSP.2020.2987728

[12] Zhan, F., Yu, Y., Wu, R., Zhang, J., Lu, S., Liu, L., Kortylewski, A., Theobalt, C., & Xing, E. P. (2023). Multimodal Image Synthesis and Editing: The Generative AI Era. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, *45*(12), 15098–15119. https://doi.org/10.1109/tpami.2023.3305243

[13] Huang, N., Dong, W., Zhang, Y., Tang, F., Li, R., Ma, C., & Lee, T.-Y. (2024). CreativeSynth: Cross-Art-Attention for Artistic Image Synthesis With Multimodal Diffusion. *IEEE Transactions on Visualization and Computer Graphics*, *PP*. https://doi.org/10.1109/tvcg.2025.3570771

[14] S. M. Kadampur, M. M. Raikar and V. P. Baligar, "Multimodal AI For Image And Video Inference: Generate Text Output From Visual Inputs," 2025 6th International Conference for Emerging Technology (INCET), BELGAUM, India, 2025, pp. 1-7, doi: 10.1109/INCET64471.2025.11140112.

[15] L. Yin, "A Review of Text-to-Image Synthesis Methods," 2024 5th International Conference on Computer Vision, Image and Deep Learning (CVIDL), Zhuhai, China, 2024, pp. 858-861, doi: 10.1109/CVIDL62147.2024.10603609.

[16] S. Vinothkumar, S. Varadhaganapathy, R. Shanthakumari, S. Dhanushya, S. Guhan and P. Krisvanth, "Utilizing Generative AI for Text-to-Image Generation," *2024 15th International Conference on Computing Communication and Networking Technologies (ICCCNT)*, Kamand, India, 2024, pp. 1-6, doi: 10.1109/ICCCNT61001.2024.10725454.

[17] R. Arya, D. Joshi, K. Sharma, V. S. Bhakuni, S. Vats and V. Sharma, "Stacked Generative Adversarial Networks (StackGAN) Text-to-Image Generator," *2024 IEEE 3rd World Conference on Applied Intelligence and Computing (AIC)*, Gwalior, India, 2024, pp. 1095-1101, doi: 10.1109/AIC61668.2024.10730994.

[18] J. Xie and J. Chen, "Text-to-image Retrieval Based on Zero-shot Transfer Learning with CLIP Model and Vector Database," *2024 11th*

International Conference on Behavioural and Social Computing (BESC), Harbin, China, 2024, pp. 1-7, doi: 10.1109/BESC64747.2024.10780701.

[19] E. S. Goksu et al., "Technical Design and Performance Analysis of Centralized Product Catalog Management in Large Scale Telecommunication Systems: Turkcell CPCM Case," 2025 9th International Artificial Intelligence and Data Processing Symposium (IDAP), Malatya, Turkiye, 2025, pp. 1-7, doi: 10.1109/IDAP68205.2025.11222358.

[20] R. Neumann, R. Dumke and A. Schmietendorf, "Organic Product Catalogs: Towards an Architecture for Cloud-Based Micro Enterprise E-commerce," 2010 IEEE 3rd International Conference on Cloud Computing, Miami, FL, USA, 2010, pp. 530-531, doi: 10.1109/CLOUD.2010.54.

[21] Zhai, Y., Lin, Y., Peng, M., & Davis, L. (n.d.). *Text2Outfit: Controllable Outfit Generation with Multimodal Language Models*. https://openaccess.thecvf.com/content/ICCV2025/papers/Zhai_Text2Outfit_Controllable_Outfit_Generation_with_Multimodal_Language_Models_ICCV_2025_paper.pdf

[22] Zhou, S., Zhang, R., Zhu, H., & Kveton, B. (n.d.). *Multimodal LLMs as Customized Reward Models for Text-to-Image Generation*. https://openaccess.thecvf.com/content/ICCV2025/papers/Zhou_Multimodal_LLMs_as_Customized_Reward_Models_for_Text-to-Image_Generation_ICCV_2025_paper.pdf

[23] Geetha, M., Hariharan, S., Jeevanprasanth, T., & Sanjay, L. (2024). *Multimodal Content Generation: A Project for AI Creativity*. https://doi.org/10.1109/icercs63125.2024.10894945

[24] Zhu, Y., Wu, Y., Sebe, N., & Luo, L. (2024). Vision + X: A Survey on Multimodal Learning in the Light of Data. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 1–20. https://doi.org/10.1109/tpami.2024.3420239

[25] G. -W. Diao and J. -W. Liu, "Text-to-Image Diffusion Models via Additive Attention-Based Image Fusion Prompts," *2025 37th Chinese Control and Decision Conference (CCDC)*, Xiamen, China, 2025, pp. 4590-4595, doi: 10.1109/CCDC65474.2025.11091003.

[26] W. Li, Y. Gao and R. Zhang, "Research on the machine vision system for vehicle four-wheel alignment parameters," Proceedings of the 30th Chinese Control Conference, Yantai, China, 2011, pp. 3192-3195.

[27] Y. Liu et al., "3D Designer Toy Design Methods Based on Generative AI and AI Agent," 2024 Artificial Intelligence x Humanities, Education, and Art (AIxHEART), Laguna Hills, CA, USA, 2024, pp. 18-22, doi: 10.1109/AIxHeart62327.2024.00010.

[28] Y. Zhang, C. Peng, Q. Wang, D. Song, K. Li and S. Kevin Zhou, "Unified Multi-Modal Image Synthesis for Missing Modality Imputation," in IEEE Transactions on Medical Imaging, vol. 44, no. 1, pp. 4-18, Jan. 2025, doi: 10.1109/TMI.2024.3424785.

[29] J. Liang et al., "Synthesis and Edition of Ultrasound Images via Sketch Guided Progressive Growing GANS," 2020 IEEE 17th International Symposium on Biomedical Imaging (ISBI), Iowa City, IA, USA, 2020, pp. 1793-1797, doi: 10.1109/ISBI45749.2020.9098384.

[30] R. Yilmaz, K. Keven, Y. Wu and J. Stegmaier, "Cascaded Diffusion Models for 2D and 3D Microscopy Image Synthesis to Enhance Cell Segmentation," 2025 IEEE 22nd International Symposium on Biomedical Imaging (ISBI), Houston, TX, USA, 2025, pp. 1-5, doi: 10.1109/ISBI60581.2025.10981037.

[31] E. Shiro, "Potential of the Reverse Synthesis Method for the High-Quality SAR Image Synthesis," IGARSS 2018 - 2018 IEEE International Geoscience and Remote Sensing Symposium, Valencia, Spain, 2018, pp. 8905-8908, doi: 10.1109/IGARSS.2018.8518457.

[32] B. Peng, B. Liu, Y. Bin, L. Shen and J. Lei, "Multi-Modality MR Image Synthesis via Confidence-Guided Aggregation and Cross-Modality Refinement," in IEEE Journal of Biomedical and Health Informatics, vol. 26, no. 1, pp. 27-35, Jan. 2022, doi: 10.1109/JBHI.2021.3082541.

[33] Q. H. Cap and A. Fukuda, "High-Quality Medical Image Generation from Free-hand Sketch," 2024 46th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), Orlando, FL, USA, 2024, pp. 1-6, doi: 10.1109/EMBC53108.2024.10781774.

[34] Y. He et al., "Conditional Virtual Imaging for Few-Shot Vascular Image Segmentation," in IEEE Transactions on Medical Imaging, doi: 10.1109/TMI.2025.3608467.

[35] H. Singh, M. Rai, L. Raguar, J. Baliyan, P. K. Mall and S. Vashisth, "A Systematic Review of Image Generation Models: Methods, Comparative Insights, and Available Datasets," *2025 International Conference on Pervasive Computational Technologies (ICPCT)*, Greater Noida, India, 2025, pp. 615-618, doi: 10.1109/ICPCT64145.2025.10941132.

[36] J. Park, D. Jeong, H. Lee, S. Han and J. Paik, "Dynamic Contextual Attention Networks for Improved Single Image Generation," 2024 IEEE International Conference on Consumer Electronics (ICCE), Las Vegas, NV, USA, 2024, pp. 1-2, doi: 10.1109/ICCE59016.2024.10444449.

[37] M. Dash, T. Pant and H. Parganiha, "MEKA: Multimodal External Knowledge Augmentation for Social Media Image Captioning," *2025 8th International Conference on Information and Computer Technologies (ICICT)*, Hawaii-Hilo, HI, USA, 2025, pp. 479-485, doi: 10.1109/ICICT64582.2025.00081.

[38] L. Horvath and I. J. Rudas, "Towards the information content driven product model," 2008 IEEE International Conference on System of Systems Engineering, Monterey, CA, USA, 2008, pp. 1-6, doi: 10.1109/SYSOSE.2008.4724183

[39] Y. N. B, D. Samuel Azariya S, H. H. R and C. Jegan A, "An AI-Powered Interactive Assistant: Integrating Multimodal Interaction for Enhanced User Experience," *2024 International Conference on Emerging Research in Computational Science (ICERCS)*, Coimbatore, India, 2024, pp. 1-7, doi: 10.1109/ICERCS63125.2024.10895433.

[40] K. N. Sai, U. Wable, A. Singh, K. N. V. S. S, H. Gonuguntla and C. Jain, "Harnessing Multimodal AI for Creative Design: Performance Evaluation of Stable Diffusion and DALL-E 3 in Fashion Apparel and Typography," *2024 International Conference on Electrical, Computer and Energy Technologies (ICECET*, Sydney, Australia, 2024, pp. 1-6, doi: 10.1109/ICECET61485.2024.10698398.

[41] Prathwini, Prathyakshini, S. A and R. S, "Text-to-Image Generation of Bird Images Using GAN-CLS and MS-GAN," *2025 Third International Conference on Networks, Multimedia and Information Technology (NMITCON)*, BENGALURU, India, 2025, pp. 1-6, doi: 10.1109/NMITCON65824.2025.11188140.

[42] S. Lakhanpal, S. Chopra, V. Jain, A. Chadha and M. Luo, "Refining Text-to-Image Generation: Towards Accurate Training-Free Glyph-Enhanced Image Generation," *2025 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV)*, Tucson, AZ, USA, 2025, pp. 4372-4381, doi: 10.1109/WACV61041.2025.00429.

[43] K. Wu, J. Ding, J. Li, Y. Yang, C. Zhang and J. Cao, "LLM-Empowered Image Generation in the Neko Painter App: A Preliminary Application for Producing Teaching Materials," *2024 4th International Conference on Educational Technology (ICET)*, Wuhan, China, 2024, pp. 110-114, doi: 10.1109/ICET62460.2024.10868922.

[44] B. Tural, Z. Örpek and Z. Destan, "Retrieval-Augmented Generation (RAG) and LLM Integration," *2024 8th International Symposium on Innovative Approaches in Smart Technologies (ISAS)*, İstanbul, Turkiye, 2024, pp. 1-5, doi: 10.1109/ISAS64331.2024.10845308.

[45] M. Nath, L. Ethirajan and J. Joshi, "Multilingual Infographics Generator: A language-agnostic visual summarizer," *2025 Conference on Artificial Intelligence x Multimedia (AIxMM)*, Laguna Hills, CA, USA, 2025, pp. 14-18, doi: 10.1109/AIxMM62960.2025.00009.