

How-To Join VRSC testnet.

Attention: Read it completely before using.

Important General Information

VRSCTEST data location:

Linux GUI: ~/.komodo/VRSCTEST

Mac OS: /Users//Library/Application Support/Komodo/VRSCTEST

Windows 10: %AppData%\Roaming\Komodo\VRSCTEST\

General remarks on CLI wallet:

On Windows command line enter the commands as shown without the surrounding quotation marks In Linux shell preced the commands without surrounding quotation marks with ./
In MacOS shell preced the commands without surrounding quotation marks with ./
Example: the windows version verus listtransactions transforms in Linux or MacOS to ./verus listtransactions.

General remarks on Windows command line formatting:

The CLI help shows the command format for Linux and MacOS.

For windows substitute the shown '-character with the "-character.

For windows substitute the shown "-character with the \"-characters.

Necessary files:

Link 1: Download latest Wallet

Procedure:

[1

Joining Verus testnet to test the latest capabilities before they are released to mainnet or simply test if your goals are possible without spending VRSC (testnet coins hold no value) is easy.

Download a wallet

The first thing you need is a VRSC wallet. The CLI-wallet and Verus Desktop GUI wallet are available on the link above for Windows,

Linux and MacOS. If you already have a wallet verify that the wallet is the most recent version and update if needed.

Verus Desktop Wallet

1. Start your Verus Desktop wallet.

- 2. If you have never run Verus testnet on your system before:
 - 1. Go to settings (cogwheel icon) and select General Settings.
 - 2. Select Enable VRSCTEST.
 - 3. Click Save Changes
 - 4. Restart Verus desktop
- 3. When logged in, click Add Coin, select Verus Testnet and click Continue.
- 4. Select the startup parameters you desire (Native (Lite mode is not available on testnet), Staking, mining (specify number of threads), reindex blockchain and/or rescan wallet) and click Add Coin.

CLI wallet

1. start CLI walletdaemon using these parameters:

verusd -chain=VRSCTEST

Any extra parameter that you are used to for VRSC (like -mint or -pubkey=) can be appended as well.

2. commands through the CLI are in the following format:

verus -chain=VRSCTEST

The only difference with the normal VRSC chain is the -chain=VRSCTEST option, that is added.

Created by Oink.vrsc@, inspired by 0x03.vrsc@.

Note: revision date 2020-11-11.

© 2020 The Verus Foundation. Website generated with MDwiki © Timo Dörr and contributors.