

Booking.com Demand API

The Booking.com Demand API enables Affiliate Partners to access Booking.com's travel inventory, including accommodations, car rentals, and flights. The version 3.2 introduces several improvements and breaking changes from version 3.1, including updates to **price structures**, inclusion of **Attractions and taxis in orders/details** for post-booking reporting, and other structural enhancements.

- The API follows REST principles and returns data in **JSON** format.
- You can access endpoints via **HTTPS POST** requests.

Authentication: Use your Affiliate ID and token credentials to use these endpoints.

[Check the Try out guide!](/demand/docs/getting-started/try-out-the-api)

Version: 3.2

Servers

[object Object]
...

<https://demandapi.booking.com/3.2>
...

[object Object]
...

<https://demandapi-sandbox.booking.com/3.2>
...

Security

BearerAuth

Type: http
Scheme: bearer
Bearer Format: string

Download OpenAPI description

- [Booking.com Demand API](https://developers.booking.com/_bundle/demand/docs/open-api/3.2/demand-api.yaml)

Accommodation

- [POST /accommodations/search](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/search.md): Use this endpoint to search for

accommodations that match your specified criteria.
By default, **the response returns the cheapest available product** for each accommodation.

When applyi

- [POST

/accommodations/availability](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/availability.md): Use this endpoint to check real-time availability, prices, and charges for **up to 50 accommodation IDs**. - By default, only product availability and prices are returned. - Use the `extras` or `filter`

- [POST

/accommodations/chains](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/chains.md): Use this endpoint to retrieve a list of accommodation chains and their associated brands. A chain-branded accommodation is part of a larger corporate group and operates under a recognised brand. The r

- [POST

/accommodations/constants](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/constants.md): Retrieve standardised codes and names for accommodation-related entities, such as facilities, room types, bed types, themes, and additional charges. These constants are canonical identifiers that can

- [POST

/accommodations/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details.md): Retrieve detailed information about accommodation properties that match your search criteria. You must provide at least one of the following parameters: `accommodations`, `airport`, `city`, `country`,

- [POST

/accommodations/details/changes](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details/changes.md): Use this endpoint to track accommodations that have opened, closed, or had content updates since a specific timestamp. Changes can include updates to general information, facilities, rooms, photos, pa

- [POST

/accommodations/reviews](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews.md): This endpoint provides access to reviews for specified accommodations, allowing you to retrieve traveller feedback associated with a particular property.

The reviews returned can be [filtere

- [POST

/accommodations/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews/scores.md): This endpoint returns score distribution and score breakdown for the specified accommodations. The scores information can be filtered by reviewer parameters and languages.

- [POST

/accommodations/third-party-suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/third-party-suppliers.md): Use this endpoint to retrieve the list of third-party suppliers that facilitate accommodation inventory on Booking.com. A third-party supplier is an external partner company that provides accommodatio

Car rentals

- [POST

/cars/search](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/s

earch.md): Use this endpoint to retrieve the available car rentals matching the search criteria.

- [POST
/cars/constants](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/constants.md): This endpoint returns localised car rental constants used across the Cars API collection, such as extras, fuel policies, payment timings, and transmission types. It also returns customer service cont

- [POST
/cars/depots](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depots.md): Retrieve a paginated list of car rental depots. Supports incremental updates via the `last\_modified` filter.

- [POST
/cars/depots/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depotscores.md): Use this endpoint to retrieve review scores and score breakdowns for depots, including the overall review score and total number of reviews.

- [POST
/cars/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/details.md): Use this endpoint to fetch car details like bag capacity, number of doors, brand and model, etc.

- [POST
/cars/suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/suppliers.md): Use this endpoint to fetch a list of car rental suppliers.
You can use a supplier ID (or an array of them), to retrieve specific details.
Alternatively, if you do not add any ID in the reque

Locations

- [POST
/common/locations/airports](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/airports.md): This endpoint returns a list of airport codes and their names in the selected languages. The airports returned may be filtered by a location id. For example, you can get the list of airports in The Ne

- [POST
/common/locations/cities](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/cities.md): This endpoint returns a list of city IDs and their names in the selected languages. You can filter the results by location ID. For example, to retrieve the list of cities in the Netherlands, pass: `{

- [POST
/common/locations/countries](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/countries.md): This endpoint returns a list of country codes and their names in the selected languages. The countries returned may be filtered by a location id. For example, you can get the list of countries that ar

- [POST
/common/locations/districts](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/districts.md): This endpoint returns a list of districts with translations in the selected languages. The districts returned may be filtered by a location id. For example, you can get the list of districts in Amster

- [POST
/common/locations/landmarks](https://developers.booking.com/demand/docs/open-api/3.2/d

emand-api/commonlocations/common/locations/landmarks.md): This endpoint returns a list of relevant geographical landmark codes and their names in the selected languages. The landmarks returned may be filtered by a location id. For example, you can get the li

- [POST

/common/locations/regions](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/regions.md): This endpoint returns a list of regions with translations in the selected languages. The regions returned may be filtered by a location id. For example, you can get the list of regions in the Netherlands

Payments

- [POST

/common/payments/cards](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/cards.md): This endpoint returns a list of supported payment cards and their names in English. Examples of payment types are the different credit and debit cards.

To get the full list call the endpoint

- [POST

/common/payments/currencies](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/currencies.md): This endpoint returns a list of currency codes and their names in the selected languages. To get the full list call the endpoint passing an empty body.

The currency codes returned are what i

Languages

- [POST

/common/languages](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlanguages/common/languages.md): This endpoint returns a list of human language codes and their names in the corresponding language. To get the full list call the endpoint passing an empty body. The language codes returned are what i

Orders

- [POST

/orders/preview](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/preview.md): Use this endpoint to validate an order before checkout and calculate the final price, including a detailed price breakdown, payment schedule, and cancellation policies for accommodation and car rental

- [POST

/orders/create](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/create.md): Use this endpoint to create and confirm an order using a valid order token and the required payment information.

- [POST

/orders/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details.md): Use this endpoint to retrieve detailed information about existing orders across supported travel services. Use it to synchronise internal systems, monitor booking updates, and generate reporting or an

- [POST

/orders/details/accommodations](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/accommodations.md): Use this endpoint to retrieve detailed information for one or more accommodation orders. You can request order details either by **reservation** or **order** ID depending on your integration. - The res

- [POST
/orders/details/cars](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/cars.md): Use this endpoint to retrieve detailed information for one or more car rental orders. - You can request car order details using your **reservation** ID. - The response includes booking and cancellatio
- [POST
/orders/details/flights](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/flights.md): Use this endpoint to retrieve detailed information for one or more flight orders. - You can request flight order details either by **order ID** or by **reservation ID**. - The response includes struct
- [POST
/orders/modify](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/modify.md): Use this endpoint to modify certain aspects of an accommodation order, such as credit card details, checkin/checkout dates, and room configurations (guest allocation, guest names, and smoking preferen
- [POST
/orders/cancel](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/cancel.md): Use this endpoint to cancel a travel service within an existing order. Provide the details of the reservation or insurance policy you want to cancel. - **Note:** Only one travel service can be cancel

Booking.com Demand API

The Booking.com Demand API enables Affiliate Partners to access Booking.com's travel inventory, including accommodations, car rentals, and flights. The version 3.2 introduces several improvements and breaking changes from version 3.1, including updates to **price structures**, inclusion of **Attractions and taxis in orders/details** for post-booking reporting, and other structural enhancements.

- The API follows REST principles and returns data in **JSON** format.
- You can access endpoints via **HTTPS POST** requests.

Authentication: Use your Affiliate ID and token credentials to use these endpoints.

[Check the Try out guide!](/demand/docs/getting-started/try-out-the-api)

Version: 3.2

Servers

[object Object]
...

https://demandapi.booking.com/3.2
...

[object Object]
...

<https://demandapi-sandbox.booking.com/3.2>

...

Security

BearerAuth

Type: http

Scheme: bearer

Bearer Format: string

Download OpenAPI description

- [Booking.com Demand API](https://developers.booking.com/_bundle/demand/docs/open-api/3.2/demand-api.yaml)

Accommodation

- [POST
/accommodations/search](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/search.md>): Use this endpoint to search for accommodations that match your specified criteria.
By default, **the response returns the cheapest available product** for each accommodation.

When applyi

- [POST
/accommodations/availability](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/availability.md>): Use this endpoint to check real-time availability, prices, and charges for **up to 50 accommodation IDs**. - By default, only product availability and prices are returned. - Use the `extras` or `filter`

- [POST
/accommodations/chains](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/chains.md>): Use this endpoint to retrieve a list of accommodation chains and their associated brands. A chain-branded accommodation is part of a larger corporate group and operates under a recognised brand. The r

- [POST
/accommodations/constants](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/constants.md>): Retrieve standardised codes and names for accommodation-related entities, such as facilities, room types, bed types, themes, and additional charges. These constants are canonical identifiers that can

- [POST
/accommodations/details](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details.md>): Retrieve detailed information about accommodation properties that match your search criteria. You must provide at least one of the following parameters: `accommodations`, `airport`, `city`, `country`,

- [POST
/accommodations/details/changes](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details/changes.md>): Use this endpoint to track accommodations that have opened, closed, or had content updates since a specific timestamp. Changes can include updates to general information, facilities, rooms, photos, pa

- [POST
/accommodations/reviews](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews.md): This endpoint provides access to reviews for specified accommodations, allowing you to retrieve traveller feedback associated with a particular property.</br></br> The reviews returned can be [filtere

- [POST
/accommodations/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews/scores.md): This endpoint returns score distribution and score breakdown for the specified accommodations. The scores information can be filtered by reviewer parameters and languages.

- [POST
/accommodations/third-party-suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/third-party-suppliers.md): Use this endpoint to retrieve the list of third-party suppliers that facilitate accommodation inventory on Booking.com. A third-party supplier is an external partner company that provides accommodatio

Car rentals

- [POST
/cars/search](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/search.md): Use this endpoint to retrieve the available car rentals matching the search criteria.

- [POST
/cars/constants](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/constants.md): This endpoint returns localised car rental constants used across the Cars API collection, such as extras, fuel policies, payment timings, and transmission types. It also returns customer service cont

- [POST
/cars/depots](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depots.md): Retrieve a paginated list of car rental depots. Supports incremental updates via the `last\_modified` filter.

- [POST
/cars/depots/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depotscores.md): Use this endpoint to retrieve review scores and score breakdowns for depots, including the overall review score and total number of reviews.

- [POST
/cars/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/details.md): Use this endpoint to fetch car details like bag capacity, number of doors, brand and model, etc.

- [POST
/cars/suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/suppliers.md): Use this endpoint to fetch a list of car rental suppliers.
You can use a supplier ID (or an array of them), to retrieve specific details.
Alternatively, if you do not add any ID in the reque

Locations

- [POST
/common/locations/airports](https://developers.booking.com/demand/docs/open-api/3.2/dem

and-api/commonlocations/common/locations/airports.md): This endpoint returns a list of airport codes and their names in the selected languages. The airports returned may be filtered by a location id. For example, you can get the list of airports in The Ne

- [POST

/common/locations/cities](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/cities.md): This endpoint returns a list of city IDs and their names in the selected languages. You can filter the results by location ID. For example, to retrieve the list of cities in the Netherlands, pass: `{`"

- [POST

/common/locations/countries](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/countries.md): This endpoint returns a list of country codes and their names in the selected languages. The countries returned may be filtered by a location id. For example, you can get the list of countries that ar

- [POST

/common/locations/districts](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/districts.md): This endpoint returns a list of districts with translations in the selected languages. The districts returned may be filtered by a location id. For example, you can get the list of districts in Amster

- [POST

/common/locations/landmarks](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/landmarks.md): This endpoint returns a list of relevant geographical landmark codes and their names in the selected languages. The landmarks returned may be filtered by a location id. For example, you can get the li

- [POST

/common/locations/regions](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/regions.md): This endpoint returns a list of regions with translations in the selected languages. The regions returned may be filtered by a location id. For example, you can get the list of regions in the Netherla

Payments

- [POST

/common/payments/cards](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/cards.md): This endpoint returns a list of supported payment cards and their names in English. Examples of payment types are the different credit and debit cards.

To get the full list call the endpoint

- [POST

/common/payments/currencies](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/currencies.md): This endpoint returns a list of currency codes and their names in the selected languages. To get the full list call the endpoint passing an empty body.

The currency codes returned are what i

Languages

- [POST

/common/languages](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlanguages/common/languages.md): This endpoint returns a list of human language codes and their names in the corresponding language. To get the full list call the endpoint passing an empty body. The language codes returned are what i

Orders

- [POST
/orders/preview](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/preview.md): Use this endpoint to validate an order before checkout and calculate the final price, including a detailed price breakdown, payment schedule, and cancellation policies for accommodation and car rental
- [POST
/orders/create](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/create.md): Use this endpoint to create and confirm an order using a valid order token and the required payment information.
- [POST
/orders/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details.md): Use this endpoint to retrieve detailed information about existing orders across supported travel services. Use it to synchronise internal systems, monitor booking updates, and generate reporting or an
- [POST
/orders/details/accommodations](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/accommodations.md): Use this endpoint to retrieve detailed information for one or more accommodation orders. You can request order details either by **reservation** or **order** ID depending on your integration. - The res
- [POST
/orders/details/cars](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/cars.md): Use this endpoint to retrieve detailed information for one or more car rental orders. - You can request car order details using your **reservation** ID. - The response includes booking and cancellatio
- [POST
/orders/details/flights](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/flights.md): Use this endpoint to retrieve detailed information for one or more flight orders. - You can request flight order details either by **order ID** or by **reservation ID**. - The response includes struct
- [POST
/orders/modify](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/modify.md): Use this endpoint to modify certain aspects of an accommodation order, such as credit card details, checkin/checkout dates, and room configurations (guest allocation, guest names, and smoking preferen
- [POST
/orders/cancel](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/cancel.md): Use this endpoint to cancel a travel service within an existing order. Provide the details of the reservation or insurance policy you want to cancel. - **Note:** Only one travel service can be cancell

Accommodation

This collection includes endpoints related to **stays** within the connected trip experience.

Use these endpoints to:

- Search for hotels, apartments, and other accommodation types.
- Check real-time availability and pricing.
- Retrieve property details and guest reviews.

- [POST

/accommodations/search](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/search.md): Use this endpoint to search for accommodations that match your specified criteria. By default, the response returns the cheapest available product for each accommodation. When applyi

- [POST

/accommodations/availability](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/availability.md): Use this endpoint to check real-time availability, prices, and charges for up to 50 accommodation IDs. - By default, only product availability and prices are returned. - Use the `extras` or `filter`

- [POST

/accommodations/chains](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/chains.md): Use this endpoint to retrieve a list of accommodation chains and their associated brands. A chain-branded accommodation is part of a larger corporate group and operates under a recognised brand. The r

- [POST

/accommodations/constants](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/constants.md): Retrieve standardised codes and names for accommodation-related entities, such as facilities, room types, bed types, themes, and additional charges. These constants are canonical identifiers that can

- [POST

/accommodations/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details.md): Retrieve detailed information about accommodation properties that match your search criteria. You must provide at least one of the following parameters: `accommodations`, `airport`, `city`, `country`,

- [POST

/accommodations/details/changes](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/details/changes.md): Use this endpoint to track accommodations that have opened, closed, or had content updates since a specific timestamp. Changes can include updates to general information, facilities, rooms, photos, pa

- [POST

/accommodations/reviews](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews.md): This endpoint provides access to reviews for specified accommodations, allowing you to retrieve traveller feedback associated with a particular property. The reviews returned can be filtered

- [POST

/accommodations/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/reviews/scores.md): This endpoint returns score distribution and score breakdown for the specified accommodations. The scores information can be filtered by reviewer parameters and languages.

- [POST
/accommodations/third-party-suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/accommodations/accommodations/third-party-suppliers.md): Use this endpoint to retrieve the list of third-party suppliers that facilitate accommodation inventory on Booking.com. A third-party supplier is an external partner company that provides accommodatio

Search

Use this endpoint to search for accommodations that match your specified criteria.
By default, **the response returns the cheapest available product** for each accommodation.

When applying location filters such as country or region, results are ranked by Booking.com popularity (top picks) rather than price, with higher-ranked listings appearing first.

Endpoint: POST /accommodations/search

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodations` (array)
- `airport` (string)
A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.
Example: AMS
- `booker` (object, required)
The booker's information.
- `booker.country` (string, required)
The booker country for showing the best price for that user and obeying laws regarding the display of taxes and fees.
- `booker.platform` (string, required)
The booker platform for showing the platform based deals and prices.
Enum: "android", "desktop", "ios", "mobile", "tablet"

- `booker.state` (string)

The booker state for showing the best price for that user and obeying laws regarding the display of taxes and fees. Currently applicable only for country US.

- `booker.travel\_purpose` (string)

The travel purpose of the booker.

Enum: "business", "leisure"

- `booker.user\_groups` (array)

The user groups that the booker is a member of.

- `checkin` (string, required)

The checkin date. Must be within 500 days in the future and in the format yyyy-mm-dd.

- `checkout` (string, required)

The checkout date. Must be later than {checkin}. Must be between 1 and 90 days after {checkin}. Must be within 500 days in the future and in the format yyyy-mm-dd.

- `city` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling common/locations/cities.

- `coordinates` (object)

Limit the result list to the specified coordinates.

- `coordinates.latitude` (number)

Specify a latitude (as well as a longitude and radius) to do searches around a specific location.

- `coordinates.longitude` (number)

Specify a longitude (as well as a latitude and radius) to do searches around a specific location.

- `coordinates.radius` (number)

The radius is km to search around the specified latitude and longitude.

- `country` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling common/locations/countries.

Example: nl

- `currency` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling common/payments/currencies.

Example: EUR

- ``district`` (integer)

A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.

- ``extras`` (array)

Input parameter to request for additional information about the products.

- ``filters`` (object)

Filter criteria for the search results

- ``filters.24_hour_reception`` (boolean)

Filter the result based if the front desk reception is available 24/7. When specified true, the result will filter the products where front desk is available 24/7.

- ``filters.accommodation_facilities`` (array)

- ``filters.accommodation_types`` (array)

- ``filters.brands`` (array)

- ``filters.cancellation_type`` (string)

Filters the results by cancellation type. Currently, only 'free_cancellation' is supported. This will return all products that can be cancelled without incurring any fees within a specified time frame. ****△ DEPRECATED:**** The 'non_refundable' cancellation type filter is deprecated and will be removed in further versions.

Enum: "free_cancellation", "non_refundable"

- ``filters.dormitories`` (string)

This parameter specifies if the results should include dormitory beds or rooms. The default behaviour will include the dormitory beds or rooms with other results. When this flag is set to 'only', the response will only include dormitory beds or rooms. When this flag is set to 'exclude', the response will exclude dormitory beds or rooms. When this flag is set to 'include', the response will include dormitory beds or rooms with other results.

Enum: "include", "exclude", "only"

- ``filters.meal_plan`` (string)

Filter the result based on the selected meal plan. Example: When specified `breakfast_included`, it will show the product with free breakfast.

Enum: "all_inclusive", "breakfast_included", "full_board", "half_board"

- ``filters.payment`` (object)

The payment filter for the request

- ``filters.payment.credit_card_required`` (boolean)

Filter to show accommodations which require credit card

- ``filters.payment.timing`` (string)

This parameter specifies that the results should only return accommodation and blocks that contain the specified payment timings.

Enum: "pay_at_the_property", "pay_online"

- `filters.price` (object)

If specified, will return only results where the price *per night* falls in the specified range (inclusive). This filter requires that a currency is passed

- `filters.price.maximum` (number)

Set the maximum price per night, in the specified currency, or omit to indicate no upper limit.

- `filters.price.minimum` (number)

Set the minimum price per night, in the specified currency, or omit to indicate no lower limit.

- `filters.rating` (object)

The rating filter for the request

- `filters.rating.minimum\_review\_score` (integer)

Show only hotels with review_score >= that. Review score should be in the range 1 to 10.

- `filters.rating.stars` (array)

Limit to accommodations with the given number(s) of stars. Stars should be in the range of 1 to 5.

- `filters.room\_facilities` (array)

- `filters.sustainability\_certification` (boolean)

Filter the result based on if the property has sustainability certification. When specified true, the result will filter and return only the accommodations that have sustainability certification.

- `filters.travel\_proud` (boolean)

Filter the result based on if the property is LGBTQ+ friendly. When specified true, the result will filter and return only the accommodations that are Proud Certified.

- `guests` (object, required)

The guest details for the request.

- `guests.allocation` (array)

The exact allocation of guests to rooms.

- `guests.allocation.children` (array)

The children ages for this room.

- `guests.allocation.number\_of\_adults` (integer, required)

The number of adults for this room.

- ``guests.children`` (array)
Array with the children ages.

- ``guests.number_of_adults`` (integer, required)
The number of adults for the search.

- ``guests.number_of_rooms`` (integer, required)
The number of rooms needed.

- ``landmark`` (integer)
A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- ``page`` (string)
Pagination token used to retrieve the next page of results. Obtained from ``next_page``.

- ``region`` (integer)
A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- ``rows`` (integer)
The maximum number of results to return.

- ``sort`` (object)
The sorting parameters for the response

- ``sort.by`` (string)
The way to sort your results. NOTE: When ordering by distance please make sure to specify the latitude and longitude!
Enum: "distance", "price", "review_score", "stars"

- ``sort.direction`` (string)
Specifies the sort direction. Please note that descending order is not supported when sorting by distance.
Enum: "ascending", "descending"

Response 200 fields (application/json):

- ``request_id`` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.

- ``data`` (array)

- `data.id` (integer)

A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling `[accommodations/details](/demand/docs/open-api/demand-api/accommodations/accommodations/details)`.

- `data.commission` (object)

Commission details for the partner for a given accommodation

- `data.commission.amount` (number)

The actual commission amount for the partner.

- `data.commission.percentage` (number)

Percentage of the fee that will be received as commission.

- `data.currency` (object)

- `data.currency.accommodation` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.

Example: EUR

- `data.deep\_link\_url` (string)

A mobile app URL that directs the user to a specific page or content within the Booking.com app. The link can only be used on a device with the Booking.com app installed. It typically includes an Affiliate ID (AID) to attribute bookings to the affiliate partner when users are redirected

- `data.price` (object)

The price components of all the products selected summed.

- `data.price.base` (object)

- `data.price.base.accommodation\_currency` (number)

- `data.price.charges` (array)

The sum of charges for all products selected, grouped by charge type.

- `data.price.charges.charge` (integer)

A signed integer number that uniquely identifies an accommodation charge type. Examples of charges are: VAT, City Tax, etc. The full list can be obtained by calling `accommodations/constants`.

- `data.price.charges.condition` (integer | null)

A signed integer number that uniquely identifies the condition ID. Find the full list in the Pricing guidelines.

- `data.price.charges.included\_in` (object)

Indicates where this charge is included

- ``data.price.charges.included_in.display`` (boolean)
Indicates if this charge is included in the display price.
- ``data.price.charges.total_amount`` (object)
The total price for this charge.
- ``data.products`` (array)
- ``data.products.id`` (string)
Unique ID of the product.
- ``data.products.bundle`` (integer)
The bundle ID of the product comprising of value added products.
- ``data.products.children`` (array)
The ages of the children allocated to this product.
- ``data.products.deal`` (object | null)
This specifies the deal tagging for the product.
- ``data.products.deal.discount_percentage`` (integer)
Discount percentage of the applied deal.
- ``data.products.deal.tags`` (array)
The tags of all the applied deals.
- ``data.products.inventory`` (object)
- ``data.products.inventory.third_party`` (boolean)
Indicates whether the product is facilitated by a third-party supplier.
- ``data.products.inventory.type`` (string)
Type of inventory - either net or sell rates.
Enum: "net", "sell"
- ``data.products.number_available`` (integer)
Number of rooms available at this price.
- ``data.products.number_of_adults`` (integer)
The number of adults allocated to this product.
- ``data.products.policies`` (object)
The policies for this product.
- ``data.products.policies.cancellation`` (object)
The cancellation policy for this product.

- `data.products.policies.cancellation.free\_cancellation\_until` (string | null)

Until when the order for this product can be cancelled for free.

- `data.products.policies.cancellation.type` (string)

The cancellation policy applicable to this product: "free_cancellation" allows a period for free cancellation, "non_refundable" means immediate loss of total amount, "partially_refundable" means a portion of the amount may be refunded if the booking is cancelled.

Enum: "free_cancellation", "non_refundable", "partially_refundable"

- `data.products.policies.meal\_plan` (object)

The meal plan policy for this product.

- `data.products.policies.meal\_plan.meals` (array)

The meals included in the meal plan.

- `data.products.policies.meal\_plan.plan` (string)

The meal plan included in this product.

Enum: "all_inclusive", "breakfast_included", "full_board", "half_board", "no_plan"

- `data.products.policies.payment` (object)

Payment terms and conditions for this product.

- `data.products.policies.payment.prepayment\_required` (boolean)

Whether prepayment is required for this product.

- `data.products.policies.payment.timings` (array)

The payment timings supported by this product.

- `data.products.price` (object)

Contains the price components of an accommodation product. The 'base', 'display', 'chargeable_online' prices, and 'charges' are returned only when explicitly requested using extras=extra_charges.

- `data.products.price.base` (object)

The base price. It does not include any extra charges.

- `data.products.price.charges` (array)

The charge breakdown. Includes taxes and fees.

- `data.products.price.charges.included\_in` (object)

Indicates where this charge is included

- `data.products.price.charges.mode` (string)

The mode of this charge. Determines how the price is calculated.

Enum: "calculated_amount", "incalculable", "percentage", "per_day", "per_night", "per_person_per_day", "per_person_per_night", "per_person_per_stay", "per_stay"

- ``data.products.price.charges.percentage`` (number)

The percentage of 'base' that this charge amounts to. Only applicable when 'mode' is 'percentage'.

- ``data.products.price.charges.unit_amount`` (object)

The price per unit for this charge. Only applicable when 'mode' is 'per_day', 'per_night', 'per_person_per_day', 'per_person_per_night', or 'per_person_per_stay'.

- ``data.products.price.display`` (object)

The display price that must be shown to the traveller in accordance with local booker protection laws. This price includes the base accommodation cost and all charges that are legally required to be part of the displayed amount. Equivalent to base + charges where `included_in.display=true`.

- ``data.products.price.total`` (object)

The total price. Includes all extra charges.

- ``data.products.room`` (string)

A unique identifier for a specific room within an accommodation property. You can retrieve the full list of available room IDs by calling `[accommodations/details](/demand/docs/open-api/demand-api/accommodations/accommodations/details)`.

- ``data.url`` (string)

Internet address for the property page on Booking.com.

- ``metadata`` (object)

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Availability

Use this endpoint to check real-time availability, prices, and charges for **up to 50 accommodation IDs**.

- By default, only product availability and prices are returned.
- Use the `extras` or `filters` parameters to retrieve additional details such as extra charges or payment information.

Mandatory fields: `accommodations`, `booker`, `checkin`, `checkout`, and `guests`.

Endpoint: POST /accommodations/availability

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodations` (array, required)
- `booker` (object, required)
The booker's information.
- `booker.country` (string, required)
The booker country for showing the best price for that user and obeying laws regarding the display of taxes and fees.
- `booker.platform` (string, required)
The booker platform for showing the platform based deals and prices.
Enum: "android", "desktop", "ios", "mobile", "tablet"
- `booker.state` (string)
The booker state for showing the best price for that user and obeying laws regarding the display of taxes and fees. Currently applicable only for country US.
- `booker.travel\_purpose` (string)
The travel purpose of the booker.
Enum: "business", "leisure"
- `booker.user\_groups` (array)
The user groups that the booker is a member of.
- `checkin` (string, required)
The checkin date. Must be within 500 days in the future and in the format yyyy-mm-dd.

- `checkout` (string, required)

The checkout date. Must be later than {checkin}. Must be between 1 and 90 days after {checkin}. Must be within 500 days in the future and in the format yyyy-mm-dd.

- `currency` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling common/payments/currencies.

Example: EUR

- `extras` (array)

Input parameter to request for additional information about this product.

- `filters` (object)

The filters to apply in this availability request.

- `filters.cancellation\_type` (string)

Filters the result for the cancellation type specified. Possible values are free_cancellation. The result will contain all the products with free_cancellation.

Enum: "free_cancellation"

- `filters.meal\_plan` (string)

Filter the result based on the selected meal plan. Example: When specified breakfast_included, it will show the product with free breakfast.

Enum: "all_inclusive", "breakfast_included", "full_board", "half_board"

- `filters.payment` (object)

Payment input information to filter results.

- `filters.payment.timing` (string)

This parameter specifies that the results should only return accommodation and blocks that contain the specified payment timings.

Enum: "pay_at_the_property", "pay_online"

- `guests` (object, required)

The guest details for the request.

- `guests.allocation` (array)

The exact allocation of guests to rooms.

- `guests.allocation.children` (array)

The children ages for this room.

- `guests.allocation.number\_of\_adults` (integer, required)

The number of adults for this room.

- `guests.children` (array)

Array with the children ages.

- `guests.number\_of\_adults` (integer, required)

The number of adults for the search.

- `guests.number\_of\_rooms` (integer, required)

The number of rooms needed.

Response 200 fields (application/json):

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (integer)

A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling [\[accommodations/details\]\[//demand/docs/open-api/demand-api/accommodations/accommodations/details\]](#).

- `data.currency` (object)

- `data.currency.accommodation` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling [common/payments/currencies](#).

Example: EUR

- `data.deep\_link\_url` (string)

A mobile app URL that directs the user to a specific page or content within the Booking.com app. The link can only be used on a device with the Booking.com app installed. It typically includes an Affiliate ID (AID) to attribute bookings to the affiliate partner when users are redirected

- `data.products` (array)

- `data.products.id` (string)

Unique ID of the product.

- `data.products.bundle` (integer)

The bundle ID of the product comprising of value added products.

- `data.products.deal` (object | null)

This specifies the deal tagging for the product.

- `data.products.deal.discount\_percentage` (integer)

Discount percentage of the applied deal.

- `data.products.deal.public\_price` (object)

- ``data.products.deal.public_price.accommodation_currency`` (number)
- ``data.products.deal.tags`` (array)
The tags of all the applied deals.
- ``data.products.inventory`` (object)
Inventory details for an accommodation product returned by ``/accommodations/availability``.
- ``data.products.inventory.third_party`` (boolean)
Indicates whether the product is facilitated by a third-party supplier.
- ``data.products.inventory.third_party_supplier_id`` (integer)
Unique identifier of a third-party accommodation supplier. Use the `[/accommodations/third-party-suppliers](#/accommodations/third-party-suppliers)` endpoint to retrieve the full list of suppliers and their details.
- ``data.products.inventory.type`` (string)
Type of inventory - either net or sell rates.
Enum: "net", "sell"
- ``data.products.maximum_occupancy`` (object)
Information related to maximum number of occupancy inside the room.
- ``data.products.maximum_occupancy.adults`` (integer)
The maximum number of adults for this room.
- ``data.products.maximum_occupancy.children`` (array)
The information about maximum number of children and their allowed ages for this room.
- ``data.products.maximum_occupancy.children.total`` (integer)
The maximum number of children for this room.
- ``data.products.maximum_occupancy.children.from_age`` (integer)
The youngest age of the children allowed in this room.
- ``data.products.maximum_occupancy.children.to_age`` (integer)
The oldest age of the children allowed in this room.
- ``data.products.maximum_occupancy.children.free_stay`` (boolean)
Whether children in this age bracket will be staying for free. False indicates their cost was already included in the price.
- ``data.products.maximum_occupancy.total`` (integer)
The maximum number of guests for this room.
- ``data.products.number_available`` (integer)
How many units of this product are still available.

- ``data.products.policies`` (object)
The policies for this product.
- ``data.products.policies.cancellation`` (object)
The cancellation policy for this product.
- ``data.products.policies.cancellation.free_cancellation_until`` (string | null)
Until when the order for this product can be cancelled for free.
- ``data.products.policies.cancellation.schedule`` (array)
The cancellation policy schedule for this product.
- ``data.products.policies.cancellation.schedule.from`` (any)
The time from which this cancellation fee applies.
- ``data.products.policies.cancellation.schedule.price`` (object)
The price in both accommodation and booker currencies (booker might be null, if not requested)
- ``data.products.policies.cancellation.type`` (string)
The cancellation policy applicable to this product: "free_cancellation" allows a period for free cancellation, "non_refundable" means immediate loss of total amount, "special_conditions" means partly refundable.
Enum: "free_cancellation", "non_refundable", "special_conditions"
- ``data.products.policies.meal_plan`` (object)
The meal plan policy for this product.
- ``data.products.policies.meal_plan.meals`` (array)
The meals included in the meal plan.
- ``data.products.policies.meal_plan.plan`` (string)
The meal plan included in this product.
Enum: "all_inclusive", "breakfast_included", "full_board", "half_board", "no_plan"
- ``data.products.policies.payment`` (object)
Payment terms and conditions for this product.
- ``data.products.policies.payment.prepayment_required`` (boolean)
Whether prepayment is required for this product.
- ``data.products.policies.payment.timings`` (array)
The payment timings supported by this product.
- ``data.products.price`` (object)

Contains the price components of an accommodation product. The 'base', 'display', 'chargeable_online' prices, and 'charges' are returned only when explicitly requested using `extras=extra_charges`.

- ``data.products.price.base`` (object)

The base price. It does not include any extra charges.

- ``data.products.price.charges`` (array)

The charge breakdown. Includes taxes and fees.

- ``data.products.price.charges.charge`` (integer)

A signed integer number that uniquely identifies an accommodation charge type. Examples of charges are: VAT, City Tax, etc. The full list can be obtained by calling `accommodations/constants`.

- ``data.products.price.charges.condition`` (integer | null)

A signed integer number that uniquely identifies the condition ID. Find the full list in the Pricing guidelines.

- ``data.products.price.charges.included_in`` (object)

Indicates where this charge is included

- ``data.products.price.charges.included_in.chargeable_online`` (boolean)

Whether this charge is chargeable online or not. Not applicable to "pay_at_the_property" timing.

- ``data.products.price.charges.included_in.display`` (boolean)

Indicates if this charge is included in the display price.

- ``data.products.price.charges.mode`` (string)

The mode of this charge. Determines how the price is calculated.

Enum: "calculated_amount", "incalculable", "percentage", "per_day", "per_night", "per_person_per_day", "per_person_per_night", "per_person_per_stay", "per_stay"

- ``data.products.price.charges.percentage`` (number)

The percentage of 'base' that this charge amounts to. Only applicable when 'mode' is 'percentage'.

- ``data.products.price.charges.total_amount`` (object)

The total price for this charge.

- ``data.products.price.charges.unit_amount`` (object)

The price per unit for this charge. Only applicable when 'mode' is 'per_day', 'per_night', 'per_person_per_day', 'per_person_per_night', or 'per_person_per_stay'.

- ``data.products.price.chargeable_online`` (object)

The amount collected by Booking.com from the Virtual Credit Cards (VCCs) when using online payment methods (e.g., `pay_online_now`, `pay_online_later`). Equivalent to ``base`` +

charges` where `included_in.chargeable_online=true`. Returns `null` for agency-model properties where Booking.com does not process payments.

- `data.products.price.display` (object)

The display price that must be shown to the traveller in accordance with local booker protection laws. This price includes the base accommodation cost and all charges that are legally required to be part of the displayed amount. Equivalent to base + charges where included_in.display=true.

- `data.products.price.total` (object)

The total price. Includes all extra charges.

- `data.products.room` (string)

A unique identifier for a specific room within an accommodation property. You can retrieve the full list of available room IDs by calling [\[accommodations/details\]/\(demand/docs/open-api/demand-api/accommodations/accommodations/details\)](#).

- `data.recommendation` (object)

The products recommended for the provided search criteria.

- `data.recommendation.price` (object)

Contains the price components of the recommended accommodation product or selection of products. The 'base', 'display', 'chargeable_online' prices, and 'charges' are returned only when explicitly requested using extras=extra_charges.

- `data.recommendation.price.charges` (array)

The charge breakdown. Includes taxes and fees.

- `data.recommendation.price.charges.included\_in` (object)

Indicates where this charge is included

- `data.recommendation.products` (array)

- `data.recommendation.products.children` (array)

The ages of the children allocated to this product.

- `data.recommendation.products.number\_of\_adults` (integer)

The number of adults allocated to this product.

- `data.url` (string)

Internet address for the property page on Booking.com.

Chains

Use this endpoint to retrieve a list of accommodation chains and their associated brands. A chain-branded accommodation is part of a larger corporate group and operates under a recognised brand. The returned information can be used to filter search results by chain or brand across other endpoints.

- To obtain the full list of chains, call this endpoint with an empty request body.
- The `id` values returned are the codes used as input and output in other API requests, ensuring consistency across your integration.

****Example of chain:**** "Radisson Hotel Group" with brands such as "Radisson Blu" or "Park Inn by Radisson."

Endpoint: POST /accommodations/chains

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (integer)

A signed integer number that uniquely identifies an accommodation chain. Examples of chains are: Radisson Hotel Group, Hilton Worldwide etc. The full list can be obtained by calling /accommodations/chains.

- `data.brands` (array)

List of all the brands associated with this accommodation chain.

- `data.brands.id` (integer)

A signed integer number that uniquely identifies an accommodation brand. Examples of brands are: Radisson Blu, WestCord Hotels, Westin etc. The full list can be obtained by calling /accommodations/chains.

- `data.brands.name` (string)

Name of the accommodation brand.

- `data.name` (string)

Name of the accommodation chain.

Constants

Retrieve standardised codes and names for accommodation-related entities, such as facilities, room types, bed types, themes, and additional charges.

These constants are canonical identifiers that can be used to filter searches, populate reference data, or ensure consistency across other accommodation endpoints.

- To fetch constants in multiple languages, provide IETF language tags (see `common/languages`).

- Sending an empty request body returns all available constants.

- Use the ``constants`` array to request only specific sections (e.g., ``accommodation_facilities``, ``bed_types``).

Endpoint: POST `/accommodations/constants`

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``constants`` (array)
Allows to filter the results only for specific sections.
- ``languages`` (array)

Response 200 fields (application/json):

- ``request_id`` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``data`` (object)
 - ``data.accommodation_facilities`` (array)
 - ``data.accommodation_facilities.id`` (integer, required)
A signed integer number that uniquely identifies an accommodation property facility. Examples of facilities are: Parking, Restaurant, Room service etc. The full list can be obtained by calling `accommodations/constants`.
 - ``data.accommodation_facilities.facility_type`` (integer, required)
A signed integer number that uniquely identifies the accommodation facility type. The full list can be obtained by calling `accommodations/constants`.
 - ``data.accommodation_facilities.name`` (object, required)
A string localised in multiple languages.

- `data.accommodation\_themes` (array)

- `data.accommodation\_themes.id` (integer, required)

A signed integer number that uniquely identifies an accommodation property theme. Examples of themes are: Beach/Seaside, Ski/Wintersports, Luxury etc. The full list can be obtained by calling accommodations/constants.

- `data.accommodation\_types` (array)

- `data.accommodation\_types.id` (integer, required)

A signed integer number that uniquely identifies an accommodation property type. Examples of accommodation types are: Apartment, Hostel, Hotel etc. The full list can be obtained by calling accommodations/constants.

- `data.bed\_types` (array)

- `data.bed\_types.id` (integer, required)

A signed integer number that uniquely identifies a bed type. Examples of bed types are: Single, Double etc. The full list can be obtained by calling accommodations/constants.

- `data.charge\_types` (array)

- `data.charge\_types.id` (integer, required)

A signed integer number that uniquely identifies an accommodation charge type. Examples of charges are: VAT, City Tax, etc. The full list can be obtained by calling accommodations/constants.

- `data.facility\_types` (array)

- `data.review\_scores` (array)

- `data.review\_scores.minimum\_score` (number, required)

The minimum score of this review score category.

- `data.review\_scores.maximum\_score` (number, required)

The maximum score of this review score category

- `data.room\_facilities` (array)

- `data.room\_facilities.id` (integer, required)

A signed integer number that uniquely identifies an accommodation property room facility. Examples of facilities are: Coffee/Tea maker, TV, Airconditioning, etc. The full list can be obtained by calling accommodations/constants.

- `data.room\_types` (array)

- `data.room\_types.id` (integer, required)

A signed integer number that uniquely identifies an accommodation property room type. Example of room types are: Suite, Apartment, Twin/Double etc. The full list can be obtained by calling accommodations/constants.

Details

Retrieve detailed information about accommodation properties that match your search criteria.

You must provide at least one of the following parameters: `accommodations`, `airport`, `city`, `country`, or `region`.

Use the `extras` parameter to request additional information such as `facilities`, `photos`, `policies`, `rooms`, or `bundles`.

Key points:

- You can request data in multiple languages using IETF language tags.
- This endpoint provides static information about properties; availability and pricing are retrieved via other endpoints.
- Passing an empty `extras` array returns only the core property details.
- Maximum 100 accommodation IDs can be queried in a single request.

Endpoint: POST /accommodations/details

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodation\_facilities` (array)
- `accommodation\_types` (array)
- `accommodations` (array)

- `airport` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- `brands` (array)

- `city` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- `country` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: `nl`

- ``extras`` (array)

Input parameter to request for additional information about the accommodation property. It should be passed as a JSON array with one or more items.

- ``languages`` (array)

- ``page`` (string)

Pagination token used to retrieve the next page of results. Obtained from ``next_page``.

- ``payment`` (object)

Payment input information to filter results.

- ``payment.timing`` (string)

This parameter specifies that the results should only return accommodation and blocks that contain the specified payment timings.

Enum: `"pay_at_the_property"`, `"pay_online"`

- ``region`` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- ``rows`` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- ``request_id`` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``data`` (array)

- ``data.id`` (integer)

A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling `[accommodations/details](/demand/docs/open-api/demand-api/accommodations/accommodations/details)`.

- ``data.accommodation_status`` (string)

Operational status of the accommodation. Note that closed accommodations are only included in the response when querying by accommodation ID (``accommodations``);

requests by location (`airport`, `city`, `country`, or `region`) exclude closed accommodations, so those responses only contain accommodations with status `open`.

- `open`: The accommodation is open and bookable.
- `closed\_fraud`: The accommodation is closed due to fraud or related trust and safety concerns. Only returned when fraud visibility is enabled for your account; otherwise such accommodations are reported as `closed\_permanently`.
- `closed\_temporarily`: The accommodation is temporarily closed.
- `closed\_permanently`: The accommodation is permanently closed.
Enum: "open", "closed_fraud", "closed_temporarily", "closed_permanently"

- `data.accommodation\_type` (integer)

A signed integer number that uniquely identifies an accommodation property type. Examples of accommodation types are: Apartment, Hostel, Hotel etc. The full list can be obtained by calling accommodations/constants.

- `data.booker\_address\_required` (boolean)

A boolean indicating whether a booker address is required for the property. If true, a booker address must be provided in the orders/create endpoint. If false, the booker address is not required and can be omitted from the orders/create endpoint.

- `data.brands` (array)

- `data.bundles` (array)

List of value-added bundles available for this accommodation. Each bundle groups one or more value-added benefits and includes localised descriptive text for display.

- `data.bundles.id` (integer)

Bundle identifier

- `data.bundles.value\_adds` (array)

- `data.bundles.value\_adds.type` (string)

Identifies the type of value-added benefit included in the bundle, such as complimentary services, monetary credits, percentage discounts, or experiential amenities. Enum values encode how the benefit is applied, including time scope (per day or per stay) and unit scope (per room or per adult).

Enum: "parking", "food_drink_credit_per_day_per_room",
"food_drink_credit_per_day_per_adult", "property_credit_per_day_per_room",
"food_drink_credit_per_stay_per_adult", "food_drink_credit_per_stay_per_room",
"property_credit_per_day_per_adult", "property_credit_per_stay_per_adult",
"property_credit_per_stay_per_room", "food_drink_discount", "property_discount",
"early_checkin", "late_checkout", "late_checkin", "spa_daily", "spa_hourly", "spa_massage",
"high_speed_internet", "airport_transfer", "safari_game_drive", "safari_walk", "pets_stay",
"bottle_of_wine", "bottle_of_champagne", "park_sleep_fly"

- `data.bundles.value\_adds.description` (object)

List of descriptive text lines for the value-added service, localised in multiple languages.

- `data.checkin\_checkout\_times` (object)
- `data.checkin\_checkout\_times.checkin\_from` (string | null)
The time from when checkin starts at this property.
- `data.checkin\_checkout\_times.checkin\_to` (string | null)
The time till when checkin can be done at this property.
- `data.checkin\_checkout\_times.checkout\_from` (string | null)
The time from when checkout starts at this property.
- `data.checkin\_checkout\_times.checkout\_to` (string | null)
The time till when checkout can be done at this property.
- `data.contacts` (object)
Contact information of the accommodation.
- `data.contacts.general` (object)
Contact information of the accommodation. It can be `null` if the data is missing.
- `data.contacts.general.email` (string)
Email address of the accommodation. It can be `null` if the data is missing.
- `data.contacts.general.telephone` (string)
Telephone number of the accommodation. It can be `null` if the data is missing.
- `data.currency` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
- `data.description` (object)
Textual information about the accommodation. Requires `{"extras":["description"]}`.
- `data.description.host\_type` (string)
Type of host.
Enum: "private", "professional", "unknown"
- `data.description.important\_information` (object)
A string localised in multiple languages.
- `data.description.license\_numbers` (array)
List of all the license numbers of this accommodation property.
- `data.description.trader` (object)
The trader information.
- `data.description.trader.address` (object)

An address object.

- ``data.description.trader.address.address_line`` (string)
- ``data.description.trader.address.city`` (string)
- ``data.description.trader.address.country`` (string)
- ``data.description.trader.address.post_code`` (string)
- ``data.description.trader.email`` (string)
The email of the trader
- ``data.description.trader.name`` (string)
The name of the trader
- ``data.description.trader.registration_number`` (string)
The registration number of the trader
- ``data.description.trader.telephone`` (string)
The telephone of the trader
- ``data.description.trader.trade_register`` (string)
The trade register name
- ``data.description.trader.trader_verified`` (boolean)
Indicates whether the trader has successfully met Booking.com's internal verification process, based on established criteria and checklists
- ``data.facilities`` (array)
The list of facilities available in this property. Requires ``{"extras":["facilities"]}``.
- ``data.facilities.id`` (integer)
A signed integer number that uniquely identifies an accommodation property facility. Examples of facilities are: Parking, Restaurant, Room service etc. The full list can be obtained by calling `accommodations/constants`.
- ``data.facilities.attributes`` (array)
- ``data.facility_details`` (object)
Comprehensive information about the facilities available at the accommodation.
- ``data.facility_details.internet_facility`` (object)
Information about the internet facilities available at the accommodation.
- ``data.facility_details.internet_facility.charge_mode`` (string)
The charging model for internet access at the accommodation.

Enum: "charges_are_applicable", "free", "per_day", "per_half_hour", "per_hour", "per_minute"

- `data.facility\_details.internet\_facility.connection\_type` (string)

The type of internet connection available, whether wireless (Wi-Fi) or wired.

Enum: "wifi", "wired"

- `data.facility\_details.internet\_facility.coverage` (string)

The extent of the internet coverage within the accommodation, indicating the areas where internet access is available.

Enum: "all_rooms", "business_center", "entire_property", "public_areas", "some_rooms"

- `data.facility\_details.internet\_facility.price` (number)

- `data.facility\_details.parking\_facilities` (array)

A list of parking facilities available at the accommodation.

- `data.facility\_details.parking\_facilities.charge\_mode` (string)

The charging model for parking, such as per hour, per day, or free.

Enum: "free", "charges_are_applicable", "charges_may_apply", "per_hour", "per_day", "per_week", "per_stay"

- `data.facility\_details.parking\_facilities.location` (string)

The location of the parking facility relative to the accommodation (on-site or nearby).

Enum: "on_site", "nearby"

- `data.facility\_details.parking\_facilities.reservation` (string)

Indicates whether a reservation is required for parking at the accommodation.

Enum: "needed", "not_needed", "not_possible"

- `data.facility\_details.parking\_facilities.type` (string)

The type of parking available, either public or private.

Enum: "private", "public"

- `data.facility\_details.restaurant\_facilities` (array)

A list of restaurant facilities available at the accommodation.

- `data.facility\_details.restaurant\_facilities.accept\_reservations` (boolean)

Indicates whether the restaurant accepts reservations.

- `data.facility\_details.restaurant\_facilities.guests\_only` (boolean)

Indicates whether the restaurant is exclusive to guests or open to the public.

- `data.facility\_details.restaurant\_facilities.name` (string)

The name of the restaurant.

- `data.facility\_details.restaurant\_facilities.status` (string)

The operational status of the restaurant (e.g., open or closed).

Enum: "closed", "open"

- `data.facility\_details.swimming\_pool\_facilities` (array)

A list of swimming pool facilities available at the accommodation.

- `data.facility\_details.swimming\_pool\_facilities.allowed\_age\_type` (string)

The age group allowed to use the swimming pool (e.g., adults only, all ages, or kids only).

Enum: "adults_only", "all_ages", "kids_only"

- `data.facility\_details.swimming\_pool\_facilities.payment\_type` (string)

The payment model for pool access, either free or paid.

Enum: "free", "paid"

- `data.facility\_details.swimming\_pool\_facilities.type` (string)

The type of swimming pool (indoor, outdoor, or a combination).

Enum: "indoor", "indoor_and_outdoor", "outdoor"

- `data.fiscal\_information` (object)

All fiscal related information of this accommodation property.

- `data.fiscal\_information.legal\_name` (string)

- `data.fiscal\_information.vat\_number` (string)

- `data.is\_genius` (boolean)

Whether the accommodation participates in the Genius programme.

- `data.key\_collection\_information` (object)

- `data.key\_collection\_information.checkin\_method` (string)

An enumeration that describes the conditions for the checkin process and for collecting the key to access the property. This is typically relevant for non-hotel accommodations (like houses or apartments) without a 24 hours front-desk.

Enum: "door_code", "lock_box", "reception", "secret_spot", "someone_will_meet", "unknown"

- `data.key\_collection\_information.key\_location` (string)

Location of the key to access this accommodation property.

Enum: "at_the_property", "door_code", "different_place", "unknown"

- `data.location` (object)

All location related information of this accommodation property.

- `data.location.city` (integer)

Uniquely identifies a city. The full list of cities can be retrieved from [\[/common/locations/cities\]\(#/common/locations/cities\)](#).

- `data.location.coordinates` (object)

- ``data.location.coordinates.latitude`` (number)
- ``data.location.country`` (string)
ISO 3166 country code. The full list of countries can be retrieved from [\[/common/locations/countries\]\(#/common/locations/countries\)](#).
- ``data.location.districts`` (array)
- ``data.location.postal_code`` (string)
- ``data.location.regions`` (array)
- ``data.long_stay_friendly`` (boolean)
Whether the accommodation is suitable for long stays.
- ``data.meal_prices`` (object)
Details regarding the meal pricing options offered at this accommodation.
- ``data.meal_prices.breakfast`` (number)
The price of breakfast per person, expressed in the accommodation's local currency. If the value is null, it indicates that breakfast pricing is not available.
- ``data.meal_prices.dinner`` (number)
The price of dinner per person, expressed in the accommodation's local currency. If the value is null, it indicates that dinner pricing is not available.
- ``data.meal_prices.lunch`` (number)
The price of lunch per person, expressed in the accommodation's local currency. If the value is null, it indicates that lunch pricing is not available.
- ``data.number_of_rooms`` (integer)
Approximate number of bookable rooms or accommodation units configured in the Booking.com system. This value is not an availability indicator and **does not necessarily represent the property's physical room count**. For holiday homes and similar private rentals, this may be 1 even when the property contains multiple bedrooms, because the entire property is offered as a single bookable unit.
- ``data.payment`` (object)
Payment information related to this property. Requires ``{"extras":["payment"]}``.
- ``data.payment.methods`` (object)
Payment methods accepted by this property.
- ``data.payment.methods.cards`` (array)
Credit cards accepted when paying at the property
- ``data.payment.methods.cash`` (boolean)

Whether this property accepts cash

Example: true

- `data.payment.methods.virtual\_cards` (array)

Virtual credit cards accepted when paying at the property

- `data.payment.timings` (array)

The payment timings supported by this product.

- `data.payment.cvc\_required` (boolean)

Whether cvc is mandatory for creating order for this accommodation.

- `data.payment.domestic\_no\_cc` (boolean)

Whether domestic bookers can book without credit card for products with free cancellation policies.

- `data.payment.amex\_cvc\_required` (boolean)

If amex card is used as payment method to create order for this accommodation, whether cvc is mandatory for that.

- `data.photos` (array)

List of photos for this accommodation property. The maximum number of photos returned may be limited by contract. Requires `{ "extras": ["photos"] }`. The photos are returned in no particular order.

- `data.photos.main\_photo` (boolean)

Flags this as the main photo. Not returned otherwise.

Example: true

- `data.photos.tags` (array)

- `data.photos.url` (object)

- `data.photos.url.large` (string)

URL of the photo image with a maximum width of 1280 pixels.

Example:

<https://q-xx.bstatic.com/xdata/images/hotel/max1280/20934654.jpg?k=806399263699a47361bdbbafc9c872a3db03eea26c4a815f5f4df95c93e38cdb&o=>

- `data.photos.url.standard` (string)

URL of the photo image with a maximum width of 500 pixels.

Example:

<https://q-xx.bstatic.com/xdata/images/hotel/max500/20934654.jpg?k=806399263699a47361bdbbafc9c872a3db03eea26c4a815f5f4df95c93e38cdb&o=>

- `data.photos.url.thumbnail` (string)

URL of the photo thumbnail image with dimensions 100x100 pixels.

Example:

<https://q-xx.bstatic.com/xdata/images/hotel/100x100/20934654.jpg?k=806399263699a47361bdbbfc9c872a3db03eea26c4a815f5f4df95c93e38cdb&o=>

- ``data.photos.url.thumbnail_large`` (string)

URL of the photo thumbnail image with dimensions 300x300 pixels.

Example:

<https://q-xx.bstatic.com/xdata/images/hotel/300x300/20934654.jpg?k=806399263699a47361bdbbfc9c872a3db03eea26c4a815f5f4df95c93e38cdb&o=>

- ``data.policies`` (object)

Set of price relevant rules, options and constraints defined by the accommodation for this product. Requires ``{"extras":["policies"]}``.

- ``data.policies.cots_and_extra_beds`` (array)

Prices for cots and extra beds.

- ``data.policies.cots_and_extra_beds.age`` (object)

Ages to which this entry is applicable. Children are aged 0-17. 18/null means adult. The interval is inclusive.

- ``data.policies.cots_and_extra_beds.age.from`` (integer)

- ``data.policies.cots_and_extra_beds.age.to`` (integer | null)

- ``data.policies.cots_and_extra_beds.mode`` (string)

How the price is applied per cot/extra bed.

Enum: "per_night", "per_stay"

- ``data.policies.cots_and_extra_beds.type`` (string)

Whether this entry relates to a cot or an extra bed.

Enum: "cot", "extra_bed"

- ``data.policies.maximum_checkin_age`` (integer)

Defines the maximum (inclusive) check-in age for this property. If null, then there is no maximum age for checking in

- ``data.policies.minimum_checkin_age`` (integer)

Defines the minimum (inclusive) check-in age for this property.

- ``data.policies.minimum_guest_age`` (integer)

Defines the minimum age (inclusive) for staying in this property. If "0", then a guest of any age is allowed.

- ``data.policies.pets`` (object)

- ``data.policies.pets.allowed`` (string)

An enumerated value describing if pets are allowed

Enum: "yes", "no", "upon_request"

- `data.policies.pets.charge\_mode` (string)

An enumerated value describing the charge mode for pets

Enum: "free", "charges_may_apply"

- `data.policies.damage` (object)

DamagePolicy of the property

- `data.policies.damage.deposit` (object)

- `data.policies.damage.deposit.collect` (object)

- `data.policies.damage.deposit.collect.date` (object)

- `data.policies.damage.deposit.collect.date.reference\_date` (string)

Enum: "checkin", "checkout"

- `data.policies.damage.deposit.collect.date.days\_offset` (integer)

The number of days on or before reference date.

- `data.policies.damage.deposit.collect.payment\_method` (string)

Enum: "bank_transfer", "cash", "credit_card", "paypal", "other"

- `data.policies.damage.deposit.refund` (object)

- `data.policies.damage.deposit.refund.date` (object)

- `data.policies.damage.deposit.refund.date.days\_offset` (integer)

The number of days on or after reference date.

- `data.policies.damage.amount` (number)

The amount that can be charged

- `data.policies.damage.currency` (string)

Currency in which payment needs to be made

- `data.price\_category` (string)

Indicates the qualitative price reference (between \$ and \$\$\$\$) on how expensive an accommodation is. Accommodations in the same city are sorted by ascending price (average per guest per night in the last month), the ones in the lowest 25 percentile are in category \$, between 25 and 50 percentile are in category \$\$, between 50 and 75 percentile are in category \$\$\$, remaining ones are in category \$\$\$\$.

- `data.programmes` (object)

Details of programmes undergone by the property.

- `data.programmes.travel\_proud` (boolean)

Boolean value is "true" if property has travel proud badge and "false" otherwise.

- `data.programmes.sustainable\_offerings` (object)

Sustainability certifications associated with the property.

- `data.programmes.sustainable\_offerings.certifications` (array)

The external sustainability certifications awarded to the property.

- `data.programmes.sustainable\_offerings.certifications.name` (string)

The name of the sustainability certification.

- `data.ranking` (number)

Public ranking score of the accommodation.

- `data.rating` (object)

- `data.rating.number\_of\_reviews` (integer)

Number of validated reviews for this accommodation.

- `data.rating.preferred` (boolean)

Boolean value is "true" if this accommodation is in the Booking.com's preferred program and "false" otherwise.

Example: true

- `data.rating.review\_score` (number)

A decimal number indicating the current review score of this accommodation property, in the range 1..10.

- `data.rating.stars` (number)

Number of stars of this accommodation property.

Example: 4

- `data.rating.stars\_type` (string)

An enumerated value describing which type of stars this accommodation has.

Enum: "estimated_by_accommodation", "estimated_by_booking", "official"

- `data.refuses\_free\_cancellation\_requests` (boolean)

Shows whether the property does not accept requests to waive the cancellation fee. Check this field before sending the cancellation request.

true: The property does not accept waiving the cancellation fee.

false: The property may approve a request to cancel the reservation without paying the cancellation fee

- `data.rooms` (array)

The list of room types available at this property. Requires `{"extras":["rooms"]}`.

- `data.rooms.id` (string)

A unique identifier for a specific room within an accommodation property. You can retrieve the full list of available room IDs by calling `[accommodations/details]/(demand/docs/open-api/demand-api/accommodations/accommodations/details)`.

- ``data.rooms.attributes`` (array)

Lists a set of attribute qualifiers for this room. Will not be returned if no relevant attributes are applicable.

- ``data.rooms.bed_options`` (array)

Lists all possible bedding options for this room or apartment.

- ``data.rooms.bed_options.bed_configurations`` (array)

Lists all alternative bed configurations that are supported.

- ``data.rooms.bed_options.bed_configurations.id`` (string)

Uniquely identifies this bed configuration.

- ``data.rooms.bed_options.bed_configurations.configuration`` (array)

Detail list of all different types and number of beds included in this configuration.

- ``data.rooms.bed_options.bed_configurations.configuration.bed_type`` (integer)

A signed integer number that uniquely identifies a bed type. Examples of bed types are: Single, Double etc. The full list can be obtained by calling `accommodations/constants`.

- ``data.rooms.bed_options.bed_configurations.configuration.number_of_beds`` (integer)

Number of similar beds included in this configuration.

- ``data.rooms.bed_options.has_bathroom`` (boolean)

Flags if this area includes its own bathroom.

- ``data.rooms.bed_options.is_bedroom`` (boolean)

Flags if this area is marked as a bedroom, otherwise, it should be considered a living room.

- ``data.rooms.cots_and_extra_beds`` (object)

Lists room options regarding adding cots and/or extra beds.

- ``data.rooms.cots_and_extra_beds.are_allowed_together`` (boolean)

Flags if cots and extra beds can be placed together in the room. ``true`` allows both up to their maximum limits. ``false`` requires exclusive choice of either cots or extra beds.

- ``data.rooms.cots_and_extra_beds.maximum_number_of_cots`` (integer)

Maximum number of cots that can be added.

- ``data.rooms.cots_and_extra_beds.maximum_number_of_extra_beds`` (integer)

Maximum number of extra beds that can be added.

- ``data.rooms.facilities`` (array)
The list of facilities available in this room. Requires ``{"extras":["rooms","facilities"]}``.
- ``data.rooms.maximum_occupancy`` (object)
Occupancy limits and options.
- ``data.rooms.maximum_occupancy.adults`` (integer)
Maximum number of adults.
- ``data.rooms.maximum_occupancy.children`` (integer)
Maximum number of children.
- ``data.rooms.number_of_rooms`` (object)
Breakdown of the internal layout, including the number of bedrooms, bathrooms, and living rooms within this room type or accommodation unit.
- ``data.rooms.number_of_rooms.bathrooms`` (integer)
Total number of bathrooms.
- ``data.rooms.number_of_rooms.bedrooms`` (integer)
Total number of rooms equipped with a bed.
- ``data.rooms.number_of_rooms.living_rooms`` (integer)
Total number of rooms without a bed.
- ``data.rooms.photos`` (array)
List of photos for this accommodation room. The maximum number of photos returned may be limited by contract. Requires ``{"extras":["rooms","photos"]}``. The photos are returned in no particular order.
- ``data.rooms.room_type`` (integer)
A signed integer number that uniquely identifies an accommodation property room type. Example of room types are: Suite, Apartment, Twin/Double etc. The full list can be obtained by calling `accommodations/constants`.
- ``data.rooms.size`` (number)
The room area in square meters.
Example: 20
- ``data.spoken_languages`` (array)
Languages spoken by the staff of this accommodation property.
- ``data.themes`` (array)
- ``data.url`` (object)
Consolidated URLs for web and app redirects.
- ``data.url.app`` (string)

A mobile app URL that directs the user to a specific page or content within the Booking.com app. The link can only be used on a device with the Booking.com app installed. It typically includes an Affiliate ID (AID) to attribute bookings to the affiliate partner when users are redirected

- ``data.url.web`` (string)

Internet address for the property page on Booking.com.

- ``data.work_friendly`` (boolean)

Whether the accommodation is suitable for working remotely.

- ``metadata`` (object)

- ``metadata.next_page`` (string | null)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Updates

Use this endpoint to track accommodations that have opened, closed, or had content updates since a specific timestamp.

Changes can include updates to general information, facilities, rooms, photos, payments, and more.

****Key points**:**

- You can filter results by `country` or `city`.
- Use the `next` timestamp from the response to fetch subsequent updates.
- Combine this endpoint with `[accommodations/details] (/demand/docs/open-api/demand-api/accommodations/accommodations/details)` to keep your local accommodation cache up to date.
- Maximum number of IDs returned is approximately 5000 per request.

Endpoint: POST /accommodations/details/changes

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `last\_change` (string, required)
The timestamp in ISO-8601 format from which changes to accommodations are returned (inclusive). Only UTC time zone is supported. We support changes for last 24 hours. Format: YYYY-MM-DDTHH:mm:ss+00:00
- `filters` (object)
parameter basis which filtering needs to be done. Only one of (countries or cities) must be provided.
- `filters.countries` (array)
Filter changes based on these countries. The valid full list can be obtained by calling `common/locations/countries`.
- `filters.cities` (array)
Filter changes based on these cities. The valid full list can be obtained by calling `common/locations/cities`.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (object)

- ``data.changes`` (object)

The list of changed accommodations.

- ``data.changes.changed`` (array)

Accommodations which have had relevant changes to their content since the given timestamp. Changes being tracked include: general information, standard phrase, photos, payments, facilities and rooms.

- ``data.changes.closed`` (object)

Accommodations which have closed since the given timestamp. Note that these same accommodations may be re-opened shortly after.

- ``data.changes.closed.fraud`` (array)

- ``data.changes.closed.permanently`` (array)

- ``data.changes.closed.temporarily`` (array)

- ``data.changes.opened`` (array)

Accommodations which have opened since the given timestamp. Note that sometimes accommodations may be closed again shortly after.

- ``data.from`` (string)

ISO 8601 timestamp which indicates the timestamp from which the changes are returned (inclusive).

- ``data.next`` (string)

ISO 8601 timestamp which indicates the next timestamp to be used for ``last_change``. This will be 1 second after the latest change returned in the result (all changes from the "last" second are returned). NOTE: this field will not be present unless changes are returned. In this case, repeat the call after one minute with the same ``last_change`` date.

- ``data.total_changes`` (integer)

Total number of changed accommodation ids returned. If 0, then repeat the call after one minute with the same ``last_change`` date.

Reviews

This endpoint provides access to reviews for specified accommodations, allowing you to retrieve traveller feedback associated with a particular property. The reviews returned can be [filtered and sorted](/demand/docs/accommodations/filter-sorting), with the option to limit the number of reviews per accommodation by specifying the `rows` parameter. Please note that the ratings **score** is based on all traveller traffic across Booking.com, and may not necessarily reflect the experience of your own customers. If you choose to display or use these ratings and reviews, you are responsible for ensuring that your travellers are properly informed about what these scores represent.

Endpoint: POST /accommodations/reviews

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodations` (array, required)
- `languages` (array)
Limits reviews to those written in this language.
- `last\_change` (string)
Limits the reviews to those changed after the given date. Format: YYYY-MM-DD.
- `page` (string)
Pagination token used to retrieve the next page of results. Obtained from `next\_page`.
- `reviewer` (object)
- `reviewer.countries` (array)
Limits reviews to those written by reviewer from the given country.
- `reviewer.travel\_purposes` (array)
Limits reviews to those written by specific travel purposes.
- `reviewer.types` (array)
Limits reviews to those written by specific reviewer type.
- `rows` (integer)
The maximum number of results to return.

- ``score`` (object)
- ``score.maximum`` (integer)
Limits the reviews to those having score lesser or equal to this value.
- ``score.minimum`` (integer)
Limits the reviews to those having score greater or equal to this value.

Response 200 fields (application/json):

- ``request_id`` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``data`` (array)
 - ``data.id`` (integer)
A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling `[accommodations/details]/(demand/docs/open-api/demand-api/accommodations/accommodations/details)`.
 - ``data.reviews`` (array)
 - ``data.reviews.id`` (integer)
Unique identifier of the review.
 - ``data.reviews.date`` (string)
The date when the review was last modified. Format: YYYY-MM-DD.
 - ``data.reviews.language`` (string)
A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. **Note:** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the ``/common/languages`` endpoint in the same Demand API version you are using.
Example: en-us
 - ``data.reviews.negative`` (string | null)
Negative comments from this review.
 - ``data.reviews.positive`` (string | null)
Positive comments from this review.
 - ``data.reviewsReviewer`` (object)
 - ``data.reviewsReviewer.country`` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: `nl`

- ``data.reviews.viewer.name`` (string | null)

Name of the reviewer. If the value is null then the reviewer is anonymous.

- ``data.reviews.viewer.travel_purpose`` (string)

Defines if this was a leisure or business trip.

Enum: "business", "leisure"

- ``data.reviews.viewer.type`` (string)

The reviewer type.

Enum: "couple", "extended_group", "family_with_children", "solo_traveller"

- ``data.reviews.score`` (number)

The aggregated score of the review.

- ``data.reviews.summary`` (string | null)

The summary of the review.

- ``data.reviews.text_meets_guidelines`` (boolean)

Set to true when review meets the guidelines. The review text will be removed if it doesn't meet guidelines.

- ``data.url`` (string)

Internet address for the property page on Booking.com.

- ``metadata`` (object)

- ``metadata.next_page`` (string | null)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Review and scores

This endpoint returns score distribution and score breakdown for the specified accommodations. The scores information can be filtered by reviewer parameters and languages.

Endpoint: POST /accommodations/reviews/scores

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodations` (array, required)
- `languages` (array)
Limits reviews to those written in this language.
- `reviewer` (object)
- `reviewer.countries` (array)
Limits reviews to those written by reviewer from the given country.
- `reviewer.travel\_purposes` (array)
Limits reviews to those written by specific travel purposes.
- `reviewer.types` (array)
Limits reviews to those written by specific reviewer type.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
- `data.id` (integer)
A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling [\[accommodations/details\]\(/demand/docs/open-api/demand-api/accommodations/accommodations/details\)](#).
- `data.breakdown` (object)

Review scores breakdown for each criteria. List of criteria includes: cleanliness, comfort, facilities, free_wifi, location, staff, value_for_money.

- `data.distribution` (object)

Overall score distribution for each score (1-10).

- `data.number\_of\_reviews` (integer)

Number of validated reviews for this accommodation.

- `data.score` (number)

A decimal number indicating the current review score of this accommodation property, in the range 1..10.

- `data.url` (string)

Internet address for the property page on Booking.com.

Third-party suppliers

Use this endpoint to retrieve the list of third-party suppliers that facilitate accommodation inventory on Booking.com.

A third-party supplier is an external partner company that provides accommodation inventory through Booking.com. When a product is facilitated by a third-party supplier:

- * ``inventory.third_party`` is ``true``.

- * ``inventory.third_party_supplier_id`` contains the supplier identifier.

Use the returned ``id`` values to match the ``inventory.third_party_supplier_id`` returned by `/accommodations/availability` and retrieve supplier information, such as the supplier name and company address.

Call this endpoint with an empty request body to retrieve the complete list of suppliers.

Endpoint: POST `/accommodations/third-party-suppliers`

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Response 200 fields (application/json):

- ``request_id`` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``data`` (array)
List of third-party accommodation suppliers.
- ``data.id`` (integer)
Unique identifier of a third-party accommodation supplier. Use the `/accommodations/third-party-suppliers`(`#/accommodations/third-party-suppliers`) endpoint to retrieve the full list of suppliers and their details.
- ``data.name`` (string)
Display name of the third-party supplier.
- ``data.company_address`` (string)
Registered company address of the third-party supplier. May be omitted or ``null`` when the address is not available.

Response 500 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Car rentals

This collection includes endpoints related to **car rental** services within the connected trip experience. Use these endpoints to:

- Search and retrieve car details.
- Retrieve car specifications, depot locations, and supplier information.

- [POST
/cars/search](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/search.md): Use this endpoint to retrieve the available car rentals matching the search criteria.

- [POST
/cars/constants](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/constants.md): This endpoint returns localised car rental constants used across the Cars API collection, such as extras, fuel policies, payment timings, and transmission types. It also returns customer service contact information.

- [POST
/cars/depots](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depots.md): Retrieve a paginated list of car rental depots. Supports incremental updates via the `last\_modified` filter.

- [POST
/cars/depots/reviews/scores](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/depotscores.md): Use this endpoint to retrieve review scores and score breakdowns for depots, including the overall review score and total number of reviews.

- [POST
/cars/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/details.md): Use this endpoint to fetch car details like bag capacity, number of doors, brand and model, etc.

- [POST
/cars/suppliers](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/cars/suppliers.md): Use this endpoint to fetch a list of car rental suppliers. You can use a supplier ID (or an array of them), to retrieve specific details. Alternatively, if you do not add any ID in the request, you will receive a list of all suppliers.

Search car rentals

Use this endpoint to retrieve the available car rentals matching the search criteria.

Endpoint: POST /cars/search

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `booker` (object, required)
Defines the booker context.
- `booker.country` (string, required)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here: https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.
Example: nl
- `currency` (string | null, required)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
- `driver` (object, required)
Defines the driver context.
- `driver.age` (integer, required)
Driver age. Affects the availability and price of the products.
- `filters` (object)
Defines the filtering criteria for refining the request results. It allows you to specify various parameters to narrow down the available car rental options based on specific attributes.
- `filters.air\_conditioning` (boolean)
Filters the results to include car rentals with or without air conditioning. Setting this value to true will only return vehicles with air conditioning, while false will exclude them.
- `filters.car\_categories` (array)
Filters the results based on the selected car categories.
- `filters.depot\_location\_type` (string)

Filters the results based on the type of depot location where the vehicle is picked up or dropped off.

Enum: "in_terminal", "car_rental_centre", "outside_terminal", "airport_hotel", "shuttle_bus", "meet_greet", "trainstation", "downtown"

- `filters.fuel_types`` (array)

Filters the results by one or more fuel types.

- `filters.mileage_type`` (string)

Filters the results based on the mileage type associated with the rental vehicle.

Enum: "limited", "unlimited"

- `filters.number_of_seats`` (integer)

Filters the results based on the number of seats in the vehicle. This allows you to specify a vehicle that can accommodate a specific number of passengers.

- `filters.price`` (object)

Filters the results to include only vehicles whose total rental price falls within the specified range (inclusive). Prices are evaluated in the requested currency.

- `filters.price.maximum`` (number)

Returns only vehicles with a total rental price less than or equal to this value, in the requested currency. Omit to indicate no upper limit.

- `filters.price.minimum`` (number)

Returns only vehicles with a total rental price greater than or equal to this value, in the requested currency. Omit to indicate no lower limit.

- `filters.rating`` (object)

Filter vehicles by the minimum review score of the depot.

- `filters.rating.minimum_review_score`` (integer)

Return only vehicles from depots with a review score greater than or equal to the specified value. Valid values range from 1 to 10.

- `filters.supplier_ids`` (array)

Filters the results based on the supplier ID of the vehicle. This allows you to retrieve vehicles from specific suppliers. A maximum of 10 supplier IDs can be provided.

- `filters.transmission_type`` (string)

Filters the results based on the transmission type of the vehicle.

Enum: "automatic", "manual"

- `maximum_results`` (integer)

The maximum number of results to return for car searches.

- `language`` (string)

A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. **Note:** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the `/common/languages` endpoint in the same Demand API version you are using.

Example: en-us

- `page` (string)

Pagination token used to retrieve the next page of results. Obtained from `next_page`.

- `payment` (object)

- `payment.timings` (array)

Filters the results to include only car rentals that offer the specified payment timings. Use this parameter to search for cars based on the timing of payment (e.g., payment upfront, partial payment, or payment at the depot).

- `route` (object, required)

Defines the route context.

- `route.pickup` (object, required)

Defines the pickup or dropoff route point.

- `route.pickup.datetime` (string, required)

Pickup / dropoff datetime. Must be a local datetime without timezone offset, in the format `yyyy-MM-dd'T'HH:mm:ss`.

Example: 2026-11-01T11:05:00

- `route.pickup.location` (object, required)

Defines the pickup or dropoff location. Provide exactly one of airport, coordinates, or city.

- `route.pickup.location.airport` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- `route.pickup.location.coordinates` (object)

- `route.pickup.location.coordinates.latitude` (number)

- `route.pickup.location.coordinates.longitude` (number)

- `route.pickup.location.city` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- `sort` (object)

Defines how the search results are sorted. If omitted, results are sorted by the recommended option.

- ``sort.by`` (string, required)

The criterion used to sort the search results.

Enum: "recommended", "price", "distance", "review_score"

- ``sort.direction`` (string)

Deprecated. Specifies the sort direction. This field is no longer used and will be removed in a future version.

Enum: "ascending", "descending"

Response 200 fields (application/json):

- ``request_id`` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``data`` (array, required)

- ``data.car`` (integer)

This ID corresponds to a specific car model and supplier (fleet) combination, as returned by the `/cars/details` endpoint. Cache the details keyed by this ID and use it to match search results to your cached data.

- ``data.categories`` (array)

The categories assigned to the car.

- ``data.deal`` (object | null)

This specifies the deal tagging for the product.

- ``data.deal.discount_percentage`` (integer)

Discount percentage of the applied deals.

- ``data.deal.public_price`` (number)

- ``data.deal.tags`` (array)

The tags of all the applied deals.

- ``data.offer`` (integer)

This ID identifies the car rental offer and its associated policies. Include it when calling the `/cars/availability` endpoint.

- ``data.policies`` (object)

The policies that apply to this product.

- ``data.policies.cancellation`` (object)

The cancellation policy that applies to this product.

- ``data.policies.cancellation.details`` (object | null)

Provides the policy details if the cancellation is free. For example:

1. `duration='PT48H'` and `context=before_pickup` means 'Free cancellation is available up to 48 hrs before pick up'.

2. `duration='P7D'` and `context=within_given_time_period_of_booking` means 'Free cancellation is available within 7 days of booking'

- ``data.policies.cancellation.details.context`` (string)

The context in which the cancellation policy applies. For example 'before_pickup'

Enum: "before_pickup", "within_given_time_period_of_booking"

- ``data.policies.cancellation.details.duration`` (string)

The duration until which the cancellation is free. This is in ISO-8601/Duration format.

- ``data.policies.cancellation.type`` (string)

The type of cancellation present. For example 'free_cancellation' or 'non-refundable'.

Enum: "free_cancellation", "non-refundable"

- ``data.policies.damage_excess`` (object | null)

The maximum amount a traveller may be charged for damages to the car during the rental period, as specified by the rental agreement.

- ``data.policies.damage_excess.amount`` (number)

The amount to be charged.

- ``data.policies.damage_excess.currency`` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.

Example: EUR

- ``data.policies.deposit`` (object | null)

The amount of money that will be temporarily pre-authorised or blocked on the traveller's credit card at the rental location as a security deposit, to cover potential damage or extra charges.

- ``data.policies.deposit.amount`` (number)

The amount to be charged.

- ``data.policies.insurance_package`` (string)

The supplier insurance package applied to this product by default. Use the insurance object instead when third-party insurance products are configured in your account.

Enum: "basic", "inclusive", "zero_excess"

- ``data.policies.fuel`` (string)

The fuel policy that applies to this product. Maps to the ``fuel_policies`` constant returned by the `/cars/constants` endpoint.

Enum: "return_same", "return_same_or_prepay_no_refunds", "return_same_preauth", "free_tank", "prepay_no_refunds", "prepay_part_refunds", "prepay_refunds"

- `data.policies.mileage` (object)
The mileage policy that applies to this product.
- `data.policies.mileage.amount` (number | null)
The amount that must be paid if the distance limit is exceeded.
- `data.policies.mileage.distance\_limit` (number | null)
The maximal distance limit allowed for this product before additional fees apply.
- `data.policies.mileage.distance\_unit` (string)
The unit of measurement for the distance limit. For example 'km' or 'miles'.
Enum: "kilometers", "miles"
- `data.policies.mileage.type` (string, required)
The type of mileage policy applied.
Enum: "limited", "unlimited"
- `data.policies.payment` (object)
The payment policy that applies to this product.
- `data.policies.payment.timing` (string, required)
The applied payment timing. For example 'pay_online_now'.
Enum: "pay_online_now", "pay_partial_online_now", "pay_at_pickup"
- `data.policies.theft\_excess` (object | null)
The maximum amount a traveller may be charged in the event of car theft during the rental period, as outlined in the rental agreement.
- `data.policies.theft\_excess.amount` (number)
The amount to be charged.
- `data.price` (object)
The price components of this product.
- `data.price.credit\_card\_required` (boolean | null)
Indicates whether a credit card is required as a guarantee for this vehicle.
- true: A credit card must be provided and will be passed to the supplier for guarantee purposes. Applies to vehicles with 'payment.timing = pay_at_pickup'.
- false: A credit card is explicitly not required.
- null: Information not available or not applicable (for example, pay-online-now vehicles where credit card requirements are currently unknown).
- `data.price.extra\_charges` (array)
The charge breakdown. Includes taxes and fees included in the drive away price.
- `data.price.extra\_charges.charge` (string)
The type of this charge.

- ``data.route`` (object)
Defines the actual route associated with the product.
- ``data.route.pickup`` (object)
Defines the product pickup / dropoff route point.
- ``data.route.pickup.depot`` (integer)
Unique identifier of a depot. Retrieve the full list by calling the `/cars/depots` endpoint.
Example: 5944
- ``data.route.pickup.depot_location_type`` (string)
Type of depot location where the vehicle is picked up or dropped off. For example, 'shuttle_bus', 'in_terminal', etc.
Enum: "in_terminal", "car_rental_centre", "outside_terminal", "airport_hotel", "shuttle_bus", "meet_greet", "trainstation", "downtown"
- ``data.special_offer`` (string | null)
The special offer included with this product, if any. This can be an additional service, a free upgrade, or a promotional feature provided by the supplier. If no special offer applies, the value will be null.
Enum: "one_additional_driver", "two_additional_drivers", "three_additional_drivers", "all_additional_drivers", "gps", "baby_or_child_seat", "priority_pickup", "wifi_device", "sim_card", "upgrade", "black_friday", "getaway_deal", "mobile_rate"
- ``data.insurance`` (object | null)
Third-party insurance product for this car rental. Only present for eligible partner configurations. Null if not available.
- ``data.insurance.name`` (string)
The display name of the insurance product.
- ``data.insurance.id`` (string)
The identifier for the type of insurance product.
- ``data.insurance.price`` (object)
The price of the insurance product for the full rental period.
- ``data.supplier`` (integer)
Uniquely identifies a vehicle supplier. The full list can be obtained by calling `/cars/suppliers` endpoint.
- ``data.url`` (object)
Urls to the relevant pages.
- ``data.url.app`` (string)
URL for the related page on Booking App.

- ``data.url.web`` (string)
URL for the related page on cars.booking.com.

- ``data.estimated_commission`` (object | null)

Estimated commission the partner may earn if the traveller books this car. Expressed in the selected currency and based on predictive modelling at search time. Only returned when the predicted commission feature is enabled for the partner. Omitted when the feature is unavailable or when a reliable estimate cannot be produced.

- ``metadata`` (object)
Metadata about the request.

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

- ``metadata.total_results`` (integer)
The total number of results available.

- ``search_token`` (string)

Encoded string that must be passed in subsequent requests to identify the context of the car search. Note: It is specific to Car rentals and differs from other tokens used in booking flows.

Response 400 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.

- ``errors`` (array, required)

- ``errors.id`` (string, required)

- ``errors.message`` (string, required)

Response 500 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.

- ``errors`` (array, required)

- ``errors.id`` (string, required)

- ``errors.message`` (string, required)

Car constants

This endpoint returns localised car rental constants used across the Cars API collection, such as extras, fuel policies, payment timings, and transmission types.

It also returns customer service contact email addresses per requested language for partner support scenarios where Booking.com handles travellers' communication directly.

To retrieve all constants, send an empty request body.

Endpoint: POST /cars/constants

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `constants` (array)
Use this field to limit the response to specific categories, such as fuel_policies, depot_services, customer_services, etc. If omitted, all constants are returned.
- `languages` (array)
List of language codes used to localise constant names. Each constant name is returned as a translated object keyed by language. If not provided, en-gb is used by default.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (object)
Contains constant groups keyed by constant type. Each group includes a list of constant identifiers and their translated names.
- `data.car\_categories` (array)
Represents a constant identifier and its translated display names for the requested languages.
- `data.car\_categories.id` (string)
- `data.car\_categories.name` (object)
A string localised in multiple languages.

Response 400 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Depots

Retrieve a paginated list of car rental depots. Supports incremental updates via the `last\_modified` filter.

Endpoint: POST /cars/depots

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `last\_modified` (string)
Returns depots modified after the specified timestamp (exclusive).
Example: 2026-03-01T11:05:00+00:00
- `maximum\_results` (integer)
The maximum number of results to return.
- `languages` (array)
List of language codes to return translated fields. If a translation is unavailable, the default language (`en-gb`) is returned.
- `page` (string)
Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
 - `data.id` (integer)
Unique identifier of a depot. Retrieve the full list by calling the (/cars/depots)(#/cars/depots).
Example: 5944
 - `data.contact` (object)
Contact information of the depot. Returns `null` when unavailable.
 - `data.contact.email` (string | null)
Email address of the depot. Returns `null` when unavailable.
Example: depot@test.booking.com

- ``data.contact.telephone`` (string | null)
Telephone number of the depot. Returns ``null`` when unavailable.
Example: +31882847620
- ``data.city`` (integer)
Unique identifier of the city where the depot is located. If the city ID is not included in the list returned by `/common/locations/cities`, call that endpoint using the city filter.
Example: -1471393
- ``data.pickup`` (object | null)
Pickup or drop-off information.
- ``data.pickup.instructions`` (object)
A string localised in multiple languages.
- ``data.pickup.working_hours`` (object)
Opening and closing times per day of the week. Days may be omitted if the depot is closed.
- ``data.location`` (object)
Depot location information.
- ``data.location.address`` (string | null)
Depot address information.
Example: 5 Aankomstpassage
- ``data.location.airport`` (string | null)
Airport IATA code.
Example: AMS
- ``data.location.depot_location_type`` (string | null)
Specifies where the depot is located (for example, inside the terminal, at a train station, or downtown). Returns ``null`` when not defined.
Enum: "in_terminal", "car_rental_centre", "outside_terminal", "airport_hotel", "shuttle_bus", "meet_greet", "trainstation", "downtown"
- ``data.location.coordinates`` (object)
- ``data.location.coordinates.latitude`` (number)
- ``data.location.coordinates.longitude`` (number)
- ``data.location.country`` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:
https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- `data.location.name` (object)

Translated depot name.

Example: {"en-gb":"Amsterdam Airport Schiphol - Terminal 3"}

- `data.location.post\_code` (string | null)

Depot post code

Example: 1118 AX

- `data.services` (array)

List of services provided by the depot.

- `data.supplier` (integer)

Uniquely identifies a vehicle supplier. The full list can be obtained by calling `/cars/suppliers`(`#/cars/suppliers`).

- `data.ratings` (object | null)

Review count and average score for the depot.

- `data.ratings.number\_of\_reviews` (integer)

Number of validated reviews for the depot.

Example: 125

- `data.ratings.score` (number)

Current review score of the depot, in the range 1.0 to 10.0.

Example: 8.7

- `metadata` (object)

Metadata about the request.

- `metadata.next\_page` (string | null)

Indicates that more results are available. Pass this token to the `page` parameter to retrieve the next page of results.

Response 400 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Depot scores

Use this endpoint to retrieve review scores and score breakdowns for depots, including the overall review score and total number of reviews.

Endpoint: POST /cars/depots/reviews/scores

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `maximum\_results` (integer)
The maximum number of results to return.
- `page` (string)
Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
 - `data.id` (integer)
Unique identifier of a depot. Retrieve the full list by calling the (/cars/depots)(#/cars/depots).
Example: 5944
 - `data.breakdown` (object)
Breakdown of review scores by evaluation category.
 - `data.breakdown.cleanliness` (object)
Review score information for a specific evaluation category.
 - `data.breakdown.cleanliness.score` (any)
 - `data.breakdown.likeliness\_rent\_again` (object)
Deprecated. This field will be removed in a future version.
 - `data.number\_of\_reviews` (any)
 - `data.score` (any)

- ``metadata`` (object)
Pagination metadata for the response.

- ``metadata.next_page`` (string | null)
Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Response 400 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``errors`` (array, required)
- ``errors.id`` (string, required)
- ``errors.message`` (string, required)

Response 500 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``errors`` (array, required)
- ``errors.id`` (string, required)
- ``errors.message`` (string, required)

Car details

Use this endpoint to fetch car details like bag capacity, number of doors, brand and model, etc.

Endpoint: POST /cars/details

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `last\_modified` (string)
The last modified date-time, only returns depots newer than this timestamp. The value should be within last 7 days
Example: 2023-11-01T11:05:00+00:00
- `maximum\_results` (integer)
The maximum number of results to return.
- `page` (string)
Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
 - `data.id` (integer)
Uniquely identifies a car specification. The full list can be obtained by calling [/cars/suppliers](#cars/details).
 - `data.capacity` (object)
Car's capacity
 - `data.capacity.bags` (object)
Car's Baggage Capacity.
 - `data.capacity.bags.large` (number)
Number of large bags.
 - `data.capacity.bags.small` (number)

Number of small bags.

- `data.capacity.doors` (string)

Number of doors in the car.

- `data.capacity.seats` (string)

Number of seats in the car.

- `data.country` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- `data.features` (array)

List of possible car's features.

- `data.image` (string)

Car's image URL.

- `data.make` (string)

Car's maker/brand.

- `data.model` (string)

Car's model.

- `data.specification` (object)

- `data.specification.code` (string)

Car's code in ACRISS Standard (<https://www.acriss.org/car-codes/expanded-matrix/>).

- `data.specification.description` (string)

Car Description Based on ACRISS Category and Type (<https://www.acriss.org/car-codes/expanded-matrix/>).

- `data.specification.fuel` (string)

Car's fuel type. Maps to the `fuel\_types` constant returned by the `/cars/constants` endpoint.

Enum: "electric", "petrol", "plug_in_hybrid", "multi_fuel", "diesel", "hybrid", "lpg", "hydrogen", "ethanol", "unspecified"

- `data.specification.transmission` (string)

Car's transmission.

Enum: "automatic", "manual"

- `data.supplier` (integer)

Uniquely identifies a vehicle supplier. The full list can be obtained by calling `/cars/suppliers`(`#/cars/suppliers`).

- ``metadata`` (object)

Metadata about the request.

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Response 400 fields (application/json):

- ``request_id`` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``errors`` (array, required)

- ``errors.id`` (string, required)

- ``errors.message`` (string, required)

Response 500 fields (application/json):

- ``request_id`` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``errors`` (array, required)

- ``errors.id`` (string, required)

- ``errors.message`` (string, required)

Suppliers

Use this endpoint to fetch a list of car rental suppliers.
You can use a supplier ID (or an array of them), to retrieve specific details.
Alternatively, if you do not add any ID in the request, the response will include all suppliers.

Endpoint: POST /cars/suppliers

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `maximum\_results` (integer)
The maximum number of results to return.
- `page` (string)
Pagination token used to retrieve the next page of results. Obtained from `next\_page`.
- `suppliers` (array)
Defines the suppliers that should be returned. Without it all suppliers will be returned

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
 - `data.id` (integer)
Uniquely identifies a vehicle supplier. The full list can be obtained by calling [/cars/suppliers](#/cars/suppliers).
 - `data.logo` (string)
Supplier logo image URL.
 - `data.name` (string)
Brand name of the vehicle supplier.
 - `metadata` (object)
Metadata about the request.
 - `metadata.next\_page` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter `page`).

- `metadata.total\_results` (integer)
The total number of results available.

Response 400 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Locations

This collection provides standardised **location identifiers** for geographical entities such as airports, countries, cities, and regions. Use the returned identifiers when constructing requests across all travel services API collections, including both accommodation and car rental endpoints.

- [POST

/common/locations/airports](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/airports.md>): This endpoint returns a list of airport codes and their names in the selected languages. The airports returned may be filtered by a location id. For example, you can get the list of airports in The Ne

- [POST

/common/locations/cities](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/cities.md>): This endpoint returns a list of city IDs and their names in the selected languages. You can filter the results by location ID. For example, to retrieve the list of cities in the Netherlands, pass: `{

- [POST

/common/locations/countries](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/countries.md>): This endpoint returns a list of country codes and their names in the selected languages. The countries returned may be filtered by a location id. For example, you can get the list of countries that ar

- [POST

/common/locations/districts](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/districts.md>): This endpoint returns a list of districts with translations in the selected languages. The districts returned may be filtered by a location id. For example, you can get the list of districts in Amster

- [POST

/common/locations/landmarks](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/landmarks.md>): This endpoint returns a list of relevant geographical landmark codes and their names in the selected languages. The landmarks returned may be filtered by a location id. For example, you can get the li

- [POST

/common/locations/regions](<https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonlocations/common/locations/regions.md>): This endpoint returns a list of regions with translations in the selected languages. The regions returned may be filtered by a location id. For example, you can get the list of regions in the Netherla

Airports

This endpoint returns a list of airport codes and their names in the selected languages. The airports returned may be filtered by a location id. For example, you can get the list of airports in The Netherlands by passing: ``{"country":"nl"}``. To get the full list call the endpoint passing an empty body. The airport codes returned are what is used as input and output for other endpoints. This endpoint implements pagination of the results.

Endpoint: POST /common/locations/airports

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- ``city`` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- ``country`` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- ``district`` (integer)

A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.

- ``landmark`` (integer)

A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- ``languages`` (array)

- ``page`` (string)

Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

- `region` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- `rows` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- `data.name` (object)

A string localised in multiple languages.

- `metadata` (object)

- `metadata.next\_page` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter `page`).

Cities

This endpoint returns a list of city IDs and their names in the selected languages.

You can filter the results by location ID. For example, to retrieve the list of cities in the Netherlands, pass: ``{"country":"nl"}``.

To retrieve the bulk list, call the endpoint with an empty request body.

The city IDs returned by this endpoint are used as input and output values in other Demand API endpoints.

If a city ID returned by another Demand API endpoint is not included in the bulk list, retrieve it by passing the ID in the ``city`` field, for example: ``{"city":900043160}``. A city returned by an ID-specific request may not be included in the bulk list.

Endpoint: POST /common/locations/cities

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- ``city`` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- ``country`` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- ``district`` (integer)

A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.

- ``landmark`` (integer)

A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- ``languages`` (array)

- ``page`` (string)

Pagination token used to retrieve the next page of results. Obtained from ``next_page``.

- ``region`` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- ``rows`` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- ``request_id`` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``data`` (array)

- ``data.id`` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- ``data.name`` (object)

A string localised in multiple languages.

- ``data.coordinates`` (object)

- ``data.coordinates.latitude`` (number)

- ``data.coordinates.longitude`` (number)

- ``metadata`` (object)

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Countries

This endpoint returns a list of country codes and their names in the selected languages. The countries returned may be filtered by a location id. For example, you can get the list of countries that are associated with the European Alps region by passing: `{"region":1199}`.

To get the full list call the endpoint passing an empty body. The returned country codes are used as input and output for other endpoints.

This endpoint implements pagination of the results.

Endpoint: POST /common/locations/countries

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)
A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.
Example: AMS
- ``city`` (integer)
A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.
- ``country`` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here: https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.
Example: nl
- ``district`` (integer)
A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.
- ``landmark`` (integer)
A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.
- ``languages`` (array)

- `page` (string)

Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

- `region` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- `rows` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- `data.name` (object)

A string localised in multiple languages.

- `metadata` (object)

- `metadata.next\_page` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter `page`).

Districts

This endpoint returns a list of districts with translations in the selected languages. The districts returned may be filtered by a location id. For example, you can get the list of districts in Amsterdam by passing: `{"city": -2140479}`.
To get the full list call the endpoint passing an empty body. The district ids returned are what is used as input and output for other endpoints.
This endpoint implements pagination of the results.

Endpoint: POST /common/locations/districts

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)
A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.
Example: AMS
- ``city`` (integer)
A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.
- ``country`` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here: https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.
Example: nl
- ``district`` (integer)
A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.
- ``landmark`` (integer)
A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.
- ``languages`` (array)
- ``page`` (string)

Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

- `region` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- `rows` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (integer)

A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.

- `data.name` (object)

A string localised in multiple languages.

- `data.coordinates` (object)

- `data.coordinates.latitude` (number)

- `data.coordinates.longitude` (number)

- `metadata` (object)

- `metadata.next\_page` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter `page`).

Landmarks

This endpoint returns a list of relevant geographical landmark codes and their names in the selected languages. The landmarks returned may be filtered by a location id. For example, you can get the list of landmarks that are associated with the city of Paris in France by passing: `{"city":-1456928}`.
To get the full list call the endpoint passing an empty body. The landmark codes returned are what is used as input and output for other endpoints.
This endpoint implements pagination of the results.

Endpoint: POST /common/locations/landmarks

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- ``city`` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- ``country`` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- ``district`` (integer)

A signed integer number that uniquely identifies a district. Typically, districts define known areas within a city. The full list can be obtained by calling `common/locations/districts`.

- ``landmark`` (integer)

A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- ``languages`` (array)

- `page` (string)

Pagination token used to retrieve the next page of results. Obtained from `next\_page`.

- `region` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- `rows` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (integer)

A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- `data.name` (object)

A string localised in multiple languages.

- `data.coordinates` (object)

- `data.coordinates.latitude` (number)

- `data.coordinates.longitude` (number)

- `metadata` (object)

- `metadata.next\_page` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter `page`).

Regions

This endpoint returns a list of regions with translations in the selected languages. The regions returned may be filtered by a location id. For example, you can get the list of regions in the Netherlands or that the Netherlands is a part of by passing: `{"country":"nl"}`. To get the full list call the endpoint passing an empty body. The region ids returned are what is used as input and output for other endpoints. This endpoint implements pagination of the results.

Endpoint: POST /common/locations/regions

Version: 3.2

Security: BearerAuth

Header parameters:

- ``X-Affiliate-Id`` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- ``airport`` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `common/locations/airports`.

Example: AMS

- ``city`` (integer)

A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.

- ``country`` (string)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.

Example: nl

- ``landmark`` (integer)

A signed integer number that uniquely identifies a relevant geographical landmark, like a monument or a natural attraction. The full list can be obtained by calling `common/locations/landmarks`.

- ``languages`` (array)

- ``page`` (string)

Pagination token used to retrieve the next page of results. Obtained from ``next_page``.

- ``region`` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- ``rows`` (integer)

The maximum number of results to return.

Response 200 fields (application/json):

- ``request_id`` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

- ``data`` (array)

- ``data.id`` (integer)

A signed integer number that uniquely identifies a geographical region. Regions usually define official administrative areas within a country, but may also include multiple countries and in some cases un-official but popular designations for geographical areas. An example of a region that crosses multiple countries is the Alps in Europe. The full list can be obtained by calling `common/locations/regions`.

- ``data.name`` (object)

A string localised in multiple languages.

- ``metadata`` (object)

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

Payments

Provides generic ****payment-related identifiers****, including supported currency codes, payment cards, and relevant metadata for booking flows.
- Use the returned identifiers when constructing requests across all travel services API collections, including both accommodation and car rental endpoints.

- [POST

/common/payments/cards](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/cards.md): This endpoint returns a list of supported payment cards and their names in English. Examples of payment types are the different credit and debit cards.

To get the full list call the endpoint

- [POST

/common/payments/currencies](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/commonpayments/common/payments/currencies.md): This endpoint returns a list of currency codes and their names in the selected languages. To get the full list call the endpoint passing an empty body.

The currency codes returned are what i

Retrieve currency codes

This endpoint returns a list of currency codes and their names in the selected languages. To get the full list call the endpoint passing an empty body.

The currency codes returned are what is used as input and output for other endpoints.

Endpoint: POST /common/payments/currencies

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `languages` (array)

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
 - `data.id` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling common/payments/currencies.
Example: EUR
 - `data.name` (object)
A string localised in multiple languages.

Retrieve language codes

This endpoint returns a list of human language codes and their names in the corresponding language. To get the full list call the endpoint passing an empty body. The language codes returned are what is used as input and output for other endpoints.

Endpoint: POST /common/languages

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)

- `data.id` (string)

A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. **Note:** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the `/common/languages` endpoint in the same Demand API version you are using.

Example: en-us

- `data.name` (string)

Orders

This API collection enables **management of booking orders** within the Demand API.

Use these endpoints to:

- Preview and create new orders.
- Check order details.
- Cancel or modify existing orders.

This collection is required to integrate booking and order management functionality.

- [POST
/orders/preview](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/preview.md): Use this endpoint to validate an order before checkout and calculate the final price, including a detailed price breakdown, payment schedule, and cancellation policies for accommodation and car rental

- [POST
/orders/create](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/create.md): Use this endpoint to create and confirm an order using a valid order token and the required payment information.

- [POST
/orders/details](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details.md): Use this endpoint to retrieve detailed information about existing orders across supported travel services. Use it to synchronise internal systems, monitor booking updates, and generate reporting or an

- [POST
/orders/details/accommodations](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/accommodations.md): Use this endpoint to retrieve detailed information for one or more accommodation orders. You can request order details either by **reservation** or **order** ID depending on your integration. - The res

- [POST
/orders/details/cars](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/cars.md): Use this endpoint to retrieve detailed information for one or more car rental orders. - You can request car order details using your **reservation** ID. - The response includes booking and cancellatio

- [POST
/orders/details/flights](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/details/flights.md): Use this endpoint to retrieve detailed information for one or more flight orders. - You can request flight order details either by **order ID** or by **reservation ID**. - The response includes struct

- [POST
/orders/modify](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/modify.md): Use this endpoint to modify certain aspects of an accommodation order, such as credit card details, checkin/checkout dates, and room configurations (guest allocation, guest names, and smoking preferen

- [POST
/orders/cancel](https://developers.booking.com/demand/docs/open-api/3.2/demand-api/orders/orders/cancel.md): Use this endpoint to cancel a travel service within an existing order. Provide the details of the reservation or insurance policy you want to cancel. - **Note:** Only one travel service can be cancell

Preview an order

Use this endpoint to validate an order before checkout and calculate the final price, including a detailed price breakdown, payment schedule, and cancellation policies for accommodation and car rentals. Provide the booker's details and preferred currency to receive personalised pricing.

For accommodations: Include check-in and check-out dates, room allocation, and selected products.

For cars: Include the offer ID and search token. Optionally include selected optional products (such as GPS or child seats) returned by /cars/availability to add extras, and/or an insurance.quote_reference from /cars/availability to attach third-party insurance.

Endpoint: POST /orders/preview

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (object)
Contains the calculated order details for accommodation or car products, including pricing, policies, etc.
 - `data.accommodation` (object)
The products to order related to an accommodation
 - `data.accommodation.id` (integer)
A signed integer number that uniquely identifies an accommodation property. The full list can be obtained by calling `[accommodations/details](/demand/docs/open-api/demand-api/accommodations/accommodations/details)`.
 - `data.accommodation.currency` (object)
 - `data.accommodation.currency.accommodation` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
 - `data.accommodation.general\_policies` (object)

- `data.accommodation.general\_policies.payment` (object)
- `data.accommodation.general\_policies.payment.pay\_online\_now` (object | null)
- `data.accommodation.general\_policies.payment.pay\_online\_now.dates` (array)
Schedule specifying the instalments for paying the order for the "pay_online_now" option. For each entry in the schedule, a charge will be made at the time of that entry.
- `data.accommodation.general\_policies.payment.pay\_online\_now.dates.at` (string)
The date at which this instalment will be charged.
- `data.accommodation.general\_policies.payment.pay\_online\_now.dates.price` (object)
The price in both accommodation and booker currencies (booker might be null, if not requested)
- `data.accommodation.general\_policies.payment.pay\_online\_now.dates.price.accommodation\_currency` (number)
- `data.accommodation.general\_policies.payment.pay\_online\_now.method\_required` (boolean)
Whether a payment method is required for this payment timing.
- `data.accommodation.general\_policies.payment.pay\_online\_now.methods` (object)
The payment methods available for the payment timing selected.
- `data.accommodation.general\_policies.payment.pay\_online\_now.methods.airplus` (boolean)
Whether airplus can be used as a payment method for this order.
- `data.accommodation.general\_policies.payment.pay\_online\_now.methods.cards` (array)
The cards available to pay.
- `data.accommodation.general\_policies.payment.pay\_online\_now.methods.wallet` (boolean)
Whether wallet can be used as a payment method for this order.
- `data.accommodation.general\_policies.payment.pay\_online\_later` (object)
- `data.accommodation.general\_policies.payment.pay\_online\_later.dates` (array)
Schedule specifying the instalments for paying the order for this product for the "pay_online_later" option. For each entry in the schedule, a charge will be made at the time of that entry.
- `data.accommodation.general\_policies.payment.pay\_online\_later.method\_required` (boolean)
Whether a payment method is required for this payment timing.

- ``data.accommodation.general_policies.payment.pay_at_the_property`` (object)
- ``data.accommodation.general_policies.payment.pay_at_the_property.dates`` (array)
Schedule specifying the instalments for paying the order for this product for the "pay_at_the_property" option. For each entry in the schedule, a charge will be made at the time of that entry.
- ``data.accommodation.general_policies.payment.pay_at_the_property.method_required`` (boolean)
Whether a payment method is required for this payment timing.
- ``data.accommodation.price`` (object)
The price components of all the products selected summed.
- ``data.accommodation.price.base`` (object)
- ``data.accommodation.price.charges`` (array)
The sum of charges for all products selected, grouped by charge type.
- ``data.accommodation.price.charges.charge`` (integer)
A signed integer number that uniquely identifies an accommodation charge type. Examples of charges are: VAT, City Tax, etc. The full list can be obtained by calling `accommodations/constants`.
- ``data.accommodation.price.charges.condition`` (integer | null)
A signed integer number that uniquely identifies the condition ID. Find the full list in the Pricing guidelines.
- ``data.accommodation.price.charges.included_in`` (object)
Indicates where this charge is included
- ``data.accommodation.price.charges.included_in.display`` (boolean)
Indicates if this charge is included in the display price.
- ``data.accommodation.price.charges.included_in.chargeable_online`` (boolean)
Whether this charge is chargeable online or not. Not applicable to "pay_at_the_property" timing.
- ``data.accommodation.price.charges.total_amount`` (object)
The total price for this charge.
- ``data.accommodation.products`` (array)
- ``data.accommodation.products.id`` (string)
Unique ID of the product.
- ``data.accommodation.products.bundle`` (integer)
The bundle ID of the product comprising of value added products.

- ``data.accommodation.products.deal`` (object | null)
This specifies the deal tagging for the product.
- ``data.accommodation.products.deal.discount_percentage`` (integer)
Discount percentage of the applied deal.
- ``data.accommodation.products.deal.tags`` (array)
The tags of all the applied deals.
- ``data.accommodation.products.inventory`` (object)
- ``data.accommodation.products.inventory.third_party`` (boolean)
Indicates whether the product is facilitated by a third-party supplier.
- ``data.accommodation.products.inventory.type`` (string)
Type of inventory - either net or sell rates.
Enum: "net", "sell"
- ``data.accommodation.products.policies`` (object)
The policies for this product.
- ``data.accommodation.products.policies.cancellation`` (array)
The cancellation policy schedule for this product.
- ``data.accommodation.products.policies.cancellation.from`` (any)
The time from which this cancellation fee applies.
- ``data.accommodation.products.policies.meal_plan`` (object)
The meal plan policy for this product.
- ``data.accommodation.products.policies.meal_plan.meals`` (array)
The meals included in the meal plan.
- ``data.accommodation.products.policies.meal_plan.plan`` (string)
The meal plan included in this product.
Enum: "all_inclusive", "breakfast_included", "full_board", "half_board", "no_plan"
- ``data.accommodation.products.price`` (object)
Contains the price components of an accommodation product. The 'base', 'display', 'chargeable_online' prices, and 'charges' are returned only when explicitly requested using `extras=extra_charges`.
- ``data.accommodation.products.price.base`` (object)
The base price. It does not include any extra charges.
- ``data.accommodation.products.price.charges`` (array)
The charge breakdown. Includes taxes and fees.

- ``data.accommodation.products.price.charges.included_in`` (object)
Indicates where this charge is included
- ``data.accommodation.products.price.charges.mode`` (string)
The mode of this charge. Determines how the price is calculated.
Enum: "calculated_amount", "incalculable", "percentage", "per_day", "per_night", "per_person_per_day", "per_person_per_night", "per_person_per_stay", "per_stay"
- ``data.accommodation.products.price.charges.percentage`` (number)
The percentage of 'base' that this charge amounts to. Only applicable when 'mode' is 'percentage'.
- ``data.accommodation.products.price.charges.unit_amount`` (object)
The price per unit for this charge. Only applicable when 'mode' is 'per_day', 'per_night', 'per_person_per_day', 'per_person_per_night', or 'per_person_per_stay'.
- ``data.accommodation.products.price.chargeable_online`` (object)
The amount collected by Booking.com from the Virtual Credit Cards (VCCs) when using online payment methods (e.g., `pay_online_now`, `pay_online_later`). Equivalent to ``base + charges`` where ``included_in.chargeable_online=true``. Returns ``null`` for agency-model properties where Booking.com does not process payments.
- ``data.accommodation.products.price.display`` (object)
The display price that must be shown to the traveller in accordance with local booker protection laws. This price includes the base accommodation cost and all charges that are legally required to be part of the displayed amount. Equivalent to `base + charges` where `included_in.display=true`.
- ``data.accommodation.products.price.total`` (object)
The total price. Includes all extra charges.
- ``data.accommodation.products.room`` (string | null)
A unique identifier for a specific room within an accommodation property. You can retrieve the full list of available room IDs by calling `[accommodations/details]/(demand/docs/open-api/demand-api/accommodations/accommodations/details)`.
- ``data.accommodation.products.occupancy_mismatch`` (object)
Represents the distribution of requested guests relative to the product's capacity. Includes the guests that can be accommodated (allocated) and those that cannot (unallocated).
Example:

```
{
  "allocated": {
    "number_of_adults": 1,
    "children": null
  },
  "unallocated": {
    "number_of_adults": 1,
    "children": null
  }
}
```
- ``data.accommodation.products.occupancy_mismatch.allocated`` (object, required)
Describes an occupancy in terms of number of adults and children's ages.

- ``data.accommodation.products.occupancy_mismatch.allocated.number_of_adults`` (integer, required)
The number of adults.
- ``data.accommodation.products.occupancy_mismatch.allocated.children`` (array | null, required)
Contains the ages of the accommodated children. Null if there are no children.
- ``data.car`` (object)
- ``data.car.offer`` (integer)
This ID identifies the car rental offer and its associated policies. Include it when calling the `/cars/availability` endpoint.
- ``data.car.currency`` (object)
The currencies requested.
- ``data.car.price`` (object)
Summary of all pricing components for the selected car products.
- ``data.car.price.base`` (object)
Price amounts in both display and local currencies.
- ``data.car.price.base.display`` (object)
Monetary amount and currency details.
- ``data.car.price.base.display.value`` (number, required)
Numeric amount for the charge.
Example: 129.99
- ``data.car.price.base.display.timing`` (string)
When the payment is due (for example, `'pay_at_pickup'` or `'pay_online_now'`).
- ``data.car.price.extra_charges`` (object)
Breakdown of conditional and non-conditional extra charges.
- ``data.car.price.extra_charges.conditional`` (array)
Charges that might apply under a specific condition.
- ``data.car.price.extra_charges.conditional.charge_type`` (string)
Identifier for the charge type applied to the rental.
- ``data.car.price.extra_charges.non_conditional`` (array)
All non-conditional charges that will necessarily be paid
- ``data.car.price.products`` (array)
List of selected additional products with their pricing and details.

- ``data.car.price.products.id`` (string)

The unique identifier of the extra.

- ``data.car.price.products.type`` (string)

Specifies the type of optional extra or service associated with the vehicle. For example, `gps` for a navigation system, `baby_seat` for a child seat, or `wifi_router` for mobile internet. Some values may represent similar extras because suppliers use different naming conventions for the same or comparable products.

Enum: `"additional_driver"`, `"baby_seat"`, `"bluetooth_handsfree_kit"`, `"booster_seat"`, `"child_booster_seat"`, `"child_seat"`, `"child_seat_isofix"`, `"etc_card_electronic_toll_collection_card"`, `"excess_protection"`, `"fast_track"`, `"gps"`, `"infant_seat"`, `"luggage_rack"`, `"personal_travel_assistant"`, `"queue_jump"`, `"roof_rack"`, `"ski_box"`, `"ski_rack"`, `"skierized_equipment"`, `"snow_chains"`, `"snow_tyres"`, `"wifi_mobile"`, `"wifi_router"`

- ``data.car.price.products.selected_quantity`` (integer)

The number of units selected for this product.

- ``data.car.price.products.mode`` (string)

Defines how the product price is calculated. This determines whether pricing is applied per unit, per day, or for the full rental period.

Enum: `"each_per_day"`, `"per_day"`, `"each_per_rental"`, `"per_rental"`

- ``data.car.price.products.price`` (object)

Pricing details for this product.

- ``data.car.policies`` (object)

The policies that apply to this car.

- ``data.car.policies.cancellation`` (object)

The cancellation policy that applies to this product.

- ``data.car.policies.cancellation.details`` (object | null)

Conditions under which free cancellation applies. For example: `\n- duration='PT48H' and context='before_pickup'` means 'Free cancellation up to 48 hours before pickup'. `\n- duration='P7D' and context='within_given_time_period_of_booking'` means 'Free cancellation within 7 days of booking'.

- ``data.car.policies.cancellation.details.context`` (string)

The context in which the cancellation policy applies. For example `'before_pickup'`

Enum: `"before_pickup"`, `"within_given_time_period_of_booking"`

- ``data.car.policies.cancellation.details.duration`` (string)

Duration during which free cancellation is available (ISO 8601 duration format, e.g. `P2D` = 2 days).

- ``data.car.policies.cancellation.type`` (string)

Cancellation policy type (e.g. `'free_cancellation'` or `'non-refundable'`).

Enum: "free_cancellation", "non-refundable"

- `data.car.policies.damage\_excess` (object)

The maximum amount a traveller may be charged for damages to the car during the rental period, as specified by the rental agreement.

- `data.car.policies.deposit` (object)

The amount of money that will be temporarily pre-authorised or blocked on the traveller's credit card at the rental location as a security deposit, to cover potential damage or extra charges.

- `data.car.policies.fuel\_policy` (string)

The fuel policy that applies to this car.

Enum: "return_same", "return_same_or_prepay_no_refunds", "return_same_preauth", "free_tank", "prepay_no_refunds", "prepay_part_refunds", "prepay_refunds", "unknown"

- `data.car.policies.mileage` (object)

Mileage policy for the selected car rental.

- `data.car.policies.mileage.distance\_limit` (number | null)

Maximum distance allowed before additional fees apply.

Example: 300

- `data.car.policies.mileage.distance\_unit` (string)

The unit of measurement for the distance limit. For example 'km' or 'miles'.

Enum: "kilometers", "miles"

- `data.car.policies.mileage.type` (string)

The type of mileage policy applied.

Enum: "limited", "unlimited"

- `data.car.policies.payment` (object)

Payment policy details for the car rental, including key dates and amounts.

- `data.car.policies.payment.dates` (array)

- `data.car.policies.payment.dates.at` (string)

Date when the payment is due (ISO 8601 format).

Example: 2025-11-01

- `data.car.policies.theft\_excess` (object)

The maximum amount a traveller may be charged in the event of car theft during the rental period, as outlined in the rental agreement.

- `data.car.insurance` (object | null)

Detailed third-party insurance quote for this car rental.

Returned when insurance is available for the selected offer and a valid quote_reference is provided.

If insurance is not available, not selected, or cannot be resolved for the current offer, this field is null.

This object represents a bookable insurance product and includes pricing, coverage, and policy documentation.

- ``data.car.insurance.quote_reference`` (string, required)
Unique reference for this insurance quote. Expires after 90 minutes.
- ``data.car.insurance.name`` (string, required)
The display name of the insurance product.
- ``data.car.insurance.id`` (string, required)
The identifier for the type of insurance product.
- ``data.car.insurance.coverage_amount`` (object)
The maximum coverage amount provided by the insurance product.
- ``data.car.insurance.documents`` (array, required)
Legal documents for this insurance product. Always returned when the insurance object is present, and always contains the ``policy_document`` entry. The ``ipid`` entry is only included when an IPID applies (EEA and UK countries) and is available in the requested language.
- ``data.car.insurance.documents.name`` (string, required)
The insurance document type.
Enum: "policy_document", "ipid"
- ``data.car.insurance.documents.url`` (string, required)
URL of the insurance document.
- ``data.order_token`` (string)
A token containing the necessary data to be used on subsequent requests to [orders/create]. This token expires 15 minutes after it is issued.

Response 400 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- ``errors`` (array, required)
- ``errors.id`` (string, required)
- ``errors.message`` (string, required)

Response 500 fields (application/json):

- ``request_id`` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Create an order

Use this endpoint to create and confirm an order using a valid order token and the required payment information.

Endpoint: POST /orders/create

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `accommodation` (object)
Additional information related to the accommodation order. Only one travel service object can be included in a request.
- `accommodation.label` (string)
Custom string defined by the partner to track attribution throughout the booking journey. Use a consistent, parseable format (e.g. brand-market_platform-channel_campaign) to encode campaign, traffic source, platform, language, or other identifiers. Recommended for accurate reporting and analytics. See the [Labels and attributions guide](/demand/docs/orders-api/labels-attributions) for more details.
- `accommodation.products` (array)
List of accommodation products returned in /orders/preview that should be included in this order.
- `accommodation.products.id` (string, required)
Unique ID of the product.
- `accommodation.products.bed\_configuration` (string)
Bed configuration ID to select for this product. `Please note that it can not be guaranteed that the selected bed\_configuration will be available.`
- `accommodation.products.guests` (array)
The guest details for this product.
- `accommodation.products.guests.email` (string, required)
The email address of the guest.
- `accommodation.products.guests.name` (string, required)
The name of the guest.
- `accommodation.remarks` (object)

Optional remarks from the guest.

- `accommodation.remarks.estimated\_arrival\_time` (object)

Estimated arrival time of the guests.

- `accommodation.remarks.estimated\_arrival\_time.hour` (integer, required)

Approximate hour of arrival to the hotel. Allowed values are from 0 to 23. This time should be within the hotel reception hours, or will be ignored otherwise with a warning will be appended to special_requests.

- `accommodation.remarks.estimated\_arrival\_time.next\_day` (boolean)

Set this to true, if the hour selected is for the day after checkin.

- `accommodation.remarks.special\_requests` (string)

Optional comments or requests from the guest. Special requests cannot be guaranteed – but the property will do its best to meet your needs.

- `booker` (object, required)

The booker's information.

- `booker.address` (object, required)

The booker's address to be used for creating this order. All fields of this object are required if the /accommodations/details endpoint indicates that the booker's address is necessary by returning booker_address_required=true.

- `booker.address.address\_line` (string)

The details of this address.

- `booker.address.city` (string)

The city for this address.

- `booker.address.country` (string, required)

A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:

https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling common/locations/countries.

Example: nl

- `booker.address.post\_code` (string)

Post code for this address.

- `booker.company` (string)

The booker's company name.

- `booker.email` (string, required)

The booker's email address.

- `booker.language` (string)

A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. **Note:** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the `/common/languages`` endpoint in the same Demand API version you are using.

Example: en-us

- ``booker.name`` (object, required)
The name of the booker.
- ``booker.name.first_name`` (string, required)
- ``booker.name.last_name`` (string, required)
- ``booker.telephone`` (string, required)
The booker's telephone number.
- ``order_token`` (string, required)
A token containing the necessary data to be used for creating this order.
- ``payment`` (object, required)
Payment related information for the order.
- ``payment.airplus`` (object)
All information related to airplus payment. ``This is required if airplus is selected as payment method.``
- ``payment.airplus.dbi`` (object)
Descriptive billing information(dbi) details to pass to AirPlus.
- ``payment.airplus.dbi.accounting_code`` (string)
Accounting code to pass in descriptive billing information.
- ``payment.airplus.dbi.accounting_unit`` (string)
Accounting unit to pass in descriptive billing information.
- ``payment.airplus.dbi.cost_centre`` (string)
Cost centre to pass in descriptive billing information.
- ``payment.airplus.dbi.department_code`` (string)
Department code to pass in descriptive billing information.
- ``payment.airplus.dbi.employee_number`` (string)
Employee number to pass in descriptive billing information.
- ``payment.airplus.dbi.internal_account`` (string)
Internal account to pass in descriptive billing information.

- `payment.airplus.dbi.order\_number` (string)
Order number to pass in descriptive billing information.
- `payment.airplus.dbi.project\_number` (string)
Project number to pass in descriptive billing information.
- `payment.airplus.number` (string, required)
12 digit Airplus Number.
- `payment.business\_information` (object)
All business related information for billing and authorisation form. This must be included for the payments that require authorisation form.
- `payment.business\_information.authorisation\_form` (object)
Information that is relevant for generating an authorisation form.
- `payment.business\_information.authorisation\_form.chargeable\_items` (array)
Items which can be charged using a provided virtual credit card.
- `payment.business\_information.billing` (object)
All information to be used in the invoice.
- `payment.business\_information.billing.address` (object)
The address to bill this reservation
- `payment.business\_information.billing.address.address\_line` (string)
The details of this address.
- `payment.business\_information.billing.address.city` (string)
The city for this address.
- `payment.business\_information.billing.address.post\_code` (string)
Post code for this address.
- `payment.business\_information.billing.email` (string, required)
Email to send the invoice to.
- `payment.business\_information.billing.vat` (string, required)
VAT number to be used in the invoice.
- `payment.business\_information.company` (string, required)
Company that will issue an authorisation form for the virtual credit card and used in the invoice.
- `payment.card` (object)
Card information for executing the payment.
- `payment.card.authentication` (object)

Card authentication information for executing the payment.

- `payment.card.cardholder` (string, required)
Name of the cardholder.
- `payment.card.cvc` (string, required)
3 or 4 digits card validation code (CVC) of this card.
- `payment.card.expiry\_date` (string, required)
Expiry date of the card. Format: YYYY-MM
- `payment.card.number` (string, required)
Number of the card.
- `payment.card.subtype` (string)
Indicates a special processing subtype for cards whose network behaviour cannot be determined reliably from the card number alone.

Use this field for supported co-branded or specialised card programmes (such as UnionPay co-branded cards) to ensure correct payment routing and authorisation handling.

Omit for standard Visa, Mastercard, or UnionPay cards

Enum: "unionpay_cobrand"

- `payment.include\_receipt` (boolean)
This is used to determine whether to include payment `receipt\_url` in the response or not.
- `payment.method` (string)
The payment method to be used for this order.
Enum: "airplus", "card", "wallet"
- `payment.timing` (string, required)
The payment timing for this order. Use the value returned in the preview response. The available values depend on the travel service.
Enum: "pay_at_pickup", "pay_at_the_property", "pay_online_later", "pay_online_now", "pay_partial_online_now"

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (any)
- `data.order` (string)
ID for this order.
- `data.accommodation` (object, required)
All accommodation related information for this order.

- ``data.accommodation.pincod` (string)`
Pincod for this accommodation order.
- ``data.accommodation.reservation` (string)`
Reservation ID for this accommodation order.
- ``data.accommodation.third_party_inventory` (object)`
- ``data.accommodation.third_party_inventory.checkin_number` (string)`
The number required at the time of check-in. It allows guests to confirm their order at the accommodation.
Example: 473026811
- ``data.accommodation.third_party_inventory.confirmation_number` (string)`
The confirmation number, when used in conjunction with the pincod, helps verify the customer's order and facilitates efficient support during inquiries or troubleshooting.
Example: 12365478936925814787
- ``data.payment` (object)`
All payment related information for this order.
- ``data.payment.authorisation_form_url` (string)`
Link to a virtual credit card's authorisation form, valid for 7 minutes from issue. `This will only be added if the request has authorisation\_form.`
Example:
https://secure-admin.booking.com/airplus_auth_form_pdf.html?token=AA&lang=en
- ``data.payment.receipt_url` (string)`
Link to the payment receipt of the order. `This will only be added if include\_receipt is true.`
Example:
https://secure.booking.com/payment_receipt.html?bn=00000000000&pincod=0000&lang=en
- ``data.car` (object, required)`
All car rental related information for this order. This field is only present for car rental orders.
- ``data.car.reservation_id` (string)`
The reservation ID (booking reference) for this car rental order. Use this identifier to retrieve the full, up-to-date booking details and status via the ``/orders/details/cars/live`` endpoint.
Example: 89423719
- ``data.car.status` (string)`
This endpoint always returns "Processing", indicating that the booking request has been accepted and is being processed asynchronously. Retrieve the order details using `/orders/details/cars/live` to obtain its latest status.

Enum: "Processing"

Response 400 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 403 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 409 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)
- `errors.reservation` (string)
The reservation ID associated with the duplicated request. Only returned when a reservation already exists.

Response 500 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)

- `errors.message` (string, required)

Orders details

Use this endpoint to retrieve detailed information about existing orders across supported travel services. Use it to synchronise internal systems, monitor booking updates, and generate reporting or analytics across travel services.

You can query orders using one of the following filter types:

- **Creation** or **update date** — retrieve orders created or updated within a 7-day range.
- **Travel dates** — filter by service start or end date (up to 7 days).
- **Order** or **reservation ID** — fetch details for specific orders.

Notes:

- 'currency' is a required field and must be a **three-letter ISO 4217 code**.
- 'services' restricts results to one or more travel services: accommodations, cars, flights, attractions, or taxis.

This endpoint is ideal for:

- Displaying booking details in partner dashboards or traveller confirmation pages.
- Retrieving payment information for invoicing or reconciliation workflows.
- Performing reporting, or analytics across all travel services.

See the [\[Reporting and reconciliation guide\]\(/demand/docs/orders-api/order-details\)](#) for more details.

Endpoint: POST /orders/details

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `updated` (object, required)
Filter orders by their "created" or "updated" timestamp. The maximum time range is 7 days.
- `updated.from` (string, required)
ISO 8601 timestamp in UTC. Start of the time range (inclusive). The value should be within last 1 year.
- `updated.to` (string)
ISO 8601 timestamp in UTC, which indicates the timestamp till which you want to filter orders to (inclusive). It has to be greater than or equal to "from".
- `currency` (string | null, required)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling [common/payments/currencies](#).

Example: EUR

- ``maximum_results`` (integer)
The maximum number of results to return.
- ``sort`` (object)
The sorting parameters for the response.
- ``sort.by`` (string, required)
The way to sort your results.
Enum: "created", "updated"
- ``sort.direction`` (string, required)
The direction you wish for your sort.by parameter to be sorted in.
Enum: "ascending", "descending"
- ``extras`` (array)
Input parameter to request for additional information about this order.
- ``services`` (array)
Restricts results to one or more travel services. If omitted, behaviour depends on the filter used. Identifier-based requests return accommodation orders only, while date-based requests return all supported travel services available to the partner.
- ``start`` (object, required)
Filter orders by date range, covering the "start" and "end" date. The maximum date range is up to 7 days (1 week).
- ``start.from`` (string, required)
ISO 8601 date in "YYYY-MM-DD" format. Start of the date range (inclusive). You can filter orders up to 1 year in the past and 500 days in the future.
Example: 2026-06-01
- ``start.to`` (string)
ISO 8601 date in "YYYY-MM-DD" format. End of the date range (inclusive). It has to be greater than or equal to "from". It uses "from" value as default.
Example: 2026-06-03
- ``orders`` (array, required)
List of order IDs for which details should be returned.
- ``reservations`` (array, required)
List of reservation IDs for which details should be returned.
- ``page`` (string, required)
Pagination token used to retrieve the next page of results. Obtained from ``next_page``.

Response 200 fields (application/json):

- `data` (array)
- `data.id` (string)
Unique identifier of the order.
- `data.accommodations` (object)
- `data.accommodations.inventory` (object)
- `data.accommodations.inventory.third\_party` (boolean)
Indicates whether the product is facilitated by a third-party supplier.
- `data.accommodations.inventory.type` (string)
Type of inventory - either net or sell rates.
Enum: "net", "sell"
- `data.accommodations.location` (object)
Accommodation location.
- `data.accommodations.location.address` (string)
Accommodation address.
- `data.accommodations.location.city` (integer)
A signed integer number that uniquely identifies a city. The full list can be obtained by calling `common/locations/cities`.
- `data.accommodations.location.country` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here: https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling `common/locations/countries`.
Example: nl
- `data.accommodations.name` (string)
Accommodation name.
- `data.accommodations.number\_of\_guests` (number)
Number of guests included in the accommodation reservation.
- `data.accommodations.reservation` (string)
This is the reservation id for the accommodation in this order.
- `data.accommodations.stay\_probability` (number | null)
Probability that the traveller will complete the stay, based on internal calculations. A score of 0 indicates the highest likelihood of cancellation, while a score of 1 represents the highest likelihood of the traveller staying. Note: This score may not always be available.

- ``data.affiliate`` (integer)
The affiliate id used for this order.
- ``data.attractions`` (object)
Details of an attraction included in this order.
- ``data.attractions.name`` (string)
The name of the attraction.
Example: Eiffel Tower Guided Tour
- ``data.attractions.location`` (object)
Location details of the attraction.
- ``data.attractions.location.city`` (string)
The city where the attraction is located.
- ``data.attractions.reservation`` (string)
This is the reservation id for the attraction in this order.
- ``data.booker`` (object)
The booker's information.
- ``data.booker.address`` (object)
The booker's address for showing the best price for that user and obeying laws regarding the display of taxes and fees.
- ``data.booker.address.city`` (string | null)
The city for this address.
- ``data.booker.address.country`` (string | null)
The country for this address.
- ``data.booker.email`` (string | null)
The booker's email address.
- ``data.booker.language`` (string)
A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. ****Note:**** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the ``/common/languages`` endpoint in the same Demand API version you are using.
Example: en-us
- ``data.booker.name`` (object)
The name of the booker.
- ``data.booker.name.first_name`` (string | null)

- `data.booker.name.last\_name` (string | null)
- `data.booker.platform` (string)
The booker platform for showing the platform based deals and prices.
Enum: "app", "desktop", "mobile_browser", "tablet", "unknown"
- `data.booker.telephone` (string | null)
The booker's telephone number.
- `data.booker.travel\_purpose` (string | null)
The travel purpose of the booker.
Enum: "business", "leisure", "unknown"
- `data.cars` (object)
- `data.cars.dropoff\_location` (object)
- `data.cars.dropoff\_location.city` (string)
The city where the dropoff location is.
- `data.cars.payment` (object)
The payment policy that applies to this car rental.
- `data.cars.payment.timing` (string, required)
Indicates when payment for this car rental is expected.

Use this field to determine whether prepayment is required or if payment will occur at pickup.
Enum: "pay_online_now", "pay_at_pickup", "pay_partial_online_now", "unknown"

- `data.cars.pickup\_location` (object)
- `data.cars.pickup\_location.city` (string)
The city where the pickup location is.
- `data.cars.reservation` (string)
This is the reservation id for the car in this order.
- `data.created` (string)
Order creation time. For taxi orders with multiple legs, this is the earliest creation date among all legs.
- `data.commission` (object)
Commission details for the partner for a given order. For taxi orders with multiple legs, amounts are the sum across all legs.
- `data.commission.actual\_commission\_amount` (object | null)
The amount in both product and booker currencies (booker might be null, if not requested)

- ``data.commission.actual_commission_amount.booker_currency`` (number)
- ``data.commission.actual_percentage`` (number | null)
Actual commission percentage for this order (``null`` if not yet available). For taxi orders with multiple legs, this is the percentage of legs.
- ``data.currencies`` (object)
Product and booker currencies. ``booker`` is ``null`` if it was not specified in the request.
- ``data.currencies.booker`` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
- ``data.end`` (string)
The date when this order ends. Must be later than ``start``. For taxi orders with multiple legs, this is the latest pickup time among all legs.
- ``data.flights`` (object)
Flight details for this order.
- ``data.flights.itineraries`` (array)
List of flight itineraries included in the order.
- ``data.flights.itineraries.arrival`` (object)
 - ``data.flights.itineraries.arrival.airport`` (string)
A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `[common/locations/airports](#/common/locations/airports)`.
Example: AMS
 - ``data.flights.itineraries.arrival.date_time`` (string)
Date time of the itinerary.
Example: 2025-09-17T18:45:00Z
 - ``data.flights.reservation`` (string)
This is the reservation id for flight in this order.
- ``data.label`` (string | null)
Custom string defined by the partner to track attribution throughout the booking journey. Use a consistent, machine-parseable format (for example, ``brand-market_platform-channel_campaign``) to encode campaign, traffic source, platform, language, or other identifiers. Recommended for reliable reporting and analytics. See the [\[Labels and attributions guide\]\(/demand/docs/orders-api/labels-attributions\)](#) for more details.
- ``data.loyalty_reward`` (array | null)
Details of the loyalty rewards associated with this order.

- `data.loyalty\_reward.amount` (number)
Reward amount expressed in the units defined by the reward type (for example, cash, miles, or points).
- `data.loyalty\_reward.eligible` (boolean)
Whether the order is eligible for the reward.
- `data.loyalty\_reward.fulfillment\_at` (string)
Date and time at which the reward should be fulfilled.
- `data.loyalty\_reward.fulfillment\_by` (string)
Entity responsible for fulfilling the reward.
Enum: "partner", "booking.com"
- `data.loyalty\_reward.loyalty\_data` (array | null)
Loyalty information required to fulfil the reward.
- `data.loyalty\_reward.loyalty\_data.name` (string)
Name of the loyalty data.
- `data.loyalty\_reward.loyalty\_data.value` (string)
Value of the loyalty data.
- `data.loyalty\_reward.type` (string)
Type of reward.
Enum: "cash", "mile", "point", "voucher", "voucher_money", "voucher_subscription", "voucher_percentage"
- `data.payment` (object)
The payment details of this order.
- `data.payment.accommodations` (object | null)
The accommodation specific payment details of this order.
- `data.payment.accommodations.authorisation\_form` (string | null)
Link to the authorisation form of the order.
Example:
https://secure-admin.booking.com/airplus_auth_form_pdf.html?token=AAAA&lang=en-us
- `data.payment.accommodations.receipt\_url` (string | null)
Link to the payment receipt of the order. `This will only be added if the payment is already charged.`
Example:
https://secure.booking.com/payment_receipt.html?bn=00000000000&pincode=0000&lang=en
- `data.payment.accommodations.reservation` (string)
Reservation ID for this accommodation order.

- ``data.payment.method`` (string)
The payment method used for this order.
Enum: "airplus", "card", "wallet"
- ``data.payment.paid`` (array)
- ``data.payment.paid.amount`` (number)
Amount of the transaction.
- ``data.payment.paid.at`` (string)
Time of the transaction.
- ``data.payment.paid.transaction_currency`` (string)
Currency in which the transaction took place.
- ``data.payment.timing`` (string)
The payment timing of this order.
Enum: "pay_at_the_property", "pay_online_later", "pay_online_now"
- ``data.price`` (object)
The price components of this order. For taxi orders with multiple legs, amounts are the sum across all legs.
- ``data.start`` (string)
The date when this order starts. For taxi orders with multiple legs, this is the earliest pickup time among all legs.
- ``data.status`` (string)
Overall status of the order. Not all status values apply to every travel service.
Enum: "booked", "cancelled", "cancelled_by_guest", "cancelled_by_accommodation", "stayed", "no_show", "unknown"
- ``data.taxis`` (array | null)
List of taxi legs included in this order. Each item represents a separate taxi leg (e.g., outbound and return trips).
- ``data.taxis.commission`` (object)
Commission details for this taxi leg.
- ``data.taxis.created`` (string)
The creation time of this taxi leg.
- ``data.taxis.currencies`` (object)
Product and booker currencies for this taxi leg.
- ``data.taxis.dropoff_location`` (object)
Details of the dropoff location for this taxi leg.

- ``data.taxis.dropoff_location.address`` (string)
The full address of the dropoff location.
Example: Stationsplein 9, 3511 CE Utrecht
- ``data.taxis.dropoff_location.city`` (string)
The city of the dropoff location.
Example: Utrecht
- ``data.taxis.end`` (string)
The end date and time of this taxi leg.
- ``data.taxis.leg`` (string)
Unique identifier for this taxi leg within the order.
Example: 607244787653565
- ``data.taxis.pickup_location`` (object)
Details of the pickup location for this taxi leg.
- ``data.taxis.pickup_location.address`` (string)
The full address of the pickup location.
Example: Amstel 51, 1018 EH Amsterdam, Netherlands
- ``data.taxis.pickup_location.city`` (string)
The city of the pickup location.
Example: Amsterdam
- ``data.taxis.price`` (object)
The price components for this taxi leg.
- ``data.taxis.reservation`` (string)
The reservation identifier shared by all taxi legs belonging to the same taxi order.
Example: 916957580
- ``data.taxis.start`` (string)
The start date and time of this taxi leg.
- ``data.taxis.status`` (string)
Enum: "booked", "cancelled", "cancelled_by_accommodation", "cancelled_by_guest", "no_show", "stayed"
- ``data.taxis.updated`` (string)
The last update time of this taxi leg.
- ``data.updated`` (string)
Time the order was last updated. For taxi orders with multiple legs, this is the latest last modified time among all legs.

- ``metadata`` (object)

Metadata about the request.

- ``metadata.next_page`` (string)

Indicates that more results are available. Use this pagination token to retrieve the next page of results (via parameter ``page``).

- ``metadata.total_results`` (integer)

The total number of results available.

- ``request_id`` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

Orders with accommodation details

Use this endpoint to retrieve detailed information for one or more accommodation orders. You can request order details either by **reservation** or **order** ID depending on your integration.

- The response includes all key information for each order, including booking status, pricing, commission, cancellation details, and optional extras.
- Results are sorted by order creation date in descending order, with the most recently booked orders listed first.

Endpoint: POST /orders/details/accommodations

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `orders` (array, required)
List of order IDs for which details should be returned.
- `currency` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
- `extras` (array)
Input parameter to request for additional information about the accommodation order. It should be passed as a JSON array with one or more items.
- `language` (string)
A [IETF language tag code](https://en.wikipedia.org/wiki/IETF_language_tag) that uniquely identifies a supported human language or dialect. **Note:** Demand API only accepts lowercase for the language codes. Examples: "nl" for Dutch/Nederlands or "en-us" for English (US). To retrieve the full list of supported languages, call the `/common/languages` endpoint in the same Demand API version you are using.
Example: en-us
- `reservations` (array, required)

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.

- `data` (array)
- `data.id` (string)
Order ID for this accommodation order.
- `data.accommodation` (integer)
Accommodation ID for this order.
- `data.accommodation\_details` (object)
Accommodation details for this accommodation order (via 'extras=accommodation_details').
- `data.accommodation\_details.email` (string)
Accommodation email.
- `data.accommodation\_details.location` (object)
Accommodation location.
- `data.accommodation\_details.location.address` (string)
Accommodation address.
- `data.accommodation\_details.location.city` (integer)
Accommodation city_id.
- `data.accommodation\_details.location.coordinates` (object)
Accommodation coordinates.
- `data.accommodation\_details.location.coordinates.latitude` (number)
Accommodation latitude coordinate.
- `data.accommodation\_details.location.coordinates.longitude` (number)
Accommodation longitude coordinate.
- `data.accommodation\_details.location.country` (string)
A two-letter code that uniquely identifies a country. This code is defined by the ISO 3166-1 alpha-2 standard (ISO2) as described here:
https://en.wikipedia.org/wiki/ISO_3166-1_alpha-2. The full list can be obtained by calling common/locations/countries.
Example: nl
- `data.accommodation\_details.location.post\_code` (string)
Accommodation post code.
- `data.accommodation\_details.name` (string)
Accommodation name.
- `data.accommodation\_details.telephone` (string)
Accommodation telephone.

- ``data.accommodation_order_references`` (array)
List of additional accommodation order references generated by the accommodation.
- ``data.booker`` (object)
The booker's information.
- ``data.booker.external_account`` (string)
This is a unique identifier that represents the account provided by the partner in Booking.com settings. This field is used to link a specific accommodation order to the corresponding account so is possible to accurately allocate loyalty points or other benefits in the partner's loyalty and rewards programs.
- ``data.booker.platform`` (string)
The booker platform for showing the platform based deals and prices.
Enum: "app", "desktop", "mobile_browser", "tablet", "unknown"
- ``data.cancellation_details`` (object | null)
Fee charged for cancellation and the datetime at which the cancellation occurred. (If not cancelled, value is null).
- ``data.cancellation_details.at`` (string)
Cancellation datetime.
- ``data.cancellation_details.fee`` (object)
The price in both accommodation and booker currencies (booker might be null, if not requested)
- ``data.cancellation_details.fee.accommodation_currency`` (number)
- ``data.checkin`` (string)
The checkin date of this accommodation order.
- ``data.checkout`` (string)
The checkout date of this accommodation order.
- ``data.commission`` (object)
Commission details for the partner for this accommodation order.
- ``data.commission.actual_percentage`` (number | null)
Actual commission percentage for this accommodation order (``null`` if value is not yet available).
- ``data.credit_slip_number`` (string | null)
The financial document issued by Booking.com to partners, detailing the payout amount and the associated transaction information. It serves as a formal record of the payment, ensuring transparency and facilitating accurate financial tracking for both parties.

- `data.currency` (object)

Accommodation and booker currencies (booker will be `null`, if the request did not specify the currency).

- `data.currency.accommodation` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.

Example: EUR

- `data.inventory` (object)

- `data.inventory.third\_party` (boolean)

Indicates whether the product is facilitated by a third-party supplier.

- `data.inventory.type` (string)

Type of inventory - either net or sell rates.

Enum: "net", "sell"

- `data.key\_collection\_information` (array | null)

- `data.key\_collection\_information.additional\_instructions` (string)

Free-text instructions that provide additional context or details about the key collection or check-in process, such as access codes, entry procedures, or contact information.

- `data.key\_collection\_information.alternate\_location` (object)

An alternate location where guests can collect the key, if applicable. Display this location in addition to the primary key collection information. This location may be provided even when the primary key collection location is at the accommodation property.

- `data.key\_collection\_information.alternate\_location.address` (string)

- `data.key\_collection\_information.alternate\_location.city` (string)

- `data.key\_collection\_information.alternate\_location.postal\_code` (string)

- `data.key\_collection\_information.checkin\_method` (string)

An enumeration that describes the check-in process and key collection method. This is typically applicable to non-hotel accommodations (such as houses or apartments) that do not have a 24-hour front desk.

Enum: "door_code", "lock_box", "reception", "secret_spot", "someone_will_meet", "unknown"

- `data.key\_collection\_information.key\_location` (string)

Location of the key to access this accommodation property.

Enum: "at_the_property", "different_place", "unknown"

- `data.label` (string | null)

Label provided when the accommodation order was created.

- `data.pin\_code` (string)
The pin code of this accommodation order.
- `data.price` (object | null)
The price components of this accommodation order.
- `data.products` (array)
- `data.products.allocation` (object)
The allocation of guests, adults and children for this product.
- `data.products.allocation.guests` (integer)
The number of guests reserved for this product.
- `data.products.allocation.adults` (integer | null)
The number of adults reserved for this product.
- `data.products.allocation.children` (array)
The list of ages of all children reserved for this product.
- `data.products.bundle` (object)
A bundle attached to the reservation that includes information about the value-added service in the specified language.
- `data.products.bundle.id` (integer)
Bundle identifier
- `data.products.bundle.value\_adds` (array)
- `data.products.bundle.value\_adds.type` (string)
Identifies the type of value-added benefit included in the bundle, such as complimentary services, monetary credits, percentage discounts, or experiential amenities. Enum values encode how the benefit is applied, including time scope (per day or per stay) and unit scope (per room or per adult).
Enum: "parking", "food_drink_credit_per_day_per_room", "food_drink_credit_per_day_per_adult", "property_credit_per_day_per_room", "food_drink_credit_per_stay_per_adult", "food_drink_credit_per_stay_per_room", "property_credit_per_day_per_adult", "property_credit_per_stay_per_adult", "property_credit_per_stay_per_room", "food_drink_discount", "property_discount", "early_checkin", "late_checkout", "late_checkin", "spa_daily", "spa_hourly", "spa_massage", "high_speed_internet", "airport_transfer", "safari_game_drive", "safari_walk", "pets_stay", "bottle_of_wine", "bottle_of_champagne", "park_sleep_fly"
- `data.products.bundle.value\_adds.description` (array)
Translated descriptive text in the requested language.
- `data.products.guests` (array)

The guest details for this product.

- `data.products.guests.email` (string | null)

The email address of the guest.

- `data.products.guests.name` (string)

The name of the guest.

- `data.products.policies` (object)

The policies for this product. Requires `{ "extras": ["policies"] }`.

- `data.products.policies.cancellation` (array)

The cancellation policy schedule for this product.

- `data.products.policies.cancellation.from` (any)

The time from which this cancellation fee applies.

- `data.products.policies.meal\_plan` (object)

The meal plan policy for this product.

- `data.products.policies.meal\_plan.meals` (array)

The meals included in the meal plan.

- `data.products.policies.meal\_plan.plan` (string)

The meal plan included in this product.

Enum: "all_inclusive", "breakfast_included", "full_board", "half_board", "no_plan"

- `data.products.policies.smoking\_preference` (string | null)

Smoking Preference for this product.

Enum: "smoking", "non-smoking"

- `data.products.price` (object)

The price components of this product. 'base', 'display', and 'charges' are returned only when explicitly requested (via 'extras=extra_charges'). Note: chargeable_online field is not available in this endpoint.

- `data.products.price.charges` (array)

The charge breakdown. Includes taxes and fees.

- `data.products.price.charges.charge` (integer)

A signed integer number that uniquely identifies an accommodation charge type. Examples of charges are: VAT, City Tax, etc. The full list can be obtained by calling accommodations/constants.

- `data.products.price.charges.mode` (string)

The mode of this charge. Determines how the price is calculated.

Enum: "calculated_amount", "incalculable", "percentage", "per_day", "per_night", "per_person_per_day", "per_person_per_night", "per_person_per_stay", "per_stay"

- ``data.products.price.charges.percentage`` (number)
The percentage of 'base' that this charge amounts to. Only applicable when 'mode' is 'percentage'.
- ``data.products.price.charges.condition`` (integer | null)
A signed integer number that uniquely identifies the condition ID. Find the full list in the Pricing guidelines.
- ``data.products.price.charges.included_in`` (object)
Indicates where this charge is included. Note: `chargeable_online` is not available in this endpoint.
- ``data.products.price.charges.included_in.display`` (boolean)
Indicates if this charge is included in the display price.
- ``data.products.room`` (string)
A unique identifier for a specific room within an accommodation property. You can retrieve the full list of available room IDs by calling `[accommodations/details][demand/docs/open-api/demand-api/accommodations/accommodations/details]`.
- ``data.products.room_details`` (object)
Room details for this product (via `'extras=accommodation_details'`).
- ``data.products.room_details.name`` (string)
The room name given to this product.
- ``data.products.room_reservation`` (string)
The room reservation id given to this product.
- ``data.products.status`` (string)
Enum: "booked", "cancelled", "cancelled_by_accommodation", "cancelled_by_guest", "no_show", "stayed"
- ``data.reservation`` (string)
Reservation ID for given accommodation order.
- ``data.remarks`` (string)
Guest remarks added while creating order.
- ``data.stay_probability`` (number | null)
Score that predicts the likelihood of a traveller's intent to stay, based on internal calculations. A score of 0 indicates the highest likelihood of cancellation, while a score of 1 represents the highest likelihood of the traveller staying. Note: This score may not always be available.
- ``data.third_party_inventory`` (object | null)

Third party inventory related information for this accommodation order. This field is only available for third party inventory orders.

- `data.third\_party\_inventory.checkin\_number` (string | null)

The number required at the time of check-in. It allows guests to confirm their order at the accommodation.

Response 400 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Orders with car details

Use this endpoint to retrieve detailed information for one or more car rental orders.

- You can request car order details using your ****reservation**** ID.
- The response includes booking and cancellation details, commission, pricing, and optional extras (for example, policies).
- Results are sorted by the date of order creation in descending order, with the most recently booked orders listed first.

Endpoint: POST /orders/details/cars

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `orders` (array, required)
List of order IDs for which details should be returned.
- `currency` (string | null)
A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.
Example: EUR
- `extras` (array)
Optional extra details to include in the response, passed as a JSON array.
- `reservations` (array, required)
List of reservation IDs for which details should be returned.

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (array)
List of car order objects containing full details for each requested reservation.
- `data.id` (string)
Order ID for this car order.
- `data.affiliate` (number)
The affiliate ID used for this order.

- ``data.commission`` (object)

Commission details for the partner for this car order. DEPRECATED: Always expect null/omitted in this endpoint. Check the orders/details endpoint for commission details instead.

- ``data.commission.actual_amount`` (object)

The price in both depot and booker currencies (booker might be null, if not requested)

- ``data.commission.actual_amount.depot_currency`` (number)

- ``data.commission.actual_percentage`` (number)

Actual commission percentage for this car order (``null`` if value is not yet available).

- ``data.currency`` (object)

Depot and booker currencies (depot will be ``null`` going forward).

- ``data.currency.depot`` (string | null)

A three-letter code that uniquely identifies a monetary currency as defined by the ISO 4217 standard. The full list can be obtained by calling `common/payments/currencies`.

Example: EUR

- ``data.dropoff`` (object)

Pickup or drop-off location details.

- ``data.dropoff.datetime`` (string)

Pickup/drop-off date and time in ISO-8601 format.

Example: 2023-11-01T11:05:00+00:00

- ``data.label`` (string)

Identifier associated with the car booking. DEPRECATED: Always expect null/omitted in this endpoint. If you need to use 'label' for attributions, refer to orders/details

- ``data.price`` (object)

The price breakdown for this car order.

- ``data.products`` (array)

- ``data.products.car`` (integer)

Uniquely identifies a car specification. The full list can be obtained by calling `/cars/suppliers`(`#/cars/details`).

- ``data.products.policies`` (object)

The policies that apply to this product.

- ``data.products.policies.payment`` (object)

The payment policy that applies to this product.

- ``data.products.policies.payment.timing`` (string, required)

The applied payment timing. For example 'pay_online_now'.

Enum: "pay_online_now", "pay_at_pickup", "pay_partial_online_now", "unknown"

- `data.products.price` (object)

Detailed breakdown of the product's price components.

- `data.products.status` (string)

Enum: "booked", "cancelled", "cancelled_by_accommodation", "cancelled_by_guest", "no_show", "stayed"

- `data.reservation` (string)

This is the reservation id for the car in this order.

Response 400 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)

Uniquely identifies the request. Please provide this identifier when contacting support.

- `errors` (array, required)

- `errors.id` (string, required)

- `errors.message` (string, required)

Orders with flight details

Use this endpoint to retrieve detailed information for one or more flight orders.

- You can request flight order details either by **order ID** or by **reservation ID**.
- The response includes structured order data, including pricing, itinerary segments with IATA airport codes, etc.

This endpoint is ideal for:

- Displaying flight booking details in traveller dashboards or confirmation pages.
- Generating post-booking communications and invoices.
- Performing reporting or reconciliation tasks that require accurate itinerary and pricing data.

Endpoint: POST /orders/details/flights

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `orders` (array, required)
List of order IDs for which details should be returned. Mutually exclusive with 'reservations'.
- `reservations` (array, required)
List of reservation IDs for which details should be returned. Mutually exclusive with 'orders'.

Response 200 fields (application/json):

- `data` (array)
- `data.id` (string)
Order id
- `data.reservation` (string)
This is the reservation id for the travel service in this order.
- `data.currency` (object)
- `data.currency.booker\_currency` (string)
The currency of the booker.
- `data.currency.order\_currency` (string)
The currency in which the order was created.

- `data.itineraries` (array)

- `data.itineraries.arrival` (object)

- `data.itineraries.arrival.airport` (string)

A three-letter code that uniquely identifies an airport as defined by the International Air Transport Association (IATA). The full list can be obtained by calling `[common/locations/airports](#/common/locations/airports)`.

- `data.itineraries.arrival.date\_time` (string)

Date time of the itinerary.

- `data.label` (string)

Identifier associated with the order.

- `data.price` (object)

- `data.price.booker\_currency` (number)

The price in the currency of the booker

- `data.price.order\_currency` (number)

The price in the currency in which order was created

- `data.status` (string)

Enum: "booked", "cancelled", "unknown"

- `request\_id` (string)

Uniquely identifies the request. Please provide this identifier when contacting support.

Modify an order

Use this endpoint to modify certain aspects of an accommodation order, such as credit card details, checkin/checkout dates, and room configurations (guest allocation, guest names, and smoking preferences). See the [Orders modification guide](/demand/docs/orders-api/order-modify) for examples and best practices.

Endpoint: POST /orders/modify

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Request fields (application/json):

- `order` (string, required)
Order ID to be modified
- `modification` (object, required)
 - `modification.accommodation` (object, required)
 - `modification.accommodation.reservation` (string, required)
Reservation ID
 - `modification.accommodation.change` (any, required)
 - `modification.accommodation.change.checkin` (string, required)
New checkin date
 - `modification.accommodation.change.checkout` (string, required)
New checkout date
 - `modification.accommodation.change.room\_reservation` (string)
 - `modification.accommodation.change.allocation` (object)
 - `modification.accommodation.change.allocation.number\_of\_adults` (integer)
 - `modification.accommodation.change.guests` (array)
Guest information for the room.
 - `modification.accommodation.change.guests.name` (string)
 - `modification.accommodation.change.smoking\_preference` (string)

Enum: "no_preference", "non_smoking", "smoking"

- `modification.accommodation.type` (string, required)

Type of the accommodation change

Enum: "dates", "room"

Response 200 fields (application/json):

- `modification` (object)

- `modification.accommodation` (object)

- `modification.accommodation.new\_price` (number)

New price to be paid after the modification

- `modification.accommodation.status` (string)

Status for this modification request.

Enum: "successful", "failed"

- `modifications` (object)

- `modifications.payment` (object)

Cancel a travel service

Use this endpoint to cancel a travel service within an existing order. Provide the details of the reservation or insurance policy you want to cancel.

- **Note:** Only one travel service can be cancelled per request.

For step-by-step instructions, see the [Cancellations guide](/demand/docs/orders-api/cancel-order).

Endpoint: POST /orders/cancel

Version: 3.2

Security: BearerAuth

Header parameters:

- `X-Affiliate-Id` (integer, required)
Include here your Affiliate identifier number

Response 200 fields (application/json):

- `request\_id` (string)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `data` (object)
- `data.status` (any)

Response 400 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 403 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 409 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

Response 500 fields (application/json):

- `request\_id` (string, required)
Uniquely identifies the request. Please provide this identifier when contacting support.
- `errors` (array, required)
- `errors.id` (string, required)
- `errors.message` (string, required)

