React.js Lab B4 – Button Component

Aim: Build your own Button component using React JS and render it three times. On user click, it should alert which button was clicked.

Step 1: Create the React app

1. Open **VS Code**.
2. Go to **Terminal → New Terminal**.
3. Run these commands one by one:

```
npx create-react-app my-app
cd my-app
npm start
```

This creates a project folder named `my-app`, moves into it, and starts the development server. You can stop the server with `Ctrl + C` while you edit the files (or leave it running, since it reloads automatically).

Step 2: Change the code in `src/App.css`

Where: `my-app → src → App.css`

Delete everything in this file and paste the following:

```
button {
  margin: 10px;
  padding: 10px 20px;
  font-size: 16px;
  cursor: pointer;
}
```

Step 3: Create a new file `src/Button.js`

Where: Right-click the **src** folder → **New File** → name it `Button.js`

Paste this code:

```
import React, { useState } from "react";

function Button({ label }) {
  const [clickCount, setClickCount] = useState(0);

  const handleClick = () => {
    setClickCount(clickCount + 1);
    alert(`${label} was clicked!`);
  };

  return (
    <button onClick={handleClick}>
      {label} (Clicked {clickCount} times)
    </button>
  );
}

export default Button;
```

Step 4: Change the code in `src/App.js`

Where: `my-app → src → App.js`

Delete everything in this file and paste the following:

```
import React from "react";
import Button from "./Button";

function App() {
  return (
    <div style={{ textAlign: "center", marginTop: "50px" }}>
      <h2>React Button with useState</h2>
      <Button label="First Button" />
      <Button label="Second Button" />
      <Button label="Third Button" />
    </div>
  );
}

export default App;
```

Step 5: Run the application

In the VS Code terminal, make sure you are inside the project folder, then start the app:

```
cd my-app
npm start
```

The browser opens at `http://localhost:3000`.

Expected output

Three buttons appear on the page: **First Button**, **Second Button** and **Third Button**. Clicking any button shows an alert such as *"Second Button was clicked!"*, and the count on that button increases by one.

