

Eclipse - RemoteSystemsTempFiles - [dbms_solA]

File Edit Navigate Search Project RdbmsAssessment Test SQL Editor Run Live Coding Database Window HandsOn Help

Commit

Rollback

Quick Access

00:57:56

ProjectsMy Oracle Credentials View

Assessment

Guidelines

SQL

dbms_solA.sql

dbms_solB.sql

dbms_solC.sql

dbms_solD.sql

dbms_solE.sql

dbms_solF.sql

dbms_solG.sql

dbms_solH.sql

test.sql

TableScripts

Connections

RemoteSystemsTempFiles

dbms_solCdbms_solDdbms_solAdbms_solBdbms_solEdbms_solFdbms_solGdbms_solH

1 SELECT substr(pizzaid,2) AS PIZZAID, pizzaname

2 FROM pizza WHERE pizzasize IN ('R','M') AND pizzarate>200;

ResultsExplain PlanExecution LogOutput

SQL

No Data

Execute query (Ctrl+Enter) or script (Alt+X) to see results

Connected to "Oracle_T1107661"

WritableSmart Insert2 : 59

Type here to search

11:17 AM1/11/2021



Quick Access



00:57:50

Projects My Oracle Credentials View

- Assessment
 - Guidelines
 - SQL
 - dbms_solA.sql
 - dbms_solB.sql
 - dbms_solC.sql
 - dbms_solD.sql
 - dbms_solE.sql
 - dbms_solF.sql
 - dbms_solG.sql
 - dbms_solH.sql
 - test.sql
 - TableScripts
 - Connections
- RemoteSystemsTempFiles

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH


```
1 SELECT DISTINCT c.custid, o.pizzaid, o.amount
2 FROM orders o INNER JOIN customer c
3 ON o.custid=c.custid
4 WHERE upper(c.custname) LIKE '_A%'
5 OR length(c.emailid)=12;
```

Result Explain Plan Execution Log Output

SELECT DISTINCT c.custid, o.p Enter a SQL expression to filter results (use Ctrl+Space)

	T CUSTID	T PIZZAID	AMOUNT
1	C106	P103	428
2	C101	P103	448
3	C101	P101	135
4	C102	P105	665
5	C101	P102	270
6	C104	P104	395

6 row(s) fetched - 16ms



Writable

Smart Insert

5:25

Projects My Oracle Credentials View

- Assessment
 - Guidelines
 - SQL
 - dbms_solA.sql
 - dbms_solB.sql
 - dbms_solC.sql
 - dbms_solD.sql
 - dbms_solE.sql
 - dbms_solF.sql
 - dbms_solG.sql
 - dbms_solH.sql
 - test.sql
 - TableScripts
 - Connections
- RemoteSystemsTempFiles

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH

```
1 SELECT distinct custid, deliverymode, amount
2 FROM orders WHERE amount > (SELECT avg(amount) FROM orders);
```

Result Explain Plan Execution Log Output

SELECT custid, deliverymode, amount FROM Enter a SQL expression to filter results (use Ctrl+Space)

	T CUSTID	T DELIVERYMODE	T AMOUNT
1	C106	TA	428
2	C101	HD	448
3	C102	HD	665
4	C105	TA	545

4 row(s) fetched - 15ms

Grid

Writable

Smart Insert

2:61

Projects My Oracle Credentials View

Assessment

- Guidelines
- SQL
 - dbms_solA.sql
 - dbms_solB.sql
 - dbms_solC.sql
 - dbms_solD.sql
 - dbms_solE.sql
 - dbms_solF.sql
 - dbms_solG.sql
 - dbms_solH.sql
 - test.sql
- TableScripts
- Connections
- RemoteSystemsTempFiles

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH

```
1 SELECT o1.orderid, o2.pizzaid
2 FROM orders o1 JOIN orders o2 ON o1.pizzaid=o2.pizzaid AND o1.TOPPINGID=o2.TOPPINGID
3 WHERE o1.deliverymode!=o2.deliverymode;
```

Result Explain Plan Execution Log Output

SELECT o1.orderid, o2.pizzaid FROM orders Enter a SQL expression to filter results (use Ctrl+Space)

	ORDERID	PIZZAID
1	O103	P103
2	O104	P103

2 row(s) fetched

Grid

Writable

Smart Insert

3:40



Quick Access



00:57:30

Projects My Oracle Credentials View

- Assessment
 - Guidelines
 - SQL
 - dbms_solA.sql
 - dbms_solB.sql
 - dbms_solC.sql
 - dbms_solD.sql
 - dbms_solE.sql
 - dbms_solF.sql
 - dbms_solG.sql
 - dbms_solH.sql
 - test.sql
 - TableScripts
 - Connections
- RemoteSystemsTempFiles

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH


```
1 SELECT DISTINCT p.pizzaid, nvl(o.custid,'NA') AS CUSTOMER, nvl(t.toppingid,'NT') AS TOPPING
2 FROM pizza p LEFT OUTER JOIN orders o ON p.pizzaid=o.pizzaid
3 LEFT OUTER JOIN topping t ON o.toppingid=t.toppingid AND t.TYPE!='NV';
```

Result Explain Plan Execution Log Output

SELECT DISTINCT p.pizzaid, nv Enter a SQL expression to filter results (use Ctrl+Space)

	T PIZZAID	T CUSTOMER	T TOPPING
1	P102	C105	T102
2	P103	C105	T102
3	P105	C102	T103
4	P105	C105	T101
5	P101	C101	T101
6	P106	NA	NT
7	P102	C103	T103
8	P102	C101	T101
9	P103	C101	T103
10	P103	C106	T103

11 row(s) fetched - 16ms



Writable

Smart Insert

3:71

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH

```
1 SELECT custid||'-'||custname AS CUSTDETAILS, emailid
2 FROM customer WHERE custid in
3 (SELECT custid FROM orders GROUP BY custid HAVING count(distinct(deliverymode))=3);
```

SELECT custid||'-'||custname A *Enter a SQL expression to filter results (use Ctrl+Space)*

[illegible]

Grid

3:84

```
1 SELECT c.custid, c.custname, c.mobilenumber
2 FROM customer c WHERE c.custid IN
3 (SELECT o.custid FROM orders o WHERE
4 (SELECT count(o1.custid) FROM orders o1, pizza p1
5 WHERE o1.pizzaid=p1.pizzaid and p1.pizzasize='M' AND o1.custid=o.custid)>
6 (SELECT count(o2.custid) FROM orders o2, pizza p2
7 WHERE o2.pizzaid=p2.pizzaid and p2.pizzasize='R' AND o2.custid=o.custid));
```

No Data

Execute query (Ctrl+Enter) or script (Alt+X) to see results



Quick Access



00:57:11

Projects My Oracle Credentials View

- Assessment
 - Guidelines
 - SQL
 - dbms_solA.sql
 - dbms_solB.sql
 - dbms_solC.sql
 - dbms_solD.sql
 - dbms_solE.sql
 - dbms_solF.sql
 - dbms_solG.sql
 - dbms_solH.sql
 - test.sql
 - TableScripts
 - Connections
- RemoteSystemsTempFiles

dbms_solC dbms_solD dbms_solA dbms_solB dbms_solE dbms_solF dbms_solG dbms_solH

```
1 SELECT o.orderid, o.custid, o.pizzaid FROM orders o
2 WHERE o.pizzaid in(SELECT p.pizzaid FROM pizza p WHERE p.pizzaid=o.pizzaid AND p.pizzasize='L')
3 AND o.toppingid in(SELECT t.toppingid FROM topping t WHERE t.toppingid=o.toppingid AND t.toppingrate<200)
4 AND o.deliverymode='HD';
```

Result Explain Plan Execution Log Output

SELECT o.orderid, o.custid, o.pizzaid | Enter a SQL expression to filter results (use Ctrl+Space)

	ORDERID	CUSTID	PIZZAID
1	O108	C105	P103
2	O104	C101	P103

2 row(s) fetched - 31ms

Grid

Writable

Smart Insert

4:25