Name- Shreyash Khapekar

PRN - B25ET1019

Division- SY1 ENTC

Title: Implement Database Management using arrays of structures with operations Create, Display,

```
#include <stdio.h>
#include <string.h>

typedef struct {
    int emp_no;
    char name[30];
    float salary;
} Employee;

int create(Employee emp[], int n) {
    int i;
    for(i = 0; i < n; i++) {
        printf("\nEnter details for employee %d:\n", i + 1);
        printf("Emp No: ");
        scanf("%d", &emp[i].emp_no);
        printf("Name: ");
        scanf("%s", emp[i].name);
        printf("Salary: ");
        scanf("%f", &emp[i].salary);
    }
    return n;
}

void display(Employee emp[], int n) {
    int i;
    if(n == 0) {
        printf("\nDatabase is empty!\n");
        return;
    }
    printf("\nEmp No\tName\t\tSalary\n");
    printf("-----------------------------------\n");
    for(i = 0; i < n; i++) {
        printf("%d\t%s\t\t%.2f\n", emp[i].emp_no, emp[i].name, emp[i].salary);
    }
}
```

```
void modify(Employee emp[], int n) {
    int id, i, found = 0;
    printf("\nEnter Emp No to modify: ");
    scanf("%d", &id);

    for(i = 0; i < n; i++) {
        if(emp[i].emp_no == id) {
            printf("Enter new Name: ");
            scanf("%s", emp[i].name);
            printf("Enter new Salary: ");
            scanf("%f", &emp[i].salary);
            printf("Record updated successfully!\n");
            found = 1;
            break;
        }
    }
    if(!found) {
        printf("Employee not found!\n");
    }
}

void search(Employee emp[], int n) {
    int id, i, found = 0;
    printf("\nEnter Emp No to search: ");
    scanf("%d", &id);

    for(i = 0; i < n; i++) {
        if(emp[i].emp_no == id) {
            printf("\nEmployee Found:\n");
            printf("Emp No: %d\nName: %s\nSalary: %.2f\n", emp[i].emp_no, emp[i].name, emp[i].salary);
            found = 1;
            break;
        }
    }
    if(!found) {
        printf("Employee not found!\n");
    }
}

void sort(Employee emp[], int n) {
    int i, j;
    Employee temp;
    for(i = 0; i < n - 1; i++) {
```

```
        for(j = 0; j < n - i - 1; j++) {
            if(emp[j].emp_no > emp[j + 1].emp_no) {
                temp = emp[j];
                emp[j] = emp[j + 1];
                emp[j + 1] = temp;
            }
        }
    }
    printf("\nDatabase sorted by Emp No!\n");
}

int deleteEmp(Employee emp[], int n) {
    int id, i, j, found = 0;
    printf("\nEnter Emp No to delete: ");
    scanf("%d", &id);

    for(i = 0; i < n; i++) {
        if(emp[i].emp_no == id) {
            found = 1;
            for(j = i; j < n - 1; j++) {
                emp[j] = emp[j + 1];
            }
            n--;
            printf("Employee record deleted successfully!\n");
            break;
        }
    }
    if(!found) {
        printf("Employee not found!\n");
    }
    return n;
}

int main() {
    Employee emp[100];
    int n = 0, choice, addCount, i;

    while(1) {
        printf("\n--- EMPLOYEE DATABASE MENU ---\n");
        printf("1. Create / Add Database\n");
        printf("2. Display Database\n");
        printf("3. Modify Employee\n");
        printf("4. Search Employee\n");
        printf("5. Sort Database\n");
```

```
        printf("6. Delete Employee\n");
        printf("7. Exit\n");
        printf("Enter your choice: ");
        scanf("%d", &choice);

        if(choice == 1) {
            printf("Enter number of employees: ");
            scanf("%d", &addCount);
            n = create(emp, addCount);
        }
        else if(choice == 2) {
            display(emp, n);
        }
        else if(choice == 3) {
            modify(emp, n);
        }
        else if(choice == 4) {
            search(emp, n);
        }
        else if(choice == 5) {
            sort(emp, n);
        }
        else if(choice == 6) {
            n = deleteEmp(emp, n);
        }
        else if(choice == 7) {
            break;
        }
        else {
            printf("Invalid choice!\n");
        }
    }

    return 0;
}
```