```
# To find the downstream depth of open channel
      g= float (input("Enter the value of Discharge:4.8"))
      q= float
T= int(input("Enter the value of top width:2"))
      float(input("Enter the value of acceleration due to Gravity:9.81"))
float(input("enter the value of upstream dupth:1.6"))
      # Dicharge per meter width
     Q+Q/T
     q=0/1
print ("The value of discharge per meter width is:", q)
     # Area Calculation
     A1= T*y1
     print ("The value of upstream area is:", Al)
     a Calculation of Froude Number
     Fr1 = (Q*Q*T)/(g*A1* A1 *A1) * 8,5
     print ("The value of Froude number is:", Fri)
     if fr1>1: - +
     - pass a Replace with desired code -
        print("The flow is Super Critical Flow")
   else:
       print("The flow is Sub Celtical Flow")
    Mupstream Energy
    E1 . y1 + (Q*Q)/(2 *g*A1 *A1)
    print ("The value of Energy at initial Section is:" E1)
    # Downstream Energy
   E2 . E1 -Z
    print ("The value of downstream Energy #2 15:",
                                                       E2)
   # Critical Depth
  # You need to define the values for 'a' and 'e
                                                     based on your problem.
   # For example:
  a = 1.8 # Replace with the actual value of 'a
   e = 1.8 # Replace with the actual value of 'e'
   yc = (q*a/e)**0.3333
  print ("The Value of critical depth is:", yc)
   # Note: In Python, a tuple is defined using parenthesis. Using a
                                                                        comma creates a tuple.
  # To perform multiplication, use the '*' operator.
   Ec = 1.5*yc
   print ("The value of critical Energy is", Ec)
  if tc>E2:
                                                                                  7G Prokon
  - print ("Chocking Condition")
  else:
   - print-("SAFE")-
  # Calculation of Zmax
 # You need to define the value for 'El' based on your problem.
  # For example:
  El = 1.8 # Replace with the actual value of 'El'
 Zmax =E1- Ec
  print ("The value of maxinmum hump is:", Zmax)
  Enter the value of Discharge:4.84.8
      Enter the value of top width: 22
     | Enter the value of accoleration due to Gravity:9.819.81
      enter the value of upstream depth:1.61 6
     Enter the Value of hump:0.1 0.1
      The value of discharge per meter width is: 2.4
    The value of upstream area is: 3.2
      The value of Froude number 1s: 0.07167431192660548
     The fluw is Sub Critical Flow
    The value of Energy at initial Section is: 1.714678899082569
      The value of downstream Energy E2 1s: 1.614678899882569
    The Value of critical depth is: 1.3388268295597898
     The value of critical Energy is 2.0082402443396847
    Chocking Condition
     The value of maximum hump is: -0.2082402- 3396847
# To find the downstream depth of open channel
a Given Data
Q. float(input("Enter the value of Discharge: 15"))
81 * float(input("Enter the value of Discharge:15 "))
82 * float(input("Enter the value of width at upstream:3.5"))
82 * float(input("Enter the value of width at downstream:2.5"))
8* float(input("Enter the value of width at downstream:2.5"))
8= float(input("Enter the value of width at downstream to (rayity:9.81"))
yl= float(input("Enter the value of acceleration due to (rayity:9.81"))
yl= float(input("enter the value of upstream depth:2"))
# Dicharge per meter width
q2= Q/82
```

Print ("The value of discharge per meter width is: ", ql) # Changed ql to ql

```
print ("The value of discharge per meter width is:", q2)
   # Area Calculation
  Al = B1*yl * Changed y1 to y1 as y1 was not defined
  print ("The value of upstream area is:", A1)
  s Calculation of Froude Number
  Fr1 = ((Q*Q*B1)/(E*A1*A1*A1)) **8.5
  print ("The value of Froude number is:", Fr1)
  if (Fr1>1:
       Frint("The flow is Super Critical Flow") # Indent this line to be part of the 'if' block
  else:
      -print("The flow is Sub G-itical Flow")
  # Upstream Energy
 # upstream the positive 'e' here or import it from a library if it represents a physical constant
 e = 1.602e-19 (2*e*A1*A1) # Use 'yl' instead of 'yl' if it's a different variable.
 E1 = y1 + (Q*6)/(1 to said the said the
 grint (type alias) B2min: Any dition * Remove or comment out this invalid line.
 Bzain = (27*Q*Q/(8*R*E1*E1*E1)) **0.5
 B2min ("The value of minimum width to be kept to avoid Chocking is:", B2min)
 if 82min > 92:
  - print ("Chocking Condition") #- Indent-this-line
    print ("SAFE") a Indent this line to be part of the 'else' block
# Critical Depth
 e = 0.8 % Or any other relevant value
yc = ((Q*Q)/(B2*B2*e)) **0.3333
 print ("The Value of critical depth is:
Ec = 1.5*yc
  Enter the value of Discharge: 1515
      Enter the value of width at upstream; 3.5 3.5
Enter the value of width at downstream; 2.5 2.5
      Enter the value of acceleration due to Gravity:9.819.81
        enter the value of upstream depth: 22
        The value of discharge per meter width is: 4.285714285714286
        The value of discharge per meter width is: 6.0
        The value of upstream area is: 7.0
     The value of Froude number is: 0.4837753296275688
        The flow is Sub Critical Flow
      The value of Energy at initial Section is: 2.0
                                                                                                                          SAC PACHONS
        The value of minimum width to be kept to avoid Chocking is
                                                                                                             3.110632107802487
      Chocking Condition
        The Value of critical depth is: 3.5564420033791078
      The value of critical Energy is 5.334663005068662
 #Design of Efficient Channel Section
Q= float(input("Enter the value of Discharge:100"))
n=float(input("Enter the value of Rugosity coefficient:0,815"))
50= float (input("Enter the value of bed slope:0.8084"))
g= float(input("Enter the value of acceleration due to Gravity: 9.81"))
 amanning's Formula
#Q = (AR^2/3 5^1/2)/n
 yn = (Q*n*50* 1.591)/(1.732) * (3/8)
 print ("The Value of yn is", yn)
 #To encounter the effect of free board
 yn1= 1.1*yn
print ("The Value of ynl is", yn1)
 # Cross Sectional Area
A = 1.732 * yn * yn1
print ("The cross sectional Are: is:", A)
 # Top Width
T= 4* yn/1.732
 print ("The value of top Width is:", T)
 # Bottom Width
B= 2 * yn/1.732
 print ("The value of Bottom Width is'", 8)
Fr= ((Q*Q*T)/(g*A*A*A)) * 0.5 # Fixed the Fr calculation
 print ("the value of Froude number is:", Fr)
     Print("The flow is Super Critical Flow") # Indented this line
    -print("The flow is Sub-Oritical Flow")
  Enter the value of Discharge:100100
Enter the value of Rugosity coefficient:0,0150.015
        inter the value of bed slope:0.00040.0004
      Enter the value of acceleration due to Gravity:9.819.81
        The Value of yn is 25.83537817551963
      The Value of ynl is 28,418915993871593
```

The cross sectional Area is: 1271.6576815774754
The value of top Width is: 59.66600040535711
The value of Bottom Width is' 8
The value of Froude number is: 1.4788266440381834e-05
The flow is Sub Critical Flow

SHREYASH KAILEBAGRACKOAS