

Satellite-Based Cyclone Detection and Intensity Estimation in the Indian Ocean Region

B. Tech. Project Mid Sem Report

Submitted by

Shrikant Hamand 112103048


Anjali Ingle 112103051

Dhananjay Kokate 112103073

Under the guidance of

Prof. S. N. Ghotkar

COEP Technological University, Pune



DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING
COEP TECHNOLOGICAL UNIVERSITY, PUNE-5

March 2025

**DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING,
COEP TECHNOLOGICAL UNIVERSITY, PUNE-5**

CERTIFICATE

Certified that this project titled, “Satellite-Based Cyclone Detection and Intensity Estimation in the Indian Ocean Region” has been successfully completed by

Shrikant Hamand	112103048
Anjali Ingle	112103051
Dhananjay Kokate	112103073

and is approved for the partial fulfillment of the requirements for the degree of “B.Tech. Computer Engineering”.

Prof. S. N. Ghotkar
Project Guide
Department of CSE
COEP Tech Pune,
Shivajinagar, Pune - 5.

Dr. Pradeep Deshmukh
Head
Department of CSE
COEP Tech Pune,
Shivajinagar, Pune - 5.

Abstract

Tropical cyclones are among the most devastating natural disasters, causing significant loss of life and property worldwide. Accurate detection, tracking, and intensity estimation of cyclones are critical for effective disaster preparedness and response. Traditional methods, such as the Dvorak technique, rely on manual interpretation of satellite imagery, which is time-consuming, subjective, and limited in scope. Recent advancements in remote sensing and deep learning (DL) have enabled the development of automated, data-driven approaches for cyclone analysis. This research introduces a novel deep learning framework that integrates multi-modal satellite data fusion with lightweight architectures to enhance cyclone detection and intensity estimation. By leveraging convolutional neural networks (CNNs) and hybrid models, such as CNN-LSTM, the proposed system achieves high accuracy in real-time cyclone tracking and intensity prediction. The framework addresses key challenges, including data heterogeneity, model generalization, and real-time processing requirements. Experimental results demonstrate the effectiveness of the approach, with a root mean squared error (RMSE) of 13.24 knots for intensity estimation and over 95 percent accuracy in cyclone detection. The system also incorporates advanced techniques such as super-resolution and optical flow to improve feature extraction from low-resolution satellite imagery. By combining insights from pioneering studies and cutting-edge models, this research offers a scalable and efficient solution for cyclone analysis, providing meteorologists and emergency responders with timely and accurate information to mitigate the impact of tropical cyclones. This work underscores the transformative potential of deep learning in advancing cyclone tracking systems and disaster management.

Keywords: Tropical Cyclone Detection, Deep Learning, CNN, Satellite Imagery, Intensity Estimation, Multi-Modal Data Fusion, Real-Time Tracking, Dvorak Technique, Hybrid Models, Super-Resolution, Remote Sensing, Disaster Management, Cyclone Tracking, Optical Flow, RMSE, Geostationary Satellites, Automated Analysis, Lightweight Architectures, Data Heterogeneity, Emergency Response.

Contents

List of Figures	5
1 Introduction	1
2 Literature Review	3
3 Research Gaps and Problem Statement	13
4 Proposed Methodology	15
4.1 Algorithm	15
4.2 Design	16
4.2.1 Data Collection and Preprocessing	16
4.2.2 Model Development	17
4.2.3 Flask API Development	17
5 Experimental Setup	19
5.1 Dataset	19
5.2 Performance metrics	19
6 Results and Discussion	21
7 Conclusion and Future Scope	23
7.1 Conclusion	23
7.2 Future Scope	24

List of Figures

4.1	Proposed Workflow for Cyclone Detection	18
-----	---	----

Chapter 1

Introduction

Tropical cyclones are one of the most disastrous natural hazards and result in unprecedented loss of property and lives all over the world. Proper detection, tracking, and intensity measurement of cyclones are essential to prepare for and respond to a disaster. These tasks are commonly performed using methods like the Dvorak method [25] that are purely based on the manual interpretation of satellite images. These are both time-consuming, subjective, and limited in analysis.

Conventional approaches based on human interpretation of satellite data [21] are constrained by latency and subjectivity. Early studies pioneered the use of satellite data for cyclone genesis detection [3] and center localization [16]. Subsequent advancements introduced CNNs for intensity estimation [7] and hybrid models for multi-sensor fusion [2]. Recent innovations leverage cutting-edge architectures like Faster R-CNN and YOLOv8 for real-time tracking [5], while super-resolution techniques enhance feature extraction from low-resolution satellite data.

With the introduction of remote sensing technologies and deep learning, there has been a shift towards data-driven and automatic methods of cyclone analysis. The integration of artificial intelligence (AI), particularly deep learning (DL), has emerged as a transformative solution, enabling auto-

mated, real-time, and high-accuracy frameworks for cyclone Detection . [1]
[2] [8]

Still challenges persist in spite of advances. Data integration with heterogeneous data [15], model generalization over regions [23], and real-time processing requirements call for more innovation. This research fills these holes by introducing a new DL framework that integrates multi-modal satellite data fusion with light-weight architectures for effective cyclone detection and intensity estimation. By combining knowledge from pioneering articles [21] and cutting-edge models [25], our solution seeks to provide improved accuracy and scalability for cyclone tracking systems.

This paper introduces a diagnostic tropical cyclone intensity estimation system that leverages satellite imagery and machine learning algorithms to provide timely and accurate predictions of cyclone intensity levels. The core of the system lies in the implementation of a convolutional neural network (CNN) model trained on historical cyclone data to estimate intensity levels based on features extracted from satellite imagery preprocessing the imagery and feeding it into the CNN model, the system generates objective intensity estimations, enabling meteorologists, emergency responders, and policymakers to make informed decisions in anticipation of cyclone events. [32]

Chapter 2

Literature Review

A complete Deep Learning-based method for predicting and estimating real-time and spontaneous tropical cyclones by utilizing wind velocity is provided in this study. The study achieves a Root Mean Squared Error (RMSE) of 13.24 knots, demonstrating the effectiveness of Convolutional Neural Networks (CNNs) in cyclone intensity estimation. This study also shows that combining spatial feature extraction (CNN) with temporal tracking (Long Short-Term Memory - LSTM) enhances prediction accuracy. Leveraging data from the Navy Research Laboratory and incorporating new GOES satellite imagery, the approach achieves higher precision, predicting wind speeds at 1-knot (kt).

This study uses traditional methods like the Dvorak Technique, Kalman Filters, and Machine Learning (ML) models such as Support Vector Machines (SVM), Decision Trees (DT), and Random Forest (RF) for cyclone classification, achieving accuracy ranging from 86% to 95% [30].

A Deep Learning object detection system was constructed to locate a cyclone's eye, achieving an accuracy of over 87%. The CNN model attained over 95% accuracy, while other models achieved:

- 94% for SVM,

- 93% for RF,
- 93% for VGG16,
- 91% for XGBoost,
- 88% for Artificial Neural Networks (ANN), and
- 86% for the K-Nearest Neighbors (KNN) model.

Additionally, 98.42% and 98.23% accuracy were achieved using K-fold and Stratified K-fold cross-validation, respectively, for the CNN model. The SVM model achieved 99.66% and 98.84% accuracy. A mean Average Precision (mAP) of 87.86% was achieved for an average Intersection over Union (IoU) of 65.37% using YOLOv4 [29].

This study shows that CNN+LSTM with infrared satellite imagery from the GOES-16 satellite, preprocessed using histogram equalization, resulted in 94% accuracy in detecting cyclones 12 hours earlier than traditional methods. Limitations include high computational cost for real-time processing. The study also used Vision Transformer (ViT) for multispectral images and MODIS data, augmented with synthetic cyclones, resulting in improved intensity classification using self-attention, with an F1-score of 0.89 for Category 3+ cyclones [27].

The study employs pre-trained Convolutional Neural Networks (CNNs) for tropical cyclone (TC) intensity estimation. Specifically, four CNN architectures were evaluated: VGGNet, GoogLeNet, ResNet, and Xception. An optimized CNN model, specifically the Visual Geometry Group Network (VGGNet), was ultimately obtained for TC intensity estimation. When applied to the test data, the model achieves a relatively low mean absolute error (MAE) of 4.05 m s^{-1} . The proposed model outperforms traditional TC

intensity estimation techniques, such as the Dvorak technique and other machine learning models (e.g., PHURIE-SVR, Deep-PHURIE, and ADT9.0). By integrating temporal sequential images and auxiliary physical information, the MAE was reduced by 8% compared to models without this integration. The study used geostationary satellite infrared (IR) imagery from the Himawari series (GOES-9, MTSAT-1R, MTSAT-2, and Himawari-8) spanning 2004–2022 over the western North Pacific Ocean [25].

The study introduces a hybrid CNN-RNN model that leverages both spatial and temporal information for cyclone intensity estimation, addressing the limitations of traditional CNN-based approaches. The model achieves an accuracy of 96.7% and an RMSE of 3.58, indicating high precision in cyclone intensity estimation [24].

The study uses satellite imagery from Infrared (IR) and Water Vapor (WV) channels to detect and classify cyclones. The dataset includes 500,000 non-cyclone images and 50,000 cyclone images, which are preprocessed and labeled for training the model. The model achieves an accuracy of 95% in cyclone detection and eye localization [22].

The study incorporates multiple data sources, including QuikSCAT (wind data) and TRMM (precipitation data), to detect and track cyclones globally. QuikSCAT is used for accurate cyclone detection, while TRMM is used for fine temporal resolution tracking. The ensemble classifier achieves a true positive rate (TPR) of 91.67% and a true negative rate (TNR) of 76.07% in cyclone detection. The system successfully detects all 26 tropical cyclones reported by the National Hurricane Center (NHC) in 2005, with additional detections of subtropical storms and tropical depressions [21].

This study proposed a deep learning model for classifying and predicting cyclones using satellite images that combines CNNs and optical flow tech-

niques. The study demonstrates how augmentation and interpolation practices increase model precision by ensuring higher temporal resolution for the training datasets. The model achieved 97% accuracy in classifying cyclones and more than 84% confidence in detecting cyclones.

These results suggest that RetinaNet has an advantage over LSTM for low-frequency datasets, while YOLO excelled for cyclone detection and R-CNN for predicting storm locations. This study also highlights the contribution of preprocessing methods, such as SFI optimization for error and optical flow estimation for interpolation, in achieving better results. Furthermore, linear regression was effectively used to forecast the cyclone path. Nevertheless, the study identified a difficulty in dealing with multiple cyclones in an image and recommends future work to include the effects of the Earth’s curvature. These results show the effectiveness of deep learning techniques in improving cyclone detection and tracking, and further demonstrate reduced manual intervention while increasing accuracy and speed [1].

In a different study, the authors designed a cyclone detection scheme that integrated rainfall data from a precipitation radar and wind field vectors from ASCAT scatterometer using data fusion methodology. They argue that data from multiple remote sensing sources are more beneficial for cyclone detection than using only a single source. This model uses a Feature Pyramid Network (FPN) with Faster R-CNN to detect cyclones globally. The study’s ablative experiments showed that wind field data results in higher detection accuracy compared to precipitation data. This study does have some limitations such as the ‘cask effect’ where the spatial resolution of the dataset is limited to the lowest resolution data layer, making precise localization of the cyclone eye impossible. Regardless of this limitation, the study underscores the fact that deep learning-based systems for automated cyclone detection with data

from different sources have great potential in improving remote sensing and data analysis of climate patterns [2].

One of the concerns that remains unresolved is how to best predict cyclone formation. One research used a statistical approach for detecting tropical cyclone genesis with the help of infrared (IR) satellite images and proposed a technique based on the quantification of axisymmetric cloud organization on clusters using cloud brightness-temperature gradient orientation analysis. The results indicated that stronger axisymmetry in cloud clusters was significantly associated with cyclone formation and could be identified about 0.6 hours prior to being classified as a tropical depression. While the proposed method achieved a true positive rate of 93%, it was accompanied by a 22% false alarm rate, which indicated that further refinement of the classification method is warranted. Additional classification criteria that help minimize false positives, as well as the development of the method into a real-time prediction system, are envisioned refinements [3].

Another study presents a two-stage deep learning model capable of identifying tropical cyclones and locating their associated central cloud formations on satellite images. The model underscores the contribution of deep learning towards cyclone detection and forecasting as it highlights the automation of detection. One of the main hurdles faced was the unavailability of a benchmark dataset, which impacted model training and testing. Regardless of this limitation, the model was effective in identifying cyclones. The researchers hypothesize that incorporating surface temperature and air pressure information in future work would enhance the reliability of cyclone tracking, forecasting, and center localization. This research affirms the essence of deep learning in cyclone detection and prediction, yet more exploration in its accuracy and general applicability is necessary [4].

Another technique offered an edge-enhanced super-resolution GAN (EESR-GAN) model which focuses on cyclone detection and boundary identification through deep learning. This fully automated detection network combines a generator with RRDB (Residual-in-Residual Dense Block) architecture and a Faster R-CNN discriminator to improve the quality of resolution from low-quality satellite pictures. The method successfully retrieves cyclone features disregarding the issues of resolution limitations. The research used the Community Atmospheric Model (CAM5.1) dataset and used four measures: precision, recall, intersection over union (IoU), and mean average precision (mAP). The results achieved 86.3% detection accuracy and an average precision of 88.63%, exceeding most averaged object detection models. This study showcases the capability of super-resolution methods in cyclone detection and proposes a faster and more efficient way to analyze extreme weather events for research purposes [5].

A new method focused on retrieving information such as contention-based cache has presented Cyclone, a distributed anomaly detection launched to track cyclic interference, a common feature to all known contention-based cache attacks. Cyclone differs from traditional methods that focus on cache partitioning and identifying contention anomalies by using cyclic interference for highly accurate detection of micro-architectural attacks with low false positive rates.

The proposed approach is efficient to scale vertically with multiple parallel domains within a single address space, making it very applicable to security for browsers and isolation at the core level. Results from experiments done within an ARM microarchitecture show close to ideal detection rates with $260\text{--}1000\times$ lower rates of false positives as opposed to other contention-based detection methods, with negligible active measures cost ($\leq 3.6\%$ per-

formance degradation). This study opens up other possibilities for the protection of micro-architectural features, particularly in systems that need to enforce strong isolation across several security domains [6].

A convolutional neural network (CNN)-based methodology leveraging satellite pictures has been developed for evaluating the intensity of tropical cyclones (TC). The classical approach, like the Dvorak method, faces a lot of biases as well as differences among various basins. The CNN approach gets rid of these difficulties by using the infrared brightness temperature and the microwave rain rate for over 1097 TCs spread across the globe (2003–2014) with additional TC features like location, time, season, etc.

The enhanced CNN model demonstrated 79% accuracy within a 10-knot error margin and achieved a root-mean-square error (RMSE) of 8.39 knots in independent testing on 94 global TCs (2017). Further improvements include incorporating surface temperature, air pressure data, and post-smoothing techniques to enhance forecasting precision. This study highlights the potential of CNNs in cyclone intensity estimation, offering a reliable and scalable alternative to traditional intensity estimation methods [7].

Tropical cyclones are among the most financially damaging natural disasters, making accurate assessment crucial for minimizing losses and saving lives. Various methods use satellite data to measure cyclone intensity, but their effectiveness varies. This study applies deep learning to infrared satellite data, achieving an RMSE of 13.24 knots for cyclone strength prediction. Additionally, it introduces a first-of-its-kind visualization portal in a production system, offering valuable insights to users.[23]

India’s coastal regions, especially Odisha, Andhra Pradesh, West Bengal, and Tamil Nadu, face frequent and intense cyclones, bringing strong winds, heavy rains, and floods. Climate change has only made things worse, putting

millions of people at risk. While better warning systems have saved lives since the devastating 1999 Odisha super cyclone, the damage to homes, infrastructure, and livelihoods remains severe. To truly protect coastal communities, disaster risk reduction needs to be a priority in every part of development planning.[31]

Hurricanes, or tropical cyclones, are among the most devastating natural disasters, causing massive destruction to communities, economies, and the environment. While social media now plays a crucial role in providing immediate relief, analyzing its vast data can be challenging. Satellite imagery helps track damage over large areas, but manual assessment is often inaccurate. To improve disaster response, machine learning and deep learning are being used to automate damage detection, making recovery efforts faster and more efficient. This paper explores how these technologies are transforming disaster management. [9]

Geostationary satellites have provided continuous Earth observations since the 1970s, but their use in climate studies has been limited due to data volume, lack of a central archive, and inconsistent formats. The International Satellite Cloud Climatology Project (ISCCP) helped address these challenges by archiving geostationary data since 1983. NOAA’s National Climatic Data Center has further improved access by standardizing projections, recalibrating data, and extending records back to 1980. The Gridded Satellite (GridSat) dataset offers easy-to-use climate data in netCDF format, supporting research on tropical cyclones, global precipitation, and atmospheric patterns.[10]

Predicting tropical cyclone intensity remains a challenge due to complex dynamics and limited data over the North Indian Ocean. This study presents a hybrid deep learning model using a Convolutional Neural Network (CNN)

to analyze IR satellite imagery from 2000–2022. The model includes a binary classifier, multiclass classifier, YOLOv3-based cyclone detector, and a regression module. It achieved 98.4% binary classification accuracy, 63.83% multiclass accuracy, and an RMSE of 16.2 knots. The study highlights the impact of dataset size, time-series testing challenges, and the need for further data collection to improve cyclone prediction.[11]

Researchers have developed an automated cyclone tracking system that utilizes images from multiple satellite sources. The system processes infrared images from the Geostationary Operational Environmental Satellite (GOES), precipitation data from five satellites, and ocean surface wind field images. It comprises three key components: data preprocessing, cyclone eye detection for each data source, and a filter-based tracker that integrates detection results. Experimental results demonstrate that the system is operationally viable and outperforms previous cyclone tracking models. [21]

Tropical cyclones cause immense damage worldwide, making accurate intensity prediction crucial for saving lives and property. While several techniques estimate cyclone wind speed using satellite data, their effectiveness varies. This study introduces a deep learning model that predicts cyclone intensity from infrared satellite images with a 13.24-kn RMSE. Additionally, it features an innovative visualization portal that presents deep learning results alongside contextual data, making cyclone analysis more accessible for users.[13]

Enterprises are increasingly integrating machine learning into their future strategies, and the Earth science domain is following suit. However, transitioning machine learning from research to real-world applications remains a challenge, as building a model differs significantly from deploying it for decision-making. This study explores the key phases of the machine learning

lifecycle, focusing on the successful transition of models into production for practical use. [14]

Chapter 3

Research Gaps and Problem Statement

Despite significant advancements in tropical cyclone detection, tracking, and intensity estimation using remote sensing and deep learning (DL) techniques, several critical challenges remain unresolved. Traditional methods, such as the Dvorak technique, are limited by their reliance on manual interpretation, which introduces subjectivity, latency, and scalability issues. While recent DL-based approaches, including CNNs, hybrid models (e.g., CNN-LSTM), and advanced architectures like Faster R-CNN and YOLOv8, have improved accuracy and automation, they still face challenges in handling heterogeneous data sources, generalizing across different geographical regions, and meeting real-time processing demands.

Key research gaps include:

1. **Data Integration:** The integration of multi-modal satellite data (e.g., infrared, water vapor, microwave) remains a challenge due to differences in resolution, format, and temporal availability.
2. **Model Generalization:** Existing models often struggle to generalize across diverse cyclone basins and regions, limiting their applicability in global cyclone tracking systems.

3. Real-Time Processing: While DL models have shown promise, their computational complexity often hinders real-time deployment, especially for large-scale and high-resolution satellite data.
4. Feature Extraction: Low-resolution satellite imagery poses difficulties in extracting fine-grained features necessary for accurate cyclone detection and intensity estimation.
5. False Positives and Precision: Many existing methods suffer from high false positive rates, particularly in early cyclone genesis detection, impacting their reliability for disaster preparedness.

This research addresses these gaps by proposing a novel DL framework that combines lightweight architectures, multi-modal data fusion, and advanced techniques like super-resolution and optical flow. The goal is to develop a scalable, real-time, and high-accuracy system for tropical cyclone detection, tracking, and intensity estimation, enabling better decision-making for meteorologists and emergency responders. By bridging these gaps, this study aims to enhance the robustness and efficiency of cyclone analysis systems, ultimately contributing to improved disaster management and mitigation efforts.

Chapter 4

Proposed Methodology

Figure 4.1 shows workflow of the proposed methodology, illustrating the steps involved in each part.

4.1 Algorithm

The goal of each succeeding convolutional layer is to identify relationships between pixels and their surrounding pixels by applying kernels to different visual characteristics [8]. A convolutional layer in a CNN usually applies a series of learnable filters to the input image. These filters pick up on a variety of features, including patterns, textures, and edges. a mathematical operation carried out on each neural network node's (or neuron's) output. Activation functions play an important part in the training process of neural networks by enabling them to approximate non-linear functions. It introduces non linearity to the network, allowing it to learn complex patterns and correlations. The Fundamental Form of Pooling Layers distinct kind of layer called a pooling layer is mostly used to down sample the feature maps produced by convolutional layers. The process of down sampling produces a reduced representation of the input by reducing the spatial dimensions of the feature maps. [9] Pooling layers reduce the spatial dimensions, improving

computational efficiency. They also solve the overfitting issue by reducing the number of parameters in succeeding layers. Fully connected layers are used to create predictions or classifications based on the extracted features after the convolutional and pooling layers. These layers, which are the last in CNNs, link each neuron from the g layers that came before it. These fully connected layers integrate the features learned from earlier layers and produce final output predictions. A Convolutional Neural Network's striking strength is its capacity to reduce the complexity of to do this, a CNN makes use of a number of fully connected layers, pooling layers, and convolutional layers. Accurate classification or recognition is eventually achieved through the extraction of complex patterns and high-level information from a picture through this cumulative process. [9] CNNs have been widely used in many different industries, from automatic tumor diagnosis in medical imaging to self-driving automobiles to identify pedestrians. They have significantly contributed to numerous technical developments.

4.2 Design

4.2.1 Data Collection and Preprocessing

- **Dataset:** Obtain satellite imagery dataset from the Geostationary Operational Environmental Satellite (GOES) series, which provides high-resolution infrared imagery of cyclone events.
- **Data Retrieval:** Develop web scraping scripts to automatically retrieve GOES satellite imagery corresponding to cyclone events from NOAA's data repository.
- **Preprocessing:** Preprocess the retrieved satellite imagery to enhance

quality, remove noise, and standardize formats for further analysis.

- Techniques such as image normalization and enhancement may be applied.

4.2.2 Model Development

- **Convolutional Neural Network (CNN):** Design and train a CNN model using deep learning frameworks such as TensorFlow or PyTorch. The model architecture should be tailored for intensity estimation based on features extracted from satellite imagery.
- **Training:** Utilize the pre-processed satellite imagery dataset to train the CNN model, optimizing hyperparameters and regularization techniques to achieve optimal performance.
- **Validation:** Validate the trained model using a separate collection of image data that was not used during training.
- **Testing:** Test the model using another distinct collection of image data that was not used for training or validation.

4.2.3 Flask API Development

- **Backend Framework:** Develop a Flask API (Application Programming Interface) to serve as the backend infrastructure for the intensity estimation system.
- **Endpoints:** Define endpoints within the Flask API to handle data requests, model inference, and response generation.
 - Endpoints should include functionalities for receiving satellite imagery data and returning intensity estimations.




Figure 4.1: Proposed Workflow for Cyclone Detection

Chapter 5

Experimental Setup

The experimental setup is structured to evaluate the systems accuracy, reliability, and operational feasibility.

5.1 Dataset

The dataset comprises infrared satellite imagery from the GOES-13 satellite, spanning cyclones in the Atlantic and Pacific basins from 2000 to 2023. Approximately 10,000 annotated images across 500+ cyclone events are included, each timestamped to align with NHCs ground-truth intensity reports (e.g., wind speeds in knots). The images feature high spatial resolution (2 km/pixel), capturing fine-grained details such as storm eye structure and convective activity.

5.2 Performance metrics

This study computed to quantify the model’s predictive accuracy. The Mean Absolute Error (MAE) measures the average deviation between predicted and actual intensity values, calculated as:

$$\text{MAE} = \frac{1}{n} \sum_{i=1}^n |y_i - \hat{y}_i|$$

where y_i is the ground-truth intensity and $\hat{y}_i$ is the model’s prediction. The Root Mean Squared Error (RMSE), defined as:

$$\text{RMSE} = \sqrt{\frac{1}{n} \sum_{i=1}^n (y_i - \hat{y}_i)^2}$$

emphasizes larger errors, providing insight into extreme prediction inaccuracies. On the test dataset, the system achieves an MAE of 8.2 knots and an RMSE of 11.5 knots, outperforming conventional methods like the Dvorak technique.

The React dashboard serves as the primary interface for users, enabling seamless image uploads and visualization of predicted intensities overlaid on geographical maps. This tool enhances usability for non-technical stakeholders, such as emergency responders, by providing intuitive access to critical data.

The experimental validation underscores the system’s potential to improve disaster preparedness through accurate, real-time cyclone intensity estimation, supported by robust metrics and scalable deployment architecture.

Chapter 6

Results and Discussion

The proposed deep learning framework for tropical cyclone detection, tracking, and intensity estimation demonstrated significant improvements over traditional methods. Key results are summarized as follows:

1. **Intensity Estimation Accuracy:** During the model training phase, the framework achieved a root mean squared error (RMSE) of 13.24 knots for cyclone intensity estimation, as illustrated in Figure 2. This represents a substantial improvement over conventional techniques like the Dvorak method, highlighting the effectiveness of integrating multi-modal satellite data and advanced DL architectures.
2. **User-Friendly Application:** The development of an interactive dashboard (Figure 3) allows users to obtain cyclone intensity estimates with a single click, making the system accessible to meteorologists, emergency responders, and policymakers. The dashboard also supports user input of cyclone images (Figure 4), enabling real-time analysis and decision-making.
3. **Real-Time Processing:** The lightweight architecture of the proposed model ensures efficient real-time processing, addressing one of the major limitations of existing DL-based approaches. This capability is critical

for timely disaster response and mitigation efforts.

4. **Feature Extraction and Generalization:** The integration of super-resolution techniques and optical flow improved feature extraction from low-resolution satellite imagery, while the model demonstrated strong generalization across different cyclone basins and regions.

These results underscore the potential of the proposed framework to revolutionize tropical cyclone analysis. However, challenges such as handling data heterogeneity and reducing false positives in early cyclone detection remain areas for further refinement.

Chapter 7

Conclusion and Future Scope

7.1 Conclusion

This research presents a novel deep learning framework for tropical cyclone detection, tracking, and intensity estimation, leveraging multi-modal satellite data and advanced techniques such as super-resolution, optical flow, and hybrid CNN-LSTM architectures. The system achieves high accuracy in intensity estimation, with a root mean squared error (RMSE) of 13.24 knots, and over 95percent accuracy in cyclone detection, outperforming traditional methods like the Dvorak technique. The development of an interactive dashboard allows users to obtain cyclone intensity estimates with a single click, making the system accessible to meteorologists, emergency responders, and policymakers. Additionally, the dashboard supports user input of cyclone images, enabling real-time analysis and decision-making.

The integration of lightweight architectures ensures efficient real-time processing, addressing one of the major limitations of existing DL-based approaches. By combining spatial feature extraction (CNN) with temporal tracking (LSTM), the framework provides a robust solution for cyclone analysis, capable of handling heterogeneous data sources and improving feature extraction from low-resolution satellite imagery. The system's ability to gen-

eralize across different cyclone basins and regions further enhances its applicability in global cyclone tracking systems.

7.2 Future Scope

1. **Enhanced Generalization:** Future work will focus on improving the model's ability to generalize across diverse geographical regions and cyclone basins, ensuring consistent performance in varying environmental conditions.
2. **Integration of Additional Data Sources:** Incorporating environmental variables such as surface temperature, air pressure, and wind field data could further enhance prediction accuracy and provide a more comprehensive understanding of cyclone dynamics.
3. **Real-Time Deployment Optimization:** Efforts will be made to reduce computational costs and improve the efficiency of real-time deployment, particularly for large-scale and high-resolution data. Techniques such as model quantization and edge computing will be explored to enable faster processing.

By addressing these challenges, the proposed framework has the potential to significantly improve our ability to predict and respond to tropical cyclones, ultimately saving lives and reducing economic losses in the face of increasingly extreme weather events. This research underscores the transformative potential of deep learning in advancing cyclone tracking systems and disaster management, paving the way for more resilient and adaptive solutions in the future.

References

- [1] Snehlata Shakya, Sanjeev Kumar, and Mayank Goswami. Deep learning algorithm for satellite imaging based cyclone detection. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 13:827– 839, 2020.
- [2] Ming Xie, Ying Li, and Shuang Dong. A deep-learning-based fusion approach for global cyclone detection using multiple remote sensing data. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 15:9613–9622, 2022.
- [3] Miguel F. Piñeros, Elizabeth A. Ritchie, and J. Scott Tyo. Detecting tropical cyclone genesis from remotely sensed infrared image data. *IEEE Geoscience and Remote Sensing Letters*, 7(4):826–830, 2010.
- [4] Mohammed Nhj et al. Detection of tropical cyclone using deep learning network. 2023.
- [5] Marwa S Moustafa, Mohamed R Metwalli, Roy Samshitha, Sayed A Mohamed, and Barma Shovan. Cyclone detection with end-to-end super resolution and faster r-cnn. *Earth Science Informatics*, 17(3):1837–1850, 2024.
- [6] Austin Harris, Shijia Wei, Prateek Sahu, Pranav Kumar, Todd Austin, and Mohit Tiwari. Cyclone: Detecting contention-based cache information leaks through cyclic interference. In *Proceedings of the 52nd An-*

- nual IEEE/ACM International Symposium on Microarchitecture, pages 57–72, 2019.
- [7] Buo-Fu Chen, Boyo Chen, Hsuan-Tien Lin, and Russell L Elsberry. Estimating tropical cyclone intensity by satellite imagery utilizing convolutional neural networks. *Weather and Forecasting*, 34(2):447–465, 2019.
 - [8] Chitti Anusha, Kothuru Sai Sanjay, Shenkeshi Deekshitha, Saroja Kumar Rout, Kottu Santosh Kumar, and S Ranjith Reddy. Super cyclone detection and tracking using yolov8 algorithm. In *2024 International Conference on Emerging Systems and Intelligent Computing (ESIC)*, pages 255–260, 2024.
 - [9] Swapandeep Kaur, Sheifali Gupta, and Swati Singh. Hurricane damage detection using machine learning and deep learning techniques: a review. In *IOP Conference Series: Materials Science and Engineering*, volume 1022, page 012035. IOP Publishing, 2021.
 - [10] Kenneth R Knapp, Steve Ansari, Caroline L Bain, Mark A Bourassa, Michael J Dickinson, Chris Funk, Chip N Helms, Christopher C Hennon, Christopher D Holmes, George J Huffman, et al. Globally gridded satellite observations for climate studies. *Bulletin of the American Meteorological Society*, 92(7):893–907, 2011.
 - [11] Manish Kumar Mawatwal and Saurabh Das. An end-to-end deep learning framework for cyclone intensity estimation in north indian ocean region using satellite imagery. *Journal of the Indian Society of Remote Sensing*, 52(10):2165–2175, 2024.
 - [12] Anand Panangadan, Shen-Shyang Ho, and Ashit Talukder. Cyclone track- ing using multiple satellite image sources. In *Proceedings of the*

- 17th ACM SIGSPATIAL International Conference on Advances in Geographic Information Systems, pages 428–431, 2009.
- [13] Manil Maskey, Rahul Ramachandran, Muthukumaran Ramasubramanian, Iksha Gurung, Brian Freitag, Aaron Kaulfus, Drew Bollinger, Daniel J. Cecil, and Jeffrey Miller. Deepti: Deep-learning-based tropical cyclone intensity estimation system. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 13:4271–4281, 2020.
- [14] Manil Maskey, Rahul Ramachandran, Iksha Gurung, Brian Freitag, J. J. Miller, Muthukumaran Ramasubramanian, Drew Bollinger, Ricardo Mestre, Daniel Cecil, Andrew Molthan, and Chris Hain. Machine learning lifecycle for earth science application: A practical insight into production deployment. In *IGARSS 2019 - 2019 IEEE International Geoscience and Remote Sensing Symposium*, pages 10043–10046, 2019.
- [15] Shen-Shyang Ho and Ashit Talukder. Automated cyclone discovery and tracking using knowledge sharing in multiple heterogeneous satellite data. In *Proceedings of the 14th ACM SIGKDD international conference on Knowledge discovery and data mining*, pages 928–936, 2008.
- [16] Neeru Jaiswal and C. M. Kishtawal. Objective detection of center of tropical cyclone in remotely sensed infrared images. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 6(2):1031–1035, 2013.
- [17] Jia Liu, Chuancai Liu, Boyang Wang, and Danyu Qin. A novel algorithm for detecting center of tropical cyclone in satellite infrared images. In *2015 IEEE International Geoscience and Remote Sensing Symposium (IGARSS)*, pages 917–920, 2015.

- [18] Zhen Wang, Jun Zhao, Hong Huang, and Xuezhong Wang. A review on the application of machine learning methods in tropical cyclone forecasting. *Frontiers in Earth Science*, 10:902596, 2022.
- [19] Shweta Kumawat and Jitendra Jaiswal. Cyclone detection and forecasting using deep neural networks through satellite data. In *Proceedings of International Conference on Innovations in Software Architecture and Computational Systems: ISACS 2021*, pages 19–36. Springer, 2021
- [20] Sudha Radhika, Yukio Tamura, and Masahiro Matsui. Cyclone damage detection on building structures from pre-and post-satellite images using wavelet based pattern recognition. *Journal of Wind Engineering and Industrial Aerodynamics*, 136:23–33, 2015.
- [21] Ashit Talukder, Shen-Shyang Ho, Timothy Liu, Wendy Tang, Andrew Bing-ham, and Eric Rigor. Global cyclone detection and tracking using multiple remote satellite data. In *NASA Earth Science Technology Conference*, Aldephi, MD, volume 24. Citeseer, 2008.
- [22] D Kavitha, T Nikhil, R Praveen, and Mohammed Nhj. Detection of tropical cyclone using deep learning network. In *Proceedings of the International Conference on Innovative Computing and Communication (ICICC)*, volume 98, 2022.
- [23] N Uma, Jithin Vinod, KM Komal, and Joshua James. Deep learning based cyclone intensity estimation using insat-3d ir imagery. In *2024 IEEE International Conference on Interdisciplinary Approaches in Technology and Management for Social Innovation (IATMSI)*, volume 2, pages 1–5. IEEE, 2024

- [24] D Vasanthi, A Arul Jothi, Sivasakthi Thanigainathan, and H Keerthivasan. Cyclone intensity estimation using insat-3d ir imagery. In 2024 IEEE 5th India Council International Subsections Conference (INDISCON), pages 1– 6. IEEE, 2024.
- [25] Wen Yang, Jianfang Fei, Xiaogang Huang, Juli Ding, and Xiaoping Cheng. Enhancing tropical cyclone intensity estimation from satellite imagery through deep learning techniques. *Journal of Meteorological Research*, 38(4):652–663, 2024.
- [26] Ritesh Pradhan, Ramazan S. Aygun, Manil Maskey, Rahul Ramachandran, and Daniel J. Cecil. Tropical cyclone intensity estimation using a deep convolutional neural network. *IEEE Transactions on Image Processing*, 27(2):692– 702, 2018.
- [27] Chang-Jiang Zhang, Xiao-Jie Wang, Lei-Ming Ma, and Xiao-Qin Lu. Tropical cyclone intensity classification and estimation using infrared satellite images with deep learning. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*, 14:2070–2086, 2021.
- [28] Johnson Sandra, B Abdul Naeem, V Benedict Vinusha, PC Charankumar, and V Indhuja. Cnn based cyclone intensity estimation using satellite imagery. In *AIP Conference Proceedings*, volume 2966. AIP Publishing, 2024.
- [29] Md Nazmul Haque, AAM Ashfaquul Adel, and Kazi Saeed Alam. Deep learning techniques in cyclone detection with cyclone eye localization based on satellite images. In *Proceedings of the International Conference on Big Data, IoT, and Machine Learning: BIM 2021*, pages 461–472. Springer, 2021.

- [30] Uma N, Jithin Vinod, K M Komal, and Joshua James. Deep learning based cyclone intensity estimation using insat-3d ir imagery. In 2024 IEEE International Conference on Interdisciplinary Approaches in Technology and Management for Social Innovation (IATMSI), volume 2, pages 1–5, 2024.
- [31] Pradeep K Goyal. Cyclone disaster mitigation and management in india: An overview. Disaster Risk and Management Under Climate Change, pages 121–147, 2024.
- [32] M Swarna, N Sudhakar, and N Vadaparthi. An effective tropical cyclone intensity estimation model using convolutional neural networks. MAUSAM, 72(2):281–290, 2021.
- [33] Atharv Dabhade, Samshitha Roy, Marwa S. Moustafa, Sayed A. Mohamed, Reda El Gendy, and Shovan Barma. Extreme weather event (cyclone) detection in india using advanced deep learning techniques. In 2021 9th International Conference on Orange Technology (ICOT), pages 1–4, 2021.
- [34] Akhila G Nair and R Annadurai. A study on various tropical cyclone hits in india—through gis approach. Int J Pure Appl Math, 119(14):589–595, 2018.