



COMPUTER COMMUNICATION NETWORKS (UE22EC351A)

PES
UNIVERSITY

CELEBRATING **50** YEARS

Department of Electronics and Communication Engineering

COMPUTER COMMUNICATION NETWORKS (UE22EC351A)

UNIT 1: INTERNET ARCHITECTURE AND APPLICATIONS – Class 14 – Web & HTTP – Message Formats


Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Request message

```
GET /somedir/page.html HTTP/1.1
Host: www.someschool.edu
Connection: close
User-agent: Mozilla/5.0
Accept-language: fr
```

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message
 - Entity body is empty (download) or non-empty (upload)



Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Request line
- The first line of an HTTP request message is called the **request line**;
- the subsequent lines are called the **header lines**.
- The request line has **three** fields: the **method** field, the **URL** field, and the **HTTP version** field.
- The method field can take on several different values, including **GET**, **POST**, **HEAD**, **PUT**, and **DELETE**.
- The great majority of HTTP request messages use the **GET** method. The **GET** method is used when the browser requests an object, with the requested object identified in the URL field.

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Header line
- Now let's look at the **header lines** in the example.
- The header line Host: **www.someschool.edu** specifies the host on which the object resides.
- You might think that this header line is unnecessary, as there is already a TCP connection in place to the host. But, the information provided by the host header line is required by **Web proxy caches**.
- By including the Connection: close header line, the browser is telling the server that it doesn't want to bother with **persistent connections**; it wants the server to close the connection after sending the requested object.

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Header line
- The **User-agent**: header line specifies the user agent, that is, the browser type that is making the request to the server.
- Here the user agent is **Mozilla/5.0**, a Firefox browser.
- This header line is useful because the server can actually send different versions of the same object to different types of user agents. (Each of the versions is addressed by the same URL.)

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Header line
- Finally, the **Accept-language**: header indicates that the user prefers to receive a French version of the object, if such an object exists on the server; otherwise, the server should send its default version.
- The **Accept-language**: header is just one of many content negotiation headers available in HTTP.

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Header line
- You may have noticed, however, that after the **header lines** (and the additional carriage return and line feed) there is an “**entity body.**”
- The entity body is empty with the **GET** method, but is used with the POST method.
- An HTTP client often uses the **POST** method when the user fills out a form—for example, when a user provides search words to a search engine.

Unit 1 – Class 14 - Web and HTTP: Message format

- HTTP Request message – Header line
- With a **POST** message, the user is still requesting a Web page from the server, but the specific contents of the Web page depend on what the user entered into the form fields. If the value of the method field is POST, then the entity body contains what the user entered into the form fields.

Unit 1 – Class 14 - Web and HTTP: Message format

- Example-GET message:

- Request webpage www.gaia.cs.umass.edu/wireshark-labs/HTTP-wireshark-file.html

```
> Frame 921: 469 bytes on wire (3752 bits), 469 bytes captured (3752 bits) on interface 0
> Ethernet II, Src: HewlettP_7a:62:9d (6c:c2:17:7a:62:9d), Dst: HewlettP_84:19:80 (d4:c9:ef:84:19:80)
> Internet Protocol Version 4, Src: 172.16.175.59 (172.16.175.59), Dst: gaia.cs.umass.edu (128.119.245.12)
> Transmission Control Protocol, Src Port: 56506, Dst Port: 80, Seq: 1, Ack: 1, Len: 415
▼ Hypertext Transfer Protocol
  > GET /wireshark-labs/HTTP-wireshark-file1.html HTTP/1.1\r\n
    Host: gaia.cs.umass.edu\r\n
    Connection: keep-alive\r\n
    Upgrade-Insecure-Requests: 1\r\n
    User-Agent: Mozilla/5.0 (Windows NT 10.0; WOW64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/55.0.2883.87 Safari/537.36\r\n
    Accept: text/html,application/xhtml+xml,application/xml;q=0.9,image/webp,*/*;q=0.8\r\n
    Accept-Encoding: gzip, deflate, sdch\r\n
    Accept-Language: en-US,en;q=0.8\r\n
```

Unit 1 – Class 14 - Web and HTTP: Message format

- Example-GET message (contd.):
 - Inspecting the raw data of the TCP segment

| | |
|---|-------------------|
| f5 0c dc b7 00 50 1c 15 d2 d7 6c d8 fa eb 50 18 |P.. ..l...P. |
| fd b8 b7 19 00 00 47 45 54 20 2f 77 69 72 65 73 |GE T /wires |
| 68 61 72 6b 2d 6c 61 62 73 2f 68 74 74 70 2d 77 | hark-lab s/http-w |
| 69 72 65 73 68 61 72 6b 2d 66 69 6c 65 31 2e 68 | ireshark -file1.h |
| 74 6d 6c 20 48 54 54 50 2f 31 2e 31 0d 0a 48 6f | tml HTTP /1.1..Ho |
| 73 74 3a 20 67 61 69 61 2e 63 73 2e 75 6d 61 73 | st: gaia .cs.umas |
| 73 2e 65 64 75 0d 0a 43 6f 6e 6e 65 63 74 69 6f | s.edu..C onnectio |
| 6e 3a 20 6b 65 65 70 2d 61 6c 69 76 65 0d 0a 55 | n: keep- alive..U |
| 70 67 72 61 64 65 2d 49 6e 73 65 63 75 72 65 2d | pgrade-I nsecure- |
| 52 65 71 75 65 73 74 73 3a 20 31 0d 0a 55 73 65 | Requests : 1..Use |
| 72 2d 41 67 65 6e 74 3a 20 4d 6f 7a 69 6c 6c 61 | r-Agent: Mozilla |
| 2f 35 2e 30 20 28 57 69 6e 64 6f 77 73 20 4e 54 | /5.0 (Wi ndows NT |
| 20 31 30 2e 30 3b 20 57 4f 57 36 34 29 20 41 70 | 10.0; W OW64) Ap |
| 70 6c 65 57 65 62 4b 69 74 2f 35 33 37 2e 33 36 | pleWebKi t/537.36 |
| 20 28 4b 48 54 4d 4c 2c 20 6c 69 6b 65 20 47 65 | (KHTML, like Ge |
| 63 6b 6f 29 20 43 68 72 6f 6d 65 2f 35 35 2e 30 | cko) Chr ome/55.0 |
| 2e 32 38 38 33 2e 38 37 20 53 61 66 61 72 69 2f | .2883.87 Safari/ |
| 35 33 37 2e 33 36 0d 0a 41 63 63 65 70 74 3a 20 | 537.36.. Accept: |
| 74 65 78 74 2f 68 74 6d 6c 2c 61 70 70 6c 69 63 | text/htm l,applic |
| 61 74 69 6f 6e 2f 78 68 74 6d 6c 2b 78 6d 6c 2c | ation/xh tml+xml, |
| 61 70 70 6c 69 63 61 74 69 6f 6e 2f 78 6d 6c 3b | applicat ion/xml; |
| 71 3d 30 2e 39 2c 69 6d 61 67 65 2f 77 65 62 70 | q=0.9,image/webp |
| 2c 2a 2f 2a 3b 71 3d 30 2e 38 0d 0a 41 63 63 65 | ,*/*;q=0 .8..Acce |

Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Response Message

```
HTTP/1.1 200 OK
Connection: close
Date: Tue, 18 Aug 2015 15:44:04 GMT
Server: Apache/2.2.3 (CentOS)
Last-Modified: Tue, 18 Aug 2015 15:11:03 GMT
Content-Length: 6821
Content-Type: text/html

(data data data data data ...)
```

Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Response Message
- Let's take a careful look at this **response** message.
- It has three sections: an initial **status line**, **six header lines**, and then the **entity body**.
- The entity body is the meat of the message—it contains the requested object itself (represented by **data data data data data**)
- The status line has three fields: the **protocol version field**, a **status code**, and a corresponding **status** message.

Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Response Message
- In this example, the status line indicates that the server is using **HTTP/1.1** and that everything is OK (that is, the server has found, and is sending, the requested object).
- Now let's look at the header lines. The server uses the **Connection: close header line** to tell the client that it is going to close the TCP connection after sending the message.
- The **Date: header line** indicates the time and date when the HTTP response was created and sent by the server.

Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Response Message
- Note that this is not the time when the object was created or last modified; it is the time when the server retrieves the object from its file system, inserts the object into the **response message**, and sends the **response message**.
- The **Server: header line** indicates that the message was generated by an **Apache Web server**; it is analogous to the **User-agent: header line** in the **HTTP request message**.

Unit 1 – Class 14 - Web and HTTP: Message format

- Typical HTTP Response Message
- The **Last-Modified: header line** indicates the time and date when the object was created or last modified.
- The Last-Modified: header, which we will soon cover in more detail, is critical for **object caching**, both in the local client and in network cache servers (also known as proxy servers).
- The **Content-Length: header line** indicates the number of bytes in the object being sent. The Content-Type: header line indicates that the object in the entity body is HTML text. (The object type is officially indicated by the Content-Type: header and not by the file extension.)

Unit 1 – Class 14 - Web and HTTP: Message format


- Common Status Codes
- **200 OK** – Request Succeeded & the information is returned in the response
- **301 Moved Permanently**: Requested object has been permanently moved; the new **URL** is specified in Location: header of the response message. The client software will automatically retrieve the new URL
- **400 Bad Request**: This is a generic error code indicating that the request could not be understood by the server.
- **404 Not Found**: The requested document does not exist on this server

Unit 1 – Class 14 - Web and HTTP: Message format

- Common Status Codes
- **505 HTTP Version Not Supported**: The requested HTTP protocol version is not supported by the server.

Unit 1 – Class 14 - Web and HTTP: Message format

- Web server sends the response message which could have the requested object



Unit 1 – Class 14 - Web and HTTP: Message format

- Example-HTTP response message:

```
Internet Protocol Version 4, Src: gaia.cs.umass.edu (128.119.245.12), Dst: 172.16.175.59 (172.16.175.59)
Transmission Control Protocol, Src Port: 80, Dst Port: 56506, Seq: 1, Ack: 416, Len: 486
Hypertext Transfer Protocol
  > HTTP/1.1 200 OK\r\n
    Date: Sat, 21 Jan 2017 08:43:06 GMT\r\n
    Server: Apache/2.4.6 (CentOS) OpenSSL/1.0.1e-fips PHP/5.4.16 mod_perl/2.0.10 Perl/v5.16.3\r\n
    Last-Modified: Sat, 21 Jan 2017 06:59:01 GMT\r\n
    ETag: "80-546954d1f3d0a"\r\n
    Accept-Ranges: bytes\r\n
  > Content-Length: 128\r\n
    Keep-Alive: timeout=5, max=100\r\n
    Connection: Keep-Alive\r\n
    Content-Type: text/html; charset=UTF-8\r\n
    \r\n
    [HTTP response 1/1]
    [Time since request: 0.555626000 seconds]
    \[Request in frame: 921\]
    File Data: 128 bytes
Line-based text data: text/html
  <html>\n
  Congratulations. You've downloaded the file \n
  http://gaia.cs.umass.edu/wireshark-labs/HTTP-wireshark-file1.html!\n
  </html>\n
```

Unit 1 – Class 14 - Web and HTTP: Message format

- Example-HTTP response (contd.):

| | | |
|------|---|--------------------|
| 0010 | 02 0e 40 5f 40 00 3f 06 28 bb 80 77 f5 0c ac 10 | ..@_@.?. (..w.... |
| 0020 | af 3b 00 50 dc ba 3b 63 bc f5 29 6a 6a 7f 50 18 | .;.P.;c..)jj.P. |
| 0030 | 75 40 df 57 00 00 48 54 54 50 2f 31 2e 31 20 32 | u@.W..HT TP/1.1 2 |
| 0040 | 30 30 20 4f 4b 0d 0a 44 61 74 65 3a 20 53 61 74 | 00 OK..D ate: Sat |
| 0050 | 2c 20 32 31 20 4a 61 6e 20 32 30 31 37 20 30 38 | , 21 Jan 2017 08 |
| 0060 | 3a 34 33 3a 30 36 20 47 4d 54 0d 0a 53 65 72 76 | :43:06 G MT..Serv |
| 0070 | 65 72 3a 20 41 70 61 63 68 65 2f 32 2e 34 2e 36 | er: Apac he/2.4.6 |
| 0080 | 20 28 43 65 6e 74 4f 53 29 20 4f 70 65 6e 53 53 | (CentOS) OpenSS |
| 0090 | 4c 2f 31 2e 30 2e 31 65 2d 66 69 70 73 20 50 48 | L/1.0.1e -fips PH |
| 00a0 | 50 2f 35 2e 34 2e 31 36 20 6d 6f 64 5f 70 65 72 | P/5.4.16 mod_per |
| 00b0 | 6c 2f 32 2e 30 2e 31 30 20 50 65 72 6c 2f 76 35 | l/2.0.10 Perl/v5 |
| 00c0 | 2e 31 36 2e 33 0d 0a 4c 61 73 74 2d 4d 6f 64 69 | .16.3..L ast-Modi |
| 00d0 | 66 69 65 64 3a 20 53 61 74 2c 20 32 31 20 4a 61 | fied: Sa t, 21 Ja |
| 00e0 | 6e 20 32 30 31 37 20 30 36 3a 35 39 3a 30 31 20 | n 2017 0 6:59:01 |
| 00f0 | 47 4d 54 0d 0a 45 54 61 67 3a 20 22 38 30 2d 35 | GMT..ETa g: "80-5 |
| 0100 | 34 36 39 35 34 64 31 66 33 64 30 61 22 0d 0a 41 | 46954d1f 3d0a"..A |
| 0110 | 63 63 65 70 74 2d 52 61 6e 67 65 73 3a 20 62 79 | ccept-Ra nges: by |
| 0120 | 74 65 73 0d 0a 43 6f 6e 74 65 6e 74 2d 4c 65 6e | tes..Con tent-Len |
| 0130 | 67 74 68 3a 20 31 32 38 0d 0a 4b 65 65 70 2d 41 | gth: 128 ..Keep-A |
| 0140 | 6c 69 76 65 3a 20 74 69 6d 65 6f 75 74 3d 35 2c | live: ti meout=5, |
| 0150 | 20 6d 61 78 3d 31 30 30 0d 0a 43 6f 6e 6e 65 63 | max=100 ..Conne |
| 0160 | 74 69 6f 6e 3a 20 4b 65 65 70 2d 41 6c 69 76 65 | ction: Ke ep-Alive |
| 0170 | 0d 0a 43 6f 6e 74 65 6e 74 2d 54 79 70 65 3a 20 | ..Conten t-Type: |
| 0180 | 74 65 78 74 2f 68 74 6d 6c 3b 20 63 68 61 72 73 | text/htm l; chars |
| 0190 | 65 74 3d 55 54 46 2d 38 0d 0a 0d 0a 3c 68 74 6d | et=UTF-8<htm |
| 01a0 | 6c 3e 0a 43 6f 6e 67 72 61 74 75 6c 61 74 69 6f | l>.Congr atulatio |
| 01b0 | 6e 73 2e 20 20 59 6f 75 27 76 65 20 64 6f 77 6e | ns. You 've down |
| 01c0 | 6c 6f 61 64 65 64 20 74 68 65 20 66 69 6c 65 20 | loaded t he file |
| 01d0 | 0a 68 74 74 70 3a 2f 2f 67 61 69 61 2e 63 73 2e | .http:// gaia.cs. |

Unit 1 – Class 14 - Web and HTTP: Message format

- Consider the HTTP messages exchanged between the client (web browser) and the web server as given below.

```
GET /ethereal-labs/lab2-3.html HTTP/1.1\r\n
Host: gaia.cs.umass.edu\r\n
User-Agent: Mozilla/5.0 (Windows; U; Windows NT 5.1; en-US; rv:1.0.2) Gecko/20021120
Accept: text/xml,application/xml,application/xhtml+xml,text/html;q=0.9,text/plain;q=0
Accept-Language: en-us, en;q=0.50\r\n
Accept-Encoding: gzip, deflate, compress;q=0.9\r\n
Accept-Charset: ISO-8859-1, utf-8;q=0.66, *;q=0.66\r\n
Keep-Alive: 300\r\n
Connection: keep-alive\r\n

HTTP/1.1 200 OK\r\n
Date: Tue, 23 Sep 2003 05:37:02 GMT\r\n
Server: Apache/2.0.40 (Red Hat Linux)\r\n
Last-Modified: Tue, 23 Sep 2003 05:37:01 GMT\r\n
ETag: "1bfff2-1194-96813940"\r\n
Accept-Ranges: bytes\r\n
Content-Length: 4500\r\n
Keep-Alive: timeout=10, max=100\r\n
Connection: Keep-Alive\r\n
Content-Type: text/html; charset=ISO-8859-1\r\n
```

Unit 1 – Class 14 - Web and HTTP: Message format

- Answer the following questions: (1 mark each)
- 1. What is the "method" used by the client?
- 2. What is name of the object requested by the client?
- 3. What is the name of the web server on which the object is to be located?
- 4. What is the type of TCP connection preferred by the client?
- 5. What are the status code and phrase returned by the web server?
- 6. What is the version of HTTP supported by the web server?
- 7. What is the time at which the HTTP message was generated by the web server?
- 8. When was the object last updated at the web server?
- 9. What is the size of object sent by the web server?
- 10. What is the server process used by the web-server?

Unit 1 – Class 14 - Web and HTTP: Message format

- Solution –
- 1. GET
- 2. lab2-3.html
- 3. gaia.cs.umass.edu
- 4. Persistent (keep alive)
- 5. 200 and OK
- 6. HTTP 1.1
- 7. Tue, 23 Sep 2003 5:37:02 GMT
- 8. Tue, 23 Sep 2003 5:37:01 GMT
- 9. 4500 bytes
- 10. Apache /2.0.40



THANK YOU

Department of Electronics and communication engineering