

Javascript Lab Assignments:

Use procedural DOM methods like `createElement()`, `querySelector()`, `appendChild()` etc for next 2 assignments. Please refer to given PPT for examples on how to do this

1. Create a HTML page with a few paragraphs. On clicking on any paragraph, it must be removed from the DOM

Click on para to see it deleted!

First Paragraph

Second Paragraph

Third Paragraph

Fourth Paragraph

2. Create a HTML page with a list and a button. Clicking on the button must remove all names starting with S

Names

- Suprita ▲
- Ajay
- Mahek
- Soha
- Shrilata
- Arnav ▼

Remove names starting with S

3. Refer to the HTML form (problem #5) already created as part of HTML lab.

Username:

Password:

City of Employment:

Web server:

Please specify your role:

☐ Admin

☐ Engineer

☐ Manager

☐ Guest

Single Sign-on to the following:

☐ Mail

☐ Payroll

☐ Self-service

The following requirements must be met:

- Username: Required, only alphabets allowed, maximum length is 10.
- Password: Required, must be of 4 digits followed by 3 alphabets
- City of employment. The company is located at 5 cities. So city of employment must match only one of those cities. Put cities in an array, so that matching is easier. Error if wrong city is entered
- Display appropriate messages in case of invalid data.

4. Create a HTML page that accepts order details: (display is a submit button)

Order ID :

Cust name : Cust name cannot be < 6 characters

Enter Billing date : Billing date cannot be greater than shipping date

Enter Shipping date :

Order total :

Following are validations required:

- All fields are mandatory
 - Order id must be a number
 - Customer name must be only alphabets and greater than 6 characters
 - Cust name must be greater than 5 characters.
 - Billing date must be lesser than shipping date
5. Refer to problem 5b in HTML. Write Javascript code to ensure that password and retype password fields contain same string data

NodeJS assignments:

Write simple JS files to do the following:

1. Write a function `min()` that takes an array and returns minimum number in the set of arguments. Do not use the Math predefined object
2. Simulate an online order confirmation process. A user places an order. We want to print three messages: "Order placed!", "Confirming order...", and "Order confirmed!". However, we want to delay the "Confirming order..." message by 3 seconds using `setTimeout`. Only after this message, the last message must be displayed, after a 2 second interval
3. Write a Node program that prints all the numbers between 1 and 100, each on a separate line. A few caveats:
 - o if the number is divisible by 3, print "fizz"
 - o if the number is divisible by 5, print "buzz"
 - o if the number is divisible by both 3 and 5, print "fizzbuzz"

Local Modules:

- 1) Create a user defined local module `calc.js` that exposes the following functions: `add(a,b)`, `subtract(a,b)`, `multiply(a,b)`, `divide(a,b)`, `square(a)`, `min(a,b,c)`, `max(a,b,c)`. You can use Javascript Math predefined object for this

Create a client application that invokes each of these methods

- 2) Create a user defined module that deals with strings: This module will have the following functions:
 - `palindrome(string)` : accepts a strings and checks if it is palindrome
 - `upper(string)` : converts given string to uppercase
 - `search()` : This module accepts an array that holds many web site names. Eg, www.google.com, www.msn.com, www.amazon.co.in, in.answers.yahoo.com, en.m.wikipedia.com, codehs.gitbooks.io, www.coderanch.com etc. Search for all sites that begin with "www" and display the total number of such sites. Eg for above eg, total is 4

Create a client application that invokes each of these methods