

INTEGRATED
ETDS PAN Services API Access Manual
Environment: LIVE
Version : 2.0

Change Review:

Version Number	Date	Edited by	Changes
1.0	17-02-2026	P.Kumaravel , J.Balasubramaniyan & Antony	Rolled out the API for ETDS Pan service api facility.

The following process describes the way to access ETDS services provided by Integrated. It involves the following

- A. Check the Server Status
- B. Get Authentication code
- C. Access ETDS Services

-----XXXXXXXX-----

A. Check the Server Status

Note : To Check the Server Status use the following url using GET Method "<https://emsapi.ieiletds.com/api/v1/status>"

Sample Response

```
{
  "Status": "Running"
}
```

B. Get Authentication Code

Step 1. To get Authentication Code

Users of the ETDS API can authenticate by providing their Client Id and Client Secret(provided by Integrated) in request headers. To use this method of authentication only POST method can be used.

Procedure

1. Concatenate the <Client Id> and the <Client Secret> with a colon.(<Client Id>:<Client Secret>)
For Example: If Client Id is "Tester" and Client Secret is "YTRkNGJhYmYtY2M0My0xMWVjLTh1YmYtMDA1MDU2YmE2ZmMyNzQ2YTA2MDI5YWVmYTZkNWRhZGY3YThkMTU5NGM5MmU=" then it should be
Tester:YTRkNGJhYmYtY2M0My0xMWVjLTh1YmYtMDA1MDU2YmE2ZmMyNzQ2YTA2MDI5YWVmYTZkNWRhZGY3YThkMTU5NGM5MmU=

2. Encode this Client Id and Client Secret into base64 encoding string format.
Base64(Client Id:Client Secret)

For Example :

Base64(Tester:YTRkNGJhYmYtY2M0My0xMWVjLTh1YmYtMDA1MDU2YmE2ZmMyNzQ2YTA2MDI5YWVmYTZkNWRhZGY3YThkMTU5NGM5MmU=)

Example output :

VGVzdGVyOllUUmR0poWW1ZdFkyTTBNeTB4TVdWakxUaGxZbVI0TURBMU1EVTJZbUUyWm1NeU56UTJZVEEYTURJNVIXRm1ZVFprTldSaFpHWTNZVGhrTVRVNU5HTTVNbVU9

3. Include this encoded Client Id and Client Secret in an HTTP Authorization: **Basic header**.

Authorization: Basic<blankspace><encodedbase64 Client Id and Client Secret>

For Example :

Authorization: Basic VGVzdGVyOllUUmR0poWW1ZdFkyTTBNeTB4TVdWakxUaGxZbVI0TURBMU1EVTJZbUUyWm1NeU56UTJZVEEYTURJNVIXRm1ZVFprTldSaFpHWTNZVGhrTVRVNU5HTTVNbVU9

4. Authorization header must be included for each and every request for calling ETDS API.
5. Method should be "POST"
6. Set content type as "application/x-www-form-urlencoded"
Request body should be empty
7. Submit your request to below URL
["https://emsapi.ieiletds.com/api/v1/Auth/GetAuthCode"](https://emsapi.ieiletds.com/api/v1/Auth/GetAuthCode)

Sample Response:

```
{
  "StatusCode": "200",
  "Status": "SUCCESS",
  "AuthCode": "35826FBE3BC443D8D31CCF70F-D94C01989405D4CD3B1DAC6B0ACAC4",
  "ErrorDetails": ""
}
```

Step 2. To get New PAN Request

Agent should create the below json format and submit the request to Integrated server

1. Create Json request as show below

```
{
  "token": "< encrypted token>",
  "payload": "<encrypted payload content>",
  "authkey": "<AgentID>"
}
```

2. Aes Key will be shared by Integrated and iv will be 0000000000000000.

3. For creating encrypted token Concatenate the <Client Id> and the <Auth Code> with a colon.
(<Client Id>:<Auth Code>) and encode the text into base64 format

For Example:

If Client Id is "Tester" and Auth Code is "MzU4MjZGQkVCM0JDNDQzRDhEMzFDQ0Y3MEYtRDk0QzAxOTg5NDA1RDRDRDNCMURBQzZCMEFDQUM0"
then it should be

Tester:MzU4MjZGQkVCM0JDNDQzRDhEMzFDQ0Y3MEYtRDk0QzAxOTg5NDA1RDRDRDNCMURBQzZCMEFDQUM0

4. Encode the above string into base64 format

For example:

VGZVzdGVyOk16VTRNaPhUWtWQ00wSkRORFF6UkRoRU16RkRRMFkzTUVZdFJEazBRkF4T1RnNU5
EQTF5SRFJEUkROQ01VUkJRelpDTUVGRFFVTTA

5. Encrypt the encoded token with random string as described in step 2 using AES encryption/decryption algorithm with following properties
 - a. Cipher mode should be CBC.
 - b. Padding should be PKCS7.
 - c. Keysize should be 256.
 - d. Output string should be base64 format with url safe base64 encoders.

For example:

TDJCUXFINVprdEYyQkhSVHJ6c1N6amEyazU1Sct4KzBsQ2dZTVVNZTJNZ3pKNzd0M0ZzQjFZbk0zbGE
3TTdqYzZkaDVSbWhCcmJzU0RJRVYzMEZ3ZGc9PQ

6. Create payload json as shown below

```
{
  "transaction":
  {
    "tid": "<Unique Transaction Id in numeric format maximum length of 10>",
    "agentid": "<Agent Id>",
    "subagentid": "<Sub Agent Id>",
    "scope": "<Scope of request [Scope id mentioned in separate mail]>",
    "redirecturl": "<Result redirect to agent server [url should be whitelist at Integrated end ]>",
    "title": "<title shri (1), smt (2) or kumari (3)>",
    "lastname": "<client last name maximum length of 25>",
    "firstname": "<client first name maximum length of 25>",
    "middlename": "<client middle name maximum length of 25>",
    "dateofbirth": "<client last dob maximum length of 10 EX: 01/12/1900 >",
    "mobilen0": "<client mobile no maximum length of 10>",
    "emailid": "<client email id maximum length of 75>",
    "pan": "<client pan maximum length of 10 only for correction >"
  }
}
```

For Example:

```
{
  "transaction":
  {
    "tid": "123",
    "agentid": "AT101",
    "subagentid": "AT10101",
    "scope": "1",
    "redirecturl": "https://emsapi.ieiletds.com/status.aspx"

    "title": "shri",
    "lastname": "raja",
    "firstname": "ram",
    "middlename": "mohanrai",
    "dateofbirth": "01/01/1900",
    "mobilen": "9999999999",
    "emailid": "ram@gmail.com",
    "pan": "ABCDE1234F",
  }
}
```

7. Encrypt the above payload with random string as described in step 2 using AES encryption/decryption algorithm with following properties
 - e. Cipher mode should be CBC.
 - f. Padding should be PKCS7.
 - g. Keysize should be 256.
 - h. Output string should be base64 format with url safe base64 encoders.
8. Method should be "POST"
9. Set content type as "application/x-www-form-urlencoded"
10. Request body sample shown below

```
<input type="hidden" id="data" name="data"
value = "{
    \"token\": \"TDJCUXFINVprdEYyQkhSVHJ6c1N6amEyazU1SCt4KzBsQ2dZTVVNZTJNZ3
    pKNzd0M0ZzQjFZbk0zbGE3TTdqYzZkaDVSbWhCcmJzU0RJRvYzMEZ3ZGc9PQ\",
    \"payload\": \"L0NMUzFqVIF2a0VmeFFWQ2VLbitXbXNCUFk5UINyVmE5MCs3Wmpxbkt
    VNVhvdMvRW8ra1pldks5djVqaCtWVjc3ai9qTTArYmFEN3MvWEJKNTZpRm9P
    Wm5xemhvVWhxR2Z5RHBIZFNxZGQ2eU1kWk1ZcHBYNXloRWxIL1lRkdvOS9Q
    ROhEbnpPbHlxTk5JZFJlZk1sTWQ1clZtTFR0VDQ4bTAra20rMUVmQTlBVXhdZWd
    CR0JZYlRoRW1YUUI1\",
    \"authkey\": \"123\"
}\"
```

11. Submit your request to below url
["https://www.idmsonline.in/etds/Auth/Authorizernew.aspx"](https://www.idmsonline.in/etds/Auth/Authorizernew.aspx)

C. Access ETDS Services

12. Now you will be redirected to New PAN Request page. Once you submit the request to NSDL the status of the request will be sent by Integrated to agents redirection URL as specified in the request.
13. The response will be encrypted using the public key of the certificate provided by the agent and the agent should use the private key of the certificate to decrypt the response received from Integrated.

Sample Error Response:

1. If invalid request is passed, the server responds like below

```
{
  "StatusCode": "405",
  "Description": "<Error description depending upon the error thrown by server>"
}
```

-----XXXXXXXXXXXXXXXXXXXX-----

After getting Response from NSDL follow the instruction :

We will send the NSDL response to your CALLBACK URL under the key "resdata". The JSON data structure is as follows:

```
{
  "AgentTid": "<Your unique reference number as received from your
  request>",
  "payload": "<Contains an encrypted NSDL response>",
  "authkey": "<Your agent ID>"
}
```

Sample response:

```
{
  "AgentTid": "1",
  "payload": "",
  "authkey": "123"
}
```

Decrypt the payload using the same AES encryption method that was used for encrypting the request