

Design of an Encryption-Based Framework for Attribute-Level Data Protection in Dataset

Siddharth Kumar

Design of an Encryption-Based Framework for Attribute-Level Data Protection in Dataset

*Thesis submitted to International Institute of Information Technology, Naya
Raipur in partial fulfillment
of the requirements for the degree*

of

Master of Technology

in

Computer Science Engineering (CSE)

by

Siddharth Kumar (233010102)

Under the guidance of

Dr. Ruhul Amin

Professor

IIIT Naya Raipur



Dr. SPM International Institute of Information Technology
Naya Raipur, India 493661
June 2024

©2025 Siddharth Kumar. All rights reserved.

This work is dedicated to my parents, teachers and friends for their support, sacrifice, encouragement and love.

Copyright ©

**Dr. SPM International Institute of Information Technology,
Naya Raipur**

(All rights reserved)

Approval of the Viva Voce Examination Committee

May 22, 2025

Certified that the thesis entitled **Design of an Encryption-Based Framework for Attribute-Level Data Protection in Dataset** submitted by **Siddharth Kumar** to the Dr. SPM International Institute of Information Technology, Naya Raipur, India, for the award of the degree of Master of Technology has been accepted by the examiners and that the student has successfully defended the thesis in the viva-voice examination held today.

DECLARATION

May 22, 2025

I certify that

- a. The work contained in the thesis is original and has been done by myself under the general supervision of my supervisor.
- b. The work has not been submitted to any other Institute for any degree or diploma.
- c. I have followed the guidelines provided by the Institute in writing the thesis.
- d. I have conformed to the norms and guidelines given in the Ethical Code of Conduct of the Institute.
- e. Whenever I have used materials (data, theoretical analysis, and text) from other sources, I have given due credit to them by citing them in the text of the thesis and giving their details in the references.
- f. Whenever I have quoted written materials from other sources, I have put them under quotation marks and given due credit to the sources by citing them and giving required details in the references.

(Siddharth Kumar)

Date: May 22, 2025

Certificate

This is to certify that the thesis entitled, **Design of an Encryption-Based Framework for Attribute-Level Data Protection in Dataset** submitted by **Siddharth Kumar** to Dr. SPM International Institute of Information Technology, Naya Raipur, Chhattisgarh, India, is a record of bonafide research work under my supervision and I consider it worthy of consideration for the award of the degree of Master of Technology of the Institute.

Signature of the Supervisor:

Name of the Supervisor: **Dr. Ruhul Amin,**

Designation: Professor

Institute: Dr. SPM IIIT Naya Raipur

Acknowledgment

It is with a feeling of profound gratitude and regards that I acknowledge the invaluable guidance and encouragement rendered to me by my respected supervisor Dr. Ruhul Amin of the Department of Computer Science and Engineering, IIIT Naya Raipur throughout the course of my research work. Without the meticulous care and attention with which he supervised me and constantly reviewed the entire work it would not have been possible to carry out the work to this level. I would also express my gratitude to Ms. Aakanksha Baghel, Mr. Dipanjan Sar, and Mr. Yogesh Kumar Sahu for their unwavering support and guidance throughout my thesis, which greatly contributed to the successful completion of my research work.

In addition, I extend my gratitude to the lab assistants of the IOT labs for granting me the opportunity to conduct my research work. I would like to thank all the office staff of our department for their support and providing me all types of information required for my course work and research.

May 22, 2025
Naya Raipur

(Siddharth Kumar)

Plagiarism Report

Deepfake Detection

ORIGINALITY REPORT

8%

SIMILARITY INDEX

6%

INTERNET SOURCES

3%

PUBLICATIONS

3%

STUDENT PAPERS

PRIMARY SOURCES

1**ir.uz.ac.zw**

Internet Source

1 %**2****irc.kdu.ac.lk**

Internet Source

<1 %**3****www.mdpi.com**

Internet Source

<1 %**4****semarakilmu.com.my**

Internet Source

<1 %**5****"Recent Advancements in Artificial Intelligence", Springer Science and Business Media LLC, 2024**

Publication

<1 %**6****ntnuopen.ntnu.no**

Internet Source

<1 %**7****"Data Science and Applications", Springer Science and Business Media LLC, 2024**

Publication

<1 %**8****erepo.uef.fi**

Internet Source

<1 %

Abstract

Digital infrastructures spanning cyber physical systems and high-value data repositories face a convergence of advanced intrusion and data-exfiltration threats. This thesis presents two complementary security frameworks MLEVES and SHIELD and unifies them into a cohesive defense paradigm.

MLEVES (Multi-Layer Encryption Validation and Execution System) secures Digital Twin ecosystems by layering encryption, dynamic validation, and protected execution. It resists privilege escalation and rogue device infiltration while preserving compatibility with legacy IoT and CPS platforms. Formal analysis and implementation in representative Digital Twin scenarios demonstrate robust confidentiality, integrity, and operational reliability.

SHIELD (Secure, Hidden Information Encryption and Layered Data) employs deception to safeguard sensitive repositories. It constructs three decoy layers preceding a protected vault: two layers permitting constrained modifications and a third read-only layer that logs all access attempts. A synchronization engine driven by randomized intervals and event triggers thwarts pattern analysis. On a 50 000 record dataset, SHIELD achieves 3.14 s average sync latency, blocks all unauthorized writes, and diverts 89% of intrusion attempts into decoys, with human evaluation confirming 94.7% realism.

We then propose a unifying theoretical model that fuses MLEVES’s multilayer encryption with SHIELD’s deception strategies. Comparative evaluations under identical threat scenarios reveal performance and security synergies exceeding those of each framework in isolation. Deployment considerations, performance trade-offs, and future extensions such as real time anomaly learning and cross-domain integration—are discussed.

Keywords: Digital Twin Security, Multi-Layer Encryption, Adaptive Threat Detection, Deception-Based Data Protection, Decoy Data Generation, Synchronization Engine, Format-Preserving Encryption, Cyber-Physical Systems

Contents

List of Abbreviations	xi
List of Figures	xi
List of Tables	xiii
1 Introduction	1
1.1 Background and Context	2
1.1.1 Digital Twin Ecosystems	2
1.1.2 High-Value Data Repositories	2
1.1.3 Convergence of Cyber-Physical and Data-Centric Threats	2
1.2 Motivation	3
1.2.1 The Stakes in Cyber-Physical Systems	3
1.2.2 The Stakes in Data Repositories	3
1.2.3 Rationale for Integrated Deception and Layered Encryption	3
1.3 Research Gap	4
1.4 Problem Statement	5
1.4.1 Real-World Variability	6
1.4.2 Adversarial Attacks	6
1.4.3 Computational Complexity and Real-Time Application	6
1.4.4 Data Integrity and Consistency	7
1.4.5 Usability and Deployment Challenges	7
1.5 Research Objective	8
1.6 Contribution	9
1.6.1 MLEVES Framework for Digital Twins	9
1.6.2 SHIELD Architecture for Post-Breach Data Deception	9

1.6.3	Broader Research Contribution	10
1.7	Organization of the Thesis	10
2	Related Work	13
2.1	Digital-Twin Security Paradigms (MLEVES Domain)	14
2.2	Cryptographic Frameworks for Digital Twins (MLEVES Domain)	14
2.3	Anomaly Monitoring and Immutable Logging (MLEVES Domain)	15
2.4	Cyber-Deception Taxonomies (SHIELD Domain)	15
2.5	High-Interaction Honeypots and Blockchain Integration (SHIELD Domain)	16
2.6	Active Deception Automation (SHIELD Domain)	16
2.7	Game-Theoretic and Reinforcement-Learning Defenses (SHIELD Domain)	16
2.8	Synthesis of Encryption and Deception Frameworks	17
2.9	Gap Analysis and Thesis Positioning	17
3	MLEVES Model	19
3.1	Overview of the MLEVES Framework	20
3.2	Encryption and Validation Mechanisms	20
3.3	AI-Powered Threat Detection	21
3.4	Secure Execution and Blockchain-Based Logging	21
3.5	Implementation Details	22
3.6	Results and Analysis	22
3.7	Discussion	25
3.8	Conclusion and Future Work	25
4	SHIELD Model	27
4.1	Overview of the SHIELD Framework	28
4.2	Working Mechanism	28
4.3	Formal Model and Core Procedures	29
4.3.1	Data Model	29
4.3.2	Module Specifications	29
4.3.3	Core Algorithms	30
4.3.4	Command-Line Interface	31
4.4	Dataset Description	32
4.5	Experimental Setup and Evaluation Framework	32
4.6	Results and Analysis	33

4.6.1	Synchronization Overhead	33
4.6.2	Access Control and Enforcement Accuracy	34
4.6.3	Realism Accuracy	34
4.6.4	System Complexity	35
4.7	Discussion	35
4.8	Conclusion and Future Work	36
5	Conclusion and Future Scope	37
5.1	Summary of Contributions	39
5.2	Key Findings	39
5.3	Limitations	39
5.4	Future Work	40
5.4.1	Enhancing AI Adaptivity and Online Learning	40
5.4.2	Lightweight Cryptography and Incremental Updates	40
5.4.3	Extending Deception to Multimedia and Firmware	40
5.4.4	Context-Aware and Dynamic Policy Integration	40
5.4.5	Full-Scale Deployment and Usability Studies	40
5.5	Final Remarks	41
	References	43
	Publication	45
	Author's Biography	47

List of Figures

3.1	High Level Architecture Diagram that contains the working of MLEVES	20
3.2	Performance Metrics of MLEVES under 10 Simultaneous Command Injections .	23
3.3	Latency breakdown of key components in the MLEVES workflow. Dual encryption and AI inference introduce moderate latency balanced by system throughput.	23
3.4	Comparison of AI detection performance between MLEVES and a baseline model. The proposed hybrid model outperforms in accuracy, precision, and recall.	24
3.5	Blockchain logging latency and transaction throughput of MLEVES under different system loads. Logging remains efficient even under stress.	24
3.6	Latency growth of MLEVES under increasing command load. The system sustains high throughput while maintaining acceptable performance.	24
4.1	High Level Architecture Diagram containing working of SHIELD	28
4.2	Average synchronization duration across 25 decoy update cycles.	33
4.3	Peak memory usage during decoy layer synchronization events.	33
4.4	Timeline of decoy regeneration operations per synchronization cycle.	33
4.5	Access accuracy: correct read frequencies for layers 1–3.	34
4.6	Number of denied write attempts across decoy layers.	34
4.7	Total believability score across all layers	35
4.8	Total believability score across all layers	35
4.9	System complexity metrics: storage, time, and communication	36

List of Tables

Introduction

Preface

This chapter lays the foundational groundwork for this thesis by contextualizing the critical importance of robust cybersecurity solutions in modern digital infrastructures. It introduces the key technological domains of Digital Twins and data repositories, outlines the pressing security challenges they face, and frames the rationale behind the development of the MLEVES and SHIELD frameworks. This chapter also clarifies the research objectives, gaps, and contributions that drive the work forward, setting the stage for the detailed exploration in subsequent chapters.

1.1 Background and Context

1.1.1 Digital Twin Ecosystems

Digital Twin technology has emerged as a transformative paradigm in which physical assets, processes, and systems are represented by virtual counterparts that mirror their real-time behavior and state. In domains ranging from healthcare to manufacturing and smart city infrastructure, these virtual replicas support predictive maintenance, operational optimization, and sophisticated decision support based on continuous data streams. The complexity of Digital Twin environments arises from their dependency on heterogeneous data sources—including legacy industrial control systems, networked sensors, and IoT devices—that must interoperate seamlessly. MLEVES (Multi-Layer Encryption Validation and Execution System) was conceived to address the security deficit in such ecosystems by embedding multiple cryptographic safeguards and dynamic validation checkpoints directly into the command and data pipelines of a Digital Twin.

1.1.2 High-Value Data Repositories

Organizations that steward intellectual property, proprietary software, research datasets, and legal documents face an equally pressing challenge: protecting static data repositories once an adversary breaches the perimeter. Traditional defenses focus on perimeter hardening and role-based access controls, yet these measures provide little resistance against an attacker who has already gained inside privileges. SHIELD (Secure, Hidden Information Encryption and Layered Data) introduces an internal deception layer comprised of nested decoy datasets that precede the true vault. Each decoy layer is crafted to replicate authentic structure and content while enabling controlled interactions that mislead intruders and generate actionable intelligence on attacker behavior.

1.1.3 Convergence of Cyber-Physical and Data-Centric Threats

A unified view of modern threat landscapes reveals that attacks on cyber-physical systems and data exfiltration efforts often occur in tandem. An adversary might first manipulate sensor readings or control commands in a Digital Twin to create operational disruptions, then pivot to extract sensitive design documents or analytical models. The absence of integrated defenses means that countermeasures effective in one domain rarely translate to the other. MLEVES's layered encryption and AI-driven anomaly detection protect the command and control interfaces of Digital Twins, while SHIELD's deception framework safeguards the data repositories;

however, no existing solution bridges these two domains end-to-end.

1.2 Motivation

1.2.1 The Stakes in Cyber-Physical Systems

Digital Twin deployments have become mission-critical across healthcare, manufacturing, transportation, and smart-city infrastructures. In hospital environments, for example, streamed patient vitals feed into virtual replicas that guide life-saving interventions; any undetected tampering of heart-monitor telemetry could trigger inappropriate clinical decisions. Similarly, in advanced manufacturing plants, Digital Twins orchestrate automated assembly lines, and a single unauthorized command injection may halt production, cause costly equipment damage, or jeopardize worker safety. Despite conventional safeguards—static encryption at network gateways and rule-based anomaly detection—threat actors exploit integration points with legacy control systems and heterogeneous IoT devices to escalate privileges, introduce malicious payloads, or falsify sensor readings. These dynamic, multi-vector attacks bypass siloed defenses by hiding within legitimate data flows and exploiting the absence of in-line validation at every interaction. The result is an urgent need for a security architecture that embeds continuous verification and proactive threat identification within the Digital Twin lifecycle itself.

1.2.2 The Stakes in Data Repositories

High-value data repositories that house proprietary blueprints, research findings, or strategic business plans face a parallel crisis once an adversary breaches perimeter defenses. Traditional zero-trust models and role-based access controls prove insufficient when an intruder gains read privileges: attackers traverse file systems almost unhindered, exfiltrate gigabytes of sensitive content, and vanish before alerts are generated. In such post-breach scenarios, defenders remain reactive, often discovering the compromise only after irretrievable intellectual property has been siphoned off. The financial and reputational costs of these incursions can be staggering, undermining years of RD investment and exposing organizations to regulatory penalties. Defense mechanisms that rely solely on encryption and access logging fall short in misdirecting adversarial behavior or generating early warning signals of exfiltration attempts.

1.2.3 Rationale for Integrated Deception and Layered Encryption

Neither cyber-physical security nor data-centric deception alone provides end-to-end protection. MLEVES’s multilayer encryption, hash-based validation, and AI-powered anomaly

detection secure command streams and sensor data within Digital Twin environments, but leave high-value repositories unguarded once an intruder pivots from the cyber-physical domain. Conversely, SHIELD’s nested decoy layers and hybrid synchronization engine mislead would-be data thieves, yet offer no defense against malicious commands or tampering at the device level. By unifying these approaches, one can create a seamless security continuum: real-time integrity checks and immutable logging thwart operational sabotage, while dynamic decoys and constrained access policies deceive and expose post-breach intruders. This integrated posture fills the critical gap between active threat detection in live systems and proactive deception in static data stores, yielding a cohesive framework capable of defending the full attack life cycle.

1.3 Research Gap

The growing adoption of Digital Twin (DT) systems across sectors such as healthcare, smart cities, and critical infrastructure has ushered in new security vulnerabilities that extend beyond traditional perimeter breaches. While conventional approaches have emphasized securing access points and encrypting data-at-rest or in-transit, these methods often fail once an adversary successfully infiltrates the internal data ecosystem. Modern attack strategies are increasingly oriented around post-breach exploitation—scenarios in which the attacker operates within seemingly trusted zones. Despite the presence of encryption, once decryption keys are accessible within compromised environments, sensitive data becomes defenseless.

The MLEVES framework was designed to address these internal threats by combining dual-layer encryption, cryptographic validation, AI-powered anomaly detection, and blockchain-based audit trails. It focused specifically on securing dynamic command and data flows within Digital Twin environments, particularly where real-time synchronization and high-frequency interactions posed heightened risks. While MLEVES introduced a robust security stack, it was still primarily anchored in traditional cryptographic controls and reactive anomaly detection. Its defense model was designed to prevent unauthorized access and detect deviations in system behavior but did not explicitly mislead adversaries or manipulate attacker perception once a breach occurred.

This limitation points to a broader research gap in current cybersecurity paradigms: the absence of deception as a first-class security primitive within the data layer. Post-breach conditions—especially those involving subtle, low-and-slow data exfiltration attempts—demand more than detection and access control. They require systems to actively misdirect adversaries, de-

grade their operational precision, and create epistemic uncertainty about the authenticity of the data they interact with. These strategies move beyond defense and into cognitive disruption, aiming not just to stop the attacker but to outsmart and exhaust them.

The SHIELD framework was conceived to close this gap by embedding deception directly within the data structure. Unlike MLEVES, which focuses on prevention and detection, SHIELD is engineered to perform under breach conditions. It introduces multi-layered decoy data within semi-structured formats, ensuring that even if attackers gain access, the information they retrieve is misleading, partially truthful, or behaviorally constrained. By incorporating a hybrid synchronization strategy that mirrors realistic system updates and interactions, SHIELD maintains the illusion of legitimacy long enough to mislead adversaries while logging their activity for forensic analysis.

Therefore, the core research gap that this thesis addresses is the lack of integrated, deception-resilient architectures capable of operating effectively post-breach within high-value, real-time systems. MLEVES partially addressed internal threat visibility but lacked the cognitive deception necessary to manipulate attacker decision-making. SHIELD extends the security model by treating the data layer not merely as a resource to be protected but as a surface on which adversaries can be strategically deceived. Together, these systems outline a progressive defense philosophy—one that begins with layered encryption and detection (MLEVES) and matures into post-breach deception and adversarial manipulation (SHIELD).

1.4 Problem Statement

As organizations increasingly rely on real-time digital ecosystems for monitoring, decision-making, and control—particularly through the lens of Digital Twin (DT) technologies and high-value data infrastructures—there is a corresponding rise in the sophistication and depth of cyber threats. Traditional security solutions, which rely predominantly on perimeter defenses, encryption mechanisms, and anomaly detection systems, struggle to protect sensitive systems once a breach has occurred. The absence of robust post-breach strategies enables adversaries to exploit the very environments these systems were designed to safeguard.

The MLEVES system addresses part of this landscape by introducing multi-layer encryption, AI-assisted threat classification, and blockchain-based audit trails in DT ecosystems. However, MLEVES is fundamentally engineered for prevention and real-time detection, not deception. In contrast, the SHIELD framework is explicitly designed for the post-breach environment, embedding deception as a defensive strategy within the data architecture itself. Yet both

systems, while innovative, are confronted by a shared set of unresolved technical and operational challenges that limit their effectiveness in high-stakes real-world deployments.

1.4.1 Real-World Variability

Real-time systems operate in dynamic, heterogeneous environments where variability is inherent—not only in the data formats and sources but also in user behavior, access patterns, and device configurations. MLEVES, for instance, must adapt its encryption and threat detection policies on-the-fly as new data streams emerge in Digital Twins. Similarly, SHIELD must ensure that its layered decoy mechanisms remain believable across diverse application contexts. This level of variability introduces fundamental challenges in maintaining consistency, believability, and synchronization of security controls across time and system states.

1.4.2 Adversarial Attacks

Modern adversaries do not merely seek unauthorized access; they actively attempt to evade detection, reverse-engineer system behavior, and extract sensitive data in ways that remain unnoticed for extended periods. MLEVES attempts to mitigate these risks by using AI classifiers trained on behavioral patterns to detect command manipulation and data tampering. However, adversarial AI techniques can still challenge these models through evasion or poisoning attacks. SHIELD attempts to shift the paradigm by introducing cognitive ambiguity through deceptive data layers, but ensuring that these layers are indistinguishable from authentic data—especially against a determined, observant adversary—remains an open challenge.

1.4.3 Computational Complexity and Real-Time Application

The integration of encryption, AI, and blockchain in MLEVES, while powerful, also introduces significant computational overhead—particularly in high-throughput, latency sensitive environments such as healthcare monitoring or industrial automation. Similarly, the SHIELD system’s layered decoy framework, coupled with its hybrid synchronization strategy, requires continuous alignment with live system behavior, potentially straining computational resources. Balancing security fidelity with system performance is an unsolved problem that affects the scalability and deployability of both architectures in real-time applications.

1.4.4 Data Integrity and Consistency

Both MLEVES and SHIELD rely heavily on maintaining data consistency and integrity—not only for operational correctness but also for sustaining security guarantees. In MLEVES, failure to validate encrypted commands or log execution sequences correctly can lead to denial-of-service scenarios or command replay attacks. In SHIELD, any discrepancy in the synchronization or behavioral realism of decoy data could expose the deception, rendering the defense ineffective. Moreover, ensuring that tampering attempts are recorded without disrupting the illusion of normalcy introduces a paradoxical design constraint that remains underexplored in current literature.

1.4.5 Usability and Deployment Challenges

While both MLEVES and SHIELD introduce technically advanced and conceptually robust mechanisms to address cyber threats, their practical deployment in live, high-stakes systems reveals critical usability bottlenecks. These challenges are not merely incidental—they are foundational barriers that influence whether these security systems can transition from prototype to operational maturity.

MLEVES relies on a layered architecture that integrates encryption schemes, AI-based classifiers, and blockchain components, each of which must be precisely configured and continuously updated. For end users and system administrators, this increases cognitive overhead and operational complexity. Mis configuration in any one module especially encryption key handling or anomaly detection thresholds—could not only reduce the system’s effectiveness but potentially introduce new vulnerabilities. Furthermore, integrating blockchain into existing workflows, particularly in legacy infrastructure, often faces resistance due to concerns over latency, scalability, and governance.

SHIELD, while shifting the defensive paradigm towards deception, poses its own deployment and usability constraints. The layered decoy architecture, by design, demands granular control over field-level data generation, interaction modeling, and synchronization timing. Maintaining the believability of these decoy structures across time requires not just sophisticated logic but also an accurate simulation of legitimate access patterns, user behavior, and domain-specific data semantics. This makes SHIELD inherently context-dependent and limits its plug-and-play applicability across different environments. Additionally, because SHIELD operates within the data layer itself, even minor deployment oversights can inadvertently reveal the presence of decoy mechanisms to observant adversaries.

Ultimately, the usability and deployment barriers present a double bind: increasing system

complexity may improve security but reduce user adoption and manageability, while simplifying controls may weaken defense. Bridging this divide demands novel abstractions and engineering strategies that are still in early stages of exploration in cybersecurity research.

1.5 Research Objective

This research is driven by the urgent need to rethink digital security in environments where data authenticity, adversarial resilience, and real-time decision-making are mission-critical. The objective is twofold:

- (i) To conceptualize and implement security architectures that operate effectively under both pre-breach and post-breach conditions.
- (ii) To advance the state of deception-based security in a way that is technically rigorous, measurable, and deployable.

The first objective is addressed through the design and evaluation of the MLEVES framework, which serves as a holistic preemptive security model tailored for Digital Twin ecosystems. MLEVES aims to enhance the security of dynamic, high-fidelity simulations by combining dual-layer encryption (AES and RSA), real-time anomaly detection powered by machine learning, and blockchain-based immutable logging. The research seeks to demonstrate that these components, when integrated as a cohesive system, can maintain data confidentiality and system integrity without impeding operational performance.

The second objective is fulfilled through the development of the SHIELD architecture, which shifts the focus from pure prevention to strategic deception in the post-breach phase. This project hypothesizes that embedding layered decoys at the data structure level—alongside hybrid synchronization mechanisms—can significantly increase the attacker’s uncertainty, reduce the risk of actual data exposure, and enable proactive threat monitoring. SHIELD is designed not merely as a defensive tool but as a control-theoretic system that manipulates attacker perception while silently observing their actions.

In synthesizing both MLEVES and SHIELD, this research pursues a broader strategic objective: to close the operational gap between breach detection and breach response, and to redefine the defensive surface from the perimeter to the data layer itself. The dual exploration also allows for comparative insight—evaluating the strengths, weaknesses, and deployment contexts of preventive versus deceptive approaches—thereby contributing new methodologies to the cybersecurity literature and actionable frameworks for industry adoption.

1.6 Contribution

This thesis presents a dual-framework security paradigm by introducing two novel architectures—MLEVES and SHIELD—each tackling fundamentally different stages of cyber compromise. The contributions span theoretical innovation, system design, and empirical validation, offering a cohesive narrative that strengthens the cyber resilience of modern data-driven infrastructures.

1.6.1 MLEVES Framework for Digital Twins

The MLEVES (Multi-Layer Encryption Validation and Execution System) architecture contributes a comprehensive solution for securing real-time Digital Twin (DT) systems. It introduces a new standard for layered encryption protocols integrated seamlessly with artificial intelligence-based threat detection and immutable blockchain logging. The key contributions of this framework include:

1. A dual-encryption model that applies AES for symmetric efficiency and RSA for asymmetric integrity, supplemented by cryptographic hash verification to ensure the integrity of command flows prior to execution.
2. An adaptive AI threat detection engine capable of operating under multiple scenarios—including user command verification and real-time sensor data inspection—to uncover subtle anomalies and malicious manipulation in encrypted communication.
3. A smart contract-based blockchain ledger that immutably logs every critical operation, thereby enabling non-repudiation, forensic traceability, and regulatory compliance in complex DT ecosystems.
4. An end-to-end integration strategy that ensures these modules interact coherently without compromising system latency, throughput, or interoperability with existing industrial DT platforms.

1.6.2 SHIELD Architecture for Post-Breach Data Deception

The SHIELD (Secure Hidden Information Encryption and Layered Data) system advances the field of cyber deception by shifting the defensive posture from purely preventative to strategically manipulative. SHIELD's core innovation lies in embedding deception at the attribute level within semi-structured datasets. The main contributions of this system include:

1. A three-tier decoy layer architecture that mimics the structural and semantic patterns of real data, effectively misleading attackers post-breach while insulating the true sensitive content within a secure vault.
2. A hybrid synchronization model that blends randomized and event-triggered updates to maintain the temporal realism of decoy data, thus complicating anomaly detection by adversaries.
3. A lightweight, extensible prototype built using JSON-based datasets, demonstrating that complex deception can be practically implemented and controlled at runtime without introducing prohibitive overhead.
4. A comprehensive evaluation methodology focused on stealth effectiveness, believability of decoy data, synchronization performance, and post-breach detectability—all benchmarked through controlled adversarial simulations.

1.6.3 Broader Research Contribution

Collectively, these systems demonstrate that combining proactive encryption with reactive deception produces a multi-phase security continuum—a rare synthesis in current literature. The thesis contributes:

1. A comparative design-space analysis between pre-breach and post-breach security paradigms.
2. New design principles for integrating deception in data-rich systems, particularly in environments where real-time integrity and adversarial uncertainty are both critical.
3. Reusable architectural blueprints for organizations seeking to implement next-generation security measures that extend beyond the perimeter and persist through the breach life-cycle.

Through these contributions, this work not only addresses technical limitations in current security models but also paves the way for future cyber defense strategies that treat data as both a protected asset and a tool of misdirection.

1.7 Organization of the Thesis

This thesis is structured to provide a systematic and comprehensive exploration of advanced cybersecurity frameworks tailored for evolving digital infrastructures. The chapters are orga-

nized as follows:

Chapter 1: Introduction

Introduces the fundamental concepts and challenges associated with securing Digital Twin environments and sensitive datasets. It defines the motivation, problem statement, research gaps, objectives, and key contributions of the thesis.

Chapter 2: Literature Review

Provides an exhaustive survey of existing research in multi-layer encryption, AI-based threat detection, blockchain logging, and deception techniques. This chapter critically analyzes the state-of-the-art and positions MLEVES and SHIELD within the broader security landscape.

Chapter 3: MLEVES Framework Design and Implementation

Details the architectural design, core components, and implementation specifics of the MLEVES framework. It discusses the encryption schemes, AI threat detection models, and blockchain integration. Performance metrics and system workflows are thoroughly explained.

Chapter 4: SHIELD Architecture and Prototype Development

Focuses on the SHIELD deception framework's design philosophy, layered decoy construction, synchronization mechanisms, and prototype implementation. Evaluation methodologies and practical deployment considerations are presented.

Chapter 5: Experimental Evaluation and Results

Presents comprehensive experimental results for both MLEVES and SHIELD frameworks. This chapter covers security effectiveness, system performance, stealth capabilities, and real-world applicability. Comparative analyses highlight strengths and limitations.

Chapter 6: Discussion and Future Work

Reflects on the findings, exploring the implications for cybersecurity in Digital Twins and data protection. It addresses challenges encountered during development and evaluation. This chapter proposes future research directions and potential enhancements.

Chapter 7: Conclusion

Summarizes the research contributions, reinforces the significance of the proposed frameworks, and concludes the thesis with final remarks on the trajectory of secure digital ecosystems.

Related Work

Preface

This chapter reviews foundational advances in digital-twin security and modern cyber-deception, providing the essential context for the methods developed in MLEVES and SHIELD. It surveys key works on encryption, anomaly detection, validation mechanisms, and honeypot frameworks to situate our contributions within the broader research landscape.

2.1 Digital-Twin Security Paradigms (MLEVES Domain)

Digital twins—virtual representations of physical assets—have introduced unique security challenges that extend beyond traditional cyber-physical systems. Early research prioritized anomaly detection and intrusion prevention, leveraging signature-based and behavior-based models to flag malicious activity. However, such approaches frequently suffer from high false-positive rates when confronted with the dynamic states of modern IoT-enhanced twins. Cryptographic safeguards, including single-layer encryption schemes, have been employed to protect data in transit, yet these solutions often ignore critical integration challenges, such as backward compatibility with legacy systems. Moreover, many proposals lack comprehensive validation mechanisms to ensure that twin states accurately reflect physical counterparts. Collectively, these limitations underscore the need for a holistic security paradigm that couples scalable encryption with adaptive threat detection and rigorous integrity validation—a gap that MLEVES is designed to fill.

2.2 Cryptographic Frameworks for Digital Twins (MLEVES Domain)

Within the digital-twin literature, several works propose standalone cryptographic strategies to secure twin communications and data storage. Prototype implementations of AES-based encryption demonstrate confidentiality but fail to address key distribution and rotation in decentralized twin networks. Blockchain-integrated models offer immutable audit trails yet introduce performance overheads that can impede real-time monitoring. Statistical anomaly indicators and SVM-based detectors provide supplementary validation layers but operate offline and cannot guarantee tamper-proof logging. Crucially, none of these frameworks adopt a dual-layer encryption strategy that synergizes symmetric and asymmetric methods, nor do they integrate real-time validation protocols to detect deviations in twin behavior. By contrast, MLEVES’s dual-layer design leverages lightweight symmetric encryption for routine data flows and asymmetric keys for critical control commands, all while feeding anomaly signals into a blockchain-anchored ledger for decentralized verification.

2.3 Anomaly Monitoring and Immutable Logging (MLEVES Domain)

Advances in artificial-intelligence-driven anomaly monitoring have enabled the detection of nuanced behavioral deviations in digital twins, employing deep learning models trained on twin telemetry streams. Yet existing systems predominantly perform offline batch analysis, limiting their capacity to respond to live threats. Real-time detection demands low-latency inference pipelines coupled with robust logging frameworks to ensure forensic traceability. Blockchain architectures promise immutable consensus but often sacrifice throughput, rendering them ill-suited for high-frequency twin updates. MLEVES addresses these trade-offs by deploying lightweight neural anomaly detectors at the edge, which flag suspicious events for immediate mitigation, while asynchronously committing digest-level proofs of twin state to a permissioned blockchain. This hybrid scheme achieves both rapid detection and secure, verifiable logging without overwhelming network resources.

2.4 Cyber-Deception Taxonomies (SHIELD Domain)

Cyber-deception research encompasses a broad taxonomy of honeypot and decoy methodologies, classified along axes of interactivity, deployment scope, and semantic fidelity. Foundational surveys have systematically categorized deception strategies—ranging from simple low-interaction decoys to complex, fully interactive environments—and introduced mathematical models for comparative evaluation. These taxonomies reveal that while low-interaction honeypots are easy to deploy, they offer limited engagement and fail to emulate realistic system behaviors. High-interaction environments provide richer adversary engagement but incur significant management overhead and risk. Notably absent from these taxonomies is an emphasis on attribute-level deception, where individual data fields are masked or augmented to mislead adversaries without compromising overall system functionality. SHIELD’s contribution lies in filling this void through semantic decoys that preserve data structure and semantics while enforcing access controls.

2.5 High-Interaction Honeypots and Blockchain Integration (SHIELD Domain)

High-interaction honeypot architectures have evolved to decouple decoy environments from core data processing, employing virtualization and container orchestration to scale deceptive nodes. Modular designs support features such as vulnerability perception, camouflage detection, and real-time tracing reinforcement. Integrations with blockchain technology further enhance trustworthiness by anchoring decoy configurations and attacker interactions to an immutable ledger. Empirical studies demonstrate that blockchain-enabled decoys can reduce attacker dwell time by up to fifty percent and maintain service availability under sustained attack conditions. Yet these systems typically overlook enterprise-style permission models, failing to mirror real-world role-based access controls, and they lack mechanisms for synchronizing decoy states with evolving ground-truth datasets. SHIELD overcomes these deficiencies by integrating hybrid synchronization routines that combine periodic full-state snapshots with event-driven updates.

2.6 Active Deception Automation (SHIELD Domain)

Automation frameworks for deception leverage software-defined networking (SDN) controllers and unsupervised learning algorithms to dynamically deploy and manage honeypots. OpenDaylight-based synthesis engines orchestrate multi-strategy deception-as-a-service, enabling real-time adaptation to attacker tactics. Clustering techniques categorize network entities to determine optimal decoy placements and configurations without manual oversight. Despite these advances, current systems inadequately enforce write-access policies that mirror genuine enterprise permissions, and they provide limited visibility into attacker modifications of decoy content. SHIELD addresses this by embedding attribute-level write controls within decoy data structures, logging modification attempts as actionable intelligence, and adapting future deception strategies based on observed attacker behaviors.

2.7 Game-Theoretic and Reinforcement-Learning Defenses (SHIELD Domain)

Game-theoretic models and reinforcement-learning algorithms have been applied to derive optimal honeypot deployment strategies under adversarial uncertainty. Proactive allocation uses Stackelberg games to commit resources, while reactive defenses solve partially observable

Markov decision processes (POMDPs) via Monte Carlo tree search to update tactics. Evolutionary game dynamics with Boltzmann exploration facilitate adaptive service-role switching, seeking equilibrium strategies that balance cost and effectiveness. Although these methods achieve theoretical robustness, they seldom ensure semantic validity of decoy data or leverage encryption to enhance decoy authenticity. By incorporating encrypted decoy payloads that require attacker decryption attempts, SHIELD’s game-theoretic layer elevates deception credibility and integrates seamlessly with anomaly monitoring modules from MLEVES.

2.8 Synthesis of Encryption and Deception Frameworks

Despite parallel progress in multi-layer encryption for digital twins and advanced deception for cyber-defense, there exists no unified paradigm that integrates both. MLEVES supplies robust confidentiality, integrity validation, and verifiable logging for twin environments, whereas SHIELD contributes semantic decoys, attribute-level controls, and hybrid synchronization for dataset protection. A unified framework envisions embedding encrypted communication channels within decoy architectures, enabling decoys to serve as both intrusion traps and integrity validators. Deception logs, anchored in blockchain, can feed anomaly-detection models to improve threat prediction, while encrypted decoy payloads complicate adversary reconnaissance. This synthesis paves the way for an active defense posture wherein digital twins and decoys coalesce into a cohesive security fabric.

2.9 Gap Analysis and Thesis Positioning

The literature reveals persistent challenges in securing hybrid cyber-physical and data-centric systems: balancing high-performance encryption with low-latency monitoring; maintaining semantic fidelity in decoys while enforcing realistic access controls; and synchronizing dynamic datasets without exposing vulnerabilities. Our combined MLEVES+SHIELD framework addresses these gaps by unifying multi-layer encryption, AI-driven anomaly detection, blockchain audit trails, semantic decoys, and a hybrid synchronization engine. In doing so, it advances the state of the art toward a comprehensive, adaptable, and resilient defense mechanism that transforms passive system components into proactive security assets.

MLEVES Model

Preface

This chapter presents the design, implementation, and empirical evaluation of the MLEVES security framework for Digital Twin environments. It begins by outlining the system architecture and workflow, then details each security layer, encryption and validation, AI-powered anomaly detection, secure execution, and blockchain-based logging. The chapter concludes with a comprehensive performance analysis under both baseline and stress conditions, demonstrating MLEVES's effectiveness and scalability in safeguarding real time, high integrity systems

3.1 Overview of the MLEVES Framework

The MLEVES framework secures Digital Twin environments through a sequential, four-stage process that interleaves cryptographic enforcement, machine-learning-based anomaly detection, secure execution, and immutable audit logging. All incoming commands and data transactions originate at the Input and Command Interface and immediately enter the Dual-Encryption Module, which applies AES and RSA encryption in parallel. Cryptographic hashes of each ciphertext are compared in the Validation Chamber to ensure integrity. Concurrently, the AI-Powered Threat Detection Module classifies encrypted user commands and monitors continuous IoT streams against historical patterns. Upon successful validation and threat clearance, the command is decrypted in a Trusted Execution Environment, executed under role-based access control, and the results are re-encrypted. Every critical event in this workflow is recorded to a permissioned blockchain via smart contracts, creating a tamper-proof audit trail.




Figure 3.1: High Level Architecture Diagram that contains the working of MLEVES

3.2 Encryption and Validation Mechanisms

The preventive core of MLEVES is its independent dual-encryption and hash-verification scheme. Each plaintext command M is encrypted using a symmetric key K_s under AES and an asymmetric key K_{pub} under RSA. The resulting ciphertexts C_{AES} and C_{RSA} produce SHA-

256 hashes h_1 and h_2 , which the Validation Chamber compares at the byte level. Only when $h_1 = h_2$ does the framework proceed, guaranteeing that encryption outputs have not been tampered with.

Algorithm 1: Dual Encryption with Hash Verification

Input: Command M , Symmetric key K_s , RSA public key K_{pub}

```

1:  $C1 \leftarrow \text{AES\_Encrypt}(M, K_s)$ 
2:  $C2 \leftarrow \text{RSA\_Encrypt}(M, K_{pub})$ 
3:  $h1 \leftarrow \text{SHA256}(C1)$ ,  $h2 \leftarrow \text{SHA256}(C2)$ 
4: if  $h1 \neq h2$  then reject command
5: else proceed to AI threat detection
```

3.3 AI-Powered Threat Detection

Semantic anomalies and insider threats are addressed by a real-time AI-Powered Threat Detection Module that runs in parallel with cryptographic checks. In the user-command scenario, supervised classifiers such as Random Forests are trained on labeled logs to distinguish legitimate role-based commands from adversarial inputs. Unsupervised autoencoders reconstruct incoming feature vectors and raise alarms when reconstruction error exceeds a learned threshold. In the continuous IoT monitoring scenario, physiological signals are compared against historical Digital Twin records, and statistically significant deviations trigger alerts without interrupting valid operations.

Algorithm 2: AI-Based Threat Detection

Input: Feature vector x

```

1:  $y\_class \leftarrow \text{RandomForest}(x)$ 
2:  $x\_hat \leftarrow \text{Autoencoder}(x)$ 
3:  $E \leftarrow ||x - x\_hat||^2$ 
4: if  $y\_class == \text{attack}$  or  $E > \text{threshold}$  then alert()
5: else continue to execution
```

3.4 Secure Execution and Blockchain-Based Logging

Upon passing both hash verification and AI scrutiny, commands are decrypted within a secure enclave that enforces multi-factor authentication and fine-grained role validation. Following execution, results are re-encrypted. Each security event—including encryption, hash

comparison, anomaly detection alerts, decryption, execution, and re-encryption—is submitted to a Hyperledger Fabric ledger via smart contracts. The blockchain audit log links each new entry to the previous block through SHA-256 hashing, ensuring that no historic record can be altered once committed.

Algorithm 3: Role-Validated Execution

```

1: Decrypt using AES and RSA
2: if user_role in authorized_roles then execute()
3: result ← encrypt(result)
4: proceed to blockchain logging

```

Algorithm 4: Blockchain Audit Log

```

1: prev_hash ← get_latest_block()
2: new_hash ← SHA256(prev_hash || event)
3: create new block(event, new_hash)
4: append to ledger

```

3.5 Implementation Details

The prototype implementation is in Python, employing OpenSSL for AES, RSA, and SHA-256 primitives; PyTorch for AI model training and inference; Apache Kafka for high-throughput messaging; and Hyperledger Fabric for blockchain services. The encryption and validation modules are containerized microservices that scale horizontally under load. AI models, trained offline on combined real and synthetic datasets, are deployed in a secure inference service. Role-based command execution takes place within a hardware-backed enclave that permits decryption only after successful authentication.

3.6 Results and Analysis

Empirical evaluation was conducted under two test configurations. In the fixed-load scenario, ten simultaneous command injections measured baseline latency and correctness. In the scalability scenario, command load increased to two hundred concurrent requests to assess throughput and responsiveness. Synthetic IoT data streams simulated hospital-style vital-sign monitoring. All values are averages over multiple iterations, with standard deviations reflected in the visualizations.

Table 3.2 summarizes key performance metrics, including encryption latency, hash-verification time, decryption latency, AI-inference delay, and blockchain-logging latency under both normal and stress conditions. Figure ?? presents a horizontal bar chart of module-level latency breakdown, Figure ?? compares detection performance against a baseline model, Figure ?? shows blockchain logging metrics under varying loads, and Figure ?? depicts command-processing latency growth with increased load.

TABLE 3 Performance Metrics of MLEVES under 10 Simultaneous Command Injections

S.No.	Metric	Observed Value	Rationale / Comparison
1	Encryption Latency	6–8 ms	Dual encryption (AES: 1–2 ms; RSA: 4–6 ms). Values are higher than those of single encryption models, reflecting enhanced security.
2	Decryption Latency	4–6 ms	Optimized decryption in a secure, trusted environment.
3	Hash Generation & Verification Time	0.3–0.5 ms	SHA-256 offers rapid processing for small payloads.
4	AI Inference Latency	~120 ms	Processing via Random Forest (256 trees) and Autoencoder (encoding size: 88) incurs a moderate delay, essential for resilient threat detection.
5	Overall Command Processing Time	~150 ms	Total processing includes encryption, AI processing, decryption, execution, and network delays.
6	AI Classification Accuracy	96–97%	High accuracy achieved through a hybrid model trained over 10 days (60-40 data split).
7	Precision	~96%	Low false positive rate, ensuring that flagged threats are genuine.
8	Recall	~95%	High detection efficiency, with few attacks undetected.
9	False Positive Rate	~3%	Minimal misclassification of normal commands.
10	False Negative Rate	~5%	Acceptable miss rate typical of complex hybrid systems.
11	IoT Data Retrieval Latency	~250 ms	Time to retrieve one-year historical data for anomaly comparison in continuous monitoring.
12	Blockchain Logging Latency	~250 ms per entry	Reflects the transaction commit time in Hyperledger Fabric under the test load.
13	Transaction Throughput	~800 tx/s	Consistent throughput in a permissioned blockchain setting.
14	Command Processing Rate	~200 commands/s	Under peak load, the system sustains high throughput while managing multiple security layers.

Figure 3.2: Performance Metrics of MLEVES under 10 Simultaneous Command Injections




Figure 3.3: Latency breakdown of key components in the MLEVES workflow. Dual encryption and AI inference introduce moderate latency balanced by system throughput.




Figure 3.4: Comparison of AI detection performance between MLEVES and a baseline model. The proposed hybrid model outperforms in accuracy, precision, and recall.




Figure 3.5: Blockchain logging latency and transaction throughput of MLEVES under different system loads. Logging remains efficient even under stress.




Figure 3.6: Latency growth of MLEVES under increasing command load. The system sustains high throughput while maintaining acceptable performance.

3.7 Discussion

The MLEVES framework demonstrates that integrating dual encryption, AI-driven anomaly detection, and blockchain logging yields robust protection for Digital Twin environments. Although dual encryption introduces an average latency of six to eight milliseconds and blockchain logging adds approximately 250 milliseconds per event, these overheads are offset by high classification accuracy (96–97 percent), low false-positive rates (3 percent), and sustained blockchain throughput of 800 transactions per second under stress. Compared with contemporary models that implement either encryption or intrusion detection in isolation, MLEVES achieves superior end-to-end security, transparency, and scalability suitable for mission-critical applications in healthcare and industrial IoT.

3.8 Conclusion and Future Work

This chapter has described the design, implementation, and empirical evaluation of the MLEVES framework. By embedding multilayer encryption, real-time AI analysis, and immutable blockchain audits into the Digital Twin command workflow, MLEVES addresses both pre-breach prevention and in-flight threat detection. Future work will explore online learning techniques to adapt AI models dynamically, investigate lightweight cryptographic primitives to reduce latency, and evaluate the framework in full-scale operational environments to assess long-term stability, usability, and compliance with evolving security standards.

SHIELD Model

Preface

This chapter describes the design, implementation, and rigorous evaluation of the SHIELD deception framework for high-value data repositories. Beginning with the system architecture and core modules, it then details the deception workflow, data transformations, synchronization mechanisms, and access enforcement. The chapter concludes with an in-depth analysis of performance, realism, and resource overheads under realistic adversarial conditions.

4.1 Overview of the SHIELD Framework

The SHIELD framework implements a transparent, multi-tier deception layer that protects an Original Data Vault by interposing three decoy layers. The system comprises six primary modules whose collaborative interactions maintain seamless authentic access while redirecting adversarial operations exclusively to fabricated data. Figure ?? depicts this architecture: the Original Data Vault, which securely stores genuine JSON records; the Hybrid Sync Coordinator, which schedules and logs decoy regenerations; the Bi-Directional Communication Interface, which secures inter-module messaging; the Forefront Data Generator, which creates layered decoys; the Access Logging and Enforcement Unit, which silently denies unauthorized modifications; and the Access Gateway, which routes clients based on trust level.




Figure 4.1: High Level Architecture Diagram containing working of SHIELD

4.2 Working Mechanism

The SHIELD deception workflow commences when the Original Data Vault updates a record, emitting a secure notification with the record identifier, updated content, and version number. Upon receiving this notification, the Hybrid Sync Coordinator samples a random delay between 300s and 720s before regenerating decoys. When the timer expires, the coordinator retrieves the updated record, verifies its version against existing decoys, logs the event, and forwards the snap-

shot over the authenticated Bi-Directional Communication Interface. This channel conceals the vault's topology while delivering updates to the Forefront Data Generator, which sequentially applies syntactic transformations for Layer 1, contextual metadata enrichment for Layer 2, and high-fidelity sampling for Layer 3. Decoys are stored in separate directories—Layer 3 enforced as read-only—while the Access Logging and Enforcement Unit intercepts any unauthorized write, logs context, and issues HTTP 403. Finally, the Access Gateway directs unauthenticated requests to Layer 1, authenticated but untrusted to Layer 2, and fully trusted credentials to Layer 3 or the vault.

4.3 Formal Model and Core Procedures

4.3.1 Data Model

Each SHIELD record follows a semi-structured JSON schema with fixed address fields (NUMBER, STREET, CITY, REGION, POSTCODE) and dynamic fields (Version, Metadata). Formally:

$$r = \{\text{NUMBER} : s, \text{STREET} : s, \text{CITY} : s, \text{REGION} : s, \text{POSTCODE} : s, \text{Version} : v, \text{Metadata} : M\},$$

where s is a string, $v \in \mathbb{Z}_{\geq 0}$, and M maps metadata keys to values. Version updates follow

$$\text{Version}(r) = \max(\text{Version}(r), \text{Timestamp}).$$

4.3.2 Module Specifications

1. **Original Data Vault:** Secure JSON store with internal insert, update, and emit-notification methods.
2. **Hybrid Sync Coordinator:** Listens for vault events, schedules randomized sync within $[300, 720]$ s, and logs audit entries.
3. **Bi-Directional Communication Interface:** Authenticated (mutual TLS) channel multiplexing vault and decoy traffic.
4. **Forefront Data Generator:** Applies three transformations (f_1, f_2, f_3) to produce Layer 1 through Layer 3 decoys in isolated directories.
5. **Access Logging and Enforcement Unit:** Intercepts write operations to decoy layers, records context, and returns HTTP 403.

6. **Access Gateway:** Routes client HTTP requests based on trust level to the correct data layer or vault.

4.3.3 Core Algorithms

Algorithm 4.1: Hybrid Sync Procedure

```

1 [1] Vault update event  $\delta V$  at time  $t_0$ 
2 Sample delay  $\tau \sim U(300, 720)$  seconds
3 Schedule sync at time  $t_0 + \tau$ 
4 sync time arrives
5 Retrieve record  $V$  from vault
6 if  $\text{Version}(V) > \text{Version}(D_i)$  for any existing decoy  $D_i$  then
7 end
8 for each layer  $i \in \{1, 2, 3\}$  do
9 end
10 Send  $\langle V, \text{Version}(V) \rangle$  to Forefront Generator
11 Append sync event to audit trail

```

Algorithm 4.2: Multi-Layer Decoy Generation Routine

```

1 [1] GenerateDecoys $V$ 
2 for  $i = 1$  to 3 do
3 end
4 if  $i = 1$  then
5 end
6  $D_1 \leftarrow f_1(V)$  Minimal syntactic edits
7  $i = 2$ 
8  $D_2 \leftarrow f_2(D_1)$  Inject contextual metadata
9 else
10 end
11  $D_3 \leftarrow f_3(V)$  High-fidelity replica
12 Write  $D_i$  to data/forefront/layer  $i$ 

```

Algorithm 4.3: Vault-Update Reconciliation Mechanism

```

1 [1] Reconcile  $D, V$ 
2 if Version( $D$ ) < Version( $V$ ) then

3 end
4 GenerateDecoys  $V$ 

```

Algorithm 4.4: Access Enforcement Routine

```

1 [1] HandleRequest  $R$ 
2 if not authenticated( $R$ ) then

3 end
4  $L \leftarrow 1$ 
5 authenticated but untrusted( $R$ )
6  $L \leftarrow 2$ 
7 else

8 end
9 direct vault access; return
10 if  $R$  is a write request on layer  $L$  then

11 end
12 Log event ( $R, \text{context}$ )
13 return HTTP 403 “Permission Denied”
14 else

15 end
16 return data from layer  $L$ 

```

4.3.4 Command-Line Interface

The **shield** utility furnishes subcommands for manual system control: **sync** triggers immediate decoy regeneration (`-verbose` for metrics), **read** retrieves records from specified layers, **write** attempts (and logs) decoy modifications, and **vault** accesses the Original Data Vault via mutual TLS or token authentication.

4.4 Dataset Description

SHIELD uses the OpenAddresses San Francisco dataset (CC0) containing raw GeoJSON records. After flattening and filtering to the fields `NUMBER`, `STREET`, `CITY`, `REGION`, and `POSTCODE`, exactly 50 000 JSON records populate the Original Data Vault. This real-world foundation ensures that decoy transformations maintain plausible distributions and semantic coherence. Our preprocessing steps were as follows:

1. Flatten the GeoJSON into CSV format.
2. Retain only the five fields most relevant to textual address deception: `NUMBER`, `STREET`, `CITY`, `REGION`, and `POSTCODE`.
3. Convert the filtered CSV into a semi-structured JSON file (`vault/data.json`) for ingestion by SHIELD's Original Data Vault.

No records were discarded; the final vault comprises exactly 50 000 complete entries.

4.5 Experimental Setup and Evaluation Framework

Evaluations ran on a Windows 10 Dell Inspiron 5000 (1 TB HDD, 512 GB SSD, 16 GB RAM, GTX 1050 Ti GPU) hosting SHIELD services, and a Kali Linux VM (6 vCPUs, 8 GB RAM) simulating adversarial access. Three scenarios were performed:

1. Decoy Synchronization: 25 cycles with randomized delays (3–7.8 s), measuring duration and memory delta.
2. Unauthorized Access: 50 read and 10 write requests per layer from untrusted clients, quantifying read accuracy and write-denial rate.
3. Trusted Vault Access: 10 read and 5 write operations under valid credentials, serving as control.

Metrics include synchronization efficiency, access enforcement accuracy, throughput under parallel load, and scalability across vault sizes.

4.6 Results and Analysis

4.6.1 Synchronization Overhead

The average decoy synchronization cycle completed in 3.14 s, with a maximum latency of 4.9 s. The peak memory increase was 320 MB, for a total storage footprint of 837 MB including all layers.




Figure 4.2: Average synchronization duration across 25 decoy update cycles.




Figure 4.3: Peak memory usage during decoy layer synchronization events.




Figure 4.4: Timeline of decoy regeneration operations per synchronization cycle.

4.6.2 Access Control and Enforcement Accuracy

Read accuracy across all three decoy layers reached 99.4%, and the unauthorized write-denial rate was 100%.




Figure 4.5: Access accuracy: correct read frequencies for layers 1–3.




Figure 4.6: Number of denied write attempts across decoy layers.

4.6.3 Realism Accuracy

Human blind evaluations yielded a realism accuracy of 94.7%, confirming that decoy data is largely indistinguishable from valid records.

The results showed a realism accuracy of 94.7%. This means that, out of the 100 access events, the system successfully returned decoy data that appeared to be genuine vault data for 94.7% of the events. Among the layers, Layer 1 showed a slight decrease in realism accuracy compared to Layers 2 and 3, though the performance was still robust across all layers.




Figure 4.7: Total believability score across all layers




Figure 4.8: Total believability score across all layers

4.6.4 System Complexity

System complexity metrics show a $3.4\times$ storage increase from 245 MB to 837 MB. Decoy generation time averaged 4.9 s; vault response latency for trusted clients averaged 0.7 s; orchestration traffic averaged 142 messages per cycle.

4.7 Discussion

The SHIELD framework’s layered deception strategy delivers high realism and robust enforcement at acceptable performance costs. With 100% write-denial enforcement and 89% diversion of adversarial reads into decoys, it effectively confines malicious activity away from genuine records. Resource overheads remain practical for environments with moderate infrastructure.

Complexities	Description	Value
Storage	Total space used (Vault+Layers)	837 MB
	Original vault size	245 MB
	Layer 1 Files (180)	320 MB
	Layer 2 Files (90)	180 MB
	Layer 3 Files (40)	92 MB
Time	Avg. sync duration per cycle	3.14 seconds
	Time to prepare decoy content (L1 $\rightarrow$ L3)	4.9 seconds
	Time to switch layers visibly (attack surface swap)	1.6 seconds
	Vault response latency	0.7 seconds
Communication	Avg. messages exchanged per sync cycle	142 Packets
	Control signals (internal triggers)	60
	Metadata sync events	45
	Vault-layer data alignment	37

Figure 4.9: System complexity metrics: storage, time, and communication

4.8 Conclusion and Future Work

This chapter has detailed SHIELD’s architecture, a novel framework that embeds multi-layer deception directly within semi-structured data stores to counter post-breach reconnaissance. Our prototype evaluation demonstrates that SHIELD synchronizes three independent decoy layers with the genuine vault in an average of 4.27 s per update cycle while imposing modest memory and network overheads. In tests, SHIELD achieved a realism accuracy of 94.7%, rendering decoy content indistinguishable from the true data in the vast majority of access events. Write requests from untrusted clients were blocked with perfect effectiveness, and 89% of adversarial read attempts were diverted into decoy layers, thereby safeguarding the original vault. These findings confirm that SHIELD transforms data from a passive liability into an active defense mechanism without compromising operational performance or scalability.

Looking ahead, three avenues will be pursued to strengthen and broaden SHIELD’s capabilities. First, we will extend decoy synthesis to binary and multimedia formats such as firmware images, PDFs, and audio files to support industrial control systems and archival repositories that handle diverse data types. Second, we will implement real-time synchronization triggers and incremental update mechanisms so that high-frequency change environments can benefit from sub-second freshness without full layer regeneration. Third, we will integrate context-sensitive access policies that leverage identity management, geolocation, and behavior analytics to adjust deception depth dynamically, reducing false positives and refining the attacker experience. By focusing on these enhancements, SHIELD will evolve into a flexible, high-fidelity defense layer suitable for a wide range of security-critical applications.

Conclusion and Future Scope

Preface

This chapter concludes by synthesizing the major findings of the MLEVES and SHIELD frameworks, highlighting their effectiveness in pre-breach and post-breach security. It also outlines future research avenues for adaptive anomaly detection, lightweight cryptography, multimedia deception, and context-aware defense policies.

This final chapter synthesizes the key contributions of the MLEVES and SHIELD frameworks, reflects on the primary findings and limitations of this work, and outlines avenues for future research to advance the security of both cyber-physical systems and data repositories.

5.1 Summary of Contributions

This thesis has presented two complementary security frameworks that together span the full lifecycle of modern digital infrastructures. First, the Multi-Layer Encryption Validation and Execution System (MLEVES) was developed to secure real-time Digital Twin environments through the integration of dual-layer AES and RSA encryption, hash-based validation, AI-powered anomaly detection, and blockchain-based audit logging. MLEVES demonstrated high classification accuracy, efficient cryptographic performance, and scalable logging, validating its applicability to high-stakes domains such as healthcare and industrial Internet of Things.

Second, the Secure, Hidden Information Encryption and Layered Data (SHIELD) framework introduced a deception-first approach for high-value data repositories. By embedding three decoy layers with incremental fidelity and a hybrid synchronization mechanism, SHIELD yielded a realism accuracy of 94.7%, a perfect write-denial rate, and the diversion of 89% of adversarial reads into fabricated data. Together, these systems form a unified security paradigm that addresses both pre-breach prevention and post-breach deception.

5.2 Key Findings

The empirical evaluations confirm that multilayer encryption coupled with real-time AI analysis can detect and prevent a wide range of tampering and intrusion attempts while maintaining sub-10 ms encryption latency and transaction throughput exceeding 800 tx/s. Similarly, continuous decoy regeneration under randomized intervals imposes an average synchronization delay of 3.14 s, with a total storage overhead of 837 MB, delivering high deception fidelity without prohibitive resource consumption. The combined findings underscore that proactive cryptographic controls and reactive deception mechanisms each contribute unique strengths, and their integration offers enhanced security coverage across disparate threat vectors.

5.3 Limitations

Despite these advances, several limitations warrant careful consideration. The threat models evaluated did not encompass side-channel or physical tampering attacks, and MLEVES assumes

access to secure enclaves for decryption and execution. SHIELD’s decoy transformations are currently limited to semi-structured text data and require periodic full-layer regeneration, which may not meet the freshness requirements of extremely high-frequency update scenarios. Furthermore, the usability and administrative complexity of configuring dual environments may impede adoption without further tooling and automation support.

5.4 Future Work

5.4.1 Enhancing AI Adaptivity and Online Learning

Future efforts will focus on enabling MLEVES to adapt its anomaly detection models in real time through online learning techniques, thereby improving responsiveness to novel threat patterns and reducing false-positive rates.

5.4.2 Lightweight Cryptography and Incremental Updates

Exploration of alternative cryptographic primitives with lower computational overhead, combined with incremental or partial decoy regeneration techniques, will aim to reduce both latency and resource consumption in SHIELD.

5.4.3 Extending Deception to Multimedia and Firmware

To broaden applicability, the SHIELD architecture will be extended to support binary, multimedia, and firmware file formats, enabling deception in industrial control systems and archival repositories.

5.4.4 Context-Aware and Dynamic Policy Integration

Integrating identity, geolocation, and behavioral analytics into access-control policies can dynamically adjust encryption strength and decoy fidelity, offering fine-grained deception tailored to specific user contexts and threat levels.

5.4.5 Full-Scale Deployment and Usability Studies

Large-scale field trials in healthcare and manufacturing environments will evaluate long-term stability, user experience, compliance with regulatory standards, and the operational overhead of maintaining dual-framework deployments.

5.5 Final Remarks

By uniting robust encryption, advanced anomaly detection, and sophisticated deception strategies, this thesis has laid the groundwork for a new generation of end-to-end security solutions. Continued research along the proposed directions promises to yield systems that not only withstand sophisticated adversaries but also integrate seamlessly into dynamic, high-integrity digital ecosystems.

References

- [1] S. R. Ahmed, E. Sonuç, M. R. Ahmed, and A. D. Duru, "Analysis survey on deepfake detection and recognition with convolutional neural networks," *In proc. Int. Cong. Human-Computer Inte. Opti. Robo. Appl.*, Jun. 2022, pp. 1-7.
- [2] L. Guarnera, O. Giudice, and S. Battiato, "Mastering Deepfake Detection: A Cutting-Edge Approach to Distinguish GAN and Diffusion-Model Images," *ACM Trans. Multi. Compu. Comm. Appl.*, 2024.
- [3] S. B. Boddu et al., "Fake Images Detection: A Comparative Study Using CNN and VGG-16 Models," *Int. J. Adv. Engi. mang.*, vol. 5, pp. 150-157, 2023.
- [4] Y. Patel et al., "An improved dense CNN architecture for deepfake image detection," *IEEE Access*, vol. 11, pp. 22081-95, Mar. 2023.
- [5] M. S. Mukta et al., "An investigation of the effectiveness of deepfake models and tools," *J. Sen. Actu. Net.*, vol. 12, no. 4, pp. 61, Aug. 2023.
- [6] P. Saikia, D. Dholaria, P. Yadav, V. Patel, and M. Roy, "A hybrid CNN-LSTM model for video deepfake detection by leveraging optical flow features," *In proc. Int. Joint Conf. Neu. Net.*, Jul. 2022, pp. 1-7.
- [7] U. Masud et al., "LW-DeepFakeNet: a lightweight time distributed CNN-LSTM network for real-time DeepFake video detection," *Sig. Imag. Video Proc.*, vol. 17, no. 8, pp. 4029-37, Nov. 2023.
- [8] K. Bansal, S. Agarwal, and N. Vyas, "Deepfake Detection Using CNN and DCGANS to Drop-Out Fake Multimedia Content: A Hybrid Approach," *In proc. Int. Conf. IoT, Comm. Auto. Tech.*, Jun. 2023, pp. 1-6.
- [9] J. Gao, T. Zhang, and C. Xu, "Learning to model relationships for zero-shot video classification," *IEEE Trans. Patt. Analy. Mach. Inte.*, vol. 43, no. 10, pp. 3476-91, 2020.
- [10] M. Gao, W. Cai, and R. Liu, "AGTH-Net: attention-based graph convolution-guided third-order hourglass network for sports video classification," *J. Heal. Engin.*, 2021.
- [11] X. Long et al., "Purely attention based local feature integration for video classification," *IEEE Trans. Patt. Anal. Mach. Inte.*, vol. 44, no. 4, pp. 2140-54, Oct. 2020.
- [12] H. Yu et al., "Convolutional neural networks for medical image analysis: state-of-the-art, comparisons, improvement and perspectives," *Neurocomputing*, vol. 444, pp. 92-110, Jul. 2021.
- [13] J. Donahue et al., "Long-term recurrent convolutional networks for visual recognition and description," *In proc. IEEE conf. compu. vision patt. reco.*, 2015, pp. 2625-2634.

- [14] Q. Li et al., "Action recognition by learning deep multi-granular spatio-temporal video representation," *In proc. ACM int. conf. mult. retr.*, Jun. 2016, pp. 159-166.
- [15] J. Naruniec et al., "High-resolution neural face swapping for visual effects," *Comp. Graph. Forum*, vol. 39, no. 4, pp. 173-184, Jul. 2020.
- [16] P. Sun et al., "Landmarkgan: Synthesizing faces from landmarks," *Patt. Reco. L.*, vol. 161, pp. 90-8, Sep. 2022.
- [17] M. Kumar and H. K. Sharma, "A GAN-based model of deepfake detection in social media," *Procedia Comp. Sci.*, vol. 218, pp. 2153-62, Jan. 2023.
- [18] S. K. Sharma et al., "Estimation and Concealment Deep Fake Detection in Images using Hybrid LSTM," *Int. J. Inte. Sys. Appl. Engi.*, vol. 12, no. 2, pp. 505-22, 2024.
- [19] S. Kingsley and M. Parthiban, "Deep Fake Detection using Advance ConvNets2D," *IEEE Int. Conf. on Sustainable Comp. Data Comm. Sys. (ICSCDS)*, 2023.
- [20] P. Sharma, M. Kumar, and H. Sharma, "Comprehensive analyses of image forgery detection methods from traditional to deep learning approaches: an evaluation," *Multimedia Tools and Applications*, vol. 82, no. 12, pp. 18117-18150, 2023.
- [21] J. Mallet et al., "Hybrid Deepfake Detection Utilizing MLP and LSTM," *2023 3rd International Conference on Electrical, Computer, Communications and Mechatronics Engineering (ICECCME)*, IEEE, 2023.
- [22] N. Kumar et al., "Deepfake image detection using cnns and transfer learning," *In proc. Int. Comp. Comm. Green Engi.*, pp. 1-6, 2021.
- [23] H. S. Shad et al., "Comparative Analysis of Deepfake Image Detection Method Using Convolutional Neural Network," *Comput. Intell. Neurosci.*, vol. 2021, pp. 3111676, 2021.
- [24] Y. Patel, M. Shohel Rana, A. Singh, and D. Rajeswari, "An improved dense cnn architecture for deepfake image detection," *IEEE Access*, vol. 11, pp. 22081-22095, 2023.
- [25] M. S. Rana, Y. Patel, A. Singh, and D. Rajeswari, "Deepfake detection: A systematic literature review," *IEEE Access*, vol. 10, pp. 25494-25513, 2022.
- [26] H. Agarwal, A. Singh, and D. Rajeswari, "Deepfake detection using svm," in *Proc. 2nd Int. Conf. Electronics Sustainable Comm. Sys. (ICESC)*, pp. 1-6, 2021.
- [27] A. Badale, S. Ashrith, V. Wesselkamp, P. Swathi, and S. Sk, "Deep fake detection using neural networks," in *Proc. 15th IEEE Int. Conf. Advanced Video Signal Based Surveillance (AVSS)*, pp. 1-6, 2018.
- [28] L. Bondi, P. Korshunov, and S. Marcel, "Training strategies and data augmentations in cnn-based deepfake video detection," in *Proc. IEEE Int. Workshop Information Forensics Security (WIFS)*, pp. 1-6, 2020.
- [29] S. A. Aduwala, A. Korshunov, P. Marcel, and V. Wesselkamp, "Deepfake Detection using GAN discriminators," in *Proc. 7th IEEE Int. Conf. Big Data Computing Service Applications (BigDataService)*, pp. 1-6, 2021.
- [30] P. Korshunov and S. Marcel, "Vulnerability assessment and detection of deepfake videos," in *Proc. Int. Conf. Biometrics (ICB)*, pp. 1-6, 2019.
- [31] P. Swathi and S. Sk, "Deepfake creation and detection: A survey," in *Proc. 3rd Int. Conf. Inventive Research Computing Applications (ICIRCA)*, pp. 1-6, 2021.

Publications

Conference Proceedings:

- Aditya Helode, Akash Yadav, Vishnu Prasad Verma and Dr. Srinivasa K G, “Fusion of Machine Learning and Deep Learning:A Hybrid Approach for Deepfake Detection,” in *Proc. of the 15th International IEEE Conference on Computing Communication and Networking Technologies (ICCCNT)*, 2024, IIT Mandi, Mandi, India (**Accepted** in Jun 2024).
- Akash Yadav, Aditya Helode, Vishnu Prasad Verma, Mayank Lovanshi and Dr. Srinivasa K G, “Language-Guided Contextual Transformer Network for Referring Video Object Segmentation,” in *2024 IEEE Region 10 Symposium (TENSYP)*, NSUT, New Delhi, India. (**Submitted** in May 2024).

Author's Biography

Aditya Helode was born in India on 25th June, 1999. He has received his Master of Science from SGBAU, Maharashtra. He has qualified GATE 2022 Examination. Aditya is currently pursuing Master of Technology from Dr. SPM IIIT Naya Raipur, India (IIIT-NR) in Computer Science Engineering (CSE), specialization in Data Science & Artificial Intelligence.

Resilience and adaptability are two characteristic that distinguish him as a person. He has research interest in the field of AI/ML. He is passionate about sports, travelling and guitar.

