

CSE 123A - Demo Script

Water Level Monitoring System

Group 8

Part 1: Introduction

Action: Hold up or gesture toward the Brita pitcher.

Script:

“Has this ever happened to you? You come home after a long day, you’re thirsty, and you go to grab the water filter pitcher—only to find it completely empty. Nobody refilled it. This is a common problem in shared living spaces—dorms, family homes, offices. Everyone uses the filtered water, but nobody knows when it’s running low until it’s too late. Our project solves this. We built a smart water level monitoring system that sits underneath your water filter pitcher, continuously tracking how much water is left, and sends a notification to everyone in the household when it’s time to refill.”

Part 2: The Hardware

Action: Pick up the prototype base and point out each component as mentioning it.

Script:

“Let’s start with the hardware. The system has three main components:

First, the load cell. This is a strain-gauge weight sensor. When weight is applied, it bends slightly, and that bending changes its electrical resistance. The change is ver tiny—so we use the **HX711 amplifier board** to boost the signal into something our microcontroller can read. The HX711 gives us 24-bit resolution, which means we can detect very small changes in weight.

Second, the ESP32 microcontroller. This is the brain of our system. It reads the weight data from the HX711, converts it into a water level percentage, and sends that data over WiFi to our cloud server.

Third, the mounting base. We designed and 3D-printed two circular plates, that sandwich the load cell. The pitcher sits on top. We designed these with M4 screw holes so everything stays secure and aligned.

Part 3: Live Demo – Weighing

Action: Place the pitcher on the platform. Have the a computer open showing the readings of the sesnor.

Script:

“Now let’s see it in action. I’m going to place this Brita pitcher on the sensor base. The load cell is now measuring the total weight. Our ESP32 reads that value, subtracts the known weight of the empty pitcher, and calculates the percentage of water remaining.

[Point to the web dashboard.] Over here on our web dashboard, you can see the water level updating. Right now it’s showing [read current percentage]. The pitcher graphic fills up to match the actual level, and you can see the exact percentage and the last time the reading was updated.

Let me pour some water out to simulate usage.

[Pour water out of the pitcher into a cup.] Watch the dashboard—you can see the percentage dropping as I pour. The system polls the database every five seconds, so there’s a short delay, but it tracks the change.”