Shri Vile Parle Kelavani Mandal's
DWARKADAS J. SANGHVI COLLEGE OF ENGINEERING
(Autonomous College Affiliated to the University of Mumbai)
NAAC Accredited with "A" Grade (CGPA : 3.18)

Innovative Product Development-I Report

on

EcoSort: SMART WASTE MANAGEMENT SYSTEM

SUBMITTED BY

Name	SAP ID
Shrutik Acharya	60002231068
Soham Bhosale	60002230150
Rugved Mane	60002231007
Siddhaant Pandit	60002231036

Under the guidance of

Prof. Abhilasha Ranghate

DEPARTMENT OF
ELECTRONICS AND TELECOMMUNICATION ENGINEERING

Academic Year: 2025-2026

Shri Vile Parle Kelavani Mandal's

Dwarkadas J. Sanghvi College of Engineering

Plot no. U-15, JVPD Scheme, Bhaktivedanta Swami Marg,

Vile Parle (W), Mumbai – 400 056

Department of Electronics and Telecommunication Engineering

This is to certify that

"EcoSort : SMART WASTE MANAGEMENT SYSTEM"

SUBMITTED BY

Name	SAP ID
Shrutik Acharya	60002231068
Soham Bhosale	60002230150
Rugved Mane	60002231007
Siddhaant Pandit	60002231036

Students of **Electronics and Telecommunication Engineering** have successfully completed their Innovative Product Development-I/III required for the fulfillment of **SEM V** during the second half of the year 2025. The project report has been assessed and found to be satisfactory.

Head of Department **Principal**

Internal Examiner **External Examiner**

Table of Contents

Page No.

I) ABSTRACT 4

II) INTRODUCTION 5

III) LITERATURE REVIEW 6

IV) THEORY 10

i) Working Principle 10

ii) Block Diagram/ Circuit Diagram/Flow chart 13

V) RESULT 15

VI) FUTURE SCOPE 16

VII) BUDGET SHEET 17

VIII) APPLICATIONS 18

IX) REFERENCES 19

I) ABSTRACT

Municipal solid waste generation has crossed **2 billion tonnes annually**, creating an urgent need for efficient and safe segregation mechanisms. Traditional methods rely on manual sorting which is slow, inaccurate, and exposes workers to harmful pathogens. Deep learning and real-time computer vision techniques have emerged as powerful solutions for automating waste classification and improving recycling efficiency.

This project proposes a **Smart Waste Management System** using **YOLOv8n**, a lightweight object detection model capable of real-time inference on CPU systems. A **laptop webcam** is used for continuous image capture, enabling on-the-spot detection of waste types such as **plastic, paper, metal, glass, and organic waste**.

The system draws inspiration from prior works—including YOLO-based recyclable detection [1], medical waste sorting [2], IoT food waste monitoring [3], YOLOv8 embedded detection frameworks [4], and advanced YOLOv11 classification systems [5]—and adapts these concepts into a simplified, low-cost prototype.

The results demonstrate that YOLOv8n provides high-speed inference while maintaining acceptable accuracy for real-time waste detection. The system represents a scalable, low-cost, AI-powered solution suited for smart bins, recycling plants, and public environmental systems.

II) INTRODUCTION

Waste segregation is a major challenge for modern cities. Manual processes lead to contamination, low recycling rates, and unsafe working conditions. Advances in AI and IoT are increasingly used in smart waste systems to automate classification and optimize collection routes.

Computer vision–based models—especially **YOLO (You Only Look Once)**—offer high-speed, single-shot object detection suitable for real-time applications. Prior research demonstrates:

- YOLOv4-tiny on Arduino UNO achieved 75% accuracy for recyclable materials [1].
- YOLO integrated with IoT sensors improved safety in medical waste sorting [2].
- Smart bins with ultrasonic and gas sensors achieved <5% error in food waste monitoring [3].
- YOLOv8 on Jetson Nano achieved 96% classification accuracy at 15 FPS [4].
- YOLOv11 achieved up to 99% mAP on diverse waste categories [5].
- Robotic-arm sorting systems achieved high physical sorting accuracy (96.5% on rigid waste) [6].

Building upon these academic advancements, this project develops a **simple but effective real-time detection system** using **YOLOv8n and a laptop webcam**, demonstrating how AI can automate waste segregation in a low-cost environment.

III) LITERATURE REVIEW

a) AI-Based Waste Classification and Smart Waste Management

Recent research highlights the significant role of artificial intelligence and computer vision in automating waste segregation and improving sustainable waste-management systems. Wahyutama and Hwang [1] demonstrated how lightweight YOLOv4-tiny models, deployed on embedded platforms such as the Raspberry Pi, can classify recyclable materials while simultaneously monitoring bin capacity through IoT sensors. Their work established the foundation for compact, low-cost waste-identification systems capable of real-time execution. Complementing this, Gowtham et al. [3] presented an IoT-enabled smart-bin framework that integrates ultrasonic, weight, and gas sensors to analyze food waste decomposition and fill-level metrics, emphasizing the increasing importance of multi-modal environmental monitoring in urban waste operations. Taken together, these studies underscore the growing shift toward intelligent, sensor-driven waste-management ecosystems.

Suchdeo and Rajnish [5] expanded on this direction by implementing YOLOv11 for multi-class waste classification, achieving high accuracy across ten waste categories. Their research illustrates how advanced deep-learning frameworks can handle diverse waste streams more effectively, although computational demands present challenges for deployment on lightweight hardware. Collectively, these works highlight the need for optimized, real-time AI architectures that balance accuracy, energy consumption, and operational efficiency.

b) Mechanical Sorting, Robotic Manipulation, and Automated Waste Handling

Beyond classification, automation in physical waste handling has emerged as a significant research direction. Maske et al. [6] developed a robotic manipulation system integrated with YOLO-based perception to perform automated sorting of rigid and deformable waste items. Their work demonstrated the feasibility of combining computer vision with actuation mechanisms, achieving high grasp success rates, particularly for rigid waste. This highlights the potential of robotic systems to reduce manual labor, increase accuracy, and improve worker safety in large-scale waste-processing environments.

Similarly, studies such as those by Bawankule et al. [4], although focused primarily on detection, provide insight into how high-speed YOLO variants can be paired with embedded hardware to support automated or semi-autonomous sorting workflows. These advancements collectively indicate a trend toward hybrid systems that combine perception, mechanical manipulation, and intelligent actuation.

c) Real-Time Computer Vision, Deep Learning, and Embedded Detection

Significant progress in deep-learning models and low-power hardware has driven widespread adoption of real-time waste-detection systems. Bawankule et al. [4] demonstrated that YOLOv8 can achieve up to 96% accuracy at 15 FPS on the Jetson Nano platform, showcasing the feasibility of deploying high-performance computer-vision pipelines on edge devices. Similarly, Wahyutama and Hwang [1] showed that lightweight YOLO variants could operate efficiently on constrained embedded hardware while maintaining acceptable accuracy levels.

Suchdeo and Rajnish [5] further emphasized the potential of advanced YOLO architectures by showcasing high mAP values across diverse waste categories. These studies collectively reveal a need for balancing detection accuracy, model complexity, and computational constraints—especially for real-time smart-bin and field-deployed systems.

d) System Integration, Sensor Fusion, and Smart-Bin Architectures

IoT-driven waste-management systems are gaining prominence through the integration of sensing, machine learning, and cloud connectivity. Gowtham et al. [3] demonstrated a food-waste monitoring system that uses multiple sensors to track decomposition, bin fill levels, and environmental conditions, offering actionable insights for optimized waste collection and processing. Their findings reflect the growing trend of sensor fusion in waste-management infrastructure.

Similarly, Wahyutama and Hwang [1] illustrated the benefits of integrating vision-based classification with IoT telemetry for real-time monitoring, supporting more efficient municipal waste-collection strategies. These smart-bin architectures highlight the importance of combining perception with complementary data sources to improve reliability, accuracy, and scalability in automated waste-management systems.

e) Performance Optimization, Edge Deployment Challenges, and Scalability

Despite significant advancements, deploying real-time classification models at scale presents challenges related to energy consumption, computational efficiency, and data diversity. Studies deploying YOLO models on embedded platforms, such as those by Bawankule et al. [4] and Wahyutama and Hwang [1], reveal limitations in frame rate, accuracy under low-light or cluttered conditions, and generalization across diverse waste types.

Suchdeo and Rajnish [5] also highlighted the need for larger, more representative datasets

to reduce class imbalance and improve overall system robustness. Furthermore, robotic-sorting research by Maske et al. [6] demonstrated that deformable and irregular waste objects remain difficult to classify and grasp compared to rigid materials. These findings point to the need for enhanced datasets, optimized AI models, and adaptive system designs capable of handling real-world variability.

f) Gaps in Research

A review of existing literature ([1]–[6]) reveals several important research gaps. First, real-world validation remains limited, as many studies test systems in controlled indoor environments rather than diverse real-world waste scenarios, reducing generalizability. Second, while deep-learning models such as YOLOv8 and YOLOv11 demonstrate high accuracy, integration with low-power, constrained hardware remains challenging, especially for continuous real-time operation on embedded platforms. Third, most research focuses on classification performance, with fewer studies addressing full-cycle automation that includes physical waste segregation and real-time system integration. Fourth, transparent, reflective, and deformable waste materials continue to pose recognition challenges, requiring advanced sensing or model enhancements. Finally, large-scale deployment, user acceptance, and long-term operational considerations are underexplored, despite their importance for municipal adoption and smart-city integration.

IV) THEORY

i) Working Principle

The proposed system is a smart waste-segregation solution built around a real-time computer-vision pipeline using YOLOv8n and a laptop webcam. Its objective is to autonomously identify and classify plastic, paper, metal, glass, and organic waste using a lightweight and fast detection workflow. The architecture relies on three cooperative subsystems: (1) Vision Acquisition Subsystem (Webcam + OpenCV), (2) AI-Based Detection and Classification Subsystem (YOLOv8n), and (3) Decision and Output Processing Subsystem (Python Application Layer), all operating simultaneously to deliver stable frame capture, efficient object detection, and real-time output rendering.

1. Image Acquisition and Pre-Processing (Webcam + OpenCV)
When the system starts, the webcam initializes and streams continuous video frames which are pre-processed using OpenCV. This includes resizing frames to 640×640 for YOLO, normalizing pixel values, and applying color adjustments to ensure consistent input quality across lighting variations. This step ensures smooth and stable frame flow, similar to acquisition pipelines used in earlier lightweight YOLO deployments [1][4].

2. Real-Time Waste Detection Using YOLOv8n
After preprocessing, each frame is passed to the YOLOv8n model for real-time inference. The model performs bounding-box prediction and multi-class waste recognition, outputting labels and confidence scores. YOLOv8n is selected for its balance of high speed and efficiency on CPU hardware, a trend also validated in YOLOv4-tiny recyclable detection systems [1] and Jetson-based YOLOv8 implementations [4]. It reliably detects plastic bottles, paper/cardboard, glass, metal cans, and organic waste.

3. Decision Logic and Classification Output
A lightweight decision logic layer evaluates detected objects based on confidence thresholds, object size, and on-screen placement. Valid detections are displayed in real time with bounding boxes and labels. This filtering approach resembles the decision-making strategies used in multi-category YOLOv11 systems and robotic sorting research [5][6].


4. Real-Time Visualization and Data Handling

The system displays annotated frames showing detected waste type, bounding-box positions, and confidence levels. Detection outputs may also be logged for IoT-based expansion, similar to the integrated sensor monitoring workflows seen in smart food-waste bin studies [3].

5. Continuous Loop and System Performance

Once a frame is processed, the system immediately moves to the next, forming a high-speed continuous loop. YOLOv8n maintains approximately 15–23 FPS on a typical laptop CPU, aligning with performance results reported in embedded YOLOv8 research [4]. This ensures smooth, uninterrupted real-time detection and makes EcoSort a practical, efficient prototype for automated waste classification.

ii) RESULT




```
import glob
from IPython.display import Image, display
for image_path in glob.glob(f'/content/runs/detect/predict/*.jpg')[:10]:
  display(Image(filename=image_path, height=400))
  print('\n')
```

```
Start coding or generate with AI.
```

+ Code + Text


```
Ultralytics 8.3.252 🚀 Python-3.12.12 torch-2.9.0+cu126 CUDA:0 (Tesla T4, 15095MiB)
YOLO11s summary (fused): 100 layers, 9,413,961 parameters, 0 gradients, 21.3 GFLOPs


image 1/7 /content/data/validation/images/045cb683-WhatsApp_Image_2026-01-12_at_21.08.10_7.jpe
image 2/7 /content/data/validation/images/11c31609-WhatsApp_Image_2026-01-13_at_11.42.38_1.jpe
image 3/7 /content/data/validation/images/165ca958-Paper_258.jpg: 640x640 1 crumbled paper, 16
image 4/7 /content/data/validation/images/4fc32c44-WhatsApp_Image_2026-01-12_at_21.08.10_4.jpe
image 5/7 /content/data/validation/images/5a97990a-WhatsApp_Image_2026-01-12_at_21.07.57.jpeg:
image 6/7 /content/data/validation/images/c99172b6-WhatsApp_Image_2026-01-12_at_21.08.11.jpeg:
image 7/7 /content/data/validation/images/f28d022f-Paper_245.jpg: 640x640 2 crumbled papers, 1
Speed: 2.0ms preprocess, 31.7ms inference, 3.5ms postprocess per image at shape (1, 3, 640, 64
Results saved to /content/runs/detect/predict3
💡 Learn more at https://docs.ultralytics.com/modes/predict
```


```
import glob
from IPython.display import Image, display
for image_path in glob.glob(f'/content/runs/detect/predict/*.jpg')[:10]:
  display(Image(filename=image_path, height=400))
  print('\n')
```


```
Start coding or generate with AI.
```


```
Start coding or generate with AI.
```


FPS: 5.81
Number of objects: 1
plastic bottle: 77%


FPS: 5.51
Number of objects: 1
crumbled paper: 71%


FPS: 5.39
Number of objects: 1
wrapper: 65%


YOLO detection results
FPS: 5.82
Number of objects: 1
wrapper: 50%
Add people
All Bookmarks


train/box_loss
train/cls_loss
results
smooth
train/dfl_loss
metrics/precision(B)
metrics/recall(B)
val/box_loss
val/cls_loss
val/dfl_loss
metrics/mAP50(B)
metrics/mAP50-95(B)


MAX PROTEIN
7 Grain Breakfast Cookie
SOFT & CHEWY
10g PROTEIN
4g FIBER
CALCIUM
NO MAIDA
plastic bottle 1
wrapper 2
crumbled paper 3

The EcoSort prototype was successfully implemented and tested using a laptop webcam and the YOLOv8n detection model. The system demonstrated stable real-time performance and accurate recognition of common waste categories during controlled indoor evaluations. The key results are summarized below:

1. **Real-Time Detection Performance**

- YOLOv8n achieved smooth real-time inference on a standard laptop CPU.
- Plastic, paper, metal, glass, and organic waste items were detected with consistent confidence levels.
- The system maintained reliable detection across small variations in lighting.
- Bounding boxes and class labels were accurately rendered on the live video output.

2. **Image Processing and Frame Handling**

- The webcam provided continuous video input without significant latency.
- OpenCV preprocessing (resizing to 640×640 and normalization) ensured clean and stable frames for model input.
- The frame rate remained within the operational range required for uninterrupted detection.

3. **Classification Accuracy**

- Distinct waste items were identified with high confidence in isolated test scenarios.
- Recognition accuracy aligned with expected performance of lightweight YOLO models used in waste classification literature [1][4][5].
- Detection accuracy slightly decreased when multiple objects were placed close together but remained within acceptable limits for prototype evaluation.

4. **Decision Logic and Output Evaluation**

- The decision module correctly filtered detections using predefined confidence thresholds.
- Multiple detected objects were separately labelled without overlap errors in most cases.
- The real-time display of bounding boxes and labels remained stable throughout testing.

V) FUTURE SCOPE

The growing demand for sustainable waste-management solutions presents several opportunities for future enhancement of the EcoSort system. With rapid progress in artificial intelligence and real-time computer vision, future versions of EcoSort can incorporate more advanced, lightweight deep-learning models optimized for edge devices such as Arduino UNO or Jetson Nano. These optimizations, including pruning and quantization, would improve detection efficiency and enable the system to operate autonomously without reliance on a laptop, aligning with trends observed in previous YOLO-based waste-classification research [1][4]. Furthermore, enhanced dataset diversity and multi-scenario training can strengthen model performance in cluttered, multi-object environments and improve recognition of complex waste types such as transparent materials and deformable organic waste, addressing limitations highlighted in waste-classification studies [5][6].

Another promising direction involves integrating EcoSort with IoT-enabled smart-bin architectures. By combining computer-vision-based classification with sensors such as ultrasonic distance modules, load cells, and gas sensors, the system could monitor fill levels, detect decomposition, and automatically communicate bin status to cloud dashboards, following approaches demonstrated in IoT-driven waste-monitoring systems [3]. This multi-modal sensing would create a more holistic waste-management ecosystem capable of adaptive collection scheduling and environmental monitoring.

The future scope also extends toward autonomous physical segregation. Incorporating robotic or servo-driven mechanisms, inspired by recent developments in automated waste-sorting robotics [6], would enable EcoSort to not only identify but also mechanically separate waste into appropriate compartments. Soft-robotics-based grippers or guided chute mechanisms could ensure safer and more accurate sorting, even for irregularly shaped items.

Scalability remains an important long-term objective. Deploying EcoSort prototypes in real-world settings—such as educational campuses, residential societies, public recycling stations, or commercial facilities—would provide insight into long-term reliability, user interaction, environmental robustness, and system cost-effectiveness. Large-scale deployment studies would also help refine maintenance requirements and operational guidelines.

Additionally, integrating EcoSort with cloud connectivity, dashboards, and data-analytics platforms can support city-wide waste-management strategies by aggregating classification trends, recycling patterns, and bin-fill data across multiple locations. Such data-driven insights can inform municipal planning and contribute to circular-economy initiatives.

Ultimately, the future development of EcoSort lies in combining edge-AI vision, IoT sensing, robotic automation, and scalable deployment frameworks to create a fully autonomous, intelligent waste-segregation ecosystem that can be seamlessly integrated into smart-city infrastructures.

VI) BUDGET SHEET

S. No.	Component	Quantity	Cost per Piece (INR)	Total Price (INR)
1	Arduino Uno + Camera Module	1	1800 + 1000	2800
2	Breadboard	1	300	300
3	Servo Motor (Low power for claw)	1	150	150
4	Servo Motor (Higher torque for bin rotation)	1	400	400
5	Weight Sensor (Load Cell)	1	150	150
6	Gas Sensor (MQ Series)	1	200	200
7	Ultrasonic Sensor (HC-SR04)	2	90	180

VII) APPLICATIONS

EcoSort, an AI-based waste-segregation system using real-time vision detection, has a wide range of potential applications across environmental, municipal, educational, and industrial domains:

1. Smart Waste Management & Recycling

- Automated classification of plastic, paper, metal, glass, and organic waste.
- Integration with smart bins for improved recycling workflows.
- Enhancing segregation efficiency at public disposal points, campuses, and residential complexes.

2. Municipal Solid Waste Operations

- Assisting city authorities in streamlining waste-collection processes.
- Reducing contamination in recyclable waste streams.
- Supporting data-driven waste-management planning through detection logs and analytics.

3. Industrial & Commercial Waste Handling

- Improving waste sorting in malls, offices, factories, and logistics centers.
- Enhancing recycling pipelines for packaging, manufacturing, and retail waste streams.
- Reducing manual labor dependency in hazardous or high-volume waste environments.

4. Environmental Monitoring & Sustainability

- Supporting eco-friendly waste disposal habits through automated categorization.

- Preventing cross-contamination that leads to soil and water pollution.

5. Education, Research & Training

- Serving as a practical tool for teaching machine learning, computer vision, and IoT concepts.
- Providing a testbed for further research in smart-bin systems, embedded detection, and automation.
- Demonstrating the role of AI in solving real-world environmental problems.

6. Smart City Infrastructure

- Integrating with IoT platforms to enable city-wide intelligent waste-collection networks.
- Supporting municipal dashboards with real-time waste-type statistics and location insights.
- Enhancing automation in urban recycling centers and public waste-management systems

VIII) REFERENCES:

[1] A. B. Wahyutama and M. Hwang, "YOLO-Based Object Detection for Separate Collection of Recyclables and Capacity Monitoring of Trash Bins," *Electronics*, vol. 11, no. 9, p. 1323, 2022, doi: 10.3390/electronics11091323.

[2] M. H. Moktar, H. Mohamed, S. S. H. Hajjaj, and M. Z. Baharuddin, "Medical Waste Sorting Machine Development with IoT and YOLO Model Utilization," *Journal of Engineering and Applied Science*, vol. 72, no. 1, 2025, doi: 10.1186/s44147-025-00661-5.

[3] S. Gowtham, H. Harsha, M. Shreyas, and P. G.-S. V., "Waste Wisely: IoT-Powered Smart Bins Redefining Food Waste Management," in *Proceedings of ICAECA 2025*, pp. 1–6, doi: 10.1109/icaeca63854.2025.11012363.

[4] R. Bawankule, V. Gaikwad, I. Kulkarni, S. Kulkarni, A. Jadhav, and N. Ranjan, "Visual Detection of Waste using YOLOv8," in *2023 IEEE International Conference on Smart Computing and Sustainable Systems (ICSCSS)*, 2023, doi: 10.1109/icscss57650.2023.10169688.

[5] E. Suchdeo and R. Rajnish, "AI-Driven Waste Classification Model for Recycling Applications Using YOLOv11," in *ICICV 2025*, pp. 1003–1008, doi: 10.1109/icicv64824.2025.11085860.

[6] S. Maske, S. Jaiswal, A. Zade, P. Agrawal, A. Goel, and R. Parvathi, "Automated Waste Sorting System Using Computer Vision and Robotic Manipulation," in *ICETETSIP 2025*, pp. 1–8, doi: 10.1109/icetetsip64213.2025.11156659