

Lab 10. Demonstrate ES6 features in JavaScript – 2

1. Demonstrate the Arrow functions. (A)

Arrow functions are a concise syntax for writing function expressions in JavaScript. Introduced in **ES6**, they eliminate the need for the function keyword and provide unique scoping behaviors.

Syntax:

Var functionName = (parameters) => { Logic of function }

```
JavaScript Demo: Arrow function expressions
1
2 const addUsingArrowFunction = (a, b) => a + b;
3
4 function add(a,b){
5     return a+b;
6 }
7
8 console.log("Add function called: ",add(5,10))
9 console.log("Add using Arrow Function Called: ",addUsingArrowFunction(5,10))
10
```

2. Write JavaScript that handles following mouse event. (B)

- If mouse left button pressed on browser, it displayed message “Left Clicked”.
- If mouse right button pressed on browser, it displayed message “Right Clicked”.

Mouse events allow you to track and respond to user interactions with a pointing device like a mouse or trackpad.

But here your are not supposed to check which event is fired (from click, dblclick etc..)

Instead you are to find if it was Right Click or the Left Click. But there are no events like RightClick or LeftClick.

Concepts used:

- `addEventListener()`
- `contextmenu` event: The box that shows up on rightClick is called context menu

Hint: Normal click always triggers left click.

```
addEventListener("click", () =>{document.write("Left Clicked")}) // for left click.
```

```
addEventListener("contextmenu", ()=>{ console.log("Right Clicked") })
```

2. Write a JavaScript having a list of checkbox and by clicking on checkbox, it should show list of selected value in comma separated format. (e.g. list of roll number as checkbox value, and display selected roll number in comma separated format) (C)

Basic Output Layout:

Roll No.

- ☐ 101
- ☐ 102
- ☐ 103
- ☐ 104
- ☐ 105

Present Number:

Logic:

UI:

Checkbox(with id and value)

```
<input type="checkbox" id="101" value="101" onclick="showIsChecked()">
<label for="101">101</label>
```

Javascript :

- use .checked() attribute to see if it is checked
- store the checked elements in temporary array and then displays it over here
-