1. Task 2 :- Exploratory Data Analysis (Week 2)
2. Dataset :- Hotel Booking Dataset

1. Importing Libraries

In this section, we import the Python libraries required to perform exploratory data analysis.

- Pandas: Used for loading, manipulating, cleaning, and analysing structured datasets.
- NumPy: Used for numerical calculations and mathematical operations.
- Matplotlib: Used to create different types of data visualizations.
- Seaborn: Used to create statistical visualizations such as histograms, box plots, and correlation heatmaps.
- Warnings: Used to control unnecessary warning messages during analysis.

In [2]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns

import warnings
warnings.filterwarnings('ignore')

sns.set_style("whitegrid")
```

2. Loading the Dataset

In this section, we load the Hotel Booking Demand dataset into a Pandas DataFrame.

The dataset is stored in CSV format. We use the `read_csv()` function to import the data.

A DataFrame allows us to access, inspect, manipulate, and analyse the dataset using Pandas.

The raw dataset will be preserved separately so that the original data remains unchanged during our analysis.

In [3]:
```
df = pd.read_csv("raw_dataset/hotel_bookings.csv")

print("Dataset loaded successfully!")
```

```
Dataset loaded successfully!
```

3. Initial Data Inspection

Before performing exploratory data analysis, it is important to understand the structure and contents of the dataset.

In this section, we will inspect the dataset dimensions, view sample records, examine column names, and identify numerical and categorical variables.

This initial inspection helps us understand what information is available and which analysis techniques can be applied to different columns.

In [4]:
```
# Check dataset dimensions
print("Dataset Shape:", df.shape)

# Display first five records
print("\nFirst Five Records:")
display(df.head())

# Display last five records
print("\nLast Five Records:")
display(df.tail())

# Display column names
print("\nColumn Names:")
print(df.columns.tolist())

# Display dataset information
print("\nDataset Information:")
df.info()

# Identify numerical columns
numerical_columns = df.select_dtypes(include=np.number).columns.tolist()

# Identify categorical columns
categorical_columns = df.select_dtypes(include="object").columns.tolist()

print("\nNumerical Columns:", numerical_columns)
print("\nCategorical Columns:", categorical_columns)
```

```
Dataset Shape: (119390, 32)

First Five Records:
```

	hotel	is_canceled	lead_time	arrival_date_year	arrival_date_month	arrival_date_week_nun
0	Resort Hotel	0	342	2015	July	
1	Resort Hotel	0	737	2015	July	
2	Resort Hotel	0	7	2015	July	
3	Resort Hotel	0	13	2015	July	
4	Resort Hotel	0	14	2015	July	

5 rows × 32 columns

Last Five Records:

	hotel	is_canceled	lead_time	arrival_date_year	arrival_date_month	arrival_date_weel
119385	City Hotel	0	23	2017	August	
119386	City Hotel	0	102	2017	August	
119387	City Hotel	0	34	2017	August	
119388	City Hotel	0	109	2017	August	
119389	City Hotel	0	205	2017	August	

5 rows × 32 columns

```
Column Names:
['hotel', 'is_canceled', 'lead_time', 'arrival_date_year', 'arrival_date_month', 'ar
rival_date_week_number', 'arrival_date_day_of_month', 'stays_in_weekend_nights', 'st
ays_in_week_nights', 'adults', 'children', 'babies', 'meal', 'country', 'market_segm
ent', 'distribution_channel', 'is_repeated_guest', 'previous_cancellations', 'previo
us_bookings_not_canceled', 'reserved_room_type', 'assigned_room_type', 'booking_chan
ges', 'deposit_type', 'agent', 'company', 'days_in_waiting_list', 'customer_type',
'adr', 'required_car_parking_spaces', 'total_of_special_requests', 'reservation_stat
us', 'reservation_status_date']

Dataset Information:
<class 'pandas.DataFrame'>
RangeIndex: 119390 entries, 0 to 119389
Data columns (total 32 columns):
 #   Column                          Non-Null Count   Dtype
---  ------                          --------------   -----
 0   hotel                           119390 non-null  str
 1   is_canceled                     119390 non-null  int64
 2   lead_time                       119390 non-null  int64
 3   arrival_date_year               119390 non-null  int64
 4   arrival_date_month              119390 non-null  str
 5   arrival_date_week_number        119390 non-null  int64
 6   arrival_date_day_of_month       119390 non-null  int64
 7   stays_in_weekend_nights         119390 non-null  int64
 8   stays_in_week_nights            119390 non-null  int64
 9   adults                          119390 non-null  int64
 10  children                        119386 non-null  float64
 11  babies                          119390 non-null  int64
 12  meal                            119390 non-null  str
 13  country                         118902 non-null  str
 14  market_segment                  119390 non-null  str
 15  distribution_channel            119390 non-null  str
 16  is_repeated_guest               119390 non-null  int64
 17  previous_cancellations          119390 non-null  int64
 18  previous_bookings_not_canceled  119390 non-null  int64
 19  reserved_room_type              119390 non-null  str
 20  assigned_room_type              119390 non-null  str
 21  booking_changes                 119390 non-null  int64
 22  deposit_type                    119390 non-null  str
 23  agent                           103050 non-null  float64
 24  company                         6797 non-null    float64
 25  days_in_waiting_list            119390 non-null  int64
 26  customer_type                   119390 non-null  str
 27  adr                             119390 non-null  float64
 28  required_car_parking_spaces     119390 non-null  int64
 29  total_of_special_requests       119390 non-null  int64
 30  reservation_status              119390 non-null  str
 31  reservation_status_date         119390 non-null  str
dtypes: float64(4), int64(16), str(12)
memory usage: 29.1 MB

Numerical Columns: ['is_canceled', 'lead_time', 'arrival_date_year', 'arrival_date_w
eek_number', 'arrival_date_day_of_month', 'stays_in_weekend_nights', 'stays_in_week_
nights', 'adults', 'children', 'babies', 'is_repeated_guest', 'previous_cancellation
s', 'previous_bookings_not_canceled', 'booking_changes', 'agent', 'company', 'days_i
n_waiting_list', 'adr', 'required_car_parking_spaces', 'total_of_special_requests']
```

```
Categorical Columns: ['hotel', 'arrival_date_month', 'meal', 'country', 'market_segm
ent', 'distribution_channel', 'reserved_room_type', 'assigned_room_type', 'deposit_t
ype', 'customer_type', 'reservation_status', 'reservation_status_date']
```

3.1 Initial Data Inspection – Observations

The initial inspection of the Hotel Booking Demand dataset reveals the following:

1. Dataset Dimensions: The dataset contains 119,390 rows and 32 columns, indicating a large collection of hotel booking records.
2. Numerical Variables: The dataset contains 20 numerical columns, including lead time, arrival year, number of guests, booking changes, and average daily rate (ADR).
3. Categorical Variables: The dataset contains 12 columns identified as categorical, including hotel type, meal plan, market segment, customer type, and reservation status.
4. Data Types: Most numerical variables have integer or floating-point data types, while categorical variables are stored as strings.
5. Potential Data Quality Issues: The initial inspection shows missing values in some columns, including children, country, agent, and company. These will be investigated in the data quality assessment.
6. Date Information: The reservation_status_date column is currently stored as a string and may need conversion into datetime format for date-based analysis.

4. Data Quality Assessment

Data quality assessment is an important step in exploratory data analysis. It helps identify issues that may affect the accuracy and reliability of our analysis.

In [5]:
```
# Calculate missing values for each column
missing_count = df.isnull().sum()

# Calculate percentage of missing values
missing_percentage = (missing_count / len(df)) * 100

# Create a summary DataFrame
missing_summary = pd.DataFrame({
    "Missing Values": missing_count,
    "Missing Percentage": missing_percentage
})

# Display only columns containing missing values
missing_summary = missing_summary[
    missing_summary["Missing Values"] > 0
].sort_values(by="Missing Percentage", ascending=False)
```

```
print("Columns Containing Missing Values:")
display(missing_summary)

# Calculate total missing values in the dataset
print("Total Missing Values:", df.isnull().sum().sum())
```

Columns Containing Missing Values:

	Missing Values	Missing Percentage
company	112593	94.306893
agent	16340	13.686238
country	488	0.408744
children	4	0.003350

Total Missing Values: 129425

In [6]:
```
# Count duplicate records
duplicate_count = df.duplicated().sum()

# Calculate duplicate percentage
duplicate_percentage = (duplicate_count / len(df)) * 100

print("Total Duplicate Records:", duplicate_count)
print("Duplicate Percentage:", round(duplicate_percentage, 2), "%")

# Display duplicate records if available
if duplicate_count > 0:
    display(df[df.duplicated(keep=False)].head(10))
else:
    print("No duplicate records found.")
```

Total Duplicate Records: 31994
Duplicate Percentage: 26.8 %

	hotel	is_canceled	lead_time	arrival_date_year	arrival_date_month	arrival_date_week_n
4	Resort Hotel	0	14	2015	July	
5	Resort Hotel	0	14	2015	July	
21	Resort Hotel	0	72	2015	July	
22	Resort Hotel	0	72	2015	July	
39	Resort Hotel	0	70	2015	July	
43	Resort Hotel	0	70	2015	July	
132	Resort Hotel	1	5	2015	July	
138	Resort Hotel	1	5	2015	July	
198	Resort Hotel	0	0	2015	July	
200	Resort Hotel	0	0	2015	July	

10 rows × 32 columns

5. Missing Value Handling

Missing values can affect statistical calculations and data analysis. Therefore, it is important to handle them before proceeding with exploratory data analysis.

Based on the initial data quality assessment, missing values were identified in four columns: `company`, `agent`, `country`, and `children`.

The following strategies will be applied:

- Company: Replace missing values with 0.
- Agent: Replace missing values with 0.
- Country: Replace missing values with "Unknown".
- Children: Replace missing values with 0.

In [7]:
```
# Create a copy of the original dataset
df_clean = df.copy()
```

```
# Replace missing values
df_clean["company"] = df_clean["company"].fillna(0)
df_clean["agent"] = df_clean["agent"].fillna(0)
df_clean["country"] = df_clean["country"].fillna("Unknown")
df_clean["children"] = df_clean["children"].fillna(0)

print("Missing values handled successfully!")
```

```
Missing values handled successfully!
```

In [8]:
```
# Check missing values after treatment
remaining_missing = df_clean.isnull().sum()

print("Missing Values After Cleaning:")
print(remaining_missing[remaining_missing > 0])

print("\nTotal Remaining Missing Values:",
      df_clean.isnull().sum().sum())
```

```
Missing Values After Cleaning:
Series([], dtype: int64)

Total Remaining Missing Values: 0
```

5.1 Observations

Missing values were handled successfully in the company, agent, country, and children columns using the selected replacement strategies.

Missing company and agent identifiers were replaced with 0.

Missing country values were replaced with "Unknown".

Missing children values were replaced with 0.

After applying these treatments, the dataset was checked again to verify the remaining missing values.

6. Duplicate Records Handling

Duplicate records are rows that contain identical values across all columns in a dataset.

Duplicates can affect statistical calculations, frequency distributions, and analytical results. Therefore, identifying and handling duplicate records is an important part of data cleaning.

6.1 Identifying Duplicate Records

Before removing duplicate records, we need to identify how many exact duplicate rows are present in the dataset.

The Pandas duplicated() method identifies rows that have already appeared earlier in the dataset.

By default, the first occurrence of a record is considered unique, while subsequent identical occurrences are marked as duplicates.

In [9]:
```
# Identify duplicate records
duplicate_count = df_clean.duplicated().sum()

# Calculate duplicate percentage
duplicate_percentage = (duplicate_count / len(df_clean)) * 100

print("Total Duplicate Records:", duplicate_count)
print("Duplicate Percentage:", round(duplicate_percentage, 2), "%")

# Display sample duplicate records
duplicate_records = df_clean[df_clean.duplicated(keep=False)]

display(duplicate_records.head(10))
```

```
Total Duplicate Records: 31994
Duplicate Percentage: 26.8 %
```

	hotel	is_canceled	lead_time	arrival_date_year	arrival_date_month	arrival_date_week_n
4	Resort Hotel	0	14	2015	July	
5	Resort Hotel	0	14	2015	July	
21	Resort Hotel	0	72	2015	July	
22	Resort Hotel	0	72	2015	July	
39	Resort Hotel	0	70	2015	July	
43	Resort Hotel	0	70	2015	July	
132	Resort Hotel	1	5	2015	July	
138	Resort Hotel	1	5	2015	July	
198	Resort Hotel	0	0	2015	July	
200	Resort Hotel	0	0	2015	July	

10 rows × 32 columns

6.2 Removing Duplicate Records

After identifying duplicate records, we will remove exact duplicate rows using the Pandas drop_duplicates() method.

The keep='first' parameter retains the first occurrence of each identical record and removes subsequent occurrences.

This approach eliminates repeated rows while retaining one representative record from each duplicate group.

In [10]:
```
# Store the dataset shape before removing duplicates
rows_before = df_clean.shape[0]

# Remove exact duplicate records
df_clean = df_clean.drop_duplicates(keep="first")

# Store the dataset shape after removing duplicates
rows_after = df_clean.shape[0]
```

```
# Calculate removed records
removed_records = rows_before - rows_after

print("Rows Before Duplicate Removal:", rows_before)
print("Rows After Duplicate Removal:", rows_after)
print("Total Records Removed:", removed_records)
```

```
Rows Before Duplicate Removal: 119390
Rows After Duplicate Removal: 87396
Total Records Removed: 31994
```

In [11]:
```
# Check remaining duplicates
remaining_duplicates = df_clean.duplicated().sum()

print("Remaining Duplicate Records:", remaining_duplicates)
print("Final Dataset Shape:", df_clean.shape)

if remaining_duplicates == 0:
    print("All exact duplicate records have been removed.")
```

```
Remaining Duplicate Records: 0
Final Dataset Shape: (87396, 32)
All exact duplicate records have been removed.
```

The dataset initially contained 31,994 exact duplicate records. These records were removed using `drop_duplicates(keep="first")`, retaining one copy of each identical record.

- Original records: 119,390
- Duplicate records removed: 31,994
- Records after cleaning: 87,396
- Remaining exact duplicates: 0

The dataset now contains 87,396 rows and 32 columns. No columns were removed. Only exact duplicate rows were eliminated.

7. Save the Cleaned Dataset

After handling missing values and removing exact duplicate records, save the cleaned dataset in the `data/cleaned` folder. This file will be used for the upcoming exploratory data analysis.

In [12]:
```
df_clean.to_csv("cleaned_dataset/hotel_bookings_cleaned.csv", index=False)

print("Cleaned dataset saved successfully!")
print("Final Dataset Shape:", df_clean.shape)
```

```
Cleaned dataset saved successfully!
Final Dataset Shape: (87396, 32)
```

8 Descriptive Statistics of Numerical Columns

Descriptive statistics provide a statistical summary of numerical variables. Measures such as mean, median, standard deviation, minimum, maximum and quartiles help us understand the central tendency, spread and distribution of the data.

Identifier columns such as `agent` and `company` will be excluded from the main numerical summary because their values represent IDs rather than measurable quantities.

In [13]:
```
numerical_features = df_clean.select_dtypes(include=np.number).columns.tolist()

# Exclude identifier columns
numerical_features = [
    col for col in numerical_features
    if col not in ["agent", "company"]
]

numerical_summary = df_clean[numerical_features].describe().T

display(numerical_summary)
```

	count	mean	std	min	25%	50%	7
is_canceled	87396.0	0.274898	0.446466	0.00	0.0	0.0	
lead_time	87396.0	79.891368	86.052325	0.00	11.0	49.0	1
arrival_date_year	87396.0	2016.210296	0.686102	2015.00	2016.0	2016.0	20
arrival_date_week_number	87396.0	26.838334	13.674572	1.00	16.0	27.0	
arrival_date_day_of_month	87396.0	15.815541	8.835146	1.00	8.0	16.0	
stays_in_weekend_nights	87396.0	1.005263	1.031921	0.00	0.0	1.0	
stays_in_week_nights	87396.0	2.625395	2.053584	0.00	1.0	2.0	
adults	87396.0	1.875795	0.626500	0.00	2.0	2.0	
children	87396.0	0.138633	0.455871	0.00	0.0	0.0	
babies	87396.0	0.010824	0.113597	0.00	0.0	0.0	
is_repeated_guest	87396.0	0.039075	0.193775	0.00	0.0	0.0	
previous_cancellations	87396.0	0.030413	0.369145	0.00	0.0	0.0	
previous_bookings_not_canceled	87396.0	0.183990	1.731894	0.00	0.0	0.0	
booking_changes	87396.0	0.271603	0.727245	0.00	0.0	0.0	
days_in_waiting_list	87396.0	0.749565	10.015731	0.00	0.0	0.0	
adr	87396.0	106.337246	55.013953	-6.38	72.0	98.1	1
required_car_parking_spaces	87396.0	0.084226	0.281533	0.00	0.0	0.0	
total_of_special_requests	87396.0	0.698567	0.831946	0.00	0.0	0.0	

Interpretation of Numerical Descriptive Statistics

1. Booking cancellations: The mean of `is_canceled` is approximately 0.275, indicating that around 27.49% of bookings in the cleaned dataset were canceled.
2. Lead time: The average lead time is approximately 79.89 days, while the median is 49 days. This indicates that the distribution is right-skewed, with some bookings made much earlier than others.
3. Stay duration: Guests stay an average of approximately 1 weekend night and 2.63 weekday nights. The median weekday stay is 2 nights.
4. Guest composition: The average number of adults is approximately 1.88 per booking. The median values for children and babies are both zero, suggesting that most bookings do not include children or babies.
5. Repeated guests: The mean of `is_repeated_guest` is approximately 0.039, suggesting that around 3.91% of bookings belong to repeated guests.
6. Special requests: The average number of special requests is approximately 0.70 per booking, while the median is zero.
7. Potential outliers: Some variables have unusually high maximum values, such as `lead_time` (737), `adults` (55), `adr` (5400), and `days_in_waiting_list` (391). The negative minimum ADR value (-6.38) also requires investigation.

These unusual values will be examined further during outlier analysis rather than removed without investigation.

8.1 Descriptive Statistics of Categorical Columns

Categorical descriptive statistics help us understand the different categories present in the dataset.

We will examine:

- Count: Total non-null records
- Unique: Number of distinct categories
- Top: Most frequently occurring category
- Freq: Frequency of the most common category

In [14]:
```
categorical_features = df_clean.select_dtypes(include="object").columns.tolist()

categorical_summary = df_clean[categorical_features].describe().T

display(categorical_summary)
```

	count	unique	top	freq
hotel	87396	2	City Hotel	53428
arrival_date_month	87396	12	August	11257
meal	87396	5	BB	67978
country	87396	178	PRT	27453
market_segment	87396	8	Online TA	51618
distribution_channel	87396	5	TA/TO	69141
reserved_room_type	87396	10	A	56552
assigned_room_type	87396	12	A	46313
deposit_type	87396	3	No Deposit	86251
customer_type	87396	4	Transient	71986
reservation_status	87396	3	Check-Out	63371
reservation_status_date	87396	926	2016-02-14	211

Interpretation of Categorical Descriptive Statistics

1. Hotel type: City Hotel is the most frequent hotel type, with 53,428 records out of 87,396.
2. Arrival month: August is the most frequently recorded arrival month, with 11,257 bookings.
3. Meal plan: BB is the most common meal plan, appearing in 67,978 records.
4. Country: PRT (Portugal) is the most frequently recorded country, with 27,453 records.
5. Market segment: Online TA (Online Travel Agents) is the most common market segment, with 51,618 records.
6. Distribution channel: TA/TO (Travel Agents/Tour Operators) is the most frequent distribution channel, with 69,141 records.
7. Room type: Room type A is the most frequently reserved room type, with 56,552 records. It is also the most frequently assigned room type, with 46,313 records.
8. Deposit type: No Deposit is the dominant deposit category, appearing in 86,251 records.
9. Customer type: Transient customers are the most frequent customer type, with 71,986 records.

10. Reservation status: Check-Out is the most common reservation status, with 63,371 records.

Overall, the dataset contains a strong concentration of City Hotel bookings, online travel-agent bookings, and transient customers.

9. Data Visualization – Univariate Analysis

9.1 Distribution of Numerical Features

Histograms show the frequency distribution of numerical variables, while Kernel Density Estimation (KDE) curves provide a smoothed representation of the distribution.

We will visualize selected numerical features, including lead time, average daily rate (ADR), stay duration, waiting-list days, and special requests. These variables can help us understand booking patterns and guest behavior.

In [15]:
```
import os

features_to_plot = [
    "lead_time",
    "adr",
    "stays_in_weekend_nights",
    "stays_in_week_nights",
    "days_in_waiting_list",
    "total_of_special_requests"
]

os.makedirs("outputs/charts", exist_ok=True)

fig, axes = plt.subplots(3, 2, figsize=(15, 15))

for feature, ax in zip(features_to_plot, axes.flatten()):
    sns.histplot(
        data=df_clean,
        x=feature,
        kde=True,
        ax=ax
    )
    ax.set_title(f"Distribution of {feature}")
    ax.set_xlabel(feature)
    ax.set_ylabel("Frequency")

plt.tight_layout()
plt.savefig("outputs/charts/numerical_distributions.png", dpi=300)
plt.show()
```



10. Correlation Analysis

Correlation analysis helps us understand the strength and direction of relationships between numerical variables.

We use the Pearson correlation coefficient, which ranges from -1 to +1.

In [16]:
```
# Select numerical columns
numeric_cols = df_clean.select_dtypes(include="number").columns.tolist()

# Remove identifier columns because IDs are not meaningful numerical measurements
numeric_cols = [
    col for col in numeric_cols
    if col not in ["agent", "company"]
]

# Calculate correlation matrix
```

```
correlation_matrix = df_clean[numeric_cols].corr(method="pearson")

# Display correlation matrix
correlation_matrix
```

Out[16]:

	is_canceled	lead_time	arrival_date_year	arrival_date_week_
is_canceled	1.000000	0.184806	0.088030	
lead_time	0.184806	1.000000	0.139135	
arrival_date_year	0.088030	0.139135	1.000000	-(
arrival_date_week_number	0.001443	0.101150	-0.514228	
arrival_date_day_of_month	0.005328	0.009866	-0.010023	
stays_in_weekend_nights	0.060191	0.235145	0.005144	
stays_in_week_nights	0.082928	0.310129	0.003645	
adults	0.081816	0.140493	0.038619	
children	0.067369	0.028650	0.041158	
babies	-0.020543	-0.003614	-0.023334	
is_repeated_guest	-0.089643	-0.147003	0.024343	-(
previous_cancellations	0.051468	0.005375	-0.054212	
previous_bookings_not_canceled	-0.052154	-0.078931	0.027256	-(
booking_changes	-0.093644	0.077028	0.008604	
days_in_waiting_list	0.004464	0.132152	-0.027939	
adr	0.127986	0.023564	0.176088	
required_car_parking_spaces	-0.184206	-0.086541	-0.039807	
total_of_special_requests	-0.120545	0.034240	0.064268	

Correlation Heatmap

A correlation heatmap provides a visual representation of relationships between numerical variables.

Positive correlations indicate variables moving in the same direction, while negative correlations indicate variables moving in opposite directions.

In [17]:

```
plt.figure(figsize=(16, 12))

sns.heatmap(
    correlation_matrix,
    annot=True,
```

```
    cmap="coolwarm",
    fmt=".2f",
    linewidths=0.5,
    center=0
)

plt.title("Correlation Heatmap - Hotel Booking Dataset")
plt.tight_layout()

plt.savefig(
    "../outputs/charts/correlation_heatmap.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



In [18]:
```
# Convert correlation matrix into pairs
correlation_pairs = correlation_matrix.unstack()

# Remove self-correlations and duplicate pairs
correlation_pairs = correlation_pairs[
    correlation_pairs.index.get_level_values(0) <
    correlation_pairs.index.get_level_values(1)
]
```

```
# Sort by absolute correlation
strongest_correlations = correlation_pairs.reindex(
    correlation_pairs.abs().sort_values(ascending=False).index
)

# Display top 10 relationships
strongest_correlations.head(10)
```

Out[18]:

```
stays_in_week_nights            stays_in_weekend_nights          0.555552
arrival_date_week_number        arrival_date_year               -0.514228
is_repeated_guest               previous_bookings_not_canceled   0.441456
previous_bookings_not_canceled  previous_cancellations            0.392064
adr                             children                         0.326293
lead_time                       stays_in_week_nights             0.310129
adr                             adults                           0.248999
lead_time                       stays_in_weekend_nights          0.235145
is_repeated_guest               previous_cancellations           0.206374
is_canceled                     lead_time                        0.184806
dtype: float64
```

Interpretation

1. The strongest positive correlation was observed between `stays_in_week_nights` and `stays_in_weekend_nights` (0.56). This indicates that guests staying longer during weekdays also tend to stay longer during weekends.

2. The strongest negative correlation was observed between `arrival_date_week_number` and `arrival_date_year` (-0.51). This indicates a moderate negative relationship between these variables, although it may be influenced by the distribution of booking dates across different years.

3. A moderate positive correlation (0.44) was observed between `is_repeated_guest` and `previous_bookings_not_canceled`, suggesting that repeat guests tend to have a history of bookings that were not canceled.

4. A weak positive correlation (0.18) was observed between `is_canceled` and `lead_time`, suggesting that bookings made further in advance have a slightly higher tendency to be canceled.

5. Most variable pairs do not show very strong linear relationships, indicating that hotel booking patterns are influenced by multiple factors.

11. Box Plot Analysis

Box plots help visualize the distribution of numerical variables and identify potential outliers.

In this analysis, we compare booking characteristics between City Hotel and Resort Hotel to understand differences in booking patterns and identify unusual observations.

In [19]:
```
# Features to compare across hotel types
features = [
    "lead_time",
    "adr",
    "stays_in_week_nights",
    "stays_in_weekend_nights"
]

# Create output directory
os.makedirs("../outputs/charts", exist_ok=True)

# Create 2x2 subplot layout
fig, axes = plt.subplots(2, 2, figsize=(16, 12))

for feature, ax in zip(features, axes.flatten()):
    sns.boxplot(
        data=df_clean,
        x="hotel",
        y=feature,
        ax=ax
    )

    ax.set_title(f"{feature} by Hotel Type")
    ax.set_xlabel("Hotel Type")
    ax.set_ylabel(feature)

plt.suptitle(
    "Box Plot Analysis: City Hotel vs Resort Hotel",
    fontsize=16
)

plt.tight_layout()

plt.savefig(
    "../outputs/charts/boxplots_by_hotel.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



In [20]:
```
outlier_results = []

for feature in features:

    for hotel_type in df_clean["hotel"].dropna().unique():

        data = df_clean.loc[
            df_clean["hotel"] == hotel_type,
            feature
        ].dropna()

        Q1 = data.quantile(0.25)
        Q3 = data.quantile(0.75)

        IQR = Q3 - Q1

        lower_limit = Q1 - 1.5 * IQR
        upper_limit = Q3 + 1.5 * IQR

        outliers = data[
            (data < lower_limit) |
            (data > upper_limit)
        ]

        outlier_results.append({
            "Feature": feature,
            "Hotel": hotel_type,
            "Outlier Count": len(outliers),
```

```
            "Outlier Percentage": round(
                len(outliers) / len(data) * 100, 2
            )
        })

outlier_summary = pd.DataFrame(outlier_results)

outlier_summary
```

Out[20]:

	Feature	Hotel	Outlier Count	Outlier Percentage
0	lead_time	Resort Hotel	606	1.78
1	lead_time	City Hotel	1697	3.18
2	adr	Resort Hotel	753	2.22
3	adr	City Hotel	2490	4.66
4	stays_in_week_nights	Resort Hotel	179	0.53
5	stays_in_week_nights	City Hotel	687	1.29
6	stays_in_weekend_nights	Resort Hotel	140	0.41
7	stays_in_weekend_nights	City Hotel	80	0.15

Interpretation

1. The box plots show differences in the distribution of booking characteristics between City Hotel and Resort Hotel.
2. The median values indicate the typical booking characteristics for each hotel type.
3. Potential outliers were identified using the IQR method. These values represent observations outside the expected range.
4. Outlier percentages help identify which numerical features contain more unusual observations.
5. Outliers will not be removed automatically because they may represent genuine booking behavior.

In [21]:

```
# Investigate unusually high ADR values
df_clean.nlargest(
    10, "adr"
)[["hotel", "adr", "adults", "children", "babies"]]
```

Out[21]:

	hotel	adr	adults	children	babies
48515	City Hotel	5400.00	2	0.0	0
111403	City Hotel	510.00	1	0.0	0
15083	Resort Hotel	508.00	2	0.0	0
103912	City Hotel	451.50	2	2.0	0
13142	Resort Hotel	450.00	2	0.0	0
13391	Resort Hotel	437.00	2	2.0	0
39155	Resort Hotel	426.25	2	2.0	0
39568	Resort Hotel	402.00	3	1.0	0
39118	Resort Hotel	397.38	3	2.0	0
13323	Resort Hotel	392.00	2	1.0	0

In [22]:
```
# Inspect the booking with the highest ADR
df_clean.loc[
    df_clean["adr"].idxmax()
].to_frame()
```

Out[22]:

	48515
hotel	City Hotel
is_canceled	1
lead_time	35
arrival_date_year	2016
arrival_date_month	March
arrival_date_week_number	13
arrival_date_day_of_month	25
stays_in_weekend_nights	0
stays_in_week_nights	1
adults	2
children	0.0
babies	0
meal	BB
country	PRT
market_segment	Offline TA/TO
distribution_channel	TA/TO
is_repeated_guest	0
previous_cancellations	0
previous_bookings_not_canceled	0
reserved_room_type	A
assigned_room_type	A
booking_changes	1
deposit_type	Non Refund
agent	12.0
company	0.0
days_in_waiting_list	0
customer_type	Transient
adr	5400.0
required_car_parking_spaces	0
total_of_special_requests	0

	48515
reservation_status	Canceled
reservation_status_date	2016-02-19

Additional Outlier Investigation – ADR

During the investigation of the highest ADR values, an unusually high ADR of 5400 was identified in a City Hotel booking.

The next highest values were considerably lower, indicating that the maximum value requires further investigation.

The record was not removed automatically because extreme values may represent genuine booking observations. Additional booking details will be examined to determine whether the value is valid or a potential data-quality issue.

ADR Outlier Investigation – Findings

An unusually high ADR value of 5400 was identified in a City Hotel booking.

Further investigation revealed that the booking involved two adults staying for one weekday night. The reservation was canceled before the scheduled arrival date.

This observation is significantly higher than other ADR values in the dataset and may represent a potential data-quality anomaly.

However, the record was retained because there is insufficient evidence to confirm that it is incorrect.

12. Time-Series Analysis

Time-series analysis helps identify booking trends and seasonal patterns over different months and years.

In this analysis, we examine monthly booking volumes and cancellation rates using arrival dates.

In [23]:
```
# Create arrival date column
df_clean["arrival_date"] = pd.to_datetime(
    df_clean["arrival_date_year"].astype(str) + "-" +
    df_clean["arrival_date_month"] + "-" +
    df_clean["arrival_date_day_of_month"].astype(str),
    format="%Y-%B-%d",
    errors="coerce"
)
```

```
# Check the new column
df_clean[["arrival_date", "arrival_date_year",
          "arrival_date_month"]].head()
```

Out[23]:

	arrival_date	arrival_date_year	arrival_date_month
0	2015-07-01	2015	July
1	2015-07-01	2015	July
2	2015-07-01	2015	July
3	2015-07-01	2015	July
4	2015-07-01	2015	July

Monthly Booking Trends

This analysis examines the number of hotel bookings received during each month across the available years.

In [24]:

```
# Extract year and month
df_clean["year_month"] = (
    df_clean["arrival_date"].dt.to_period("M")
)

# Calculate monthly bookings
monthly_bookings = (
    df_clean.groupby("year_month")
    .size()
    .reset_index(name="total_bookings")
)

# Convert period to datetime for plotting
monthly_bookings["year_month"] = (
    monthly_bookings["year_month"].dt.to_timestamp()
)

monthly_bookings.head()
```

Out[24]:

	year_month	total_bookings
0	2015-07-01	1674
1	2015-08-01	2453
2	2015-09-01	2839
3	2015-10-01	2700
4	2015-11-01	1665

In [25]:
```
plt.figure(figsize=(15, 6))

sns.lineplot(
    data=monthly_bookings,
    x="year_month",
    y="total_bookings",
    marker="o"
)

plt.title("Monthly Hotel Booking Trends")
plt.xlabel("Month")
plt.ylabel("Number of Bookings")
plt.xticks(rotation=45)

plt.tight_layout()

plt.savefig(
    "../outputs/charts/monthly_booking_trends.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```

1. Monthly Hotel Booking Trends

The first line chart tracks the total volume of monthly hotel bookings over a multi-year period stretching from mid-2015 to mid-2017.

Key Observations

• Overall Growth Trajectory: The dataset showcases a strong macro-upward trend. Total bookings started around 2,500 in mid-2015 and surged to peaks well above 4,500 by mid-2017. • Cyclical Seasonality: Clear seasonal patterns emerge with bookings consistently plunging during the winter months (dipping near or below 2,500 around January 2016 and January 2017) and peaking during warmer summer intervals. • Peak Booking Windows: Major

volume surges occurred during late summer 2016 and reached their highest historical levels around May/July 2017.

In [27]:
```
monthly_cancellations = (
    df_clean.groupby("year_month")
    .agg(
        total_bookings=("is_canceled", "count"),
        canceled_bookings=("is_canceled", "sum")
    )
    .reset_index()
)

monthly_cancellations["cancellation_rate"] = (
    monthly_cancellations["canceled_bookings"] /
    monthly_cancellations["total_bookings"] * 100
)

monthly_cancellations.head()
```

Out[27]:

	year_month	total_bookings	canceled_bookings	cancellation_rate
0	2015-07	1674	512	30.585424
1	2015-08	2453	571	23.277619
2	2015-09	2839	566	19.936597
3	2015-10	2700	440	16.296296
4	2015-11	1665	243	14.594595

In [28]:
```
plt.figure(figsize=(15, 6))

sns.lineplot(
    data=monthly_cancellations,
    x="year_month",
    y="cancellation_rate",
    marker="o"
)

plt.title("Monthly Hotel Cancellation Rate")
plt.xlabel("Month")
plt.ylabel("Cancellation Rate (%)")
plt.xticks(rotation=45)

plt.tight_layout()

plt.savefig(
    "../outputs/charts/monthly_cancellation_rate.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



2. Monthly Hotel Cancellation Rate

The second line chart tracks the percentage of bookings canceled each month across the exact same timeline.

Key Observations

• Correlated Volatility: Cancellations fluctuated dynamically between roughly 15% and over 40%. • The 2015 Drop & Recovery: The cancellation rate saw a sharp initial decline from mid-2015 down to its lowest historical floor (around 15%) near January 2016. From that point onward, the rate steadily climbed back up. • Upward Trend in Rejections: By late 2016 and moving into 2017, the baseline cancellation rate shifted upward, culminating in an all-time high of over 40% near the end of the observed timeline in mid-2017.

13. Group-by Analysis

Group-by analysis helps us compare booking patterns across different categorical variables.

In this section, we analyze booking volumes and cancellation rates across hotel types, market segments, customer types, and distribution channels.

In [29]:
```
# Booking count by hotel type

hotel_bookings = (
    df_clean.groupby("hotel")
    .size()
    .reset_index(name="total_bookings")
    .sort_values("total_bookings", ascending=False)
)

hotel_bookings
```

Out[29]:

	hotel	total_bookings
0	City Hotel	53428
1	Resort Hotel	33968

In [30]:
```
plt.figure(figsize=(8, 5))

sns.barplot(
    data=hotel_bookings,
    x="hotel",
    y="total_bookings"
)

plt.title("Total Bookings by Hotel Type")
plt.xlabel("Hotel Type")
plt.ylabel("Total Bookings")

plt.tight_layout()

plt.savefig(
    "../outputs/charts/bookings_by_hotel.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



In [31]:
```
market_cancellation = (
    df_clean.groupby("market_segment")
    .agg(
        total_bookings=("is_canceled", "count"),
```

```
        canceled_bookings=("is_canceled", "sum")
    )
    .reset_index()
)

market_cancellation["cancellation_rate"] = (
    market_cancellation["canceled_bookings"] /
    market_cancellation["total_bookings"] * 100
)

market_cancellation = market_cancellation.sort_values(
    "cancellation_rate",
    ascending=False
)

market_cancellation
```

Out[31]:

	market_segment	total_bookings	canceled_bookings	cancellation_rate
7	Undefined	2	2	100.000000
6	Online TA	51618	18245	35.346197
4	Groups	4942	1335	27.013355
0	Aviation	227	45	19.823789
5	Offline TA/TO	13889	2063	14.853481
3	Direct	11804	1737	14.715351
1	Complementary	702	88	12.535613
2	Corporate	4212	510	12.108262

Key Observations

• The Online TA Risk: Online Travel Agencies represent the single biggest segment by a massive margin (51,618 bookings). However, they also suffer from a highly severe cancellation rate of 35.35%. Over a third of your main revenue pipeline falls through. • Groups and Volatility: Group bookings show the second highest structured cancellation rate at 27.01%. When groups cancel, it leaves large blocks of rooms empty simultaneously, creating a distinct revenue management risk. • Stable Channels: Direct bookings and Corporate accounts demonstrate excellent stability, maintaining low cancellation rates between 12% and 15%.

In [32]:

```
plt.figure(figsize=(11, 6))

sns.barplot(
    data=market_cancellation,
    x="market_segment",
    y="cancellation_rate"
)
```

```
plt.title("Cancellation Rate by Market Segment")
plt.xlabel("Market Segment")
plt.ylabel("Cancellation Rate (%)")
plt.xticks(rotation=30)

plt.tight_layout()

plt.savefig(
    "../outputs/charts/cancellation_by_market_segment.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



In [33]:
```
customer_analysis = (
    df_clean.groupby("customer_type")
    .agg(
        total_bookings=("is_canceled", "count"),
        canceled_bookings=("is_canceled", "sum")
    )
    .reset_index()
)

customer_analysis["cancellation_rate"] = (
    customer_analysis["canceled_bookings"] /
    customer_analysis["total_bookings"] * 100
)

customer_analysis.sort_values(
    "total_bookings",
    ascending=False
)
```

Out[33]:

	customer_type	total_bookings	canceled_bookings	cancellation_rate
2	Transient	71986	21672	30.105854
3	Transient-Party	11727	1787	15.238339
0	Contract	3139	512	16.310927
1	Group	544	54	9.926471

Key Observations

• Transient Dominance: Standard "Transient" customers (independent, individual travelers) make up the overwhelming majority of your customer base (71,986 bookings). They also cancel at a high rate of 30.11%. • Transient-Party vs. Transient: Interestingly, when transient customers book as part of a package or party (Transient-Party), their cancellation rate drops by half down to 15.24%, indicating significantly stronger commitment.

In [34]:

```
channel_analysis = (
    df_clean.groupby("distribution_channel")
    .agg(
        total_bookings=("is_canceled", "count"),
        canceled_bookings=("is_canceled", "sum")
    )
    .reset_index()
)

channel_analysis["cancellation_rate"] = (
    channel_analysis["canceled_bookings"] /
    channel_analysis["total_bookings"] * 100
)

channel_analysis.sort_values(
    "total_bookings",
    ascending=False
)
```

Out[34]:

	distribution_channel	total_bookings	canceled_bookings	cancellation_rate
3	TA/TO	69141	21412	30.968600
1	Direct	12988	1925	14.821374
0	Corporate	5081	648	12.753395
2	GDS	181	36	19.889503
4	Undefined	5	4	80.000000

Key Observations

• TA/TO Dependency: The hotel relies heavily on Third-Party intermediaries (TA/TO) for 69,141 bookings. This reliance introduces major volatility with a 30.97% cancellation rate, likely driven by easy "free cancellation" terms offered on modern booking apps. • Direct Channel Value: Direct bookings are vastly superior in terms of reliability, holding steady at a low 14.82% cancellation rate.

14. Scatter Plot Analysis

Scatter plots help identify relationships, patterns, clusters, and unusual observations between two numerical variables.

In this section, we explore relationships between booking lead time, average daily rate, and length of stay.

14.1 Scatter plot: Lead time vs ADR

In [35]:
```
plt.figure(figsize=(10, 6))

sns.scatterplot(
    data=df_clean,
    x="lead_time",
    y="adr",
    alpha=0.3
)

plt.title("Lead Time vs Average Daily Rate")
plt.xlabel("Lead Time (Days)")
plt.ylabel("ADR")

plt.tight_layout()

plt.savefig(
    "../outputs/charts/lead_time_vs_adr.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



Interpretation

1. Lead Time vs ADR

The scatter plot shows that ADR values are widely distributed across different lead times. There is no clear pattern indicating that bookings made earlier have higher or lower daily rates. This suggests that booking lead time does not have a noticeable relationship with the average daily rate.

14.2 Scatter plot: Weeknight stays vs ADR

In [36]:
```
plt.figure(figsize=(10, 6))

sns.scatterplot(
    data=df_clean,
    x="stays_in_week_nights",
    y="adr",
    alpha=0.3
)

plt.title("Weeknight Stays vs ADR")
plt.xlabel("Weeknight Stays")
plt.ylabel("ADR")

plt.tight_layout()

plt.savefig(
    "../outputs/charts/weeknight_stays_vs_adr.png",
    dpi=300,
    bbox_inches="tight"
```

```
)

plt.show()
```



Interpretation

2. Weeknight Stays vs ADR

The scatter plot shows that ADR varies across different weekday stay durations. However, there is no strong visible pattern between the number of weeknight stays and ADR. This indicates that guests staying for more weekdays do not necessarily pay higher daily rates.

14.3 Scatter plot: Weekend stays vs Weeknight stays

In [ ]:
```
plt.figure(figsize=(10, 6))

sns.scatterplot(
    data=df_clean,
    x="stays_in_weekend_nights",
    y="stays_in_week_nights",
    alpha=0.3
)

plt.title("Weekend Stays vs Weeknight Stays")
plt.xlabel("Weekend Nights")
plt.ylabel("Weeknight Nights")

plt.tight_layout()

plt.savefig(
```

```
    "../outputs/charts/weekend_vs_weeknight_stays.png",
    dpi=300,
    bbox_inches="tight"
)

plt.show()
```



Interpretation

3. Weekend Stays vs Weeknight Stays

The scatter plot shows a positive relationship between weekend and weeknight stays. Guests who stay for more weekend nights generally also tend to stay for more weeknights. Most bookings are concentrated around shorter stay durations, with fewer bookings involving longer stays.

Key Findings and Data-Driven Insights

1. Guest Stay Duration

The analysis found a moderate positive relationship between weeknight stays and weekend stays (approximately 0.56). Guests who stay for more weekend nights generally tend to stay for more weeknights as well.

Business Recommendation: Hotels can use guest stay-duration patterns to improve room availability, staffing, and resource allocation.

2. Booking Lead Time and Cancellation

The correlation between lead time and cancellations was approximately 0.18, indicating a weak positive relationship. This suggests that bookings made further in advance are slightly more likely to be associated with cancellations.

Business Recommendation: Hotels can monitor bookings with longer lead times and consider sending booking reminders or offering suitable confirmation policies to reduce cancellation risks.

3. Differences in Potential Outliers Between Hotels

City Hotels had higher potential outlier percentages than Resort Hotels for lead time (3.18% vs. 1.78%), ADR (4.66% vs. 2.22%), and weeknight stays (1.29% vs. 0.53%). Resort Hotels had a slightly higher percentage of weekend-stay outliers (0.41% vs. 0.15%).

Business Recommendation: Hotels should monitor unusual booking durations, lead times, and room rates separately for each hotel type to identify unusual booking patterns and maintain data quality.

4. Relationship Between ADR and Booking Behaviour

The scatter plots showed no clear relationship between ADR and lead time or between ADR and weekday stay duration.

Business Recommendation: Hotels should consider additional factors, such as customer type, seasonality, and market segment, when reviewing room pricing strategies rather than relying only on booking lead time or stay duration.

Overall Finding

The analysis highlights differences in guest booking behaviour, stay duration, and potential outliers between hotel types. These findings can help hotel management improve booking management, room allocation, pricing reviews, and operational planning.

Conclusion and Business Recommendations

Conclusion

The exploratory data analysis of the Hotel Booking Demand dataset provided useful insights into hotel booking patterns, customer behaviour, cancellation trends, room pricing, and stay durations.

The analysis revealed that City Hotels and Resort Hotels have differences in booking characteristics and potential outlier patterns. A moderate positive relationship was observed between weekend and weeknight stays, while ADR showed no clear relationship with lead

time or weekday stay duration. The analysis also highlighted unusual ADR values that require further investigation.

Overall, the findings help understand customer booking behaviour and identify areas where hotel management can improve operational efficiency and decision-making.

Business Recommendations

1. Improve Cancellation Management: Monitor cancellation rates across different market segments and distribution channels. Hotels can review booking confirmation processes and consider reminders for bookings made well in advance.
2. Optimize Room and Resource Allocation: Use monthly booking trends and guest stay-duration patterns to plan room availability, housekeeping schedules, and staff requirements more effectively.
3. Review Pricing Strategies: Analyze ADR across hotel types, customer segments, and seasons to identify opportunities for better pricing decisions. Avoid relying on lead time or stay duration alone when setting room rates.
4. Improve Data Quality: Investigate unusual ADR values, negative rates, and extreme booking durations before using the data for business reporting or pricing decisions.
5. Understand Customer Behaviour: Study booking patterns across customer types and distribution channels to develop targeted marketing strategies and improve the guest experience.

Final Summary

This analysis demonstrates how exploratory data analysis can transform raw hotel booking data into meaningful business insights. By monitoring cancellations, understanding customer preferences, improving resource planning, and reviewing pricing patterns,