



Unit1-
Slides

CSO322: Theory of Computation

Unit-1: Formal Languages and Finite Automata

Dr. Lavanya Selvaganesh

Dr. Lavanya Selvaganesh CSO322 1/46

Formal Languages

Definition

Let Σ be an alphabet. Let Σ^* be the set of all strings over Σ . A language is a subset of Σ^* .

Σ^*

Dr. Lavanya Selvaganesh CSO322 2/46

Formal Languages

Definition

Let Σ be an alphabet. Let Σ^* be the set of all strings over Σ . A language is a subset of Σ^* .

Example

Let $\Sigma = \{a, b\}$. $\Sigma^* = \{\epsilon, a, b, aa, bb, ab, ba, aaa, \dots\}$.

Examples of languages over Σ are

① $L_1 = \{\epsilon, a, aa, aab\} \subset \Sigma^*$

Formal Languages

Definition

Let Σ be an alphabet. Let Σ^* be the set of all strings over Σ . A language is a subset of Σ^* .

Example

Let $\Sigma = \{a, b\}$. $\Sigma^* = \{\epsilon, a, b, aa, bb, ab, ba, aaa, \dots\}$.

Examples of languages over Σ are

① $L_1 = \{\epsilon, a, aa, aab\}$.

② $L_2 = \{x \in \Sigma^* : |x| \leq 8\}$.

length of

Formal Languages

Definition

Let Σ be an alphabet. Let Σ^* be the set of all strings over Σ . A language is a subset of Σ^* .

Example

Let $\Sigma = \{a, b\}$. $\Sigma^* = \{\epsilon, a, b, aa, bb, ab, ba, aaa, \dots\}$.

Examples of languages over Σ are

① $L_1 = \{\epsilon, a, aa, aab\}$.

② $L_2 = \{x \in \Sigma^* : |x| \leq 8\}$.

③ $L_3 = \{x \in \Sigma^* : n_a(x) \geq n_b(x)\}$ where n_a and n_b are the number of a 's and b 's in x respectively.

a, aa, ab, ba, aab, aba, ...

Formal Languages

Definition

Let Σ be an alphabet. Let Σ^* be the set of all strings over Σ . A language is a subset of Σ^* .

Example

Let $\Sigma = \{a, b\}$. $\Sigma^* = \{\epsilon, a, b, aa, bb, ab, ba, aaa, \dots\}$.

Examples of languages over Σ are

① $L_1 = \{\epsilon, a, aa, aab\}$.

② $L_2 = \{x \in \Sigma^* : |x| \leq 8\}$.

③ $L_3 = \{x \in \Sigma^* : n_a(x) \geq n_b(x)\}$ where n_a and n_b are the number of a 's and b 's in x respectively.

④ $L_4 = \{x \in \Sigma^* : |x| \geq 2 \text{ and } x \text{ begins and ends with } b\}$

Formal Languages

- ① New languages can be constructed using set operations, since languages are sets of strings.

Formal Languages

1 New languages can be constructed using set operations, since languages are sets of strings.

- For any two languages over an alphabet Σ , their union, intersection and difference are also languages over Σ .

Formal Languages

1 New languages can be constructed using set operations, since languages are sets of strings.

- For any two languages over an alphabet Σ , their union, intersection and difference are also languages over Σ .
- Complement of a language over Σ is defined by $L' = \Sigma^* - L$.

Formal Languages

1 New languages can be constructed using set operations, since languages are sets of strings.

- For any two languages over an alphabet Σ , their union, intersection and difference are also languages over Σ .
- Complement of a language over Σ is defined by $L' = \Sigma^* - L$.
- Suppose $L_1 \subseteq \Sigma_1^*$ and $L_2 \subseteq \Sigma_2^*$, then L_1 and L_2 are languages over $(\Sigma_1 \cup \Sigma_2)^*$ i.e.

$$L_1, L_2 \subseteq (\Sigma_1 \cup \Sigma_2)^*$$

$$\Sigma^* \subseteq (\Sigma_1 \cup \Sigma_2)^*$$

Formal Languages

1 New languages can be constructed using set operations, since languages are sets of strings.

- ▶ For any two languages over an alphabet Σ , their union, intersection and difference are also languages over Σ .
- ▶ Complement of a language over Σ is defined by $L' = \Sigma^* - L$.
- ▶ Suppose $L_1 \subseteq \Sigma_1^*$ and $L_2 \subseteq \Sigma_2^*$, then L_1 and L_2 are languages over $(\Sigma_1 \cup \Sigma_2)^*$ i.e.

$$L_1, L_2 \subseteq (\Sigma_1 \cup \Sigma_2)^*$$

- ▶ **However**, there is a possibility for complement of L_1 to be either

$$L_1 = \Sigma_1^* - L_1 \text{ or } L_1' = (\Sigma_1 \cup \Sigma_2)^* - L_1.$$

Depending on the context, it will be clear which alphabet is referred to.

Formal Languages

2 Concatenation operation on strings will allow us to construct new languages.

Formal Languages

2 Concatenation operation on strings will allow us to construct new languages.

- ▶ If x and y are elements of Σ^* , the concatenation of x and y is the string xy formed by writing the symbols of x followed by symbols of y .

$$\Sigma = \{a, b\} \quad \left. \begin{array}{l} x = aab \\ y = bab \end{array} \right\} \quad \begin{array}{l} xy = aabbab \\ yx = bab aab \end{array}$$

$xy \neq yx$.

Formal Languages

2 Concatenation operation on strings will allow us to construct new languages.

- ▶ If x and y are elements of Σ^* , the concatenation of x and y is the string xy formed by writing the symbols of x followed by symbols of y .

Example

If $x = abb$ and $y = ba$, then $xy = abbba$ and $yx = baabb$.

Formal Languages

2 Concatenation operation on strings will allow us to construct new languages.

- ▶ If x and y are elements of Σ^* , the concatenation of x and y is the string xy formed by writing the symbols of x followed by symbols of y .

Example

If $x = abb$ and $y = ba$, then $xy = abbba$ and $yx = baabb$.

- ▶ For any string x , $x\epsilon = \epsilon x = x$.

ϵ - empty string. lang. cont.
 $\epsilon \in \Sigma^*$, $L = \{\epsilon\}$ - empty string.
 $L = \emptyset$ - empty language

Formal Languages

2 Concatenation operation on strings will allow us to construct new languages.

- ▶ If x and y are elements of Σ^* , the concatenation of x and y is the string xy formed by writing the symbols of x followed by symbols of y .

Example

If $x = abb$ and $y = ba$, then $xy = abbba$ and $yx = baabb$.

- ▶ For any string x , $x\epsilon = \epsilon x = x$.
- ▶ For strings x, y, z ; $(xy)z = x(yz)$
i.e. concatenation is associative.

$(xy)z$ or $x(yz)$.

$$x\epsilon = \epsilon x = x.$$

Formal Languages

3 Substring of a string

- ▶ x is a substring of another string y , if there are strings w and z , either or both may be null, so that $y = wxz$.

Formal Languages

Substring of a string

- x is a substring of another string y , if there are strings w and z , either or both may be null, so that $y = wxz$.

Example

The string "car" is a substring of "descartes", "vicar", "cartridge" and "car", but not a substring of "charity".

Formal Languages

Substring of a string

- x is a substring of another string y , if there are strings w and z , either or both may be null, so that $y = wxz$.

Example

The string "car" is a substring of "descartes", "vicar", "cartridge" and "car", but not a substring of "charity".

- A **prefix** of a string is an initial substring.
Example - Prefixes of abaa - ϵ , a, ab, aba, abaa.

Formal Languages

Substring of a string

- x is a substring of another string y , if there are strings w and z , either or both may be null, so that $y = wxz$.

Example

The string "car" is a substring of "descartes", "vicar", "cartridge" and "car", but not a substring of "charity".

- A **prefix** of a string is an initial substring.
Example - Prefixes of abaa - ϵ , a, ab, aba, abaa.
- A **suffix** of a string is a final substring.
Example - Suffixes of abaa - ϵ , a, aa, baa, abaa.

Formal Languages

Concatenation of languages is also possible.

► If $L_1, L_2 \subseteq \Sigma^*$, $L_1 L_2 = \{xy \mid x \in L_1, y \in L_2\}$

Formal Languages

⑤

Concatenation of languages is also possible.

► If $L_1, L_2 \subseteq \Sigma^*$, $L_1 L_2 = \{xy \mid x \in L_1, y \in L_2\}$

Example

$L_1 = \{001, 011\}$,

$L_2 = \{011, 10, 110\}$

$L_1 L_2 = \{001011, 00110, 001110, 011011, 01110, 011110, 011111, 0111110\}$

is the concatenation of L_1 and L_2 .

► Concatenation of L with $\{\epsilon\}$: $L\{\epsilon\} = \{\epsilon\}L = L$.

$$L_2 L_1 = \{ya : y \in L_2, a \in L_1\}$$