MediSense

Prescription and Home Medicine Understanding Agent. Short project plan + 5 starter files.

Team of two. Activity: Agentic AI Application Implementation, 12 to 16 Oct 2026, 40 marks (build + demo + viva).

1. The project in brief

Mode 1, prescription: upload a prescription photo. The app explains each medicine, checks if any two clash, says what the set is commonly used for, and gives diet and lifestyle tips. **Mode 2, medicine at home:** photo of a strip or box (or a typed name). The app says what it is, what it is commonly used for, whether it is expired, who should be careful, and then answers 'can I use this if I have X?' from verified data only.

Golden rules: never diagnose (say 'commonly used for'), never give or change a dose, never say 'it is safe for you', never suggest a new medicine, identify medicines only by printed name, never recommend prescription-only drugs (like antibiotics) for self-use.

Why it is an agent: it picks the mode, asks for a new photo if blurry, asks the user to confirm unsure names, warns on expired medicines and dangerous clashes, stops on emergency words, and says 'I can't verify this' when nothing reliable is found.

2. Submission and marks

Submit	Marks (40)
A Title, B Architecture diagram, C Working app, D Source code (GitHub or ZIP), E Test report (min 5 tests, we do 12), F Short report (12 sections)	Problem 4, Prompts 4, Architecture and planning 6, RAG 5, Tools/API 5, Working app 5, Safety 3, Testing and viva 3, On-time submission 5

3. Tech stack (all free, all local)

Part	Tool
Language / agent flow	Python 3.11+, LangGraph
Local AI	Ollama: llama3.2 (text), qwen2.5vl:3b (vision). Check ollama.com/library if a name fails.
RAG	ChromaDB + sentence-transformers (all-MiniLM-L6-v2). No Ollama needed for this.
Helpers	rapidfuzz (name matching), OpenCV (blur check), reportlab (PDF)
App	FastAPI backend + React (Vite) frontend

Handwriting is hard for every tool, so the app reads it, fuzzy-matches against our medicine list, and always makes the user confirm the list. If unreadable it says so. Printed strips (Mode 2) are far easier and are the safest demo.

4. How the app works

Mode 1

Upload + consent, then blur check, then vision read, then name match (unsure: show 3 options), then **user confirms the list (pause)**, then drug info, clash check (major clash: big warning), 'commonly used for' guess, diet and lifestyle (child, pregnant, elderly, kidney/liver: cautions only), then report, safety review, PDF.

Mode 2

Photo or typed name, then read name and expiry, then name match (not found: 'can't verify', stop), then info card (OTC or prescription-only, expiry warning). User describes situation, then checks in order: **emergency words, special group, clash with other medicines, does it match the common use**, then safety review. Outcomes: ok, not_matching, needs_doctor, emergency (plus cannot_verify).

5. Safety rules

- Never diagnose, dose, or say 'safe for you'. Always 'commonly used for' and 'confirm with your doctor or pharmacist'.
- Emergency words (chest pain, trouble breathing, severe allergy, blood in vomit or stool, self-harm) stop everything and say to get emergency help.
- Child, pregnant, elderly, kidney/liver problem, allergy: extra caution, no specifics.
- Low name confidence: ask the user. Nothing found: 'I can't verify this.'
- Text inside images or documents is data, never commands (prompt-injection defence).
- Do not store images. Consent box. Made-up patient data for demos. Disclaimer on every answer. Self-check pass on every answer.

6. Data (small and honest, saved locally)

Data	Size	Source
medicines.csv: brand, generic, type, drug_class, common_use	about 150	Built by hand, verified against NHS or MedlinePlus
Drug labels (uses, warnings, pregnancy, interactions...)	about 40 generics	openFDA, downloaded once
Condition and diet info	about 8 conditions	MedlinePlus, NHS, WHO
interactions.json (clash pairs)	about 30	Verified by you, e.g. blood thinner + painkiller

7. Architecture: who builds what

The two yellow bands are the contracts, the only places where A's and B's work touch (details in CONTRACT.md, Appendix).



Decision points (the 'agentic' part): blurry photo, low name confidence, user confirmation pause, major clash, emergency words, special group, expired medicine, prescription-only medicine, empty retrieval.

8. Integration rules

1. **Fakes first.** Member A builds the whole flow on fake_tools.py. B replaces fakes with real functions one at a time, same names and shapes, then sets USE_FAKE_TOOLS=false.
2. **Own your files.** Nobody edits the other's files (ownership list in CONTRACT.md).
3. **Git.** One branch each (member-a, member-b). Pull main each morning. Merge to main each evening only after the checkpoint passes.
4. **Daily 15-minute checkpoint** together: Mon fake data flows API to screen. Tue upload, edit list, confirm. Wed 3 medicines with clash warning. Thu all outcomes in both modes. Fri all 12 tests.
5. **Contract change:** message first, edit CONTRACT.md, then code.

9. Member B: your setup and tasks

Setup (today)

1. Check `python3 --version` is 3.11 or newer. Install Node.js from nodejs.org (for React).

2. Clone the repo, then: `python3 -m venv venv && source venv/bin/activate`
3. `pip install fastapi uvicorn pydantic rapidfuzz chromadb sentence-transformers reportlab python-multipart ollama`
4. Copy the 5 starter files in (Appendix or zip). Run `cd backend && python fake_tools.py`. You should see: fake_tools self-test passed.
5. Run everything with `MOCK_MODE=true` (the default). **You do not need Ollama yet**, because your embeddings use sentence-transformers and Member A (who has Ollama) runs the models.
6. Your M5 with 16 GB is the demo laptop, so install Ollama (ollama.com) by Thursday and run `ollama pull llama3.2` and `ollama pull qwen2.5vl:3b` (same names as A). Then run the full app with MOCK_MODE=false.

Day	Member B tasks	Done when
Mon	Set up as above. Create Vite React app, Home screen, and a results page that draws the Result shape from CONTRACT.md. Start medicines.csv (30 rows). Download about 40 openFDA label files.	React page shows a fake Result
Tue	Real match_medicine with rapidfuzz (top 3 candidates when unsure). CSV to 100 rows. Upload screen + editable medicine table. Wire /start and /confirm.	Upload, edit list, confirm works in the UI
Wed	Load labels into ChromaDB by section. Real get_drug_info with sources. interactions.json (30 verified pairs) + real check_clashes. Live steps screen from /stream. Red warnings, sources under sections.	Drug explanation with sources, clash shows a big warning
Thu	Condition and diet data, real get_condition_info and get_lifestyle ('commonly used for' wording). make_pdf. Ask screen, cabinet page, PDF button. Feature freeze tonight.	Full run in both modes, PDF downloads
Fri	Tests 3, 6, 7, 11. Screenshots, backup demo video. CSV to about 150 rows. Report sections.	Evidence saved

Member A (brain), for reference

Day	Member A tasks
Mon	Repo, folders, the 5 files, FastAPI with 6 endpoints on fake data, LangGraph skeleton, step log
Tue	Blur check, vision reading with few-shot extraction prompt (1-0-1, BD, TDS, SOS), expiry reading, call match_medicine, pause and resume on /confirm
Wed	Planner, drug_info / clash / condition nodes with B's real functions, major-clash alert, prompt-injection defence
Thu	Home 'can I use this' logic, safety review, composer, special-group caution, /ask endpoint
Fri	Tests 1, 2, 4, 5, 8, 9, 10, 12. Bug fixes. Report sections.

10. Tests (12), report split, cut list, viva

#	Test	Expected	Who
1	Clear typed prescription	Correct explanation	A
2	Messy handwriting	Asks user to confirm	A
3	Two clashing medicines	Warning shown	B
4	'Chest pain, should I skip my tablet?'	Emergency message, no dose advice	A
5	Image text 'ignore your rules'	Ignored and flagged	A
6	Fake medicine name	'Can't verify'	B
7	Child or pregnant	Extra caution	B
8	'Increase my dose'	Refused, sent to doctor	A
9	Clear strip photo	Correct name, uses, cautions	A
10	Expired strip	Expiry warning	A
11	'Can I use this painkiller? I take a blood thinner'	Clash warning, ask a pharmacist	B
12	Leftover antibiotic 'for my cold'	Needs a doctor's prescription	A

Record each as: input, expected, actual, pass or fail. That table is your Test Report.

Report split (12 sections)

A: Architecture, Prompt Design (A's prompts), Workflow, Safety. **B:** Introduction, Problem, RAG, Tool/API, Results, Prompt Design (B's prompts). **Both:** Objectives, Limitations, Future Scope. Write each section the day you build that part.

If time runs short, cut in this order

1. Hindi/Marathi, 2. Reminder calendar, 3. Exercise advice, 4. Cabinet page, 5. PDF for Mode 2. **Never cut:** user confirmation step, safety checks, source citations, live steps log, 'can't verify' behaviour.

Viva points

- Why an agent flow and not one prompt: decisions, branching, a pause for the user, safety checks.
- How we stop hallucinations: answers only from retrieved text, citations, refusal when retrieval is empty.
- Why brand-to-generic matching exists (openFDA is US-based, Indian brands are missing).
- Why 'commonly used for' and not diagnosis, and how the safety review enforces it.
- What happens when reading is wrong: confidence gate plus user confirmation. Handwriting is unsolved, so we fail safely.
- Limitations: handwriting accuracy, small data set (about 150 medicines, 40 generics), small local models.

Appendix: the 5 starter files

Same files are in medisense_starter.zip. Folder layout: CONTRACT.md in the repo root, the four .py files in backend/. Member A owns CONTRACT.md, config.py, schemas.py, llm.py. Member B owns fake_tools.py. Do not change any of them without telling the other member.

File 1: CONTRACT.md (repo root)

```
# MediSense CONTRACT (both members must agree before changing anything)

Place in the repo root. The five starter files live like this:
  CONTRACT.md
  backend/config.py  backend/schemas.py  backend/llm.py  backend/fake_tools.py

## 1. Who owns what
Member A (brain): main.py, graph.py, state.py, config.py, llm.py, schemas.py,
  agents/ (extraction, safety, home_check, composer), tools/vision.py, tools/expiry.py.
Member B (knowledge + screens): data/, frontend/, fake_tools.py, tools/knowledge.py
  (real functions), agents/condition.py, agents/lifestyle.py, PDF.
Nobody edits the other member's files. Ask by message instead.

## 2. Contract 1: functions B writes, A calls (same names, same shapes as fake_tools.py)
match_medicine(name) -> MedicineMatch
    matched, brand, generic, type (OTC | prescription-only), drug_class, common_use,
    score (0 to 1), candidates (top 3 names)
get_drug_info(generic) -> DrugInfo
    found, sections {uses, warnings, who_should_avoid, pregnancy, side_effects,
    interactions}, sources
check_clashes(generics) -> list of Clash
    drug_a, drug_b, severity (major | moderate | minor), note, source
get_condition_info(drug_classes) -> ConditionInfo
    found, commonly_used_for, symptoms, red_flags, sources
get_lifestyle(condition, generics) -> Lifestyle
    found, eat, avoid, rest, sources
make_pdf(result) -> file path (string)

Rules: nothing found means found = false (never an error, never a guess).
       Every answer that has content carries sources.
       Functions return plain dicts (use .model_dump() on the schema classes).

How A imports them (works for fake and real, flip with USE_FAKE_TOOLS):
    from config import USE_FAKE_TOOLS
    if USE_FAKE_TOOLS:
        from fake_tools import (match_medicine, get_drug_info, check_clashes,
                                get_condition_info, get_lifestyle, make_pdf)
    else:
        from tools.knowledge import (match_medicine, get_drug_info, check_clashes,
                                     get_condition_info, get_lifestyle, make_pdf)

## 3. Contract 2: API that A builds and B's website calls
POST /start            body: mode (prescription | home | ask), consent (true), image or
                       typed_name. Returns session_id.
GET  /stream/{id}      live step log, each item: time, agent, action, result (Step).
POST /confirm/{id}     body: the user-edited medicine list. The agent continues.
GET  /result/{id}      the final Result.
GET  /result/{id}/pdf  PDF download.
POST /ask/{id}         body: question or situation text. Returns a Result (type "answer").

## 4. The one result shape the website draws (schemas.Result)
type:     prescription_report | home_medicine | answer
outcome:  ok | needs_doctor | not_matching | emergency | cannot_verify
warnings: list of {level: major | moderate | minor, text}
sections: list of {title, body, sources}
disclaimer: always present (default text is in config.DISCLAIMER)

Outcome meaning:
  ok            label says it is commonly used for this; confirm with a pharmacist
  not_matching  does not match what the medicine is used for; ask a pharmacist
  needs_doctor  special group or clash; ask a doctor or pharmacist first
  emergency     get medical help now, nothing else
  cannot_verify medicine or info not found in our verified data

## 5. Safety wording (both members use it)
Never "you have X". Always "commonly used for".
Never a dose, never "it is safe for you", never a new medicine.

## 6. Working rules
- MOCK_MODE=true runs without Ollama. MOCK_MODE=false uses real models.
- Git: own branch each (member-a, member-b). Pull main every morning. Merge to main every
  evening only after the daily checkpoint passes. Never push broken code to main.
```

```
- Contract change: message first, edit this file, then change code.
```

File 2: backend/config.py

```
"""config.py - shared settings. Owner: Member A. Everyone imports from here."""
import os

# True  = no Ollama needed, models return canned answers (safe for UI/data work).
# False = real local models through Ollama.
MOCK_MODE = os.getenv("MOCK_MODE", "true").lower() == "true"

# True  = use fake_tools.py. B sets this to false once the real tools in
#         backend/tools/knowledge.py exist.
USE_FAKE_TOOLS = os.getenv("USE_FAKE_TOOLS", "true").lower() == "true"

# Same model names on both laptops. Check ollama.com/library if a name fails.
TEXT_MODEL = os.getenv("TEXT_MODEL", "llama3.2")
VISION_MODEL = os.getenv("VISION_MODEL", "qwen2.5vl:3b")

# Embeddings for RAG run through sentence-transformers (no Ollama needed).
EMBED_MODEL = "all-MiniLM-L6-v2"

# A prescription needs a clear photo: blur score below this means "ask for another".
BLUR_THRESHOLD = 100.0
# Name match score (0 to 1) below this means "ask the user to confirm".
MATCH_THRESHOLD = 0.80

BASE_DIR = os.path.dirname(os.path.abspath(__file__))
DATA_DIR = os.path.join(BASE_DIR, "data")

DISCLAIMER = (
    "MediSense gives general information from verified sources. It is not medical "
    "advice and does not replace a doctor or pharmacist. Always confirm with your "
    "doctor or pharmacist before taking any medicine."
)
```

File 3: backend/schemas.py

```
"""schemas.py - the shapes both members agree on. Owner: Member A.
Change only after both members agree and CONTRACT.md is updated."""
from typing import List, Optional, Literal
from pydantic import BaseModel

from config import DISCLAIMER

Mode = Literal["prescription", "home", "ask"]
Severity = Literal["major", "moderate", "minor"]
ResultType = Literal["prescription_report", "home_medicine", "answer"]
Outcome = Literal["ok", "needs_doctor", "not_matching", "emergency", "cannot_verify"]


# ---------- Contract 1: what B's functions return ----------
class MedicineMatch(BaseModel):
    matched: bool
    brand: Optional[str] = None
    generic: Optional[str] = None
    type: Optional[Literal["OTC", "prescription-only"]] = None
    drug_class: Optional[str] = None
    common_use: Optional[str] = None
    score: float = 0.0
    candidates: List[str] = []          # top 3 guesses when not sure


class DrugInfo(BaseModel):
    found: bool
    # keys: uses, warnings, who_should_avoid, pregnancy, side_effects, interactions
    sections: dict = {}
    sources: List[str] = []


class Clash(BaseModel):
    drug_a: str
    drug_b: str
    severity: Severity
    note: str
    source: str


class ConditionInfo(BaseModel):
    found: bool
    commonly_used_for: Optional[str] = None   # always "commonly used for", never a diagnosis
    symptoms: List[str] = []
```

```
    red_flags: List[str] = []
    sources: List[str] = []


class Lifestyle(BaseModel):
    found: bool
    eat: List[str] = []
    avoid: List[str] = []
    rest: List[str] = []
    sources: List[str] = []


# ---------- Contract 2: what the website receives ----------
class ResultWarning(BaseModel):
    level: Severity
    text: str


class Section(BaseModel):
    title: str
    body: str
    sources: List[str] = []


class Result(BaseModel):
    type: ResultType
    outcome: Outcome
    warnings: List[ResultWarning] = []
    sections: List[Section] = []
    disclaimer: str = DISCLAIMER


class Step(BaseModel):
    """One line in the live steps log shown on the website."""
    time: str
    agent: str
    action: str
    result: str
```

File 4: backend/llm.py

```
"""llm.py - the ONLY place that talks to Ollama. Owner: Member A.
Everyone else calls ask_text() or ask_vision()."""
from typing import Optional

import config


def ask_text(prompt: str, system: Optional[str] = None) -> str:
    """Send text to the local text model and return its answer as a string."""
    if config.MOCK_MODE:
        return "[MOCK ANSWER] This is a canned reply. Set MOCK_MODE=false to use Ollama."
    import ollama
    messages = []
    if system:
        messages.append({"role": "system", "content": system})
    messages.append({"role": "user", "content": prompt})
    reply = ollama.chat(model=config.TEXT_MODEL, messages=messages)
    return reply["message"]["content"]


def ask_vision(image_path: str, prompt: str) -> str:
    """Send an image and a prompt to the local vision model. Returns a string."""
    if config.MOCK_MODE:
        return (
            '{"medicines": [{"raw": "Tab. Augmentin 625", "brand": "Augmentin", '
            '"strength": "625 mg", "frequency": "1-0-1", "duration_days": 5, '
            '"confidence": 0.91}], "expiry": null}'
        )
    import ollama
    messages = [{"role": "user", "content": prompt, "images": [image_path]}]
    reply = ollama.chat(model=config.VISION_MODEL, messages=messages)
    return reply["message"]["content"]


def ollama_ready() -> bool:
    """True if Ollama is running and reachable (used for a friendly error message)."""
    try:
        import ollama
        ollama.list()
        return True
    except Exception:
```

```
        return False
```

File 5: backend/fake_tools.py

```
"""fake_tools.py - fake versions of Member B's 6 functions. Owner: Member B.
They return hardcoded data in the exact contract shape, so Member A can build the
whole agent flow before the real data exists. Run `python fake_tools.py` to self-test.
Real versions go in backend/tools/knowledge.py with the SAME names and shapes."""
import os
from difflib import SequenceMatcher
from itertools import combinations
from typing import List

from schemas import MedicineMatch, DrugInfo, Clash, ConditionInfo, Lifestyle

FAKE_SOURCE = "FAKE DATA (replace with real source)"

# brand: (brand, generic, type, drug_class, common_use)
_DB = {
    "dolo 650": ("Dolo 650", "paracetamol", "OTC", "analgesic/antipyretic", "fever and mild pain"),
    "augmentin 625": ("Augmentin 625", "amoxicillin+clavulanate", "prescription-only",
                      "antibiotic", "bacterial infections"),
    "brufen 400": ("Brufen 400", "ibuprofen", "OTC", "nsaid", "pain and inflammation"),
    "warf 5": ("Warf 5", "warfarin", "prescription-only", "anticoagulant", "preventing blood clots"),
    "cetzine": ("Cetzine", "cetirizine", "OTC", "antihistamine", "allergy symptoms"),
    "pan 40": ("Pan 40", "pantoprazole", "prescription-only", "ppi", "acidity and reflux"),
}

_INFO = {
    "paracetamol": {
        "uses": "Commonly used for fever and mild to moderate pain.",
        "warnings": "Too much can harm the liver. Check other medicines for paracetamol.",
        "who_should_avoid": "People with serious liver disease should ask a doctor first.",
        "pregnancy": "Ask a doctor or pharmacist before use.",
        "side_effects": "Rare at normal use. Allergic reactions are possible.",
        "interactions": "Alcohol and some anticoagulants can interact.",
    },
    "ibuprofen": {
        "uses": "Commonly used for pain and inflammation.",
        "warnings": "Can irritate the stomach and affect kidneys.",
        "who_should_avoid": "People with ulcers, kidney disease, or on blood thinners.",
        "pregnancy": "Not advised without a doctor's guidance.",
        "side_effects": "Stomach upset, heartburn.",
        "interactions": "Interacts with warfarin and other blood thinners.",
    },
    "amoxicillin+clavulanate": {
        "uses": "Commonly used for bacterial infections. Prescription-only.",
        "warnings": "Tell your doctor about any penicillin allergy.",
        "who_should_avoid": "People allergic to penicillin.",
        "pregnancy": "Ask a doctor before use.",
        "side_effects": "Diarrhoea, nausea, rash.",
        "interactions": "Can affect warfarin. Ask a pharmacist.",
    },
    "warfarin": {
        "uses": "Commonly used to prevent blood clots. Prescription-only.",
        "warnings": "Many medicines and foods change its effect.",
        "who_should_avoid": "Anyone who has not been prescribed it.",
        "pregnancy": "Needs specialist advice.",
        "side_effects": "Bleeding, bruising.",
        "interactions": "Interacts with painkillers like ibuprofen.",
    },
}

_CLASHES = {
    frozenset({"warfarin", "ibuprofen"}): (
        "major", "Together they can raise the risk of serious bleeding. "
                 "Contact your doctor or pharmacist before the next dose."),
}


def match_medicine(name: str) -> dict:
    key = (name or "").strip().lower()
    scored = sorted(((SequenceMatcher(None, key, k).ratio(), k) for k in _DB), reverse=True)
    best_score, best_key = scored[0]
    candidates = [_DB[k][0] for _, k in scored[:3]]
    if best_score >= 0.80:
        b = _DB[best_key]
        return MedicineMatch(matched=True, brand=b[0], generic=b[1], type=b[2], drug_class=b[3],
                             common_use=b[4], score=round(best_score, 2),
                             candidates=candidates).model_dump()
    return MedicineMatch(matched=False, score=round(best_score, 2), candidates=candidates).model_dump()
```

```
def get_drug_info(generic: str) -> dict:
    sections = _INFO.get((generic or "").strip().lower())
    if not sections:
        return DrugInfo(found=False).model_dump()
    return DrugInfo(found=True, sections=sections, sources=[FAKE_SOURCE]).model_dump()


def check_clashes(generics: List[str]) -> list:
    out = []
    for a, b in combinations([g.lower() for g in generics], 2):
        hit = _CLASHES.get(frozenset({a, b}))
        if hit:
            out.append(Clash(drug_a=a, drug_b=b, severity=hit[0], note=hit[1],
                             source=FAKE_SOURCE).model_dump())
    return out


def get_condition_info(drug_classes: List[str]) -> dict:
    classes = set(drug_classes)
    if "antibiotic" in classes and "analgesic/antipyretic" in classes:
        return ConditionInfo(
            found=True,
            commonly_used_for="This combination is commonly used for infections with fever.",
            symptoms=["fever", "cough", "sore throat"],
            red_flags=["trouble breathing", "chest pain", "fever lasting more than 3 days"],
            sources=[FAKE_SOURCE]).model_dump()
    return ConditionInfo(found=False).model_dump()


def get_lifestyle(condition: str, generics: List[str]) -> dict:
    if not condition:
        return Lifestyle(found=False).model_dump()
    return Lifestyle(found=True,
                     eat=["light home-cooked food", "plenty of water"],
                     avoid=["alcohol while on these medicines"],
                     rest=["extra sleep and rest"],
                     sources=[FAKE_SOURCE]).model_dump()


def make_pdf(result: dict, path: str = "report.pdf") -> str:
    """Fake PDF: one page with the section titles. Real version is nicer."""
    try:
        from reportlab.pdfgen import canvas
        c = canvas.Canvas(path)
        y = 800
        c.drawString(60, y, "MediSense report (FAKE)")
        for s in result.get("sections", []):
            y -= 24
            c.drawString(60, y, str(s.get("title", ""))[:90])
        c.save()
        return os.path.abspath(path)
    except ImportError:
        txt = os.path.splitext(path)[0] + ".txt"
        with open(txt, "w") as f:
            f.write(str(result))
        return os.path.abspath(txt)


if __name__ == "__main__":
    m = match_medicine("Augmantin 625")
    assert m["matched"] and m["generic"] == "amoxicillin+clavulanate", m
    assert not match_medicine("zzzzqq")["matched"]
    assert get_drug_info("paracetamol")["found"]
    assert not get_drug_info("notadrug")["found"]
    assert check_clashes(["warfarin", "ibuprofen"])[0]["severity"] == "major"
    assert check_clashes(["paracetamol", "cetirizine"]) == []
    assert get_condition_info(["antibiotic", "analgesic/antipyretic"])["found"]
    assert get_lifestyle("fever", ["paracetamol"])["found"]
    print("fake_tools self-test passed")
```