

Assignment

Database Technologies

Diploma in Advance Computing (PG-DAC)

Procedure

1. Create a LOGIN table (username, password, and email). Write a procedure (named ***addUser***) to pass the username, password, and email-ID through the procedure and store the data in the LOGIN table.

```
DROP PROCEDURE IF EXISTS addUser;
DELIMITER $
CREATE PROCEDURE addUser(u varchar(50), p varchar(50), e varchar(50))
begin
    insert into login(username, password, emailID)
    values(u, p, e);
end $

DELIMITER ;
```

2. Create a LOG table having following columns (id (auto_increment), curr_date, curr_time, and message). Write a procedure (named ***checkUser***) to pass the email-ID as an input, check whether passed email-ID is available in LOGIN table or not available. If the email-ID is available then display the username and his password. If the email-ID is not available then, insert (curr_date, curr_time, and message) in LOG table.

```
DROP PROCEDURE IF EXISTS checkUser;
DELIMITER $

CREATE PROCEDURE checkUser(IN e varchar(100))
BEGIN

    IF EXISTS(SELECT 1 FROM LOGIN where emailID = e) THEN
        select Concat(username," ",password) from login
        WHERE emailID = e;

    ELSE
        insert into log(curr_date, curr_time, message)
        values(curdate(), curtime(), "Not available");
    END IF ;
END $
DELIMITER ;
```

3. Write a procedure(named getQualification) that takes studentID as a parameter. If studentID is present in the student table, then print his student details along with STUDENT_QUALIFICATION details and if the studentID is not present display message "Student not found..." (Use: STUDENT, and STUDENT_QUALIFICATION tables)

```

DROP PROCEDURE IF EXISTS getQualification;
DELIMITER $

CREATE PROCEDURE getQualification(IN i int)
begin

    IF EXISTS(select 1 from student WHERE ID = i) THEN

        SELECT CONCAT(s.ID," ",s.namefirst," ",s.namelast," ",s.DOB," ",s.emailID," ",q.name,"
",q.college," ",q.university)
        AS C
        FROM student AS s JOIN student_qualifications AS q ON s.ID=q.ID WHERE s.ID = i ;
    ELSE
        select("Student not found");
    END IF ;

end $
delimiter ;

```

4. Write a procedure (named addStudent) that inserts a new student with his phone number and his address into the STUDENT, PHONE, and ADDRESS table.

```

DROP PROCEDURE IF EXISTS addStudent;
DELIMITER $

CREATE PROCEDURE addStudent(IN a_ID int, a_namefirst varchar(100), a_namelast
varchar(100),
                                a_DOB date, a_emailID varchar(100),
a_number bigint, a_address varchar(100))

BEGIN

    INSERT INTO student(ID, namefirst, namelast, DOB, emailID)
    VALUES(a_ID, a_namefirst, a_namelast, a_DOB, a_emailID);

    INSERT INTO student_phone(number)
    VALUES(a_number);

    INSERT INTO student_address(address)
    VALUES(a_address);

END $
DELIMITER ;

```

5. Write a procedure (named addQualification) that takes studentID, and qualification details as a parameter. If studentID is present in the STUDENT table, then insert the qualification in STUDENT_QUALIFICATION table and return a message "Record inserted" or else print 'Student

not found'. (hint: using OUT parameter) (Use: STUDENT, and STUDENT_QUALIFICATION tables)

```
DROP PROCEDURE IF EXISTS addQualification;
DELIMITER $

CREATE PROCEDURE addQualification(
    IN q_ID int,
    IN q_studentID int,
    IN q_name varchar(30),
    IN q_college varchar(20),
    IN q_university varchar(20),
    IN q_marks int,
    IN q_year int,
    OUT message varchar(100)
)
BEGIN
    IF EXISTS(SELECT 1 from student where ID = q_studentID) THEN
        INSERT INTO student_qualifications(ID, studentID, name, college, university, marks,
year)
        VALUES(q_ID, q_studentID, q_name, q_college, q_university, q_marks, q_year);

        SET message = "Record Inserted";
    ELSE
        SET message = "Student not found";
    END IF;

END $
DELIMITER ;
```