

## Congratulations

You have completed a Codility demo.

Tweet this!
I scored 100% in #py on @Codility! http://codility.com/demo/take-sample-test/max\_counters/

Sign up for our newsletter!

Like us on Facebook!

## Demo ticket

### Session

ID: demo6VRT5R-YVV Time limit: 120 min.

### Status: closed

Created on: 2014-04-25 03:54 UTC Started on: 2014-04-25 03:54 UTC Finished on: 2014-04-25 04:02 UTC

score: 100 of 100

#### Tasks in test

1 | {} MaxCounters

#### Correctness Performance

100%

100%

## Task score

100%

**Test score** 3

Training center

ck out Codility training tasks

## 1. MaxCounters

Calculate the values of counters after applying all alternating operations: increase counter by 1; set

## value of all counters to current maximum.

## Task description

You are given N counters, initially set to 0, and you have two possible operations on them:

- increase(X) counter X is increased by 1,
- max\_counter all counters are set to the maximum value of any counter.

A non-empty zero-indexed array A of M integers is given. This array represents consecutive operations:

- if A[K] = X, such that 1 ≤ X ≤ N, then operation K is
- if A[K] = N + 1 then operation K is max counter.

For example, given integer N = 5 and array A such that:

- A[0] = 3
- A[1] = 4
- A[2] = 4
- A[3] = 6
- A[4] = 1
- A[5] = 4A[6] = 4

the values of the counters after each consecutive operation will be:

- (0, 0, 1, 0, 0)
- (0, 0, 1, 1, 0) (0, 0, 1, 2, 0)
- (2, 2, 2, 2, 2)
- (3, 2, 2, 2, 2)(3, 2, 2, 3, 2)

## Solution

Programming language used: Python

Total time used: 8 minutes

Effective time used: 8 minutes

Notes: correct functionality and scalability


Task timeline

03:54:36

04:02:08

 $\nabla$ 

Code: 04:02:08 UTC, py, final, score: 100.00



```
(3, 2, 2, 4, 2)
```

The goal is to calculate the value of every counter after all operations.

Write a function:

```
def solution(N, A)
```

that, given an integer N and a non-empty zero-indexed array A consisting of M integers, returns a sequence of integers representing the values of the counters.

The sequence should be returned as:

- a structure Results (in C), or
- a vector of integers (in C++), or
- · a record Results (in Pascal), or
- an array of integers (in any other programming language).

For example, given:

A[0] = 3

A[1] = 4

A[2] = 4

A[3] = 6

A[4] = 1

A[5] = 4

A[6] = 4

the function should return [3, 2, 2, 4, 2], as explained above. Assume that:

- N and M are integers within the range [1..100,000];
- each element of array A is an integer within the range [1..N + 1].

#### Complexity:

- expected worst-case time complexity is O(N+M);
- expected worst-case space complexity is O(N), beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

12.	
13.	<pre>if cur_max &lt; counters[v-1]:</pre>
14.	<pre>cur_max = counters[v-1]</pre>
15.	if v == (N+1):
16.	<pre>max_op = cur_max</pre>
17.	
18.	<pre>for i in xrange(N):</pre>
19.	<pre>if counters[i] &lt; max_op:</pre>
20.	counters[i] = max_op
21.	
22.	return counters

# Detected time complexity: O(N + M)

**Analysis** 

test	time	result	
Example tests			
example example test	0.050 s.	ок	
Correctness tests			
extreme_small all max_counter operations	0.050 s.	ок	
single only one counter	0.050 s.	ок	
small_random1 small random test, 6 max_counter operations	0.050 s.	ОК	
small_random2 small random test, 10 max_counter operations	0.050 s.	ок	
Performance tests			
medium_random1 medium random test, 50 max_counter operations	0.050 s.	ок	
medium_random2 medium random test, 500 max_counter operations	0.060 s.	ок	
large_random1 large random test, 2120 max_counter operations	0.180 s.	ок	
large_random2 large random test, 10000 max_counter operations	0.340 s.	ок	
extreme_large all max_counter operations	0.460 s.	ОК	

## Training center