

Congratulations

You have completed a Codility demo.

Tweet this!

I scored 100% in #python on @Codility!
<https://codility.com/demo/take-sample-test/dominator/>

Sign up for our newsletter!

Like us on Facebook!

Demo ticket

Session

ID: demo2VRR9T-DXZ
 Time limit: 120 min.

Status: closed

Created on: 2014-08-28 02:36 UTC
 Started on: 2014-08-28 02:37 UTC
 Finished on: 2014-08-28 03:09 UTC

Tasks in test

1 | Dominator

Correctness

100%

Performance

100%

Task score

100%

Test score

100%

100 out of 100 points

EASY

1. Dominator

Find an index of an array such that its value occurs at more than half of indices in the array.

score: 100 of 100



Task description

A zero-indexed array *A* consisting of *N* integers is given. The *dominator* of array *A* is the value that occurs in more than half of the elements of *A*.

For example, consider array *A* such that

```
A[0] = 3   A[1] = 4   A[2] = 3
A[3] = 2   A[4] = 3   A[5] = -1
A[6] = 3   A[7] = 3
```

The dominator of *A* is 3 because it occurs in 5 out of 8 elements of *A* (namely in those with indices 0, 2, 4, 6 and 7) and 5 is more than a half of 8.

Write a function

```
def solution(A)
```

that, given a zero-indexed array *A* consisting of *N* integers, returns index of any element of array *A* in which the dominator of *A* occurs. The function should return *-1* if array *A* does not have a dominator. Assume that:

- N* is an integer within the range [0..100,000];
- each element of array *A* is an integer within the range [-2,147,483,648..2,147,483,647].

For example, given array *A* such that

```
A[0] = 3   A[1] = 4   A[2] = 3
A[3] = 2   A[4] = 3   A[5] = -1
A[6] = 3   A[7] = 3
```

the function may return 0, 2, 4, 6 or 7, as explained above.

Solution

Programming language used: Python

Total time used: 33 minutes

Effective time used: 33 minutes

Notes: correct functionality and scalability

Task timeline



02:37:05

03:09:44

Code: 03:09:44 UTC, py, final, score: 100.00

```
1 # you can use print for debugging purposes, e.g.
2 # print "this is a debug message"
3
4 def solution(A):
5     n = len(A)
6     leader = -1
7     size = 0
8
9     for k in xrange(n):
```

Complexity:

- expected worst-case time complexity is $O(N)$;
- expected worst-case space complexity is $O(1)$, beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

```
10     if size == 0:
11         value = k
12         size += 1
13     else:
14         if A[k] == A[value]:
15             size += 1
16         else:
17             size -= 1
18
19     if size == 0:
20         return -1
21     else:
22         candidate = value
23
24     count = 0
25     for k in xrange(n):
26         if A[k] == A[candidate]:
27             count += 1
28
29     if count > n // 2:
30         return candidate
31     else:
32         return -1
```

Analysis



Detected time complexity:

$O(N \cdot \log(N))$ or $O(N)$

test	time	result
Example tests		
example example test	0.064 s	OK
Correctness tests		
small_nondominator all different and all the same elements	0.060 s	OK
small_half_positions half elements the same, and half + 1 elements the same	0.064 s	OK
small small test	0.064 s	OK
small_pyramid decreasing and plateau, small	0.064 s	OK
extreme_empty_and_single_item empty and single element arrays	0.064 s	OK
extreme_half1 array with exactly N/2 values 1, N even + [0,0,1,1,1]	0.064 s	OK
extreme_half2 array with exactly floor(N/2) values 1, N odd + [0,0,1,1,1]	0.064 s	OK
extreme_half3 array with exactly ceil(N/2) values 1 + [0,0,1,1,1]	0.064 s	OK
Performance tests		
medium_pyramid decreasing and plateau, medium	0.080 s	OK
large_pyramid decreasing and plateau, large	0.244 s	OK
medium_random random test with dominator, N = 10,000	0.084 s	OK
large_random random test with dominator, N = 100,000	0.256 s	OK

Training center