

Congratulations

You have completed a Codility demo.

Tweet this!

I scored 100% in #py on @Codility!
http://codility.com/demo/take-sample-test/tape_equilibrium/

Sign up for our newsletter!

Like us on Facebook!

Demo ticket

Session

ID: demo349895-5N4
 Time limit: 120 min.

Status: closed

Created on: 2014-04-23 04:12 UTC
 Started on: 2014-04-23 04:13 UTC
 Finished on: 2014-04-23 04:24 UTC

Tasks in test

1 | TapeEquilibrium

Correctness

100%

Performance

100%

Task score

100%

Test score

100%

100 out of 100 points

EASY

1. TapeEquilibrium

Minimize the value $|(A[0] + \dots + A[P-1]) - (A[P] + \dots + A[N-1])|$.

score: 100 of 100



Task description

A non-empty zero-indexed array A consisting of N integers is given. Array A represents numbers on a tape. Any integer P , such that $0 < P < N$, splits this tape into two non-empty parts: $A[0], A[1], \dots, A[P-1]$ and $A[P], A[P+1], \dots, A[N-1]$. The *difference* between the two parts is the value of: $|(A[0] + A[1] + \dots + A[P-1]) - (A[P] + A[P+1] + \dots + A[N-1])|$. In other words, it is the absolute difference between the sum of the first part and the sum of the second part. For example, consider array A such that:

```
A[0] = 3
A[1] = 1
A[2] = 2
A[3] = 4
A[4] = 3
```

We can split this tape in four places:

- $P = 1$, difference = $|3 - 10| = 7$
- $P = 2$, difference = $|4 - 9| = 5$
- $P = 3$, difference = $|6 - 7| = 1$
- $P = 4$, difference = $|10 - 3| = 7$

Write a function:

```
def solution(A)
```

that, given a non-empty zero-indexed array A of N integers, returns the minimal difference that can be achieved.

For example, given:

```
A[0] = 3
A[1] = 1
A[2] = 2
```

Solution

Programming language used: Python

Total time used: 12 minutes

Effective time used: 12 minutes

Notes: correct functionality and scalability

Task timeline



Code: 04:24:25 UTC, py, final, score: 100.00

```
01. def solution(A):
02.     left = A[0]
03.     right = sum(A[1:])
04.     min = abs(left-right)
05.
06.     for i in range(1, len(A)-1):
07.         left += A[i]
08.         right -= A[i]
09.         diff = abs(left-right)
10.         if diff < min:
11.             min = diff
12.
13.     return min
```

A[3] = 4
A[4] = 3

the function should return 1, as explained above.
Assume that:

- N is an integer within the range [2..100,000];
- each element of array A is an integer within the range [-1,000..1,000].

Complexity:

- expected worst-case time complexity is $O(N)$;
- expected worst-case space complexity is $O(N)$, beyond input storage (not counting the storage required for input arguments).

Elements of input arrays can be modified.

Copyright 2009–2014 by Codility Limited. All Rights Reserved. Unauthorized copying, publication or disclosure prohibited.

Analysis



Detected time complexity:

$O(N)$

test	time	result
Example tests		
example example test	0.050 s.	OK
Correctness tests		
double two elements	0.050 s.	OK
simple_positive simple test with positive numbers, length = 5	0.050 s.	OK
simple_negative simple test with negative numbers, length = 5	0.050 s.	OK
small_random random small, length = 100	0.050 s.	OK
small_range range sequence, length = ~1,000	0.050 s.	OK
small small elements	0.050 s.	OK
Performance tests		
medium_random1 random medium, numbers from 0 to 100, length = ~10,000	0.070 s.	OK
medium_random2 random medium, numbers from -1,000 to 50, length = ~10,000	0.070 s.	OK
large_ones large sequence, numbers from -1 to 1, length = ~100,000	0.250 s.	OK
large_random random large, length = ~100,000	0.270 s.	OK
large_sequence large sequence, length = ~100,000	0.150 s.	OK
large_extreme large test with maximal and minimal values, length = ~100,000	0.220 s.	OK

Training center