

Real-world (one reusable session) — Solution

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Basic Version

Approach 1 — a module-level session

```
# session_reuse_practice.py
import requests

session = requests.Session()
session.headers.update({"Authorization": "Bearer fake-token"})

urls = [
    "https://api.github.com",
    "https://api.github.com/zen",
    "https://api.github.com/octocat",
]

for url in urls:
    response = session.get(url)
    print(url, "->", response.status_code)

print("Authorization header set to:", session.headers["Authorization"])
```

Expected output:

```
https://api.github.com -> 200
https://api.github.com/zen -> 200
https://api.github.com/octocat -> 200
Authorization header set to: Bearer fake-token
```

This works and proves the header sticks across calls. It doesn't yet confirm the header was actually *sent* on the wire, just that it's set on the session object — the Intermediate version checks that distinction.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Intermediate Version

Approach 1 — a typed factory function

```
# session_reuse_practice.py
import requests

def make_authenticated_session(token: str) -> requests.Session:
    session = requests.Session()
    session.headers.update({"Authorization": f"Bearer {token}"})
    return session

def main() -> None:
    session = make_authenticated_session("fake-token")

    urls = [
        "https://api.github.com",
        "https://api.github.com/zen",
        "https://api.github.com/octocat",
    ]

    for url in urls:
        response = session.get(url)
        print(f"{url} -> {response.status_code}")

    sent_header = response.request.headers.get("Authorization")
    print(f"header actually sent on the last request: {sent_header}")

if __name__ == "__main__":
    main()
```

Expected output:

```
https://api.github.com -> 200
https://api.github.com/zen -> 200
```

```
https://api.github.com/octocat -> 200  
header actually sent on the last request: Bearer fake-token
```

`response.request.headers` reads back the *actual* request object `requests` sent, not the session's own dict — confirming the header genuinely went out over the wire, not just that it's set somewhere in Python.

Difference from Basic: a named, typed factory function (`make_authenticated_session`) instead of module-level statements is reusable and importable, and checking `response.request.headers` instead of `session.headers` confirms the header was actually transmitted, not just configured.

Which one should you actually write? This factory function is enough for a script or a one-off tool with a single, short-lived call site — including this document's Build Task, which holds one module-level `Session` for the whole wrapper. Configure headers once, right after creating the session, and treat them as read-only after that — the moment more than one part of a program might mutate a shared session's headers from different places is the moment that discipline starts to matter.