

Intermediate (build the gate) — Hints

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Only 2 hints — work through them in order, and don't jump ahead until you've genuinely tried. Each hint has 2 depth levels: **Basic** (the plain idea) and **Intermediate** (proper Python, including how a real release gate refuses to be an easy-to-skip formality). Read Basic first even if you already know Python — it's the fastest way to spot exactly what each deeper level adds.

- [Hint 1 — The idea, and the exact pieces](#)
- [Hint 2 — The plan, and almost the whole thing](#)

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Hint 1 — The idea, and the exact pieces

Basic Version

A release gate is one function: try to make a version "live," but only actually do it if that version's test score is good enough. If it isn't, print why, and don't touch anything.

Things to use:

- A function `deploy(version_name, threshold)`.
- Your `run_eval_suite(prompt_text)` stub from the `version_log` exercise, to get a score.
- An `if score >= threshold:` check.
- Writing the winning version's name into a plain text file, `live_version.txt`, only inside that `if`.

Intermediate Version

The whole exercise is really just one `if / else` with real consequences on each side. `deploy()` looks up the version (from the log you built in `version_log`), runs the test suite against its prompt text, and compares the score to `threshold`. If it passes, it writes the version name to `live_version.txt` — that file *is* your "what's currently live" pointer, the thing every other part of the system reads to know which prompt to actually use. If it fails, `deploy()` must not touch `live_version.txt` at all — not write an empty string, not write anything — since any write at all means it changed state on a rejected release.

The exact pieces:

- Your `load_versions(path)` and `run_eval_suite(prompt_text)` from `version_log`, reused here — look the target version up by name out of the loaded list.
- `open("live_version.txt", "w") as f: f.write(version_name)` — only inside the passing branch.
- A return value or printed message on failure that names the score and the threshold, e.g. `f"Score {score} below threshold {threshold} – not deploying."` — a gate that fails silently is nearly as bad as one that doesn't exist.
- Reading the current live version back: `open("live_version.txt").read().strip()`.

Going further — the harder question:

The real design question isn't "how do I write an if-statement," it's **what does `deploy()` return, and what can the caller (or a human reading the terminal) actually learn from it?** A function that just prints something and returns `None` is hard to test and hard to build other tools on top of — and this document's whole Build Task is built on top of exactly this function. Return a small, structured result instead — a `DeployResult` with `passed: bool`, `score: float`, and `failing_cases: list` — so both a human and later code (the Build Task's `deploy_gate.py`) can act on it without re-parsing printed text.

The other real design question: **what happens if `deploy()` is called with a version name that was never saved in the version log?** Looking it up and getting `None` back, then trying to read `.prompt_text` off of `None`, is exactly the "confusing failure somewhere later" problem Doc01's config loader was built to avoid. Check explicitly, and raise a clear, named error (`VersionNotFoundError`) instead of letting a missing lookup blow up as an unrelated `AttributeError`.

The extra pieces needed:

- A small result type — either a `@dataclass DeployResult` or, simplest, a dict with a fixed shape (`{"passed": bool, "score": float, "failing_cases": list}`).
- `class VersionNotFoundError(Exception): pass`, raised the moment the looked-up version comes back missing — before anything else runs.
- Keep `live_version.txt` untouched on any failure path, including this new one — a version that doesn't exist obviously can't become live.

Sketch `DeployResult` and the not-found check yourself before checking Hint 2.

Difference between Basic and Intermediate: Basic names the one `if / else` that decides whether a version goes live. Intermediate adds a real not-found path, a required threshold from `.env`, a way to read the live pointer back — and returns the decision as a typed `DeployResult`, raising a named error for a missing version.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Hint 2 — The plan, and almost the whole thing

Basic Version

```
function deploy(version_name, threshold):
    versions = load all saved versions
    find the one matching version_name
    result = run_eval_suite(that version's prompt_text)
    if result's score >= threshold:
        write version_name into live_version.txt
        print "deployed"
    else:
        print "score too low, not deploying" with the actual score
```

Here's almost the whole thing — just try running it and reading it line by line:

```
# release_gate_practice.py – Intermediate section
def deploy(version_name, threshold):
    versions = load_versions("versions.json")
    target = None
    for v in versions:
        if v["version_name"] == version_name:
            target = v

    result = run_eval_suite(target["prompt_text"])
    if result["score"] >= threshold:
        with open("live_version.txt", "w") as f:
            f.write(version_name)
        print(version_name, "deployed, score", result["score"])
    else:
        print(
            version_name,
            "NOT deployed, score",
            result["score"],
            "below threshold",
            threshold,
        )
```

Expected output, calling `deploy("v2", 0.9)` then `deploy("v1", 0.9)` against the `versions.json` from `version_log`:

```
v2 deployed, score 1.0  
v1 NOT deployed, score 0.6 below threshold 0.9
```

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Intermediate Version

```
function deploy(version_name: str, threshold: float) -> None:
    versions = load_versions("versions.json")
    target = find the dict in versions where version_name matches
    if target is None:
        print "no such version", return

    result = run_eval_suite(target["prompt_text"])
    if result["score"] >= threshold:
        write version_name to live_version.txt
        print a success message with the score
    else:
        print a failure message with the score and threshold,
        do NOT write the file
```

```
# release_gate_practice.py – Intermediate section
def find_version(versions: list[dict], name: str) -> dict | None:
    for v in versions:
        if v["version_name"] == name:
            return v
    return None

def deploy(version_name: str, threshold: float) -> None:
    versions = load_versions("versions.json")
    target = find_version(versions, version_name)
    if target is None:
        print(f"No such version: {version_name}")
        return

    result = run_eval_suite(target["prompt_text"])
    if result["score"] >= threshold:
        with open("live_version.txt", "w") as f:
            f.write(version_name)
        print(
            f"{version_name} deployed – score {result['score']} >= {threshold}"
        )
    else:
        score = result["score"]
        print(f"{version_name} NOT deployed – score {score} < {threshold}")
```

Now add a `get_live_version()` function that reads `live_version.txt` back, and compare against the [Solution](#).

Going further, as a plan:

```
class VersionNotFoundError is an Exception

function deploy(version_name, threshold) -> DeployResult:
    versions = load_versions("versions.json")
    target = find_version(versions, version_name)
    if target is None:
        raise VersionNotFoundError naming version_name

    result = run_eval_suite(target["prompt_text"])
    passed = result["score"] >= threshold

    if passed:
        write version_name to live_version.txt

    return DeployResult(passed, result["score"], result.get("failed", []))
```

Here's almost the whole thing — fill in `DeployResult` yourself:

```
# release_gate_practice.py – Intermediate section
class VersionNotFoundError(Exception):
    pass

# your turn: define DeployResult, either as a @dataclass with fields
# passed: bool, score: float, failing_cases: list – or a plain dict
# with those same 3 keys

def deploy(version_name: str, threshold: float) -> "DeployResult":
    versions = load_versions("versions.json")
    target = find_version(versions, version_name)
    if target is None:
        raise VersionNotFoundError(f"No saved version named: {version_name}")

    result = run_eval_suite(target["prompt_text"])
    passed = result["score"] >= threshold

    if passed:
        with open("live_version.txt", "w") as f:
            f.write(version_name)
```

```
# your turn: build and return a DeployResult from passed, result["score"],  
# and result.get("failed", [])
```

Fill in `DeployResult` and the return statement yourself, then compare all 3 of your finished versions against the [Solution](#).

Difference between Basic and Intermediate: Basic looks up the version, scores it, and writes the pointer only on a pass. Intermediate hardens the lookup and the threshold, then returns the decision as data other code can check.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Full solution: [Show me the solution](#)