Step 2 — One Tool, One Loop: the Smallest Possible Working Agent — Solution

> Back to this step · Hint 1 · Hint 2 · Solution

Story — Step 2: an agent is a model in a loop that can ask for tools. This step builds the **real** Worker loop — the one the finished project uses — but gives it only one pure-logic tool, so every line can be understood before more tools arrive. Think → act → observe, a step log, and a hard step limit are all here from the start. **If not:** Step 3 would have to rewrite the loop to add a limit and a log, instead of just adding tools.

After this step the project runs as a small agent: ask for a temperature in Fahrenheit and the model calls the converter, you see each step, and it can never loop forever. Files from Step 1 that aren't shown here don't change.

The tool

Story — `tools/converter.py` : the simplest possible tool — pure maths, no network, so it can't fail for outside reasons. (Also create an empty `tools/__init__.py`.) **If not:** a network problem could look like a loop bug.

```
# src/tools/converter.py
# The converter tool: celsius_to_fahrenheit(), pure logic with no outside
# calls. Its docstring tells the model when to use it.
from langchain_core.tools import tool

@tool
def celsius_to_fahrenheit(celsius: float) -> float:
    """Convert a temperature from Celsius to Fahrenheit. Use it only when
    you already have a Celsius number and the user wants Fahrenheit."""
    return round(celsius * 9 / 5 + 32, 1)
```

Solution — the finished loop shape, with one tool

Changed from Step 1: `exceptions.py` adds Doc07's `MaxIterationsExceeded`.

Story — `exceptions.py`: `MaxIterationsExceeded` carries the partial step log, so hitting the limit still shows where the Worker got stuck. **If not:** the limit would throw away every step that happened before it.

```
# src/exceptions.py
# The project's named errors: MissingConfigError (Doc01), and
# MaxIterationsExceeded (Doc07), which carries the partial step log.

class MissingConfigError(Exception):
    """Raised when a required setting is missing from the environment."""
    pass

class MaxIterationsExceeded(Exception):
    def __init__(self, message: str, steps: list[dict]) -> None:
        self.steps = steps
        super().__init__(message)
```

Story — `prompts/worker.txt`: tells the model *when* to use its tool. Without it, the model often converts temperatures itself — and gets it slightly wrong. **If not:** the tool would exist, but be used only sometimes.

`src/prompts/worker.txt`

```
You are a research assistant. Use your tool for every temperature
conversion — never convert in your head. Answer everything else directly.
```

(Step 3 rewrites this prompt once there are 3 tools.)

Story — `agents/worker.py`: Doc07's Build Task Worker, driving Doc06's `@tool` tools. `ALL_TOOLS` is the toolbox — one tool for now. `find_tool()` and `run_tool()` turn **any** failure (unknown tool, bad arguments, a crash inside the tool) into an `Error: ...` observation the model can read. Every call becomes a step record; the log comes back in `AgentResult`, or inside `MaxIterationsExceeded` when the limit is hit. **If not:** a bad tool call would crash the run, and a wrong answer would have no record of how it was reached. This file does **not** change in Step 3 except for the tool list.

```
# src/agents/worker.py
# The Worker agent: run_worker() is the ReAct loop — ask the model, run the
# tool it asks for, send the result back — with a step log and a hard
# step limit. ALL_TOOLS lists the tools it may use.
from dataclasses import dataclass, field

from langchain_core.tools import BaseTool
from langchain_openai import ChatOpenAI
```

```
from src.exceptions import MaxIterationsExceeded
from src.tools.converter import celsius_to_fahrenheit
from src.utils.logger import get_logger
from src.utils.prompts import load_prompt

ALL_TOOLS = [celsius_to_fahrenheit]

@dataclass
class AgentResult:
    final_answer: str
    steps: list[dict] = field(default_factory=list)

def find_tool(tools: list[BaseTool], name: str) -> BaseTool | None:
    for candidate in tools:
        if candidate.name == name:
            return candidate
    return None

def run_tool(
    call: dict, tools: list[BaseTool]
) -> tuple[str | None, str | None]:
    tool = find_tool(tools, call["name"])
    if tool is None:
        return None, f"unknown tool: {call['name']}"
    try:
        result = tool.invoke(call["args"])
        return str(result), None
    except Exception as e:
        return None, str(e)

def run_worker(
    model: ChatOpenAI, task: str, max_iterations: int
) -> AgentResult:
    logger = get_logger(__name__)
    model_with_tools = model.bind_tools(ALL_TOOLS)
    messages = [
        {"role": "system", "content": load_prompt("worker")},
        {"role": "user", "content": task},
    ]
    steps: list[dict] = []

    for step in range(max_iterations):
        response = model_with_tools.invoke(messages)
        messages.append(response)

        if not response.tool_calls:
```

```
            return AgentResult(final_answer=response.content, steps=steps)

        for call in response.tool_calls:
            result, error = run_tool(call, ALL_TOOLS)
            if error is None:
                observation = result
                logger.info("step %s: %s -> %s", step, call["name"], result)
            else:
                observation = f"Error: {error}"
                logger.warning(
                    "step %s: %s failed -> %s", step, call["name"], error
                )
            messages.append({
                "role": "tool",
                "tool_call_id": call["id"],
                "content": observation,
            })
            steps.append({
                "step": step,
                "tool": call["name"],
                "arguments": call["args"],
                "result": result,
                "error": error,
            })

    message = f"No answer after {max_iterations} steps"
    raise MaxIterationsExceeded(message, steps)
```

Changed from Step 1: `main.py` calls `run_worker()` instead of the chain, prints the step log with `print_steps()`, and catches `MaxIterationsExceeded` and `openai.RateLimitError`.

Story — `main.py`: hitting the limit ends one task with its partial log, not the whole app. **If not:** you'd see "gave up" with no clue why.

```
# main.py
# The file you run: python main.py
# Runs the Worker on each task, prints its step log and the answer, and
# turns each known error into one clear message.
import sys

import openai

from src.agents.worker import run_worker
from src.config import load_config
from src.exceptions import MaxIterationsExceeded, MissingConfigError
from src.models.llm import get_model
```

```
from src.utils.logger import get_logger

MAX_ITERATIONS = 5

def print_steps(steps: list[dict]) -> None:
    for step in steps:
        if step["error"] is None:
            outcome = step["result"]
        else:
            outcome = "Error: " + step["error"]
        print(f"  step {step['step']}: {step['tool']}({step['arguments']})")
        print(f"          -> {outcome}")

def main() -> None:
    try:
        config = load_config()
    except MissingConfigError as e:
        print(f"Setup problem: {e}")
        sys.exit(1)

    logger = get_logger(__name__)
    model = get_model(config)
    print("ResearchHand — ask a question, or /quit to exit.")

    while True:
        task = input("You: ").strip()
        if task == "/quit":
            break
        if task == "":
            continue

        try:
            result = run_worker(model, task, MAX_ITERATIONS)
        except MaxIterationsExceeded as e:
            print(f"Gave up: {e}")
            print_steps(e.steps)
            continue
        except openai.AuthenticationError:
            logger.error("Authentication failed — check OPENAI_API_KEY.")
            print("Login failed — check OPENAI_API_KEY in your .env file.")
            sys.exit(1)
        except openai.RateLimitError:
            logger.warning("Rate limited after the client's retries.")
            print("We're busy right now — wait a moment and try again.")
            continue

        print_steps(result.steps)
```

```
        print(f"Answer: {result.final_answer}")

if __name__ == "__main__":
    main()
```

Story — `tests/unit/test_tools.py`: checks the tool with no model and no network. Case 2 proves `@tool` checks the argument's type *before* the function runs — the Pydantic contract from Doc06. **If not:** a wrong argument type would only show up during a real run.

```
# tests/unit/test_tools.py
# Checks the tools. No API calls, no API key, no network needed.
# Run from the repo root: python -m tests.unit.test_tools
from pydantic import ValidationError

from src.tools.converter import celsius_to_fahrenheit

def test_converter() -> None:
    result = celsius_to_fahrenheit.invoke({"celsius": 18})
    print(f"case 1 (18°C in °F)          -> {result}")

def test_converter_rejects_bad_arguments() -> None:
    try:
        celsius_to_fahrenheit.invoke({"celsius": "hot"})
    except ValidationError:
        print("case 2 (celsius='hot')       -> ValidationError")

if __name__ == "__main__":
    test_converter()
    test_converter_rejects_bad_arguments()
```

Story — `tests/unit/test_agents.py`: checks `find_tool()` and `run_tool()` with hand-made tool calls — no model needed. **If not:** a bug in how failures are turned into observations would only appear during a real, paid run.

```
# tests/unit/test_agents.py
# Checks the Worker's helper functions with hand-made
# tool calls and steps. No API calls, no API key needed.
# Run from the repo root: python -m tests.unit.test_agents
from src.agents.worker import ALL_TOOLS, find_tool, run_tool

def test_find_tool() -> None:
    found = find_tool(ALL_TOOLS, "celsius_to_fahrenheit")
    missing = find_tool(ALL_TOOLS, "send_email")
    print(f"case 1 (known tool)          -> {found.name}")
    print(f"case 1 (unknown tool)        -> {missing}")
```

```
def test_run_tool() -> None:
    good = {"name": "celsius_to_fahrenheit", "args": {"celsius": 0}}
    unknown = {"name": "send_email", "args": {}}
    bad_args = {"name": "celsius_to_fahrenheit", "args": {"celsius": "x"}}
    print(f"case 2 (good call)           -> {run_tool(good, ALL_TOOLS)}")
    print(f"case 2 (unknown tool)        -> {run_tool(unknown, ALL_TOOLS)}")
    result, error = run_tool(bad_args, ALL_TOOLS)
    print(f"case 2 (bad arguments)       -> result={result}, error set: "
          f"{error is not None}")

if __name__ == "__main__":
    test_find_tool()
    test_run_tool()
```

Changed from Step 1: `tests/integration/test_live_agents.py` gets cases 2-4 — `tools_used()`, three test functions, their imports, and three calls at the bottom.

Story — `tests/integration/test_live_agents.py`: three Worker cases with the real model: a conversion uses the tool, a general question uses none, and `max_iterations=1` raises `MaxIterationsExceeded`. **If not:** "it only calls the tool when needed" and "it always stops" would be claims, not checks.

```
# tests/integration/test_live_agents.py
# The project's checks against the real OpenAI API (and Open-Meteo) —
# each step adds cases. Needs a valid OPENAI_API_KEY in .env.
# Run from the repo root: python -m tests.integration.test_live_agents
#   case 1 — the no-tools chain answers a question from memory
#   case 2 — a conversion uses the converter tool
#   case 3 — general knowledge needs no tool at all
#   case 4 — 1 round can't finish a tool task: MaxIterationsExceeded
from langchain_openai import ChatOpenAI

# new in Step 2
from src.agents.worker import AgentResult, run_worker
from src.chains.direct_answer import build_direct_chain
from src.config import load_config
# new in Step 2
from src.exceptions import MaxIterationsExceeded
from src.models.llm import get_model


def test_direct_answer(model: ChatOpenAI) -> None:
    chain = build_direct_chain(model)
    answer = chain.invoke({"question": "What is the capital of France?"})
    print(f"case 1 (direct answer)  -> {answer}")
```

```
# new in Step 2
def tools_used(result: AgentResult) -> list[str]:
    names = []
    for step in result.steps:
        names.append(step["tool"])
    return names


# new in Step 2
def test_conversion_uses_tool(model: ChatOpenAI) -> None:
    task = "What is 25 degrees Celsius in Fahrenheit?"
    result = run_worker(model, task, 5)
    print(f"case 2 (conversion)     -> tools: {tools_used(result)}")


# new in Step 2
def test_no_tool_needed(model: ChatOpenAI) -> None:
    result = run_worker(model, "What is the capital of France?", 5)
    print(f"case 3 (no tool needed) -> {len(result.steps)} steps: "
          f"{result.final_answer}")


# new in Step 2
def test_step_limit(model: ChatOpenAI) -> None:
    task = "What is 25 degrees Celsius in Fahrenheit?"
    try:
        run_worker(model, task, 1)
        print("case 4 (step limit)     -> WRONG, no error was raised")
    except MaxIterationsExceeded as e:
        print(f"case 4 (step limit)     -> raised, {len(e.steps)} step(s) "
              f"in the partial log")


if __name__ == "__main__":
    config = load_config()
    model = get_model(config)
    test_direct_answer(model)
    # new in Step 2
    test_conversion_uses_tool(model)
    test_no_tool_needed(model)
    test_step_limit(model)
```

Run everything:

```
python -m tests.unit.test_config
python -m tests.unit.test_tools
python -m tests.unit.test_agents
python -m tests.integration.test_live_agents
python main.py
```

Expected app session (log lines left out; wording varies):

```
You: What is 25 degrees Celsius in Fahrenheit?
  step 0: celsius_to_fahrenheit({'celsius': 25})
          -> 77.0
Answer: 25°C is 77.0°F.
You: What is the capital of France?
Answer: The capital of France is Paris.
```