Basic (your first coroutine) — Hints

> Back to the exercise · Hint 1 · Hint 2 · Solution

Only 2 hints — work through them in order, and don't jump ahead until you've genuinely tried. Each hint builds toward the full solution.

- Hint 1 — The idea, and the exact pieces
- Hint 2 — The plan, and almost the whole thing

Hint 1 — The idea, and the exact pieces

Same idea, with the exact vocabulary. Writing `async def wait_and_return() -> str:` defines a **coroutine function**. Calling `wait_and_return()` does not execute its body — it constructs and returns a **coroutine object**, a suspended unit of work that hasn't started yet. Python will even print a `RuntimeWarning: coroutine 'wait_and_return' was never awaited` if you build one and never do anything else with it — that warning exists specifically to catch this exact mistake.

The exact pieces:

- `async def wait_and_return() -> str:` — the `async` keyword marks this as a coroutine function; the `-> str` documents what it eventually resolves to.
- `await asyncio.sleep(1)` — the async equivalent of `time.sleep`; hands control back to the event loop for that second instead of blocking anything.
- `return "done"` — an ordinary `return`. It sets what the coroutine resolves to once it finishes; it does not run the function immediately.
- `asyncio.run(wait_and_return())` — `wait_and_return()` builds the coroutine object; `asyncio.run(...)` is what actually starts the event loop, drives it to completion, and hands back the return value.

Think about where this code actually gets called from in a real program, not just a standalone script. `asyncio.run(...)` assumes it's the *only* thing starting an event loop — it creates one, runs your coroutine, and tears the loop down afterward. That assumption breaks the moment this code runs somewhere a loop is already running: inside a FastAPI route (Doc12), inside a Jupyter notebook, inside any other `async def` function. Call `asyncio.run(...)` from any of those places and you get `RuntimeError: asyncio.run() cannot be called from a running event loop` — not a bug in your coroutine, a bug in *where* you tried to start it.

The real design question isn't just "how do I run this coroutine" — it's "does the code that calls this function control its own event loop, or does it need to work whether or not one is already running?"

The extra piece that answers that question:

- **Don't call `asyncio.run()` inside reusable functions.** Keep it at the true entry point of your program (the `if __name__ == "__main__":` block) and nowhere else. Any function meant to be reused from inside an already-async caller should just be `async def` and get `await`ed directly by whatever calls it — never wrapped in its own `asyncio.run()`.
- **`asyncio.get_running_loop()`** (inside a `try/except RuntimeError`) is how you can detect, at runtime, whether a loop is already running — useful in library code that genuinely needs to support being called both ways, though the cleaner fix is almost always to just not call `asyncio.run()` from library code at all.

Hint 2 — The plan, and almost the whole thing

```
import asyncio

define:
    async def wait_and_return() -> str:
        await asyncio.sleep(1)
        return "done"

demonstrate the gotcha:
    unstarted = wait_and_return()
    print(unstarted)                    # coroutine object, not "done"

run it for real:
    result: str = asyncio.run(wait_and_return())
    print(result)                       # "done"
```

```
# coroutine_basics_practice.py
async def wait_and_return() -> str:
    await asyncio.sleep(1)
    return "done"

if __name__ == "__main__":
    result: str = asyncio.run(wait_and_return())
```

Fill in the `unstarted = wait_and_return()` demonstration and both `print(...)` calls yourself, then compare against the Solution.

Once that's working, add a timeout, the way a real caller should — a coroutine that never actually finishes (a network call that hangs, say) shouldn't be able to freeze your whole program forever:

```
import asyncio

define wait_and_return, same as before

try:
    result = asyncio.run(asyncio.wait_for(wait_and_return(), timeout=5))
    print(result)
except asyncio.TimeoutError:
    print("wait_and_return took too long, giving up")
```

```
# coroutine_basics_practice.py
import asyncio

async def wait_and_return() -> str:
    await asyncio.sleep(1)
    return "done"

async def main() -> None:
    try:
        result = await asyncio.wait_for(wait_and_return(), timeout=5)
        print(result)
    except asyncio.TimeoutError:
        print("wait_and_return took too long, giving up")

if __name__ == "__main__":
    asyncio.run(main())
```

Notice `asyncio.run()` now only appears once, at the very bottom, wrapping `main()` — exactly the Hint 1 point about keeping it at the true entry point. Try lowering `timeout=5` to `timeout=0.5` yourself (shorter than the 1-second sleep) to see the `except` branch actually trigger, then compare your finished versions against the Solution.

One more tool: `asyncio.create_task(coro)` starts a coroutine running in the background straight away. Keep the task in a variable, do other awaited work, then `await task` to collect its result.

Full solution: Show me the solution