

Edge cases (an unhandled routing value) — Hints

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Only 2 hints — work through them in order, and don't jump ahead until you've genuinely tried. Each hint has 3 depth levels: **Basic** (the plain idea), **Intermediate** (proper LangGraph), **Advanced** (making the failure message actually useful). Read Basic first even if you already know LangGraph — it's the fastest way to spot exactly what each deeper level adds.

- [Hint 1 — The idea, and the exact pieces](#)
- [Hint 2 — The plan, and almost the whole thing](#)

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Hint 1 — The idea, and the exact pieces

Basic Version

Take your Intermediate exercise's conditional edge and deliberately break the routing function so it sometimes returns a string that isn't one of the mapping's keys — like returning `"path_c"` when the mapping only knows `"path_a"` and `"path_b"`. Run it, and actually read the error `LangGraph` gives you, instead of guessing.

The question this exercise is really asking: does an unrecognized routing value fail loudly and clearly (good — you'll notice immediately), or does it silently do something unexpected, like defaulting to some node anyway (bad — you'd never notice until something was already wrong)?

Things to use:

- Your Intermediate exercise's graph, with `route` changed to sometimes return an unmapped string.
- A `try / except` around `graph.invoke(...)` so you can read the exception type and message without your script just crashing.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Intermediate Version

`add_conditional_edges("from_node", route, {"path_a": "node_a", "path_b": "node_b"})` builds, internally, a lookup: call `route(state)`, then look up whatever it returned in that mapping to find the real next node. A plain dict lookup with a missing key raises `KeyError` — and that's exactly what happens here too: `LangGraph` doesn't quietly fall through to some default node, it lets the lookup fail, which surfaces as an exception at the moment that branch actually runs (**not** when you call `compile()` — the mapping isn't checked until the routing function's return value is actually looked up during a real `invoke()`).

The exact pieces:

- Change `route` so it returns `"path_c"` under some condition your test input can trigger — e.g. `return "path_c" if state["flag"] is None else ("path_a" if state["flag"] else "path_b")`.
- `try: graph.invoke({"flag": None, ...}) except Exception as e: print(type(e), e)` — catch broadly first, so you can see exactly what `LangGraph` actually raises, rather than assuming.
- Confirm it fails **at invoke time**, not at `compile()` time — compiling a graph doesn't run any routing function, so a bad mapping only shows up once you actually execute the branch that hits it.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Advanced Version

Think about who actually reads the error LangGraph raises when this happens. It correctly fails loudly — that's the good news this exercise is meant to teach you to notice. But the message you get from the library's internal lookup failing doesn't necessarily say anything about *your* routing function, *your* state, or *why* the value was wrong — it just tells you a key lookup failed somewhere inside the library's branch-running code.

The real design question isn't just "does an unmapped value fail loudly" (yes) — it's "when it does, does the failure actually help whoever's debugging it, or just tell them something broke?"

The extra piece that helps:

- Add your own explicit check **inside** the routing function itself, before returning, and raise a clear, custom error naming exactly what went wrong: `raise ValueError(f"route() produced an unhandled value: {result!r} for state: {state}")`. This fails at the same moment (still loud, still immediate), but the message now names your actual routing function, the actual bad value, and the actual state that caused it — instead of a generic lookup failure several stack frames inside LangGraph's own code.

```
# conditional_routing_practice.py – Edge cases section
def route(state: AgentState) -> str:
    if state["flag"] is None:
        result = "path_c" # deliberately not in the mapping
    else:
        result = "path_a" if state["flag"] else "path_b"

    valid_paths = {"path_a", "path_b"}
    if result not in valid_paths:
        raise ValueError(f"route() returned {result!r}, which isn't one of {valid_paths}")
    return result
```

Difference between Basic, Intermediate, and Advanced: Basic and Intermediate establish the fact this exercise is testing for — an unmapped value fails loudly, via a `KeyError`-style lookup failure, at invoke time rather than compile time. Advanced doesn't change *whether* it fails — it changes *how useful the failure is*, by adding your own explicit check with a message naming your routing function, the actual bad value, and the state that produced it, instead of relying on a generic error from several layers inside the library.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Hint 2 — The plan, and almost the whole thing

Basic Version

```
reuse the conditional-routing graph from the Intermediate exercise

change route so it can return "path_c" -- a string the mapping doesn't know about

wrap the invoke call in try/except

run it once with a normal input (flag=True) -- confirm it still works
run it once with the input that triggers "path_c" -- read the actual exception
```

Here's almost the whole thing — just try running it and reading it line by line:

```
# conditional_routing_practice.py – Edge cases section
def route(state):
    if state["flag"] is None:
        return "path_c"
    return "path_a" if state["flag"] else "path_b"

# ... same graph wiring as the Intermediate exercise, mapping only has path_a/pat

try:
    graph.invoke({"flag": None, "message": ""})
except Exception as e:
    print(type(e).__name__, "-", e)
```

Expected output if you run just this: nothing prints unless the exception actually gets raised — that only happens once `invoke` runs the broken branch. Run it and read exactly what type of exception you got and what its message says.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Intermediate Version

same graph as the Intermediate exercise (conditional_routing), but:

```
def route(state: GraphState) -> str:
    if state["flag"] is None:
        return "path_c"    # not in the mapping on purpose
    return "path_a" if state["flag"] else "path_b"
```

confirm:

```
graph.invoke({"flag": True, ...})    -> works fine, unchanged
graph.invoke({"flag": None, ...})    -> raises, at invoke time
```

print the exception's type and message -- is it a KeyError? does it name "path_c"
also confirm builder.compile() itself does NOT raise -- the bad mapping isn't checked

```
# conditional_routing_practice.py – Edge cases section
builder = StateGraph(GraphState)
# ... add_node / add_conditional_edges / add_edge exactly as in conditional_routing.py
graph = builder.compile() # this line should NOT raise

try:
    graph.invoke({"flag": None, "message": ""})
except Exception as e:
    print(f"{type(e).__name__}: {e}")
```

Run this and read the real output before checking the [Solution](#) — the exact exception type and message matter here, that's the whole point of the exercise.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Advanced Version

same setup, but `route()` itself checks its own result before returning:

```
def route(state) -> str:
    result = "path_c" if state["flag"] is None else ("path_a" if state["flag"] else "path_b")
    valid_paths = {"path_a", "path_b"}
    if result not in valid_paths:
        raise ValueError(f"route() returned {result!r}, which isn't one of {valid_paths}")
    return result
```

run the same 2 invoke calls as Intermediate, and compare:
 the library's own `KeyError`-style message, vs.
 your own `ValueError`'s message

which one would actually help you debug this faster at 2am?

Try writing this yourself, then compare your own message quality against the [Solution](#).

Difference between Basic, Intermediate, and Advanced: Basic and Intermediate confirm the fact — an unmapped routing value fails loudly, at invoke time, via whatever error `LangGraph`'s internal lookup raises. Advanced adds a check inside `route()` itself so the failure carries a message written for a human debugging *your* graph, not a generic error from inside the library's branch-running code.

[Back to the exercise](#) · [Hint 1](#) · [Hint 2](#) · [Solution](#)

Full solution: [Show me the solution](#)