Step 4 — Forgetting, and a Privacy-Respecting Delete — Hints

> Back to the step · Hint 1 · Hint 2 · Solution

- Hint 1 — The idea, and why one key isn't enough
- Hint 2 — The plan, and proving it

Hint 1 — The idea, and why one key isn't enough

A real "forget me" deletes **everything** about a user, not one key. By Step 3 the Store may hold several keys (`preferred_name` , a preference, …). So:

```
def forget_user(store, user_id):
    ns = namespace_for(user_id)
    for item in store.search(ns):     # list every item first
        store.delete(ns, item.key)    # then delete each
```

`search` the namespace to discover the keys — don't assume there's only one. Wire a `forget_me` command into `main.py` 's loop.

Hint 2 — The plan, and proving it

```
store.py:  forget_user(store, user_id) -> deletes every item, returns count
main.py:   if text == "forget_me":
               forget_user(store, user_id); print(...); continue
test_store: save two facts -> forget_user
            -> assert recall_facts == [] and count == 2
integration: say name -> forget_user -> a new thread recalls nothing
```

The proof that matters is the **fresh run after the forget**: `recall_node` returns nothing, so the model genuinely has no idea who you are. A delete you can't prove emptied the store isn't a real forget. The whole file set is in the Solution.