Step 4 — A Router That Sends Each Message to the Right Agent Automatically — Solution

> Back to this step · Hint 1 · Hint 2 · Solution

Story — Step 4: after Step 3, *you* choose the agent by typing `/extract`. This step hands that choice to a router, gives the Concierge its own file, and moves the "router → agent" flow into a service. That turns two modes of one script into a real 2-agent system. **If not:** users would have to know and type a command to file a ticket — exactly the manual sorting this project exists to remove.

After this step the project is complete. Files from Steps 1-3 that aren't shown here (`config.py`, `exceptions.py`, `models/llm.py`, `agents/triage.py`, `prompts/concierge.txt`, `prompts/triage.txt`, everything in `utils/`, `tests/unit/test_history.py`, `scripts/triage_samples.py`) don't change.

Solution — a model-call router with a logged reason, and a service layer

Changed from Step 3: `SupportTicket` is unchanged; `RouteDecision` is added below it.

Story — `schemas.py`: adds `RouteDecision` next to `SupportTicket`. The router's answer is structured output too, the way Doc04's table suggests for "a supervisor picks the next agent". **If not:** you'd be parsing a free-text reply like "I think triage." by hand, and a typo'd agent name could slip through.

```
# src/schemas.py
# The shapes the model must answer in. SupportTicket: one support ticket.
# RouteDecision: which agent gets a message, and why.
from typing import Literal

from pydantic import BaseModel

class SupportTicket(BaseModel):
    customer_name: str | None
    issue_category: Literal["billing", "technical", "account_access", "other"]
    urgency: Literal["low", "medium", "high"]
    summary: str

# new in Step 4
```

```
class RouteDecision(BaseModel):
    agent: Literal["concierge", "triage"]
    reason: str
```

Story — `prompts/router.txt`: says exactly what counts as "triage" and what counts as "concierge", and asks for a short reason. **If not:** the model would guess its own dividing line, and it would move from message to message.

`src/prompts/router.txt`

```
You route messages for a customer support desk. Choose 'triage' if the
message reports a problem that needs a support ticket (a wrong charge,
something broken, no access to an account). Choose 'concierge' for
greetings, small talk and general questions. Give a one-sentence reason.
```

Story — `agents/router.py`: one small structured call per message, which understands wording no keyword list covers. It starts from a safe default (Concierge) and only replaces it with a usable answer. Every decision is logged with its reason. **If not:** unclear messages would be misrouted with no trace, and a failed routing call could crash the loop or file a false ticket.

```
# src/agents/router.py
# The router: decide() asks the model which agent should answer a message,
# and falls back to the Concierge when the answer can't be used.
from pydantic import ValidationError

from src.models.llm import MODEL
from src.schemas import RouteDecision
from src.utils.logger import get_logger
from src.utils.prompts import load_prompt

def decide(client, message):
    logger = get_logger(__name__)
    messages = [
        {"role": "system", "content": load_prompt("router")},
        {"role": "user", "content": message},
    ]
    decision = RouteDecision(
        agent="concierge", reason="router could not decide"
    )
    try:
        completion = client.beta.chat.completions.parse(
            model=MODEL, messages=messages, response_format=RouteDecision
        )
        reply = completion.choices[0].message
        if reply.parsed is not None:
```

```
            decision = reply.parsed
    except ValidationError as e:
        logger.warning(f"Router output did not match RouteDecision: {e}")

    logger.info(
        f"routed to {decision.agent} ({decision.reason}): {message}"
    )
    return decision
```

Moved from Step 3's `main.py`: the system-prompt line, `MAX_HISTORY_TOKENS`, and the trim + stream lines of the chat branch. Nothing new is added — they're just given their own file.

Story — `agents/concierge.py`: Step 3's chat branch becomes an agent: its own prompt (`start_history()`), its own token budget, one function to call. **If not:** the "Concierge" would only be a name for some lines inside `main.py`.

```
# src/agents/concierge.py
# The Concierge agent: start_history() begins a chat with its system
# prompt, and concierge_agent() trims the chat and streams the reply.

from src.models.llm import stream_message
from src.utils.history import trim_history
from src.utils.prompts import load_prompt

def start_history():
    system_prompt = load_prompt("concierge")
    return [{"role": "system", "content": system_prompt}]

def concierge_agent(client, history, message):
    trim_history(history, 3000)
    return stream_message(client, history, message)
```

Changed from Step 3: `print_ticket()` stays exactly as it was; three imports and `handle_message()` are added below it. `handle_message()` holds the old `/extract`-or-chat `if`, but the router makes the choice now.

Story — `services/desk_service.py`: the whole flow in one function: ask the router, run the agent it picked, show the result. **If not:** `main.py` would mix keyboard input with business logic, and Project 5's web API would have to copy this flow instead of calling it.

```
# src/services/desk_service.py
# The app's flow, apart from the keyboard: handle_message() asks the router,
# then calls the chosen agent. print_ticket() shows a ticket.
# new in Step 4: every import except SupportTicket
```

```
from src.agents.concierge import concierge_agent
from src.agents.router import decide
from src.agents.triage import triage_agent
from src.utils.logger import get_logger

def print_ticket(ticket):
    name = ticket.customer_name
    if name is None:
        name = "(not given)"
    print("Ticket created:")
    print(f"  customer: {name}")
    print(f"  category: {ticket.issue_category}")
    print(f"  urgency:  {ticket.urgency}")
    print(f"  summary:  {ticket.summary}")

# new in Step 4
def handle_message(client, history, message):
    logger = get_logger(__name__)
    decision = decide(client, message)

    if decision.agent == "triage":
        ticket = triage_agent(client, message)
        if ticket is None:
            print("Sorry, I couldn't turn that into a ticket – please")
            print("describe the problem again in a little more detail.")
        else:
            logger.info(
                f"ticket: {ticket.issue_category} / {ticket.urgency}"
            )
            print_ticket(ticket)
    else:
        print("Concierge: ", end="", flush=True)
        concierge_agent(client, history, message)
```

Changed from Step 3: the startup and every `except` block are the same. What's gone: the `print_ticket` import, `MAX_HISTORY_TOKENS` and the `if/else` body (they now live in `desk_service.py` and `concierge.py`). What's new: `history = start_history()` and one call, `handle_message(...)`, inside the `try`.

Story — `main.py`: now only startup, the input loop, and Step 3's error handling (unchanged). `/extract` is gone. **If not:** `main.py` would keep growing with every new agent, instead of staying a thin entry point.

```
# main.py
# The file you run: python main.py
# Startup, the input loop and the error messages – every message goes to
```

```
# handle_message(), which picks the agent.
import sys

import openai

from src.agents.concierge import start_history
from src.config import load_config
from src.exceptions import MissingConfigError
from src.models.llm import check_api_key_at_startup, create_client
from src.services.desk_service import handle_message
from src.utils.logger import get_logger

def main():
    try:
        config = load_config()
    except MissingConfigError as e:
        print(f"Setup problem: {e}")
        sys.exit(1)

    logger = get_logger(__name__)
    client = create_client(config)
    if not check_api_key_at_startup(client):
        logger.error("Authentication failed — check OPENAI_API_KEY.")
        print("Login failed — check OPENAI_API_KEY in your .env file.")
        sys.exit(1)

    history = start_history()
    print("SupportDesk AI — type a message, or /quit to exit.")

    while True:
        message = input("You: ").strip()
        if message == "/quit":
            break
        if message == "":
            continue

        # changed in Step 4: one call replaces the /extract-or-chat if/else
        try:
            handle_message(client, history, message)
        except openai.AuthenticationError:
            logger.error("API key stopped working mid-session.")
            print("Login failed — check OPENAI_API_KEY in your .env file.")
            sys.exit(1)
        except openai.RateLimitError:
            logger.warning("Rate limited after the client's retries.")
            print("We're busy right now — wait a moment and try again.")
        except openai.BadRequestError as e:
```

```
            logger.warning(f"Request rejected (likely too long): {e}")
            if history[-1]["role"] == "user":
                history.pop()
            print("That message was too long to handle — please shorten it.")

if __name__ == "__main__":
    main()
```

Changed from Step 3: the `"triage"` list is the same; the `"routing"` list is new.

Story — `data/sample/messages.json`: adds routing cases — each message with the agent it should reach. **If not:** routing could only be checked by chatting by hand.

`data/sample/messages.json`

```
{
  "triage": [
    "Hi, I'm Sarah Khan. I was charged twice this month. Please fix it today.",
    "can't log into my account, tried resetting password twice, still nothing",
    "just wondering what your refund policy is, no rush"
  ],
  "routing": [
    {"message": "hi there, how are you today?", "expected": "concierge"},
    {"message": "what are your support hours?", "expected": "concierge"},
    {
      "message": "I was charged twice this month, please fix it",
      "expected": "triage"
    },
    {
      "message": "the app crashes every time I open settings",
      "expected": "triage"
    }
  ]
}
```

(The first message is wrapped onto 2 lines here only to fit the page — in your file keep it on **one** line, because a JSON string can't contain a line break.)

Changed from Step 3: the import adds `RouteDecision`; cases 1-2 are the same; `test_route_rejects_unknown_agent()` is new.

Story — `tests/unit/test_schemas.py`: one more case — `RouteDecision` rejects an agent name that doesn't exist. **If not:** someone could widen the `Literal` by mistake, and the router could return an agent `handle_message()` doesn't know.

```
# tests/unit/test_schemas.py
# Checks the Pydantic schemas accept good data and reject bad data.
# Each case prints OK or WRONG. No API calls, no API key needed.
# Run from the repo root: python -m tests.unit.test_schemas
from pydantic import ValidationError

from src.schemas import RouteDecision, SupportTicket

def test_ticket_without_a_name():
    ticket = SupportTicket(
        customer_name=None,
        issue_category="account_access",
        urgency="medium",
        summary="Customer can't log in after two password resets.",
    )
    result = "OK"
    if ticket.customer_name is not None:
        result = "WRONG"
    print(f"case 1 (no name allowed)  -> {result}")

def test_ticket_rejects_unknown_urgency():
    result = "WRONG"
    try:
        SupportTicket(
            customer_name="Sarah Khan",
            issue_category="billing",
            urgency="urgent",
            summary="Charged twice.",
        )
    except ValidationError:
        result = "OK"
    print(f"case 2 (bad urgency)      -> {result}")

# new in Step 4
def test_route_rejects_unknown_agent():
    result = "WRONG"
    try:
        RouteDecision(agent="billing", reason="looks like billing")
    except ValidationError:
        result = "OK"
    print(f"case 3 (bad agent name)   -> {result}")

if __name__ == "__main__":
    test_ticket_without_a_name()
    test_ticket_rejects_unknown_urgency()
```

```
    # new in Step 4
    test_route_rejects_unknown_agent()
```

Changed from Step 3: one new import (`decide`), one new function (`test_routing()`), and one new call at the bottom. Cases 1-5 are the same.

Story — `tests/integration/test_live_agents.py` : Step 3's checks plus case 6 — every routing case must reach its expected agent. **If not:** a small change to `router.txt` could quietly send complaints to the Concierge.

```
# tests/integration/test_live_agents.py
# Checks the app against the real OpenAI API — each step adds cases.
# Each case prints OK or WRONG. Needs a valid OPENAI_API_KEY in .env.
# Run from the repo root: python -m tests.integration.test_live_agents
import json

from openai import OpenAI

# new in Step 4
from src.agents.router import decide
from src.agents.triage import triage_agent
from src.config import load_config
from src.models.llm import (
    check_api_key_at_startup,
    create_client,
    send_message,
)

def test_first_reply(client):
    reply = send_message(client, [], "What's 2+2?")
    result = "OK"
    if "4" not in reply:
        result = "WRONG"
    print(f"case 1 (first reply) -> {result}: {reply}")

def test_bad_key():
    bad_client = OpenAI(api_key="sk-fake-key-123")
    result = "OK"
    if check_api_key_at_startup(bad_client):
        result = "WRONG"
    print(f"case 2 (bad key)     -> {result}")

def test_memory(client):
    history = [{"role": "system", "content": "You are a helpful assistant."}]
    send_message(client, history, "My order number is 4471.")
    send_message(client, history, "Thanks, that's all for now.")
```

```
    reply = send_message(client, history, "What was my order number?")
    result = "OK"
    if "4471" not in reply:
        result = "WRONG"
    print(f"case 3 (memory)      -> {result}: {reply}")

def load_samples():
    with open("data/sample/messages.json") as samples_file:
        return json.loads(samples_file.read())

def test_every_sample_gets_a_ticket(client, samples):
    for message in samples["triage"]:
        ticket = triage_agent(client, message)
        if ticket is None:
            print("case 4 (ticket)      -> WRONG: no ticket")
        else:
            print("case 4 (ticket)      -> OK:", ticket.issue_category)

def test_no_invented_name(client, samples):
    ticket = triage_agent(client, samples["triage"][1])
    result = "OK"
    if ticket is None or ticket.customer_name is not None:
        result = "WRONG"
    print(f"case 5 (no name)     -> {result}")

# new in Step 4
def test_routing(client, samples):
    for case in samples["routing"]:
        decision = decide(client, case["message"])
        result = "OK"
        if decision.agent != case["expected"]:
            result = "WRONG"
        print(f"case 6 (routing)     -> {result}: {decision.agent}")

if __name__ == "__main__":
    config = load_config()
    client = create_client(config)
    samples = load_samples()
    test_first_reply(client)
    test_bad_key()
    test_memory(client)
    test_every_sample_gets_a_ticket(client, samples)
    test_no_invented_name(client, samples)
    # new in Step 4
    test_routing(client, samples)
```

Run everything (from the repo root):

```
python -m tests.unit.test_config
python -m tests.unit.test_history
python -m tests.unit.test_schemas
python -m tests.integration.test_live_agents
python main.py
```

Expected output — `test_schemas` gets one more line, and `test_live_agents` ends with four routing lines:

```
case 3 (bad agent name)   -> OK
```

```
case 6 (routing)     -> OK: concierge
case 6 (routing)     -> OK: concierge
case 6 (routing)     -> OK: triage
case 6 (routing)     -> OK: triage
```

Expected app session (the log lines go to the console too; the model's wording varies):

```
SupportDesk AI — type a message, or /quit to exit.
You: hi! what are your support hours?
... src.agents.router INFO routed to concierge (The user asks
a general question about support hours.): hi! what are your support
hours?
Concierge: We're available Monday to Friday, 9am to 6pm.
You: can't log into my account, tried resetting password twice
... src.agents.router INFO routed to triage (The user cannot
access their account.): can't log into my account, tried ...
... src.services.desk_service INFO ticket: account_access / medium
Ticket created:
  customer: (not given)
  category: account_access
  urgency:  medium
  summary:  Customer can't log in even after resetting the password twice.
You: /quit
```

(Log lines are shortened with `...` and wrapped to fit the page.)

Now try an unclear one, like `"just wondering what your refund policy is, no rush"`, and read the log's reason. Whichever agent it picks, you can see *why* — that's what the checklist's "logged, with the reason" means.